

# scoped\_read

---

## scoped\_read.sh – Companion Guide

---

Revision: 1 Last modified: 2026-07-17T00:00:00Z

### Overview

---

§11.4.141 M4 implementation. Prevents full-file loading when a targeted read suffices.

### Functions

---

| Function                       | Purpose                                         | Example                                                             |
|--------------------------------|-------------------------------------------------|---------------------------------------------------------------------|
| <code>sr_grep_then_read</code> | Grep pattern → read matching lines with context | <code>sr_grep_then_read "func"</code><br><code>"main.go" 5</code>   |
| <code>sr_section_read</code>   | Read section by heading match                   | <code>sr_section_read "## Usage"</code><br><code>"README.md"</code> |
| <code>sr_cached_result</code>  | Cache command results (5min TTL)                | <code>sr_cached_result "key"</code><br><code>"command"</code>       |
| <code>sr_clear_cache</code>    | Clear the cache                                 | <code>sr_clear_cache</code>                                         |

## Usage

---

```
source constitution/scripts/token_efficiency/scoped_read.sh
```

```
# Read 5 lines of context around "func main" in main.go
```

```
sr_grep_then_read "func main" "main.go" 5
```

```
# Read the "## Usage" section from README.md
```

```
sr_section_read "## Usage" "README.md"
```

```
# Cache a command result
```

```
sr_cached_result "git_status" "git status --short"
```

## Cross-references

---

- Constitution §11.4.141 M4
- `token_efficiency_lib.sh` — for status and caching
- `context_compactor.sh` — for context pruning