

token_efficiency_lib

token_efficiency_lib.sh – Companion Guide

Revision: 1 Last modified: 2026-07-17T00:00:00Z

Overview

§11.4.141 M5+M6 implementation. Provides terse status, batch reads, and cached grep for token-efficient operations.

Functions

Function	Purpose	Example
<code>te_status_line</code>	Terse one-line status	<code>te_status_line "Build started"</code>
<code>te_batch_read</code>	Read multiple files, return summary	<code>te_batch_read file1.md file2.md</code>
<code>te_cached_grep</code>	Grep with result caching	<code>te_cached_grep "pattern" "file.sh"</code>
<code>te_clear_cache</code>	Clear the cache	<code>te_clear_cache</code>

Usage

```
source constitution/scripts/token_efficiency/token_efficiency_lib.sh
```

```
# Terse status
```

```
te_status_line "Processing item ATM-751"
```

```
# Batch read multiple files
```

```
te_batch_read docs/Issues.md docs/Fixed.md
```

```
# Cached grep (result cached for 5 minutes)
```

```
te_cached_grep "§11.4" CLAUDE.md
```

Cross-references

- Constitution §11.4.141 M5+M6
- `scoped_read.sh` — for targeted file reads
- `context_compactor.sh` — for context pruning