

challenges/scripts/ no_suspend_calls_challenge.sh — operator guide

Revision: 1 **Last modified:** 2026-07-01T00:00:00Z **Status:**
Active CONST-033 source-tree gate. Thin challenge wrapper
around the static scanner `check-no-suspend-calls.sh`.

Companion (§11.4.18) to the in-source documentation block
at the top of the script.

Overview / Purpose

CONST-033 forbids any code that triggers a host-level power-state transition (suspend / hibernate / hybrid-sleep / poweroff / halt / reboot / kexec). This challenge asserts the project's **source tree** contains zero such forbidden invocations. It is the source-side complement of `host_no_auto_suspend_challenge.sh` (which checks the running host's state).

It is a wrapper: it locates and runs `check-no-suspend-calls.sh` (the actual scanner) against the project root and propagates its verdict. It resolves the scanner relative to its own location, so it works whether invoked from the project root or from `challenges/scripts/`.

Usage

```
bash challenges/scripts/no_suspend_calls_challenge.sh
```

No arguments. It walks up from its own directory until it finds `scripts/host-power-management/check-no-suspend-calls.sh`, treats that directory's parent as the project root, and scans it.

Inputs

- None on the command line.

- Discovers the project root by walking parent directories from `$ {BASH_SOURCE[0]}` looking for `scripts/host-power-management/check-no-suspend-calls.sh`.

Outputs

- A header (Scanner: / Root: paths), the scanner's own findings, and a `=== summary: PASS|FAIL ===` line on stdout; violations (if any) are printed by the scanner.
- Exit code: 0 = clean (no forbidden calls); 1 = one or more violations; 2 = the scanner could not be located.

Side-effects

None. Read-only static scan of the source tree — no files written, no host power state touched (§11.4.14).

Dependencies

bash; the delegated scanner `scripts/host-power-management/check-no-suspend-calls.sh` (which itself uses `grep/find-class` tooling to walk the tree). If the scanner is missing the wrapper exits 2 with a diagnostic rather than a false PASS (§11.4.1).

Edge cases

- **Scanner not found** (walking up to / fails) → exit 2, message cannot locate `scripts/host-power-management/check-no-suspend-calls.sh`.
- **Invoked from any cwd** → the self-relative root resolution makes the verdict independent of the working directory.
- The scanner excludes third-party / generated / justified-non-host-context directories (`.git`, `vendor`, `upstreams`, the constitution submodule, ...) so a documentation reference to a forbidden command is not a false positive.

Related scripts

- `scripts/host-power-management/check-no-suspend-calls.sh` — the wrapped scanner (the real logic).
- `challenges/scripts/host_no_auto_suspend_challenge.sh` — the HOST-state gate (this one is the SOURCE-tree gate).
- Constitution CONST-033 (host power-management hard ban), §11.4.1.

Last verified

2026-07-01 — documented against the script + scanner source;
sh -n / bash -n parse-clean. Run as part of the CONST-033 source-
tree verification.