

# BUGFIXES

Root-cause-analysed bug fixes for this project, per the Universal Mandatory Constraints (CLAUDE.md mandate #10). Each entry records the defect, root cause, affected files, the fix, and a link to the reproduction/verification evidence.

---

## BUGFIX-0001 — run-tests.sh aborts after the first test under set -e

- **Type:** Bug (script-internal failure — Helix Constitution §11.4.1)
- **Status:** Fixed
- **Date:** 2026-06-30
- **Affected file:** tests/run-tests.sh (test\_result())

### Symptom

bash tests/run-tests.sh printed only its banner and the first test's section header, then exited 1 (7 lines of output total) — every test after the first was silently never run, and no TEST SUMMARY was printed.

### Reproduction (captured, run in-session before the fix)

```
$ bash -c 'set -euo pipefail; x=0; ((x++)); echo "SURVIVED,
x=$x"; echo "exit=$?"
exit=1                                # "SURVIVED" never printed
```

```
$ bash tests/run-tests.sh 2>&1 | wc -l
7                                     # aborted; exit=1
```

### Root cause (FACT — not a guess, Helix Constitution §11.4.6)

test\_result() counted with the bash post-increment idiom (( TESTS\_RUN++ )). The arithmetic command (( expr )) returns exit status **1** when expr evaluates to **0**. TESTS\_RUN++ is a *post*-increment, so its value is the value *before* incrementing — 0 on the very first call — making (( TESTS\_RUN++ )) return status 1. The script runs

under `set -euo pipefail` (line 7), so that non-zero status aborted the entire suite at the first `test_result` call, before any results or the summary could print. The same trap applied to the first PASS (`(( TESTS_PASSED++ ))`) and first FAIL (`(( TESTS_FAILED++ ))`).

This was a **pre-existing** latent defect (the `(( ... ++ ))` idiom was original); it surfaced while wiring the constitution-inheritance pre-flight gate in as the first test.

## Fix (at source, Helix Constitution §11.4.1)

Replaced the three post-increment arithmetic commands with the assignment form, which always returns status 0 and is immune to the `set -e` trap:

```
- ((TESTS_RUN++))
+ TESTS_RUN=$((TESTS_RUN + 1))
- ((TESTS_PASSED++))
+ TESTS_PASSED=$((TESTS_PASSED + 1))
- ((TESTS_FAILED++))
+ TESTS_FAILED=$((TESTS_FAILED + 1))
```

## Verification (captured, run in-session after the fix)

```
$ bash -c 'set -euo pipefail; x=0; x=$((x+1)); echo "SURVIVED,
x=$x"; echo "exit=$?"
SURVIVED, x=1
exit=0
```

```
$ bash tests/run-tests.sh 2>&1 | wc -l
28                                # suite now runs to completion (was 7)
# first line of results:
✓ PASS: Constitution inheritance gate (§11.4.35)
```

The suite now executes every test and prints its summary. (Its overall exit remains non-zero in an environment without the running proxy services — those are real-infrastructure tests that correctly FAIL/skip when the live System is absent, Helix Constitution §11.4.11 — that is a separate, pre-existing, infrastructure-dependent condition, not this defect.)

---

**Cross-reference (§11.4.138):** the "proxy services not running" condition noted above was treated as merely environmental. It was not — BUGFIX-0002 below is the *reason* the proxy would not stay up under rootless Podman. Driving the real data path (not just "tests pass") surfaced it.

---

# BUGFIX-0002 — squid crash-loops under rootless Podman (log dir not writable) → proxy never serves

- **Type:** Bug (product defect — end-user-visible: the proxy does not work)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** lib/container-runtime.sh (create\_directories()), start (init\_cache())
- **Regression guard:** tests/regression/log\_dir\_writable\_test.sh (§11.4.135, §11.4.115 RED\_MODE polarity)
- **Workable item:** #38 (the live-usability proof stream)

## Symptom

A freshly-booted proxy (./start --no-vpn, rootless Podman) returned http\_code=000 for every request through it. proxy-squid was not (healthy) — it was restarting in a loop, never accepting a connection, so **no feature of the proxy worked for the end user** — the exact "tests pass but the feature can't be used" failure mode §11.4 forbids.

## Reproduction (captured, run in-session before the fix — §11.4.115 RED)

```
# Live boot of the real orchestrator, then curl through the proxy:
$ curl -s -o /dev/null -w '%{http_code}' -x http://127.0.0.1:53128 http://example.com/
000
```

```
# squid's own log (read from inside the container) showed the FATAL:
$ podman logs proxy-squid | tail
FATAL: Cannot open '/var/log/squid/access.log' for writing.
       The parent directory must be writeable by the user 'proxy',
       which is the cache_effective_user set in squid.conf.
```

```
# Unit reproduction of the orchestrator code path (pre-fix replica):
$ RED_MODE=1 tests/regression/log_dir_writable_test.sh
[PASS] BUGFIX#38 log-dir-writable (RED_MODE=1): RED reproduced:
       pre-fix LOG_DIR mode=755 is NOT world-writable
```

## Root cause (FACT — not a guess, §11.4.6)

Under **rootless** Podman the invoking host uid (1000) maps to the container's root, but every other container uid is remapped through `/etc/subuid` into a high host range. `squid.conf` sets `cache_effective_user proxy`, so squid drops privileges to its non-root proxy user — which, on the host, is a high subuid that owns **none** of the host-created bind-mount dirs. The host `./logs` directory was created mode `0755` (owner-write only), so the container proxy user had only world `r-x` — no write — and squid `FATALed` opening `access.log`, then crash-looped. The orchestrator already `chmod 777`-ed the **cache** bind-mount (`init_cache`) for this exact reason, but the **log** bind-mount was missed — a single missing site of an already-known remedy.

## Fix (at source, §11.4.1 / §11.4.108 SOURCE layer)

Make the squid log bind-mount world-writable in the orchestrator's `dir-init`, mirroring the existing `cache chmod 777`. Applied at **both** self-sufficient sites so it holds regardless of call order:

```
# lib/container-runtime.sh  create_directories()
    mkdir -p "$LOG_DIR"
+  chmod 777 "$LOG_DIR"

# start  init_cache()
+  mkdir -p "$LOG_DIR"
+  chmod 777 "$LOG_DIR"
```

## Verification (captured, run in-session after the fix)

**Unit — regression guard, §11.4.115 polarity (RED reproduces, GREEN proves):**

```
$ RED_MODE=1 tests/regression/log_dir_writable_test.sh  # pre-fix
replica
[PASS] RED reproduced: LOG_DIR mode=755 NOT world-writable
$ tests/regression/log_dir_writable_test.sh              # real
fixed code
[PASS] GREEN: create_directories() made LOG_DIR mode=777 world-
writable
```

**§1.1 paired mutation (guard is not a tautology):** stripping the `chmod 777 "$LOG_DIR"` from `create_directories()` made the GREEN guard **FAIL** (REGRESSION: ... mode=755 NOT world-writable, exit 1); the lib was restored byte-identical (md5 `0128a96b6d467c2da5b7cef8a808e563` before == after) and the guard **PASSed** again.

### **Live data-plane (§11.4.108 RUNTIME + USER-VISIBLE):**

after the fix the booted proxy serves real HTTP through it:

```
$ curl -x http://127.0.0.1:53128 http://example.com/ ->
http_code=200
Via: 1.1 proxy-squid (squid/6.13)
# squid access.log (the file that FATAL'd pre-fix) – real request
logged:
1782858066.886 189 10.89.1.249 TCP_MISS/200 951 GET http://
example.com/ - HIER_DIRECT/104.20.23.154 text/html
$ podman ps -> proxy-squid Up (healthy)
```

Evidence: qa-results/regression/bugfix38/.

---

## **BUGFIX-0003 — tests/run-tests.sh aborts mid-suite on a no-message FAIL (set -e); ~29 of 39 tests silently never ran**

- **Type:** Bug (script-internal failure — §11.4.1; sibling of BUGFIX-0001)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected file:** tests/run-tests.sh (test\_result())
- **Regression guard:** tests/regression/test\_result\_returns\_zero\_test.sh (§11.4.135, §11.4.115 RED\_MODE polarity)

### **Symptom**

bash tests/run-tests.sh printed only ~10 results then stopped — no TEST SUMMARY, exit 1. The Directory / Config / Compose / Runtime / Port / Cache / VPN / Service-startup groups after the first FAIL never ran, so the suite *appeared* to run while actually exercising under a third of its tests and hiding real failures.

### **Reproduction (captured, run in-session before the fix — §11.4.115 RED)**

```
# Extract the pre-fix test_result and call it with a no-message
FAIL under set -e:
$ bash -c 'set -euo pipefail; <test_result>; test_result "x"
"FAIL"; echo SURVIVED'
x FAIL: x
# exit=1 – "SURVIVED" never printed (the function returned 1 and
aborted)

$ RED_MODE=1 tests/regression/test_result_returns_zero_test.sh
```

[PASS] RED reproduced: pre-fix test\_result aborts under set -e on a no-message FAIL

## Root cause (FACT — not a guess, §11.4.6)

test\_result()'s FAIL branch ended on `[[ -n "$message" ]] && echo -e " → $message"`. When message is empty (every test\_result "... " "FAIL" call with no third argument), the `[[ -n "$message" ]]` test is false, the `&&` list short-circuits, and the list — the **last command of the function** — returns exit status **1**. When such a test\_result is the last command executed in a test function (e.g. the final "Upstreams" iteration of test\_directories's for loop, where the dir is absent → FAIL), that function returns 1, and under set -euo pipefail main() aborts immediately — every later test group and the summary never run. This is the same §11.4.1 class as BUGFIX-0001 (a reporting helper leaking a non-zero status into control flow), a *different* site (test\_result's tail, not the `(( ++ ))` counter), so BUGFIX-0001's fix did not cover it.

## Fix (at source, §11.4.1)

test\_result is a reporting helper; its exit status must never gate control flow. Append an explicit return 0:

```
        [[ -n "$message" ]] && echo -e "  ${YELLOW}→ $message$
        {NC}"
    fi
+
+   return 0
+ }
```

## Verification (captured, run in-session after the fix)

```
# §11.4.115 GREEN (real fixed test_result survives a no-message
FAIL):
```

```
$ tests/regression/test_result_returns_zero_test.sh
```

```
[PASS] GREEN: real test_result returns 0 on a no-message FAIL
```

```
# Full suite now runs to completion (was 32 lines, aborted):
```

```
$ bash tests/run-tests.sh # 82 lines, reaches TEST SUMMARY
```

```
Tests Run: 41
```

```
Tests Passed: 34
```

```
Tests Failed: 7
```

**§1.1 paired mutation (guard is not a tautology):** deleting the return 0 re-introduced the abort → the GREEN guard **FAILED** (REGRESSION: test\_result aborts the suite ..., exit 1); tests/run-

tests.sh was restored byte-identical (md5 7c2bab18c4566d081b1c8aa7a9a412e0 before == after) and the guard PASSED again.

**Follow-up (separate, tracked):** with the abort fixed, the suite now honestly reports **7 pre-existing FAILs** (e.g. Directory Upstreams) that the abort had been masking. These are real existing-system findings to triage — not regressions from this fix, but newly *visible* because the suite finally runs to completion.

Evidence: qa-results/regression/bugfix0003/.

---

## BUGFIX-0004 — run-tests.sh reports FAILURE on a HEALTHY serving proxy (§11.4.1 false-FAIL); skips recorded as PASS

- **Type:** Bug (anti-bluff — §11.4.1 false-FAIL + §11.4.3 PASS-by-default-for-skip)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected file:** tests/run-tests.sh (test\_result, test\_environment, test\_directories, test\_container\_runtime, test\_ports + new port\_verdict/\_ports\_check\_one, test\_vpn, test\_service\_startup, print\_summary)
- **Regression guard:** tests/regression/port\_topology\_aware\_test.sh (§11.4.135, §11.4.115 RED\_MODE polarity)
- **Bluff audit:** docs/research/existing\_test\_bluffs\_audit/README.md (B7)
- **Workable item:** #47 (P8)

### Symptom

Once BUGFIX-0003 let the suite run to completion, bash tests/run-tests.sh reported Tests Run: 41, Passed: 34, Failed: 7 and exited **1 against a perfectly healthy, serving proxy** (proxy-squid + proxy-dante Up (healthy)). A suite that declares FAILURE on a working System is a §11.4.1 false-FAIL — as misleading as a false-PASS.

### Reproduction (captured, run in-session before the fix — §11.4.115 RED)

```
# Against the running, healthy proxy:
$ bash tests/run-tests.sh | tail -4
```

```

Tests Run:      41
Tests Passed: 34
Tests Failed: 7      # exit 1
# The 7 FAILs: .env file exists, HTTP_PROXY_PORT set, Directory
Upstreams,
# Docker installed, Port 53128 available, Port 51080 available,
Port 58080 available

$ RED_MODE=1 tests/regression/port_topology_aware_test.sh
[PASS] RED reproduced: pre-fix logic classifies a healthy serving
proxy port
(owner up + listening) as FAIL

```

## Root cause (FACT — not a guess, §11.4.6)

Three independent bluff classes, all FACT-confirmed against the live host:

1. **Port-semantics inversion (§11.4.1).** `test_ports` reported any port that was IN USE as FAIL ("Port in use"). The running proxy's own listening ports (squid 53128, dante 51080) are *in use by their own healthy service* — the serving state — so the suite FAILED on health.
2. **Inverted runtime check (§11.4.161).** `test_container_runtime` asserted Docker installed and FAILED on its absence. The project MANDATES rootless Podman and FORBIDS Docker as a workflow — the check tested for the forbidden runtime and failed on the compliant state.
3. **Config-absent-as-FAIL (§11.4.3).** `.env` (gitignored, §11.4.10/ §11.4.30) and `Upstreams/` absence FAILED, though their absence is the *expected* fresh-checkout topology. And (B7) `test_result` had no SKIP state, so `test_vpn/test_service_startup` skipped paths were recorded as PASS, inflating TESTS\_PASSED (§11.4.3 PASS-by-default).

## Fix (at source, §11.4.1 / §11.4.3 / §11.4.161)

- **3-state test\_result** — add a SKIP branch + TESTS\_SKIPPED counter + Tests Skipped: summary line; the suite exit gates on TESTS\_FAILED -eq 0 only (skips are neither pass nor fail). BUGFIX-0001 assignment-form counters + BUGFIX-0003 return 0 preserved.
- **§11.4.3 topology-aware ports** — a *pure* `port_verdict(owner_serving, listening)` truth-table (serving→PASS, owner-up-but-not-listening→FAIL, pre-start-free→PASS, foreign-process-holds-it→SKIP); `_ports_check_one` resolves `owner_serving` from real podman `ps/podman` port and listening from real `ss` (no data-plane probe).
- **§11.4.161** — assert the mandated podman; Docker informational only, absence is SKIP not FAIL.

- **§11.4.3 SKIP** for absent gitignored .env/HTTP\_PROXY\_PORT (validate the tracked .env.example template instead) and absent upstreams//Upstreams/.
- **B7** — test\_vpn/test\_service\_startup disabled paths emit SKIP.

## Verification (captured, run in-session after the fix)

```
# Full suite vs the healthy running proxy – zero failures, honest skips:
$ bash tests/run-tests.sh | tail -5
Tests Run:      43
Tests Passed:   37
Tests Skipped:  6
Tests Failed:   0      # exit 0 – "All tests passed (6 skipped ...)"
```

```
# §11.4.115 polarity guard (tests the REAL pure port_verdict, not a copy):
$ RED_MODE=1 tests/regression/port_topology_aware_test.sh  #
reproduces
[PASS] RED reproduced: healthy serving port classified FAIL
$ tests/regression/port_topology_aware_test.sh              #
GREEN
[PASS] GREEN: HEALTHY=PASS NOTSERVING=FAIL PRESTART_FREE=PASS
PRESTART_BUSY=SKIP
```

**§1.1 paired mutation (guard is not a tautology):** flipping port\_verdict's PASS/FAIL branch made the GREEN guard **FAIL** (REGRESSION: ... HEALTHY=FAIL ..., exit 1) with bash -n still clean (assertion, not parse error); tests/run-tests.sh restored byte-identical (md5 2f4d3e4bf33cd391036cee595839d439) and the guard PASSED again. The guard is wired into test\_regression\_guards() (GREEN + RED self-check); the 5 pre-existing guards still PASS.

**Honest note (§11.4.6 / §11.4.174):** port 58080 (the control-API port) is currently held by a **non-project** host process — no proxy container publishes it — so the suite classifies it SKIP (readiness not assertable), never a false-FAIL blaming the proxy. The foreign process was **not** touched (shared-host ownership). This is a real condition to free before P10 deploys the control-API there.

Evidence: qa-results/p8/, qa-results/regression/portstopology/.

---

## BUGFIX-0005 — final-verify.sh + verify-proxy.sh greened a NO-VPN config (false-VPN-routing §15 bluff) + aborted under set -e

- **Type:** Bug (anti-bluff — false-VPN-routing §15 + §11.4.1 script-abort)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** tests/final-verify.sh (audit B5), tests/verify-proxy.sh (audit B6)
- **Bluff audit:** docs/research/existing\_test\_bluffs\_audit/README.md (B5, B6)
- **Future guard:** the standing assert\_egress\_ip invocation (live RED/GREEN at P10, §11.4.135) — SKIPS honestly until a real tunnel + VPN\_EXIT\_IP exists.
- **Workable item:** #49 (P8b)

### Symptom & root cause (FACT — §11.4.6)

Both scripts declared VPN routing verified **PASS** when the egress IP seen THROUGH the proxy EQUALS the host's real direct IP (`host_ip == proxy_ip`). That equality is PROOF traffic was **NOT** routed through any VPN — both paths exit the same address — so the test greened the exact no-VPN configuration it claimed to forbid (the §15 bluff; `verify-proxy.sh:46`'s comment literally encoded the wrong invariant "proxy uses same IP as host"). Neither compared against an EXPECTED tunnel-exit IP. Additionally both `test_pass/test_fail` used `((PASS++))/((FAIL++))`, which returns exit 1 when the counter is 0 and aborts the script under `set -euo pipefail` (the §11.4.1 class of BUGFIX-0001/B4) — so the VPN block was unreachable until that was fixed too.

### Fix (at source)

Remove the `egress==host PASS` entirely; assert the real data-plane contract via `evidence.sh`: egress through the proxy must equal the EXPECTED tunnel exit AND differ from the host IP; absent a configured `VPN_EXIT_IP` (no tunnel yet) emit an honest §11.4.3 SKIP (`operator_attended`) — never a fabricated PASS. `((PASS++))/((FAIL++))` → assignment form `PASS=$((PASS + 1))`, matching the `run-tests.sh` §11.4.1 fix.

```
- [[ "$host_ip" == "$proxy_ip" && "$host_ip" != "unknown" ]] &&
    test_pass "VPN routing verified"
+ . "$SCRIPT_DIR/lib/evidence.sh"
+ if [[ -n "${VPN_EXIT_IP:-}" ]]; then
+     assert_egress_ip "http://localhost:${HTTP_PROXY_PORT}"
+         "$VPN_EXIT_IP" "$host_ip" \
```

```

+         && test_pass "VPN routing (egress=$VPN_EXIT_IP, !=
+             host)" || test_fail "..."
+ else
+     ab_skip_with_reason "VPN routing (egress == expected tunnel
+         exit, != host)" "operator_attended"
+ fi

```

## Verification (captured, run in-session after the fix)

```

# Both run to completion vs the running proxy – connectivity PASS,
VPN SKIP:
$ bash tests/final-verify.sh -> Passed: 4 Failed: 0, exit 0
  SKIP: VPN routing (egress == expected tunnel exit, != host)
[reason: operator_attended]
$ bash tests/verify-proxy.sh -> Passed: 4 Failed: 0, exit 0

# Inverse anti-bluff proof (the §15 condition the OLD code
GREENed): set
# VPN_EXIT_IP to the host's real IP (no tunnel => egress == host)
– new code REDs:
$ VPN_EXIT_IP=<host real ip> bash tests/final-verify.sh
  FAIL: assert_egress_ip [reason: egress IP <host> == host real IP
– traffic NOT routed via VPN (§15 bluff)]
  Failed: 1, exit 1

```

The live VPN-routing GREEN (egress == real tunnel exit, != host) requires a real tunnel + VPN\_EXIT\_IP and is deferred to P10; until then the corrected assertion SKIPS honestly. bash -n clean both files. Reviewed independently by the conductor (§11.4.142): diffs, both runs, the inverse proof, parse — all verified against the real tree before commit.

Evidence: qa-results/p8b/.

---

## BUGFIX-0006 — comprehensive-test.sh 100% dead ((( )) set -e abort) + green-on-bluff data-plane checks + false-VPN-routing

- **Type:** Bug (anti-bluff — §11.4.1 script-abort + green-without-evidence + false-VPN-routing §15)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** tests/comprehensive-test.sh (audit B1–B4, B8)
- **Bluff audit:** docs/research/existing\_test\_bluffs\_audit/README.md (B1–B4, B8)
- **Discovered regression (§11.4.124):** #50 — the documented cache management CLI (./cache stats|clear|invalidate|trim,

docs/CACHE.md) is gone from HEAD (path collision: the ./cache CLI file vs the runtime data dir CACHE\_DIR=\$PROJECT\_ROOT/cache, lib/container-runtime.sh:180).

- **Workable item: #48 (P8c)**

## Symptom & root cause (FACT — §11.4.6)

The whole script was **dead**: set -euo pipefail plus bash arithmetic counters ((( ... )) / ((PASS++))) abort with exit 1 the moment a counter is 0, so the suite exited before a single test ran — it could never report a failure (a §11.4.1 false-pass-by-silence, the BUGFIX-0001/0003/0005 class). Behind that abort, the checks themselves were bluffs once revived:

- **B1** declared VPN routing PASS when the egress IP through the proxy equals the host's real IP — the §15 false-VPN-routing bluff (BUGFIX-0005 class).
- **B2** "cache works" asserted nothing from Squid — no TCP\_\*HIT evidence.
- **B3** "concurrent" never checked per-request HTTP status.
- **B8** "status" never inspected a real field.

## Fix (at source)

Revive + de-bluff. (( )) counters → assignment form (PASS=\$((PASS + 1))), matching the run-tests.sh / verify-proxy.sh §11.4.1 fixes — the 44-check suite now actually runs. Each revived check now captures real data-plane evidence:

- **B2** assert\_cache\_hit greps a real TCP\_\*HIT out of the podman-exec'd Squid access.log for a re-fetched object (§11.4.69 evidence path).
- **B3** asserts per-request %{http\_code} 200 across all 10 concurrent requests (10/10), not merely that curl returned.
- **B8** asserts the status command emits real fields (plain, verbose, JSON).
- **B1** egress==host PASS deleted → honest §11.4.3 SKIP (operator\_attended, VPN\_EXIT\_IP unset) until the P10 real tunnel — never a fabricated PASS.
- **Cache-CLI checks** are §11.4.3 topology-aware: when the documented cache CLI is absent they SKIP citing the tracked regression #50 (the §11.4.124 investigation that found it), rather than fabricate a PASS or hard-FAIL the suite on a known-tracked gap.
- **Large-file** asserts faithful relay (proxy\_size == direct\_size); the earlier FAIL was root-caused to an EXTERNAL endpoint cap, NOT proxy truncation (evidence: direct\_size=102400 proxy\_size=102400).
- .env sourcing is optional — its absence is a topology SKIP, not a FAIL.

## Verification (captured, run in-session after the fix — independent re-runs)

```
# Fresh clone, no .env present — runs to the summary,
deterministic across 2 runs:
$ bash tests/comprehensive-test.sh
  Tests Run: 44   Passed: 34   Failed: 0   Skipped: 10   (exit
0)   [no FAIL lines]

# Real data-plane PASSes present (not metadata):
✓ PASS: Cache HIT (Squid TCP_*HIT in access.log)
✓ PASS: Concurrent connections (10)
✓ PASS: Large file download (proxy relays faithfully)
✓ PASS: Status command reports real fields (+ verbose + JSON)

# All 10 SKIPS audited honest: 4× cache-CLI (regressed out, #50),
# 3× no-.env vars, .env-topology, VPN routing (B1), VPN container
(no-vpn mode).
```

Re-run #2 byte-identical (44/34/0/10, exit 0 — deterministic §11.4.50). Residue

- secret scan CLEAN; no ((VAR++)) remain; bash -n clean. Reviewed independently by the conductor (§11.4.142/ §11.4.134, iterate-to-GO): the lane returned with 5 hard FAILs on the first pass; the §11.4.124 investigation proved 4 were a REAL regression (#50, not a test bug → SKIP-with-reason) and 1 an external cap (faithful-relay, not truncation), and the corrected lane was re-reviewed clean before commit.

Evidence: qa-results/comprehensive/.

---

## BUGFIX-0007 — documented cache management CLI accidentally deleted (path collision with the runtime cache/ data dir) → restored as cachectl

- **Type:** Bug (regression — documented end-user feature unusable; §11.4.124)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** cachectl (restored + 3 runtime fixes), tests/run-tests.sh
  - tests/comprehensive-test.sh (cache-CLI checks → real PASS), README.md / USER\_GUIDE.md / docs/CACHE.md / docs/TROUBLESHOOTING.md (./cache→./cachectl), docs/scripts/cachectl.md, tests/regression/cache\_cli\_present\_test.sh (guard)

- **Workable item:** #50 (surfaced by BUGFIX-0006's revival of `comprehensive-test.sh`)

## Symptom & root cause (FACT — §11.4.6 / §11.4.124 git-history investigation)

The documented 368-line cache management CLI (`stats|clear|invalidate|warmup|list|size|trim`, referenced in README / USER\_GUIDE / docs/CACHE / docs/TROUBLESHOOTING) was **gone from HEAD** — every documented `./cache <cmd>` was a broken instruction. Git history proves an ACCIDENTAL deletion: `CACHE_DIR` has always been `$PROJECT_ROOT/cache` and `.gitignore:16` ignores `cache/` (the directory), so the tracked cache FILE and the runtime cache/ DATA directory occupy the SAME path and cannot coexist. Once the runtime materialised the directory, commit `6ec58ef` ("fix: container config for host-vpn mode") recorded the cache file as deleted in a broad `git add` — collateral to an unrelated change. The data dir `cache/{squid,streaming}` is LIVE (bind-mounted into the running proxy), so it must NOT move (§11.4.133).

## Fix (at source)

Restore the CLI faithfully from `84e1754:cache` under the NON-colliding name `cachectl` (§11.4.101 safe/reversible — coexists with the gitignored `cache/ data dir`; the live data dir + running proxy untouched). The byte-restored file did NOT work under rootless Podman; three FACT-grade runtime defects fixed at source (the §11.4.108 SOURCE-restored ≠ RUNTIME-works lesson):

1. **pipefail partial-read abort** — squid's cache subdirs are owned by a remapped subuid the host cannot traverse, so `du/ find` exit non-zero; the sourced `lib/container-runtime.sh` re-enables `set -o pipefail`, aborting every `stat/list` mid-output. Fix: `set +o pipefail` after the source.
2. **CONTAINER\_RUNTIME unset** — `main()` never called `init_runtime`, so the `invalidate squid-flush` case aborted under `set -u`. Fix: `init_runtime + detect_container_runtime fallback + export` in `main()`.
3. **((removed++)) set -e abort in trim** — post-increment returns exit 1 when `removed=0`. Fix: `removed=$((removed + 1))` (the §11.4.1 class).

Docs synced (`./cache <cmd>` → `./cachectl <cmd>`, 28 replacements; the `CACHE_DIR=./cache data-dir` value correctly untouched). NB: the documented command name changes `cache`→`cachectl`; the operator may later prefer a different collision resolution (e.g. relocating the data dir) — the capability is restored now and the name choice is reversible.

## Verification (captured, re-run independently by the conductor §11.4.142)

```
# cachectl works LIVE against the rootless-podman cache (read-only):
$ ./cachectl stats|size|list -> exit 0, real figures (Cache Directory, 4.0K, Files: 2, full tree)
# §11.4.135 guard (RED_MODE polarity §11.4.115):
$ tests/regression/cache_cli_present_test.sh -> GREEN
PASS (dispatches all 7 subcommands)
$ RED_MODE=1 tests/regression/cache_cli_present_test.sh -> RED
PASS (reproduces "CLI absent → unusable")
# §1.1 mutation (conductor's own): drop `trim` from dispatch -> guard FAILs
# "missing-subcommands:[trim]" (bash -n still clean = assertion, not parse error);
# restored byte-identical md5 7e935b1deb4fed1435f6b48274844c2f (before==after).
# Suites (conductor re-run):
$ bash tests/comprehensive-test.sh -> 44 run / 38 pass / 0 fail / 6 skip (the 4 cache-CLI checks now PASS)
$ bash tests/run-tests.sh -> 45 run / 39 pass / 0 fail / 6 skip, exit 0 (incl. BUGFIX-CACHECLI GREEN+RED)
```

Honest gap (§11.4.6): the invalidate squid-flush WIRING is proven (CONTAINER\_RUNTIME=podman, is\_container\_running proxy-squid=TRUE, podman branch selected) but the live squid -k rotate was not executed end-to-end (target-safety §11.4.133 — not flushing the live proxy's cache); destructive subcommands were proven on a throwaway dir. warmup remains the original documented placeholder.

Evidence: qa-results/cachectl/, qa-results/regression/cachecli/.

---

## BUGFIX-0008 — un-audited mutation window: control-API mutate+audit were two separate store calls (audit-fail left the mutation persisted)

- **Type:** Bug (latent data-integrity defect — transactional atomicity; P6 WARNING-4)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** control-plane/internal/store/store.go (WithTx), internal/store/postgres.go (dbExecutor seam + real tx), internal/api/handlers.go (mutateWithAudit), 2 test fakes, internal/api/atomicity\_test.go (§11.4.135 guard), internal/store/postgres\_integration\_test.go (real-PG proof)

- **Workable item:** #52 (P6 review WARNING-4 follow-up)

## **Symptom & root cause (FACT — §11.4.102/ §11.4.124 investigation)**

All 9 mutating control-API handlers did TWO separate store calls — Upsert\*/Delete\* then a distinct AppendAudit — with no transaction spanning them. Proven on the pre-fix artifact (RED\_MODE=0 FAILED): when AppendAudit fails, the mutation is already durable and the handler returns HTTP 500 → an **un-audited mutation persists** (a silent integrity hole: the audit trail no longer reflects the data).

## **Fix (at source, §11.4.150 pgx-tx research)**

One store-interface method WithTx(ctx, func(tx Queries) error) error (chosen over 9 per-op \*WithAudit methods — 1 vs 9, audit SQL in one place). Real impl begins a \*sql.Tx (a dbExecutor seam lets both \*sql.DB and \*sql.Tx satisfy the query path with zero SQL duplication), commits on nil / rolls back on error; the fake snapshot-restores. The handler seam mutateWithAudit runs mutate(tx) + AppendAudit inside ONE WithTx — the mutation error passes through UNWRAPPED (so errors.Is(..., ErrNotFound)→404 is preserved), the audit error is wrapped (→500 + rollback). The store owns begin/commit/rollback; the handler never orchestrates a transaction it cannot roll back.

## **Verification (captured, re-run independently by the conductor §11.4.142)**

```
# §11.4.135 guard atomicity_test.go (RED_MODE polarity, 3 entity
types):
# RED_MODE=0 GREEN – audit-fail rolls back the mutation (0
profiles / row restored / 0 targets)
# RED_MODE=1 reproduces the defect on the 2-call pre-fix path
# Conductor §1.1 mutation: swallow the audit error in the WithTx
seam ->
# atomicity_test FAILs with real assertions (audit-fail returns
200/204 not 500,
# across all 3 subtests) -> byte-identical restore md5
a0fb9b65dac430e641130200bcb802d4.
$ go test -race -count=3 -short ./internal/... -> all 8
packages ok, no data races (§11.4.50)
$ go test -run TestIntegration_WithTxAtomicAuditAndMutation ./
internal/store/
-> PASS 4.76s (real postgres:16-alpine: commit persists both;
rollback leaves NEITHER)
$ go build/vet ./... exit 0; gofmt -l . empty
```

Honest gaps (§11.4.6): the `-count=3` determinism sweep is the logic layer (the real-PG integration is proven once — booting N postgres containers is wall-time non-deterministic by nature, §12.6); the fake `WithTx` is single-process snapshot/restore (real atomicity proven separately against live PG); nested `WithTx` is unsupported (documented; handlers never nest). Operator PG (lava-postgres-thinker) never touched — the integration test boots a throwaway `hp-it-pg-<port>` (`--rm, t.Cleanup`).

Evidence: pasted `-race/integration` output; test at `internal/api/atomicity_test.go`.

## **BUGFIX-0009 — VPN-aware dynamic proxy FAIL-OPENED: tunnel-down leaked direct to the internet instead of a branded 503 (P10 security defect)**

- **Type:** Bug (RELEASE-BLOCKING security defect — fail-open egress leak; §11.4.129 huge-blocker)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** `docker-compose.dynamic.yml` (entrypoint override), `config/squid/squid.dynamic.conf` (NEW fail-closed dynamic base), `config/squid/Containerfile.dynamic` (bakes fail-closed base + `*.squid` glob + branded `ERR_TUNNEL_DOWN` page + `00-failclosed.squid` default + `debian.conf` neutralize), `config/squid/errors/ERR_TUNNEL_DOWN` (NEW branded page), `config/squid/templates/dynamic-routing.conf.tmpl` + `control-plane/internal/routing/routing.go` + `control-plane/internal/routing/testdata/squid_dynamic.golden` (gated allow localnet AFTER deny `!tun_up`), `control-plane/internal/routing/routing_failclosed_test.go` (NEW §11.4.135 guard), `control-plane/internal/routing/routing_integration_test.go` (fail-closed placement)
- **Workable item:** #38 (P10 fail-closed half)

### **Symptom & root cause (FACT — §11.4.102 investigation, captured live)**

Booted `./start --dynamic` with the tunnel DOWN (no WireGuard creds): a client request through squid returned **HTTP 200 with `HIER_DIRECT/<ip>` in squid's own access.log** — squid egressed DIRECTLY to the real internet instead of denying the request. A

VPN-aware proxy that leaks direct when its tunnel is down is the exact opposite of its purpose. FIVE stacked root causes (§11.4.6 FACT, file:line):

1. **Entrypoint override.** control-plane/Containerfile:55  
ENTRYPOINT ["compiler"]; docker-compose.dynamic.yml overrode command: (not entrypoint:) for proxy-compiler + proxy-healthd → both ran compiler <args> and died --dsn required. The include was never rendered; redis was never seeded; tun\_up was unevaluable.
2. **depends\_on ignored.** podman-compose ignores condition: service\_completed\_successfully, so squid started on the permissive base even though the compiler failed.
3. **Fail-OPEN config assembly.** Containerfile.dynamic baked the *static* squid.conf (unconditional http\_access allow localnet) and appended the include AFTER http\_access deny all → first-match-wins made the fail-closed deny !tun\_up unreachable; no branded error page was baked.
4. **RC-4 (dominant leak):** the ubuntu/squid base image ships /etc/squid/conf.d/debian.conf with its OWN unconditional allow localnet; the \*.conf include glob pulled it in — so the stack leaked even with a perfect compiler (and \*.conf would also grab the Dante \*.sockd.conf → parse break).
5. **RC-5 (compiler couldn't render):** the generated volume was namespace-root-owned (compiler runs non-root helix → Permission denied); the one-shot raced Postgres init; and squid FATALs on a zero-match include glob.

## **Fix (fail-closed BY DEFAULT — at source; §11.4.150 squid never\_direct/deny\_info/error\_directory research)**

- **New config/squid/squid.dynamic.conf** baked as the running config (static squid.conf UNTOUCHED, §11.4.122): NO unconditional allow localnet, include /etc/squid/conf.d/\*.squid placed BEFORE the terminal http\_access deny all. A MISSING include falls through to deny all → fail-closed.
- **Positive allow-list glob \*.squid** (compiler --squid-out .../dynamic-routing.squid) matches ONLY the compiler's file — never debian.conf/\*.sockd.conf; debian.conf allow localnet additionally sed-neutralized (defense-in-depth).
- **Gated client-allow:** the template now emits never\_direct allow all → http\_access deny !tun\_up (tunnel down → branded 503) → http\_access allow localnet (the ONLY client-allow; reached only when tun up) → deny\_info 503:ERR\_TUNNEL\_DOWN.
- **Branded ERR\_TUNNEL\_DOWN page** baked + error\_directory pinned.
- **00-failclosed.squid** (rules-free) baked + written by the compiler wrapper before compile so the glob is never empty (contributes NO allow → deny all).

- **Entrypoint override** for proxy-compiler (/bin/sh -c wrapper) + proxy-healthd (healthd); :U volume mount + compiler retry-until-postgres-ready loop.

## Verification (captured, re-run INDEPENDENTLY by the conductor §11.4.142 via ./start --dynamic)

```
# §11.4.135 guard routing_failclosed_test.go (assembles the REAL
base + REAL
# rendered include, directive-lines-only so prose can't satisfy/
defeat a rule):
#   RED_MODE=0 GREEN – deny !tun_up before any allow localnet;
never_direct present; terminal deny all
#   RED_MODE=1 reproduces the shipped fail-OPEN assembly (allow
localnet before deny all; include appended)
# Conductor §1.1 mutation: swap the template order (allow localnet
BEFORE deny !tun_up) ->
#   guard FAILs with an ASSERTION (build still compiles, §11.4.1)
-> byte-identical
#   restore md5 dc8f61241e4100bf60aea64b20cca906.
$ go build/vet ./... exit 0
```

```
# LIVE fail-closed proof (tunnel DOWN via ./start --dynamic;
evidence under
# qa-results/p10_failclosed_fix/conductor_reproof/):
$ podman exec proxy-squid squid -k parse -> exit 0, assembled
order:
```

```
... never_direct allow all / http_access deny !tun_up /
http_access allow localnet /
    deny_info 503:ERR_TUNNEL_DOWN tun_up / http_access deny
all
$ curl -x http://localhost:53128 http://example.com/    (x3,
deterministic §11.4.50)
    -> iter 1/2/3: http_code=503 ERR_TUNNEL_DOWN_in_body=3
<title>503 – VPN tunnel unavailable</title>
$ squid access.log (this-boot client 10.89.2.26): TCP_DENIED/
503 ... HIER_NONE/-    (x3, no HIER_DIRECT)
    squid PID stable 36->36 (no crash); MEM 45% (<=60% §12.6)
    operator lava-postgres-thinker/lava-api-go-thinker "Up 8
hours" before AND after (untouched)
    static proxy restored -> 200
```

Honest gaps (§11.4.6): (1) the **healthy path** (tunnel UP → allowed egress) and the **real-VPN-egress** proof are operator-gated on gluetun WireGuard credentials (§11.4.21) — only the fail-closed half (tunnel-down → branded 503) is proven autonomously. (2) The shared \${LOG\_DIR}/access.log is NOT rotated between boots, so HIER\_DIRECT lines from the PRE-FIX boot (different client IP 10.89.1.11) persist in the file; the current-boot signal is the 3 curl 503s + this-boot client 10.89.2.26 all TCP\_DENIED — not the historical aggregate count. (3) podman-compose ignores

depends\_on so squid can start before the compiler renders — the baked 00-failclosed.squid keeps that window fail-closed (production relies on restart: unless-stopped + the baked default).

Evidence: pasted squid -k parse + 3× 503/ERR\_TUNNEL\_DOWN + access.log TCP\_DENIED; guard at control-plane/internal/routing/routing\_failclosed\_test.go; proof artifacts under qa-results/p10\_failclosed\_fix/conductor\_reproof/.

## **BUGFIX-0010 — two P12-retest-discovered test-suite bluffs: CONST-033 scanner false-FAIL + comprehensive-test admin fail-open**

- **Type:** Bug (test-suite integrity — a §11.4.1 false-FAIL + a §11.4.68/§11.4.69 fail-open false-PASS)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** scripts/host-power-management/check-no-suspend-calls.sh (EXCLUDE\_DIRS/PATHS), tests/comprehensive-test.sh (\_port\_topology\_check + test\_ports + test\_admin), tests/run-tests.sh (register the new guard), tests/regression/comprehensive\_admin\_topology\_test.sh (NEW §11.4.135 guard), docs/scripts/comprehensive\_admin\_topology\_test.md (+ html/pdf), control-plane/cmd/healthd/healthd\_integration\_test.go (fake-WG-key §11.4.10 comment)
- **Workable item:** #39 (P12 iterate-to-GO — the full retest found both)

### **Symptom & root cause (FACT — §11.4.102, independently re-verified by the conductor)**

The P12 full retest surfaced two test-integrity defects (neither a product defect; the proxy genuinely serves — but a green suite that lies is exactly what §11.4 forbids):

#### **(A) CONST-033 scanner false-FAIL (§11.4.1).**

no\_suspend\_calls\_challenge.sh exited 1. All 26 hits were forbidden-command *strings* inside vendored-submodule DOCUMENTATION that describes the CONST-033 ban (submodules/{challenges,containers}/ docs/HOST\_POWER\_MANAGEMENT.html, a CHALLENGE.md) plus the scanner's OWN captured output under qa-results/ — ZERO hits in the project's shippable tree. Root cause: the scanner excluded HOST\_POWER\_MANAGEMENT.md but not its §11.4.65 .html/.pdf exports, and did not exclude the vendored submodules/tree (which police their own CONST-033 compliance, exactly like

the already-excluded constitution) nor the generated qa-results/output. A guard that FAILs on its own ban-documentation is a §11.4.1 false-FAIL.

**(B) comprehensive-test admin fail-open (§11.4.68/§11.4.69).**

test\_ports() + test\_admin() asserted :58080 health purely on "is something listening / does it answer 200?" — with NO check the responder is the project's proxy-admin. In the host topology proxy-admin is unpublished (internal port only) and :58080 is held by a foreign whoami that answers 200 to any path (and echoes Hostname: proxy-admin). So 3 checks were FALSE PASSes hitting the foreign service — a fail-open-to-whatever-answers bluff. run-tests.sh handles the same port correctly via an ownership check; comprehensive-test lacked it.

**Fix (at source)**

**(A)** EXCLUDE\_DIRS += submodules (vendored/owned submodules police their own CONST-033 compliance — same class as constitution) + qa-results/recordings/logs (generated);  
EXCLUDE\_PATHS HOST\_POWER\_MANAGEMENT.md →  
HOST\_POWER\_MANAGEMENT. (covers the .md/.html/.pdf export siblings).

**(B)** New \_port\_topology\_check(port, owner, label) mirroring run-tests.sh's \_ports\_check\_one: a listening port is a PASS only if the owner container is running AND publishes it (podman/docker port <owner> | grep :<port>); non-project-held + listening → SKIP;  
test\_ports+test\_admin both route through the ownership gate.

**Verification (captured, re-run by the conductor)**

```
# (A) CONST-033 scanner – §11.4.120 gate reconciliation (still catches REAL violations):
$ bash challenges/scripts/no_suspend_calls_challenge.sh
-> PASS (clean tree)
$ printf 'systemctl suspend\n' > tests/_probe.txt; bash ../check-no-suspend-calls.sh .
    -> exit 1, 1 hit on the probe (guard NOT neutered – still FAILs a real invocation)
$ rm tests/_probe.txt; bash ../no_suspend_calls_challenge.sh
-> PASS again
$ bash challenges/scripts/host_no_auto_suspend_challenge.sh
-> 4 pass / 0 fail

# (B) comprehensive-test admin fail-open – §11.4.135 guard (RED_MODE polarity):
# podman port proxy-squid -> :53128 (owns), proxy-dante -> :51080 (owns),
# proxy-admin -> (publishes nothing); :58080 held by foreign whoami pid 1106372.
$ bash tests/regression/comprehensive_admin_topology_test.sh
```

```
-> GREEN (foreign→SKIP, owned→PASS)
$ RED_MODE=1 ../comprehensive_admin_topology_test.sh
-> RED reproduces (foreign→PASS bluff)
$ bash tests/comprehensive-test.sh -> 35 pass / 0 fail / 8 skip
(admin now SKIP, not 3 false PASS)
$ bash tests/run-tests.sh -> 41 pass / 0 fail / 6 skip
(new guard registered GREEN+RED)
```

Honest boundary (§11.4.6): both are test-suite-integrity fixes — they make the suite HONEST (a false-FAIL stops lying about a clean tree; a fail-open stops passing on a foreign responder). Neither changes proxy behaviour. The admin interface being unreachable on host :58080 in this topology (proxy-admin unpublished) is a separate observation for the operator, not a proxy defect — the test now correctly SKIPS it rather than fabricating a PASS.

Evidence: guard at tests/regression/  
comprehensive\_admin\_topology\_test.sh; companion docs/scripts/  
comprehensive\_admin\_topology\_test.md.

---

## **BUGFIX-0011 — CONST-033 scanner false-FAIL: BUGFIXES ledger exclusion missed its .html export sibling (incomplete BUGFIX-0010)**

- **Type:** Bug (test-suite integrity — a §11.4.1 false-FAIL)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** scripts/host-power-management/check-no-suspend-calls.sh (EXCLUDE\_PATHS), tests/regression/no\_suspend\_export\_sibling\_test.sh (NEW §11.4.135 guard), tests/run-tests.sh (register the new guard), docs/scripts/no\_suspend\_export\_sibling\_test.md (+ html/pdf)
- **Workable item:** #39 (P12 iterate-to-GO — the §11.4.40 final-tree retest found it)

### **Symptom & root cause (FACT — §11.4.102, independently re-verified by the conductor)**

The §11.4.40 final-tree retest (run on the committed BUGFIX-0010 tree, 9ce8335) reported no\_suspend\_calls\_challenge.sh FAIL with exactly one hit: docs/issues/fixed/BUGFIXES.html:1210 — the systemctl suspend literal inside the BUGFIX-0010 **verification**

**block** (the ledger legitimately quotes the banned pattern when documenting the CONST-033 fix). ZERO hits anywhere in the shippable tree.

Root cause: BUGFIX-0010 generalized the HOST\_POWER\_MANAGEMENT. exclusion to cover its .html/.pdf export siblings, but the **pre-existing** ledger entry /docs/issues/fixed/BUGFIXES.md still named the .md extension explicitly — so the .md source was excluded (filtering the line-828 hit) while the §11.4.65-mandated .html sibling generated from it was **not**. .pdf escapes only because grep's -I skips binary files. Same sibling-blindness class BUGFIX-0010 fixed for HOST\_POWER\_MANAGEMENT. — simply not generalized to the BUGFIXES ledger. An incomplete fix, caught by the retest exactly as §11.4.40 intends.

## Fix (at source)

EXCLUDE\_PATHS: /docs/issues/fixed/BUGFIXES.md → /docs/issues/fixed/BUGFIXES. (extension-agnostic prefix covering .md + .html + .pdf), with a comment recording the sibling rationale. The scanner still catches a real invocation in any script and still trips on a **non-ledger** .html — the exclusion is BUGFIXES-specific, not "all .html".

## Verification (captured, re-run by the conductor — §11.4.120 reconciliation + §1.1)

```
$ bash challenges/scripts/no_suspend_calls_challenge.sh
-> PASS (clean tree)
$ printf '#!/bin/sh\nsystemctl suspend\n' > tests/_probe.sh
$ bash scripts/host-power-management/check-no-suspend-calls.sh .
-> exit 1, hit on _probe.sh
    (still catches a REAL invocation – gate NOT neutered)
$ (rogue non-ledger .html with the literal)
-> exit 1, hit on rogue.html
    (exclusion is BUGFIXES-specific, not "all html")
# §1.1 mutation – revert exclusion to ".md"-only:
$ (mutated) no_suspend_calls_challenge.sh
-> exit 1, hit on BUGFIXES.html
    (defect reproduced) ; restore byte-identical (md5 0c11a86...
816db5 match) -> PASS
$ tests/regression/no_suspend_export_sibling_test.sh ->
[PASS] GREEN (exit 0)
$ RED_MODE=1 tests/regression/no_suspend_export_sibling_test.sh ->
[PASS] RED reproduces (exit 0)
```

Honest boundary (§11.4.6): a test-suite-integrity fix making the scanner HONEST about its own fix-documentation; no proxy behaviour changes. The permanent §11.4.135 guard is fixture-driven, so it protects the sibling-exclusion invariant independently of the live ledger's future content.

Evidence: guard at tests/regression/  
no\_suspend\_export\_sibling\_test.sh; companion docs/scripts/  
no\_suspend\_export\_sibling\_test.md.

---

## **BUGFIX-0012 — comprehensive-test.sh false-FAIL on a third-party outage: external-site checks hard-FAILED instead of SKIPping when httpbin.org was down**

- **Type:** Bug (test-suite integrity — a §11.4.1 false-FAIL / §11.4.50 non-determinism / §11.4.98 non-re-runnable)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** tests/comprehensive-test.sh  
(`_external_egress_verdict` helper, the sites loop in `test_http_proxy`, the direct pre-probe in `test_concurrent`), tests/regression/external\_egress\_verdict\_test.sh (NEW §11.4.135 guard), tests/run-tests.sh (register the new guard), docs/scripts/external\_egress\_verdict\_test.md (+ html/pdf)
- **Workable item:** #39 (P12 iterate-to-GO — the §11.4.40 final-tree retest found it)

### **Symptom & root cause (FACT — §11.4.102, captured direct-vs-proxy probes)**

The §11.4.40 final-tree retest reported comprehensive-test.sh FAIL (33 pass / **2 fail** / 8 skip). Both fails were the SAME cause — httpbin.org was externally **down**:

- Access `https://httpbin.org/ip` — captured: DIRECT (no proxy) `curl https://httpbin.org/ip → HTTP 000/503` (host cannot reach it at all); PROXIED → 503 (the proxy's honest upstream-unreachable). The working sibling `api.ipify.org → 200` both direct and proxied, proving the proxy's egress is fine.
- Concurrent connections (10): Success 0/10 — the concurrency test hammered `https://httpbin.org/get`, all 10 failed for the same outage.

Root cause: both call sites decided

proxy\_http\_code == 200 ? PASS : FAIL with no direct-reachability distinction, so a **third-party outage** the proxy did not cause hard-FAILED the suite — a §11.4.1 false-FAIL that also makes the suite non-deterministic (§11.4.50: retest #1 PASSEd when httpbin.org was up, retest #2 FAILED when it was down) and not re-runnable (§11.4.98). The sibling test\_large\_file() already handled this exact class (its network\_unreachable\_external SKIP gate); the sites loop + concurrency test simply were not given the same treatment.

## Fix (at source)

New shared pure classifier \_external\_egress\_verdict(proxy\_code, direct\_code): proxy 200 → PASS; proxy fails but direct 200 → FAIL (the proxy cannot fetch a directly-reachable site — a REAL proxy defect, the anti-bluff catch preserved); proxy fails and direct fails → SKIP (external endpoint down — network\_unreachable\_external, §11.4.3). The sites loop now probes direct-reachability on a proxy miss and routes through the classifier; test\_concurrent pre-probes direct-reachability and SKIPS a down endpoint (a real concurrency defect on a reachable endpoint still FAILs). Not fail-open: the proxy's egress is still proven every run by the reachable sibling (api.ipify.org) plus the earlier www.google.com PASSes.

## Verification (captured, re-run by the conductor — §11.4.115 RED→GREEN + §1.1)

```
# helper truth table (unit):
200,000 -> PASS    503,200 -> FAIL    503,000 -> SKIP    000,000 ->
SKIP
# live comprehensive-test.sh on the fixed tree (httpbin.org still
down):
  -> exit 0 : 33 pass / 0 fail / 10 skip
  -> Access https://httpbin.org/ip    = SKIP (proxy=503 direct=503,
network_unreachable_external)
  -> Concurrent connections (10)      = SKIP (endpoint unreachable
directly)
  -> Access https://api.ipify.org     = PASS (proxy egress genuinely
proven – not fail-open)
# §11.4.135 guard:
$ tests/regression/external_egress_verdict_test.sh          ->
[PASS] GREEN (exit 0)
$ RED_MODE=1 tests/regression/external_egress_verdict_test.sh ->
[PASS] RED reproduces the false-FAIL (exit 0)
# §1.1 paired mutation – revert the helper to proxy!=200=>FAIL:
$ (mutated) external_egress_verdict_test.sh                ->
```

[FAIL] REGRESSION (exit 1) ; restore byte-identical (md5 match) -> PASS

Honest boundary (§11.4.6): a test-suite-integrity fix making the suite HONEST about third-party outages (SKIP, not FAIL) while STILL catching a real proxy egress defect (direct-reachable-but-proxy-fails → FAIL); no proxy behaviour changes. The proxy was verified genuinely working throughout (api.ipify.org 200 direct+proxied).

Evidence: guard at tests/regression/  
external\_egress\_verdict\_test.sh; companion docs/scripts/  
external\_egress\_verdict\_test.md.

## **BUGFIX-0013 — CONST-033 scanner false-FAIL: governance-carrier exclusions (CLAUDE.md etc.) missed their .html/.pdf export siblings (F4, incomplete BUGFIX-0011)**

- **Type:** Bug (test-suite integrity — a §11.4.1 false-FAIL, latent; the export-sibling blind spot BUGFIX-0011 fixed for the ledger but not for the governance carriers)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** scripts/host-power-management/check-no-suspend-calls.sh (EXCLUDE\_PATHS — the five governance entries), tests/regression/no\_suspend\_export\_sibling\_test.sh (GREEN branch extended with a governance-doc sibling case, §11.4.135), docs/scripts/no\_suspend\_export\_sibling\_test.md (companion, Rev 2), + .html/.pdf.
- **Discovered by:** the §11.4.118 anti-bluff discovery sweep (finding F4, CONFIRMED-latent).

Root cause: BUGFIX-0011 made the bug-ledger exclusion extension-agnostic (/docs/issues/fixed/BUGFIXES.) but the governance carriers — CONSTITUTION.md, AGENTS.md, CLAUDE.md, QWEN.md, GEMINI.md — stayed extension-specific. These files ARE the source of CONST-033 and legitimately quote the banned host-power literals (pm-suspend, dbus-send ... Suspend, etc.). The moment §11.4.65 generates their .html/.pdf export siblings, the .md-only exclusion misses the sibling and the scanner false-FAILs on its own governance documentation — the identical sibling-blindness class as BUGFIX-0011, one layer over.

Fix: make the five governance entries extension-agnostic prefixes (CONSTITUTION., AGENTS., CLAUDE., QWEN., GEMINI.) so .md + .html + .pdf (+ .json) are all excluded, while a **non-governance** file carrying a banned literal and any **real script invocation** still trip the scanner (gate not neutered, §11.4.120).

## Verification (captured, §11.4.115 RED→GREEN + §1.1 + §11.4.146 reproduce-first)

```
# reproduce-first (pre-fix scanner vs a CLAUDE.html governance
sibling):
$ bash check-no-suspend-calls.sh <fixture-with-CLAUDE.html> ->
exit 1, CLAUDE.html listed (false-FAIL reproduced)
# post-fix GREEN: CLAUDE.html + AGENTS.pdf excluded, a real
scripts/real.sh still caught (exit 1 on real.sh only)
# real challenge on the actual tree:
$ bash challenges/scripts/no_suspend_calls_challenge.sh ->
OK / PASS (no regression)
# §11.4.135 guard (extended):
$ tests/regression/no_suspend_export_sibling_test.sh ->
[PASS] GREEN (excludes ledger + governance siblings)
$ RED_MODE=1 tests/regression/no_suspend_export_sibling_test.sh ->
[PASS] RED reproduces the sibling-blind false-FAIL
# §1.1 paired mutation – revert "CLAUDE." -> "CLAUDE.md" in the
scanner:
$ (mutated) no_suspend_export_sibling_test.sh ->
[FAIL] gov_flagged=yes (exit 1) ; restore byte-identical (md5
match) -> PASS
```

Honest boundary (§11.4.6): a latent test-suite-integrity fix — the false-FAIL only fires once the governance-doc HTML/PDF exports exist; it changes NO product behaviour and the scanner still catches every real host-power invocation.

Evidence: guard at tests/regression/  
no\_suspend\_export\_sibling\_test.sh; companion docs/scripts/  
no\_suspend\_export\_sibling\_test.md.

## BUGFIX-0014 — proxy-connectivity checks false-FAIL on a third-party / local-internet outage (F2/F3)

- **Type:** Bug (test-suite integrity — a §11.4.1 false-FAIL; the connectivity scripts hard-FAILED a healthy proxy whenever the probed SITE was unreachable, making them non-deterministic (§11.4.50) and not re-runnable (§11.4.98))
- **Status:** Fixed
- **Date:** 2026-07-01

- **Affected files:** tests/lib/evidence.sh (new proxy\_conn\_verdict classifier
  - \_code\_in + port\_is\_listening), tests/verify-proxy.sh + tests/final-verify.sh (tests 1–4 routed through a conn\_check helper), tests/lib/evidence\_selftest.sh (8 truth-table cases, now 37/37), tests/regression/proxy\_conn\_verdict\_test.sh (new §11.4.135 guard), tests/run-tests.sh (guard registered, GREEN+RED), docs/scripts/proxy\_conn\_verdict\_test.md (companion), + .html/.pdf.
- **Discovered by:** the §11.4.118 anti-bluff discovery sweep (findings F2/F3, CONFIRMED).

Root cause: verify-proxy.sh and final-verify.sh classified every through-proxy check as code == expected -> PASS else FAIL. That conflates two entirely different worlds: (a) the proxy is broken (a real defect worth a FAIL), and (b) the *site* the probe targets is momentarily unreachable (an external outage the proxy cannot be blamed for). When connectivitycheck.gstatic.com / www.google.com blip — or the host has no egress at all — a perfectly healthy proxy scored FAIL. That is a §11.4.1 false-FAIL: the suite reports a product defect that does not exist, and cannot be re-run to a stable verdict.

Fix: a single client-side classifier proxy\_conn\_verdict <proxy\_code> <direct\_code> <expected> <port\_listening> in the shared evidence.sh — the *sink-side* discipline of BUGFIX-0012 (\_external\_egress\_verdict) applied to the *client* side:

| proxy in<br>expected | direct in<br>expected | port<br>listening | verdict                                                                                                                                                                                                        |
|----------------------|-----------------------|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| yes                  | —                     | —                 | <b>PASS</b>                                                                                                                                                                                                    |
| no                   | yes                   | —                 | <b>FAIL</b> (site reachable directly, proxy can't serve it — a real defect whether the port is up-but-broken OR the proxy crashed; the positive direct signal outranks the port probe, §11.4.68 not fail-open) |
| no                   | no                    | yes               | <b>SKIP:network_unreachable_external</b> (site outage — no §11.4.1 false-FAIL)                                                                                                                                 |
| no                   | no                    | no                | <b>SKIP:topology_unsupported</b> (proxy absent AND no network signal to substantiate a FAIL)                                                                                                                   |

verify-proxy.sh / final-verify.sh call it through a conn\_check wrapper; the VPN egress check is unchanged (still an honest operator\_attended SKIP absent a live tunnel, §11.4.52).

**Independent-review reconciliation (§11.4.120/§11.4.134):** the first cut gated the port-listening probe *before* the direct-reachability check, so a fully-crashed proxy (port down) on a host

with working internet resolved to SKIP:topology\_unsupported instead of FAIL — a §11.4.68 fail-open (the conn\_check consumers gate their exit banner on the FAIL counter only). An independent reviewer caught it; the fix was reconciled (not fake-passed): a positive **direct**-reachability signal now out-ranks the port probe, so a dead-proxy-on-a-working-host FAILs; the port probe only distinguishes the two already-non-FAIL SKIP reasons. The guard + selftest truth tables were updated to pin the corrected behaviour (000 204 '204' no -> FAIL).

## **Verification (captured, §11.4.115 RED→GREEN + §1.1 + §11.4.146 reproduce-first)**

```
# unit truth table (both polarities of the classifier, incl.
crashed-proxy + exact-match cases):
$ bash tests/lib/evidence_selftest.sh                -> 1..37
tests=37 passed=37 failed=0
# §11.4.135 guard:
$ tests/regression/proxy_conn_verdict_test.sh        -> [PASS]
GREEN (PASS/FAIL/SKIP truth table)
$ RED_MODE=1 tests/regression/proxy_conn_verdict_test.sh -> [PASS]
RED reproduces the pre-fix false-FAIL (proxy=000 outage => FAIL)
# §1.1 paired mutation – outage branch SKIP -> FAIL in evidence.sh
proxy_conn_verdict:
$ (mutated) proxy_conn_verdict_test.sh    -> [FAIL] MISMATCH:
proxy_conn_verdict 000 000 204 yes -> FAIL (want SKIP) ; restore
byte-identical (md5 0d70728...ced5) -> PASS
# live smoke against the running proxy (:53128 / :51080):
$ bash tests/verify-proxy.sh    -> 4 PASS + 1 SKIP (VPN
operator_attended), exit 0
$ bash tests/final-verify.sh    -> 4 PASS + 1 SKIP (VPN
operator_attended), exit 0
```

Honest boundary (§11.4.6): a test-suite-integrity fix — it makes the connectivity checks deterministic + re-runnable and refuses to score a proxy FAIL for a site the host itself cannot reach; it changes NO product behaviour and STILL FAILs a genuine proxy defect (proxy down while the site is reachable directly). The narrower F1 (comprehensive-test.sh canaries) is tracked as its own focused pass to give each canary the defect-vs-intentional-probe judgment it needs.

Evidence: guard tests/regression/proxy\_conn\_verdict\_test.sh; unit tests/lib/evidence\_selftest.sh; companion docs/scripts/proxy\_conn\_verdict\_test.md.

# BUGFIX-0015 — ddos\_flood\_suite scored "survived the flood" PASS with no proof a flood occurred (F5)

- **Type:** Bug (test-suite integrity — a §11.4.69 evidence gap / §11.4.1 PASS-bluff: a vacuous "survived" PASS on a flood that issued zero requests)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** tests/dynamic/suites/ddos\_flood\_suite.sh (new pure flood\_survival\_verdict classifier + flood\_total/flood\_responses counters in both the vegeta and curl paths + proxy-listening probe), tests/regression/ddos\_flood\_evidence\_test.sh (new §11.4.135 guard), docs/scripts/ddos\_flood\_evidence\_test.md (companion), + .html/.pdf.
- **Discovered by:** the §11.4.118 anti-bluff discovery sweep (finding F5, CONFIRMED).

Root cause: the suite's "degraded-not-collapsed" GREEN gate asserted only `pid_stable=1 && recovery=200`. The flood request counters were captured into the evidence file but never asserted `> 0`, and `ab_pass_with_evidence` accepts any non-empty evidence file (the recovery line is always appended). So a run in which the flood issued ZERO requests still PASSED as "survived the flood" — the proxy survived nothing. A vacuous survival claim (§11.4.69 evidence gap / §11.4.1 bluff).

Fix: a pure self-testable classifier `flood_survival_verdict`  
`<pid_stable> <rec> <flood_total> <flood_responses>`  
`<proxy_listening>` requiring POSITIVE captured flood evidence — `flood_total>0` (requests issued) AND `flood_responses>0` (measurable non-000 responses) — before any survival PASS. A zero-flood run on a listening proxy → FAIL: no-flood-evidence; on an absent proxy → honest SKIP: topology\_unsupported (never a silent PASS); a real-flood crash/no-recovery → FAIL: crashed-or-no-recovery.

## Verification (captured, independently reviewed §11.4.142 — GO)

```
$ bash tests/regression/ddos_flood_evidence_test.sh ->
[PASS] GREEN (4-fixture verdict: zero=FAIL, survived=PASS,
crashed=FAIL, absent=SKIP)
$ RED_MODE=1 tests/regression/ddos_flood_evidence_test.sh ->
[PASS] RED reproduces the pre-fix zero-flood PASS-bluff (faithful
to git-diff pre-fix gate)
# §1.1 paired mutation (neutralise the flood_total>0 guard):
$ (mutated) ddos_flood_evidence_test.sh -> [FAIL] ZERO=PASS
resurrected (real assertion mismatch) ; restore byte-identical
```

(md5 00a1b6f...49c4) -> PASS

# no-stack invocation -> honest SKIP:topology\_unsupported exit 0

Honest boundary (§11.4.6): a test-suite-integrity fix — it requires proof the flood actually happened before any survival PASS; no false-PASS tuple exists. Known follow-up (reviewer LOW note, non-bluff): a hard crash where the port ALSO stops listening currently reports SKIP:topology\_unsupported (honest SKIP, never a false-PASS) rather than FAIL:crashed — precise crashed-vs-absent disambiguation needs a distinct "observed-up-before" signal and is tracked separately (the naive pid\_stable=0 -> FAIL would false-FAIL the legitimate no-stack SKIP, §11.4.1).

Evidence: guard tests/regression/ddos\_flood\_evidence\_test.sh;  
companion docs/scripts/ddos\_flood\_evidence\_test.md.

## BUGFIX-0016 — benchmark performance ratchet never compared against a persistent baseline (F6)

- **Type:** Bug (test-suite integrity — a §11.4.169(13) / §11.4.1 bluff: a performance suite that always PASSes regardless of a real regression)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** tests/dynamic/suites/benchmark\_suite.sh (new pure bench\_regression\_verdict classifier; baseline moved to a committed path; seed-once
  - SKIP on absent baseline; FAIL on regression beyond tolerance; auto-refresh drift removed), tests/regression/benchmark\_baseline\_ratchet\_test.sh (new §11.4.135 guard), docs/scripts/benchmark\_baseline\_ratchet\_test.md (companion), tests/dynamic/baselines/README.txt (committed baseline-path anchor), + .html/.pdf.
- **Discovered by:** the §11.4.118 anti-bluff discovery sweep (finding F6, CONFIRMED).

Root cause: the benchmark defaulted its regression baseline to qa-results/p9-harness/bench\_baseline.p95 — a path under the git-IGNORED qa-results/ tree (.gitignore). So the baseline was a throwaway that never persisted across clean runs → base\_p95="" → the p50/p95/p99-vs-baseline comparison never fired → every run PASSED purely on the absolute budget regardless of a real regression. Compounding it: a first run with no baseline emitted a PASS (not a seed+SKIP), and a PASS auto-refreshed the throwaway (ratchet drift). A §11.4.169(13) / §11.4.1 bluff — a performance guard that cannot fail on a regression.

Fix: a pure `bench_regression_verdict()` classifier; the baseline moved to the committed/tracked path `tests/dynamic/baselines/benchmark_p95.baseline`; a first run with no committed baseline SEEDs it from the REAL measurement and SKIPS-with-reason (never a silent budget-only PASS, never a fabricated value per §11.4.6); a present baseline is compared and a p95 growth beyond `BENCH_REGRESS_PCT FAILs` as a regression; the baseline is seeded once and never auto-refreshed.

## Verification (captured, independently reviewed §11.4.142 — GO)

```
$ bash tests/regression/benchmark_baseline_ratchet_test.sh
-> [PASS] GREEN (PASS in-tolerance + FAIL:regression 50%>25% +
SEED no-baseline + FAIL:budget)
$ RED_MODE=1 tests/regression/benchmark_baseline_ratchet_test.sh
-> [PASS] RED reproduces the pre-fix budget-only bluff (PASSes a
50%-regressed p95)
# §1.1 paired mutation (neutralise the tolerance compare):
$ (mutated) benchmark_baseline_ratchet_test.sh -> [FAIL]
REGRESS=PASS (real assertion mismatch) ; restore byte-identical
(md5 70860ed...f751) -> PASS
# baseline path NOT gitignored: git check-ignore tests/dynamic/
baselines/* -> rc=1 (empty)
```

Honest boundary (§11.4.6): a test-suite-integrity fix — it makes the ratchet real. The `benchmark_p95.baseline` value file is intentionally seed-on-first-real-run (fabricating a value would violate §11.4.6); after the first genuine P10 measurement the operator commits the seeded baseline to arm the ratchet — documented in `tests/dynamic/baselines/README.txt`.

Evidence: guard `tests/regression/benchmark_baseline_ratchet_test.sh`; companion docs/scripts/`benchmark_baseline_ratchet_test.md`.

---

## BUGFIX-0017 — comprehensive-test.sh proxy canaries false-FAIL on a third-party / local-internet outage (F1)

- **Type:** Bug (test-suite integrity — Helix Constitution §11.4.1 false-FAIL: a healthy proxy hard-FAILs when an external site is down)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** `tests/comprehensive-test.sh` only (new `conn_check` wrapper; `test_http_proxy` basic + HTTPS-through-proxy canaries; `test_socks_proxy` basic + HTTPS-through-

SOCKS canaries; test\_dns DoH-Answer canary re-routed through the same classifier via synthetic ANSWER/MISS tokens; test\_network\_client HTTP + SOCKS canaries driven on the real interface IP via a 6th proxy\_host arg). Consumes the already-committed tests/lib/evidence.sh classifier from BUGFIX-0014 — no library change in this lane.

- **Discovered by:** the §11.4.118 anti-bluff discovery sweep (finding F1, CONFIRMED).

Root cause: seven proxy canaries in comprehensive-test.sh used the pre-BUGFIX-0014 pattern code != expected -> FAIL with no direct-reachability / port gate. So when a third-party endpoint (connectivitycheck.gstatic.com, www.google.com, dns.google) was momentarily down, or the local internet uplink dropped, the canary hard-FAILED a perfectly healthy proxy — a §11.4.1 false-FAIL, non-deterministic (§11.4.50), not re-runnable (§11.4.98). The exact class BUGFIX-0014 already de-bluffed in verify-proxy.sh / final-verify.sh, still live in this suite.

Fix: a conn\_check <label> <scheme> <port> <url> <expected-codes> [proxy\_host] wrapper routes each canary through the same anti-bluff classifier as verify-proxy/final-verify — curl through the proxy → \_code\_in → on a miss, curl the SAME url DIRECTLY + port\_is\_listening → proxy\_conn\_verdict → PASS / FAIL (proxy miss but url reachable directly = real defect, §11.4.68 — never fail-open) / SKIP (proxy miss AND direct miss = external outage, §11.4.3 — never a false-FAIL). The DoH canary asserts BODY content (a JSON Answer field), not an HTTP code, so it encodes answer-present/absent as synthetic ANSWER/MISS tokens and reuses proxy\_conn\_verdict (the classifier is domain-agnostic set-membership via \_code\_in, so the tokens behave exactly like codes) — the content assertion is preserved: a 200-with-no-Answer proxy reply is still a MISS. The \_external\_egress\_verdict "various sites" loop was already de-bluffed and left unchanged.

## **Verification (captured, conductor live smoke against the real data plane §11.4.142 — GO)**

```
# data plane :53128 listening=yes (live proxy)
CASE1 working-proxy real-endpoint (connectivitycheck.gstatic.com/
generate_204):
    proxy_code=204  verdict=PASS
(expect PASS)
CASE2 working-proxy simulated outage (203.0.113.253 TEST-NET-3):
    proxy_code=000000 direct=000000
verdict=SKIP:network_unreachable_external
    (expect SKIP:* — the old blind `code!=expected->FAIL`
produced a false-FAIL here)
$ bash -n tests/comprehensive-test.sh    -> OK
```

evidence: qa-results/regression/comprehensive\_f1\_conductor\_smoke/  
smoke.\*.txt

No new §11.4.135 guard in this lane: the classifier proxy\_conn\_verdict is already covered by BUGFIX-0014's committed guard tests/regression/proxy\_conn\_verdict\_test.sh (full truth-table, RED/GREEN polarity, §1.1 mutation). This lane only re-wires callers onto that already-guarded classifier; the conductor live smoke above is its runtime proof.

Honest boundary (§11.4.6): a test-suite-integrity fix — it stops healthy-proxy false-FAILs on external outages while preserving every real proxy-defect FAIL. It does not change proxy behaviour.

Evidence: conductor smoke qa-results/regression/  
comprehensive\_f1\_conductor\_smoke/; classifier guard tests/  
regression/proxy\_conn\_verdict\_test.sh (BUGFIX-0014).

---

## **BUGFIX-0018 — assert\_egress\_ip fail-opens the VPN-routing §15 proof when the host's real IP is undeterminable (F7 + F-1)**

- **Type:** Bug (anti-bluff library fail-open — Helix Constitution §11.4.68: the hardest-to-fake VPN-routing proof loses half its assertion, so a NO-VPN case can fake-PASS)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** tests/lib/evidence.sh (assert\_egress\_ip host-undeterminable guard + new \_evidence\_ip\_shaped validator), tests/lib/evidence\_selftest.sh (F7 + F-1 cases, now 45), tests/regression/assert\_egress\_ip\_host\_unknown\_test.sh (new §11.4.135 guard), docs/scripts/assert\_egress\_ip\_host\_unknown\_test.md (companion), tests/run-tests.sh (registers this guard + closes the F5/F6 registration gap — see note below), + .html/.pdf.
- **Discovered by:** the §11.4.118 anti-bluff discovery sweep (finding F7, CONFIRMED); F-1 by the independent §11.4.142 review of the F7 fix (GO + hardening finding).

Root cause: assert\_egress\_ip proves VPN routing with TWO independent halves — egress == expected\_exit AND egress != host\_real (design §15: an egress that equals the host's real IP means traffic was NOT routed via any VPN). Callers learn host\_real via curl ifconfig.me || echo "unknown" (verify-proxy / final-verify / comprehensive-test) or || true (real\_vpn\_egress\_proof). When that IP-echo was unreachable, host\_real became the literal "unknown" / "". Comparing the

observed egress against "unknown"/"" trivially satisfies "different", silently COLLAPSING the !=host half — so a genuine egress == host (NO-VPN §15 bluff) could still PASS. A §11.4.68 fail-open: the anti-VPN-bluff check losing half its assertion the moment the host IP is unknown.

Fix (F7): when host\_real is undeterminable the !=host half is UNVERIFIABLE, so the call returns exit-2 OPERATOR-BLOCKED (§11.4.69 reason network\_unreachable\_external) — NEVER a fail-open PASS/SKIP-as-PASS. A definitively-wrong exit is still a provable defect and FAILs(1); a fully-known correctly-routed case still PASSes(0). Hardening (F-1, from the review): host\_real is validated to be IP-SHAPED (\_evidence\_ip\_shaped — IPv4 with 0-255 octets or an IPv6 hex:colon form) rather than deny-listing the two literal sentinels ""/"unknown". A non-empty, non-"unknown" garbage value (a captive-portal / rate-limit HTML body a curl -s 200 can echo) or a non-public sentinel (0.0.0.0, 127.x, ::, ::1) is exactly as unverifiable as an empty one and takes the same exit-2 branch — closing the residual window where garbage host\_real could re-collapse the !=host half. F-1 is a strict superset: every prior F7 case behaves identically; only garbage/sentinel routing is newly closed.

## **Verification (captured, F7 independently reviewed §11.4.142 → GO; F-1 conductor-verified)**

```
$ sh tests/lib/
evidence_selftest.sh                                -> tests=45
passed=45 failed=0 (F7 + F-1 cases green)
$ bash tests/regression/
assert_egress_ip_host_unknown_test.sh                -> [PASS] GREEN
(unknown/empty/garbage/sentinel => OPERATOR-BLOCKED-2; wrong-exit
FAIL; genuine PASS kept)
$ RED_MODE=1 tests/regression/
assert_egress_ip_host_unknown_test.sh  -> [PASS] RED reproduces
the pre-fix fail-open (egress==host, host "unknown" -> rc0 PASS)
# §1.1 paired mutation (return 2 -> return 0 in the unverifiable-
host branch):
$ (mutated)
assert_egress_ip_host_unknown_test.sh                -> [FAIL]
"fail-open re-opened" (real rc mismatch) ; restore byte-identical
(md5 976cb15...d176d) -> PASS
# standing suite (data plane up): tests/run-
tests.sh                                             -> 59 run / 53 pass / 6 skip / 0 fail;
BUGFIX-0018 GREEN+RED both PASS
# no fail-open at any of the 5 callers (review-verified): exit-2
-> test_fail / _record FAIL / verbatim rc — never a PASS.
```

Note (§11.4.135 registration-gap closure): the F5 (ddos\_flood\_evidence\_test) and F6 (benchmark\_baseline\_ratchet\_test) standing guards, committed with BUGFIX-0015/0016, were

present on disk but NOT wired into `run-tests.sh`'s `test_regression_guards()`, so they never ran on a build — a live §11.4.135 gap this conductor audit surfaced. This change registers F5, F6 AND F7 (each GREEN + RED\_MODE=1) into the standing suite; the full-suite run above proves all three execute and gate.

Honest boundary (§11.4.6): an anti-bluff-library fix — it closes a fail-open in the hardest-to-fake routing proof and its standing-guard wiring. It does not change proxy behaviour. The genuine-PASS path (fully-known, correctly-routed egress) is preserved and guarded so the fix cannot over-block into false-FAILs (§11.4.1).

Evidence: `guard tests/regression/assert_egress_ip_host_unknown_test.sh`; companion docs/scripts/`assert_egress_ip_host_unknown_test.md`; unit cases `tests/lib/evidence_selftest.sh` (F7 + F-1 block).