

Hermetic protocol-promotion research — pure-python peer servers over a kernel-WireGuard netns tunnel

Revision: 1 **Last modified:** 2026-07-02T00:00:00Z **Status:** Research findings (deep multi-angle web research per §11.4.150 / §11.4.99). No code changed by the research pass. Authority: inherits constitution/Constitution.md per §11.4.35. **Scope:** strengthen the hermetic WireGuard test harness so operator-gated VPN-LAN protocol round-trips (Chromecast/DIAL, FTP, WebDAV, SMB, mDNS, SMTP/IMAP) can be promoted to run AUTONOMOUSLY inside unprivileged unshare -Urnm user+net namespaces joined by a real kernel-WireGuard tunnel, with pure-python-stdlib peer servers bound to the WG overlay address.

Harness context this research feeds

The committed harnesses (tests/vpn_lan/hermetic_wg_roundtrip.sh, hermetic_bridge_run.sh, hermetic_ftp_run.sh) prove a real payload round-trips over an encrypted kernel-WireGuard tunnel between two unprivileged network namespaces, fully rootless:

```
netns A (in the usersn)                netns B (peer /
holder)
veth0 10.9.0.1 — underlay (UDP) — veth1 10.9.0.2    <-
carries encrypted WG
wg0 10.10.0.1 == WireGuard tunnel == wg0 10.10.0.2  <- the
overlay
python3 peer server
bound to 10.10.0.2
```

The peer server binds the WG-only overlay 10.10.0.2 (allowed-ips 10.10.0.2/32), reachable ONLY through the tunnel; independent oracles gate PASS (payload round-trip + wg show handshake with rx>0 && tx>0); a per-layer golden-bad (WG_MUT=badkey, H2_MUT=badeureka, FT_MUT=empty) is the §1.1 control. The live protocol tests (SMB/NFS/FTP/SFTP/WebDAV/IMAP/SMTP/POP3S/Cast/DIAL/ADB) are AUTHORED but SKIP-gated on the operator's

sword/Mullvad bridge. This research is about replacing the "need a live remote server" gate with a pure-stdlib peer server inside netns B.

1. Pure-python-stdlib FTP server correctness in a network namespace

RFC 959 §4.1.2: the 227 Entering Passive Mode (h1,h2,h3,h4,p1,p2) reply encodes the **host address the server is listening on** (h1 = high octet) and the data port as $p1*256 + p2$. The load-bearing gotcha: a naïve server advertises 127,0,0,1 (or the underlay), so the client dials an unreachable address and the data channel hangs — the classic FTP-in-NAT/namespace bug (vsftpd fixes it with pasv_address). For our harness the reachable address is the WG overlay 10.10.0.2; the server **MUST** encode 10,10,0,2 in the 227 reply. **EPSV** (229 Entering Extended Passive Mode (|||port|), RFC 2428) sidesteps the IP-encoding entirely — it carries no address, so the client reuses the control connection's peer (10.10.0.2 over the tunnel); curl prefers EPSV. Because the overlay is allowed-ips 10.10.0.2/32, a successful data connection is itself proof of tunnel traversal (the client cannot reach 10.10.0.2 any other way).

Minimal command set curl --ftp-pasv drives for LIST + RETR: USER/PASS/SYST/PWD/TYPE/(EPSV|PASV)/LIST/RETR/QUIT. Python has NO stdlib FTP *server* (only the ftplib client), so a ~85–120-line socket-based server is required — no pyftplib install (§11.4.122). **Implemented** in hermetic_ftp_run.sh (EPSV/PASV both advertise 10.10.0.2; golden-bad FT_MUT=empty serves an empty listing → the promoted test SKIPS, proving a real PASS needs a real non-empty listing).

Gotcha found in review: the LIST output is CRLF-terminated; the promoted test's awk 'NF{print \$NF}' leaves a trailing \r on the filename, and curl rejects a URL with an embedded \r (CVE-2014-8150 → CURLE_URL_MALFORMAT). The promoted test's fetch is best-effort and NOT part of its PASS gate, so this is harmless there — but the harness must prove the byte-transfer half itself: hermetic_ftp_run.sh RETRs the nonce file by its exact (self-constructed, CRLF-free) name and byte-compares to the known payload (§11.4.107(9)).

2. WebDAV origin + forward proxy in pure python stdlib

http.server.BaseHTTPRequestHandler dispatches by method name → define do_PROPFIND, do_OPTIONS, do_GET, do_PUT. RFC 4918 §9.1: PROPFIND with Depth: 0|1, response 207 Multi-Status, Content-

Type: application/xml, body rooted at DAV:multistatus with per-resource DAV:response → DAV:href + DAV:propstat(DAV:prop + DAV:status). Minimal valid body:

```
<?xml version="1.0" encoding="utf-8"?>
<D:multistatus xmlns:D="DAV:">
  <D:response>
    <D:href>/dav/file.txt</D:href>
    <D:propstat>
      <D:prop><D:displayname>file.txt</D:displayname>
        <D:getcontentlength>12</D:getcontentlength>
        <D:resourcetype/></D:prop>
      <D:status>HTTP/1.1 200 OK</D:status>
    </D:propstat>
  </D:response>
</D:multistatus>
```

Forward proxy (RFC 7230 §5.3.2): a proxy **MUST** accept **absolute-form** request targets; `curl -x http://proxy http://upstream/path` sends `PROPFIND http://upstream/path HTTP/1.1` to the proxy, which parses the absolute-URI, connects upstream, and **re-emits origin-form** (`PROPFIND /path HTTP/1.1` + a fresh `Host:` from the request-target, §5.3.1). Both origin and a ~40-line stdlib forward proxy are feasible. The promoted WebDAV leg (`ftp_sftp_webdav.sh`) routes through `HELIX_SQUID_PROXY` and expects 207 (non-207 ⇒ FAIL, fail-closed §11.4.68) — so the hermetic promotion needs BOTH a 207-returning origin at 10.10.0.2 and a client-side forward proxy the `curl -x` routes through. Golden-bad `WEBDAV_MUT=plain200` (origin returns 200) **MUST** trip the test's fail-closed non-207 branch.

3. Kernel-WireGuard in an unprivileged user namespace — caveats

Works because `CLONE_NEWUSER + CLONE_NEWNET` grants `CAP_NET_ADMIN` **inside** the new userns, so `ip link add wg0 type wireguard + wg set` succeed with the host wireguard module loaded — no wireguard-go, no host root. `ip netns add` still needs root (persists under `/run/netns/`); `unshare -Ur` is the rootless path but namespaces are process-lifetime, non-persistent, invisible to `ip netns` (our harness relies on this).

The real risk is portability, not a WG-specific CVE.

Independent research (Edera, kernel 6.18): creating virtual net devices auto-loads 15+ kernel modules unprivileged; 40+ kernel CVEs (2020–2025) had userns as a prerequisite; userns raised reachable sensitive kernel operations 8/40 → 27/40 (~262%).

Hardening: `kernel.unprivileged_userns_clone=0` AND `user.max_user_namespaces=0`. **Ubuntu 23.10+ restricts unprivileged userns via AppArmor**

(kernel.apparmor_restrict_unprivileged_userns=1): an unconfined process CANNOT create a usersns without a profile carrying usersns, — so a tool invoking unshare -Urn from an arbitrary path simply fails on such hosts. **Actionable:** keep the honest-SKIP taxonomy first-class — probe + SKIP-with-reason separately on (a) /sys/module/wireguard absent, (b) unshare -Urn true denied, (c) ip link add type wireguard failing — so a hardened CI host SKIPS honestly, never false-greens. Our harnesses already SKIP on (a) and (b); (c) is covered by the inner || fail.

4. OSS / tools for rootless hermetic network testing (§11.4.74)

Tool	What	Root/ install	Relevance
unshare -Urn + kernel WG (current)	rootless usersns + in- kernel WG	none; needs host WG module + usersns permitted	simplest, real encryption; fragile on usersns- hardened hosts
slirp4netns	user-mode TCP/IP stack for a netns	none; small binary	netns egress w/o veth/ CAP_NET_ADMIN; NAT overhead
pasta / passt	newer user- mode net; Podman rootless default	none; small binary	faster than slirp4netns (no NAT); best rootless egress
wireguard-go	compliant userspace WG (Go, TUN)	Go binary; / dev/net/ tun	kernel-module fallback when WG module absent
boringtun	Cloudflare userspace WG (Rust)	binary; drop-priv caveat	same fallback, faster; Rust binary dep
wireguard4netns (CMU)	patched wireguard- go for unprivileged netns	none	closest art to "hermetic WG w/o kernel module"; reuse per §11.4.74
gVisor netstack	userspace TCP/IP as a Go lib	Go build	fully in-process encrypted stack (no TUN/netns/ module); future direction

Tool	What	Root/ install	Relevance
rootless podman + vasic-digital/ containers	container fixtures	rootless podman; §11.4.76	for SMB/NFS/TLS- mail: boot a real server container in netns B rather than hand-roll

Per-protocol promotion verdict (autonomous, no host install): FTP, WebDAV, Cast/DIAL eureka, plaintext SMTP/IMAP/POP3, HTTP-family → pure-stdlib peer feasible now. Implicit-TLS mail (465/993/995) → stdlib ssl + a self-signed cert generated at test time (bounded dep for cert-gen). mDNS/DNS-SD → pure-python multicast responder feasible (socket + IP_ADD_MEMBERSHIP on 224.0.0.251:5353) — but bind the overlay addr, not localhost (python-zeroconf caveat), and note real cross-subnet mDNS still needs a reflector in production. **SMB, NFS → no faithful pure-stdlib server; use a container-backed peer via vasic-digital/containers (§11.4.76) or stay operator-gated. Do NOT hand-roll SMB/NFS.**

5. Anti-bluff verification patterns (the oracle problem)

Determining "did the round-trip really happen over the encrypted tunnel vs leak over the underlay" is a test-oracle problem; **metamorphic testing** (checking relations between related runs) is the standard escape when there is no golden output. Our stack maps to it:

1. **Byte/sha256 payload verification** (own-content golden source) — strongest oracle when we control the payload.
2. **Wrong-key negative control** (WG_MUT=badkey) — a metamorphic relation with negation (corrupt key → PASS transitions to hard-FAIL); doubles as §11.4.107(10) self-validated golden-bad. Replicate per protocol.
3. **Reachability-as-proof** — allowed-ips 10.10.0.2/32 means a successful L4 connection is itself tunnel-traversal evidence. Strengthen with a wrong-destination negative control (same fetch to underlay 10.9.0.2 / wg0-down MUST fail).
4. **Transport-counter cross-check** (wg show handshake + rx/tx) — an oracle in a different domain than the payload check (§11.4.107(2) multi-oracle).
5. **Underlay-sniff differential** (optional, strongest) — capture on the underlay veth (AF_PACKET/tcpdump) and assert the plaintext nonce never appears in cleartext on the underlay while ciphertext flows. Gate behind an honest SKIP where unavailable.

Precedent (§11.4.8): mature literature exists for metamorphic testing / the oracle problem generally (Wikipedia; arXiv 1912.05278 security-flavoured MT), but **no external precedent covers the exact composite** — "prove a plaintext payload round-tripped over a rootless kernel-WireGuard netns tunnel and did not leak on the underlay, via self-fetched nonce + wg-transport-counter + wrong-key golden-bad." That specific composite is **original work**, well-grounded in the general MT/oracle literature.

Three most actionable findings for the next iterations

1. **Promote FTP + WebDAV first with pure-stdlib peers bound to 10.10.0.2 — the 227-reply IP (or EPSV) is the load-bearing correctness rule.** FTP done (hermetic_ftp_run.sh); WebDAV needs a 207-returning do_PROPFIND origin + a client-side forward proxy the curl -x routes through.
2. **Make the users/kernel-WG environment dependency an explicit greppable SKIP taxonomy** — Ubuntu 23.10+/hardened kernels deny unshare -Urn; separate SKIP reasons prevent a hardened host from false-greening. Note wireguard-go/boringtun/wireguard4netns/ gVisor-netstack as the no-kernel-module fallback (build cost accepted only then).
3. **Replicate the WG_MUT=badkey golden-bad per protocol + add a wrong-destination (underlay) negative control**, and an optional AF_PACKET underlay-sniff differential as the rock-solid non-leak proof (§11.4.123).

Sources verified

All URLs accessed **2026-07-02**.

- RFC 959 (FTP — PASV/227, TYPE, RETR/LIST): <https://www.rfc-editor.org/rfc/rfc959>
- RFC 2428 (FTP EPSV/EPRT): <https://www.rfc-editor.org/rfc/rfc2428>
- D. J. Bernstein, "The PASV, RETR, REST, and PORT verbs": <https://cr.yp.to/ftp/retr.html>
- IBM support — internal IP in 227 reply: <https://www.ibm.com/support/pages/remote-ftp-client-doing-passive-mode-gets-internal-ip-address-returned-227-entering-passive-mode-message>
- oneuptime — FTP passive mode troubleshooting: <https://oneuptime.com/blog/post/2026-03-20-ftp-passive-mode-troubleshoot-ipv4/view>
- Cerberus FTP support — passive data connection failures: <https://support.cerberusftp.com/hc/en-us/articles/202639399>

- Check Point sk169993 — 227 header IP vs command IP mismatch: <https://support.checkpoint.com/results/sk/sk169993>
- everything.curl.dev — FTP directory listing (CRLF): <https://everything.curl.dev/ftp/dirlist.html>
- curl(1) man page: <https://curl.se/docs/manpage.html>
- libcurl error codes (CURLE_URL_MALFORMAT): <https://curl.se/libcurl/c/libcurl-errors.html>
- Debian LTS — CVE-2014-8150 URL sanitization: <https://lists.debian.org/debian-lts/2015/01/msg00012.html>
- MicroPython FTPdLite — minimalist RFC-959 asyncio FTP server: <https://github.com/orgs/micropython/discussions/13016>
- Python stdlib http.server docs: <https://docs.python.org/3/library/http.server.html>
- PEP 268 — Extended HTTP functionality and WebDAV: <https://peps.python.org/pep-0268/>
- RFC 4918 (WebDAV — PROPFIND, 207 Multi-Status): <https://www.rfc-editor.org/rfc/rfc4918>
- sourceperl gist — WebDAV PROPFIND in python: <https://gist.github.com/sourceperl/8d50995a5265f84fa5ea1dd4adf7522f>
- RFC 7230 (§5.3.1 origin-form, §5.3.2 absolute-form/proxy): <https://www.rfc-editor.org/rfc/rfc7230.html>
- curl issue #6769 — proxy request absolute-form vs RFC 7230: <https://github.com/curl/curl/issues/6769>
- Edera — "User namespaces are not a security boundary": <https://edera.dev/stories/user-namespaces-are-not-a-security-boundary>
- Ubuntu — "Ubuntu 23.10 restricted unprivileged user namespaces": <https://ubuntu.com/blog/ubuntu-23-10-restricted-unprivileged-user-namespaces>
- Ubuntu bug 2046477 — enable userns restrictions by default: <https://bugs.launchpad.net/ubuntu/+source/apparmor/+bug/2046477>
- systemshardening.com — Restricting Unprivileged User Namespaces: <https://www.systemshardening.com/articles/linux/linux-unprivileged-namespace-restriction/>
- Kicksecure — User Namespace hardening: https://www.kicksecure.com/wiki/User_Namespace
- Red Hat — "Use a net namespace for VPNs": <https://www.redhat.com/en/blog/use-net-namespace-vpn>
- blog.0x1b.me — Unprivileged Linux Network Namespaces Pt 1: <https://blog.0x1b.me/posts/unprivileged-linux-netns-pt1/>
- benjamintoll — On Unsharing Namespaces Pt 2: <https://benjamintoll.com/2022/12/14/on-unsharing-namespaces-part-two/>
- Podman docs — podman-unshare: <https://docs.podman.io/en/latest/markdown/podman-unshare.1.html>
- slirp4netns: <https://github.com/rootless-containers/slirp4netns>
- passt/pasta: <https://passt.top/passt/about/>
- sanj.dev — Podman pasta vs slirp4netns: <https://sanj.dev/post/podman-pasta-vs-slirp4netns-networking/>

- Cloudflare — BoringTun userspace WireGuard: <https://blog.cloudflare.com/boringtun-userspace-wireguard-rust/>
- cloudflare/boringtun: <https://github.com/cloudflare/boringtun>
- cmusatyalab/wireguard4netns: <https://github.com/cmusatyalab/wireguard4netns>
- gVisor pkg/tcpip/stack GoDoc: <https://pkg.go.dev/gvisor.dev/gvisor/pkg/tcpip/stack>
- ryan-schachte — userspace WireGuard with netstack: https://ryan-schachte.com/blog/userspace_wireguard_tunnels/
- python-zeroconf (pure-python mDNS): <https://github.com/python-zeroconf/python-zeroconf>
- Wikipedia — Metamorphic testing: https://en.wikipedia.org/wiki/Metamorphic_testing
- emergentmind — Metamorphic Relations: <https://www.emergentmind.com/topics/metamorphic-relations-mrs>
- arXiv 1912.05278 — Metamorphic Security Testing for Web Systems: <https://arxiv.org/pdf/1912.05278>