

tests/regression/ no_suspend_export_sibling_test.sh — operator guide

Revision: 1 **Last modified:** 2026-07-01T06:30:00Z **Status:**
Active standing regression guard (§11.4.135) for BUGFIX-0011.

Companion (§11.4.18) to the in-source documentation block at the top of the script. Sibling of docs/scripts/comprehensive_admin_topology_test.md.

Overview

A standing regression guard that proves the CONST-033 static scanner scripts/host-power-management/check-no-suspend-calls.sh excludes a **documentation ledger's §11.4.65 export siblings** (.html / .pdf), not only its .md source.

Pre-fix, EXCLUDE_PATHS carried the bugfix ledger with an explicit .md extension (/docs/issues/fixed/BUGFIXES.md). The ledger legitimately quotes the banned host-power patterns when **documenting** a CONST-033 fix (e.g. a §1.1 mutation example systemctl suspend). When BUGFIXES.md was exported to BUGFIXES.html per §11.4.65, that literal landed in a sibling the .md-anchored exclusion did **not** cover — so the scanner tripped on its own fix documentation (BUGFIXES.html:1210): a §11.4.1 **false-FAIL**. The same sibling-blindness class as the HOST_POWER_MANAGEMENT. entry fixed one commit earlier (BUGFIX-0010).

The fix makes the exclusion **extension-agnostic** — the prefix / docs/issues/fixed/BUGFIXES. covers .md + .html + .pdf — while a **non-ledger** .html and any **real script invocation** still trip the scanner (the gate is not neutered, §11.4.120).

It does **not** grep the source. It builds a throwaway fixture tree and drives the **real** scanner, so it is deterministic and independent of the live ledger's current content.

Prerequisites

- POSIX sh, sed, mktemp, grep, awk. No network, no privileges.

Usage examples

```
# GREEN guard (default) – assert the real scanner excludes a
    ledger .html sibling
# AND still catches a real script invocation:
tests/regression/no_suspend_export_sibling_test.sh #
    exit 0 = PASS

# RED reproduce – the ".md"-only replica trips on the ledger .html
    sibling:
RED_MODE=1 tests/regression/no_suspend_export_sibling_test.sh #
    exit 0 = defect reproduced

# Runs automatically inside the suite:
bash tests/run-tests.sh #
    test_regression_guards()
```

§11.4.115 RED_MODE polarity

RED_MODE	What it runs	PASS means
0 (default)	the REAL check-no-suspend-calls.sh against a fixture ROOT holding a ledger docs/issues/fixed/BUGFIXES.html (quotes the banned literal) and a real scripts/real_invocation.sh	the ledger .html is not in the violation list (excluded) and the real script is (still caught) → the sibling exclusion is present and the gate is not neutered (GREEN guard)
1	a PRE-FIX replica (EXCLUDE_PATHS reverted to .md-only via sed) against a ledger-.html-only ROOT	the replica FAILs on BUGFIXES.html → the sibling-blind false-FAIL reproduces

A RED_MODE=1 run that cannot reproduce is a finding per §11.4.7, not a pass.

Edge cases

- **Fix reverted** (exclusion flipped back to /docs/issues/fixed/BUGFIXES.md) → the GREEN guard reports REGRESSION: ledger_flagged=yes ... and exits 1. This is the §1.1 paired-mutation behaviour, verified against the real scanner.

- **Non-ledger** `.html` containing the literal `→` still trips (the exclusion is BUGFIXES-specific, not "all `.html`").
- **cleanup trap** forces `return 0` so a conditional last command never leaks a non-zero status into the script exit under `set -e` (§11.4.1).

Internal behaviour

- `#!/bin/sh, set -eu; POSIX-only, sh -n parse-clean` (§11.4.67).
- Fixture `ROOT` under `mktemp -d`, removed on every exit path (§11.4.14).
- Writes one evidence file per run under `qa-results/regression/no_suspend_export_sibling/` (gitignored).

Related

- Fix site: `scripts/host-power-management/check-no-suspend-calls.sh` (`EXCLUDE_PATHS — /docs/issues/fixed/BUGFIXES.`).
- Standing challenge: `challenges/scripts/no_suspend_calls_challenge.sh`.
- Sibling guard: `docs/scripts/comprehensive_admin_topology_test.md`.
- `tests/run-tests.sh — registers this guard via test_regression_guards().`
- `docs/issues/fixed/BUGFIXES.md — BUGFIX-0011.`

Last verified

2026-07-01 — `sh -n parse-clean`; GREEN excludes the ledger `.html` sibling + catches the real script (exit 0); `RED_MODE=1` reproduces (exit 0); paired mutation (revert exclusion) makes GREEN FAIL (exit 1) then restores byte-identical; registered in `run-tests.sh`.