

BUGFIXES

Root-cause-analysed bug fixes for this project, per the Universal Mandatory Constraints (CLAUDE.md mandate #10). Each entry records the defect, root cause, affected files, the fix, and a link to the reproduction/verification evidence.

BUGFIX-0001 — run-tests.sh aborts after the first test under set -e

- **Type:** Bug (script-internal failure — Helix Constitution §11.4.1)
- **Status:** Fixed
- **Date:** 2026-06-30
- **Affected file:** tests/run-tests.sh (test_result())

Symptom

bash tests/run-tests.sh printed only its banner and the first test's section header, then exited 1 (7 lines of output total) — every test after the first was silently never run, and no TEST SUMMARY was printed.

Reproduction (captured, run in-session before the fix)

```
$ bash -c 'set -euo pipefail; x=0; ((x++)); echo "SURVIVED,
x=$x"; echo "exit=$?"
exit=1                                # "SURVIVED" never printed
```

```
$ bash tests/run-tests.sh 2>&1 | wc -l
7                                     # aborted; exit=1
```

Root cause (FACT — not a guess, Helix Constitution §11.4.6)

test_result() counted with the bash post-increment idiom ((TESTS_RUN++)). The arithmetic command ((expr)) returns exit status **1** when expr evaluates to **0**. TESTS_RUN++ is a *post*-increment, so its value is the value *before* incrementing — 0 on the very first call — making ((TESTS_RUN++)) return status 1. The script runs

under `set -euo pipefail` (line 7), so that non-zero status aborted the entire suite at the first `test_result` call, before any results or the summary could print. The same trap applied to the first PASS (`(( TESTS_PASSED++ ))`) and first FAIL (`(( TESTS_FAILED++ ))`).

This was a **pre-existing** latent defect (the `(( ... ++ ))` idiom was original); it surfaced while wiring the constitution-inheritance pre-flight gate in as the first test.

Fix (at source, Helix Constitution §11.4.1)

Replaced the three post-increment arithmetic commands with the assignment form, which always returns status 0 and is immune to the `set -e` trap:

```
- ((TESTS_RUN++))
+ TESTS_RUN=$((TESTS_RUN + 1))
- ((TESTS_PASSED++))
+ TESTS_PASSED=$((TESTS_PASSED + 1))
- ((TESTS_FAILED++))
+ TESTS_FAILED=$((TESTS_FAILED + 1))
```

Verification (captured, run in-session after the fix)

```
$ bash -c 'set -euo pipefail; x=0; x=$((x+1)); echo "SURVIVED,
x=$x"; echo "exit=$?"
SURVIVED, x=1
exit=0
```

```
$ bash tests/run-tests.sh 2>&1 | wc -l
28                                # suite now runs to completion (was 7)
# first line of results:
✓ PASS: Constitution inheritance gate (§11.4.35)
```

The suite now executes every test and prints its summary. (Its overall exit remains non-zero in an environment without the running proxy services — those are real-infrastructure tests that correctly FAIL/skip when the live System is absent, Helix Constitution §11.4.11 — that is a separate, pre-existing, infrastructure-dependent condition, not this defect.)

Cross-reference (§11.4.138): the “proxy services not running” condition noted above was treated as merely environmental. It was not — BUGFIX-0002 below is the *reason* the proxy would not stay up under rootless Podman. Driving the real data path (not just “tests pass”) surfaced it.

BUGFIX-0002 — squid crash-loops under rootless Podman (log dir not writable) → proxy never serves

- **Type:** Bug (product defect — end-user-visible: the proxy does not work)
- **Status:** Fixed
- **Date:** 2026-07-01
- **Affected files:** lib/container-runtime.sh (create_directories()), start(init_cache())
- **Regression guard:** tests/regression/log_dir_writable_test.sh (§11.4.135, §11.4.115 RED_MODE polarity)
- **Workable item:** #38 (the live-usability proof stream)

Symptom

A freshly-booted proxy (./start --no-vpn, rootless Podman) returned http_code=000 for every request through it. proxy-squid was not (healthy) — it was restarting in a loop, never accepting a connection, so **no feature of the proxy worked for the end user** — the exact “tests pass but the feature can’t be used” failure mode §11.4 forbids.

Reproduction (captured, run in-session before the fix — §11.4.115 RED)

```
# Live boot of the real orchestrator, then curl through the proxy:
$ curl -s -o /dev/null -w '%{http_code}' -x http://127.0.0.1:53128 http://example.com/
000
```

```
# squid's own log (read from inside the container) showed the FATAL:
$ podman logs proxy-squid | tail
FATAL: Cannot open '/var/log/squid/access.log' for writing.
       The parent directory must be writeable by the user 'proxy',
       which is the cache_effective_user set in squid.conf.
```

```
# Unit reproduction of the orchestrator code path (pre-fix replica):
$ RED_MODE=1 tests/regression/log_dir_writable_test.sh
[PASS] BUGFIX#38 log-dir-writable (RED_MODE=1): RED reproduced:
       pre-fix LOG_DIR mode=755 is NOT world-writable
```

Root cause (FACT — not a guess, §11.4.6)

Under **rootless** Podman the invoking host uid (1000) maps to the container's root, but every other container uid is remapped through /etc/subuid into a high host range. squid.conf sets cache_effective_user proxy, so squid drops privileges to its non-root proxy user — which, on the host, is a high subuid that owns **none** of the host-created bind-mount dirs. The host ./logs directory was created mode 0755 (owner-write only), so the container proxy user had only world r-x — no write — and squid FATAled opening access.log, then crash-looped. The orchestrator already chmod 777-ed the **cache** bind-mount (init_cache) for this exact reason, but the **log** bind-mount was missed — a single missing site of an already-known remedy.

Fix (at source, §11.4.1 / §11.4.108 SOURCE layer)

Make the squid log bind-mount world-writable in the orchestrator's dir-init, mirroring the existing cache chmod 777. Applied at **both** self-sufficient sites so it holds regardless of call order:

```
# lib/container-runtime.sh  create_directories()
    mkdir -p "$LOG_DIR"
+  chmod 777 "$LOG_DIR"

# start  init_cache()
+  mkdir -p "$LOG_DIR"
+  chmod 777 "$LOG_DIR"
```

Verification (captured, run in-session after the fix)

Unit — regression guard, §11.4.115 polarity (RED reproduces, GREEN proves):

```
$ RED_MODE=1 tests/regression/log_dir_writable_test.sh  # pre-fix
replica
[PASS] RED reproduced: LOG_DIR mode=755 NOT world-writable
$ tests/regression/log_dir_writable_test.sh              # real
fixed code
[PASS] GREEN: create_directories() made LOG_DIR mode=777 world-
writable
```

§1.1 paired mutation (guard is not a tautology): stripping the chmod 777 "\$LOG_DIR" from create_directories() made the GREEN guard **FAIL** (REGRESSION: ... mode=755 NOT world-writable, exit 1); the lib was restored byte-identical (md5 0128a96b6d467c2da5b7cef8a808e563 before == after) and the guard PASSED again.

Live data-plane (§11.4.108 RUNTIME + USER-VISIBLE):

after the fix the booted proxy serves real HTTP through it:

```
$ curl -x http://127.0.0.1:53128 http://example.com/ ->  
http_code=200  
Via: 1.1 proxy-squid (squid/6.13)  
# squid access.log (the file that FATAL'd pre-fix) – real request  
logged:  
1782858066.886 189 10.89.1.249 TCP_MISS/200 951 GET http://  
example.com/ - HIER_DIRECT/104.20.23.154 text/html  
$ podman ps -> proxy-squid Up (healthy)
```

Evidence: [qa-results/regression/bugfix38/](#).