

tests/dynamic/parse_check.sh — operator guide

Revision: 1 **Last modified:** 2026-07-01T00:00:00Z **Status:** Active §11.4.67 target-shell parseability gate for the dynamic test tree (P9 harness). Wire into the project pre_build sweep in P10.

Companion (§11.4.18) to the in-source documentation block at the top of the script.

Overview

A re-runnable §11.4.67 pre-build gate that asserts **every** shell script under tests/dynamic/ parses cleanly under **both** sh -n and bash -n — i.e. no bash-only construct leaks outside an eval. Android mksh and other POSIX shells parse a whole script before executing it, so a bash-only construct that a runtime guard “protects” still aborts at parse time; this gate catches that class at source time.

Prerequisites

- bash (the runner shebang) plus sh and bash both on PATH (it runs each script through both parsers).
- find, sort, tee, grep, date.
- Write access to qa-results/ (gitignored) for the run log.

Usage examples

```
# Run the gate over the whole dynamic tree:
bash tests/dynamic/parse_check.sh          # exit 0 = all
scripts parse-clean
```

```
# Inspect the per-run log it tees:
cat qa-results/p9-harness/<run-id>/parse_check.log
```

Edge cases

- **A bash-only construct outside eval** (e.g. `>( )`, `<<<`, `[[ ]]`, arrays, `${v^^}`) → the offending script reports FAIL with the captured `sh -n / bash -n` diagnostic, and the gate exits 1. Fix at **source** per §11.4.67, never patch the call site.
- **Empty tree / no *.sh found** → `scripts=0`, RESULT line still printed, exit 0 (nothing to fail).
- **New script added under tests/dynamic/** → automatically enumerated next run (depth-N find), no list to maintain.

Internal behaviour

- `#!/usr/bin/env bash`; resolves its own dir + the repo root, stamps a UTC `RUN_ID`, and tees the full report to `qa-results/p9-harness/<run-id>/parse_check.log`.
- Enumerates `find "$DIR" -type f -name '*.sh' | sort`, then for each runs `sh -n` and `bash -n`, capturing both diagnostics.
- A script is OK only when **both** parsers return 0; otherwise FAIL with the captured errors.
- Final exit: `grep -q '^FAIL ' "$OUT" → exit 1`, else exit 0.

Related

- Every `*.sh` under `tests/dynamic/` (lib, analyzers, suites) — the gate's scope.
- `tests/dynamic/analyzers/run_analyzer_selftests.sh` — the sibling self-validation gate (analyzer correctness vs. this gate's parseability).
- Constitution §11.4.67 (target-shell parseability); design spec §13.

Last verified

2026-07-01 — run over the dynamic tree: all scripts parse under `sh -n` AND `bash -n`; the gate itself is `sh -n + bash -n` parse-clean.