

tests/dynamic/suites/ run_all_suites.sh — operator guide

Revision: 1 **Last modified:** 2026-07-01T00:00:00Z **Status:**
Active orchestrator for the six §11.4.169 dynamic data-plane
suites. Honest-SKIPs (topology_unsupported) until the live dynamic
stack lands (P10, §11.4.69) — never a fake PASS.

Companion (§11.4.18) to the in-source documentation block
at the top of the script.

Overview

Runs every §11.4.169 dynamic data-plane suite (stress, chaos, concurrency/race, ddos/flood, memory soak, benchmark) and aggregates PASS / FAIL / SKIP. The suites drive the live dynamic stack; when it is absent (today — design-only) every suite emits an honest §11.4.69 SKIP-with-reason and this orchestrator records it as SKIP. Exit 0 iff there is **no FAIL** (all PASS or honest SKIP).

Prerequisites

- bash/sh, grep, tee, date.
- The six suite scripts present under tests/dynamic/suites/.
- For real (non-SKIP) runs in P10: HELIX_DYNAMIC_STACK=1 + HELIX_PROXY_URL pointing at the live dynamic proxy, plus the per-suite injection/hook env vars each suite documents.
- Write access to qa-results/ (gitignored) for the aggregate log.

Usage examples

```
# Today (no live stack): every suite honest-SKIPs, orchestrator  
exits 0:
```

```
bash tests/dynamic/suites/run_all_suites.sh
```

```
# P10 live run (GREEN guards):
```

```
HELIX_DYNAMIC_STACK=1 HELIX_PROXY_URL=http://127.0.0.1:34128 \  
bash tests/dynamic/suites/run_all_suites.sh
```

```
# P10 RED-baseline polarity (reproduce defects on the pre-fix
stack):
HELIX_DYNAMIC_STACK=1 HELIX_PROXY_URL=... RED_MODE=1 \
  bash tests/dynamic/suites/run_all_suites.sh
```

Edge cases

- **Live stack absent** → all six suites SKIP; aggregate RESULT notes all N suites honest-SKIPped (live dynamic stack absent; run in P10); exit 0.
- **A suite script missing** → counted as FAIL.
- **A suite emits no PASS/FAIL/SKIP verdict line** → treated as FAIL (no PASS/FAIL/SKIP verdict emitted) — an unclassifiable suite is never a pass.
- **Any FAIL** → aggregate exit 1 (investigate per §11.4.102).

Internal behaviour

- `#!/usr/bin/env bash`, POSIX-clean (`sh -n + bash -n`, §11.4.67).
- Iterates the fixed suite list, runs each via `sh "$script"`, and classifies by the **last** PASS:/FAIL:/SKIP: verdict line the suite emitted.
- Tees the full report to `qa-results/p9-harness/<run-id>/suite_results.txt`.
- Final exit: `grep -q '^FAIL:'` → exit 1, else exit 0.

Related

- The six suites it orchestrates: `stress_suite.sh`, `chaos_suite.sh`, `concurrency_race_suite.sh`, `ddos_flood_suite.sh`, `memory_soak_suite.sh`, `benchmark_suite.sh`.
- `tests/dynamic/lib/analyzer_common.sh` — the base each suite sources.
- Constitution §11.4.69 / §11.4.85 / §11.4.169 / §11.4.115; design spec §13.

Last verified

2026-07-01 — run with no live stack: all six suites honest-SKIP (`topology_unsupported`), aggregate exit 0; `sh -n + bash -n` parse-clean. Live PASS/FAIL classification is exercised in **P10**.