

FINDING

FB2 BUG-FB2-HARDCODED-LANG — live re-validation on nezha (§11.4.108 runtime signature)

Run: 2026-06-16T16:38:12Z · **Image:** 2bb4de5df2c7 (helixtranslate-api, confirmed via podman inspect) **Endpoint:** POST https://nezha.local:18443/api/v1/translate/fb2 (cmd/server, pkg/api Handler.translateFB2) **Fix under test:** commit c2aa7c8 — handler parses+validates source_lang/target_lang, threads resolved codes (legacy ru→sr kept ONLY when both omitted), unknown → 400. **Fixture:** test/fixtures/ebooks/sample.fb2 (English <lang>en</lang> source).

Result: PASS (3 probes, real captured evidence — §11.4.123)

Probe	Request	Expected	Observed	Verdict
A (positive)	target_lang=es	Spanish output, NOT Serbian	EPUB w/ "Capítulo de Prueba" · "Este es un documento de prueba FB2 para la validación de la traducción." · "Sección 1.1"	PASS
C (cross-check)	target_lang=de	German, distinct from A	EPUB w/ "Testkapitel" · "Dies ist ein Test-FB2-Dokument zur Prüfung der Übersetzung." · "Abschnitt 1.1"	PASS
B (negative)	target_lang=klingon	HTTP 400, no translation	{"error":"unknown target_lang:klingon"} HTTP 400	PASS

Why this proves the fix (§11.4.6 no-guessing)

- Source is **English**. Pre-fix, the handler hardcoded ru→sr and ignored `target_lang`, so EVERY FB2 request produced **Serbian**. Probe A produced **Spanish**, Probe C produced **German** (distinct outputs) — only possible if `target_lang` is honored.
- Probe B's 400 with the exact unknown `target_lang: klingon` message proves the validate-BEFORE-translate path is live on the deployed image (pre-fix would silently fall back).
- Output is a real `application/epub+zip` artifact (EPUB document, ffile-verified), with translated chapter prose — not a `session_id/status` (§11.4 anti-bluff).

Artifacts

- `probe_a_es_output.epub + epub_extracted/OEBPS/chapter1.xhtml` (Spanish)
- `probe_c_de_output.epub + epub_de_extracted/OEBPS/chapter1.xhtml` (German)
- `probe_b_klingon_400.txt` (400 response)
- `probe_a_es_meta.txt / probe_c_de_meta.txt` (HTTP status + content-type + size)
- `run_meta.txt` (run context)