

# commit\_all.sh — companion guide

Revision: 1 Last modified: 2026-06-13T00:00:00Z

## Overview

scripts/commit\_all.sh is the project's **single authorised commit + push entry point** for the main repo, mandated by Constitution §11.4.22 (document-sync / official commit wrapper) and the “MANDATORY COMMIT & PUSH CONSTRAINTS” section of CLAUDE.md (“NEVER use git add, git commit, or git push directly”).

It mechanically encodes the git discipline the inherited Helix Constitution requires, so the conductor never enforces it by hand. Companion to §11.4.18 (script documentation) and validated by scripts/commit\_all\_selftest.sh (§11.4.27 / §11.4.85 anti-bluff).

## Prerequisites

- bash and git on PATH.
- A configured git identity (user.name, user.email).
- Remotes configured (this repo's remotes resolve to two distinct push URLs: git@github.com:milos85vasic/Translator.git and git@github.com:HelixDevelopment/HelixTranslate.git).
- flock is used when present; on macOS (no flock) an atomic mkdir lock is used instead.

## Usage examples

```
# Commit explicit paths and push synchronously (default) to every  
distinct push URL:
```

```
scripts/commit_all.sh -m "feat(fb2): preserve tail text in nested  
elements" \  
    pkg/fb2/parser.go pkg/ebook/fb2_parser.go
```

```
# Commit + detached background push (releases the commit lock  
immediately,
```

```
# orchestrator exit reports COMMIT success per §11.4.88):
```

```
scripts/commit_all.sh -m "docs: update architecture notes" --  
background docs/ARCHITECTURE.md
```

```
# Commit only, no push (staging-only / offline):
```

```
scripts/commit_all.sh -m "wip: local checkpoint" --no-push pkg/  
translator/llm/openai.go
```

## Flags

| Flag                                   | Meaning                                                                            |
|----------------------------------------|------------------------------------------------------------------------------------|
| <code>-m, --message &lt;msg&gt;</code> | Commit message ( <b>required</b> ).                                                |
| <code>--sync-push</code>               | Push synchronously, report push exit code ( <b>default</b> ).                      |
| <code>--background</code>              | Detached push ( <code>nohup &amp;+disown</code> ); exit reports the COMMIT result. |
| <code>--no-push</code>                 | Commit only; do not push.                                                          |
| <code>&lt;pathspec&gt;...</code>       | <b>Explicit</b> paths to stage. At least one required.                             |

## Exit codes

| Code | Meaning                                                                                             |
|------|-----------------------------------------------------------------------------------------------------|
| 0    | Commit succeeded (and, in <code>--sync-push</code> , push succeeded).                               |
| 2    | Usage error / forbidden flag / no <code>pathspec</code> / mutation residue / non-fast-forward STOP. |
| 3    | Nothing staged to commit (informational, mirrors §11.4.22).                                         |
| 1    | Unexpected git failure (commit failed, or a sync push partially failed).                            |

## Constitutional discipline encoded

| Rule                                                       | Mechanism in the script                                                                                                                                                                                                                                                                                                                  |
|------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| §11.4.113 absolute no-force-push                           | <code>reject_force_tokens</code> (run on the whole <code>argv</code> first) refuses <code>--force</code> , <code>--force-with-lease [=...]</code> , <code>-f</code> , and any leading- <code>+</code> refspec. The push step passes an explicit <code>&lt;branch&gt;:&lt;branch&gt;</code> refspec with <b>no</b> <code>--force</code> . |
| §2.1 multi-upstream push                                   | <code>collect_push_remotes</code> enumerates every remote's push URLs and <b>de-duplicates by URL</b> , so each physical repo is pushed exactly once (the 5 remote/URL entries collapse to the 2 distinct repos).                                                                                                                        |
| §11.4.71 / §11.4.113 fetch-before-push + fast-forward-only | <code>push_one</code> runs <code>git fetch &lt;remote&gt;</code> first; if the remote-tracking branch is <b>not</b> an ancestor of HEAD, it <b>STOPS</b> (exit 2) and tells the operator to integrate manually — it never auto-merges and never force-pushes.                                                                            |

| Rule                                          | Mechanism in the script                                                                                                                                                                      |
|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| §11.4.84 working-tree quiescence              | quiescence_check greps the staged scope for mutation markers (MUTATED for paired, // always pass, _mutated_, conflict markers) and ABORTs (exit 2) on any unaccounted hit.                   |
| §11.4.30 never git add -A; never helix_qa     | Requires $\geq 1$ explicit pathspec (refuses none); explicitly rejects -A / --all / . / :/; and refuses the helix_qa submodule path in any spelling.                                         |
| §11.4.88 background push + early lock release | The .git/.commit_all.lock is released the instant git commit returns 0 (before any push). --background detaches the push via nohup ... & ; disown, logging to .git/commit_all.push.<ts>.log. |
| §11.4.67 target-shell parseable               | #!/usr/bin/env bash, set -euo pipefail, passes both bash -n and sh -n.                                                                                                                       |

## Edge cases

- **Nothing to commit** → exit 3 (not an error); the lock is released, no push.
- **Non-fast-forward** on any remote → STOP (exit 2); the local commit is already durable. Integrate with git fetch + merge-onto-latest-<branch> and re-run.
- **Partial sync-push failure** → exit 1, but the SUMMARY notes the commit is durable locally.
- **Hooks** are never skipped — the wrapper never passes --no-verify.

## Internal behaviour

1. Guard argv for force tokens (§11.4.113) **before** option parsing.
2. Parse flags + pathspecs; enforce §11.4.30 (explicit-only, no helix\_qa).
3. Locate repo root (override via COMMIT\_ALL\_REPO\_ROOT), verify it is a git repo.
4. §11.4.84 quiescence scan of the staged scope.
5. Acquire the commit lock, stage the explicit pathspecs, create one commit.
6. Release the lock immediately (§11.4.88).
7. Sync or background push, fast-forward-only, to every distinct push URL (§2.1).

## Test / environment overrides

- COMMIT\_ALL\_REPO\_ROOT — point at a throwaway repo (used by the self-test).
- COMMIT\_ALL\_REMOTE — restrict pushes to one named remote (self-test uses a local bare remote so **no real remote is ever touched**).

## Related scripts

- `scripts/commit_all_selftest.sh` — hermetic anti-bluff test (builds a throwaway repo + local bare remote under `$TMPDIR`, asserts every guard fires; **no real push**).
- `scripts/no-silent-skips.sh`, `scripts/testing/meta_test_constitution_inheritance.sh` — sibling Definition-of-Done / constitution-inheritance enforcement scripts.

## Last verified

2026-06-13 — `bash -n + sh -n clean; self-test PASS=13 FAIL=0`.