

ARCHITECTURE_AND_DIAGRAMS


HelixCode Architecture & System Design

System Architecture Overview

Version: 1.0.0 **Date:** 2026-04-30 **Status:** Foundation verified, critical bluff areas identified

1. High-Level Architecture

Client Layer




Architecture Layers

Layer	Components	Status
Client Layer	CLI, TUI (tview), Desktop (Fyne), Web/Mobile	Structure exists, need verification
API Gateway	REST (Gin), WebSocket, MCP Protocol	Partially implemented
Core Services	Auth, LLM, Task, Worker, Workflow, Project	Auth VERIFIED REAL, LLM BLUFF AREA
Tools & Editor	Filesystem, Shell, Git, Browser, Editor	Need verification
Data Layer	PostgreSQL, Redis, Session Store	Schema advertised, need verification
Infrastructure	Docker, K8s, Monitoring, Health Checks	Docker exists, need verification
External	15+ LLM Providers (OpenAI, Anthropic, Ollama, etc.)	NOT connected (simulated)

2. Component Interaction Flow

2.1 LLM Generation Flow (TARGET - Current is Simulated)



v
User receives actual AI-generated text

Current State (BLUFF): The flow stops at `CLI.handleGenerate()` which returns a simulated response without ever calling `ProviderManager`.

Required Fix: Implement real provider dispatch with circuit breakers and fallback chains.

2.2 Task Distribution Flow (TARGET)

```
User -> API: POST /api/v1/tasks (project build)
|
v
TaskManager.Create(ctx, task)
|
v
TaskManager.Distribute(task)
|
+---> Worker Pool Selection:
      - Filter by capabilities (CPU, GPU, memory)
      - Health check (SSH probe)
      - Load balancing (least loaded)
      |
      +---> SSHWorkerPool.Dispatch(task, worker)
            |
            +---> SSH Connection
                  |
                  +---> Remote Execution
                        |
                        +---> Checkpoint every 300s
                              |
                              +---> Result Collection
                                    |
                                    v
                                TaskManager.Complete(task, result)
```

2.3 Authentication Flow (VERIFIED REAL)

```
User -> API: POST /api/v1/auth/register
|
v
AuthService.Register(username, email, password)
|
+---> validateRegistration() [input validation]
|
+---> hashPassword() [bcrypt with configured cost]
|
+---> db.CreateUser() [persist to PostgreSQL]
|
v
```

User created

User -> API: POST /api/v1/auth/login

```
|
v
AuthService.Login(username, password)
|
+---> db.GetUserByUsername() [fetch user + hash]
|
+---> verifyPassword() [bcrypt.CompareHashAndPassword]
|
|       +---> fallback: verifyArgon2Password()
|               [parse Argon2 params, decode salt, compute hash, c
|
+---> generateSessionToken() [crypto/rand, 32 bytes]
|
+---> db.CreateSession() [persist session]
|
v
Session returned with JWT token
```

User -> API: GET /api/v1/workers (with Bearer token)

```
|
v
AuthService.VerifyJWT(token)
|
+---> jwt.Parse() [validate signature, check expiry]
|
+---> VerifyJWTWithDB() [optional: fetch complete user, check IsActive]
|
v
Request authorized
```

Verified Quality: This flow uses real cryptography (bcrypt/argon2), real database operations, proper input validation, and secure token generation. This is the quality standard all other subsystems must match.

3. Database Schema (Advertised - Verification Required)

Core Tables

-- users: User accounts and authentication

```
CREATE TABLE users (
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  username VARCHAR(255) UNIQUE NOT NULL,
  email VARCHAR(255) UNIQUE NOT NULL,
  password_hash VARCHAR(255) NOT NULL,
```

```
display_name VARCHAR(255),
is_active BOOLEAN DEFAULT true,
is_verified BOOLEAN DEFAULT false,
mfa_enabled BOOLEAN DEFAULT false,
last_login TIMESTAMP,
created_at TIMESTAMP DEFAULT NOW(),
updated_at TIMESTAMP DEFAULT NOW()
);
```

-- sessions: Active user sessions

```
CREATE TABLE sessions (
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  user_id UUID REFERENCES users(id) ON DELETE CASCADE,
  session_token VARCHAR(255) UNIQUE NOT NULL,
  client_type VARCHAR(50),
  ip_address INET,
  user_agent TEXT,
  expires_at TIMESTAMP NOT NULL,
  created_at TIMESTAMP DEFAULT NOW()
);
```

-- workers: Distributed worker nodes

```
CREATE TABLE workers (
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  hostname VARCHAR(255) NOT NULL,
  display_name VARCHAR(255),
  ssh_host VARCHAR(255),
  ssh_port INTEGER DEFAULT 22,
  ssh_username VARCHAR(255),
  ssh_key_path VARCHAR(255),
  status VARCHAR(50) DEFAULT 'inactive',
  cpu_count INTEGER,
  memory_bytes BIGINT,
  gpu_count INTEGER,
  gpu_model VARCHAR(255),
  last_heartbeat TIMESTAMP,
  created_at TIMESTAMP DEFAULT NOW()
);
```

-- tasks: Task management with checkpoints

```
CREATE TABLE tasks (
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  project_id UUID,
  title VARCHAR(255) NOT NULL,
  description TEXT,
  status VARCHAR(50) DEFAULT 'pending',
  priority INTEGER DEFAULT 0,
  worker_id UUID REFERENCES workers(id),
```

```

dependencies UUID[],
checkpoint_data JSONB,
result_data JSONB,
retry_count INTEGER DEFAULT 0,
max_retries INTEGER DEFAULT 3,
started_at TIMESTAMP,
completed_at TIMESTAMP,
created_at TIMESTAMP DEFAULT NOW()
);

-- projects: Project lifecycle
CREATE TABLE projects (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    name VARCHAR(255) NOT NULL,
    description TEXT,
    status VARCHAR(50) DEFAULT 'planning',
    owner_id UUID REFERENCES users(id),
    config JSONB,
    created_at TIMESTAMP DEFAULT NOW(),
    updated_at TIMESTAMP DEFAULT NOW()
);

-- llm_providers: Provider configurations
CREATE TABLE llm_providers (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    name VARCHAR(255) NOT NULL,
    provider_type VARCHAR(50) NOT NULL,
    config JSONB,
    is_enabled BOOLEAN DEFAULT true,
    priority INTEGER DEFAULT 0,
    last_health_check TIMESTAMP,
    created_at TIMESTAMP DEFAULT NOW()
);

-- notifications: Notification history
CREATE TABLE notifications (
    id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    title VARCHAR(255),
    message TEXT,
    type VARCHAR(50),
    priority VARCHAR(50),
    channels VARCHAR(50)[],
    status VARCHAR(50) DEFAULT 'pending',
    sent_at TIMESTAMP,
    created_at TIMESTAMP DEFAULT NOW()
);

```

Verification Required: These tables must exist in migration files and be verified by component tests.

4. API Specification

4.1 Authentication Endpoints

Method	Endpoint	Description	Auth Required
POST	/api/v1/auth/register	User registration	No
POST	/api/v1/auth/login	User login	No
POST	/api/v1/auth/refresh	Token refresh	Yes
POST	/api/v1/auth/logout	Logout	Yes

4.2 Worker Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/v1/workers	List workers	Yes
POST	/api/v1/workers	Register worker	Yes
GET	/api/v1/workers/:id	Get worker details	Yes
POST	/api/v1/workers/:id/health	Worker health check	Yes

4.3 Task Endpoints

Method	Endpoint	Description	Auth Required
GET	/api/v1/tasks	List tasks	Yes
POST	/api/v1/tasks	Create task	Yes
GET	/api/v1/tasks/:id	Get task details	Yes
POST	/api/v1/tasks/:id/start	Start task	Yes
POST	/api/v1/tasks/:id/checkpoint	Create checkpoint	Yes

4.4 LLM Endpoints

Method	Endpoint	Description	Auth Required
POST	/api/v1/llm/generate	Generate text	Yes
POST	/api/v1/llm/generate/stream	Stream generation	Yes
GET	/api/v1/llm/models	List models	Yes
GET	/api/v1/llm/providers	List providers	Yes
POST	/api/v1/llm/providers/:id/health	Provider health	Yes

Anti-Bluff Requirement: The /api/v1/llm/generate endpoint MUST make real HTTP calls to configured providers. The response MUST NOT contain simulated content.

5. Provider Architecture

5.1 Provider Interface

```
type Provider interface {  
    // Generate completes a single generation request  
    Generate(ctx context.Context, req *GenerateRequest)  
        (*GenerateResponse, error)  
  
    // GenerateStream returns a channel of response chunks  
    GenerateStream(ctx context.Context, req *GenerateRequest)  
        (<-chan *GenerateChunk, error)  
  
    // GetModels returns available models from this provider  
    GetModels() ([]Model, error)  
  
    // GetCapabilities returns provider capabilities  
    GetCapabilities() *Capabilities  
  
    // ValidateConfig validates provider-specific configuration  
    ValidateConfig(config map[string]interface{}) error  
  
    // HealthCheck verifies provider is accessible  
    HealthCheck(ctx context.Context) error  
}
```

5.2 Provider Registry

```
type ProviderRegistry struct {
    providers map[string]Provider
    mu        sync.RWMutex
}

func (r *ProviderRegistry) Register(name string, provider
    Provider) {
    r.mu.Lock()
    defer r.mu.Unlock()
    r.providers[name] = provider
}

func (r *ProviderRegistry) Get(name string) (Provider, bool) {
    r.mu.RLock()
    defer r.mu.RUnlock()
    p, ok := r.providers[name]
    return p, ok
}
```

5.3 Provider Implementations Required

Provider	Protocol	Status
Ollama	HTTP /api/generate	TO IMPLEMENT
Llama.cpp	HTTP /completion	TO IMPLEMENT
OpenAI	HTTP /v1/chat/completions	TO IMPLEMENT
Anthropic	HTTP /v1/messages	TO IMPLEMENT
Gemini	HTTP /v1beta/models	TO IMPLEMENT
xAI/Grok	HTTP /v1/chat/completions	TO IMPLEMENT
OpenRouter	HTTP /v1/chat/completions	TO IMPLEMENT
GitHub Copilot	HTTP /v1/engines/copilot-codex/completions	TO IMPLEMENT
Qwen	HTTP /compatible-mode/v1/chat/completions	TO IMPLEMENT
Azure	HTTP /openai/deployments	TO IMPLEMENT
AWS Bedrock	AWS SDK	TO IMPLEMENT
VertexAI	HTTP /v1/projects	TO IMPLEMENT
Groq	HTTP /v1/chat/completions	TO IMPLEMENT
vLLM	HTTP /v1/completions	TO IMPLEMENT

Provider	Protocol	Status
KoboldAI	HTTP /api/v1/generate	TO IMPLEMENT

6. Worker Architecture

6.1 SSH Worker Pool

```
type SSHWorkerPool struct {
    workers      map[string]*SSHWorker
    mu            sync.RWMutex
    healthInterval time.Duration
    maxConcurrent int
}
```

```
type SSHWorker struct {
    Hostname      string
    DisplayName   string
    SSHConfig     *ssh.ClientConfig
    Status        WorkerStatus
    Capabilities  *WorkerCapabilities
    LastHeartbeat time.Time
}
```

6.2 Worker Lifecycle

1. **Registration:** Admin adds worker via CLI or API
 2. **Connection:** Pool establishes SSH connection
 3. **Capability Discovery:** Worker reports CPU, GPU, memory
 4. **Health Monitoring:** Periodic SSH probe every 30s
 5. **Task Dispatch:** Tasks assigned based on capabilities
 6. **Auto-Installation:** If helix binary missing, auto-install via SSH
 7. **Removal:** On failed health checks or admin command
-

7. Security Architecture

7.1 Authentication Layers

Layer	Mechanism	Implementation
API Auth	JWT Bearer tokens	VERIFIED REAL
Session	Redis-backed sessions	To verify
Worker	SSH key-based	To verify

Layer	Mechanism	Implementation
Database	Password + SSL	To configure

7.2 Input Validation



- Path validation: Prevent directory traversal (. . /)
- Command blocklist: Prevent dangerous shell commands
- Schema validation: All tools validate params against JSON schema
- SQL injection: Use parameterized queries (pgx)

7.3 Sandboxing

- Shell execution: Whitelist + timeout + resource limits
 - File operations: Restrict to workspace directory
 - Network: Rate limiting on web requests
 - Container: Non-root user, read-only root fs where possible
-

8. Testing Architecture

ANTI-BLUFF RULE: Unit tests a



Testing Pyramid

8.1 Test Infrastructure

```
tests/
├── unit/                # Unit tests (mocks OK)
│   ├── auth_test.go
│   ├── llm_test.go
│   └── ...
├── contract/           # Provider API contracts (NO MOCKS)
│   ├── ollama_contract_test.go
│   └── openai_contract_test.go
├── component/          # Real subsystems (NO MOCKS)
│   ├── database_component_test.go
│   └── worker_component_test.go
├── integration/        # Full app (NO MOCKS)
│   ├── api_integration_test.go
│   └── workflow_integration_test.go
├── e2e/
│   ├── challenges/     # Real user workflows (NO MOCKS)
│   │   ├── run_all_challenges.sh
│   │   ├── llm_generation_challenge.sh
│   │   └── command_execution_challenge.sh
│   └── ...
├── security/           # OWASP tests (NO MOCKS)
└── performance/       # Benchmarks
```

9. Container Architecture

9.1 Docker Compose Stack

```
version: '3.8'
services:
  helixcode-server:
    build: .
    ports:
      - "8080:8080"
      - "2222:2222"
    environment:
      - HELIX_DATABASE_URL=postgres://helix:${
        {HELIX_DATABASE_PASSWORD:?set HELIX_DATABASE_PASSWORD
        in .env (run ./setup.sh, or cp .env.example .env)}
        @postgres:5432/helixcode_prod
      - HELIX_REDIS_URL=redis://redis:6379
      - HELIX_AUTH_JWT_SECRET=${HELIX_AUTH_JWT_SECRET}
    depends_on:
      - postgres
      - redis
```

```
healthcheck:
  test: ["CMD", "curl", "-f", "http://localhost:8080/health"]
  interval: 30s
  timeout: 10s
  retries: 3
networks:
  - helix-network

postgres:
  image: postgres:15-alpine
  environment:
    - POSTGRES_USER=helix
    - POSTGRES_PASSWORD=${HELIX_DATABASE_PASSWORD}
    - POSTGRES_DB=helixcode_prod
  volumes:
    - postgres_data:/var/lib/postgresql/data
  healthcheck:
    test: ["CMD-SHELL", "pg_isready -U helix"]
    interval: 10s
    timeout: 5s
    retries: 5
  networks:
    - helix-network

redis:
  image: redis:7-alpine
  command: redis-server --requirepass ${HELIX_REDIS_PASSWORD}
  volumes:
    - redis_data:/data
  healthcheck:
    test: ["CMD", "redis-cli", "ping"]
    interval: 10s
    timeout: 5s
    retries: 5
  networks:
    - helix-network

nginx:
  image: nginx:alpine
  ports:
    - "80:80"
    - "443:443"
  volumes:
    - ./docker/nginx.conf:/etc/nginx/nginx.conf:ro
  depends_on:
    - helixcode-server
  networks:
    - helix-network
```

```
volumes:
  postgres_data:
  redis_data:

networks:
  helix-network:
    driver: bridge
```

9.2 Health Check Requirements

Per CONST-019: Container Up $\neq$ Healthy. Each service MUST implement deep health checks:

Service	Health Check	Deep Check
helixcode-server	GET /health	DB connection, provider availability
postgres	pg_isready	SELECT 1
redis	redis-cli ping	PONG
nginx	curl localhost	upstream server response

10. Deployment Architecture

10.1 Development

Developer Machine

```
|
+---> make dev
      |
      +---> config/dev/config.yaml
      +---> PostgreSQL (local or container)
      +---> Redis (local or container)
      +---> ./bin/helixcode (server)
```

10.2 Staging

Docker Compose Stack

```
|
+---> nginx (reverse proxy)
+---> helixcode-server (2 replicas)
+---> PostgreSQL (1 instance)
+---> Redis (1 instance + sentinel)
+---> Prometheus + Grafana
```

10.3 Production (Kubernetes)

```
K8s Cluster
|
+---> Ingress (nginx-ingress)
+---> helixcode-deployment (3+ replicas, HPA)
+---> PostgreSQL StatefulSet
+---> Redis Cluster
+---> Prometheus + Grafana
+---> cert-manager (TLS)
```

11. Monitoring & Observability

11.1 Metrics (Prometheus)

Metric	Type	Description
helix_requests_total	Counter	Total HTTP requests
helix_request_duration_seconds	Histogram	Request latency
helix_llm_generation_duration	Histogram	LLM generation time
helix_llm_provider_failures	Counter	Provider failure count
helix_workers_total	Gauge	Active workers
helix_tasks_pending	Gauge	Pending tasks
helix_db_connections	Gauge	DB connection pool

11.2 Logging (Structured)

```
{
  "timestamp": "2026-04-30T12:00:00Z",
  "level": "info",
  "service": "helixcode",
  "component": "llm",
  "provider": "ollama",
  "model": "llama3.2",
  "request_id": "uuid",
  "duration_ms": 1250,
  "tokens_input": 10,
  "tokens_output": 50,
  "status": "success"
}
```

11.3 Tracing (OpenTelemetry)

- Request tracing across API -> LLM -> Provider
 - Task execution tracing across Task -> Worker -> Result
 - Error tracing with full stack context
-

12. Multi-Platform Architecture

12.1 Platform Matrix

Platform	UI Framework	Build Target	Status
Linux	CLI + TUI	x86_64, ARM64	Target
macOS	CLI + TUI + Desktop	x86_64, ARM64	Target
Windows	CLI + Desktop	x86_64	Target
iOS	SwiftUI	.xcframework	Target
Android	Jetpack Compose	.aar	Target
Aurora OS	Qt/QML	RPM	Target
Harmony OS	ArkUI	.hap	Target

12.2 Shared Core

```
shared/mobile-core/  
|  
+---> Go bindings (gomobile bind)  
|  
+---> iOS: .xcframework  
+---> Android: .aar
```

Appendix A: File References

Component	Key Files	Lines (Approx)
Auth	internal/auth/auth.go	470
CLI	cmd/cli/main.go	341
Dockerfile	Dockerfile	55
go.mod	go.mod	10
.gitmodules	.gitmodules	233

Appendix B: Verification Commands

Verify architecture diagrams are accurate

```
cat internal/auth/auth.go | grep -c "func.*AuthService"
```

Should be > 0

```
cat cmd/cli/main.go | grep -c "simulate" # Should be 0 after fix
```

Verify database schema

```
cat internal/database/schema.sql | grep "CREATE TABLE" | wc -l
```

Should be >= 11

Verify API endpoints

```
cat internal/server/routes.go | grep "POST\|GET\|PUT\|DELETE" |
```

wc -l # Should be >= 20

Verify provider implementations

```
ls internal/llm/providers/ | wc -l # Should be >= 15
```

Verify health checks

```
cat docker-compose.yml | grep -c "healthcheck" # Should be >= 4
```