

Issues_Summary

Issues_Summary

Open workable items (current_location = Issues), regenerated from the SQLite single-source-of-truth (§11.4.12).

Counts by Type × Status

Type	Status	Count
Bug	In progress	2
Bug	Operator-blocked	1
Bug	Queued	103
Bug	Ready for testing	4
Bug	Reopened	1
Task	Queued	20
TOTAL		131

Items

ATM ID	Type	Status	Severity	Description
HXC-159	Task	Queued	High	Reported-Via: §11.4.202 reporting directive task of HelixAgent the HelixSkills System (git@github.com:HelixDevelopment/skills.git , we MUST be fully ready to implement all power-features fully without nothing leftout! Full coverage with ll supported test types (suites) is mandatory! Extend and update all existing guides, FAQs, create stunning illustrations, graphs and all materials! Any gaps, shortcomings, weak spots, inconsistencies MUST BE detected in advance during the process and properly tackled with comprehensive risk-free and safe! Track all progress through the co

ATM ID	Type	Status	Severity	Description
				and remembering mechanisms we have! Use GitHub with bridge to Superpowers used for the implementation development mechanism!" PRE-VERIFIED ENVIRONMENT not assumed — §11.4.6): - GitHub SpecKit IS installed NOT yet initialized in this repo (no .specify/ and no is therefore an explicit early task, not an assumption skills.git IS reachable via SSH. git ls - remote - - feature/catalog-docs, feature/deep-research, feature full branch/tag inventory MUST be re-derived at re this partial listing. - The repository is NOT currently .gitmodules contains no HelixDevelopment/skills is cli_agents/codex-skills -> vasic-digital/caf-codex-s repository and must not be confused with it. - Both module helix_code/ (module dev.helix.code) and the (module dev.helix.agent). MANDATORY DELIVERY C GitHub SpecKit for ALL phases of the incorporation implementation, executed subagent-driven (§11.4.7 structured as phases -> tasks -> subtasks, with an ex of-code and micro-POCs where the design is load-b §11.4.169: unit, integration, e2e, full-automation, CH HelixQA banks (HelixDevelopment/helix_qa) with a stress + chaos, concurrency/atomicity, race/deadloc carries captured evidence (§11.4.5 / §11.4.69); every Documentation: extend AND update every existing only new ones. Produce illustrations, graphs and di materials. Four-format export discipline per §11.4.6 the main README per §11.4.212. - Risk work is a PI note: every gap, shortcoming, weak spot, danger zo detected DURING planning and each one paired wi free and safe solution (§11.4.102 systematic-debugg before rewrite (§11.4.74 / §11.4.28): survey the vasic catalogues on GitHub AND GitLab first; extend own duplicating, keeping them project-agnostic and dec incorporated as a properly-laid-out dependency pe level or submodules/, never a nested own-org chain and HelixAgent must BOTH receive the full feature the other is an incompleteness to be tracked, not sil through the continuation docs, the memory/knowledge the workable-items SSoT (§12.10 / §11.4.131 / §11.4. 1. A SpecKit specification exists and is initialized in feature, with an explicit feature inventory proven c repository (an enumerated list, not a sample — §11 implementation plan exists at the stated depth, wit

ATM ID	Type	Status	Severity	Description
				mitigation. 3. Every planned capability is wired and consumers, proven by §11.4.108 runtime signatures compiled. 4. The full §11.4.169 test-type matrix is gr and HelixQA banks included. 5. All documentation produced diagrams/illustrations incorporated, and Independent code review reaches a zero-finding GO No capability is claimed without runtime evidence every closure (§11.4 / §11.4.1 / §11.4.123). §11.4.213 PROGRAM (scheduled, not yet executed): (a) Deep v scientific papers / open-source projects+codebases / to incorporate this feature into the project (§11.4.8 debug (§11.4.102) of ALL data obtained to enumera zone / inconsistency / imperfection, and design a ri one found. (c) The design MUST ALWAYS be enterpr innovative – never less. (d) MANDATORY exhaustiv documents, an implementation plan down to lines- diagrams / schemes / graphs, illustrations, SQL defi relevant material (§11.4.65 / §11.4.73). (e) Investigat + HelixDevelopment submodules/components BEFO freely where genuinely needed while keeping them reusable (§11.4.28 / §11.4.74 / §11.4.177). (f) Plan fro one: every supported test type, the Challenges subn (§11.4.27 / §11.4.169). (g) Divide the work into phase nano-detailed enough to drive integration / implem directly. (h) Plan explicitly for enterprise scalability the feature has a UI/UX surface, produce full wirefr PSD / PDF, or whatever the project mandates) autho §11.4.190). (j) Plan full CodeGraph integration with synchronisation (§11.4.78 / §11.4.79 / §11.4.80). (k) C items (every detail + reference + attachment) synce source-of-truth (§11.4.93 / §11.4.95) + every derived related project doc/component + every connected e (§11.4.148 D5) – honestly SKIPPING any absent trac (credentials_absent / tracker_client_absent, §11.4.10 Research-doc destination (to be populated when th fully_incorporate_the_helixskills_system_into_helix Execution model (§11.4.213 clauses 1-2): this item is multi-day research/planning/documentation work project's standing autonomous loop (§11.4.87 / §11.4. when it claims this item, and MUST be driven to a g explicitly evidence-backed CLOSED terminal state u be left sitting un-wired in the backlog. Affected sco research/planning – destination: docs/research/

ATM ID	Type	Status	Severity	Description
				fully_incorporate_the_helixskills_system_into_helix Reproduction / context: UNKNOWN: not stated in established before any fix (§11.4.102 / §11.4.146 / §11.4.147) research-doc tree exists under docs/research/ fully_incorporate_the_helixskills_system_into_helix every enumerated weak-spot/gap/danger-zone carried out implementation plan down to lines-of-code exists, tests are created, and the whole effort is validated per §11.4.148 ADDENDUM — BINDING OPERATOR REQUIREMENTS === VERBATIM: “Make sure that SpecKit and Superpowers and with all extensions we have created derived from not optional colour on the SpecKit mandate — it cannot work MUST compose with rather than duplicate (§11.4.149) BRIDGE EXTENSION (verified to exist, 2026-07-29): speckit_superpowers/implementation/ — the “Helix Superpowers Bridge”. Eight documents, each in .md IMPLEMENTATION_PLAN, NANO_TASK_ENGINE, E TDD_INTEGRATION, CONSTITUTION_INTEGRATION SEVEN-LAYER architecture: 1 Developer Workstation SuperSpec bridge (orchestration — github.com/War (discipline enforcement — speckit-community.github MCP (execution) 6 Helix LLM (inference — github.c Distributed host cluster (llama.cpp RPC) CONSTITUTION MUST BE IN SCOPE (inherited BY REFERENCE per §11.4.150 diverges silently): constitution/skills/ (7) action-pref reporting-workable-items, scheduled-work-queue, constitution/mcp/ (2) media-validator-mcp.json, sch plugins/ (2) helix, scheduled-work constitution/action system), subagent_tiering.yaml constitution/scripts, credential_scan_lib.sh, guard-branch-consistency.sh guard-track-branch-label.sh, guard-work-track-bin LOCALLY — do not re-create: .claude/skills/ 10 regist clarify, constitution, converge, implement, plan, spe workflows/speckit/workflow.yml, integrations/{clau templates/, memory/ ADDED ACCEPTANCE CRITERIA extension above has an explicit disposition — reuse reason. Silence is not an answer (§11.4.118). 9. Each WIRED vs DESIGNED-ONLY with a captured probe. evidence a layer is installed — that is precisely the and reporting a documented layer as an available c namespace collision risk is addressed with a design skills system, while §11.4.164’s post_update_hook.sh into .claude/skills/. Two systems registering into on

ATM ID	Type	Status	Severity	Description
				and clash handling, not discovery at runtime. 11. S non-own-org dependencies (§11.4.74 vendor path) - supply-chain exposure must be assessed, not assumed them.
HXC-164	Task	Queued	Medium	The script that brings up the supporting services for directly, rather than going through the shared component maintains for exactly this purpose. That component the same way, gets the same health checking, and b repeatedly. Bypassing it means this project carries i and has already caused one outage of its own. A rel service startups still hide their errors, so a failure t was flagged honestly in a commit message, but a no obligation anyone will act on, which is why it is bei routing the startup through the shared component hiding so a failed start is visible.
HXC-166	Bug	Queued	Medium	When publishing the agent component, the hosting outstanding security advisories against the libraries 204. That figure turns out to be unreliable in three drifts upward on its own as new advisories are pub 205 the next day, and 210 on a live re-query on 202 be “the” count. It over-states the work by about a fi counted once for every dependency file it appears i distinct advisories, and the five criticals collapse to two places this code is published; the other copy re was never switched on there. The recorded breakd critical, 88 high, 99 moderate and 18 low. A full rea completed, and it changes the picture substantially the affected code can actually be reached in someth them currently qualify. The Go vulnerability scanner actually release, reports our code is affected by zer against a container library are reachable only from in the codebase refers to and that never enters a re remaining alerts, including three of the four critica third-party project whose container definition poin cannot start today. Most of the rest belong to a brow builds. Exactly one alert touches a component that defence that advisory asks for has already been wr alert stays open only because the dependency versi related piece of housekeeping was resolved while t files of downloaded third-party library code, includ behind one critical advisory, had been committed i removed from the tracked files, though they remain

ATM ID	Type	Status	Severity	Description
				benefit of finishing this work is that the alarming p the product, and we regain the ability to say honest carries a reachable known vulnerability. This item acceptance criterion has not been done: the depend findings have not yet been upgraded or removed, a retire the copied-in project that carries most of the
HXC-168	Bug	Operator- blocked	High	The password used to reach the project database is setup and container files, and those files are public accounts. Anyone who reads the project can read the not introduced by recent work; the project's own ea it as something that must be replaced, and that has depends on whether the same password is used any has not been established either way and should not value is already public, changing the files alone is n be changed everywhere it is used, and the setup file configuration source rather than containing it. Unti cannot honestly claim its credentials are protected.
HXC-171	Bug	Queued	Medium	A complete copy of somebody else's web application it alone accounts for one hundred and thirty-nine c dependency security warnings, including three of t be built or run: the startup configuration points at that folder, and its supporting packages have never two opposite ways at once. Because it is not built, th we actually run today, which is why they rank low. references it, the setup is broken and misleading, a recipe file, all one hundred and thirty-nine warnin to whoever does it. Anyone reading our security re distortion, since it currently buries the small numb The expected outcome is an explicit decision, recor properly maintain and build it, or remove it and its a reference to the upstream hosted service. Becaus approval, the decision must be put to the operator tracked this identical component (submodules/heli separately-minted ticket id with no Duplicate-of lin recurrence-links-not-mints violation. HXC-225 has I closed Obsolete (reason duplicate-of, superseding it investigation evidence at docs/qa/hxc225_gitmcp_in ANALYSIS.md, which identifies both tickets as track git-mcp. The operator has approved removal of this granted 2026-09-02); this item is no longer awaiting
HXC-175	Bug	Queued	Low	

ATM ID	Type	Status	Severity	Description
				The cache that remembers model information has a fallback where its clock was never configured. That fallback is the only way to build the cache always configures the clock unexercised. On its own that is harmless. The reason is if someone later edits it: a plausible-looking change to the current time would make every cached entry appear to be in the past that the freshness check reads as a negative expiry limit. Every entry would then be considered stale and keep serving outdated model information indefinitely. The choice is to either add a small test that pins the cache branch entirely and document that there is one sup
HXC-178	Bug	Queued	Low	When a caller presents an API key, the server compares it to an ordinary text comparison. That kind of comparison is one that does not match, so a key sharing the first few characters is more reject than one that differs immediately. An attacker can use differences across many attempts to recover the key by guessing it outright. Network timing noise makes this a low is low rather than urgent, but it is a genuine weakness. It's cheap: use the comparison function designed for secret matching amount of time regardless of where the difference is introduced by recent work.
HXC-179	Task	Queued	Medium	The check that decides which websites may open a connection deliberately allows requests that carry no origin information in their behaviour, because only browsers send that information and legitimately omit it. It is safe today only because a server can't away anyone without valid credentials. The two problems are nothing records or enforces that coupling: if someone bypasses the login check while working on something unrelated, the information would become completely ungated, and the work here is to add a check that specifically confirms the connection upgrade, so the dependency is protected.
HXC-180	Task	Queued	Low	Three commits in the current release range do not refer to a piece of data that was not added until those three points gets a build error. The tip of the branch is corrected shortly afterwards. This cannot be repaired by rewriting published history, which the project forbids. It is for anyone hunting a regression by stepping back to those three points that fail to build for a reason unrelated to the may wrongly conclude the fault lies there. The worst affected points and their shared cause somewhere

ATM ID	Type	Status	Severity	Description
				so the failure is recognised immediately as known and not a surprise from scratch.
HXC-181	Task	Queued	Medium	HXC-160 corrected the 21 stale references to scripts/generate_fixed_summary.sh across the 12 projects. It also added the CM-SUPERSEDED-GENERATOR-NAMING mechanism. The sets were deliberately left untouched and are the source of the Constitution.md still carries 14 references across several projects. The universal rules that projects other than HelixCode carry in their records such as the Phase 5 Go-binary-shim plan. A new rule is a governance amendment that CONST-049 requires a rule to be configured upstream, then re-cascaded and pointer-bumped in a session that closed HXC-160, and a canon amended to reflect the drift than the stale wording, so the canon was left as is. The 45 owned submodules carry cascaded restatements of the rule. The correction applied in the parent repo is deliberately not applied because the fix names a HelixCode-specific mechanism. The new wording into decoupled, project-agnostic submodule pointers. They don't them and violate CONST-051(B). The correct sequence is to use neutral canonical wording that names the workable rule, and push it in the constitution submodule per CONST-049. The fleet and bump pointers. Who benefits: every consumer of the anchor text, and any agent reading a submodule's summaries are produced. Acceptance: canon name is changed to the new wording, the change is pushed to every constitution submodule. They are re-cascaded, submodule pointers are bumped, and the CM-SUPERSEDED-GENERATOR-NAMING both pass with flying colors.
HXC-188	Task	Queued	Low	The main handbook that tells contributors and authors how to organise lists several folders at the top level that don't exist when only one is present, and refers to a top-level canonical folder. Anyone following it — a new contributor, or an author — will look for things that are not there, and get confused or broken or that they have checked out the wrong thing. The fix of the document, which is otherwise the authoritative source. The correction is small and purely descriptive: mean the same section to match, then keep the two in step as the last time.
HXC-189	Task	Queued	Low	One of the external projects this codebase depends on. Its configuration still refers to it by its previous name, and the hosting service silently forwards requests from the old name. The forwarding is a courtesy, not a guarantee: it disappears if the project under the old name, and it is not honoured as a dependency. If it stops working, fetching the project will fail.

ATM ID	Type	Status	Severity	Description
				name nobody recognises, which is unusually confusing. The project's current canonical name so the reference should be on a redirect continuing to exist.
HXC-190	Bug	Queued	Low	When a running command is cut short because it times out, it says it was not a timeout. The check that sets that flag is the caller's own deadline, which usually has none and is not stopped the command. Investigation showed the problem was either, because the internal signal it would consult was for cancellation and never a timeout, and the timer that was the mechanism entirely. The effect is that anyone diagnosing the failure and no indication that a time limit was the cause was in the wrong place. A sibling code path that runs commands correctly by doing it inside the timer's own callback was not a copy.
HXC-191	Bug	Queued	Low	When a command is cancelled or times out, the system continues but anything it started, by signalling the whole group of processes works if the command was placed into its own group. If the sandbox enabled — the normal configuration — it is the sandbox switched off, the grouping step is skipped and the operating system to signal a group that does not exist. The error is discarded. The result is a cancelled command that is dormant, because the only configuration that disables it is so no shipped path reaches it. It is worth fixing because it would appear only in an unusual configuration, which is hard to diagnose later.
HXC-192	Bug	Queued	Low	Output from a running command is read line by line. A single line may be. When a line exceeds that limit the reader is permanently for that stream, because the buffer is full and has past it. Nothing else takes over the reading. The correct solution is until the operating system's own small buffer fills, and someone to read. So one unusually long line, which is readable output produce quite naturally, can wedge the reader. The fix is to keep draining and discarding the remainder of the line and abandoning the stream, so the producing command can continue.
HXC-196	Task	Queued	Medium	The handbook that describes this project's technology is one of its networking libraries. Both parts of the code are wrong because a security fix required moving off the older code. It is deliberate; it is the handbook that is now wrong. The fix is a new contributor or an automated helper reads the code and will confidently state a version that has not been used before. The same document has already been found describing the problem.

ATM ID	Type	Status	Severity	Description
				additional inaccuracy makes the whole document l recorded version to what is actually in use, and to n reason, so nobody later reverts it believing the han
HXC-197	Bug	Queued	Low	One test directory contains a duplicate of its own p files appear twice in the project at two different dep renaming exercise that moved a tree while leaving the new one. Nothing reads the nested copy, so it ca anyone searching the project finds two results for e which is real, and any tool that scans for duplicate blocks a useful check from being switched on: a gu duplicates cannot be enabled while this one exists, every run. Removing it requires first confirming th nested copy is genuinely the leftover and not the or
HXC-200	Bug	Queued	Low	A detector was written to catch a specific kind of st stuck trying to hand off a result nobody is collectin one particular description of what the worker is wa form of the same stall — where the worker waits o rather than a single handoff — and the detector do demonstrated rather than theorised: a deliberately went completely undetected while the detector rep does catch is the historical one, so the guard is not the newer structure while breaking its escape rout recognise both descriptions is a small change and n defect rather than half of it.
HXC-204	Bug	Queued	Medium	Two long-running tests — one exercising heavy sim one exercising leader election among worker nodes report failure when the machine is under load, and own. Measured: during a full test run both failed, w times consecutively, one finishing in roughly a fifth about a twentieth. Their verdicts are therefore rep whether the product works. This matters most at ex test run performed before a release is by definition these two will mark a healthy release as broken an through. A third test with the same problem was al inconclusive run report as skipped rather than fail the same treatment fits here. Both should wait for t than assuming a fixed time is enough.
HXC-206	Bug	Queued	Low	The newly-fixed health refresh deliberately release provider over the network, so that a slow or hangin It then re-acquires the lock and only applies its ver changed underneath it. There is a narrow remainin

ATM ID	Type	Status	Severity	Description
				started again entirely within one probe, the check s applies a verdict formed against the previous insta briefly reported unhealthy when it is fine, which th dangerous direction — reporting a stopped provide Worth recording that this is cheap to close rather th incremented on each state change is invisible to the to any published structure. An earlier note describi was wrong and has been retracted.
HXC-207	Bug	Queued	Low	When a model provider record is created, its enviro shared template by reference rather than copied. E points at the same underlying settings, including ac Nothing writes to those settings today, and the valu no corruption occurs at present — this was verified record it is that the protection now added to these r manager cannot protect a structure shared with an legitimate, properly-locked write to a provider's set manager's view as well, and the locking will look co when the record is created removes the hazard per
HXC-208	Bug	Queued	Low	Four compose entries across two end-to-end test sta the Slack mock and the LLM-provider mock, but ne Any attempt to build those stacks therefore fails at which means the containerised form of these two s exercised. This was surfaced while fixing an unrela same two services: the fix could be proven at the sc against a running container, precisely because no c produced. That gap matters beyond these two mock process leaves the deployed-artifact layer unprover failure the four-layer verification discipline exists t Dockerfiles, or to remove the build entries if these s run containerised, and then to prove the choice by
HXC-216	Task	Queued	Low	A blanket rule excluding log files from version cont evidence, because evidence transcripts are written corrected so this cannot happen again, and the thre have been recovered and committed. Thirty-five ol the runs exist only on the machine that produced th an evidence folder that appears empty, which is inc never run. Recovering them is not automatic, becau seventy-eight megabytes and committing those into deserves a deliberate decision rather than a reflex. keep what genuinely substantiates a closed item, tr

ATM ID	Type	Status	Severity	Description
				ones rather than storing them whole, and record exactly why, so the gap is visible rather than silent.
HXC-219	Task	Queued	Medium	A recent repair changed how the release gate decides if evidence really belongs to the change it claims to do. It now commit on a labelled line rather than merely happen somewhere in the text. That new requirement was not to have to follow it: the guide that authors read before the new labelled field, so a contributor following the guide and evidence the gate will reject without understanding why. Describing the gate itself has printable and web copy. The page was last edited, so all three versions disagree on how to describe. Fixing this means updating the author-facing guide, the citation field and regenerating the exported copies. Contributors who benefit are contributors recording evidence and contributors who have no accurate written description of the rule because they can't follow the written guide and produce evidence without a successful attempt.
HXC-224	Bug	Queued	High	When we mark a piece of work finished, we record the work. Nobody ever checked that those pointers actually worked. Different kinds of rot accumulated silently and none was reported. First, some pointers hold a whole paragraph of text, but there is no way for a machine to follow them. Second, some pointers never created because the person doing the work said they were done means the proof exists but nobody can find it from the logs. Ordinary progress updates rather than to the actual work. The notes look like formal proof. The effect is that a completion is backed in every summary and dashboard while the actual work is not. The way anyone finds out is by manually hunting for it. The fix is to make the completion pointer a checked field: it must be checked if it exists, it must be attached only to real completions, and it must be refused at the moment someone tries to re-use it later. This protects everyone who relies on our finished work as a claim of proof that cannot be produced on demand.
HXC-226	Bug	Queued	Medium	The agent project is mirrored to two hosting accounts. The first was only ever switched on for one of them. Queried regularly, it has a hundred and ten open alerts while the other reports none. The first one the main project is configured to pull from, so a list of the component we actually consume is shown as a list of a hundred findings sit unseen on the sibling copy. Note that the two mirrors hold the same commits. What differs is what is watched. This is dangerous precisely because the agent is not

ATM ID	Type	Status	Severity	Description
				findings is indistinguishable from a report of zero findings. The second case is what we have. The work is to swap the two so a future divergence is noticed rather than a statement about this component's vulnerability starting from.
HXC-227	Bug	Reopened	Critical	A design document committed forty-eight days ago appears to be a genuine access key for an external service placeholder. The section is headed as being copied from and described as already configured, and the value the placeholder would have: it is fifty-one characters long, contains no example or to-be-filled-in text, is on the main branch and has therefore been published for a day it was written. Anyone with read access to any fork made at any point in those forty-eight days, although now would remove it from the current revision only if history is forbidden, and rewriting would in any case be The only action that actually withdraws the key is replacement, which requires access to the provider within the repository. Until that happens the key must be revoked, the document should be edited to reference of quoting its contents, and a check added that refuses this shape.
HXC-231	Bug	Queued	High	The HelixLLM gateway downloads large AI model files and starts accepting network connections. During that time the service as running and healthy, but every attempt on 2026-08-06 this window lasted thirty-seven minutes actually began listening. Anyone checking the service everything is fine while the service is in fact unusable depends on the gateway will fail for the whole window because the download depends on an external site. If one of the two downloads timed out after roughly ten minutes that site were unreachable the gateway might never be accepting connections first and download models in an honest not-ready state while the downloads are still
HXC-232	Bug	Queued	Medium	HelixAgent expects two tables to exist in its database: agent_instances, but neither of them has ever been anywhere in the project that creates them. As a result, locks once every minute, the database refuses the request and an error is written to the log. Verified on 2026-08-06 directly: neither table exists in any of them, and the

ATM ID	Type	Status	Severity	Description
				minute period plus a further hundred and thirty times. HelixAgent otherwise runs normally, so nothing visibly breaks. HelixAgent buries genuine problems in the log and means the log is not useful to support is silently doing nothing at all. Fixing this would require these tables were intended to contain to write the logs. This is guessed.
HXC-234	Bug	Queued	Medium	On startup HelixAgent tries to build and launch a set of servers known as MCP servers, using the container engine. Some of these inside the container fail during their dependency-installation operation is abandoned. HelixAgent records a warning about these servers and then continues running normally. Nothing obviously breaks. The real effect is that even if the servers were meant to provide is silently missing, and because it is so easy for nobody to notice. Observed live on 2026-08-08. The build was attempted twice and failed both times. HelixAgent uses a large container image each time, which also makes it difficult to repair the dependency installation inside those containers.
HXC-235	Bug	Queued	High	The HelixLLM gateway provides a feature that finds the closest exact wording. On startup it reports that no real language model purpose, so it has fallen back to a simple hashing model. HelixAgent states plainly that this fallback does not capture meaning and that it will be significantly degraded. The important part is that it does not off or return an error: it keeps answering every request with an effectively arbitrary rather than relevant. Anyone using HelixAgent from the responses that it is not working properly. This is a full platform boot. Resolving this means pointing to a more genuine embedding provider, and deciding whether this is acceptable behaviour or whether the feature should be removed.
HXC-236	Bug	Queued	Medium	The standard library routine that splits a web address into components differently in two parts of this codebase, using the same routine. In the main application it rejects an address whose host component contains a colon. In the containers component it quietly accepts the same address with a colon. The cause is that each component declares with the newer version tightened this routine; the containers component is older, so it keeps the older, permissive behaviour. Two different pieces of reasoning about address handling is only valid for one, which has already caused one incorrect conclusion. This is a Second, and more seriously, the day someone raises a new language version, addresses it accepts today as a failure will appear as unreachable services rather than a change. The work is to make the difference explicit.

ATM ID	Type	Status	Severity	Description
				deliberately which behaviour each component should be. The reader will find it, and add a check that fails if the test is not noticing.
HXC-238	Bug	Queued	Low	The safety check that stops half-finished experiments from throwing an exception for captured proof files, which was never intended to satisfy the old exception rule and so could not be safely used. It is narrow: the file must sit in the evidence folder, cannot be deleted, saved as non-runnable, and not begin with the line "evidence". Together those make the file inert in normal use. We were not aware of deliberately pointing a program interpreter at the file, which no file property can stop. The practical risk is that it is a bug rather than an accident, and the alternative was leaving it as is. The proof it is required to keep. Recording it so the exception is not absolute, and so anyone widening it later can be done.
HXC-239	Bug	Ready for testing	High	When HelixQA runs a test bank that needs to sign in, it does not send a sign-in reply, so every test in that bank that needs to sign in fails. MECHANISM (the original wording of this item was "the test bank") the reply carries the real access pass at the top level. A separate bookkeeping reference for the session sits in the session object. The runner looked for the bookkeeping reference, found nothing there, and stopped with a plain complaint "no access pass". It never handed the server a wrong value and was never rejected. It failed before making a single signed-in request. The fix was to send the wrong value and being rejected, which is not what was intended. That text were nonetheless correct. A SECOND PLACE: the test step had its own copy of the same assumption with "no access pass" and could not find the pass it simply carried on without checking. Unsigned and the resulting rejections were recorded as "no access pass" rather than as a failure to sign in — which is why the test failed. THE OBVIOUS FIX WAS WRONG: the bookkeeping reference was in a different family of about fourteen banks that targeted the test bank. The access pass genuinely does sit at the top level under "access pass". The names would have repaired one product by breaking the existing name first and adds fallbacks tried only once. The support for reaching a nested location, and reports "no access pass". HOW TO REPRODUCE: run a bank requiring sign-in. The test will run stop with a missing-field complaint before any sign-in. OUTCOME: the bank used for measurement went from passing to failing and two failing. The two that remain are unsigned. The work: one posts an empty body where the service expects a sign-in with a leftover record created by the very measurement. The original figures, because that bank does not clean up.

ATM ID	Type	Status	Severity	Description
				the originally reported nine-and-one is no longer relevant; banks needing sign-in authenticate against both server and database changes; a failure to find a usable pass is reported as a service fault; no credential value ever appears in a database; it proves the behaviour, shown real by a paired mutation.
HXC-240	Bug	Queued	Low	One of the HelixCode test banks signs up a new account and uses the very same account name, 'hxc_gen_e2e'. The first run succeeds and the check passes. Every run after that fails. In the database, the server correctly refuses with 'user not found', recorded as a failure forever after. This was observed when a first run of the bank passed that step, and a second run failed. Visible in the database timestamped to the moment of failure. The checks work under require that automated checks can be run with the same answer, cleaning up after themselves. As a result, the bank quietly poisons its own results, so a permanent red flag is set. It does not do with whether the product works. The fix is for the bank to do each run, or to remove the account it created when it fails.
HXC-241	Bug	Queued	Low	The checks that confirm HelixCode can generate AI responses are broken. Inside the server's reply, and that comparison treats the AI response as a string. Two checks in the generate-e2e bank ask for words with different capitalisation, so they are marked as failed. The checks behaved correctly. The most serious case asks the AI to generate a reply for 'hello' in small letters; the AI answered 'Hello'. A working feature was reported as broken. This was observed when the server: asking it to reply with an invented word returned 'hello', it what seventeen times three is returned fifty-one, which proves real AI generation is running and healthy. The server reply for 'authorization' in small letters while the server returns capital A. Expecting exact capitalisation of freely generated text. The consequence is false alarms that hide real bugs over time.
HXC-242	Bug	Queued	Medium	Five checks covering the built-in screenshot and query engine against the running HelixCode server, and every other server answers 'QA engine is disabled' and reports that the server is being honest here rather than misbehaving. The whole advertised area of the product is switched off. The feature cannot be used by anyone or confirmed as working. The checks listing the available screenshot engines, listing quality of a session, status of a session, starting a new session, and the health of the server with nothing to run. Because the feature is off, we have no way to know whether the underlying code behind it functions. So the feature is broken.

ATM ID	Type	Status	Severity	Description
				feature is meant to be available, and if so switch it to a different behaviour is actually proven; if it is meant to stay on the current reporting failures.
HXC-243	Bug	Ready for testing	Critical	Several of the automated test collections that check about what a correct answer looks like. They send a request and record a pass regardless of the reply. This was a mistake. The collection was deliberately aimed at the wrong service, so an error for every request, and it reported both of them as passes against a service known to be broken cannot be trusted, so its green result carries no information at all. This is a failing test, because a suite that cannot fail is worse than one where there is none, and it will keep producing it even if every check an explicit expectation — the status it should be — answer must contain — and then prove each one is false. This is something known to be wrong and confirming it repeatedly in the same run: four apparent failures in the worker harness looking for the wrong field name in the log, and that mismatch should be corrected so real failures are reported.
HXC-245	Bug	Queued	High	One blocked work item (HXC-172) has its explanation written into its own description. The tracker rebuilds those stored explanations every time it regenerates its records, so an explanation that is discarded the next time the tracker runs. This happens today: a regenerate-and-reread cycle drops the explanation, then correctly reports the item as blocked-without-explanation, that explanation is what makes a blocked item actionable, what was already tried, and which decision would be made. The decision waiting on a person into an item nobody could keep the context needed to make the blocking decision, why the item stalled. The expected outcome is that the explanation again, the stored and written copies are preserved — proven by the tracker's validation process.
HXC-246	Bug	Queued	High	A complete run of the agent runtime's automated tests found 12 groups failing, and 74 individual test failures. This is more than assumed, because the early evidence points at the agent rather than at the product. Three patterns account for most of the failures: the in-memory cache service because they look for a service in a container while this machine publishes it on a different port; a running service to answer a web request and fails to do so; and answering correctly when asked by hand; a third pattern is against fixed limits and overshoot them by about a quarter.

ATM ID	Type	Status	Severity	Description
				jobs and a service rebuild were competing for the s product is healthy, and none of it proves the produ parallel investigations are now establishing, each r rather than a plausible story. This matters because reasons is as damaging as one that passes while the everyone to stop trusting the result, and both hide operator benefits from a suite whose red means som signal they can act on. The expected outcome is eve evidence as a genuine product defect, a test defect, contention artifact, each real defect fixed with a tes returning to a trustworthy state.
HXC-247	Bug	Queued	High	Two separate parts of the system have both been to and neither knows about the other. The agent runti decides which service gets which port number - ass itself. But a different component, the model verifier names port 8100, and because the verifier starts fir agent runtime is launched from a settings file that s never even tries to claim the one it was allocated. T port 8100 for the agent runtime and are answered recognise the requests and rejects them with a not- runtime as broken when it is running perfectly wel because it makes a large part of the test suite struct names, and because the same collision would misle real. Whoever operates or deploys this benefits dire failing, and a genuinely failing one would look exac a single place that decides port allocation for every claiming the same number, the agent runtimes own and the tests then passing or failing for reasons tha Later evidence settles which of the two sides is the deployment is not misconfigured at all. The model file that starts it on this machine - documents in its agreed meeting point between the verifier and the gateway looks there by default, and, in as many wo runs on the other address here. The choice was the down at deployment time, in the verifier's favour. T clearer than first described: the agent runtime's int date, still claiming an address that a different, docu with a note that the old address was abandoned wh still in use. A contributing cause is that the verifier so the one mechanism meant to prevent two compo not arbitrate a component it had never been told al unchanged - the tests inherit the stale claim and ar

ATM ID	Type	Status	Severity	Description
				the repair direction is now settled rather than open the address it genuinely serves, give the verifier an recur, and point the test defaults at the real address establishes which side is stale and why; it does not safe to execute, because that entry is consumed across change still needs its impact review before it lands.
HXC-248	Bug	Queued	High	A cleanup step in the automated test suite can shut the only thing preventing that is a coincidence. When to stop any containers they started. To avoid stopping first check whether the agent service is still running <i>something</i> answers on network port 8100, with no v On this machine port 8100 is held by a different container the check says yes, and the shutdown is skipped. The different port and is never actually consulted. If the late, or moved, that same check would say no and the live platform out from under whoever was using it also untrue: it reports that the agent is still running all. This matters to anyone running the test suite on deployment, which is the normal case here. The expected the identity of what is answering - not merely that it makes its decision on the real condition rather than logs is true.
HXC-251	Bug	Queued	Medium	One of our own services could not start while our containers both had been told to use the same network address conventional default that the wider industry uses for precisely what makes it the number most likely to be on our own machine it was taken, by a supporting database. The result was that the service refused to start when a client dialling that same well-known address reached which completed a perfectly healthy-looking connection. Because the wrong service was alive rather than absent something is unreachable did not skip: they ran, failed our service, which had never been running at all. The twenty test failures that had been attributed to the service in the project's central address book so its address never silently collide again, and it now fails immediately rather than starting somewhere unexpected. What is misleading: the startup message printed for the operation so anyone reading the log is told the wrong place to platform benefits, and the expected outcome is that the rest of the stack and that every message it prints bound.

ATM ID	Type	Status	Severity	Description
HXC-254	Bug	Queued	Medium	Tests in one area of the codebase interfere with each other because they share a single piece of network machinery, so a test that is supposed to do with the code it is testing. When each connection is given its own timeout setting but no connection handler is provided, the library quietly falls back to one shared handler behind the scenes. Tests in this area start roughly a hundred and forty-five minutes apart, so around five hundred cases to run simultaneously; each test is expected to run at the end of its own test, politely tells that shared handler that it is done because the handler is shared, it also severs connections to the network it is using. The result is a failure that appears in a different form in the test setup rather than in the product. It reproduces the failure that runs in ten fails this way. Developers are the people who are responsible; unpredictably teaches everyone to re-run it rather than to ignore it comfortably inside that noise. The expected outcome is that each has its own connection handler so shutting one pretend session down doesn't affect the test, and the suite becomes trustworthy enough that a failure is genuinely wrong.
HXC-255	Task	Queued	Medium	Two things are left over in the scripts that run the project: the first needs a decision from the operator rather than a question of whether it is a problem: the end-of-run summary prints “Integration successful” whenever the log file merely exists, regardless of whether the tests which tests genuinely failed still shows a reassuring message, the most likely to read. The second is deliberate and more subtle: it is written to note test failures as warnings and carry on with the status even when real tests have failed, which means that the project blocks a release. That behaviour was chosen on purpose to allow to abort a long run and lose the rest of the information gathered between gathering everything in one pass and refusing to continue. It is broken. Because it is a deliberate posture rather than an operator decision about how the project wants its release status to be altered silently by whoever happens to touch the project, the runs to judge release readiness benefits from settling for the fact that only that the script reached the end. The expected outcome is that it reflects the real result rather than the presence of a warning, an explicit, recorded choice about whether these runs are successful.
HXC-256	Bug	Queued	Low	The tool that regenerates the project’s tracker documentation happens to be run from unless it is explicitly told otherwise, and one optional setting quietly produces a second, unnecessary, copy while the real ones stay out of date. The tool’s own documentation is optional, which is what invites the omission, and it is in the wrong folder rather than the folder where this project actually runs.

ATM ID	Type	Status	Severity	Description
				found the hard way during routine work: running a setting created sixteen stray copies at the top of the one directory down, kept their old contents. The co someone can look at freshly written files, see today records are current when the versions under version the tracker documents by hand is exposed, which is automated helpers working outside the standard so bounded and that bounds the severity: every wrap destination explicitly, the tool prints the full path of visible to a careful reader, the stray copies show up separate consistency check would eventually notice. What is missing is the tool itself objecting. The expected documents without naming a destination either write or refuses and says so, instead of succeeding somehow caught this does not exist today: the existing guard supplies the destination explicitly, so it can never fail out - adding that second case is the specified follow
HXC-257	Bug	Queued	Medium	The automated check that guards our workable-items actually measures, so a reader who trusts its words computed. Internally it names the thing it inspects written description states that it proves the commit it never consults version control at all - it simply copies folder, which may contain changes that have not been genuinely proves is narrower and still useful: that they right now agree with each other. The gap was demonstrated the check reported success while the database held yet been committed - exactly the situation its own words stating plainly is that the underlying behaviour is part of the pre-release sweep, where the point is to confirm commit is self-consistent, so inspecting the working there is a documented reason for the copy - opening as a side effect. On that reading the repair is the name. Everyone who reads that check's verdict before applying the difference between "what is on your disk is correct" is exactly the difference that matters when the name has already spread: the description of the problem repeats the same claim. The expected outcome is that and the sentence it prints all describe only what it is. The guarantee is wanted it is added deliberately as a self-control. The test that would have caught this does not disagreement between the documents and the data

ATM ID	Type	Status	Severity	Description
				between the committed copy and the working copy adding that case is the specified follow-up.
HXC-258	Bug	Queued	Medium	Our workable-items database keeps a small bookkeeping synchronisation run between the database and the documents. That note is only ever written by one of the two synchronisation documents into the database - and the value it writes is the path that actually ran. The path that goes the other way, from documents into database, never updates the note at all. The practical consequence is that regenerated the note still describes an older run in the database. This makes it difficult to read it to find out what happened most recently. It also makes it difficult to decide matters because deciding the direction of a synchronisation run can destroy records if it is made backwards, and the database is not capable of supporting it. The database was last updated by an into-database run dated the eleventh of July while the documents were still in the database-into-documents regeneration on the ninth of July. The database-into-documents shared tooling that performs the synchronisation, which was used to regenerate the database, genuinely ran on both paths rather than assuming that the database-into-documents hand would be undone by the next run and is therefore still present.
HXC-259	Task	Queued	Low	Every workable item is supposed to accumulate a status trail. If its status changed - opened, reopened, closed - together with the date and author of what evidence justified it. A recent repair noted in the database that there was no such trail. Measurement across the whole database showed that there were no such trails to those two: eighty-one distinct records covering over a year of history entries at all, and all but one of them are item records. This is a problem filed away. In other words the majority of our closed items have no account of how it reached that state, which weakens our ability to understand why something was reopened, or to record the reason. The cause is that items created by direct database write using the database creation command skip the step that opens the audit trail. Items created before the trail existed never had one. This is deliberate, but it is a filling: inventing dates and authors for events nobody can verify. It is a trail that is worse than an absent one because it works by pretending instead is a decision on how to mark these records. The database-into-documents tooling that prevents any newly created item from joining the database-into-documents regeneration on the ninth of July.
HXC-260	Bug	Queued	High	The Kubernetes manifests for HelixAgent told every node to listen on port 9090, and they set an environment variable called HELIXAGENT_LISTENING_PORT which was true. No Go source in the repository reads GRPC_LISTENING_PORT, so the port the server listens on; this was proven at runtime by the fact that the port bound :8112 while the real variable HELIXAGENT_LISTENING_PORT was 9090 is a port no HelixAgent process ever binds: the port is not in the internal/ports registry (HelixAgentGRPC, core band).

ATM ID	Type	Status	Severity	Description
				by running the built cmd/grpc-server binary and ol The practical effect is that anyone deploying HelixA manifests would get a Deployment exposing contain gRPC traffic to targetPort 9090, and a NetworkPolicy artifacts agreeing with each other and all pointing port the server would actually bind was blocked. The number because the manifest LOOKED configurable and edited GRPC_PORT would see no change whatsoever. This item covers correcting all four manifests that r service.yaml, networkpolicy.yaml, configmap.yaml) the dead variable with the one the server honours. limitation: the image this Deployment runs is built no gRPC server at all (that is a separate binary, cmd correct but INERT until a grpc-server container is a corrected manifests make a one-line change instead checking out the pre-fix tree and running the polar RED_MODE=1, which asserts the dead variable and Acceptance criteria: internal/ports/published_grpc_ unset (asserting every manifest names the registry outside a comment) and fails on the pre-fix tree, cit
HXC-262	Bug	Queued	Medium	The project keeps a battery of tests whose whole job catch problems, by deliberately breaking things and assertion in that battery — the one covering a servi occasionally reports a problem when nothing is wr consecutive runs, and ran correctly six times out of intermittent rather than consistently broken. The c check itself: it asks the system two separate question which process is running it, and between those two move on, so the two answers describe different mo happens the check cannot find a process to examin anything. The practical harm is not a missed defect a condition that is not present, and worse, people w it, which quietly erodes the value of the one battery The fix is to read both pieces of information in a sin same instant. This was deliberately left unfixed by changes the sampling behaviour of a check that wa such a change deserves its own review rather than
HXC-263	Bug	Queued	Medium	The project keeps a folder of tests whose purpose is genuinely work, by deliberately introducing a fault check reports a failure. A test like that only has val Counting the invocations at the current revision, on folder are ever executed by anything; the remainin

ATM ID	Type	Status	Severity	Description
				never run. This is the same problem the project already had when three safety checks turned out to exist but be the same reason: a check nobody runs cannot fail, so provide coverage. The presence of these files is actually counting test files sees protection that is not being delivered look better than it is — five of the files are mentioned in the mentions are a comment, an entry in a skip list, and none of which run anything. Resolving this means either to wire it into the release sweep so it runs, or to return a choice visible rather than leaving the file sitting there to deliver.
HXC-264	Bug	Queued	Low	A single entry in the project's work tracker manages to be different ways in three different fields, and the third field says a required program is not installed on the machine but exists but cannot be found because of where the service such file exists anywhere on the system. Those are different fixes, so a reader cannot tell from the entry what also proposes a remedy, giving the service a direct path, not what was eventually done: the capability was removed from a different service that was already running, and the service was absent from the machine today. This matters because of what was reported and why, and an entry that conveys the purpose for anyone reviewing the history later. It is out of step with the database, which is a problem that the rendered documents faithfully reproduce what the entry is inside the database entry itself. Resolving it means an accurate account that records both what was originally reported and resolved, without erasing the original report.
HXC-265	Task	Queued	Medium	HelixAgent keeps 36 Go modules nested inside its repository. Most of them are never compiled by anything the test suite. A developer can rename a package, change a shared dependency, and every build and test still reports green — the build is successful. That silent-failure surface is what this item tracks, and the documentation samples, because the project anti-builds the documentation example works when copy-pasted and the build cannot honour that promise. WHO IS AFFECTED: developers and readers who copy a documentation example expecting it to be verifiable by one command (the quotes are load-bearing). The pattern before git sees it and reports 2 instead of 36: <code>git ls-files '*/go.mod' \ wc -l</code> reports 36. The pattern after: <code>'challenges/codebase/go_files/*/go.mod' \ wc -l</code> reports 2. Makefile build-challenge-modules recipe walks. By

ATM ID	Type	Status	Severity	Description
				under challenges/, 2 under plugins/, 2 under docker/ and cli_agents/. THE CLASSIFICATION IS PER-MODULE. Previous revisions of this item stated a single wrong total because it was answered by any one command, so each class below is a separate COMPILER PATH AT ALL — 25 modules: the 23 under challenges/ compile nowhere, the three challenges/ only run presence checks (test -f, grep -q), and root/ because Go does not cross nested-module boundaries. (1) GATED CONTAINER IMAGES — 2 modules: docker/ and cli_agents/ declared as build contexts in docker-compose.proto but not in their Dockerfiles, but no test suite or gate exercises are run, so rebuilds only when the image is absent, so breakage is non-deterministically rather than never. (2) FULLY INSIDIOUS: api: it is required and replaced in the root go.mod, but not with no build tags, and built for four platforms by compiler increment PHASE_FAILURES and set the exit code. (3) needs no work. Note for future readers: go list -f {{.Path}} not contain package”, which is a true output but an artifact rather than whether the module is ever compiled — I mistook the one for the other. (4) PARTIALLY INSIDIOUS: Toolkit: internal/verifier/startup.go imports Toolkit, which pulls in three more Toolkit packages, so at least 4 of the 17 every root build while roughly 17 remain outside. (5) UNRECORDED REASON AND A GUARD — 1 module, cli_agents/, isolation marker whose header documents why the test suite is paired with the regression guard at tests/regression_test.go, satisfies this item’s second acceptance arm and is tested in module in classes (1), (2) and the un-compiled remainder. (6) or compile-check target the test suite actually runs, but no recorded reason in the manner of class (5); and a guard appears that is neither built nor explicitly excluded.
HXC-266	Bug	Queued	Medium	The function that builds the URL clients use to reach the host “http://%s:%d” without ever bracketing the host, so malformed URL. WHY THIS IS REACHABLE RATHER THAN NOT: the layer deliberately treats the IPv6 loopback ::1 as a valid configuration that sets the host to ::1 passes every validation formatter. HOW IT MANIFESTS: the emitted address is not a parseable URL — the colons of the address and the host to any URL parser, so the client fails to connect with a clear configuration error. WHO IS AFFECTED: any client using IPv6-only or IPv6-preferred host, and any deployment using IPv6 literal instead of a name. HOW TO REPRODUCE:

ATM ID	Type	Status	Severity	Description
				the client base URL, and observe the returned string in correct bracketed form http://[::1]:7061. ACCEPTANCE CRITERIA: literals per RFC 3986 so ::1 yields http://[::1]:7061, IF a regression test covers IPv6 literal, bracketed input IPv4, and hostname cases.
HXC-267	Bug	Queued	Medium	When HelixQA signs in to run an API test bank and but a reply the runner cannot read, the runner goes sign-in, carries on making requests with no credentials, faults in the API being tested rather than as its own, the case where the reply IS readable but carries the this item covers the door that fix left open. WHY IT IS REACHABLE: explanatory finding is nested inside the branch taking structured data, and that branch has no counterpart, unreadable reply skips the reporting entirely. HOW TO REPRODUCE: tested service is broken when in fact the runner never reads the report to investigate the wrong system. MORE INFORMATION: this item originally described two silent shapes, the established by running every case against the genuine, out of eleven tested. Silent: an empty reply; an HTML data; bytes that are not valid text; a bare quoted string; an object; a bare true or false; and a very large reply. item's reporting: the literal null, and an empty object. whether the reply PARSES, not whether it carries a narrower descriptions kept undercounting it. WHY IT IS REACHABLE: HelixQA report for a service whose sign-in route carries error pages produced by a proxy or gateway in front. REPRODUCE: point the pipeline at a test server which with a body of empty text or HTML, run the API validation finding is recorded while the later unauthenticated. ACCEPTANCE CRITERIA: an unreadable sign-in reply. finding as an unusable one, naming what was attempted to be read; the message never contains any byte of the standing test covers all nine silent shapes plus the top paired mutation that removes the new reporting and already-working shapes must produce byte-identical change cannot disturb the path that already reports.
HXC-268	Bug	Ready for testing	Medium	The model verifier builds web addresses by pasting colon, without the square brackets that IPv6 addresses host is an IPv6 address produces addresses no client operators on IPv6-first hosts, and any deployment with rather than a name. WHY IT IS REACHABLE: the generator with no validation, so an IPv6 value passes straight

ATM ID	Type	Status	Severity	Description
				MANIFESTS: the emitted address looks like http://::: read because the colons of the address are indistinguishable from the port; the client then fails with a confusing parsing error. A configuration message, sending whoever debugs it to the log, says: PLACES, AND A CORRECTION WORTH RECORDING. The log contains FIFTEEN such build sites, one in each of fifteen files. Every one reachable from the single dispatch that sent the message. A revision of this item said three. That was wrong in that the fifteen sites use only three distinct format SHAPES (one plain, one ending in a messages segment), and three upstream reports were recorded as if they were the same. The places. Had the earlier figure stood, the acceptance test with twelve sites still broken. HOW TO REPRODUCE: run the submodule, count occurrences of the formatting pattern in the file; it reports fifteen, while listing the distinct patterns as three. FIX DIRECTION: do not hand-bracket fifteen places. The submodule is introducing a shared endpoint helper that does not correctly using the standard library join, including the YET part of any committed state of the submodule, and nobody should expect to find it there today. Once it is fixed, it, which fixes them uniformly and prevents a sixteen-site problem. Coordinate with that work before starting. SCOPE: The capability-config generator is not the whole surface of the problem. It appears in at least nine further files elsewhere in the code, in agent config writers and two unrelated subsystems. The fix is deliberately, but a fixer should know the capability-config problem. ACCEPTANCE CRITERIA: all fifteen sites produce properly bracketed addresses for IPv6 literals. The addresses are unchanged; an already-bracketed value is not bracketed. The IPv6 literal, already-bracketed, IPv4 and hostnames are unchanged. A mutation that removes the bracketing and makes the addresses unbracketed sites in that file is zero, verified by the test. Fifteen.
HXC-272	Bug	Queued	High	Two automated checks that start in the same second and append to the same running log, so each is judged parallel. HAPPENS: each run names its results folder after the first second, with nothing added to make it unique, and the outcome lines in that shared log to decide the overall result. BOTH WAYS, AND THE SECOND DIRECTION IS THE SAME. The lines flip a healthy run red, which wastes investigation. The flip a run that achieved nothing into a reported success. A success vector sitting in shared infrastructure that

ATM ID	Type	Status	Severity	Description
				uses, which places it in the same class as a check that is OBSERVED: a guard's positive case passed alone and neighbour's failures; and two back-to-back runs later attempt, with the second run's results file reporting plus the first run's four. A SECOND, RELATED DEFECT: the pointer meant to indicate the most recent run never because the command used to update it follows the and drops its contents inside the first run's folder; the folder's timestamp, so ordering the folders by recency. Measured live: the pointer still names the first run runs existing beside it, with those later runs' pointer the by-recency listing therefore silently return stale reviewers into reading an old run as current. HOW IT MANIFESTS: within the same second and observe they share a folder one's verdict counting the first one's outcomes; separately the recent-run pointer still names the first. ACCEPTANCE CRITERIA: share a results folder or log; the recent-run pointer names the recent run; a test starts two runs in the same second independent in BOTH directions, proven real by a paired naming and makes the test fail.
HXC-273	Bug	Queued	Medium	Several health checks treat any reply from a service that say the requested thing does not exist. WHAT HAPPENS: address but do not ask the fetching tool to treat unsuccessful found reply is indistinguishable from a healthy one places — two in the shared checking framework and HOW IT MANIFESTS: a service that is running but listening on the right port with the wrong application entirely. shape as a check that cannot fail: it consumes a slot but almost nothing. RELATIONSHIP TO OTHER WORK: defects closed recently where a check confirmed that the RIGHT thing answered; the remedy there was a service could produce. WHO IS AFFECTED: anyone in a half-broken deployment before it reaches manual health check at a server that returns a not-found status; the check passes. ACCEPTANCE CRITERIA: all three site practical the check asserts something only the internet; merely a successful status; and a test points each check and asserts it fails, proven real by a paired mutation test behaviour and makes the test fail.
HXC-274	Bug	Queued	Medium	Starting the remote-call server makes real outbound provider APIs before it finishes starting, using what is in the environment. WHAT HAPPENS: start-up builds

ATM ID	Type	Status	Severity	Description
				automatic discovery; a flag passed there disables V. providers but does not disable discovery itself, so the provider whose credential it finds and enumerates across SEVEN providers in a single start-up, driven by host shell rather than supplied to the process: fifty twice, because two different credential names both eight, six, five, three and two from the rest. WHY THE local server does not expect it to contact external servers serving anything; in a sandboxed or air-gapped environment delay start-up; and the credentials used are whatever operator deliberately supplied. IT ALSO CAUSES A S why the server accepts connections into the operation seconds before it actually begins serving them, which server was not speaking the expected protocol on a IMPORTANT NOTE FOR WHOEVER FIXES THIS: reach a wrong conclusion. The flag that disables verification of outbound behaviour, and the catalogue fetches happens discovery routine, so an investigation that stopped outbound traffic and returned a refutation. Only the case where the source and the behaviour genuinely evidence for any claim about it. ACCEPTANCE CRIT calls unless explicitly asked to, discovery is opt-in or are taken from deliberate configuration rather than begins serving promptly after it begins accepting; a present and asserts no outbound calls occur, proven restores eager discovery and makes the test fail.
HXC-275	Bug	Queued	Medium	The automated check that confirms our own remote answering has two decision branches that no test ever either one would not be noticed. WHAT IS NOT COVERED test asks the service a deliberately invalid question refusal code AND the service's own wording of the proves the real service answered rather than any peer guard now pins that the two demands stay joined, but runtime, because doing so needs a stand-in service wording, plus a second path for hosts that have the deliberately cautious fallback branch for a peer that in wording we do not recognise; peers built on other differently and land exactly there, yet no test ever covers the two branches that decide whether a half-brokered as ours, which is the failure this whole check exists relying on the automated gate to notice a wrong or testing begins. CORRECTION TO AN EARLIER RECORD

ATM ID	Type	Status	Severity	Description
				logged as unguarded — that the two failure messages. Measurement shows a full swap IS caught, because change to the not-speaking-the-protocol message also added assertion would close. HOW TO REPRODUCE: it accepts either demand instead of both, and observe separately, point the check at a peer that speaks the refusal wording and observe no test exercises that runtime test drives the invalid-question branch again the same validation as the real one, with an honest the query tool rather than a silent pass; a second test fallback using a peer that answers every request as protocol message gains its own assertion; and each mutation that weakens the branch it covers and makes
HXC-276	Bug	Queued	Medium	The test-bank machinery copies an excerpt of a server diagnostics, and unlike the sibling defect just fixed, bank author writes an expectation about reply content part of the reply is precisely how the author sees world bounded only by a fixed character count, with no alternative, so a bank pointed at a sign-in route or any route that value into a durable report exactly as the received. SIMPLY THE SAME FIX: stripping the excerpt would be for, turning a useful failure message into an unusable in kind — the excerpt should stay, but be filtered so it is masked while ordinary content survives intact. When request executor and one in its structured-assertion helper that folds a decoder's own complaint into a message quotes the input that upset it. WHO IS AFFECTED: a report, since these reports are kept and shared, and an authenticated service. RELATIONSHIP TO OTHER WORK: a mechanical leak in the pipeline's own validation path wanted; the fixer measured these five, judged them deliberately rather than silently — this item recorded. HOW TO REPRODUCE: write a bank whose expectation route returning a recognisable marker in its body, and into the recorded result message. ACCEPTANCE CRITERIA: ordinary content so the diagnostic stays useful; validate before the excerpt is recorded; the decoder-complaint rather than quoting input; and a standing test proving a credential-shaped marker never appears, while an unproven real by a paired mutation that restores the message fail, and one that strips the excerpt entirely and makes
HXC-277	Task	Queued	High	

ATM ID	Type	Status	Severity	Description
				The document that tells a newly-started session what has been updated since the twenty-eighth of July, while the commits have changed the very state it describes. We have no agreed authority on what is finished, what is in progress, or our own governing rules class an out-of-date copy as a liability — that reports success for something broken — because it gives an answer that is wrong. WHAT GOES WRONG IN PRACTICE: the work from it plans against a fortnight-old picture, not the current completion for items that moved on, or misses a block that has DRIFTED: the rule requires the record to advance in time, but it moves the project's state, but the burn-down has been updated by whose commits land in other repositories, so the history is lost. WHO IS AFFECTED: every future session, and anyone who reads more than reading the commit history themselves. RELATIONSHIP: a companion handoff document at the repository root, which shows the current picture, so the immediate risk of a lost session is reduced by restoring the longer-lived record and, more importantly, by keeping it current. HOW TO REPRODUCE: compare the date of the record against the dates of the commits made since, and if the record is brought level with the current state, it is correct; if left in progress across the gap; the discipline is made more rigorous so that a state-advancing commit which leaves the record out of date automatically rather than noticed weeks later; and the risk of making such a commit and confirming it is refused.
HXC-279	Bug	Queued	Medium	The check that confirms our remote-call service is good, and a solid guard over HOW its decisive test is composed of conditions that hold — but nothing guards what happens AFTER the test. The distinct promises are unprotected. THE FIRST IS POOR: the composition exactly as the guard requires, inverting the whole condition, so a pass is recorded precisely when the condition leaves the condition untouched and simply exchanges it beneath it, with the same inverting effect. THE SECOND IS widening this item's scope: an edit can make the whole condition recorded at all — the condition remains a clean composition guard perfectly, while the check silently fails. THE EXISTING GUARD CANNOT COVER EITHER: these are about how the question is asked; these two are about whether it is written down the right way round. Stripping them would blur what any of them certifies, and revealing what produced four rounds of chasing its edges. While the four live-execution arms all reach their verdict, the one that would reach it deliberately removes it.

ATM ID	Type	Status	Severity	Description
				so none of them ever observes the recorded result. the automated gate to notice a wrong, foreign or ha begins — an inverted check reports every healthy s broken one as healthy, while a dead check reports n HOW THESE WERE FOUND: while verifying unrela single edit could still defeat the test; the answer for rather than a failed search, but asking the question asking again surfaced reachability. All three edits w package with the query tool present, and nothing c REPRODUCE: negate the decisive condition as a wh statements beneath it, or make the statement unrea observe every check still passing. ACCEPTANCE CRI statement is genuinely REACHED and that the passi taken when the condition holds, with the failing ve condition, exchanging the branches, or killing reac real by paired mutations performing each of those the guard fail; and the existing composition guard l absorbing this one.
HXC-280	Bug	Queued	High	Seven places where we build a network address for defect a sibling item has just repaired everywhere o the repair would make them worse rather than bet for a modern-style numeric host must wrap that ho appended, or every reader sees a different host and NOT FIT: the shared builder brackets correctly, but substitutes a default host of our own while KEEPIN right for the many places addressing our own agen address a search database, a log-analysis service, a and a message broker: a misconfigured outside add machine on the right port — a connection that may which is worse than one that fails. THE SEVENTH S by searching for one way of writing an address; the appending with a small local number-to-text helper could see it. CORRECTION TO AN EARLIER VERSION seventh site sits in a part of the codebase that cann therefore must call the underlying routine directly. parts of the codebase are already wired together an import each other today, and a compile check confi reason the shared builder does not fit is the one tha user name, a password and a trailing path segment composes. Whoever takes this item should therefor shared helper on the real facts rather than inheriti MORE SERIOUS SECOND FACT about that site: it als

ATM ID	Type	Status	Severity	Description
				without escaping it, so any password containing a c will either corrupt the address or place secret mate displayed. That is a credential-handling concern in same pass. WHO IS AFFECTED: any deployment cor modern-style numeric address, or with a password ACCEPTANCE CRITERIA: a defaults-free way of buil by extending the shared helper or otherwise, decid difference from the substituting builder stated whe placed in an address are escaped; each of the sever justified per site; an unusable host produces an exp substitution; and a standing test proves every direc paired mutation restoring the old concatenation, or and one removing the escaping.
HXC-281	Bug	Queued	Low	One of our streaming tests examines the pieces of a them carries a fabricated confidence figure — but t empty, so the check has never actually examined a the server it exercises could not reach any provider single piece; the test therefore looped over nothing unrelated to what it claims to verify. WHY THIS IS V LATER: a sibling item has just repaired that server, real pieces to examine, and the check it was written first time. WHAT IT WAS MEANT TO CATCH: a strea number the underlying provider never supplied — way to distinguish from a genuine measurement. V streamed replies, and anyone reading this test as ev since it currently provides no such evidence. RELAT while repairing the server, and deliberately left alo unrelated test inside a critical fix would have obscu REPRODUCE: examine the list the test iterates over alternatively, break the property the test claims to p ACCEPTANCE CRITERIA: the test drives the repaired streams more than one piece, so the list it examines real pieces; and it is proven real by a paired mutati fabricated confidence figure and confirms the test t
HXC-282	Bug	Queued	High	Before every commit we sweep the working files fo and-see experiments, and that sweep searches for a experiments are supposed to leave behind. It there whole method was to DELETE something, because WHAT ACTUALLY HAPPENED: an experiment that source file was left un-restored on disk. The sweep reported clean, and the damage was one staging co and published. It was caught only because an indep

ATM ID	Type	Status	Severity	Description
				against a preserved copy rather than searching it for MUCH HERE: the rule that had been deleted was the secret from being written verbatim into records we damage was not a harmless experiment residue — leak that file had just been repaired to prevent, sitting check called clean. WHY IT ESCAPED EVERYTHING it were reported as passing because the passing report of what changed shows the file as modified but says modification is wanted; and the phrase-search sweeper is spotting experiment leftovers. WHO IS AFFECTED experiment has ever been run against, which in practice careful about — the ones with the most guards get WHAT IS NEEDED: the leftover check must compare good version rather than searching it for phrases, so intend is surfaced whatever its shape — added, changed record that known-good version before they begin and the confirmation must be a comparison, not an any experiment that deletes a protective rule, do not observe it report clean. ACCEPTANCE CRITERIA: the un-restored deletion as reliably as it detects an un- records a known-good reference before it starts; re against that reference and the verification is captured proven by a paired test that deletes a protective rule the check refuses the commit.
HXC-283	Bug	Queued	Medium	Where we take an incoming caller's address apart to split it at the LAST colon rather than using the standard BREAKS: a modern-style numeric address is full of square brackets, so splitting at the last colon leaves caller's identity for some requests and not others. This can be counted as several different callers, or several which is precisely what a request limiter must never through by splitting their requests across identities merging them. WHERE: the request-limiting middle key from the remote address. RELATIONSHIP TO OTHER a sibling item that has just repaired thirty-one places but it is the opposite direction — this one takes an address the sibling work touched it and why searches shapes surface it; it was found by a reviewer sweeping from the producing side. WHO IS AFFECTED: any caller reaching address, and anyone relying on request limits to hold from a modern-style numeric address and observe bracket punctuation inconsistently across requests

ATM ID	Type	Status	Severity	Description
				address is taken apart with the standard routine the addresses; one caller yields exactly one identity across standing test proves it for old-style, modern-style, both callers, proven real by a paired mutation restoring the test fails.
HXC-284	Bug	Queued	Medium	The guard that decides whether a host is a usable site is protected by a test suite that does not actually pin the test to be altered and every test still passes. WHY THIS MATTERS: a future edit can silently remove, and one of the three guards is more than merely for tidiness — altering it makes the guard currently rejects, producing a nonsense destination. FOUND: a review deliberately broke each rule in turn. The test suite caught; five alterations survived, of which two cannot change behaviour for any possible input, despite the single-character input space) and three were shown to be wrong on specific input that demonstrates the difference. THE PROBLEM: an address whose zone marker appears twice, which the working guard altered one rejects; an address mixing a plain number and a zone marker, which the working guard cleans and the altered one untouched. A RELATED OBSERVATION FROM THE SAME REVIEW: a trailing zone marker rather than rejecting it, which the working guard repair philosophy the rest of the file follows, and demonstrates the WHO IS AFFECTED: every place that composes an address, and the sibling repair is all fifteen capability sites plus the test suite. EXISTING PROPERTIES OF THE SUITE, not defects in the test suite. ACCEPTANCE CRITERIA: each of the three rules must be demonstrated input, so that altering that rule makes the behaviour is either justified in place or changed to something else. Each new pin is proven real by restoring the alteration.
HXC-285	Bug	Queued	Low	Three separate translation-helper files each carry the same shared translation package lives in a different module, without adding a module dependency. THAT ASSEMBLY: the module dependency is already declared, the shared package is used in the same module import across that boundary. THE ENTRY POINT that builds and runs. WHY A WRONG COMMENT: a comment does not merely describe, it JUSTIFIES — the test suite defines its own local translation helper instead of claiming it is actively holding three duplicate implementations. THE DECISION: deciding whether to consolidate them will read the test suite and leave the duplication alone. HOW IT WAS FOUND: the test suite comment for accuracy traced the module wiring to the test suite.

ATM ID	Type	Status	Severity	Description
				crossable, and found these three making the oppos already misled one earlier briefing about which file anyone reading these three files to decide whether ACCEPTANCE CRITERIA: the comment in each of th of the module wiring; if the duplication is still want that reason replaces the false one rather than the c whether to consolidate onto the shared package is c inheriting a constraint that does not exist.
HXC-286	Bug	Queued	High	A family of four tracked items covers a defect when host and a port together, which breaks for the mod were scoped to one component, and its published c covers that component only. A survey of the neighb CONSUMES the repaired addresses — found roughl defect that no item covers. WHY THIS IS THE STRO the very service kinds one of the four items names what it covers — a search database, a stream proce reads as complete while its own named examples s them is a second, independent copy of a defect alre nobody thought to look at. Another twenty-one are that was already repaired in the first component, s clones. WHO IS AFFECTED: anyone configuring any address, which reaches them as a different address ACCEPTANCE CRITERIA: the true scope of the defec names the components searched rather than assum repaired, deliberately deferred with a written reaso published count states which components it covers partial census for a complete one.
HXC-287	Bug	Queued	High	A test file whose name declares it checks for rate-lim limiting code at all. Instead it constructs its own sm that, so it reports on a thing that does not ship. WH MERELY WASTEFUL: a genuine bypass was found i for, and this file passed throughout — it could not h looking at it. A SECOND, INDEPENDENT WAY IT CA checks respond to an unexpected outcome by print failure, so even against the right code they would r happened. A THIRD: the whole file sits behind a bu test runs. Any one of the three would be enough to named for; it has all three. WHO IS AFFECTED: any concluding that rate-limit bypasses are covered. AC the real shipping rate limiter rather than an imitati than a warning when the outcome is wrong; the file

ATM ID	Type	Status	Severity	Description
				and the whole is proven by reintroducing the real k red.
HXC-288	Task	Queued	High	A recently landed repair states in its own ticket tha documentation written alongside it in the same cha twenty-four repaired plus seven deferred. A direct returns thirty. WHY THE NUMBERS CANNOT SIMPLY touched files its own ticket had explicitly declared inherited the repair for free from an earlier piece o each of the four numbers is measuring a slightly di which. THE ITEM CANNOT CLOSE UNTIL THIS RES require the counting command to be re-run and re because there is no agreed definition of what is bei the same ticket already documents one earlier insta makes a repeat worth treating as a process signal r CRITERIA: one published number, stated together w components it covers; every other published count command recorded so any reader can reproduce th
HXC-289	Bug	Queued	Medium	A shared library used by every automated check in pointer meant to name the most recent run never r has been repaired in the library. Three individual c library for this and each maintain their own copy o defect. WHY THEY WERE LEFT: the repair was deli and these three sit outside it, so extending the chan reviewed piece of work after review. WHAT THE CO specifically, the most-recent-run pointer continues latest, and anyone reading their results by followin which has already misled two readers when the sh IS AFFECTED: anyone investigating the results of th sustained-load, concurrent-load and rate-limit stres of the three either uses the repaired shared library the pointer names the genuinely most recent run in running each twice and confirming the pointer mo
HXC-290	Bug	Queued	Low	When work was published to the hosting service, it default branch carries two hundred twenty-nine kn dependencies: five critical, one hundred one high, o nineteen low. These are published advisories again not defects in code written here. WHY THIS MATTE component being prepared for release with five cri dependency advisories is carrying known, publicly risk into that release, and the count is high enough already reviewed it. WHAT IS NOT YET KNOWN: ho

ATM ID	Type	Status	Severity	Description
				from the paths the product actually uses, which is t exposure and an inherited advisory on an unused c been done and must not be assumed either way. W the agent component. ACCEPTANCE CRITERIA: each for whether the vulnerable path is reachable in our resolved by upgrading or by a documented mitigati such with the reasoning; and the resulting position than left to a dashboard nobody reads. DETERMINA database last modified 2026-08-11, symbol/source n negative was trusted): NOT release-blocking, and th object than its framing implies. The figure has no c repository. Its whole committed footprint is prose – with no command, no query date, no repository na ancestor counted the entire GitHub repository acro npm one hundred eighty-three, pip seventeen, Go t with three of them inside a vendored copy. Zero cri documented that per-manifest counting inflates by alerts are one hundred sixty-nine distinct advisorie agent component this row names is CLEAN across a reachable. The inner application has exactly one re to itself plus the standard library. Three hundred si paths in the build graph; six apply to the pinned ve loaded records reports hundreds, version-filtering one. THE ONE REACHABLE FINDING is a metric-ex the inner application, gated off by default — the co op exporter rather than guessing, so the vulnerable operator explicitly selects it. Exploitation requires c exports to. Fixed by a single minor bump whose sib exactly the target version in the same manifest: a p exporter was advanced and the metric exporter wa runtime advisories are daemon-side; this project in markings are a tool artifact — those advisory recor every reachable symbol in every imported package printed traces are package initializers. The entire s verified two independent ways each with its own p under a renamed module path, so no version of the COVERAGE GAPS, stated rather than implied clean: tree was not scanned because its build needs syste six nested Go manifests inside the agent were not n run, so all non-Go figures are manifest counts rathe FOLLOW-UP is not an upgrade. It is replacing this i

ATM ID	Type	Status	Severity	Description
				measurement — a fresh capture, deduplicated by a the tracker stops carrying a figure no artifact backs
HXC-291	Bug	Queued	High	A guard exists to prove that a particular protocol cl should report failure. It works by taking the check the rest, then running the remainder twice — once failure. The part it discards was recently rewritten, part still depends on into the discarded part. THE R immediately on a missing value, under a setting tha does so SILENTLY because the surrounding loop dis therefore end in failure, which means it reports the guards is healthy or broken. A guard that gives the certifies nothing at all, and it currently looks like a broken instrument. WHY IT WENT UNNOTICED: its failure it is designed to detect, so a reader seeing it subject is broken rather than the guard. HOW IT W against two different versions of a shared library, s ran it with error output restored to find the real ca supplies whatever the kept part needs rather than a demonstrably reports success in one direction and no longer discarded, so a broken instrument can ne subject.
HXC-292	Bug	Queued	High	One component decides who a request came from l colon. For the modern numeric address form the su to the result, so the same caller is recorded under t which path the request arrived by. A SECOND AND SAME PLACE: when the request carries a header cl claim is believed exactly as written, with no list of v make such a claim. Anyone able to send a request c and mint themselves an unlimited number of ident identity here is what everything downstream coun request shape or that a caller can choose freely ma than real. THIS IS A SEPARATE DEFECT FROM THE sibling item repaired the same class of problem in a description actually describes THIS site rather than they are in different components, and only one has published 2026 advisory records the identical punc defeat an access check in another product. ACCEPT taken apart by the standard routine rather than by yields one identity regardless of the path the requer honoured only from intermediaries on an explicit p and each is proven by a test that fails if the old beh

ATM ID	Type	Status	Severity	Description
HXC-293	Bug	Queued	Medium	The web framework this project uses has a setting that says whether servers are allowed to state, on a callers behalf, what they believe. This setting is never configured anywhere in this codebase, so every intermediary and to believe any such claim. THAT IS THE PROBLEM. THE COMPONENT THAT HAS THE PROBLEM TODAY is the web framework, so the permissive default is inherited by the request handling path rather than by one component, and the default is on caller origin will inherit it silently without any indication. WHAT LIMITS THE IMPACT RIGHT NOW: the one component that is is not currently connected to the live request path, so it is a trap laid for whoever connects it. THAT IS PRECISELY WHY IT IS CHEAP — an inherited permissive default cost is hard to notice later. ACCEPTANCE CRITERIA: the permissive default is configured explicitly, with the chosen value written in the test. The test proves a claim from a non-permitted intermediary is not recorded where someone adding a new request path.
HXC-294	Bug	Queued	Low	When an automated check finishes, it seals its results. A cleanup step that runs afterwards then deletes a snapshot of the same folder, which updates the folders last-changed time to be sealed. WHY THAT MATTERS AT ALL: one way of finding folders by last-changed time, and a folder touched by a run. WHEN IT CAN ACTUALLY BITE: only where two runs overlap. This cleanup after the later one has already sealed, so the overlap cannot happen for runs that do not overlap, and it is a helper process. THIS IS PRE-EXISTING AND WAS NOT A REPAIR to the same area — that repair fixed the cron job. This is the remaining same-run version, which is much more likely. Either the housekeeping file lives outside the sealed folder, or the sealing step happens after cleanup rather than before. It to be correct for two deliberately overlapping runs.
HXC-295	Bug	Queued	Low	A code comment explains, in the present tense, that the state is where the pointer to the most recent run never advances. It is repaired. The comment now states as current fact that the state is IT IS NOT SIMPLY DELETED: the advice the comment gives is an announcement in the log rather than by following the pointer. It remains correct, but for a different reason than the one that was. It are still safest resolved from their own announcement. The justification does not. THAT COMBINATION IS THE REASON. The stated reason and finds it no longer applies may remain. It along with the stale explanation. WHO IS AFFECTED? The code checks who reads this comment to decide how to log the state. CRITERIA: the comment describes the repaired state.

ATM ID	Type	Status	Severity	Description
				gives is kept, restated against the reason that still h reader can confirm the history rather than having
HXC-296	Bug	Queued	Low	The project handbook lists the web framework ver version recorded there is older than the version ac and actually compiled into the product. WHY A VEL WORTH CORRECTING: contributors consult it when or behaviour is available to them, and behaviour g versions in areas this project touches, including ho contributor reasoning from the stated version can correct for that version and wrong for the one that needed the exact behaviour of a framework functio assuming, and found the handbook disagreed with CRITERIA: the handbook states the version actually the single place the version is decided; and any oth either corrected or changed to point at the depende
HXC-297	Bug	Queued	Low	The checks that run before each commit build their control tool using its default settings. Under those c characters outside the plain English range comes b characters escaped, rather than as the name itself. I file under that quoted-and-escaped name, does not inspecting it. THE EFFECT IS ALWAYS THE SAME D never wrongly rejected, so nobody is ever blocked precisely why it has survived — it produces no sym checking was one of the ones skipped. WHO IS AFF filenames include accented letters, non-Latin script project with contributors and documentation in mo EXISTING AND SHARED BY ALL FOUR CHECKS rath which is why it was deliberately not folded into the fixing it properly means changing how the file list i IS SMALL: ask the version-control tool not to escap file whose name contains non-English characters is checks exactly as an English-named file would be; a with a problem the checks are meant to catch and c gains a new way to reject a file it should accept.
HXC-298	Bug	Queued	Medium	A second place in the same component works out v by believing a header in which the caller states the written, with no list of which intermediaries are pe falls back to the raw connection address including under a different identity on every connection. WH access-control audit log, which is the record of who caller can both choose the identity recorded agains

ATM ID	Type	Status	Severity	Description
				fragment their own history into unrelated-looking ALREADY-REPAIRED DEFECT, NOT THE SAME ONE same class in a different function of the same comp consumers of its own function and stopped there; n across the component, which is how this one and o was closed. WHO IS AFFECTED: anyone relying on establish who performed an action. ACCEPTANCE C same way as the repaired sibling, including honour permitted intermediaries and choosing the entry a the connection port never forms part of an identity if the old behaviour returns.
HXC-299	Bug	Queued	Medium	A third place in the same component extracts a call connection address at its FIRST colon and keeping v address that happens to work. For the modern num square brackets and is full of colons, it returns a fra and the first group of digits — not an address at all, numbers of unrelated callers. THIS IS WORSE THAN REPAIRED: that one retained surrounding punctua so the identity was at least unique per caller. This o callers collapse onto the same identity — and anyth counts them as one. IT ALSO BELIEVES A CLAIMED list of permitted intermediaries, so a caller may sta FOUND: a review of the sibling repair took the com that the repair itself had not, and found this and or security decision or record keyed on this helpers ov address is taken apart by the standard routine rath modern form survives intact; a claimed-origin head intermediaries; and a test proves two genuinely dif collapse onto one identity.
HXC-300	Bug	Queued	Medium	The shared mechanism for looking up which mode second of which asks an outside third-party catalog does not use that shared mechanism at all: it carrie three-stage logic, with its own separate call to that s PRIVATE COPY MATTERS MORE THAN THE DUPLIC mechanism does not reach it. A sibling repair has j from the shared path at start-up; this copy is untou making them wherever it is reached. WHEN IT IS R operator-triggered refresh, and only when a partic installed on the machine — which it is on the curre reachable here today rather than hypothetical. WH refresh on a machine with that tool present, whose website that no part of our configuration names. H

ATM ID	Type	Status	Severity	Description
				shared path traced every call that reaches the outside through the shared path at all. ACCEPTANCE CRITERIA: the shared mechanism or its private copy is brought up to how we contact outside services reaches every path; proves no path contacts the outside catalogue except as configured.
HXC-301	Bug	Queued	Medium	A component is constructed with a true-or-false setting that controls whether providers are checked over the network and then never read, anywhere, by anything. It has been in the project history. WHY AN UNREAD SETTING IS IN PLACE: the place that constructs this component passes the value without reading that line — including three separate reviews that conclude that start-up network checking is switched on; checking happened regardless, on every start, using the setting. The setting did not merely fail to help, it actively misled. This is the reason the underlying problem was described as an UNDERLYING PROBLEM IS BEING FIXED SEPARATELY: the control that hid it. WHAT MUST NOT HAPPEN: the setting is not without establishing what it was intended to do, per the project — it may represent an intention that was never finalized or abandoned. ACCEPTANCE CRITERIA: the project history shows the setting was meant to control; it is then either connected or removed in its own separate change with the evidence that it is anywhere in that constructor claims to control some part of the system.
HXC-302	Bug	Queued	Medium	A repair stopped the server from making paid outside calls; a guard meant to catch anyone reintroducing them into an empty environment with no credentials present, without any credentialed providers at all — so the four places that the guard only ever observes one of them. WHY THAT IS: the three include the primary path, the loop that handles the environment credential, which is where the original problem was most likely to put it back. PROVEN, NOT SUSPECTED: the guard left the rest alone; the entire guard suite stayed green and correctly caught, which is what makes the gap easy to find. WHO IS AFFECTED: anyone who edits this area later. HOW KNOWN AND SMALL: the test can register a synthetic address points at a local stand-in server with its environment; only path must then record zero arrivals at that server. ACCEPTANCE CRITERIA: each of the four sites, un-gated, the primary path is exercised through a local stand-in server; an outside call is made to prove any of it.

ATM ID	Type	Status	Severity	Description
HXC-303	Bug	Queued	Medium	Providers are ranked by a score out of ten, and up to comes from the capabilities a provider reports. The during start-up. A recent repair stopped that collect paid calls to outside services on every start — but t collect them itself. THE CONSEQUENCE: unless an c first, that portion of every score is now zero, and th it. WHAT IT IS NOT: this is not fabricated data. The actually applied, and every provider is affected equ consistent and the base score dominates. WHAT IT can shift the relative ordering of providers by up to to change which provider is chosen for a multi-pro happened. WHO IS AFFECTED: any automatic selec without a refresh first. ACCEPTANCE CRITERIA: eitl capabilities from the provider it has just contacted refresh is documented where a reader will meet it; whether or not a refresh preceded it, or proves the
HXC-304	Bug	Queued	Low	A repair that stopped paid outside calls at start-up c overstate it. THE FIRST: the code says the start-up p activity of any kind. It performs none to any outsid which is the property that matters and the one the branch still makes a request to a service on the ma command, both of which pre-date the repair and a statement is no third-party and no credentialed act description says roughly forty of forty-five provider blends two different populations. Counted properly constructible from an environment credential mak separately, forty of about fifty provider packages ar BOTH ARE WORTH CORRECTING RATHER THAN LI first claim finds a local request and may conclude t recounts the second finds neither number. A claim wrong teaches readers to distrust the precise ones. statements say what the code does; the local-only si is not surprised by them; and the counts state whic
HXC-305	Bug	Queued	High	Test collections exist in two forms: an older prose f run, and a newer structured form that actually exe whole directory of collections, it silently discards th whose prose namesake is also present. No message from the outside the directory appears fully loaded LARGER PROBLEM: because those runnable collect hundred and twenty-five of their individual checks would report success against any reply whatsoever repaired. Nor did anyone notice that eight of them

ATM ID	Type	Status	Severity	Description
				makes the loader refuse the file outright. Both went files were never executed. THE REPAIR TO THOSE C FIXED. Adding a proper expectation to a check that what the system actually verifies, so this defect det anything at all. There is one path that does reach th the command line bypasses the directory scan — b not. WHO IS AFFECTED: anyone who runs the colle reported total reflects what was checked. ACCEPTA either loads the runnable form in preference to the files it declined and why; the count it reports match test proves a collection with both forms present is g dropped. REVIEW SHARPENING (2026-08-12): an im precise state. As STRUCTURAL checks the affected c test cycle — a companion repair drives every one o executor, so their content can no longer rot unnotic service they remain available only when someone committed pipeline does so: the release testing scri entirely. So the outstanding decision is narrower th collections into a pipeline that consumes their resu framework fixtures rather than release gates.
HXC-306	Bug	Queued	Medium	A repair gave every previously-unasserted check a and nineteen of them that expectation was then pr fails when the answer is wrong and passes when th could not be proven, and the reason is a separate p address contains a placeholder standing in for an i fill in, so the run reports them as skipped before th HONEST RATHER THAN HIDDEN — the repair reco does not claim they were verified — but it leaves r expectations in a state where nobody has ever seen HAS WATCHED FAIL IS NOT YET EVIDENCE, which to serve, so this remainder deserves closing rather IT: the ability to capture an identifier from an earli address, which is already tracked as a known limit these thirty-three begin being exercised with no fu AFFECTED: anyone reading the coverage figure and live. ACCEPTANCE CRITERIA: the runner can carry address; the thirty-three are then proven to fail aga pass against a right one, exactly as the other hund category count returns to zero or is restated with w SHARPENING (2026-08-12): twenty-four of the twen from convention rather than from a direct precede literal precedent disagreed and convention was cor

ATM ID	Type	Status	Severity	Description
				unexercised set. So the checks whose expected answers are exactly the ones nobody has yet watched fail. Nothing is growing either; asserting its size would stop it expanding.
HXC-307	Bug	Queued	Low	A guard runs a fast text-based pre-check before its body. It refuses to proceed whenever the body it scans appears to equal sign, or one of a handful of other constructs that TRIP IT: a message string that happens to contain several parameters, a here-document body, a pattern in a body of a program written in another small language, a command that creates nothing lasting, a comparison against a value that is reading input appearing anywhere in any string. We went in the direction — a refusal, never a wrongly-cheerful pass. The code today contains none of the nine, so the shipped code is safe for whoever next edits that subject, not a live fault. The guard the guard now has a runtime check that catches even the ones to catch, and catches it correctly, so the pre-check is now an early warning whose cost is now the only thing it costs. THE RECOMMENDED SHAPE OF THE FIX, from the review, is to harness actually supplied each expected value is still the original problem before anything runs and names the guard that refuses on unrecognised constructs carries the cost of the remaining benefit, and narrowing or removing it is the cost. CRITERIA: none of the nine harmless shapes causes a failure, a genuinely missing value before the run; and a test that previously refused.
HXC-308	Task	Queued	Medium	The rule that decides which address a request genuinely belongs to the same component: once on the path that is live to the component connected. The second copy was made deliberately to ensure the first copy cannot be called from where the second copy is. THE LINK BETWEEN THEM: no test loads both, no test loads against each, and nothing compares their answers. THE PROBLEM: other, everything stays green. WHY THAT IS MORE OF A PROBLEM: the SAME setting to decide which intermediaries manage the path that one setting and reasonably expects both paths to be connected, any difference between the two paths is an inconsistency that the setting itself gives no hint of. EITHER COPY: the shared rule can live in a lower-level component downward, which removes the duplication without losing the available when the second copy was made only because the first was frozen at the time. ACCEPTANCE CRITERIA: either test loads both, use, or a test loads both copies and checks them against each other.

ATM ID	Type	Status	Severity	Description
				difference cannot pass unnoticed; and the written report presents the duplication as unavoidable when it was a change.
HXC-309	Bug	Queued	High	Before every commit, a check searches staged file content by deliberate break-it-and-see experiments. It does not search command through a pipe. WHY IT SILENTLY FAILS: the search command stops as soon as it finds a match; and feeding it is then killed by that closure; and because it returns one result, a killed feeder is reported as failure — v. FOUND. On small files the feeder finishes writing before the problem never appears. MEASURED: files of four and sixteen, thirty-two and sixty-four kilobytes and a hundred. POINTED EXAMPLE: the check's own source file is found staged with leftover damage in it, it would pass its own check. RATHER THAN THEORETICAL: this is the check which was an experiment damage before it reaches a commit, and it is exactly the substantial source files most likely to have the damage. IT IS PRE-EXISTING, not introduced by any recent commit or neighbouring checks — one in the direction of wrongness, not allowing. HOW IT WAS FOUND: a review of a related issue, not directly rather than reading the code. ACCEPTANCE: the file inspected correctly; a test proves a file well above the threshold; refused; and the neighbouring checks with the same defect share it. CONTESTED — DO NOT ACT ON THIS ITEM (2026-08-12). Two independent parties reproduced the defect at the threshold; a third could not reproduce it at all. The defect ships — feeding the content with an explicit format string of every size from four kilobytes to one megabyte, eleven different instrument validated by correctly reporting no-match phrases. The two that did reproduce it ran a standard test. NOT YET CONFIRMED: the two shapes differ materially. The format specifier treats that content as a formatting defect, which is both a separate defect and changes the timing of the reproductions used that second shape and the shipped code as filed describes a defect the shipped code does not have. difference itself. RESOLUTION REQUIRED BEFORE COMMIT: reproduction conditions — the precise invocation, the exact which of the two shapes each party used. Then either party genuinely reproduces, or close it as not-a-defect with a test on two measurements was reasonable; leaving it up to the user would not be. CONTEST RESOLVED (2026-08-13) — THE CHECK IS CORRECT, AND THE ITEM STANDS WITH A RESTATEMENT OF THE DEFECT.

ATM ID	Type	Status	Severity	Description
				isolated, each verified directly. FIRST: the failure belongs to the writer, not the external program of the shell. A second, otherwise identical pipeline gave the killed-writer a clean result every time with the external one. The conclusion is the finding rather than retracting it. SECOND, and third, the disagreement: the size at which it begins depends on the host. It holds before a writer blocks. This host holds eight kilobytes, assumed, which is well below the sixty-four kilobyte threshold. The failure needs the writer to block on a full pipe match and exited, so on a host with a larger pipe it would not. Of content — plausibly more than the one megabyte threshold reached, which explains a clean result there without the threshold. THRESHOLD IS NOW PINNED EXACTLY on this host at two thousand two hundred and eighty-eight bytes always. A hundred and above never does. Deterministic, not nondeterministic — validated as required — content genuinely free of the threshold at every size from four kilobytes to one megabyte. That is, 70 KILOBYTES; that was directionally right and quantitatively correct. A universal figure when it is host-dependent. RESTATEMENT: any size is inspected correctly regardless of how many times it depends on the writer being either the built-in or the external. Above the threshold with a planted phrase is refused. The test is against; and the two neighbouring checks sharing the threshold share it. WORTH RECORDING FOR THE NEXT INVESTIGATION: to reproduce it initially also could not because an internal reader command, and that shadow does NOT propagate. In the same environment-mismatch class this check own the failure encountered twice in one night from opposite directions. PENDING REVIEW (2026-08-13). A repair round would be required. The mechanism precisely: the searching command is killed by the feeding command is killed by that closure; and the result of the pipeline as one result, the killed feeder is read as NOT. The reader reads the SEARCHER own status rather than the pipe status. That CANNOT ANSWER now refuses the commit instead of the end through a real commit: a thirty-kilobyte file committed. NOT ALLOWED before the change and REFUSED after. The failure IS NOT SETTLED — three measurements now disagree. The failure belongs to the shell built-in form of the writer. It states an external command reproduces it identically. THE FAILURE IS AT ALL: four different writers, forty kilobytes, phrase. The first run reported a correct match. That third probe had not. It may have matched the shipped code path at all, so it does not. It may mean the cause attribution rests on measurements

ATM ID	Type	Status	Severity	Description
				against the SHIPPED invocation. WHATEVER SETTLED SHIPPED CHECK ITSELF, citing its line number, not to-end refusal evidence stands independently of what VERIFIED (2026-08-13): a scan of every commit across — ninety-five commits — found ZERO added lines of phrase. So although this check was failing open for have reached a commit. That scan can only see results works by DELETING code leaves no phrase to find, neighbouring item exists to close. SETTLED (2026-08-13) AND TWO EARLIER CONCLUSIONS RECORDED HERE paragraph in preference to everything above it. IT is earlier “pinned exactly” figures were an artefact of size: at twelve thousand nine hundred and seventy time; at twenty thousand and eighteen it fails open and eighteen it fails open SIXTEEN times out of forty transition band. It also depends on WHERE the phrase fixed thirty-kilobyte file, a phrase early in the file fails the file does not. The governing quantity is how much matching line compared with how much the pipe contains its own apparent threshold, which is why three paragraphs IS NOT SPECIFIC TO THE SHELL BUILT-IN WRITER. This disproved: the same failure was reproduced with two in, all showing the identical killed-writer signature. The conclusion was measuring the race, not the writer. TO REPRODUCE IT WAS WRONG, AND THE REASON IS a single enormous line with no line breaks. The search cannot stop early on one unbroken line — it must reach condition under which the fault cannot occur. Their detecting the thing it was testing for, and its clean re-testing this MUST use content containing line breaks phrase positions, because a single lucky probe has failed. WHAT REMAINS TRUE: the repair is correct and correct commits, with a fresh repository for each version of carrying the phrase was allowed before and refused encoding and very large single-line files continued refused.
HXC-310	Bug	Queued	High	A component exists whose job is to limit how often complete, it is tested, and a genuine bypass in it was connected to the running service. THREE INDEPENDENT single place that assembles the live request path in handling, compression, a concurrency cap, a body-size and not this. The second way the service can be started

ATM ID	Type	Status	Severity	Description
				lives in. No connection to it exists anywhere outside THE REPAIR THAT WAS JUST MADE: the bypass was concern a component no request currently passes through today and the original defect endangered nothing. The should be weighed. A SECOND LAYER MAKES IT WORK setting that decides which intermediaries may speak framework default of believing everyone applies. Can claim a different origin and evade the limit anyway configuring that setting would deliver a limit that does anyone assuming request-rate limiting is in force. If component is either connected to the live request per intermediary setting, or it is recorded plainly and without rate limiting is deliberately not in force; and which state rather than the intended one.
HXC-311	Task	Queued	Medium	A suite of adversarial tests exists which, until today imitation of the real component rather than the component the suite is now genuinely capable of failing. WHAT INVOKED: the only thing requiring it to run before document, which a person marks by hand. Nothing never run, and nothing refuses if it ran and failed. THAN YESTERDAY: while the suite could not fail, its because running it proved nothing either way. Now fail and must-run is the whole of its value — a capability protects exactly as little as one that cannot fail. OUT for a check that BLOCKS a release rather than one that WORTH DECIDING: the same suite is deliberately slow because it is slower and drives real requests — that so the fix is to require it at the release boundary, not AFFECTED: anyone reading a completed checklist as passed. ACCEPTANCE CRITERIA: the release path re not run or has failed; the tick-box either reflects that nobody is asked to vouch by hand for something not refusal by making the suite fail deliberately.
HXC-312	Bug	Queued	Low	The check that inspects every test collection now low level. That is the correct behaviour and it was the problem one narrow weakness: if any file with a collection-level that folder cannot be read as a collection, the inspection that one problem. The other roughly one hundred are examined and nothing says so. WHY IT IS ONLY LOW nobody is told everything is fine when it is not; and in sub-folder the inspection currently reaches holds a filtered out before reading. A file of the right extension

ATM ID	Type	Status	Severity	Description
				an ordinary thing for someone to drop into a folder FIXING RATHER THAN ACCEPTING: the value of the and a single unreadable stray silently reduces its co reach first while still appearing to have run. THE F one more problem to report and carry on, rather th CRITERIA: an unreadable file is reported as its own through every remaining file; the report names bot problems found; and a test proves it by placing a de genuine problem and confirming both are reported
HXC-313	Bug	Queued	High	The rule that works out which address a request ge origin header by asking for it once. The standard li FIRST line of that header when a caller sends it mo header twice: their own forged value first, and the the first and never sees the second. MEASURED: tw first resolved to the forged address. WHY IT DEFEA careful right-to-left walk over the chain, skipping i — and it is applied to the wrong line. All the care g chain the attacker got to choose. THE CORRECT HA header and join them, which is what the standard p defined to mean the same thing as one header with IT APPLIES: this shape was identical in all three pla three have just been consolidated into a single shar than three — which is the clearest argument yet th IS AFFECTED: anything keying on caller identity, in security audit record, wherever the shared rule is r CRITERIA: every line of the header is considered, jo sends the header twice with a forged value first and and the same test proves a single-line header is una
HXC-314	Bug	Queued	Low	The enterprise service defines a handler whose nam make requests. Its body discards the caller identity through untouched, with comments saying a real in it passes through for demonstration purposes. It is handler names are registered and a fourth is consu one is written into the registry and never read again nothing if reached, and it is not reached. WHY IT IS placeholder text of this kind in code that is not a tes rules, and a handler named for a protection that pr leads a reader to believe a protection exists. The en unreachable from any shipped program, which is v but if that service is ever connected, this handler jo AFFECTED: anyone auditing what protections the e CRITERIA: the handler either does what its name sa

ATM ID	Type	Status	Severity	Description
				it is removed with the reasoning recorded per our placeholder or demonstration text remains in code
HXC-315	Bug	Queued	High	When the runner loads cases from a folder, it walks one at a time with no handling for the two-format collection. Both forms of a twin therefore load, and keyed by case identifier, so whichever loads last wins the runnable form first and the descriptive form second wins and the runnable one is discarded. WHY THAT case decides two things. It decides which steps are decided whether a case contains a step that makes a condition that is supposed to PREVENT a result being skipped to passed. When the descriptive form wins an assertion is seen as containing only prose, so nothing result is promoted to a pass it never earned. THAT PROJECT HAS SPENT THIS ENTIRE CYCLE CLOSING not a check that cannot fail, but a check whose failure CONCRETE EXAMPLE WAS MEASURED: a specific a form carries a request step is loaded as description SEPARATE from the folder-loading defect being reported that loader at all, so repairing it does not help here. prefers the runnable form of a twin, or refuses to load asserting step blocks the upgrade; and a test proves change which form wins.
HXC-316	Bug	Queued	Medium	The script that runs this product test collections select that ends in a hyphen. Two collections declare in this product, but their filenames use an underscore position, so the selection never matches them and t ITSELF IS CORRECT AND DELIBERATE: it exists to e consumers, which rely on their own services, and t The defect is that two of OUR OWN collections are c naming inconsistency nobody noticed. WHY IT MAY GENERAL: one of the two was among the collection every check a real expectation. That repair was ma longer pass regardless of the answer — and this col does not reach it. HOW IT WAS FOUND: a review ch belonging to another product were correctly excluded while confirming it noticed these two are incorrect ACCEPTANCE CRITERIA: both collections are named selection matches both spellings; a run proves both prevents a future collection declaring this product
HXC-317	Bug	Queued	Low	

ATM ID	Type	Status	Severity	Description
				The main run path does not use the folder loader the collections through a loader belonging to a different file it finds and lets the last one written win, with n contains pairs of files describing the same cases in Milder here than in the sibling defect, because the carry executable steps at all — so what is lost is des ability to run something. WHY IT IS STILL WORTH folder loader does not reach this path either, so any the main run actually sees will be wrong if they rea loading paths with two different sets of blind spots, is a fact about this system that deserves to be writte ACCEPTANCE CRITERIA: the main run path either s twin files with the same rule; the choice is recorded proves which form of a twin the main run actually
HXC-318	Bug	Queued	High	The only web server the shipped program starts re, them in nothing. The component that serves those protective handlers — one limiting how often a call who did what, one setting protective response head one cleaning outgoing content. NONE of the five is a reference anywhere in the codebase at all, not even in a neighbouring package has no caller whatsoever limiter cannot be reached even in principle. WHY T tests for these handlers construct each one directly one of them passes. A reader looking at the test res reader looking at the request path finds none of the about the mechanisms — it is silent about whether anywhere reports that gap. HOW THE PATTERN WA during one cycle, each judged serious on its shape, that never runs — an entire enterprise service with a request limiter attached to no route, a record of v behind it, a limiter that is a placeholder, and now th lower severity as the evidence arrived. The sixth in errors but one architectural fact. WHY IT MATTERS statement about this system is not that its vulnerab were never reachable, AND that the protections a r force are not applied to any request. Both halves ne because the second half is what an operator would CRITERIA: every defined protective handler is either recorded plainly as deliberately not applied, with th it; a test asserts which protections a real request ac one without applying it can no longer pass unnotic resulting position rather than leaving it to be infer

ATM ID	Type	Status	Severity	Description
HXC-319	Bug	Queued	High	One helper composes the address for every service; it does so by joining the host and the port with a colon. This helper has been repairing elsewhere, but this instance of the nine just fixed. WHY IT IS MORE CONSEQUENT: it was fixed twice, by the service-discovery path and by the head of the path across roughly eighteen configured services, each of which had a configuration file with an environment-variable over the modern numeric form at any of them. Several of the configuration files with the documentation stating plainly that start-up requires a single operator setting the modern form on a required environment variable, starting, with an error that points at the service rather than the path for it. AND THE HALVES OF ONE PATH NOW DISAGREE: the path settings from this very configuration package, was the path of the helper, which serves the same package, was not. Two paths compose addresses by different rules — which is exactly what was trying to eliminate. HOW IT WAS FOUND: a review of the work itself had not, and ranked this above everything else. CRITERIA: this helper composes addresses through the path of sites use; a test proves a required service configuration is reachable rather than fatal at start-up; and a check of the package composing addresses differently from another package.
HXC-320	Bug	Queued	High	The set-up path for the message broker builds a connection with an account name and password, and when that path fails, it returns an error it returns. Any handler that records or forwards the password with it. THIS IS THE SAME CLASS AS THE ONE THAT WAS ALREADY TRACKED as our most serious open item, but it is not a secret committed into a file, but a secret written into a log. something goes wrong — which is precisely when the secret is captured, forwarded and kept. WHAT LIMITS IT TO: it is not before the address is used to connect, so it is not a leak. That makes it lower urgency than a secret already leaked. Alongside the address-composition defect it was found alongside, but it is rather than a failure to connect. HOW IT WAS FOUND: a review of the composition sites noticed this one carries a credential. CRITERIA: treating it as one more instance of the address defect. access to logs or error reports from a failed broker. The error, log line, or returned message contains the password inside a larger address; a test proves a deliberately constructed address containing neither the password nor anything from the surrounding paths are checked for the same shape and corrected.

ATM ID	Type	Status	Severity	Description
HXC-321	Bug	Queued	High	WHAT THIS IS: when someone signs in to the main machine the sign-in came from and stores that along with the web framework it is built on. That framework allows intermediaries are allowed to tell it “this request came from out of the box the framework trusts EVERY sender address, never changes that setting, so the address it writes is what it is. HOW IT MANIFESTS: a person signing in can add any naming any origin address they like, and the system shows that invented address rather than the real one. An account or permission is needed first — anyone who can write The recorded value is checked for being a well-formed address. Arbitrary text getting stored; the danger is narrowed to a completely legitimate while being entirely chosen by the user. History is what anyone reviewing a security incident would see: “access come from”. If that record can be set by the user, it can merely go missing — it actively misleads, and can be used to impersonate address. Any future feature that reasons about session locations, restricting access by region, throttling requests, or forged input. HOW TO REPRODUCE: start the shipping process carrying a header that states a different origin address than the record. The stored address matches the invented one. HOW IT IS AFFECTED: anyone relying on sign-in records — especially any future origin-based protection built on top of them. The shipping framework is told explicitly which intermediaries are allowed (or none, using the real sender directly). A test proves that a claim from an untrusted sender records the REAL address, and the setting is removed again. RELATED BUT DISTINCT: this is a bug fixed in a different component under HXC-292, and this is a bug in that component in that component own security notes. This is a path, which is why this is filed separately rather than with HXC-318 concern protections not being connected to the component that IS connected but is fed an attacker-chosen value.
HXC-322	Bug	Queued	Medium	WHAT THIS IS: a group of tests in the quality-assurance suite with no direct checks. Each carries a written note explaining what they do. Of them give the same reason: that a special detector exists to catch the specific class of problem they exist to find. The detector is switched on. The command the project uses to run the tests does not switch it on. Switching it on lives in a separate command to be asked for by name. HOW IT MANIFESTS: run the tests and they finish in about eight thousandths of a second and do nothing. Run the separate command and the same tests finish in about eight thousandths of a second and the detector really is working. Both report success to the user.

ATM ID	Type	Status	Severity	Description
				find. The difference is invisible in the result and visible in the command. MATTERS: these four tests exist specifically to catch the case where several things happen at once — the kind that surfaces only when you try to diagnose after the fact. Someone who introduces a new test command will be told everything passes. The protection is for the people actually use, which is worse than having no protection. A failing result is mistaken for coverage. A SECOND, RELATED TEST is filed separately: about twenty-three further tests exist, but they are justifying themselves on the grounds that the code is correct. Their own standards say plainly that nothing failing is not a failure. Unlike the four above, these have no detector that can be turned on to enable. They may still have modest value as coarse-grained checks, but they are counted as coverage, and whether they stay as they are or are removed is a defect to repair. FOR COMPARISON: the two sibling tests exist in their ordinary test command. The quality-assurance test command is optional, which is most likely an oversight rather than a feature. To run the ordinary test command against the affected code, you must run the detector-enabled command and note it is not a failure. There is written justification on each of the four tests names. AFFECTED: anyone relying on the ordinary test command as evidence of work, and anyone reading a passing result as evidence of work. ACCEPTANCE CRITERIA: either the ordinary test command or the four tests packages, or the four tests state plainly that they are correct. The command and something mechanically prevents the test from failing otherwise. A check proves the four are actually executed. The project treats as its standard, and that check fails if it fails.
HXC-323	Bug	Queued	Low	WHAT THIS IS: an operator can list which upstream machine a request really came from somewhere else”. If an entry in the upstream system cannot understand, it logs a warning so the entry does not match. There is one address form — the kind used in the upstream link, which carries a trailing interface name — that is not used. Such an entry is correctly ignored, which is the safe behavior. To emit the warning sits AFTER an earlier check that the entry is an address form, so for this one case the warning never occurs. THE WORST ONE TO BE SILENT ABOUT: a directly-ignored entry in which an operator would write an entry of this kind. This always fails is also the single form that produces no warning. “the upstream machine I explicitly listed is being ignored because it is not configured anything” — which is precisely the configuration error. HOW IT MANIFESTS: configure an allowed-upstream machine. Send a request from that machine carrying a claimed origin. The request is ignored (correct) and that no warning of any kind is emitted.

ATM ID	Type	Status	Severity	Description
				ONLY LOW SEVERITY: the behaviour is safe. It refuses to trust, so nothing is exposed. What is lost is the diagnostic that was established that this ordering is INHERITED — the original ordering of consolidation had exactly the same sequence — so the bug was not introduced, and it was deliberately left out of that change. THE FIX IS SMALL: the warning depends only on the permission of the machine is calling, so it can be emitted before the commit. THE COST IS ONE INEXPENSIVE READ PER DECISION, AND THE EFFECT IS THAT SUPPRESSION STILL PREVENTS LOG SPAM. WHO IS AFFECTED? THE DIRECTLY-ATTACHED LOCAL-NETWORK PROXY, WHO WOULD OTHERWISE BE A SILENT NON-MATCH. ACCEPTANCE CRITERIA: the warning is emitted in this form, proven by a test that captures the log output and that still refused trust, so improving the diagnostic has no effect.
HXC-324	Bug	Ready for testing	Medium	WHAT THIS IS: before every commit, a check decides whether an exemption reserved for captured-evidence files. To do this, the control system for the file record, then reads the FILENAME and checks that the question it asks is interpreted as a PATTERN. The question contains characters that happen to be pattern syntax, but it is not a pattern — the question can match SEVERAL files, and the answer is the first line then describes a DIFFERENT file than the one that was asked. PROVEN: a file literally named with a question mark was used as an unrelated decoy that sorts ahead of it. The check was wrong, and the wrong permission for the file it was actually asked for was confirmed directly: one such query returned two results. IT MATTERS: this is one of the checks that stops left over from the old commit. The exemption exists so genuinely captured evidence can be made on a neighbouring file, a file that is not captured through on the strength of a different file entirely — the question is in the direction, which is the worse of the two. REACHABLE: the bug is REACHABLE SHOULD NOT BE ASSUMED: this needs a filename check to be made on the evidence directory. Nothing in the project is known to require deliberate action rather than arising by accident. The bug reflects that it is a permissive failure in a protective check that can be triggered in normal use. Several items this session were found to be a defect and later found to sit in paths that never run, but the bug was stated rather than discovered later. RELATED BUT DIFFERENT: I replaced a check that looked at the working copy in the file, but this is a different mistake in the same file — asking a question about the wrong file — and it survived that repair. HOW TO REPAIR: the file contains a question mark inside the evidence directory, and the check that sorts before it, and observe that the permission is not its real permission. ACCEPTANCE CRITERIA: the local file is not captured.

ATM ID	Type	Status	Severity	Description
				rather than by pattern, so it can never describe a n character filename beside a decoy and proves the c if the lookup reverts to the pattern form. CONFIRM (2026-08-13), AND IT IS WORSE THAN FILED IN TH UNKNOWN HAZARD, IT IS A DOCUMENTED ONE A lines further down, the SAME FILE explains why a an exact-object lookup instead of the pattern form: characters could otherwise fail to match and re-ope here does precisely what that comment warns again edge case to a known hazard left unguarded in one SECOND — THERE IS A SECOND SYMPTOM, IN THE report covered the permissive failure: a file that sh on a neighbour record. The reverse also happens — ordinary kind that should qualify, can be DENIED t because the neighbour whose record is read is an e opposite polarity: one lets the wrong thing through second is a usability failure on exactly the captured require us to commit. THIRD — THE TRIGGER IS EA DESCRIBED. The neighbouring file does not need to needs to already exist in version control. An ordina added file with a pattern character in its name is su IT IS ALREADY PROVEN. Marking the lookup as a li the permissive failure, and the legitimate exemption the neighbouring test suite still fully passing. SIZIN ESTIMATED: there are currently ZERO tracked files names contain pattern characters, against roughly evidence files. So this cannot be triggered today by still matters is that the check fails in the permissive moment such a name appears, and the evidence di generated names accumulate. Reachability today: l Filing it rather than fixing it inside an unrelated ro
HXC-325	Bug	Queued	Medium	WHAT THIS IS: some test banks exist as two files de of two formats. When both describe the same test, t keep. It picks by counting how many steps in each v — a content-protection check — the two versions ti break keeps the default version. The trouble is that version that was DISCARDED contained an actual c the version that was KEPT contains a step of a kind which is reported as pending rather than run. THE used to genuinely exercise the device now runs not told. The test still appears in the catalogue and still ESCAPES EVERY EXISTING SAFEGUARD: one safegu

ATM ID	Type	Status	Severity	Description
				worse than the one discarded — it compares the runner to the one, and is satisfied. Another safeguard checks that the runner is exactly what happened, correctly. Both are working, but the counting treats a step the runner skips as if it were a step. If genuinely different things are counted as equal. HCC-326 and twelve cases decided this way, two hundred and twelve cases kept version is genuinely the better one and the discarded version is not. This is the single case where the trade goes the other way. A vague note about the counting into a real assertion. The runner is not at some later point. WHY THE FIX WAS DELIBERATE: the correct repair is to rank genuinely-runners by the order of counting them together. That repair is right, but it was not treated as the default for the largest bank in the collection. The bank recorded name, version, and the order its cases were changed and deserves its own review with a before-and-after catalogue, rather than being appended to an unrelated one. MEANWHILE: this specific case is now pinned by name to a repair that falls into the same trap fails immediately and later fails an acceptance test for the repair — when the repair is applied, the acceptance test and its removal must leave everything passing. WHY THE FIX WAS NOT: content-protection test as evidence that the feature was not working. ACCEPTANCE CRITERIA: runnable steps outrank previous steps; two versions of the same test; the content-protection test is a real device command; a before-and-after comparison of the repair case changed unintentionally; and the by-name pinning test is passing.
HXC-326	Bug	Queued	High	WHAT THIS IS: one of the security-repair command-line tools has found a problem it has found. Before doing so it announces the problem. That folder IS created — and nothing is ever done with it. The tool then overwrites each affected source file. ESTABLISHED: the backup folder name is referenced in the message — once where the name is composed, once where the message announcing success. There is no fourth step. Meanwhile the repair step writes modified content to the backup folder. The halves were read directly rather than inferred. WHY THIS IS A PROBLEM: ORDINARY BUG: the danger is not that the backup is not created. IT TOLD it exists. Someone running a repair tool on a system with an announced backup as their way out if the repair goes wrong. The repair is incorrect, or is applied to the wrong file, then the standards require a recoverable copy before any deletion. The shape that rule exists to prevent — with the addition of a backup — actively discourages taking an independent copy first.

ATM ID	Type	Status	Severity	Description
				THE SAME PLACE: if creating that folder fails, the tool is not allowed to modify files anyway. Nothing stops the destructive path if it could not be set up. That is moot while the folder is not created and left in place once the backup is made real. A THIRD OPTION EXISTS: from the current time to the nearest second, so two seconds, to share it. That is a genuine flaw but the least of the tool's flaws. The folder actually holds anything. REACHABILITY, the buildable command in the application tree and is often named in the project manual. It compiles cleanly. Very often anyone runs it, or whether the repair step finishes, the severity here reflects that the destructive path is not a demonstration that it has already caused loss. A command against a tree containing at least one issue: a backup folder is created and remains empty, and the tool is in place. ACCEPTANCE CRITERIA: every file the tool is to backup is in the backup folder before it is touched; failure to create the folder rather than warning and continuing; the folder name is correct and a test proves that after a run the backup folder contains the modified file, failing if the copy step is removed.
HXC-327	Bug	Queued	Low	WHAT THIS IS: addresses for the newer numbering scheme, separated by a percent sign. Because the percent sign is in sequence in web addresses, it has to be escaped when used in the escape for a percent sign itself begins with the character. The ambiguity: when the system sees an interface name with digits, it cannot tell whether the operator wrote a regular name or an already-escaped percent sign followed by a short name. The latter, which silently rewrites the name — an interface name two-five-one becomes one, and so on. The address is not the DIFFERENT interface than the operator configured. FIX: the ambiguity is inherent, not an oversight. Rejecting such input, treating those digits as part of the name — was meant to be stable when fed through the system twice, given a reasonable limit. So there is no version of “escape it correctly” that changes to what the function PROMISES about its input. A change rather than a repair. A THIRD OPTION EXISTS: REJECTED: refuse such input outright, which is what should happen for other ambiguous or malformed host it is given. It would not be narrowed to the ambiguous case — it would also reject the escaped form that operators use routinely. Rejecting such input is the wrong trade, but the reasoning should be clear. IMPORTANT CONSTRAINT ON ANY FIX: a sibling command exists and currently produces byte-identical output for the same input.

ATM ID	Type	Status	Severity	Description
				other would leave two parts of the system quietly d configured address means — which is the exact cla exists to eliminate. Any repair must land in both at rewriting behaviour AND the agreement between t one alone fails loudly rather than silently diverging this needs an interface name that literally begins w index of two hundred and fifty or above, or a name twenty-five-gigabit link. Neither is common, but ne interfaces are named that way in practice. Low pro SEPARATELY RATHER THAN FIXED IN PLACE: it wa correct repair spans two components, and leaving i hundred-line source comment meant it was discove own standards treat work that stays un-wired in th which is why it now carries an identifier. ACCEPTAI on which reading the contract guarantees; both cor together; the test pinning current behaviour is upda proves the two components still agree byte for byte
HXC-328	Bug	Queued	Low	WHAT THIS IS: when two files describe the same se the other aside, and reports which individual cases list of left-out cases to the file that was SET ASIDE — from the file that was KEPT. So the message names the other. HOW IT WAS PROVEN: one particular cas all of one format, and in no file of the other format directly. Yet the system reports that identifier as ex format, which do not contain it anywhere. WHY IT naming individual cases in these messages is so tha component own documentation states plainly that were excluded FROM THAT FILE. Anyone following contain the case they were sent to find, and has no misnamed, or the message is wrong. A diagnostic th than one that says nothing, because it costs the rea misleading. WHAT IS NOT AFFECTED: the catalogu verifies no case is lost combines the lists from every attribution cancels out there and no case actually g not a data-loss fault, which is why it is filed at low s shipped behaviour. WHY NO TEST CAUGHT IT: the set-aside entries for the identifier it expects, rather should belong to. Under that check, an identifier at found. This is the same shape as several other findi something is present somewhere, when the thing th CRITERIA: the list of excluded cases is attached to th from; a test asserts the identifier appears on the CO

ATM ID	Type	Status	Severity	Description
				sibling entry; and the existing test is tightened so that it satisfies it.
HXC-329	Bug	In progress	High	WHAT THIS IS: before every commit, a check reads the staged content directly and inspects each one for tell-tale phrases left behind by earlier experiments. The command that produces that list of files whose filename contains anything outside plain ASCII — a filename with a backslash, a tab — it does not print the name as-is. Instead, it prints the filename with the unusual characters replaced by escape sequences. The check treats the decorated string to the next command as though it were a normal filename. If the file exists, that command fails, and the check treats the failure as a bug. The check then moves on to the next file. The file is never inspected. WHY THIS IS A BUG: files were prepared with byte-identical contents, but the check only looks at them only in their names. The plain-ASCII one was correct. If the accented letter was ALLOWED, the check printed no output. If the accented phrase is present in the resulting commit. WHY THIS IS A BUG: THE REACH IS WIDER THAN THE ONE THAT THE FAMILY: it fails in the PERMISSIVE direction — the check is too strict. The accomplice file, no unusual repository state, and no unusual character in a filename is the entire requirement, and the check is completely ordinary. A closely related fault found elsewhere is that a named neighbouring file to exist and currently cannot be added to the repository; this one can be triggered by anyone. The bug is in its own language. IT ALSO CONTRADICTS A CLAIM THAT THE REASON FOR THE comment written during an earlier repair explains the bug precisely BECAUSE it reads the staged content directly and does a match and re-open a permissive hole”. That sentence is the reasoning to follow. It is wrong: the lookup cannot fail. The check is fooled by the decorated name, and the result is erroneous. The bug is impossible. THE REACH IS WIDER THAN THE ONE THAT THE REACH IS CONSUMED BY a second check that verifies experiments. The bug is and by two earlier classification steps. All of them are correct. Some of them silently mis-handle such files. That second check is a work item exists to build. HOW TO REPRODUCE: stage a file with an accented character and whose contents carry a planted phrase. The check succeeds with no output from the check, and the phrase is committed. Repeat with a plain-ASCII name and observe the commit. WHY THIS IS A BUG: CRITERIA: the file list is read in a form that cannot be read as a readable, separator-delimited form — at every place where the test stages an accented filename carrying a planted phrase. The plain-ASCII controls proving nothing was over-tightened. The false form returns; and the false comment is corrected.
HXC-330	Bug	In progress	High	WHAT THIS IS: before every commit a separate scan of the staged content is committed and refuses the commit if it finds something wrong.

ATM ID	Type	Status	Severity	Description
				password. It builds its own list of those files using a containing an accent, a quotation mark, a backslash marks and replacing the unusual characters with e by that decorated name. No such file exists, the req failure as “skip this one” and moves on. The file is n INFERRED: two files were prepared with the same only in their names. The plain-ASCII one was corre The one with a single accented letter was ALLOWE is present in the resulting commit. WHY THIS IS MO almost identical fault was found the same night in t damage, and repaired. This is the same mechanism is worse — a leaked credential is a release blocker mortem under our own standards, whereas leftover problem. The repair of the sibling explicitly claimed list; this consumer was overlooked, and the claim n list is used. WHY IT WAS NOT CAUGHT: the scanner building logic rather than sharing the one that was accented-filename problem exercise the two checks scanner, so nothing failed when the scanner was le SAME PLACE: when the scanner cannot read a file i report” and continues. A scanner that cannot read t examine it, and those are different outcomes. That so. HOW TO REPRODUCE: place a synthetic access k accented character, stage it, and commit. The comm appears. Repeat with a plain-ASCII name and the co anyone who names a file naturally in a language us — no unusual setup or deliberate action is required builds its file list in the machine-readable, separato names; an unreadable file blocks the commit with a silently; a test places a key in an accented-name file a plain-ASCII control proving nothing was over-tigh decorated form returns.
HXC-331	Bug	Queued	High	A full tracked-tree scan by the project’s own creden across four documentation HTML exports and one pre-fix scanner, so this is pre-existing and was not i It matters because docs/audit/bypass_events.md ro their evidence that the tree is secret-clean; that cita actually runs today. WHAT IT IS: either the tracked strings that were never triaged, or the scanner pro does not cover. Nobody has determined which, and item. WHY IT MATTERS: if any finding is a real cred requiring operator rotation and a post-mortem bef

ATM ID	Type	Status	Severity	Description
				positives, the bypass audit trail still rests on an exit produce, so the audit evidence needs correcting either cited as proof, but which does not actually exit clear TRIAGE: run the scanner in tree mode and list the findings WITHOUT printing the matched value (CON credential into a log or a ticket). Classify each as a real documentation example or pattern definition (allowlist synthetic planted fixture (allowlist by path). All five minutes for the scan: tree mode spawns 16 grep sub WHO BENEFITS: the operator, who currently holds the tooling does not corroborate. EXPECTED OUTCOME allowlist extended with a recorded reason for every to operator rotation; and the bypass_events.md citation genuinely exits as described. INSTRUMENT NOTE: a separately matched only the scanner itself and a pattern contain the patterns as pattern definitions. That is a hypothesis but does not establish it, and is not complete CORRECTION (round 19, measured): the framing the case in two ways, and both are now proven. (1) Only scope claim. Row 1 cites “both FILES verified secret named files, which passes raw argv and was never (2) The repo contains ZERO non-ASCII tracked path tree-mode fail-open could not have manifested here trail and the scanner is caused entirely by the severe defect. The item still stands: a full tracked-tree scan files (four documentation HTML exports plus script the pre-fix scanner produces an identical seven-finding directly, not inferred), and all five files predate 2026-05-16). So row 2 is contradicted by the scan as tree scan takes 645 seconds (10.75 minutes) on this PATTERNS holds 13 entries, not 16; tracked files number (2026-08-13, triage complete): ZERO real credentials findings resolved with affirmative evidence, none listed documentation examples (PEM BEGIN-headers quoted table, with zero base64 body lines anywhere in the header plus a literal ellipsis), and five synthetic fixture planted secret that must be detected, at 43 characters two rendered Go tests asserting a redaction filter find allowlist already documents as intentional fakes; and planted key body is an English sentence describing on the pattern shape, never on a value, shows each and never changed afterwards, so none was ever a ROOT CAUSE: the allowlist lists every markdown source

ATM ID	Type	Status	Severity	Description
				and no entry for the meta-test script. The document is dated 2026-06-10; the allowlist entries were authored 2026-06-10; the sources and never extended the same decision to the meta-test script. Note: the PDF twins are silent for a different reason: they were not allowlisted. They are not covered, merely unrecovered. The moment was reconstructed (scanner blob, allowlist entries, cited push) and re-run: it exits 1, with a clean contrast. The safety half of the path was already false when written. The safety half of the path is corroborated by this triage. Row 1 is NOT implicated. The paths, which returns 0 both today and at its own conclusion, are REMAINING WORK: apply the validated allowlist paths, which deliberately not a wildcard — a wildcard was measured in that directory, while the explicit form still returns 0. To correct the audit-trail sentence. Both are proposed. REVIEW CORRECTION (2026-08-13, independent re-derivation of path and label): the determination of ZERO REAL COUNTER on composition and context, both re-verified independently. The recorded above are however wrong and are retracted. The is FALSE and was never valid. Re-derived by the same path enters in eight commits, the PEM literal in six, the COUNTER apiece. One of the overlooked commits is titled “re-ephemeral generation”, which is exactly the was-tracked. The asserted had never happened. Independently of the path, the established non-realness, because a genuine key counter is (2) The evidence that a file contains zero long based on a probe blind to material embedded inline in code means the file finds 28 runs in that file. All 28 are benign — twenty are file paths — and none sits near the flagged lines. The stated evidence does not. (3) The PDF twins resurfaced. The extraction mangles the dash runs in one document. The recover its single match. SCOPE BOUNDARY: “zero” is about THESE SEVEN FINDINGS, not about the whole document. Roughly ninety allowlist entries suppress entire sub-entries. A line containing certain words is skipped by content. The proof. BOTH PROPOSED CHANGES ARE BLOCKED by the re-statement names a finding count that only today’s path. At the cited revision had no path allowlist at all and the allowlist proposal would permanently blind a line. The content marker achieves the same result with no blind. The export entries are sound and stand as proposed. CC BY-NC-SA. DISCREPANCY EXPLAINED (independent re-derivation of fix commit, with the scanner verified byte-identical at head): the true number is SEVEN findings across

ATM ID	Type	Status	Severity	Description
				correct and needs no reconciliation. The recurring wrong only as a whole-tree claim. Six findings sit in which were remediated by ALLOWLIST ENTRIES. T and was remediated by an IN-CONTENT MARKER c mechanisms — and the control used to verify the fi entries and confirming the findings return, which i no entry to delete. A second contributor stacks on t rather than the index, so a run made after the scrip only six. CORRECTION TO A DETAIL OF THE COMM history must not be rewritten: the sub-classification and five synthetic fixtures does not map to the mea documentation-context findings (the prior triage ta whose body is an ellipsis) and FOUR synthetic fixtu redaction unit-test fixtures, and the gate meta-test p and remains correct. The stale note in the scanner . for is UNCOMMITTED working-tree text, and the ar same change: the audit document states six in the e script for seven total, and names its line. Replacing decomposition is tracked with the scanner stream.
HXC-332	Bug	Queued	Medium	When a documentation source is triaged and added applies only to that one path. Every generated copy future format — still carries the same strings and s notion that one path is a rendering of another. WH traced to exactly this. The allowlist lists every mark globs. The exports were committed 2026-06-10; the 2026-07-11 and covered only sources. Nobody made had no way to travel to the twins. WHY IT MATTER files, so the gap reopens every time documentation triaged example to a document introduces a fresh f — a directory wildcard — was measured to silently directory, which is worse than the problem. HOW I flat list of paths and globs. It has no relationship be two are independent decisions that must be made t WHO BENEFITS: whoever next triages a document. know that the export exists and remember to list it scanner derives twin coverage — a path allowlisted generated forms — so one triage decision covers th file in the same directory still fires. This is a scanne belongs with the scanner work rather than with th not currently fire, but not because they are covered unreadable to the scanner. A future scanner that le whole set again, so binary-skip must not be mistake

ATM ID	Type	Status	Severity	Description
HXC-333	Bug	Queued	Critical	The kubernetes MCP container was built without its directory for something executable, finds nothing, and policy then starts it again, several times a second, instead directly by running the image — the directory the executables. Each attempt lives about 89 microseconds. 291,505 and was climbing by roughly four per second. MATTERS: the service has never been available, so degraded since it was first deployed. Separately, the continuously on a shared host for as long as the container help; only rebuilding the image with its program in relying on that capability, who currently has no sense except a restart counter nobody reads. ACTION TAKEN: the CPU burn, after confirming it belongs to this process its program. The counter froze and held across two containers was already incapable of serving, so nothing. OUTCOME: the image is rebuilt so it contains the program answers a real protocol request, and a check exists without its payload.
HXC-334	Bug	Queued	High	The health check used across the service fleet opens if the connection is accepted. It never sends a request to distinguish a working server from a process that merely fifteen of twenty-nine services do not answer a probe HEALTHY while silent — verified with a positive connection answered correctly through the identical instrument. two requires credentials, so credential-gating cannot. MATTERS: a green health check over a broken service failure this project treats as a critical defect class. A healthy fleet. Separately, twenty-six of the forty-one check at all, so their silence carries no information, nor bad. HOW IT SHOULD WORK: the check should send a well-formed reply, so that a process holding a port WHO BENEFITS: anyone who trusts the health display most common way a service breaks. EXPECTED OUTCOME: genuine round-trip; the fifteen silent services are either broken; and the twenty-six without any check either deliberately unchecked.
HXC-335	Bug	Queued	High	The repository-root helper script is documented as inspect the platform. Run against a host with forty-platform is not created and advises starting it. WHAT deployment described by a different compose file, what status check looks for a container by an exact name documented subcommand does not exist at all and

ATM ID	Type	Status	Severity	Description
				Five subcommands exist but are undocumented, and a stack despite looking like read-only inspection command instructs an operator to use this script. Following it on a healthy system, and three of its commands have side effects. The script also refers throughout to a container tool that doesn't exist because a compatibility shim happens to exist — without requiring the sanctioned runtime. RELATED DOCUMENTATION: a smoke-test address whose port is wrong. The correct address is documented one is held by a different user on this system. The manual probes a foreign service and reports on some information to any operator or agent following the documented procedure. The correct confident wrong answer. EXPECTED OUTCOME: the script should find that actually exists or is marked retired; the documentation should include side effects; the smoke-test address is correct and should match the sanctioned tool.
HXC-336	Bug	Queued	High	Across the service fleet, eighteen entries read a port for a service. Two are outright swapped: one service reads a port for another service. Two are outright swapped: one service reads a port for another service. Another reads a variable named for an unreferenced variable. INVISIBLE TODAY: no configuration file exists, so entry falls back to its own default. The mismatch has no effect. The moment anyone creates that file and sets one value, the entry reads the service they named. WHY IT CANNOT BE FIXED PIVOT: the entry readers has been noticed before and partially worked. The entry reads the variable belonging to the first, so renaming the entry causes a collision between them. The set has to be corrected. The entry collisions resolved together. WHO BENEFITS: whoever creates the entry who currently has no way to discover the mismatch. The entry is watching the wrong thing move. EXPECTED OUTCOME: the entry is named after itself; no two services read the same or write to the same service references a variable belonging to another.
HXC-337	Bug	Queued	High	Nine of twenty-seven services fail for reasons fixed by patching. They cannot be repaired by editing settings; the implementation is broken. BY GROUP: two install a dependency compiled for one environment expecting another — the compiled file is missing because the name the interpreter looks for and the name in the file. Three have no build output at all: one directory is supposed to be a source that the runtime refuses to load, needing a build. Two point their entry at a library file that only defines a function while the real entry sits beside it unused. One ships a binary in a completely different execution environment and cannot be run. One is supposed to speak. One runs a command-line program that prints its own help text and exits successfully. WHY IT WAS IDENTIFIED: the entry's own help text and exits successfully.

ATM ID	Type	Status	Severity	Description
				pattern that tries one installer, falls back to another on failure so the build always reports success. A broken build is the same green build. WHO BENEFITS: everyone relying on the build. WHY IT MATTERS: have been unavailable since first deployment while the build is green. OUTCOME: each image is rebuilt so the program it is built for is a real protocol request; and the build fails loudly without discarding the error.
HXC-338	Bug	Queued	High	Across the tracked deployment there are two hundred and twenty-nine images referencing two hundred twenty-nine distinct image digests. Sixty-six of them float on a moving latest tag in vector databases, the metrics stack and a headless liveness service. Tags that also move. The package surface is the same as the manifests only six have a lockfile beside them, so the build time for the other twenty-four. Three images install in a way that is disabled, and two more install in a way that lets a failure to install a hundred twenty-two Python requirements, fifty-eight of which are entirely unpinned. WHY IT MATTERS: this is why the build lives. A separate analysis established that the language is the one that every one of the critical-severity advisories on the build is unmeasured surface rather than in the compiled code. The build that passed testing and the artifact that ships can do the build and no record of what actually ran. HOW IT SHOULD BE: the build resolves to a digest, so a rebuild produces the same artifact. The manifest has a committed lockfile that installation can use. If an install failure fails the build instead of being swallowed, the build has to answer what was actually deployed, which the build can't do in a repository alone. EXPECTED OUTCOME: image references are documented update mechanism; lockfiles exist and are used; and patterns are removed; and a check fails when a new manifest is introduced.
HXC-339	Task	Queued	Medium	A single source file is the entire reason the project can't build a container-runtime client library. That file has ZERO tests, no ways, each with its own positive control, and confirms the closure of every shipped binary while present in the build. There is no build tag, no feature flag and no configuration. WHY IT MATTERS TWICE OVER. First, it is the only file in the advisories in the dependency graph — unresolvably so. Second, a renamed module path, so no version of the current build. Removing or rewiring the file drops all five. Second, the build's execute path passes a caller-supplied command line, and its file-transfer paths take unvalidated host local paths to a writable mount. None of that is reachable today, pr

ATM ID	Type	Status	Severity	Description
				WHAT MUST NOT HAPPEN: it must not simply be d importers is a lead, not a finding — the project rule history where it was meant to be used and how it b evidence, before any removal. It may be unfinished is intended to be wired then the shell-injection and first, with tests. EXPECTED OUTCOME: a document meant to connect and why it never did; then either citing that history, or the wiring completed with the covered by tests. Either way the dependency require
HXC-340	Bug	Queued	High	The agent service publishes three separate health a — but all three are wired to the exact same piece of ‘the process is alive’ from ‘the process is ready to ta a server can be running perfectly well and still be s answer a request. This matters because load balanc where to send live user traffic based on the readine the HTTP status code rather than the message body 200 (success) even while the body honestly says ‘sta taking roughly seven minutes. For that whole wind is ready and sends it real user requests, which fail. place: once the server has reported itself ready one permanently and never revisited, so if a dependen advertising itself as ready forever. Who benefits fro otherwise hit a failed request during a deployment currently have no reliable signal for when a rollout returns a failure status code whenever the server g separate and always succeeds while the process is a false when a dependency is lost.
HXC-341	Bug	Queued	High	The main server exposes a health endpoint that is s service and everything it depends on are working. database and cache when those are configured, con unreachable. However, when no database is wired skips the entire checking block, then reports succes language-model providers, even though serving mo purpose. The written documentation for this endpo dependencies, which is not true in either respect. T documentation is what an operator reasons from w signal means anything: a deployment missing its da perfectly healthy, and so will one whose model pro benefits: operators and on-call responders who nee an incident, and anyone automating deployment ga the endpoint reports an honest failure when a requ

ATM ID	Type	Status	Severity	Description
				unreachable rather than treating absence as success verdict, and the documentation is corrected to describe
HXC-342	Bug	Queued	Medium	The agent service exposes a health endpoint that always returns a success response. It performs no check whatsoever of the health of the provider, any connection, or any internal state, and returns success, which it could return anything other than success. This is a health check, which means anyone reading the documentation can reasonably assume a green result carries information about the health of the agent. The agent returns exactly the same response as a perfect agent, so that any monitoring, alerting, or automated gate built on top of it will stay green through any outage. This is the least severe problem because a companion endpoint on the same service, which is also health, remains actively misleading while it is labelled a health check. Building monitoring on this service, and any automation built on top of it, is a mistake. Expected outcome: either the endpoint performs a real health check, or it is explicitly relabelled as a liveness-only signal, and the documentation so that nobody mistakes it for a dependency check.
HXC-343	Bug	Queued	High	The project keeps its list of work items in a database. The documents are generated from that database. For fifty-six items, there is a gap between the database record and the document layer. This is a severe and silent: if anyone regenerates the trackers, the gap disappears. The normal supported command, those fifty-six items are regenerated with no warning, no error, and no indication that anything was wrong. They still hold them, but every human-readable view of the trackers shows that anyone reading the trackers would reasonably conclude that nothing had happened yet only because the regeneration has not happened yet. The system does detect and report the problem, which is how it is caught. The fix is: everyone who reads the trackers to understand the state of the system needs to regenerate the documents without first pruning the database. Expected outcome: the missing links are restored for all fifty-six items, gaps, and a regeneration can be run and verified to ensure that every item the database holds.
HXC-344	Task	Queued	Medium	During the security-hook work a file was produced that was an earlier, deliberately-broken version of a script, kept as a test. This version detects the old fault. Two sibling files of exactly the same name show up: each carries a header marking it as an intentional test, and the other as a named test. This third file has neither. Nothing in the code has such a header, so the commit safety check correctly rejects it. From the point of view it is indistinguishable from leftover documentation from an experiment. Two outcomes are possible and the difference is in the baseline whose wiring was never finished, in which

ATM ID	Type	Status	Severity	Description
				and add the header its siblings have; or it is genuine or retired deliberately. Guessing either way is wrong: the checker would make the checker agree with a claim without proof risks discarding real work. The file has been outside the project and removed from the working set while the question is settled. Who benefits: anyone who mean what it says, and whoever next needs that background origin is traced through project history, a decision is made and the file is either restored and properly wired in its own clearly-labelled change.
HXC-345	Bug	Queued	High	Word documents are produced outside the export tool and contain their pictures
HXC-346	Task	Queued	Medium	The password-in-documentation check can be fooled by something