

mr_gate_isolation/ – cross-gate cache isolation (T case , "not others")

Every OTHER scenario under `fixtures/mutation_reuse/` uses a single hardcoded gate id (`GATE-MR-DEMO`) and its own isolated scratch cache directory, so none of them individually proves the "(not others)" half of tasks.md T057's case 1: "changing one gate's input content re-runs THAT gate's mutations (not others)". This directory closes that gap directly: two DIFFERENT gates (`GATE-MR-ISO-A` , `GATE-MR-ISO-B`), each with its own gate script + mutation patch (so their DEC-23 keys are genuinely distinct -- confirmed by the RED test's Section B before any claim is made about the real tool), are `put` into ONE SHARED cache directory. Gate A's observed input is then flipped between `put` and `get` (expect MISS -- its own mutations must re-run); gate B's inputs are left byte-identical in that SAME shared cache directory (expect HIT -- its cached verdict must remain servable, untouched by gate A's change). All four envelope JSON files reuse the SAME real file/patch/script bytes (and their real sha256 sums) as the sibling scenarios in this directory -- see `../gate_script.sh` / `../gate_script_v2.sh` / `../mutation_patch.diff` / `../mutation_patch_v2.diff` / `../observed_input.txt` / `../observed_input_flipped.txt` -- so this scenario is non-vacuous by construction, not by assertion.