EXTENSION_DEVELOPMENT

SpecKit Extension, Superpowers Skill & MCP Server Development Specification

Revision: 2 **Last modified:** 2026-09-22T00:00:00Z

> **ARCHITECTURE AMENDMENT — 2026-09-22 (HXC-159 Phase B3).** Part C of this document ("MCP Server (`superbridge-mcp`)") specifies a server that was never built and does not exist as software — independently re-derived twice (GitHub `total_count: 0`; npm exact-name lookup `HTTP 404`). This document describes the project's OWN proposed FUTURE `helix-nano-bridge` extension (Part A) and its (unbuilt) MCP server companion (Part C) — NOT the real, live Bridge architecture, which is 6 layers with no MCP execution tier; the execution role is filled by Spec Kit + Superpowers + Claude Code's own skill/subagent machinery. See `../README.md#architecture-amendment-2026-09-22` for the finding and the worked proof. Content is retained as historical design intent (§11.4.35/§11.4.124), not a description of shipped software.

Part A: SpecKit Extension (`helix-nano-bridge`)

A.1 Extension Manifest (`extension.yml`)

```yaml
id: helix-nano-bridge
name: "Helix Nano-Bridge"
version: "1.0.0"
description: >
  Decomposes SpecKit task plans into executable nano-tasks with
        TDD enforcement,
```

```
  anti-bluff verification, and hardware-optimized parallel
        execution.

author: "HelixDevelopment"
license: "Apache-2.0"
repository: "https://github.com/vasic-digital/helix-nano-bridge"

specKitVersion: ">=2.0.0"
superpowersVersion: ">=3.1.0"

commands:
  decompose:
    description: "Decompose tasks.md into dependency-ordered nano-
        tasks"
    file: "speckit.helix-nano-bridge.decompose.md"
    flags:
      - name: "--granularity"
        type: "string"
        default: "function"
        enum: ["function", "method", "block", "line"]
        description: "Target granularity for nano-task
        decomposition"
      - name: "--max-tasks"
        type: "integer"
        default: 512
        description: "Maximum number of nano-tasks to generate"
      - name: "--parallelism"
        type: "integer"
        default: 0
        description: "Max parallel nano-tasks (0 = auto-detect
        from hardware)"

  execute:
    description: "Execute nano-tasks with TDD enforcement and
        anti-bluff verification"
    file: "speckit.helix-nano-bridge.execute.md"
    flags:
      - name: "--phase"
        type: "string"
        description: "Execute only tasks in this phase"
      - name: "--retry-failed"
        type: "boolean"
        default: false
        description: "Retry previously failed tasks before new
        ones"
      - name: "--timeout"
        type: "integer"
        default: 3600
        description: "Per-task timeout in seconds"
      - name: "--gpu-offload"
        type: "boolean"
        default: true
        description: "Use GPU for inference when available"
```

```yaml
graph:
  description: "Generate and visualize the nano-task dependency
      graph"
  file: "speckit.helix-nano-bridge.graph.md"
  flags:
    - name: "--format"
      type: "string"
      default: "mermaid"
      enum: ["mermaid", "dot", "json", "svg", "png"]
      description: "Output format for the dependency graph"
    - name: "--highlight"
      type: "string"
      description: "Comma-separated task IDs to highlight"
    - name: "--critical-path"
      type: "boolean"
      default: false
      description: "Show only the critical path"

status:
  description: "Show execution status of all nano-tasks with
      evidence links"
  file: "speckit.helix-nano-bridge.status.md"
  flags:
    - name: "--format"
      type: "string"
      default: "table"
      enum: ["table", "json", "summary", "report"]
      description: "Output format"
    - name: "--filter"
      type: "string"
      default: "all"
      enum: ["all", "pending", "running", "passed", "failed",
      "skipped"]
      description: "Filter tasks by status"
    - name: "--evidence"
      type: "boolean"
      default: false
      description: "Include evidence artifact paths in output"

retry:
  description: "Retry failed nano-tasks with optional parameter
      tuning"
  file: "speckit.helix-nano-bridge.retry.md"
  flags:
    - name: "--task-ids"
      type: "string"
      description: "Comma-separated task IDs to retry (default:
      all failed)"
    - name: "--max-attempts"
      type: "integer"
      default: 3
      description: "Maximum retry attempts per task"
```

```yaml
      - name: "--strategy"
        type: "string"
        default: "sequential"
        enum: ["sequential", "parallel", "dependency-chain"]
        description: "Retry strategy"

hooks:
  after_tasks:
    - command: "decompose"
      auto: true
      description: "Auto-decompose tasks.md into nano-tasks after
        task generation"
  before_implement:
    - command: "execute"
      auto: false
      description: "Gate — run execution gate before implement
        phase begins"

config:
  template: |
    # Helix Nano-Bridge Configuration
    # Generated: {{ TIMESTAMP }}

    ## Nano-Task Settings
    granularity: "function"
    max_tasks: 512
    auto_decompose: true

    ## Execution Settings
    tdd_enforcement: "strict"
    anti_bluff_mode: "full"
    per_task_timeout: 3600
    max_retries: 3
    retry_backoff: "exponential"

    ## Hardware Settings
    gpu_offload: true
    cuda_device: 0
    thread_pool_size: 0
    numa_aware: true
    memory_budget_gb: 0

    ## Evidence Settings
    evidence_dir: "{{ PROJECT_ROOT }}/qa-results/nano-tasks"
    capture_artifacts: true
    artifact_format: "md"

    ## Integration
    superb_bridge: true
    mcp_server_enabled: true
    mcp_port: 9595
```

```
    ## LLM Settings
    model: "helix-nano"
    fallback_model: "deepseek-v4-pro"
    temperature: 0.0
    max_tokens: 32768

dependencies:
  runtime:
    - "superbridge-mcp"
    - "superb"
  development:
    - "typescript"
    - "node >=18"
    - "ripgrep"
    - "graphviz"
    - "jq"
```

A.2 Command Markdown Files

speckit.helix-nano-bridge.decompose.md

```
# Decompose — tasks.md → Nano-Tasks

## Purpose
Reads the current SpecKit `tasks.md`, analyzes each task for
        implementation
surface, and decomposes it into a dependency-ordered list of
        atomic nano-tasks.

## Prerequisites
- `tasks.md` present at `{{ SPECS_DIR }}/{{ FEATURE }}/tasks.md`
- `plan.md` present for design context
- `spec.md` present for acceptance criteria
- Constitution loaded for anti-bluff rules

## Input
| Parameter | Type | Required | Default | Description |
|-----------|------|----------|---------|-------------|
| tasks_path | string | no | tasks.md | Path to tasks file |
| granularity | string | no | function | Decomposition depth |
| max_tasks | integer | no | 512 | Upper bound on nano-tasks |
| parallelism | integer | no | 0 | Max parallel (0=auto-detect) |

## Process

1. **Parse tasks.md** — extract all `## Task N: ...` blocks with
        their
   descriptions, acceptance criteria, and dependencies.
2. **Analyze each task** — resolve against `plan.md` design
        artifacts:
   - What files need creation/modification
```

```
   - What functions/methods/classes are involved
   - What imports/dependencies must exist
   - What tests must pass (RED phase)
3. **Generate diff-map** — for each task, produce the exact diff
       of changes
   required, decomposed into atomic units.
4. **Build dependency DAG** — construct a directed acyclic graph
       where each
   nano-task depends on its prerequisites (file existence,
       function signature,
   test setup, etc.).
5. **Assign phases** — group nano-tasks into execution phases
       where all tasks
   within a phase are independent and can run in parallel.
6. **Write nano-tasks** — emit `nano-tasks.json` with the full
       decomposition.

## Output
```json
{
  "meta": {
    "source": "tasks.md",
    "granularity": "function",
    "generated": "2026-07-24T00:00:00Z",
    "total_tasks": 42,
    "phases": 5,
    "critical_path_length": 12
  },
  "tasks": [
    {
      "id": "N001",
      "parent_task": "T1",
      "phase": 1,
      "description": "Create src/auth/login.ts with empty
        exports",
      "file": "src/auth/login.ts",
      "action": "CREATE",
      "imports": [],
      "symbols": ["login", "logout", "refreshToken"],
      "dependencies": [],
      "test_id": "N001_RED",
      "estimated_tokens": 400,
      "estimated_duration_s": 15
    }
  ],
  "graph": {
    "nodes": ["N001", "N002"],
    "edges": [["N001", "N003"]],
    "phases": [
      ["N001", "N002"],
      ["N003", "N004"]
    ]
```
```

```
  }
}
```

Anti-Bluff

- RED test IDs reference actual test files that MUST exist before execution
- Every nano-task links to at least one acceptance criterion from spec.md
- Dependency graph is topologically sorted and verified acyclic
- Evidence directory created and writable before decomposition completes

Exit Codes

Code	Meaning
0	Decomposition successful
1	tasks.md not found or unparseable
2	Dependency cycle detected
3	Plan/spec missing required sections
4	Evidence directory unwritable

````
#### `speckit.helix-nano-bridge.execute.md`

```markdown
# Execute — TDD-Driven Nano-Task Execution

## Purpose
Executes nano-tasks phase-by-phase with strict TDD enforcement:
RED (test fails) → GREEN (implementation passes) → VERIFY (anti-
bluff).

## TDD Cycle (per nano-task)

┌──────────────────────────────────────────────────────────┐ │ 1. RED
— Write/run failing test │ │ 2. RECORD — Capture failure evidence │ │
3. GREEN — Write minimal implementation │ │ 4. RECORD — Capture
pass evidence │ │ 5. VERIFY — Anti-bluff oracle confirms real │ │ 6.
REPEAT — Next nano-task (if dep's met) │
└──────────────────────────────────────────────────────────┘
````
````

```
## Execution Gate
Before ANY implementation code is written, the gate asserts:
1. `RED_MODE=1` test exists for every nano-task in the current
phase
2. Every RED test FAILs (exit ≠ 0) on the clean artifact
3. Evidence directory exists and is writable
4. No stale `/data/app` shadow on target (if on-device)
5. Runtime signature registry is loaded

## Phase Execution
Phases are executed sequentially. Within a phase, independent
nano-tasks
(those with all dependencies satisfied AND no shared-file
conflicts) run
in parallel up to `parallelism` limit.

## Evidence Capture
Every nano-task execution produces:
- `qa-results/nano-tasks/<ID>/RED_<timestamp>.log` — pre-fix
failure
- `qa-results/nano-tasks/<ID>/GREEN_<timestamp>.log` — post-fix
pass
- `qa-results/nano-tasks/<ID>/diff.patch` — the actual change
- `qa-results/nano-tasks/<ID>/verdict.json` — anti-bluff verdict

## Exit Codes
| Code | Meaning |
|------|---------|
| 0 | All executed tasks GREEN |
| 1 | One or more tasks FAIL |
| 2 | Pre-execution gate FAIL |
| 3 | Evidence directory unwritable |
| 4 | Timeout on task execution |
```

speckit.helix-nano-bridge.graph.md

```
# Graph — Nano-Task Dependency Visualization

## Purpose
Generates a visual representation of the nano-task dependency DAG
        in
multiple output formats.

## Process
1. Load `nano-tasks.json` from the feature directory
2. Build adjacency list from `graph.edges`
3. Color nodes by status (pending=gray, running=blue,
        passed=green,
   failed=red, skipped=yellow)
4. Highlight critical path if `--critical-path` is set
5. Render in the specified format
```

```
## Mermaid Output
```mermaid
graph TD
  N001["N001: Create auth/login.ts"] --> N003["N003: Implement
        login()"]
  N002["N002: Create auth/types.ts"] --> N003
  N002 --> N004["N004: Implement types"]
  N003 --> N005["N005: Wire login to router"]
  N004 --> N005
  style N001 fill:#90EE90
  style N002 fill:#90EE90
  style N003 fill:#87CEEB
```

JSON Output

```
{
  "graph": {
    "directed": true,
    "nodes": [
      {"id": "N001", "phase": 1, "status": "passed",
        "critical_path": true},
      {"id": "N003", "phase": 2, "status": "running",
        "critical_path": true}
    ],
    "edges": [
      {"from": "N001", "to": "N003"},
      {"from": "N002", "to": "N003"}
    ]
  },
  "critical_path": ["N001", "N003", "N005"],
  "stats": {
    "total": 42,
    "passed": 12,
    "failed": 0,
    "running": 2,
    "pending": 28,
    "skipped": 0
  }
}
```

`speckit.helix-nano-bridge.status.md`

```markdown
# Status — Execution Dashboard

## Purpose
Reports the current status of every nano-task with evidence links
and
summary statistics for use in CI/CD and operator dashboards.
```
```

Summary Output

```
╔═══════════════════════════════════════════════════════════════════════╗ ║
Helix Nano-Bridge Status ║
╠═══════════════════════════════════════════════════════════════════════╣ ║
Total: 42 │ Passed: 12 (28.6%) ║ ║ Failed: 0 │ Running: 2 ( 4.8%) ║ ║
Pending: 28 │ Skipped: 0 ( 0.0%) ║
╠═══════════════════════════════════════════════════════════════════════╣ ║
Phase 1: ████████████████████ 6/6 PASS ║ ║ Phase 2:
████████░░░░░░░░░░░░ 4/12 RUNNING ║ ║ Phase 3:
░░░░░░░░░░░░░░░░░░░░ 0/8 PENDING ║ ║ Phase 4:
░░░░░░░░░░░░░░░░░░░░ 0/10 PENDING ║ ║ Phase 5:
░░░░░░░░░░░░░░░░░░░░ 0/6 PENDING ║
╚═══════════════════════════════════════════════════════════════════════╝
```

JSON Output

```json
{
  "summary": {
    "total": 42,
    "passed": 12,
    "failed": 0,
    "running": 2,
    "pending": 28,
    "skipped": 0,
    "completion_pct": 28.6
  },
  "phases": [
    {"id": 1, "total": 6, "passed": 6, "status": "PASS"},
    {"id": 2, "total": 12, "passed": 4, "running": 2, "status":
"RUNNING"}
  ],
  "tasks": [
    {
      "id": "N001",
      "status": "passed",
      "phase": 1,
      "duration_s": 12.4,
      "attempts": 1,
      "evidence": {
        "red": "qa-results/nano-tasks/N001/
RED_20260724T000000Z.log",
        "green": "qa-results/nano-tasks/N001/
GREEN_20260724T000012Z.log",
        "diff": "qa-results/nano-tasks/N001/diff.patch",
        "verdict": "qa-results/nano-tasks/N001/verdict.json"
      }
    }
```

```
  ]
}
```

Evidence Mode (`--evidence`)

When enabled, every task row includes the full `evidence` object with paths to captured artifacts. The `verdict.json` contains:

```
{
  "task_id": "N001",
  "verdict": "PASS",
  "evidence_class": "source_code",
  "red_exit": 1,
  "green_exit": 0,
  "iterations": 3,
  "artifact_fingerprint": "sha256:abc123...",
  "oracle": "helix-nano-bridge/anti-bluff",
  "timestamp": "2026-07-24T00:00:12Z",
  "witness": "codegraph_explore"
}
```

`speckit.helix-nano-bridge.retry.md`

```markdown
# Retry — Failed Nano-Task Retry Engine

## Purpose
Retries failed nano-tasks with configurable strategy, backoff, and
dependency-chain resolution.

## Retry Strategies

### Sequential
Retries each failed task one at a time, in order of failure
timestamp.

### Parallel
Retries all independent failed tasks simultaneously.

### Dependency-Chain
For each failed task, traces back through its dependency graph to
find the ROOT cause task that failed first, retries that chain
from
the root, then propagates forward.

## Retry Decision Matrix
| Failure Class | Action | Max Attempts |
|---------------|--------|--------------|
| TEST_FAIL | Re-run RED, then GREEN | 3 |
```

TIMEOUT	Increase timeout 2x, retry	2
OOM	Reduce parallelism, retry	2
COMPILE_ERR	Fix dependency, retry chain	3
EVIDENCE_MISSING	Re-run with capture	2
ORACLE_FAIL	Human review, then retry	1

Exit Codes
Code	Meaning
0	All retried tasks now GREEN
1	Some tasks still FAIL after max attempts
2	Dependency chain unresolvable

A.3 Bash Script Implementations

`bin/helix-nano-bridge-decompose`

```bash
#!/usr/bin/env bash
set -euo pipefail

SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
source "${SCRIPT_DIR}/../lib/nano_bridge_common.sh"

GRANULARITY="${1:-function}"
MAX_TASKS="${2:-512}"
PARALLELISM="${3:-0}"
TASKS_PATH="${4:-tasks.md}"
FEATURE_DIR="${5:-$(pwd)}"
EVIDENCE_DIR="${FEATURE_DIR}/qa-results/nano-tasks"

nano_log "INFO" "Decomposing ${TASKS_PATH} at granularity=$
{GRANULARITY}"

[[ -f "${FEATURE_DIR}/${TASKS_PATH}" ]] || {
    nano_log "ERROR" "${TASKS_PATH} not found in ${FEATURE_DIR}"
    exit 1
}

mkdir -p "${EVIDENCE_DIR}" || {
    nano_log "ERROR" "Cannot create evidence dir: ${EVIDENCE_DIR}"
    exit 4
}

nano_log "INFO" "Parsing tasks from ${TASKS_PATH}..."
TASK_COUNT=$(grep -c '^## Task [0-9]' "${FEATURE_DIR}/$
{TASKS_PATH}" || true)
nano_log "INFO" "Found ${TASK_COUNT} tasks"

if [[ "${TASK_COUNT}" -eq 0 ]]; then
    nano_log "ERROR" "No tasks found in ${TASKS_PATH}"
```

```
    exit 1
fi

NANO_ID=1
declare -A FILE_TASKS=()
declare -A SYMBOL_DEPS=()
NANO_TASKS_JSON='{"meta":{"source":"tasks.md","granularity":"'"$
{GRANULARITY}"'","generated":"'"$(date -u +%Y-%m-%dT%H:%M:
%SZ)"'","total_tasks":0,"phases":0,"critical_path_length":0},"tasks
[],"graph":{"nodes":[],"edges":[],"phases":[]}}'

declare -i TASK_NUM=1
while IFS= read -r LINE; do
    if [[ "${LINE}" =~ ^##\ Task\ ([0-9]+):\ (.+) ]]; then
        TASK_NUM="${BASH_REMATCH[1]}"
        TASK_TITLE="${BASH_REMATCH[2]}"
        nano_log "DEBUG" "Processing Task ${TASK_NUM}: $
{TASK_TITLE}"
        nano_decompose_task "${TASK_NUM}" "${TASK_TITLE}" "$
{GRANULARITY}"
    fi
done < "${FEATURE_DIR}/${TASKS_PATH}"

nano_build_dependency_dag
nano_assign_phases
nano_detect_cycles || exit 2

OUTPUT_FILE="${FEATURE_DIR}/nano-tasks.json"
echo "${NANO_TASKS_JSON}" | jq '.' > "${OUTPUT_FILE}"
nano_log "INFO" "Wrote $(jq '.tasks | length' "${OUTPUT_FILE}")
nano-tasks to ${OUTPUT_FILE}"
nano_log "INFO" "Decomposition complete — $(jq '.meta.phases' "$
{OUTPUT_FILE}") phases"
```

bin/helix-nano-bridge-execute

```
#!/usr/bin/env bash
set -euo pipefail

SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
source "${SCRIPT_DIR}/../lib/nano_bridge_common.sh"
source "${SCRIPT_DIR}/../lib/anti_bluff_oracle.sh"

FEATURE_DIR="${1:-$(pwd)}"
PHASE_FILTER="${2:-all}"
RETRY_FAILED="${3:-false}"
TASK_TIMEOUT="${4:-3600}"
GPU_OFFLOAD="${5:-true}"
NANO_FILE="${FEATURE_DIR}/nano-tasks.json"
```

```
[[ -f "${NANO_FILE}" ]] || { nano_log "ERROR"
        "nano-tasks.json not found. Run decompose first."; exit
        1; }
[[ -f "${FEATURE_DIR}/tasks.md" ]] || { nano_log "ERROR"
        "tasks.md not found"; exit 1; }

nano_log "INFO" "=== Pre-Execution Gate ==="
nano_run_pre_execution_gate "${FEATURE_DIR}" || {
    nano_log "ERROR" "Pre-execution gate FAILED"
    exit 2
}
nano_log "INFO" "Pre-execution gate PASSED"

if [[ "${GPU_OFFLOAD}" == "true" ]]; then
    nano_detect_gpu && nano_log "INFO" "GPU detected — offloading
        inference"
fi

TOTAL_PHASES=$(jq '.meta.phases' "${NANO_FILE}")
PASSED=0
FAILED=0

for ((PHASE=1; PHASE<=TOTAL_PHASES; PHASE++)); do
    if [[ "${PHASE_FILTER}" != "all" && "${PHASE_FILTER}" != "$
        {PHASE}" ]]; then
        continue
    fi

    nano_log "INFO" "=== Phase ${PHASE}/${TOTAL_PHASES} ==="
    PHASE_TASKS=$(jq -r --argjson p "${PHASE}" \
        '.tasks[] | select(.phase == $p and .status != "passed")
        | .id' "${NANO_FILE}")

    for TASK_ID in ${PHASE_TASKS}; do
        if [[ "${RETRY_FAILED}" == "false" ]]; then
            STATUS=$(jq -r --arg id "${TASK_ID}" \
                '.tasks[] | select(.id == $id) | .status //
        "pending"' "${NANO_FILE}")
            [[ "${STATUS}" == "failed" ]] && continue
        fi

        nano_log "INFO" "  Executing ${TASK_ID}..."

        ab_run_n_times "nano_${TASK_ID}" 3
        nano_execute_single_task \
            "${TASK_ID}" "${FEATURE_DIR}" "${TASK_TIMEOUT}"

        if [[ $? -eq 0 ]]; then
            nano_mark_task_status "${NANO_FILE}" "${TASK_ID}"
        "passed"
            ((PASSED++))
            nano_log "INFO" "  ${TASK_ID} PASSED"
        else
```

```
            nano_mark_task_status "${NANO_FILE}" "${TASK_ID}"
        "failed"
            ((FAILED++))
            nano_log "ERROR" "  ${TASK_ID} FAILED"
        fi
    done

    nano_log "INFO" "Phase ${PHASE} complete — ${PASSED} passed, $
        {FAILED} failed"
done

if [[ "${FAILED}" -gt 0 ]]; then
    nano_log "ERROR" "Execution complete with ${FAILED} failures"
    exit 1
fi

nano_log "INFO" "All ${PASSED} tasks GREEN"
exit 0
```

bin/helix-nano-bridge-graph

```
#!/usr/bin/env bash
set -euo pipefail

SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
source "${SCRIPT_DIR}/../lib/nano_bridge_common.sh"

FEATURE_DIR="${1:-$(pwd)}"
FORMAT="${2:-mermaid}"
HIGHLIGHT="${3:-}"
CRITICAL_PATH="${4:-false}"
NANO_FILE="${FEATURE_DIR}/nano-tasks.json"

[[ -f "${NANO_FILE}" ]] || { nano_log "ERROR"
        "nano-tasks.json not found"; exit 1; }

case "${FORMAT}" in
    mermaid)
        nano_generate_mermaid "${NANO_FILE}" "${HIGHLIGHT}" "$
        {CRITICAL_PATH}"
        ;;
    dot)
        nano_generate_dot "${NANO_FILE}" "${HIGHLIGHT}" "$
        {CRITICAL_PATH}"
        ;;
    json)
        nano_generate_graph_json "${NANO_FILE}" "${CRITICAL_PATH}"
        ;;
    svg)
        DOT_OUT=$(nano_generate_dot "${NANO_FILE}" "${HIGHLIGHT}"
        "${CRITICAL_PATH}")
        echo "${DOT_OUT}" | dot -Tsvg 2>/dev/null || {
```

```
            nano_log "ERROR" "graphviz 'dot' not found — install
        graphviz"
            exit 3
        }
        ;;
    png)
        DOT_OUT=$(nano_generate_dot "${NANO_FILE}" "${HIGHLIGHT}"
        "${CRITICAL_PATH}")
        echo "${DOT_OUT}" | dot -Tpng 2>/dev/null || {
            nano_log "ERROR" "graphviz 'dot' not found — install
        graphviz"
            exit 3
        }
        ;;
    *)
        nano_log "ERROR" "Unknown format: ${FORMAT}"
        exit 2
        ;;
esac
```

bin/helix-nano-bridge-status

```
#!/usr/bin/env bash
set -euo pipefail

SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
source "${SCRIPT_DIR}/../lib/nano_bridge_common.sh"

FEATURE_DIR="${1:-$(pwd)}"
FORMAT="${2:-table}"
FILTER="${3:-all}"
INCLUDE_EVIDENCE="${4:-false}"
NANO_FILE="${FEATURE_DIR}/nano-tasks.json"

[[ -f "${NANO_FILE}" ]] || { nano_log "ERROR"
        "nano-tasks.json not found"; exit 1; }

case "${FORMAT}" in
    table)
        nano_status_table "${NANO_FILE}" "${FILTER}"
        ;;
    json)
        nano_status_json "${NANO_FILE}" "${FILTER}" "$
        {INCLUDE_EVIDENCE}"
        ;;
    summary)
        nano_status_summary "${NANO_FILE}"
        ;;
    report)
        nano_status_report "${NANO_FILE}" "${FILTER}" "$
        {INCLUDE_EVIDENCE}"
        ;;
```

```
    *)
        nano_log "ERROR" "Unknown format: ${FORMAT}"
        exit 2
        ;;
esac
```

bin/helix-nano-bridge-retry

```
#!/usr/bin/env bash
set -euo pipefail

SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
source "${SCRIPT_DIR}/../lib/nano_bridge_common.sh"

FEATURE_DIR="${1:-$(pwd)}"
TASK_IDS="${2:-}"
MAX_ATTEMPTS="${3:-3}"
STRATEGY="${4:-sequential}"
NANO_FILE="${FEATURE_DIR}/nano-tasks.json"

[[ -f "${NANO_FILE}" ]] || { nano_log "ERROR"
        "nano-tasks.json not found"; exit 1; }

FAILED_IDS=$(jq -r '.tasks[] | select(.status == "failed") | .id'
        "${NANO_FILE}")

if [[ -z "${FAILED_IDS}" ]]; then
    nano_log "INFO" "No failed tasks to retry"
    exit 0
fi

FAILED_COUNT=$(echo "${FAILED_IDS}" | wc -l)
nano_log "INFO" "Found ${FAILED_COUNT} failed tasks — strategy=$
        {STRATEGY}"

ATTEMPT=0
RERUN_PASSED=0
RERUN_FAILED=0

for TASK_ID in ${FAILED_IDS}; do
    CURRENT_ATTEMPTS=$(jq -r --arg id "${TASK_ID}" \
        '.tasks[] | select(.id == $id) | .attempts // 0' "$
        {NANO_FILE}")

    if [[ "${CURRENT_ATTEMPTS}" -ge "${MAX_ATTEMPTS}" ]]; then
        nano_log "WARN" "  ${TASK_ID} exhausted max attempts ($
        {MAX_ATTEMPTS})"
        ((RERUN_FAILED++))
        continue
    fi
```

```
    nano_log "INFO" "  Retrying ${TASK_ID} (attempt $
        {CURRENT_ATTEMPTS}+1/${MAX_ATTEMPTS})"
    nano_mark_task_status "${NANO_FILE}" "${TASK_ID}" "pending"
    nano_increment_attempts "${NANO_FILE}" "${TASK_ID}"

    ab_run_n_times "nano_retry_${TASK_ID}" 3
        nano_execute_single_task \
        "${TASK_ID}" "${FEATURE_DIR}" 3600

    if [[ $? -eq 0 ]]; then
        nano_mark_task_status "${NANO_FILE}" "${TASK_ID}" "passed"
        ((RERUN_PASSED++))
    else
        nano_mark_task_status "${NANO_FILE}" "${TASK_ID}" "failed"
        ((RERUN_FAILED++))
    fi
done

nano_log "INFO" "Retry complete — ${RERUN_PASSED} passed, $
        {RERUN_FAILED} failed"
[[ "${RERUN_FAILED}" -gt 0 ]] && exit 1
exit 0
```

A.4 Shared Library (`lib/nano_bridge_common.sh`)

```
#!/usr/bin/env bash
# Helix Nano-Bridge Common Library
# Source: helix-nano-bridge/lib/nano_bridge_common.sh
# Inherited BY REFERENCE per §11.4.28(B) — never copied into
        consumer projects

set -euo pipefail

NANO_LOG_FILE="${NANO_LOG_FILE:-/tmp/helix-nano-bridge.log}"

nano_log() {
    local LEVEL="$1"
    shift
    printf '[%s] [%s] [nano-bridge] %s\n' \
        "$(date -u +%Y-%m-%dT%H:%M:%SZ)" "${LEVEL}" "$*" | tee -a
        "${NANO_LOG_FILE}"
}

nano_decompose_task() {
    local TASK_NUM="$1"
    local TASK_TITLE="$2"
    local GRANULARITY="$3"

    # Resolve files from plan.md
    local PLAN_FILE="${FEATURE_DIR}/plan.md"
    local TASK_FILES=""
    if [[ -f "${PLAN_FILE}" ]]; then
```

```
        TASK_FILES=$(grep -A20 "Task ${TASK_NUM}" "${PLAN_FILE}"
        | \
            grep -oP '(?:src|lib|tests?)/[^\s,]+\.(?:ts|js|py|rs|
        kt|java|go)' | sort -u || true)
    fi

    if [[ -z "${TASK_FILES}" ]]; then
        nano_log "WARN" "  Task ${TASK_NUM}: no files resolved
        from plan.md — using heuristic"
        TASK_FILES=$(grep -oP '`[^`]+\.(?:ts|js|py|rs|kt|java|
        go)`' \
            "${FEATURE_DIR}/${TASKS_PATH}" | tr -d '`' | sort -u
        || true)
    fi

    for FILE in ${TASK_FILES}; do
        local NID
        NID=$(printf "N%03d" "${NANO_ID}")
        NANO_ID=$((NANO_ID + 1))

        local ACTION="MODIFY"
        if [[ ! -f "${FEATURE_DIR}/${FILE}" ]]; then
            ACTION="CREATE"
        fi

        nano_add_nano_task "${NID}" "T${TASK_NUM}" "${FILE}" "$
        {ACTION}" "${TASK_TITLE}"
    done
}

nano_add_nano_task() {
    local ID="$1"
    local PARENT="$2"
    local FILE="$3"
    local ACTION="$4"
    local TITLE="$5"

    local TASK_JSON
    TASK_JSON=$(jq -n \
        --arg id "${ID}" \
        --arg parent "${PARENT}" \
        --arg file "${FILE}" \
        --arg action "${ACTION}" \
        --arg desc "${TITLE} — ${FILE}" \
        --arg test_id "${ID}_RED" \
        '{
            id: $id,
            parent_task: $parent,
            phase: 0,
            description: $desc,
            file: $file,
            action: $action,
            imports: [],
```

```
            symbols: [],
            dependencies: [],
            test_id: $test_id,
            estimated_tokens: 400,
            estimated_duration_s: 15,
            status: "pending",
            attempts: 0,
            evidence: null
        }')

    NANO_TASKS_JSON=$(echo "${NANO_TASKS_JSON}" | jq --argjson t
        "${TASK_JSON}" \
        '.tasks += [$t]')
}

nano_build_dependency_dag() {
    nano_log "INFO" "Building dependency DAG..."
    local EDGES_JSON='[]'

    local TASK_IDS
    TASK_IDS=$(echo "${NANO_TASKS_JSON}" | jq -r '.tasks[].id')

    for TID in ${TASK_IDS}; do
        local TFILE
        TFILE=$(echo "${NANO_TASKS_JSON}" | jq -r --arg id "$
        {TID}" \
            '.tasks[] | select(.id == $id) | .file')

        for OTHER_ID in ${TASK_IDS}; do
            [[ "${TID}" == "${OTHER_ID}" ]] && continue

            local OTHER_ACTION
            OTHER_ACTION=$(echo "${NANO_TASKS_JSON}" | jq -r --
        arg id "${OTHER_ID}" \
                '.tasks[] | select(.id == $id) | .action')

            if [[ "${OTHER_ACTION}" == "CREATE" ]]; then
                local OTHER_FILE
                OTHER_FILE=$(echo "${NANO_TASKS_JSON}" | jq -r --
        arg id "${OTHER_ID}" \
                    '.tasks[] | select(.id == $id) | .file')

                if [[ "${TFILE}" == "${OTHER_FILE}" ]]; then
                    EDGES_JSON=$(echo "${EDGES_JSON}" | jq --arg
        from "${OTHER_ID}" --arg to "${TID}" \
                        '. += [{"from": $from, "to": $to}]')
                    NANO_TASKS_JSON=$(echo "${NANO_TASKS_JSON}" |
        jq --arg id "${TID}" --arg dep "${OTHER_ID}" \
                        '(.tasks[] | select(.id == $id)
        | .dependencies) += [$dep]')
                fi
            fi
        done
```

```
    done

    NANO_TASKS_JSON=$(echo "${NANO_TASKS_JSON}" | jq --argjson
        edges "${EDGES_JSON}" \
        '.graph.edges = $edges')
    NANO_TASKS_JSON=$(echo "${NANO_TASKS_JSON}" | jq --argjson
        nodes \
        "$(echo "${NANO_TASKS_JSON}" | jq '[.tasks[].id]')" \
        '.graph.nodes = $nodes')
}

nano_assign_phases() {
    nano_log "INFO" "Assigning phases..."

    local REMAINING
    REMAINING=$(echo "${NANO_TASKS_JSON}" | jq -r '.tasks[].id')
    local PHASE=0

    while [[ -n "${REMAINING}" ]]; do
        PHASE=$((PHASE + 1))
        local PHASE_TASKS=""

        for TID in ${REMAINING}; do
            local DEPS_MET=true
            local DEPS
            DEPS=$(echo "${NANO_TASKS_JSON}" | jq -r --arg id "$
        {TID}" \
                '.tasks[] | select(.id == $id)
        | .dependencies[]?')

            for DEP in ${DEPS}; do
                local DEP_PHASE
                DEP_PHASE=$(echo "${NANO_TASKS_JSON}" | jq -r --
        arg id "${DEP}" \
                    '.tasks[] | select(.id == $id) | .phase')
                if [[ "${DEP_PHASE}" -ge "${PHASE}" ]]; then
                    DEPS_MET=false
                    break
                fi
            done

            if [[ "${DEPS_MET}" == "true" ]]; then
                NANO_TASKS_JSON=$(echo "${NANO_TASKS_JSON}" | jq
        --arg id "${TID}" --argjson p "${PHASE}" \
                    '(.tasks[] | select(.id == $id) | .phase) =
        $p')
                PHASE_TASKS="${PHASE_TASKS} ${TID}"
            fi
        done

        local PHASE_ARR
        PHASE_ARR=$(echo "${PHASE_TASKS}" | jq -R 'split(" ") |
        map(select(. != ""))')
```

```
        NANO_TASKS_JSON=$(echo "${NANO_TASKS_JSON}" | jq --
        argjson arr "${PHASE_ARR}" \
            '.graph.phases += [$arr]')

        REMAINING=""
        for TID in $(echo "${NANO_TASKS_JSON}" | jq -r
        '.tasks[] | select(.phase == 0) | .id'); do
            REMAINING="${REMAINING} ${TID}"
        done
        REMAINING="${REMAINING# }"
    done

    NANO_TASKS_JSON=$(echo "${NANO_TASKS_JSON}" | jq --argjson p
        "${PHASE}" \
        '.meta.phases = $p')
}

nano_detect_cycles() {
    local EDGES
    EDGES=$(echo "${NANO_TASKS_JSON}" | jq -r '.graph.edges[] | "\
        (.from) \(.to)"')

    local declare -A ADJ=()
    while IFS=' ' read -r FROM TO; do
        [[ -z "${FROM}" ]] && continue
        ADJ["${FROM}"]="${ADJ[$FROM]:-} ${TO}"
    done <<< "${EDGES}"

    for NODE in $(echo "${NANO_TASKS_JSON}" | jq -r
        '.graph.nodes[]'); do
        if nano_dfs_cycle "${NODE}" ADJ; then
            nano_log "ERROR" "Cycle detected involving node: $
        {NODE}"
            return 1
        fi
    done
    return 0
}

nano_dfs_cycle() {
    local NODE="$1"
    local -n ADJ_REF="$2"
    local -A VISITED=()
    local -A IN_STACK=()

    nano_dfs_visit() {
        local V="$1"
        VISITED["${V}"]=1
        IN_STACK["${V}"]=1

        for NEIGHBOR in ${ADJ_REF[$V]:-}; do
            if [[ -z "${VISITED[$NEIGHBOR]:-}" ]]; then
                nano_dfs_visit "${NEIGHBOR}" && return 0
```

```
            elif [[ -n "${IN_STACK[$NEIGHBOR]:-}" ]]; then
                return 0
            fi
        done
        unset "IN_STACK[${V}]"
        return 1
    }

    nano_dfs_visit "${NODE}"
    return $?
}

nano_execute_single_task() {
    local TASK_ID="$1"
    local FEATURE_DIR="$2"
    local TIMEOUT="$3"

    local TASK_DATA
    TASK_DATA=$(jq -r --arg id "${TASK_ID}" \
        '.tasks[] | select(.id == $id)' "${FEATURE_DIR}/nano-
        tasks.json")

    local TASK_FILE
    TASK_FILE=$(echo "${TASK_DATA}" | jq -r '.file')
    local TEST_ID
    TEST_ID=$(echo "${TASK_DATA}" | jq -r '.test_id')
    local EVIDENCE_DIR="${FEATURE_DIR}/qa-results/nano-tasks/$
        {TASK_ID}"

    mkdir -p "${EVIDENCE_DIR}"

    # Phase 1: RED — verify test fails on clean artifact
    local RED_EXIT=0
    if [[ -f "${FEATURE_DIR}/tests/${TEST_ID}.sh" ]]; then
        timeout "${TIMEOUT}" bash "${FEATURE_DIR}/tests/$
        {TEST_ID}.sh" > \
            "${EVIDENCE_DIR}/RED_$(date -u +%Y%m%dT%H%M%SZ).log"
        2>&1 && RED_EXIT=$? || RED_EXIT=$?
    fi

    if [[ "${RED_EXIT}" -eq 0 ]]; then
        nano_log "ERROR" "  ${TASK_ID}: RED test passed (should
        fail)"
        echo '{"verdict":"FAIL","reason":"RED test did not
        fail"}' > "${EVIDENCE_DIR}/verdict.json"
        return 1
    fi

    nano_log "INFO" "  ${TASK_ID}: RED phase confirmed (exit=$
        {RED_EXIT})"

    # Phase 2: GREEN — produce the implementation
```

```
    ab_pass_with_evidence "nano_${TASK_ID}_red" "${EVIDENCE_DIR}/
        RED_"*

    local GREEN_EXIT=0
    if [[ -f "${FEATURE_DIR}/tests/${TASK_ID}_green.sh" ]]; then
        timeout "${TIMEOUT}" bash "${FEATURE_DIR}/tests/${TASK_ID}
        _green.sh" > \
            "${EVIDENCE_DIR}/GREEN_$(date -u +
        %Y%m%dT%H%M%SZ).log" 2>&1 && GREEN_EXIT=$? ||
        GREEN_EXIT=$?
    fi

    if [[ "${GREEN_EXIT}" -ne 0 ]]; then
        nano_log "ERROR" "  ${TASK_ID}: GREEN test failed (exit=$
        {GREEN_EXIT})"
        echo '{"verdict":"FAIL","reason":"GREEN test failed"}' >
        "${EVIDENCE_DIR}/verdict.json"
        return 1
    fi

    # Phase 3: VERIFY — anti-bluff oracle
    ab_assert_kernel_value "nano_${TASK_ID}_green" "$
        {EVIDENCE_DIR}/GREEN_"* ".*" || {
        echo '{"verdict":"FAIL","reason":"Anti-bluff oracle
        rejected"}' > "${EVIDENCE_DIR}/verdict.json"
        return 1
    }

    # Write verdict
    jq -n \
        --arg id "${TASK_ID}" \
        --arg red_exit "${RED_EXIT}" \
        --arg green_exit "${GREEN_EXIT}" \
        '{
            task_id: $id,
            verdict: "PASS",
            evidence_class: "source_code",
            red_exit: ($red_exit | tonumber),
            green_exit: ($green_exit | tonumber),
            iterations: 3,
            artifact_fingerprint: "sha256:placeholder",
            oracle: "helix-nano-bridge/anti-bluff",
            timestamp: (now | strftime("%Y-%m-%dT%H:%M:%SZ"))
        }' > "${EVIDENCE_DIR}/verdict.json"

    return 0
}

nano_mark_task_status() {
    local NANO_FILE="$1"
    local TASK_ID="$2"
    local STATUS="$3"
```

```
    local TMP_FILE="${NANO_FILE}.tmp.$$"
    jq --arg id "${TASK_ID}" --arg status "${STATUS}" \
        '(.tasks[] | select(.id == $id) | .status) = $status' "$
        {NANO_FILE}" > "${TMP_FILE}"
    mv "${TMP_FILE}" "${NANO_FILE}"
}

nano_increment_attempts() {
    local NANO_FILE="$1"
    local TASK_ID="$2"

    local TMP_FILE="${NANO_FILE}.tmp.$$"
    jq --arg id "${TASK_ID}" \
        '(.tasks[] | select(.id == $id) | .attempts) += 1' "$
        {NANO_FILE}" > "${TMP_FILE}"
    mv "${TMP_FILE}" "${NANO_FILE}"
}

nano_run_pre_execution_gate() {
    local FEATURE_DIR="$1"
    local NANO_FILE="${FEATURE_DIR}/nano-tasks.json"
    local GATE_PASSED=true

    nano_log "INFO" "  Gate check 1/4: RED tests exist for all
        tasks..."
    local TOTAL
    TOTAL=$(jq '.tasks | length' "${NANO_FILE}")
    local RED_COUNT
    RED_COUNT=$(jq '[.tasks[] | select(.test_id != null)] |
        length' "${NANO_FILE}")

    if [[ "${RED_COUNT}" -lt "${TOTAL}" ]]; then
        nano_log "ERROR" "  ${RED_COUNT}/${TOTAL} tasks have RED
        tests — missing $((TOTAL - RED_COUNT))"
        GATE_PASSED=false
    else
        nano_log "INFO" "  OK: ${RED_COUNT}/${TOTAL}"
    fi

    nano_log "INFO" "  Gate check 2/4: Evidence directory
        writable..."
    local EVIDENCE_DIR="${FEATURE_DIR}/qa-results/nano-tasks"
    if ! mkdir -p "${EVIDENCE_DIR}" 2>/dev/null && touch "$
        {EVIDENCE_DIR}/.write_test" 2>/dev/null; then
        nano_log "ERROR" "  Evidence dir not writable: $
        {EVIDENCE_DIR}"
        GATE_PASSED=false
    else
        rm -f "${EVIDENCE_DIR}/.write_test"
        nano_log "INFO" "  OK: ${EVIDENCE_DIR}"
    fi
```

```
    nano_log "INFO" "  Gate check 3/4: No stale /data/app
        shadows..."
    if adb get-state 2>/dev/null; then
        local SHADOWS
        SHADOWS=$(adb shell 'pm list packages -f' 2>/dev/null |
        grep '/data/app/' || true)
        if [[ -n "${SHADOWS}" ]]; then
            nano_log "WARN" "  Data app shadows detected — verify
        clean target"
        fi
    fi
    nano_log "INFO" "  OK: ADB device state verified"

    nano_log "INFO" "  Gate check 4/4: Runtime signature registry
        loaded..."
    if [[ -f "${FEATURE_DIR}/runtime_signatures.json" ]]; then
        nano_log "INFO" "  OK: runtime_signatures.json present"
    else
        nano_log "WARN" "  runtime_signatures.json not found —
        proceeding without runtime registry"
    fi

    ${GATE_PASSED}
    return $?
}

nano_generate_mermaid() {
    local NANO_FILE="$1"
    local HIGHLIGHT="$2"
    local CRITICAL_PATH="$3"

    echo '```mermaid'
    echo 'graph TD'

    jq -r '.tasks[] | "  \(.id)[\"\(.id): \(.description[0:60])
        \"]"' "${NANO_FILE}"

    jq -r '.graph.edges[] | "  \(.from) --> \(.to)"' "$
        {NANO_FILE}"

    local COLORS='passed:#90EE90 failed:#FF6B6B running:#87CEEB
        pending:#E0E0E0 skipped:#FFF8DC'
    for PAIR in ${COLORS}; do
        local STATUS="${PAIR%%:*}"
        local COLOR="${PAIR##*:}"
        jq -r --arg status "${STATUS}" --arg color "${COLOR}" \
            '.tasks[] | select(.status == $status) | "  style \
        (.id) fill:\($color)"' "${NANO_FILE}"
    done

    echo '```'
}
```

```
nano_generate_dot() {
    local NANO_FILE="$1"
    local HIGHLIGHT="$2"
    local CRITICAL_PATH="$3"

    echo 'digraph NanoTasks {'
    echo '  rankdir=TB;'
    echo '  node [shape=box, style=rounded];'

    jq -r '.tasks[] | "  \(.id) [label=\"\(.id)\\n\
        (.description[0:40])\", fillcolor=lightgray,
        style=filled];"' \
        "${NANO_FILE}"

    jq -r '.graph.edges[] | "  \(.from) -> \(.to);"' "$
        {NANO_FILE}"
    echo '}'
}

nano_generate_graph_json() {
    local NANO_FILE="$1"
    local CRITICAL_PATH="$2"

    jq '{
        graph: {
            directed: true,
            nodes: [.tasks[] | {id: .id, phase: .phase,
        status: .status}],
            edges: [.graph.edges[] | {from: .from, to: .to}]
        },
        stats: {
            total: (.tasks | length),
            passed: ([.tasks[] | select(.status == "passed")] |
        length),
            failed: ([.tasks[] | select(.status == "failed")] |
        length),
            running: ([.tasks[] | select(.status == "running")] |
        length),
            pending: ([.tasks[] | select(.status == "pending")] |
        length),
            skipped: ([.tasks[] | select(.status == "skipped")] |
        length)
        }
    }' "${NANO_FILE}"
}

nano_status_table() {
    local NANO_FILE="$1"
    local FILTER="$2"

    printf '%-8s %-6s %-8s %-8s %-50s\n' "ID" "Phase" "Status"
        "Att" "Description"
    printf '%.0s─' {1..90}
```

```
    echo

    local FILTER_EXPR='.'
    [[ "${FILTER}" != "all" ]] && FILTER_EXPR="select(.status ==
        \"${FILTER}\")"

    jq -r --arg filter "${FILTER}" \
        '.tasks[] | '"${FILTER_EXPR}"' | "\(.id)\t\(.phase)\t\
        (.status // "pending")\t\(.attempts // 0)\t\
        (.description[0:50])"' \
        "${NANO_FILE}" | while IFS=$'\t' read -r ID PHASE STATUS
        ATT DESC; do
        printf '%-8s %-6s %-8s %-8s %-50s\n' "${ID}" "${PHASE}" "$
        {STATUS}" "${ATT}" "${DESC}"
    done
}

nano_status_json() {
    local NANO_FILE="$1"
    local FILTER="$2"
    local INCLUDE_EVIDENCE="$3"

    jq --arg filter "${FILTER}" --argjson evidence "$
        {INCLUDE_EVIDENCE}" '
    {
        summary: {
            total: (.tasks | length),
            passed: ([.tasks[] | select(.status == "passed")] |
        length),
            failed: ([.tasks[] | select(.status == "failed")] |
        length),
            running: ([.tasks[] | select(.status == "running")] |
        length),
            pending: ([.tasks[] | select(.status == "pending")] |
        length),
            skipped: ([.tasks[] | select(.status == "skipped")] |
        length)
        },
        tasks: [.tasks[] | {
            id, phase, status, description, attempts,
            evidence: (if $evidence then .evidence else null end)
        }]
    }' "${NANO_FILE}"
}

nano_status_summary() {
    local NANO_FILE="$1"

    local TOTAL PASSED FAILED RUNNING PENDING SKIPPED
    TOTAL=$(jq '.tasks | length' "${NANO_FILE}")
    PASSED=$(jq '[.tasks[] | select(.status == "passed")] |
        length' "${NANO_FILE}")
    FAILED=$(jq '[.tasks[] | select(.status == "failed")] |
        length' "${NANO_FILE}")
```

```
    RUNNING=$(jq '[.tasks[] | select(.status == "running")] |
        length' "${NANO_FILE}")
    PENDING=$(jq '[.tasks[] | select(.status == "pending")] |
        length' "${NANO_FILE}")
    SKIPPED=$(jq '[.tasks[] | select(.status == "skipped")] |
        length' "${NANO_FILE}")

    local PCT=0
    [[ "${TOTAL}" -gt 0 ]] && PCT=$((PASSED * 100 / TOTAL))

    cat <<EOF
╔═══════════════════════════════════════════════════╗
║         Helix Nano-Bridge Status                  ║
╠═══════════════════════════════════════════════════╣
║ Total:  ${TOTAL}  | Passed: ${PASSED}  (${PCT}%)
║ Failed:  ${FAILED}  | Running: ${RUNNING}
║ Pending: ${PENDING} | Skipped: ${SKIPPED}
╚═══════════════════════════════════════════════════╝
EOF
}

nano_status_report() {
    local NANO_FILE="$1"
    local FILTER="$2"
    local INCLUDE_EVIDENCE="$3"

    nano_status_summary "${NANO_FILE}"
    echo
    nano_status_table "${NANO_FILE}" "${FILTER}"
    echo

    if [[ "${INCLUDE_EVIDENCE}" == "true" ]]; then
        echo "=== Evidence Artifacts ==="
        jq -r
        '.tasks[] | select(.status == "passed" or .status ==
        "failed") |
            "\(.id) (\(.status)): \(.evidence.verdict // "N/A")"'
        "${NANO_FILE}"
    fi
}

nano_detect_gpu() {
    if command -v nvidia-smi &>/dev/null; then
        nvidia-smi -L 2>/dev/null | head -1
        return 0
    elif command -v rocminfo &>/dev/null; then
        rocminfo 2>/dev/null | grep -i 'Name:' | head -1
        return 0
    fi
    return 1
}
```

A.5 Installation

```
# Install the extension into SpecKit
specify extension add helix-nano-bridge \
    --from "https://github.com/vasic-digital/helix-nano-bridge" \
    --version "1.0.0"

# Verify installation
specify extension list | grep helix-nano-bridge

# Run decompose on a feature
specify helix-nano-bridge decompose --granularity function

# Execute
specify helix-nano-bridge execute --phase all

# Check status
specify helix-nano-bridge status --format table
```

Part B: Superpowers Skills

B.1 Skill: `nano-task-execution`

```
# nano-task-execution

## Description
Executes individual nano-tasks with strict TDD enforcement, anti-
        bluff
verification, and evidence capture. Composes with the Helix Nano-
        Bridge
extension for full SpecKit integration.

## Dependencies
- Skill: `nano-task-decompose`
- Tool: `superbridge-mcp.execute_tdd_cycle`
- Library: `constitution/scripts/lib/anti_bluff.sh`

## Workflow

### Input
The skill receives a nano-task JSON object or `nano-tasks.json`
        path.

### Execution Flow

┌──────────────────────────────────────────────────────────────┐ │ 1.
VALIDATE │ │ - Task has RED test ID │ │ - Evidence directory exists │ │
- Dependencies are satisfied │
```

├──┤ │ 2. RED PHASE │ │ - Run RED test (expected: FAIL) │ │ - Capture failure output │ │ - Verify exit code ≠ 0 │ │ - Verify failure is EXPECTED failure mode │
├──┤ │ 3. GREEN PHASE │ │ - Generate implementation │ │ - Write code to target file │ │ - Run GREEN test (expected: PASS) │ │ - Capture pass output │ │ - Verify exit code = 0 │
├──┤ │ 4. VERIFY PHASE │ │ - Anti-bluff oracle check │ │ - 3-iteration deterministic consistency │ │ - Evidence hash verification │ │ - Write verdict.json │
├──┤ │ 5. REPORT │ │ - Update nano-tasks.json status │ │ - Log to conduit events │ │ - Return verdict │
└──┘

Configuration

```yaml
# .superpowers/nano-task-execution.yaml
task_timeout: 3600
max_retries: 2
tdd_enforcement: strict
anti_bluff_mode: full
capture_artifacts: true
evidence_dir: "{{ FEATURE_DIR }}/qa-results/nano-tasks"
```

Errors

Code	Meaning	Recovery
NTX001	RED test passed (should fail)	Check test correctness
NTX002	GREEN test failed	Fix implementation
NTX003	Evidence dir unwritable	Check permissions
NTX004	Dependency not satisfied	Execute dependency first
NTX005	Timeout	Increase timeout or optimize

B.2 Skill: `nano-task-decompose`

```markdown
# nano-task-decompose

## Description
```

```
Decomposes a SpecKit task from `tasks.md` into atomic, dependency-
ordered
nano-tasks suitable for TDD-driven execution.

## Dependencies
- Tool: `superbridge-mcp.nano_task_decompose`
- Tool: `superbridge-mcp.nano_task_graph`
- SpecKit: `tasks.md`, `plan.md`, `spec.md`

## Workflow

### Input
- Path to `tasks.md` (resolved from SpecKit feature directory)
- Granularity: `function` | `method` | `block` | `line`
- Max tasks: upper bound (default 512)

### Decomposition Algorithm
```

1. PARSE tasks.md └── Extract task blocks with descriptions and acceptance criteria
2. RESOLVE against plan.md └── Map each task to concrete files, symbols, and imports
3. ANALYZE dependencies └── For each file/symbol, determine what must exist first └── Build adjacency list of prerequisites
4. GENERATE nano-tasks └── CREATE tasks: new files/directories └── MODIFY tasks: changes to existing code └── TEST tasks: RED tests that gate implementation
5. BUILD dependency DAG └── Topological sort └── Cycle detection (Kahn's algorithm) └── Critical path computation (longest path in DAG)
6. ASSIGN phases └── Level-order grouping where all tasks in a phase are independent └── Parallel-safe: no two tasks in same phase share a file
7. WRITE nano-tasks.json

```
### Quality Gates

| Gate | Check |
|------|-------|
| G1 | Every nano-task maps to exactly one file |
| G2 | Dependency graph is acyclic |
| G3 | Every task has a RED test ID |
| G4 | No two tasks in the same phase share a file |
```

```
| G5 | Critical path length ≤ max_tasks |
| G6 | Estimated total tokens ≤ context window |

### Output Schema

See `nano-tasks.json` schema in EXTENSION_DEVELOPMENT.md §A.2.
```

B.3 Skill Installation

```
# Install skills into Superpowers plugin system
superpowers plugin install nano-task-execution \
    --from "https://github.com/vasic-digital/helix-nano-bridge" \
    --skill "nano-task-execution"

superpowers plugin install nano-task-decompose \
    --from "https://github.com/vasic-digital/helix-nano-bridge" \
    --skill "nano-task-decompose"

# Verify
superpowers plugin list | grep nano-task

# The skills are now available to any agent:
#   - Claude Code: auto-discovered from .superpowers/
#   - Codex: invoked via /superpowers:nano-task-execution
#   - Cursor: available via Superpowers panel
#   - Gemini CLI: loaded via superpowers gemini-plugin
```

Part C: MCP Server (`superbridge-mcp`)

C.1 Server Specification

```
// superbridge-mcp/src/index.ts
import { Server } from "@modelcontextprotocol/sdk/server/
         index.js";
import { StdioServerTransport } from "@modelcontextprotocol/sdk/
         server/stdio.js";
import {
  CallToolRequestSchema,
  ListToolsRequestSchema,
} from "@modelcontextprotocol/sdk/types.js";

const server = new Server(
  {
    name: "superbridge-mcp",
    version: "1.0.0",
  },
  {
    capabilities: {
```

```
      tools: {},
    },
  }
);

// ============================================================
// Tool: execute_tdd_cycle
// ============================================================
server.setRequestHandler(ListToolsRequestSchema, async () => ({
  tools: [
    {
      name: "execute_tdd_cycle",
      description:
        "Execute a single TDD cycle: RED (fail) → GREEN (pass) →
        VERIFY (anti-bluff)",
      inputSchema: {
        type: "object",
        properties: {
          task_id: {
            type: "string",
            description: "Nano-task identifier (e.g., N001)",
          },
          feature_dir: {
            type: "string",
            description: "Absolute path to the feature directory",
          },
          red_test_path: {
            type: "string",
            description: "Path to the RED test script",
          },
          green_test_path: {
            type: "string",
            description: "Path to the GREEN test script",
          },
          target_file: {
            type: "string",
            description: "Path to the file being modified",
          },
          timeout_seconds: {
            type: "integer",
            default: 3600,
            description: "Per-phase timeout in seconds",
          },
          iterations: {
            type: "integer",
            default: 3,
            description: "Number of GREEN iterations for
        consistency check",
          },
        },
        required: ["task_id", "feature_dir", "red_test_path",
        "green_test_path", "target_file"],
```

```
    },
  },
  {
    name: "verify_anti_bluff",
    description: "Verify that a PASS is genuine through the
      anti-bluff oracle",
    inputSchema: {
      type: "object",
      properties: {
        task_id: {
          type: "string",
          description: "Nano-task identifier",
        },
        evidence_dir: {
          type: "string",
          description: "Directory containing RED and GREEN
      evidence",
        },
        evidence_class: {
          type: "string",
          enum: ["source_code", "audio_output",
      "video_display", "network_connectivity",
                 "bluetooth_a2dp", "mediacodec_decode",
      "display_topology", "drm_playback"],
          description: "§11.4.69 feature class for evidence
      taxonomy",
        },
        expected_content_patterns: {
          type: "array",
          items: { type: "string" },
          description:
      "Regex patterns that MUST appear in GREEN evidence",
        },
        forbidden_patterns: {
          type: "array",
          items: { type: "string" },
          description: "Regex patterns that MUST NOT appear
      (bluff indicators)",
        },
      },
      required: ["task_id", "evidence_dir", "evidence_class"],
    },
  },
  {
    name: "nano_task_decompose",
    description: "Decompose a SpecKit task into atomic nano-
      tasks",
    inputSchema: {
      type: "object",
      properties: {
        tasks_path: {
          type: "string",
          description: "Path to tasks.md",
```

```
      },
      plan_path: {
        type: "string",
        description: "Path to plan.md for design context",
      },
      spec_path: {
        type: "string",
        description: "Path to spec.md for acceptance
    criteria",
      },
      granularity: {
        type: "string",
        enum: ["function", "method", "block", "line"],
        default: "function",
      },
      max_tasks: {
        type: "integer",
        default: 512,
        minimum: 1,
        maximum: 4096,
      },
      output_path: {
        type: "string",
        description: "Where to write nano-tasks.json",
      },
    },
    required: ["tasks_path", "plan_path", "output_path"],
  },
},
{
  name: "nano_task_execute",
  description:
    "Execute a single nano-task with full TDD cycle and
    evidence capture",
  inputSchema: {
    type: "object",
    properties: {
      task: {
        type: "object",
        properties: {
          id: { type: "string" },
          file: { type: "string" },
          action: { type: "string", enum: ["CREATE",
    "MODIFY", "DELETE"] },
          test_id: { type: "string" },
          description: { type: "string" },
        },
        required: ["id", "file", "action", "test_id"],
      },
      feature_dir: { type: "string" },
      evidence_dir: { type: "string" },
      timeout: { type: "integer", default: 3600 },
```

```
          gpu_offload: { type: "boolean", default: false },
        },
        required: ["task", "feature_dir", "evidence_dir"],
      },
    },
    {
      name: "nano_task_graph",
      description: "Generate and analyze the nano-task dependency
        graph",
      inputSchema: {
        type: "object",
        properties: {
          nano_tasks_path: {
            type: "string",
            description: "Path to nano-tasks.json",
          },
          format: {
            type: "string",
            enum: ["mermaid", "dot", "json", "svg", "png"],
            default: "json",
          },
          compute_critical_path: {
            type: "boolean",
            default: true,
          },
          highlight_ids: {
            type: "array",
            items: { type: "string" },
          },
        },
        required: ["nano_tasks_path"],
      },
    },
  ],
}));

// ============================================================
// Tool Handler: execute_tdd_cycle
// ============================================================
server.setRequestHandler(CallToolRequestSchema, async (request)
        => {
  const { name, arguments: args } = request.params;

  switch (name) {
    case "execute_tdd_cycle": {
      const { task_id, feature_dir, red_test_path,
        green_test_path, target_file, timeout_seconds,
        iterations } = args;

      // Phase 1: RED
      const redResult = await runPhase("RED", red_test_path,
        timeout_seconds, true);
```

```
    if (!redResult.success) {
      return errorResponse(task_id,
      "RED phase failed — test did not fail as expected",
      redResult);
    }

    // Phase 2: GREEN
    const greenResults: Array<{ iteration: number; success:
      boolean; output: string }> = [];
    for (let i = 0; i < iterations; i++) {
      const greenResult = await runPhase("GREEN",
      green_test_path, timeout_seconds, false);
      greenResults.push({ iteration: i + 1, ...greenResult });
      if (!greenResult.success) {
        return errorResponse(task_id, `GREEN phase failed at
      iteration ${i + 1}`, greenResult);
      }
    }

    // Phase 3: VERIFY
    const verifyResult = await verifyEvidence(task_id,
      feature_dir, redResult, greenResults);

    return {
      content: [{
        type: "text",
        text: JSON.stringify({
          task_id,
          verdict: verifyResult.passed ? "PASS" : "FAIL",
          red: redResult,
          green_iterations: greenResults,
          verify: verifyResult,
          timestamp: new Date().toISOString(),
        }, null, 2),
      }],
    };
  }

  case "verify_anti_bluff": {
    const { task_id, evidence_dir, evidence_class,
      expected_content_patterns, forbidden_patterns } = args;

    const verdict = await runAntiBluffOracle(
      task_id, evidence_dir, evidence_class,
      expected_content_patterns || [], forbidden_patterns || []
    );

    return {
      content: [{
        type: "text",
        text: JSON.stringify(verdict, null, 2),
      }],
    };
```

```
}

case "nano_task_decompose": {
  const { tasks_path, plan_path, spec_path, granularity,
    max_tasks, output_path } = args;

  const decomposition = await decomposeNanoTasks(
    tasks_path, plan_path, spec_path, granularity, max_tasks
  );

  await writeJson(output_path, decomposition);

  return {
    content: [{
      type: "text",
      text: JSON.stringify({
        output_path,
        total_tasks: decomposition.tasks.length,
        phases: decomposition.meta.phases,
        critical_path_length:
    decomposition.meta.critical_path_length,
      }, null, 2),
    }],
  };
}

case "nano_task_execute": {
  const { task, feature_dir, evidence_dir, timeout,
    gpu_offload } = args;

  const result = await executeNanoTask(task, feature_dir,
    evidence_dir, timeout, gpu_offload);

  return {
    content: [{
      type: "text",
      text: JSON.stringify(result, null, 2),
    }],
  };
}

case "nano_task_graph": {
  const { nano_tasks_path, format, compute_critical_path,
    highlight_ids } = args;

  const graphData = await loadJson(nano_tasks_path);
  const graph = buildDependencyGraph(graphData,
    compute_critical_path);

  let output: string;
  switch (format) {
    case "mermaid": output = renderMermaid(graph); break;
    case "dot": output = renderDot(graph); break;
```

```
        case "json": output = JSON.stringify(graph, null, 2);
        break;
        case "svg": output = await
        renderDotToSvg(renderDot(graph)); break;
        case "png": output = await
        renderDotToPng(renderDot(graph)); break;
        default: output = JSON.stringify(graph, null, 2);
      }

      return {
        content: [{
          type: "text",
          text: output,
        }],
      };
    }

    default:
      throw new Error(`Unknown tool: ${name}`);
  }
});

// ============================================================
// Core Implementation
// ============================================================

async function runPhase(
  phase: string, testPath: string, timeout: number,
        expectFailure: boolean
): Promise<{ success: boolean; output: string; exitCode: number }
        > {
  const { exec } = await import("child_process");
  return new Promise((resolve) => {
    exec(`timeout ${timeout} bash "${testPath}"`, {
      cwd: process.cwd(),
      maxBuffer: 10 * 1024 * 1024,
    }, (error, stdout, stderr) => {
      const output = `${stdout}\n${stderr}`;
      const exitCode = error ? (error as any).code || 1 : 0;

      if (expectFailure) {
        resolve({ success: exitCode !== 0, output, exitCode });
      } else {
        resolve({ success: exitCode === 0, output, exitCode });
      }
    });
  });
}

async function verifyEvidence(
  taskId: string, featureDir: string,
  redResult: { output: string }, greenResults: Array<{ output:
        string }>
```

```
): Promise<{ passed: boolean; checks: Record<string, boolean>;
        message: string }> {
  const checks: Record<string, boolean> = {};

  checks.red_output_not_empty = redResult.output.length > 0;
  checks.green_output_not_empty = greenResults.every(g =>
        g.output.length > 0);
  checks.green_all_pass = greenResults.every(g => g.success);
  checks.green_no_error = greenResults.every(g => !
        g.output.includes("Error:") && !
        g.output.includes("FAIL"));

  const allChecks = Object.values(checks).every(Boolean);

  return {
    passed: allChecks,
    checks,
    message: allChecks ? "All anti-bluff checks passed" : "Some
        checks failed",
  };
}

async function runAntiBluffOracle(
  taskId: string, evidenceDir: string, evidenceClass: string,
  expectedPatterns: string[], forbiddenPatterns: string[]
): Promise<{
  verdict: string; task_id: string; evidence_class: string;
  expected: { pattern: string; found: boolean }[];
  forbidden: { pattern: string; found: boolean }[];
}> {
  const fs = await import("fs/promises");
  const path = await import("path");

  const files = await fs.readdir(evidenceDir);
  const greenFiles = files.filter(f => f.startsWith("GREEN_"));
  const allEvidence = await Promise.all(
    greenFiles.map(f => fs.readFile(path.join(evidenceDir, f),
        "utf-8"))
  );
  const combined = allEvidence.join("\n");

  const expected = expectedPatterns.map(p => ({ pattern: p,
        found: new RegExp(p).test(combined) }));
  const forbidden = forbiddenPatterns.map(p => ({ pattern: p,
        found: new RegExp(p).test(combined) }));

  const verdict = expected.every(e => e.found) &&
        forbidden.every(f => !f.found) ? "PASS" : "FAIL";

  return { verdict, task_id: taskId, evidence_class:
        evidenceClass, expected, forbidden };
}
```

```
async function decomposeNanoTasks(
  tasksPath: string, planPath: string, specPath: string,
  granularity: string, maxTasks: number
): Promise<any> {
  const fs = await import("fs/promises");
  const tasksMd = await fs.readFile(tasksPath, "utf-8");

  const taskRegex = /^## Task (\d+): (.+)$/gm;
  const tasks: Array<{ num: number; title: string }> = [];
  let match;
  while ((match = taskRegex.exec(tasksMd)) !== null) {
    tasks.push({ num: parseInt(match[1]), title: match[2] });
  }

  let nanoId = 1;
  const nanoTasks: any[] = [];
  const edges: Array<{ from: string; to: string }> = [];

  for (const task of tasks) {
    const files = extractFilesFromTask(tasksMd, task.num,
        granularity);
    const taskIds: string[] = [];

    for (const file of files) {
      const nid = `N${String(nanoId).padStart(3, "0")}`;
      nanoId++;

      const nanoTask = {
        id: nid,
        parent_task: `T${task.num}`,
        phase: 0,
        description: `${task.title} — ${file}`,
        file,
        action: "MODIFY",
        imports: [],
        symbols: [],
        dependencies: [],
        test_id: `${nid}_RED`,
        estimated_tokens: 400,
        estimated_duration_s: 15,
        status: "pending",
        attempts: 0,
        evidence: null,
      };

      if (taskIds.length > 0) {
        nanoTask.dependencies = [taskIds[taskIds.length - 1]];
      }

      nanoTasks.push(nanoTask);
      taskIds.push(nid);
    }
```

```
  }

  const totalTasks = Math.min(nanoTasks.length, maxTasks);
  const sliced = nanoTasks.slice(0, totalTasks);
  const phases = assignPhases(sliced, edges);

  return {
    meta: {
      source: "tasks.md",
      granularity,
      generated: new Date().toISOString(),
      total_tasks: sliced.length,
      phases: phases.length,
      critical_path_length: computeCriticalPath(sliced,
        edges).length,
    },
    tasks: sliced,
    graph: {
      nodes: sliced.map(t => t.id),
      edges,
      phases: phases.map(p => p.map((t: any) => t.id)),
    },
  };
}

function extractFilesFromTask(tasksMd: string, taskNum: number,
        granularity: string): string[] {
  const taskBlock = tasksMd.split(`## Task ${taskNum}:`)
        [1]?.split(/^## /m)[0] || "";
  const fileMatches = taskBlock.matchAll(/`([^`]+\.(?:ts|js|py|rs|
        kt|java|go|sh|yaml|json|toml))`/g);
  return [...new Set([...fileMatches].map(m => m[1]))];
}

function assignPhases(tasks: any[], edges: Array<{ from: string;
        to: string }>): any[][] {
  const inDegree: Record<string, number> = {};
  const adj: Record<string, string[]> = {};

  for (const t of tasks) {
    inDegree[t.id] = t.dependencies.length;
    adj[t.id] = [];
  }
  for (const e of edges) {
    adj[e.from].push(e.to);
  }

  const phases: any[][] = [];
  const remaining = new Set(tasks.map(t => t.id));

  while (remaining.size > 0) {
    const currentPhase = tasks.filter(t => remaining.has(t.id) &&
        inDegree[t.id] === 0);
```

```
    if (currentPhase.length === 0) break;

    for (const t of currentPhase) {
      for (const neighbor of adj[t.id]) {
        inDegree[neighbor] = Math.max(0, (inDegree[neighbor] ||
        0) - 1);
      }
      remaining.delete(t.id);
      t.phase = phases.length + 1;
    }

    phases.push(currentPhase);
  }

  return phases;
}

function computeCriticalPath(tasks: any[], edges: Array<{ from:
        string; to: string }>): string[] {
  const adj: Record<string, string[]> = {};
  const revAdj: Record<string, string[]> = {};
  for (const t of tasks) {
    adj[t.id] = [];
    revAdj[t.id] = [];
  }
  for (const e of edges) {
    adj[e.from].push(e.to);
    revAdj[e.to].push(e.from);
  }

  const topo = topologicalSort(tasks.map(t => t.id), adj);
  const dist: Record<string, number> = {};
  const prev: Record<string, string | null> = {};

  for (const id of topo) {
    dist[id] = 1;
    prev[id] = null;
    for (const pred of revAdj[id]) {
      if ((dist[pred] || 0) + 1 > dist[id]) {
        dist[id] = dist[pred] + 1;
        prev[id] = pred;
      }
    }
  }

  let end = topo[topo.length - 1];
  for (const id of topo) {
    if ((dist[id] || 0) > (dist[end] || 0)) end = id;
  }

  const path: string[] = [];
  let cur: string | null = end;
```

```
  while (cur) {
    path.unshift(cur);
    cur = prev[cur];
  }
  return path;
}

function topologicalSort(nodeIds: string[], adj: Record<string,
        string[]>): string[] {
  const inDeg: Record<string, number> = {};
  for (const id of nodeIds) inDeg[id] = 0;
  for (const id of nodeIds) {
    for (const neighbor of adj[id]) inDeg[neighbor] =
        (inDeg[neighbor] || 0) + 1;
  }

  const queue = nodeIds.filter(id => inDeg[id] === 0);
  const result: string[] = [];

  while (queue.length > 0) {
    const node = queue.shift()!;
    result.push(node);
    for (const neighbor of adj[node]) {
      inDeg[neighbor]--;
      if (inDeg[neighbor] === 0) queue.push(neighbor);
    }
  }

  return result;
}

function renderMermaid(graph: any): string {
  let out = "```mermaid\ngraph TD\n";
  for (const node of graph.tasks || graph.graph.nodes.map((id:
        string) => ({ id }))) {
    out += `  ${node.id}["${node.id}: ${(node.description ||
        node.id).substring(0, 40)}"]\n`;
  }
  for (const e of graph.graph.edges) {
    out += `  ${e.from} --> ${e.to}\n`;
  }
  out += "```";
  return out;
}

function renderDot(graph: any): string {
  let out = "digraph NanoTasks {\n  rankdir=TB;\n";
  const nodes = graph.tasks || graph.graph.nodes.map((id: string)
        => ({ id }));
  for (const node of nodes) {
    out += `  ${node.id} [label="${node.id}\\n${(node.description
        || "").substring(0, 30)}"];\n`;
  }
```

```
  for (const e of graph.graph.edges) {
    out += `  ${e.from} -> ${e.to};\n`;
  }
  out += "}";
  return out;
}

async function renderDotToSvg(dot: string): Promise<string> {
  const { execSync } = await import("child_process");
  try {
    return execSync("dot -Tsvg", { input: dot, maxBuffer: 10 *
        1024 * 1024 }).toString();
  } catch {
    return dot;
  }
}

async function renderDotToPng(dot: string): Promise<string> {
  const { execSync } = await import("child_process");
  try {
    const buf = execSync("dot -Tpng", { input: dot, maxBuffer: 10
        * 1024 * 1024 });
    return buf.toString("base64");
  } catch {
    return Buffer.from(dot).toString("base64");
  }
}

async function executeNanoTask(
  task: any, featureDir: string, evidenceDir: string, timeout:
        number, gpuOffload: boolean
): Promise<any> {
  const fs = await import("fs/promises");
  await fs.mkdir(evidenceDir, { recursive: true });

  const redScript = `${featureDir}/tests/${task.test_id}.sh`;
  const greenScript = `${featureDir}/tests/${task.id}_green.sh`;

  let redResult: any = { success: false, output: "", exitCode:
        1 };
  if (await fileExists(redScript)) {
    redResult = await runPhase("RED", redScript, timeout, true);
  } else {
    redResult = { success: true, output: "[RED script not found —
        skipping RED phase]", exitCode: 1 };
  }

  if (!redResult.success) {
    await fs.writeFile(`${evidenceDir}/verdict.json`,
        JSON.stringify({
      verdict: "FAIL", reason: "RED phase failed", task_id:
        task.id,
    }));
```

```
    return { verdict: "FAIL", task_id: task.id, phase: "RED",
        details: redResult };
  }

  const greenResults = [];
  for (let i = 0; i < 3; i++) {
    const gr = await runPhase("GREEN", greenScript, timeout,
        false);
    greenResults.push(gr);
    if (!gr.success) {
      await fs.writeFile(`${evidenceDir}/verdict.json`,
        JSON.stringify({
        verdict: "FAIL", reason: `GREEN failed at iter ${i + 1}`,
        task_id: task.id,
      }));
      return { verdict: "FAIL", task_id: task.id, phase: "GREEN",
        iteration: i + 1, details: gr };
    }
  }

  await fs.writeFile(`${evidenceDir}/verdict.json`,
        JSON.stringify({
    task_id: task.id,
    verdict: "PASS",
    evidence_class: "source_code",
    red_exit: redResult.exitCode,
    green_exit: 0,
    iterations: 3,
    timestamp: new Date().toISOString(),
    oracle: "superbridge-mcp/anti-bluff",
  }));

  return { verdict: "PASS", task_id: task.id, red: redResult,
        green_iterations: greenResults };
}

async function fileExists(p: string): Promise<boolean> {
  const fs = await import("fs/promises");
  try { await fs.access(p); return true; } catch { return false; }
}

async function loadJson(p: string): Promise<any> {
  const fs = await import("fs/promises");
  return JSON.parse(await fs.readFile(p, "utf-8"));
}

async function writeJson(p: string, data: any): Promise<void> {
  const fs = await import("fs/promises");
  const path = await import("path");
  await fs.mkdir(path.dirname(p), { recursive: true });
  await fs.writeFile(p, JSON.stringify(data, null, 2));
}
```

```
function errorResponse(taskId: string, message: string, details:
        any) {
  return {
    content: [{
      type: "text",
      text: JSON.stringify({
        task_id: taskId,
        verdict: "FAIL",
        message,
        details,
        timestamp: new Date().toISOString(),
      }, null, 2),
    }],
  };
}

function buildDependencyGraph(data: any, computeCriticalPath:
        boolean): any {
  return {
    graph: {
      directed: true,
      nodes: data.tasks.map((t: any) => ({ id: t.id, phase:
        t.phase, status: t.status || "pending" })),
      edges: data.graph.edges || [],
    },
    stats: {
      total: data.tasks.length,
      passed: data.tasks.filter((t: any) => t.status ===
        "passed").length,
      failed: data.tasks.filter((t: any) => t.status ===
        "failed").length,
      running: data.tasks.filter((t: any) => t.status ===
        "running").length,
      pending: data.tasks.filter((t: any) => t.status ===
        "pending" || !t.status).length,
      skipped: data.tasks.filter((t: any) => t.status ===
        "skipped").length,
    },
    critical_path: computeCriticalPath
      ? computeCriticalPath(data.tasks, data.graph.edges)
      : [],
  };
}

async function main() {
  const transport = new StdioServerTransport();
  await server.connect(transport);
}

main().catch(console.error);
```

C.2 MCP Server Configuration

```
{
  "mcpServers": {
    "superbridge-mcp": {
      "command": "node",
      "args": ["/path/to/superbridge-mcp/dist/index.js"],
      "env": {
        "NODE_ENV": "production",
        "EVIDENCE_BASE_DIR": "/path/to/qa-results",
        "LOG_LEVEL": "info"
      }
    }
  }
}
```

C.3 Wiring into CLI Agents

```
// Claude Code: ~/.config/claude/claude_desktop_config.json
{
  "mcpServers": {
    "superbridge-mcp": {
      "command": "node",
      "args": ["/path/to/superbridge-mcp/dist/index.js"]
    }
  }
}

// Codex: ~/.config/codex/mcp.json
{
  "servers": {
    "superbridge": {
      "transport": "stdio",
      "command": "node",
      "arguments": ["/path/to/superbridge-mcp/dist/index.js"]
    }
  }
}

// Cursor: .cursor/mcp.json
{
  "mcpServers": {
    "superbridge-mcp": {
      "command": "node",
      "args": ["/path/to/superbridge-mcp/dist/index.js"]
    }
  }
}

# Gemini CLI: ~/.gemini/mcp.yaml
servers:
```

```yaml
  superbridge-mcp:
    command: node
    args:
      - /path/to/superbridge-mcp/dist/index.js
    env:
      NODE_ENV: production
```

Part D: SuperB Integration

D.1 Integration with SuperB's 7 Commands

The `helix-nano-bridge` extension integrates with the `superb` extension's 7-command workflow as follows:

SuperB Command	Nano-Bridge Integration
`superb:init`	Sets up nano-task directories and config
`superb:plan`	Feeds plan.md into nano-task decomposition
`superb:spec`	Maps acceptance criteria to nano-task assertions
`superb:implement`	Executes nano-tasks with TDD enforcement
`superb:verify`	Runs anti-bluff oracle on all evidence
`superb:docs`	Generates nano-task status reports
`superb:ship`	Gates on 100% GREEN + all evidence captured

```yaml
# .superpowers/superb/integrations/helix-nano-bridge.yaml
superb_commands:
  init:
    runs: ["helix-nano-bridge status --format json"]
    output: "nano-tasks.json baseline"

  plan:
    runs: ["helix-nano-bridge decompose"]
    output: "nano-tasks.json"

  implement:
    pre_gate: "implementation-gate"
    runs: ["helix-nano-bridge execute"]
    output: "execution results"

  verify:
    runs: ["helix-nano-bridge status --format report --evidence"]
    output: "verification report"
```

```
  docs:
    runs: ["helix-nano-bridge graph --format mermaid"]
    output: "dependency graph"

  ship:
    gate: "all_nano_tasks_green"
    runs: ["helix-nano-bridge status --filter failed"]
    output: "ship-readiness report"
```

D.2 Implementation Gate (`implementation-gate.js`)

```
#!/usr/bin/env node
/**
 * implementation-gate.js
 *
 * Pre-implementation gate that MUST pass before any nano-task
       execution.
 * Enforces TDD discipline: RED tests must exist and must FAIL on
       the
 * clean artifact before a single line of implementation code is
       written.
 *
 * Per §11.4.43 (TDD-Fix-Discipline): RED → LIVE-ADB-PROBE → GREEN
       → VERIFY → DOCUMENT
 * Per §11.4.115 (RED-baseline-on-the-broken-artifact): RED_MODE=1
       reproduces the defect
 */

const fs = require("fs");
const path = require("path");
const { execSync } = require("child_process");

const FEATURE_DIR = process.argv[2] || process.cwd();
const NANO_FILE = path.join(FEATURE_DIR, "nano-tasks.json");
const EVIDENCE_DIR = path.join(FEATURE_DIR, "qa-results", "nano-
       tasks");
const GATE_LOG = path.join(EVIDENCE_DIR,
       "implementation_gate.log");

function log(level, msg) {
  const line = `[${new Date().toISOString()}] [${level}] ${msg}`;
  console.log(line);
  fs.appendFileSync(GATE_LOG, line + "\n");
}

function gateFail(reason, details = {}) {
  log("FAIL", reason);
  fs.writeFileSync(path.join(EVIDENCE_DIR, "gate_verdict.json"),
       JSON.stringify({
    gate: "implementation-gate",
    verdict: "FAIL",
    reason,
```

```
    details,
    timestamp: new Date().toISOString(),
  }, null, 2));
  process.exit(2);
}

function gatePass() {
  log("PASS", "All gates passed — implementation may proceed");
  fs.writeFileSync(path.join(EVIDENCE_DIR, "gate_verdict.json"),
        JSON.stringify({
    gate: "implementation-gate",
    verdict: "PASS",
    timestamp: new Date().toISOString(),
  }, null, 2));
  process.exit(0);
}

// ============================================================
// Gate 1: nano-tasks.json exists and is valid
// ============================================================
log("INFO", `Gate 1/7: Validating ${NANO_FILE}...`);

if (!fs.existsSync(NANO_FILE)) {
  gateFail("nano-tasks.json not found — run 'helix-nano-bridge
        decompose' first");
}

let nanoData;
try {
  nanoData = JSON.parse(fs.readFileSync(NANO_FILE, "utf-8"));
} catch (e) {
  gateFail(`nano-tasks.json is invalid JSON: ${e.message}`);
}

if (!nanoData.tasks || nanoData.tasks.length === 0) {
  gateFail("nano-tasks.json contains zero tasks");
}

log("INFO", `  OK: ${nanoData.tasks.length} nano-tasks found`);

// ============================================================
// Gate 2: Every nano-task has a RED test file
// ============================================================
log("INFO", `Gate 2/7: Checking RED test existence...`);

const missingTests = [];
for (const task of nanoData.tasks) {
  const testPath = path.join(FEATURE_DIR, "tests", `$
        {task.test_id}.sh`);
  if (!fs.existsSync(testPath)) {
    missingTests.push({ id: task.id, test_id: task.test_id, path:
        testPath });
```

```
  }
}

if (missingTests.length > 0) {
  gateFail(`${missingTests.length} RED tests missing`, { missing:
        missingTests });
}

log("INFO", `  OK: All ${nanoData.tasks.length} RED tests found`);

// ============================================================
// Gate 3: Evidence directory is writable
// ============================================================
log("INFO", `Gate 3/7: Checking evidence directory...`);

fs.mkdirSync(EVIDENCE_DIR, { recursive: true });

const testFile = path.join(EVIDENCE_DIR, ".write_test");
try {
  fs.writeFileSync(testFile, "test");
  fs.unlinkSync(testFile);
} catch (e) {
  gateFail(`Evidence directory not writable: ${EVIDENCE_DIR}`, {
        error: e.message });
}

log("INFO", `  OK: ${EVIDENCE_DIR} is writable`);

// ============================================================
// Gate 4: No orphan evidence from a prior run
// ============================================================
log("INFO", `Gate 4/7: Checking for stale evidence...`);

const staleVerdicts = [];
for (const task of nanoData.tasks) {
  const verdictPath = path.join(EVIDENCE_DIR, task.id,
        "verdict.json");
  if (fs.existsSync(verdictPath)) {
    staleVerdicts.push(task.id);
  }
}

if (staleVerdicts.length > 0) {
  log("WARN", `  Found ${staleVerdicts.length} stale verdicts —
        cleaning`);
  for (const id of staleVerdicts) {
    const taskDir = path.join(EVIDENCE_DIR, id);
    fs.rmSync(taskDir, { recursive: true, force: true });
  }
}

log("INFO", `  OK: Evidence directories clean`);
```

```
// ============================================================
// Gate 5: Runtime signature registry is loaded (if present)
// ============================================================
log("INFO", `Gate 5/7: Checking runtime signature registry...`);

const sigFile = path.join(FEATURE_DIR, "runtime_signatures.json");
if (fs.existsSync(sigFile)) {
  try {
    const sigs = JSON.parse(fs.readFileSync(sigFile, "utf-8"));
    log("INFO", `  OK: ${Object.keys(sigs).length} runtime
        signatures loaded`);
  } catch (e) {
    gateFail(`runtime_signatures.json is invalid: ${e.message}`);
  }
} else {
  log("WARN", `  No runtime_signatures.json — proceeding without
        runtime registry`);
}

// ============================================================
// Gate 6: Dependency graph is acyclic
// ============================================================
log("INFO", `Gate 6/7: Verifying dependency graph is acyclic...`);

const graph = nanoData.graph;
const adj = {};
const inDeg = {};

for (const node of graph.nodes) {
  adj[node] = [];
  inDeg[node] = 0;
}

for (const edge of graph.edges) {
  adj[edge.from].push(edge.to);
  inDeg[edge.to] = (inDeg[edge.to] || 0) + 1;
}

const queue = graph.nodes.filter(n => inDeg[n] === 0);
const visited = [];

while (queue.length > 0) {
  const node = queue.shift();
  visited.push(node);
  for (const neighbor of adj[node]) {
    inDeg[neighbor]--;
    if (inDeg[neighbor] === 0) queue.push(neighbor);
  }
}

if (visited.length !== graph.nodes.length) {
```

```
  const inCycle = graph.nodes.filter(n => !visited.includes(n));
  gateFail("Dependency graph contains cycles", { cyclic_nodes:
        inCycle });
}

log("INFO", `  OK: Graph is acyclic (${graph.nodes.length} nodes,
        ${graph.edges.length} edges)`);

// ============================================================
// Gate 7: Phase assignment is valid
// ============================================================
log("INFO", `Gate 7/7: Validating phase assignments...`);

const phaseFiles = {};
let phaseErrors = [];


for (const task of nanoData.tasks) {
  const key = `${task.phase}:${task.file}`;
  if (phaseFiles[key]) {
    phaseErrors.push({
      file: task.file,
      phase: task.phase,
      task1: phaseFiles[key],
      task2: task.id,
    });
  }
  phaseFiles[key] = task.id;
}


if (phaseErrors.length > 0) {
  gateFail("Phase collision detected — two tasks in same phase
        share a file", {
    collisions: phaseErrors,
  });
}

log("INFO", `  OK: Phase assignments valid ($
        {nanoData.meta.phases} phases)`);

// ============================================================
// ALL GATES PASSED
// ============================================================
gatePass();
```

D.3 TDD Enforcement Flow





Part E: Hardware Optimization

E.1 Hardware Detection and Configuration

```
#!/usr/bin/env bash
# bin/hardware_detect.sh
# Detects Threadripper NUMA, CUDA GPUs, and configures optimal
        settings

set -euo pipefail
```

```
detect_hardware() {
    local HARDWARE_REPORT=""

    # CPU detection
    HARDWARE_REPORT+="=== CPU ===\n"
    local CPU_MODEL
    CPU_MODEL=$(grep -m1 'model name' /proc/cpuinfo | cut -d: -f2
        | xargs)
    HARDWARE_REPORT+="Model: ${CPU_MODEL}\n"

    local CPU_CORES
    CPU_CORES=$(nproc)
    HARDWARE_REPORT+="Cores: ${CPU_CORES}\n"

    # Threadripper / NUMA detection
    local NUMA_NODES=0
    if command -v numactl &>/dev/null; then
        NUMA_NODES=$(numactl --hardware 2>/dev/null | grep -c
        'node [0-9]' || echo 0)
    fi

    if [[ "${NUMA_NODES}" -gt 1 ]]; then
        HARDWARE_REPORT+="NUMA: ${NUMA_NODES} nodes (Threadripper
        multi-die detected)\n"
        HARDWARE_REPORT+="NUMA-AWARE scheduling: ENABLED\n"
    else
        HARDWARE_REPORT+="NUMA: single-node (UMA)\n"
    fi

    # GPU detection
    HARDWARE_REPORT+="\n=== GPU ===\n"
    local CUDA_COUNT=0
    local ROCM_COUNT=0

    if command -v nvidia-smi &>/dev/null; then
        CUDA_COUNT=$(nvidia-smi -L 2>/dev/null | wc -l)
        HARDWARE_REPORT+="CUDA GPUs: ${CUDA_COUNT}\n"
        nvidia-smi --query-gpu=name,memory.total --
        format=csv,noheader 2>/dev/null | \
            while IFS=, read -r NAME MEM; do
                HARDWARE_REPORT+="  - ${NAME} (${MEM})\n"
            done
        HARDWARE_REPORT+="CUDA toolkit: $(nvcc --version 2>/dev/
        null | grep 'release' | awk '{print $5,$6}' || echo 'not
        found')\n"
    elif command -v rocminfo &>/dev/null; then
        ROCM_COUNT=$(rocminfo 2>/dev/null | grep -c 'Name:' ||
        echo 0)
        HARDWARE_REPORT+="ROCm GPUs: ${ROCM_COUNT}\n"
    else
        HARDWARE_REPORT+="GPU: None detected (CPU-only mode)\n"
    fi
```

```
    # Memory
    HARDWARE_REPORT+="\n=== Memory ===\n"
    local TOTAL_MEM_KB
    TOTAL_MEM_KB=$(grep MemTotal /proc/meminfo | awk '{print $2}')
    local TOTAL_MEM_GB=$((TOTAL_MEM_KB / 1024 / 1024))
    HARDWARE_REPORT+="Total RAM: ${TOTAL_MEM_GB} GB\n"

    local AVAIL_MEM_KB
    AVAIL_MEM_KB=$(grep MemAvailable /proc/meminfo | awk '{print
        $2}')
    local AVAIL_MEM_GB=$((AVAIL_MEM_KB / 1024 / 1024))
    HARDWARE_REPORT+="Available RAM: ${AVAIL_MEM_GB} GB\n"

    # Parallelism budget
    local SAFE_JOBS=$((CPU_CORES / 2))
    [[ "${SAFE_JOBS}" -lt 1 ]] && SAFE_JOBS=1
    local SAFE_PARALLELISM=${SAFE_JOBS}

    if [[ "${NUMA_NODES}" -gt 1 ]]; then
        SAFE_PARALLELISM=$((CPU_CORES / NUMA_NODES))
    fi

    HARDWARE_REPORT+="\n=== Recommended Settings ===\n"
    HARDWARE_REPORT+="Parallelism (nano-tasks): $
        {SAFE_PARALLELISM}\n"
    HARDWARE_REPORT+="Build jobs: ${SAFE_JOBS}\n"
    HARDWARE_REPORT+="GPU offload: $([[ "${CUDA_COUNT}" -gt 0 ||
        "${ROCM_COUNT}" -gt 0 ]] && echo 'ENABLED' || echo
        'disabled')\n"
    HARDWARE_REPORT+="NUMA-aware: $([[ "${NUMA_NODES}" -gt 1 ]]
        && echo 'ENABLED' || echo 'disabled')\n"

    echo -e "${HARDWARE_REPORT}"

    # Write config file
    cat > "${FEATURE_DIR:-.}/.helix-hardware.json" <<HEREDOC
{
  "cpu": {
    "model": "${CPU_MODEL}",
    "cores": ${CPU_CORES},
    "numa_nodes": ${NUMA_NODES},
    "numa_aware": $([[ "${NUMA_NODES}" -gt 1 ]] && echo 'true' ||
        echo 'false')
  },
  "gpu": {
    "cuda_count": ${CUDA_COUNT},
    "rocm_count": ${ROCM_COUNT},
    "offload_enabled": $([[ "${CUDA_COUNT}" -gt 0 || "$
        {ROCM_COUNT}" -gt 0 ]] && echo 'true' || echo 'false'),
    "cuda_device": 0
  },
  "memory": {
```

```
    "total_gb": ${TOTAL_MEM_GB},
    "available_gb": ${AVAIL_MEM_GB}
  },
  "recommended": {
    "parallelism": ${SAFE_PARALLELISM},
    "build_jobs": ${SAFE_JOBS}
  }
}
HEREDOC

    echo "Wrote hardware config to .helix-hardware.json"
}

detect_hardware "$@"
```

E.2 Environment Template (`.env.template`)

```
# ================================================================
# Helix Nano-Bridge Hardware Configuration Template
# Copy to .env and customize for your hardware
# ================================================================

# === LLM Configuration ===
HELIX_LLM_MODEL=helix-nano
HELIX_LLM_FALLBACK=deepseek-v4-pro
HELIX_LLM_ENDPOINT=https://api.helix.ai/v1
HELIX_LLM_API_KEY=sk-REPLACE_ME
HELIX_LLM_TEMPERATURE=0.0
HELIX_LLM_MAX_TOKENS=32768

# === Hardware Detection ===
# Set to 'auto' to auto-detect or provide explicit values
HELIX_CPU_CORES=auto
HELIX_CPU_NUMA_NODES=auto
HELIX_NUMA_AWARE=true

# === GPU Configuration ===
# Set to 'auto' to auto-detect
HELIX_GPU_ENABLED=true
HELIX_GPU_BACKEND=auto
HELIX_CUDA_DEVICE=0
HELIX_GPU_MEMORY_FRACTION=0.85

# === Parallelism Budget ===
# 0 means auto-compute from hardware
HELIX_PARALLEL_NANO_TASKS=0
HELIX_PARALLEL_BUILD_JOBS=0
HELIX_PARALLEL_LLM_REQUESTS=4

# === Memory Budget ===
# Per §12.6: never exceed 60% of total system RAM
```

```
HELIX_MEMORY_MAX_PCT=60
HELIX_MEMORY_BUDGET_GB=0

# === TDD Settings ===
HELIX_TDD_ENFORCEMENT=strict
HELIX_ANTI_BLUFF_MODE=full
HELIX_RED_MODE_DEFAULT=1
HELIX_CONSISTENCY_ITERATIONS=3

# === MCP Server ===
SUPERBRIDGE_MCP_ENABLED=true
SUPERBRIDGE_MCP_PORT=9595
SUPERBRIDGE_MCP_HOST=127.0.0.1

# === Evidence & Logging ===
HELIX_EVIDENCE_DIR=./qa-results/nano-tasks
HELIX_LOG_LEVEL=info
HELIX_CAPTURE_ARTIFACTS=true
HELIX_ARTIFACT_FORMAT=jsonl

# === SuperB Integration ===
SUPERB_BRIDGE_ENABLED=true
SUPERB_FEATURE_DIR=.specify/features

# === Network ===
HELIX_MCP_TIMEOUT=30
HELIX_LLM_TIMEOUT=300
HELIX_TASK_TIMEOUT=3600

# === Retry Configuration ===
HELIX_MAX_RETRIES=3
HELIX_RETRY_BACKOFF=exponential
HELIX_RETRY_BASE_DELAY_MS=1000
```

E.3 Distribution Script (`pack.sh`)

```
#!/usr/bin/env bash
set -euo pipefail

VERSION="${1:-1.0.0}"
RELEASE_DIR="helix-nano-bridge-${VERSION}"
ARCHIVE_NAME="${RELEASE_DIR}.tar.gz"

echo "=== Helix Nano-Bridge Packager v${VERSION} ==="
echo "Packaging ${RELEASE_DIR}..."

rm -rf "${RELEASE_DIR}" "${ARCHIVE_NAME}"
mkdir -p "${RELEASE_DIR}"/{bin,lib,spec,skills,mcp,config,docs}

# Core scripts
```

```
cp bin/helix-nano-bridge-* "${RELEASE_DIR}/bin/" 2>/dev/null ||
        true
cp lib/nano_bridge_common.sh "${RELEASE_DIR}/lib/" 2>/dev/null ||
        true
cp lib/anti_bluff_oracle.sh "${RELEASE_DIR}/lib/" 2>/dev/null ||
        true

# SpecKit extension
cp -r spec/helix-nano-bridge/ "${RELEASE_DIR}/spec/" 2>/dev/null
        || true
cp extension.yml "${RELEASE_DIR}/" 2>/dev/null || true

# Superpowers skills
cp -r skills/nano-task-*/ "${RELEASE_DIR}/skills/" 2>/dev/null ||
        true

# MCP server
cp -r mcp/superbridge-mcp/ "${RELEASE_DIR}/mcp/" 2>/dev/null ||
        true

# Config templates
cp .env.template "${RELEASE_DIR}/" 2>/dev/null || true
cp hardware_detect.sh "${RELEASE_DIR}/bin/" 2>/dev/null || true

# Docs
cp README.md LICENSE CHANGELOG.md "${RELEASE_DIR}/" 2>/dev/null
        || true
cp -r docs/ "${RELEASE_DIR}/docs/" 2>/dev/null || true

# Install script
cat > "${RELEASE_DIR}/install.sh" <<'INSTALL_SCRIPT'
#!/usr/bin/env bash
set -euo pipefail

INSTALL_DIR="${1:-${HOME}/.helix-nano-bridge}"

echo "Installing Helix Nano-Bridge to ${INSTALL_DIR}..."

mkdir -p "${INSTALL_DIR}"
cp -r bin lib spec skills mcp config "${INSTALL_DIR}/"
cp extension.yml .env.template "${INSTALL_DIR}/"

# Register with SpecKit
if command -v specify &>/dev/null; then
    specify extension add helix-nano-bridge \
        --from "${INSTALL_DIR}" \
        --version "$(grep version extension.yml | head -1 | awk
        '{print $2}')"
fi

# Register with Superpowers
if command -v superpowers &>/dev/null; then
```

```
    superpowers plugin install nano-task-execution --from "$
        {INSTALL_DIR}/skills/nano-task-execution"
    superpowers plugin install nano-task-decompose --from "$
        {INSTALL_DIR}/skills/nano-task-decompose"
fi

# Install MCP server config
MCP_CONFIG_DIR="${HOME}/.config/claude"
mkdir -p "${MCP_CONFIG_DIR}"
if [[ -f "${MCP_CONFIG_DIR}/claude_desktop_config.json" ]]; then
    echo "MCP config exists at ${MCP_CONFIG_DIR} — add
        superbridge-mcp manually"
else
    echo '{"mcpServers":{"superbridge-mcp":
        {"command":"node","args":["'"${INSTALL_DIR}"'/mcp/
        superbridge-mcp/dist/index.js"]}}}' > "${MCP_CONFIG_DIR}/
        claude_desktop_config.json"
fi

# Build MCP server if TypeScript sources present
if [[ -f "${INSTALL_DIR}/mcp/superbridge-mcp/package.json" ]];
        then
    echo "Building MCP server..."
    (cd "${INSTALL_DIR}/mcp/superbridge-mcp" && npm install && npm
        run build) || \
        echo "WARNING: MCP server build failed — install
        dependencies manually"
fi

echo ""
echo "Installation complete."
echo "  Extension: ${INSTALL_DIR}"
echo "  Run: specify helix-nano-bridge --help"
echo "  Detect hardware: bash ${INSTALL_DIR}/bin/
        hardware_detect.sh"
echo ""
INSTALL_SCRIPT

chmod +x "${RELEASE_DIR}/install.sh"
chmod +x "${RELEASE_DIR}/bin/"*

# Create archive
tar -czf "${ARCHIVE_NAME}" "${RELEASE_DIR}"
SHA256=$(sha256sum "${ARCHIVE_NAME}" | awk '{print $1}')

echo ""
echo "Package ready: ${ARCHIVE_NAME}"
echo "SHA256: ${SHA256}"
echo "Size: $(du -h "${ARCHIVE_NAME}" | cut -f1)"

# Cleanup
rm -rf "${RELEASE_DIR}"
```

```
# Optional: create release manifest
cat > "release-${VERSION}.json" <<MANIFEST
{
  "name": "helix-nano-bridge",
  "version": "${VERSION}",
  "archive": "${ARCHIVE_NAME}",
  "sha256": "${SHA256}",
  "size_bytes": $(stat --printf="%s" "${ARCHIVE_NAME}"),
  "created": "$(date -u +%Y-%m-%dT%H:%M:%SZ)",
  "contents": {
    "extension": "SpecKit extension (extension.yml + 5 commands)",
    "skills": "2 Superpowers skills (nano-task-execution, nano-
        task-decompose)",
    "mcp_server": "superbridge-mcp (5 tools, TypeScript)",
    "hardware": "Auto-detection for Threadripper NUMA + CUDA/
        ROCm",
    "scripts": "decompose, execute, graph, status, retry"
  },
  "minimum_requirements": {
    "node": ">=18",
    "bash": ">=5",
    "specify": ">=2.0.0",
    "superpowers": ">=3.1.0"
  }
}
MANIFEST

echo "Release manifest: release-${VERSION}.json"
echo "Done."
```