Helix Constitution-Powered SpecKit-Superpowers Bridge: Implementation Documentation

Revision: 1 **Last modified:** 2026-07-24T12:00:00Z **Description:** Master index and architecture overview for the Helix Constitution–powered SpecKit–Superpowers Bridge implementation. **Maintainer:** HelixDevelopment **Scope:** `constitution/docs/research/extensions/speckit_superpowers/implementation/`

Table of Contents

1. Executive Summary
2. System Architecture
    - Architecture Diagram
    - Layer 1 — Developer Workstation
    - Layer 2 — Spec-Kit Core (Governance Layer)
    - Layer 3 — SuperSpec Bridge (Orchestration Layer)
    - Layer 4 — SuperB Extension (Discipline Enforcement)
    - Layer 5 — SuperBridge MCP (Execution Layer)
    - Layer 6 — Helix LLM (Inference Layer)
    - Layer 7 — Distributed Host Cluster
3. Data Flow
    - Feature Lifecycle Through the Layers
    - Nano-Task Decomposition Flow
4. Document Index
5. Quick Start

6. Key Design Decisions
7. Constitutional Mandates Applied
8. Directory Structure
9. References

Executive Summary

This documentation defines the **Helix Constitution–Powered SpecKit–Superpowers Bridge** — a unified, multi-layer development system that integrates the full SDD (Specification-Driven Development) lifecycle of Spec-Kit with the agent-skill ecosystem of Superpowers, orchestrated through the SuperSpec and SuperB bridge extensions, with distributed inference powered by Helix LLM backed by a `llama.cpp` RPC cluster.

Problem It Solves

Modern software development with LLM-assisted agents suffers from four structural problems:

Problem	Manifestation	Root Cause
Context fragmentation	Each tool (specifier, planner, coder, reviewer) runs in its own silo; no shared understanding of what is being built	No canonical bridge between specification artifacts and execution tools
Discipline drift	Specifications written but never consulted during implementation; plans that do not reflect reality; "fix it later" culture	No mechanical enforcement that the spec *governs* the work
Inference latency & cost	Centralized LLM APIs introduce round-trip latency, rate limits, and per-token billing that blocks autonomous-loops	No local-first distributed inference pipeline
Anti-bluff gap	Tests pass but features do not work; configuration-only PASS; metadata-only PASS; grep-without-runtime PASS	No §11.4 positive-evidence mandate wired into the development lifecycle

This bridge closes all four gaps by composing Spec-Kit's `specify → plan → tasks → implement` lifecycle with Superpowers' `brainstorm / debug / review / test` skills under a single Constitution-governed execution framework, all powered by local distributed inference that keeps the autonomous loop running without API rate-limit interruptions.


What This Documentation Covers


1. The **7-layer system architecture** with each layer's responsibilities, technologies, and contractual interfaces.
2. The **data flow** — how a natural-language feature description moves through the layers and emerges as tested, verified, checked-in code.
3. The **nano-task decomposition engine** — how Helix LLM breaks tasks into sub-100-line units suitable for subagent-driven execution per §11.4.70.
4. The **constitutional enforcement points** — where the Helix Constitution §11.4 anti-bluff covenant, TDD-fix-discipline, mechanical enforcement, and reporting-directive system plug into the bridge.


5. The **onboarding path** — how any consuming project (e.g., ATMOSphere) integrates the Constitution submodule, wires its CLI-agent context carriers, installs the bridge extensions, and goes from zero to full autonomous-loop development.


System Architecture


Architecture Diagram


Layer 7: Distributed Host Cluster
llama.cpp RPC Node 1 (GPU 0)
llama.cpp RPC Node 2 (GPU 1)
llama.cpp RPC Node 3 (GPU 2)
llama.cpp RPC Node N (GPU N)
Layer 6: Helix LLM (Inference Layer)
Gateway (API router, load-balancer, fallback)
Brain (planner, reasoner, prompt-optimizer)
Knowledge (RAG, embeddings, vector store)
Agents (subagent dispatch, lifecycle, registry, respawn)


Layer 5: SuperBridge MCP (Execution Layer)
MCP Server exposing Superpowers skill suite:
brainstorm | debug | review | test-gen | red-green-refactor |
analyze-arch | refactor | document | search | more...
Tool contracts: each tool emits structured (PASS/FAIL + evidence path) per §11.4.69; self-validated with golden-good/golden-bad fixtures per §11.4.107(10)
Layer 4: SuperB Extension (Discipline Enforcement)


check
brainstorm
implementation
critique /
(pre-
(solution
-gate
debug / finish
gate)
design)
(TDD RED-first)
(verify+close)
Gate contracts:
Each gate emits a PASS/FAIL verdict backed by
captured physical evidence; no metadata-only PASS
Layer 3: SuperSpec Bridge (Orchestration
Layer)
status
brainstorm
tasks
execute
review
(context
(solution
(nano-
(subagent
(indep.
snapshot
design)
decomp)
dispatch)
review)


Layer 2: Spec-Kit Core (Governance Layer)
Constitution (mandates, invariants, enforcement)
Specify (feature specification with accept- ance criteria)
Plan (architectural design, research)
Tasks (nano-task dependency DAG)
Implement (subagent-driven per §11.4.70, TDD RED→GREEN per §11.4.43, four-layer coverage per §11.4.4(b), independent code-review per §11.4.125/§11.4.142)
Layer 1: Developer Workstation



Layer — Developer Workstation

The physical development machine running the CLI agent, git repositories, container runtime, MCP servers, and the local Helix LLM Gateway instance.

Component	Specification	Role
CPU	AMD Threadripper 64-core (128 threads)	Parallel subagent execution (§11.4.70/.103), AOSP builds, multi-track development
RAM	256 GB DDR5 ECC (384 GB peak per §12.6 ceiling)	Bounded by §12.6 60% memory budget; `bounded_run` enforced
GPU	NVIDIA RTX A6000 32 GB VRAM	Local inference for Helix LLM Gateway; offloads smaller models
Storage	NVMe RAID, ≥4 TB	btrfs CoW for feature work-streams per §11.4.167
Container Runtime	Podman rootless (§11.4.161)	AOSP 42 GB containerised builds per §12.9
MCP Servers	CodeGraph, SuperBridge, filesystem	Tool-accessible subprocesses providing structured agent capabilities
CLI Agent	Claude Code / Cursor / Gemini CLI / Qwen Code	The human-facing agent conducting the autonomous loop (§11.4.126)
Git Layout [2]	Multi-track with own `.git` per track (§11.4.179)	Isolated concurrent development streams

Layer — Spec-Kit Core (Governance Layer)

The canonical Spec-Kit SDD toolkit, extended by the Helix Constitution. This is the **source of truth** for what is being built and how.

Phase	Tool	Input	Output	Constitutional Binding
Constitution	`speckit-constitution`	Project principles, invariants	Constitution file with mandates and enforcement points	§11.4 (anti-bluff covenant), §11.4.6 (no-guessing), §11.4.10 (credentials), §11.4.75 (mechanical enforcement), §11.4.65 (documentation exports)
Specify	`speckit-specify`	Natural-language feature description	`spec.md` with acceptance criteria, edge cases, topology constraints	§11.4.91 (≥6-word/≥40-char clear meaning), §11.4.146 (reproduce-first test workflow)
Plan	`speckit-plan`	`spec.md` + `constitution.md`	`plan.md` with architecture, data-model, research citations, contract definitions	§11.4.8 (deep-web-research citation), §11.4.99 (latest authoritative sources), §11.4.150 (multi-angle research pass)
Tasks	`speckit-tasks`	`spec.md` + `plan.md`	`tasks.md` with dependency-ordered nano-task DAG	§11.4.70 (subagent-driven default), §11.4.58 (PWU parallel pipeline)
Implement	`speckit-implement` / `speckit-speckit-super-powers-bridge-execute`	`tasks.md` → bridge dispatch	Checked-in code with four-layer coverage	§11.4.43 (TDD RED→GREEN), §11.4.4(b) (four-layer coverage), §11.4.125/§11.4.142 (code review)

Governance enforcement — The Constitution file produced by `speckit-constitution` contains:

- **Invariants** — assertions that must hold true at every gate (e.g., "no commit without captured evidence")
- **Gates** — `CM-*` pre-build / post-build / pre-commit / pre-push gates with paired §1.1 meta-test mutations
- **Propagation directives**[3] — §11.4.17 classification markers that determine which rules propagate to submodules and dependencies

Layer — SuperSpec Bridge (Orchestration Layer)

The SuperSpec bridge sits between Spec-Kit's governance artifacts and the execution layer. It translates `spec.md` / `plan.md` / `tasks.md` into structured workflows that can be dispatched to subagents.

Command	Purpose	Input	Output
`superspec status`	Capture current project context snapshot	All `.md` artifacts + git state	Structured context JSON fed to every sub-agent dispatch
`superspec brainstorm`	Generate solution approaches	`spec.md` + `plan.md` + constitution	Ranked solution alternatives with trade-offs
`superspec tasks`	Nano-task decomposition DAG	`spec.md` + `plan.md` + `tasks.md`	Sub-100-line tasks with file-scope manifests per §11.4.58
`superspec execute`	Subagent dispatch loop	Nano-task DAG + context snapshot	Checked-in code with verdict files per task
`superspec review`	Independent code-review dispatch	Change diff + context snapshot	Review findings + GO/NO-GO verdict per §11.4.142

Nano-task contract — Each nano-task MUST:

- Be ≤100 lines of net-new / changed code (breaker rule: a task exceeding this splits)
- Declare a file-scope manifest (exactly which files it touches, per §11.4.58 L4 locking)
- Carry a `RED_MODE=1` acceptance test BEFORE the implementation (per §11.4.115/§11.4.146)
- Emit a machine-written verdict file (per §11.4.115(F)) with the pre-fix artifact fingerprint
- Be independently reviewable (per §11.4.142 — a nano-task is the atomic review unit)

Layer — SuperB Extension (Discipline Enforcement)

The SuperB extension enforces Spec-Kit discipline mechanically — no implementation proceeds past any gate that fails its §11.4.107(10) golden-good/golden-bad self-validation.

Gate	When It Fires	What It Checks	Pass Condition
`superb check`	Pre-specify, pre-plan, pre-implement	Constitution invariants, spec completeness, plan consistency	All `CM-*` gates GREEN
`superb brainstorm`	After `speckit-plan`, before `speckit-tasks`	Solution design covers all acceptance criteria, cites research, enumerates alternatives	Zero unexamined acceptance criteria
`superb implementation-gate`	Before `superspec execute` dispatches any subagent	RED test exists per nano-task, file-scope manifests declared, pre-build gates wired	All RED tests parse with `sh -n` / `bash -n` per §11.4.67
`superb critique`	After each nano-task's subagent returns	Independent adversarial review of the subagent's output	Zero unreviewed outputs; findings iterate to GO per §11.4.134
`superb debug`	Triggered by any test FAIL or critique finding	Systematic-debugging per §11.4.102	Root cause identified at `file:line`, not "the test timed out"
`superb finish`	After all nano-tasks complete + review clean	Full-suite retest per §11.4.40, meta-test mutation sweep per §1.1, Issues.md→Fixed.md migration per §11.4.19	Zero FAIL, zero WARN, zero uncovered verdicts

Discipline enforcement is mechanical, not advisory — per §11.4.205, every gate is a `commit_all.sh`-wrapper refusal, not a prose suggestion. The gate's paired §1.1 mutation MUST FAIL the gate; a gate whose mutation passes is a bluff gate and a release blocker.

Layer — SuperBridge MCP (Execution Layer)

An MCP (Model Context Protocol) server that exposes the Superpowers skill suite as tool-callable endpoints consumable by any MCP-compatible CLI agent.

Tool	Superpowers Skill	Contract
`super-bridge_brainstorm`	`super-powers:brainstorming`	Input: problem statement + constraints. Output: ranked alternatives with evidence per §11.4.69.
`superbridge_debug`	`superpowers:systematic-debugging`	Input: failure evidence (logcat, tombstone, crash dump). Output: `file:line` root cause + blast radius.
`super-bridge_review`	`superpowers:executing-code-review`	Input: diff + context. Output: findings classified (BLOCKING/WARNING/NIT) per §11.4.134.
`super-bridge_test_gen`	`superpowers:writing-tests`	Input: function signatures + spec. Output: TDD RED test with four-layer coverage.
`super-bridge_red_green`	`superpowers:executing-testing-tdd`	Input: RED test. Output: GREEN implementation + verdict file per §11.4.115(F).
`super-bridge_analyze`	`superpowers:systematic-debugging` (impact)	Input: change diff. Output: §11.4.145 eight-angle impact research report.
`super-bridge_refactor`	Writing clean / refactoring code	Input: target file + goal. Output: refactored code with preserved behaviour proven by tests.
`super-bridge_document`	`superpowers:writing-documentation`	Input: code + context. Output: §11.4.44 revision-headed, §11.4.65 four-format-exported doc.

Tool	Superpowers Skill	Contract
`super-bridge_search`	Web research per §11.4.8 / §11.4.99 / §11.4.150	Input: research question + angle set. Output: cited findings with URLs + access dates.

MCP server requirements:

- Runs rootless per §11.4.161 (no rootful Docker; podman-compose or systemd user unit)
- Emits structured `conduit.events.jsonl` per §11.4.116 (append-only event stream)
- All verdicts carry `evidence_path` per §11.4.69
- Self-validated with golden-good + golden-bad + negative-control fixtures per §11.4.107(10)

Layer — Helix LLM (Inference Layer)

The Helix LLM distributed inference system provides **local-first, zero-cost-per-token** inference powering the entire bridge pipeline.

Component	Role	Technology
Gateway	API router, load-balancer, fallback-orchestrator, rate-limit manager	Go HTTP server with RPC client pool; routes to local instance first, then remote cluster nodes
Brain	Planner (task decomposition), reasoner (systematic debugging per §11.4.102), prompt-optimizer (constitution-aware system prompts)	Helix LLM model loaded via `llama.cpp`; prompt templates keyed to skill
Knowledge	RAG (Retrieval-Augmented Generation) with vector embeddings of all project specs, plans, constitution, and codebase	`llama.cpp` embedding endpoint + `chromadb` / `qdrant` vector store
Agents	Subagent dispatch lifecycle, registry per §11.4.147, respawn-on-crash per §11.4.147(b), verdict tracking per §11.4.116	Go agent orchestration calling the Gateway

Gateway routing logic:

```
Request arrives at Gateway
  ├── Can the local GPU handle it? (check VRAM available, model loaded)
  │     YES → route to local llama.cpp instance
  │     NO  → check remote cluster health
  │              ├── N ≥ 1 nodes available → round-robin to remote RPC
nodes
  │              └── N = 0 nodes available → fallback to Helix LLM cloud
API
  │                                          or Operator-blocked per
§11.4.21
  └── Return response to caller
```

Models supported (2026-07-24):

- **Fable** (`deepseek-v4-pro`) — architecture design, code review (§11.4.209), merge-conflict resolution (§11.4.211)

- **Opus** (`claude-opus-4-20250514`) — fallback for Fable-only tasks, systematic debugging
- **Helix-local**[7] (custom fine-tune on RK3588/ATMOSphere corpus) — nano-task implementation, test generation, documentation

Layer — Distributed Host Cluster

A pool of machines running `llama.cpp` in RPC-server mode, providing horizontally-scalable inference capacity.

Node Type	Hardware	Role	Typical Model Assignment
GPU Node	≥1 × RTX 4090 / A6000 / H100	High-throughput batch inference	Fable (32B+), Opus (large models)
CPU Node	≥64-core, ≥128 GB RAM	Inference for smaller models, RAG embedding generation	Helix-local (7-13B), embeddings
Edge Node	Orange Pi 5 Max / RK3588 (16 GB)	Inference at the edge for on-device agents	Tiny (1-3B) models for on-device classification

RPC configuration (per node `llama-server` invocation):

```
# On each cluster node:
llama-server \
  --model /models/deepseek-v4-pro-Q4_K_M.gguf \
  --host 0.0.0.0 \
  --port 8080 \
  --n-gpu-layers 40 \
  --ctx-size 32768 \
  --parallel 4 \
  --cont-batching \
  --mlock
```


Health monitoring:


- Per-node heartbeat at 5 s interval (via `/health` endpoint)

- Gateway auto-evicts unresponsive nodes after 3 consecutive missed heartbeats
- Re-admission requires 5 consecutive successful heartbeats (hysteresis prevents flapping)
- All node state changes logged to `conduit.events.jsonl` per §11.4.116

Data Flow

Feature Lifecycle Through the Layers


Operator prompt: "Add multi-channel audio passthrough for Dolby TrueHD"
L7: Helix LLM Brain classifies intent → "Feature", enriches with RAG context (existing audio HAL docs, ALSA config, ES8388 codec spec, HDMI EDID passthrough constraints)
enriched prompt + context
L2: speckit-specify generates spec.md:
- Feature: Dolby TrueHD passthrough over HDMI
- Acceptance criteria: Arvus AVR reports Codec-In-Use == "Dolby TrueHD" when TrueHD stream is played
- Edge cases: fallback to PCM on non-TrueHD sink, channel count mismatch, sample-rate negotiation
- Topology constraints: D1 (HDMI sink present), D2 (no sink)
spec.md
L2: speckit-plan generates plan.md:
- Research: HDMI 2.1 audio infoframe spec, CEA-861, ALSA IEC958 passthrough driver implementation, Rockchip audio HAL codec_config path
- Architecture: modify audio_hw.c out_set_parameters, add TrueHD codec profile to audio_policy_config, add Arvus sink-probe assertion to test harness
- Contract: audio_hw.c:audio_out_set_parameters() must accept AUDIO_FORMAT_TRUEHD and set IEC958 non-audio bit
plan.md
L2: speckit-tasks generates tasks.md:
T1: [RED] test_audio_truehd_passthrough_red.sh — captures pre-fix Arvus state (Codec-In-Use != TrueHD)
T2: audio_hw.c: add TrueHD format to supported codecs
T3: audio_policy_config_hifi.xml: register TrueHD devicePort
T4: Arvus probe assertion in test harness
T5: [GREEN] T1 flipped to RED_MODE=0 — captures post-fix Arvus state (Codec-In-Use == TrueHD)
Dependency DAG: T1 → T2,T3 → T4 → T5


tasks.md
L3+L4+L5: SuperSpec + SuperB + SuperBridge execute loop:
superb check → superspec status → superspec tasks (nano) →
→ superb implementation-gate (verify RED tests) →
→ superspec execute (dispatch nano-subagents per task) →
→ superb critique (review each subagent output) →
→ superb debug (fix any findings) →
→ superb check (re-verify) → loop until GO
Each nano-task subagent:
1. Reads context snapshot (superspec status)
2. Reads spec + plan + tasks
3. Reads existing code via CodeGraph MCP
4. Writes RED test first (§11.4.43 step 1)
5. Writes implementation (§11.4.43 step 3)
6. Runs RED test → GREEN (§11.4.43 step 4)
7. Writes verdict file + evidence path (§11.4.115(F))
8. Submits for review
completed nano-tasks + verdicts
L2: speckit-converge assesses remaining gaps, appends to
tasks.md any unbuilt work
Final gate (§11.4.40 full-suite):
- pre_build_verification.sh → ALL GREEN
- post_build_verification.sh → ALL GREEN
- On-device (D1+D2) test_all_fixes.sh → ALL GREEN
- meta_test_false_positive_proof.sh → ALL MUTATIONS FAIL
- HelixQA Challenge sweep → ALL GREEN
- Issues.md → Fixed.md migration → COMMITTED
- Tag created + pushed to all remotes + submodules

Nano-Task Decomposition Flow

The SuperSpec bridge's nano-task decomposer (backed by Helix LLM Brain) transforms Spec-Kit tasks into subagent-dispatchable units:

```
Input: tasks.md task "T2: audio_hw.c: add TrueHD format to supported
codecs"

Step 1 — File-scope partition (§11.4.58 L4):
  ├── NT2a: audio_hw.c: add AUDIO_FORMAT_TRUEHD to format enum (7 lines)
  ├── NT2b: audio_hw.c: add TrueHD case to out_set_parameters() (23 lines)
  └── NT2c: audio_hw.c: add TrueHD pcm_config entry (12 lines)

Step 2 — Dependency resolution:
  ├── NT2a (no deps) → dispatchable immediately
  ├── NT2b (depends on NT2a — needs the enum value) → queued after NT2a
  └── NT2c (depends on NT2a + NT2b) → queued after NT2b

Step 3 — Parallel dispatch (when deps permit):
  ┌──────────────────────────────────────────────┐
  │ Queue: [NT2a]                                │
  │ Dispatch NT2a → subagent-1                   │
  │   NT2a completes → enqueue NT2b              │
  │     Dispatch NT2b → subagent-2               │
  │       NT2b completes → enqueue NT2c          │
  │         Dispatch NT2c → subagent-3           │
  │           NT2c completes → done              │
  └──────────────────────────────────────────────┘

Step 4 — Per-nano-task verdict:
  NT2a/verdict.json: {"id":"NT2a","status":"PASS","red-exit":1,"green-
exit":0,
                      "artifact-fingerprint":"a3f8...","evidence":"qa-
results/.../NT2a/"}

Step 5 — Merge gate (§11.4.41):
  All nano-tasks for T2 complete → merge subagent outputs → superb
critique →
  → T2 complete → ready for T3 dispatch
```

Nano-task size rule (mechanical): The decomposer counts net-new/changed lines. A task producing >100 net-new/changed lines is automatically split. A split task <5 lines merges back into its parent. This bounds every subagent's context to ≤100 lines of code-under-test + surrounding context.

Document Index

Document	Path	Description
Architecture Deep Dive	`01_architecture/`	Detailed layer-by-layer architecture with component diagrams, interface definitions, and contract specifications
SpecKit Extensions	`02_extensions/`	Custom Spec-Kit skill extensions (`speckit-superpowers-bridge-*`), manifest definitions, extension installation guide
Helix LLM Integration	`03_helix_llm/`	Gateway configuration, Brain prompt templates, Knowledge RAG pipeline, Agents orchestration engine, llama.cpp RPC backend setup
TDD & QA Pipeline	`04_tdd_qa/`	TDD workflow automation, RED→GREEN verdict pipeline, four-layer test coverage, HelixQA Challenge bank integration, quality-gate configuration
Deployment & Operations	`05_deployment/`	Container setup (podman-compose), MCP server deployment, multi-node cluster provisioning, health monitoring, backup/restore
Risk & Mitigation	`06_risk/`	Risk register, failure-mode analysis, circuit-breaker design, fallback chains, rollback procedures
Proof-of-Concept	`poc/`	Working POC walkthrough, sample feature lifecycle trace, benchmark results, known limitations

Quick Start

Prerequisites

Require-ment	Minimum	Verified Command
Git	2.40+	`git --version`
Podman	4.0+ (rootless)	`podman info | grep root-less`
Python	3.11+	`python3 --version`
Node.js	20+ (for MCP servers)	`node --version`
Go	1.22+ (for Helix LLM Gateway / Agents)	`go version`
llama.cpp	Built with RPC support	`llama-server --help | grep rpc`
Disk space	≥50 GB free (container images + models)	`df -h /var/lib/containers`

Step — Add the Constitution Submodule

```
# In the consuming project's root (e.g., /mnt/track1/atmosphere-t1):
git submodule add git@github.com:HelixDevelopment/helix_constitution.git constitution
git submodule update --init --recursive
```

Step — Wire CLI-Agent Context Carriers

Add the inheritance pointer to the consuming project's context carriers:

CLAUDE.md (project root):

```
## INHERITED FROM constitution/CLAUDE.md

> Base agent rules: `constitution/CLAUDE.md` ...
```

AGENTS.md (project root):

```
## INHERITED FROM constitution/AGENTS.md

> Base agent rules: `constitution/AGENTS.md` ...
```

Do the same[3] for `QWEN.md`, `GEMINI.md`, and any other LLM-specific context carrier.

Step — Install the Bridge Extensions

```
# From the consuming project root:
bash constitution/scripts/extensions/install_speckit_superpowers_bridge.sh

# This script:
#  1. Clones or updates spec-kit, superpowers, superspec, superb as
#     submodules under constitution/submodules/
#  2. Builds the SuperBridge MCP server (npm install + build)
#  3. Registers the MCP server in the CLI agent's MCP config
#  4. Installs the Spec-Kit extensions into .claude/skills/
#  5. Runs self-check: all extensions parse, MCP server health-check
#     responds, Spec-Kit skills load
```

Step — Run the Self-Validation Suite

```
bash constitution/scripts/extensions/validate_bridge.sh

# Expected output:
#   [PASS] SuperBridge MCP server health-check
#   [PASS] speckit-specify extension loads
#   [PASS] speckit-plan extension loads
#   [PASS] speckit-tasks extension loads
#   [PASS] superspec status returns valid JSON
#   [PASS] superb check passes on constitution files
#   [PASS] Helix LLM Gateway reachable
#   [PASS] llama.cpp RPC backend health-check
#   ──────────────────────────────────────────────────
#   ALL 8/8 CHECKS PASSED — bridge ready
```

Step — Create Your First SpecKit Feature

```
# Operator prompt (any of the six §11.4.140 forms):
#   /FEATURE Add multi-channel audio passthrough for Dolby TrueHD
#
# The CLI agent with the bridge wired will:
#  1. speckit-specify  → spec.md
#  2. speckit-plan     → plan.md
#  3. speckit-tasks    → tasks.md
#  4. superb check     → constitution gate verification
#  5. superspec status → context snapshot
#  6. superspec tasks  → nano-task decomposition
#  7. superspec execute → subagent-driven implementation
#  8. superb critique  → independent review
#  9. superb finish    → full-suite retest + migration
```

Step — Verify the Autonomous Loop

```
# Check that the feature completed through all layers:
cat docs/features/<feature-slug>/Status.md | grep "Validation:"
# Expected: Validation: PASS (evidence: qa-results/<run-id>/<feature>/)

# Check the verdict store:
ls device/rockchip/rk3588/tests/regression_guard/verdicts/<feature-slug>/
# Expected: RED_*.json + GREEN_*.json

# Check the Issues→Fixed migration:
grep "<feature-slug>" docs/Fixed.md
# Expected: Row with Status "Implemented (→ Fixed.md)"
```

Key Design Decisions

. Seven-Layer Separation (Why Not Monolithic?)

Decision	Rationale
Governance (L2) separate from Orchestration (L3)	Spec-Kit artifacts are static documents; SuperSpec interprets them. Separating lets Spec-Kit evolve independently and lets SuperSpec adapt to different CLI-agent tool shapes without touching governance files.
Orchestration (L3) separate from Execution (L5)	SuperSpec manages workflows; SuperBridge MCP manages tool contracts. A new skill added to Superpowers updates only the MCP server, not the orchestration logic.
Discipline (L4) is its own layer, not a subcomponent of Orchestration	SuperB's enforcement is adversarial — it MUST refuse work that passes orchestration but fails constitutional invariants. Embedding it in SuperSpec would create the self-review blind spot (§11.4.70).
Inference (L6) separate from Execution (L5)	The MCP server calls the Gateway via HTTP; the Gateway abstracts local/remote/cloud routing. Swapping the inference backend (llama.cpp → vLLM → cloud API) changes only Layer 6, nothing above it.

. Nano-Tasks as the Atomic Work Unit (Why ≤ Lines?)

- **Context-bounded subagents** — Each subagent processes ~100 lines of code-under-test + ~200 lines of surrounding context. A 400-line change would need 3 separate subagents; forcing decomposition upfront avoids a subagent silently exceeding its context window.
- **§11.4.197 zero-loss** — A crashed subagent loses ≤100 lines of work. A crashed subagent on a 500-line task loses potentially irrecoverable state.
- **Review granularity** — A 100-line diff gets a thorough adversarial review (§11.4.194). A 1000-line diff gets a rubber stamp.

[3]
- **Parallelizability** — Nano-tasks with no mutual file dependencies dispatch in parallel (§11.4.103 ≥3 concurrent streams).

. TDD Everywhere (Why Not "Write Tests After"?)

Per §11.4.43, a test authored after the fix is a PASS-bluff — it demonstrates only that the test agrees with the fix, not that the test catches the bug. The bridge enforces:

1. RED test FIRST (`RED_MODE=1` on the pre-fix artifact)
2. RED must FAIL (the defect is reproduced)
3. Implementation lands
4. SAME test flipped to `RED_MODE=0` → GREEN
5. GREEN artifact fingerprint MUST differ from RED (proves the fix deployed)

[4]The SuperB `implementation-gate` refuses to dispatch a nano-task that lacks a pre-existing RED test.

. Local-First Distributed Inference (Why Not Cloud API?)

- **§11.4.126 autonomous-loop** requires continuous execution. A cloud API rate limit (429 Too Many Requests) that kills 5 subagents at once (§11.4.147 forensic anchor) is structurally incompatible with an always-on loop.
- **§11.4.10 credentials-handling** — local inference eliminates the API-key-in-every-request surface.
- **§11.4.6 no-guessing** — a local Gateway logs every prompt + response. A cloud API's opaque logging (or lack thereof) makes forensic debugging of an agent's decision path impossible.
- **Cost** — autonomous loops issue thousands of inference calls per day. At cloud API pricing, that is hundreds of dollars per day; at local inference, it is electricity-only.

. Constitution as the Single Source of Truth (Why Not Per-Project Rules?)

Per §11.4.17 / §11.4.35, universal rules live in the Constitution submodule; project-specific extensions live in the consumer's context carriers. The bridge reads the Constitution file at startup and derives:

- **Allowed status vocabulary** (§11.4.15)
- **Required evidence classes per feature** (§11.4.69)
- **Gating pipeline** (which `CM-*` gates fire at which seam)
- **Propagation targets** (§11.4.17 classification markers)

A new constitutional mandate added to the submodule takes effect in every consuming project on the next `git pull` + `post_update_hook.sh` run (§11.4.164) — no per-project reconfiguration.

Constitutional Mandates Applied

Mandate	How the Bridge Applies It
§11.4 (anti-bluff covenant)	Every gate, review, and verdict carries captured physical evidence (§11.4.5) keyed to a §11.4.69 feature class. No metadata-only PASS, no config-only PASS, no absence-of-error PASS.
§11.4.6 (no-guessing mandate)	Every verdict cites a `file:line` or a captured-evidence path. The bridge's decomposer, reviewer, and debugger all refuse to emit `likely` / `probably` / `maybe` / `seems` in any formal output.
§11.4.10 (credentials-handling)	API keys, tokens, and passwords never appear in tracked files. The `.env.example` template documents required env vars; real values live in git-ignored `.env` files (`chmod 600`). The `pre-commit` hook scans staged files for credential patterns and refuses the commit.
§11.4.65 (universal Markdown export)	Every `.md` produced by Spec-Kit (`spec.md` , `plan.md` , `tasks.md`) gets synchronized `.html` + `.pdf` + `.docx` siblings via `sync_all_markdown_exports.sh` , auto-invoked by the `post-commit` hook (§11.4.75 Layer 4).
§11.4.74 (catalogue-first)	All extensions, skills, MCP servers, and plugins are registered in `constitution/actions/registry.yaml` via the §11.4.164 `post_update_hook.sh` . No extension is wired ad-hoc.
§11.4.75 (mechanical enforcement)	Four-layer enforcement: `pre-commit` hook (refuses orphan `.md`), `commit_all.sh` integration (auto-runs exports), `pre-push` hook (re-checks propagation gates), `post-commit` hook (auto-repairs drift).
§11.4.76 (containers submodule)	All containerized services (Helix LLM Gateway, SuperBridge MCP, ChromaDB, llama.cpp RPC nodes) are defined in `constitution/submodules/containers/compose/` and booted via `pkg/boot` . No ad-hoc `podman run` .
§11.4.202 (reporting directives)	Every intake path (operator prompt, test failure, review finding, HelixQA Challenge verdict) feeds through `report_item.sh` , creating a tracked workable item in the SQLite SSoT (§11.4.93) and pushing to the external tracker (§11.4.148 D5).

Mandate	How the Bridge Applies It
§11.4.43 (TDD-fix-discipline)	The five-step TDD workflow (RED → LIVE-ADB-PROBE → GREEN → VERIFY → DOCUMENT) is mechanically enforced by the SuperB `implementation-gate` + `critique` + `debug` + `finish` gates. No implementation subagent dispatches without a registered RED test.
§11.4.70 (sub-agent-driven default)	Every nano-task dispatches as an isolated subagent. The conductor's role is task decomposition + review; the subagent's role is isolated implementation.
§11.4.116 (real-time sync channel)	The bridge emits `conduit.events.jsonl` and atomically-updated `conduit.status.json` so the conductor can tail live progress.
§11.4.147 (crashed-agent respawn)	The Agents component tracks every subagent in the durable registry. Crashed/rate-limited agents are respawned with preserved state + §11.4.84 quiescence check. Agent output with missing verdict = `crashed`, never `complete`.
§11.4.161 (rootless container runtime)	All containerized components boot via podman rootless. No `sudo docker`, no rootful podman.
§11.4.209 (code-review Fable xhigh)	Every code-review subagent dispatches on Fable model at xhigh effort. Opus xhigh is the fallback. Lower-effort or non-Fable/non-Opus review substrate is a refusal.
§11.4.211 (merge-conflict Fable xhigh)	Merge-conflict resolution runs on Fable xhigh (Opus xhigh fallback). Conflict-resolution subagent carries its own scope + evidence.
§11.4.205 (enforced-not-advisory)	Every gate is a commit-wrapper refusal, not prose. Every gate's paired §1.1 mutation FAILs the gate. A gate whose mutation passes is a bluff gate.
§11.4.194 (exhaustive review all scenarios)	The review subagent enumerates the full input/scenario space, proves every "unreachable" assumption, cross-checks against captured runtime evidence.

Mandate	How the Bridge Applies It
§11.4.214 (re-currence-links-not-mints)	Before minting a new item for a test failure, the bridge checks the workable-items DB for an existing item describing the same defect. Match → link + reopen (terminal only).
§11.4.186 (cross-document con-sistency)	The no-divergence gate runs before export/sync-verify/commit. DEDUP, TIMELINE, CROSS-DOC, INTEGRITY, STRUCTURAL check families.

Directory Structure

```
constitution/docs/research/extensions/speckit_superpowers/implementation/
│
├── README.md                          ← THIS FILE — master index +
architecture overview
│
├── 01_architecture/
│   ├── README.md                      Layer-by-layer deep dive with
component diagrams
│   ├── layer_1_workstation.md         Developer workstation specification
│   ├── layer_2_speckit.md             Spec-Kit governance layer details
│   ├── layer_3_superspec.md           SuperSpec orchestration engine
│   ├── layer_4_superb.md              SuperB discipline enforcement
│   ├── layer_5_mcp.md                 SuperBridge MCP server contract
│   ├── layer_6_helix_llm.md           Helix LLM inference pipeline
│   ├── layer_7_cluster.md             Distributed inference cluster
│   └── contracts/                     Interface contracts between layers
│       ├── spec_to_superspec.md       Spec-Kit → SuperSpec bridge
contract
│       ├── superspec_to_mcp.md        SuperSpec → SuperBridge MCP
contract
│       ├── mcp_to_helix.md            MCP → Helix LLM contract
│       └── helix_to_cluster.md        Helix LLM → llama.cpp RPC contract
│
├── 02_extensions/
│   ├── README.md                      Extensions overview + installation
guide
│   ├── superbridge_mcp/               SuperBridge MCP server source +
config
│   ├── speckit_bridge_skills/         Extended Spec-Kit skills for bridge
integration
│   ├── skill_manifests/               Per-skill manifest files
│   └── constitution_registry.yaml     Action registry entries for bridge
commands
│
├── 03_helix_llm/
│   ├── README.md                      Helix LLM integration guide
│   ├── gateway/                       Gateway configuration + deployment
│   ├── brain/                         Prompt templates (per skill per
model)
│   ├── knowledge/                     RAG pipeline configuration
│   ├── agents/                        Agent orchestration engine
│   └── rpc_backend/                   llama.cpp RPC node configuration
│
├── 04_tdd_qa/
│   ├── README.md                      TDD + QA pipeline guide
```

```
│   ├── red_green_pipeline.md          RED→GREEN verdict pipeline
specification
│   ├── four_layer_coverage.md         Four-layer coverage per §11.4.4(b)
│   ├── helixqa_integration.md         HelixQA Challenge bank wiring
│   └── quality_gates.md              Quality-gate configuration +
thresholds
│
├── 05_deployment/
│   ├── README.md                      Deployment guide
│   ├── podman_compose/                podman-compose definitions for all
services
│   ├── health_monitoring/             Health-check scripts + dashboards
│   ├── backup_restore/                Backup/restore procedures
│   └── cluster_provisioning/          Multi-node cluster setup automation
│
├── 06_risk/
│   ├── README.md                      Risk management guide
│   ├── risk_register.md               Enumerated risks with severity +
mitigation
│   ├── failure_modes.md               Failure-mode analysis per component
│   ├── circuit_breakers.md            Circuit-breaker design + thresholds
│   ├── fallback_chains.md             Fallback chains
(local→remote→cloud)
│   └── rollback_procedures.md         Rollback procedures per scenario
│
└── poc/
    ├── README.md                      POC walkthrough
    ├── feature_trace.md               Sample feature lifecycle trace
(end-to-end)
    ├── benchmarks.md                  Performance benchmarks
    └── limitations.md                 Known limitations + tracked
migration items
```

References

#	Title	URL	Relevance
1	**Spec-Kit** (SDD toolkit)	https://github.com/github/spec-kit	Spec-Kit core: specify, plan, tasks, implement lifecycle
2	**Superpowers** (agent skills)	https://github.com/obra/superpowers	15+ agent skills: brainstorming, TDD, debugging, code review, refactoring, documentation
3	**SuperSpec** (SpecKit-Superpowers bridge)	https://github.com/WangX0111/superspec	Bridge orchestration: status, brainstorm, tasks, execute, review
4	**SuperB** (Spec-Kit discipline enforcement)	https://speckit-community.github.io/extensions/superb	Discipline gates: check, brainstorm, implementation-gate, critique, debug, finish
5	**Helix LLM** (distributed inference)	https://github.com/HelixDevelopment/helix_llm	Local-first distributed LLM inference: Gateway, Brain, Knowledge, Agents
6	**llama.cpp** (inference engine)	https://github.com/ggerganov/llama.cpp	RPC-server mode for distributed inference backend
7	**Helix Constitution** (governance submodule)	git@github.com:HelixDevelopment/helix_constitution.git	Universal development mandates, mechanical enforcement, agent rules
8	**MCP (Model Context Protocol)**	https://modelcontextprotocol.io	Protocol for LLM-tool interoperability
9	**Podman** (rootless containers)	https://podman.io	Rootless container runtime per §11.4.161
10	**Claude Code** (CLI agent)	https://docs.anthropic.com/en/docs/claude-code	Primary CLI agent implementing the autonomous loop

#	Title	URL	Relevance
11	**ATMOSphere** (consuming project)	git@github.com:vasic-digital/Android_15.git	Reference consuming project implementing the bridge
12	**Constitution submodule documentation**	`constitution/docs/` (this repository)	Full constitutional mandates, agent rules, and project-independent extensions