generate_agent_prefix_commands.sh

Revision: 2 **Last modified:** 2026-07-14T22:05:00Z **Authority:** constitution §11.4.140 (universal action-prefix system) + §11.4.202 (reporting directives) + §11.4.28 (decoupling — the registry is data, not code) **Maintainer:** constitution submodule (inherited by reference per §11.4.177 / §11.4.28(B)) **Scope:** §11.4.18 companion doc for `constitution/scripts/generate_agent_prefix_commands.sh`

Overview

`generate_agent_prefix_commands.sh` turns `actions/registry.yaml` — the single source of truth — into the **LAYER-2 slash commands** for every supported CLI agent. It is the mechanism that makes "adding a directive is a registry row, never a code change" literally true: add the row, re-run this generator, and the directive appears on every agent.

For each registered action it emits **two** command files per agent — the bare form and a `default-` alias:

Agent	Files emitted	Argument token
Claude Code	`plugins/helix/commands/<name>.md`, `default-<name>.md`	`$ARGUMENTS`
Gemini CLI	`actions/generated/gemini/<name>.toml`, `default-<name>.toml`	`{{args}}`
Qwen Code	`actions/generated/qwen/<name>.toml`, `default-<name>.toml`	`{{args}}`
Codex CLI	`actions/generated/codex/<name>.md`, `default-<name>.md`	`$ARGUMENTS`

It also **regenerates two READMEs** so the published inventory can never drift from the registry: `plugins/helix/README.md` (the Claude Code command table + the conflict rule) and `actions/generated/README.md` (per-agent install targets + the action count).

Claude Code's commands are written **straight into the plugin tree** — the plugin *is* the delivery mechanism, so there is no copy step and no second source of truth.

Why a `default-<name>` alias exists: `::` is not a legal character in a Gemini / Qwen / Codex command name (the name *is* the filename), so those agents cannot express the §11.4.140 form-4 `/PREFIX::ACTION` escape literally. `default-<name>` maps to the **identical expansion**, giving every agent a collision-free invocation. On Claude Code the native plugin namespacing `/helix:<name>` *is* the form-4 escape, and `/default-<name>` is generated as well, for parity.

System-level narrative: `docs/actions/REFERENCE.md`.

Prerequisites

- `bash` (`set -euo pipefail`), and `scripts/action_prefix_lib.sh` (sourced).
- `python3` **preferred** for reading per-action metadata (`summary` , `slash_conflicts`) and for the library's YAML parse. Without `python3` / `PyYAML` the library falls back to its awk reader for names and expansions; the `apx_gen_field` metadata helper then yields empty values and the generator substitutes a **generic** summary and assumes **no** collisions. That degradation is silent by design (non-fatal), so run the generator on a host with `python3` + `PyYAML` if you want the conflict comments and real summaries.
- A registry that passes `apx_validate_registry` — the generator **aborts** (exit 1) otherwise, rather than emitting half-correct commands.

Usage examples

```
# Regenerate every agent's commands from the default registry
bash constitution/scripts/generate_agent_prefix_commands.sh

# Use an alternate registry (e.g. a consumer-owned one, §11.4.28)
HELIX_ACTION_REGISTRY=/path/to/registry.yaml \
  bash constitution/scripts/generate_agent_prefix_commands.sh

# Typical: add a registry row, regenerate, re-wire
$EDITOR constitution/actions/registry.yaml
bash constitution/scripts/generate_agent_prefix_commands.sh
bash constitution/scripts/install_cli_agent_plugins.sh
```

Output (stderr):

```
generate_agent_prefix_commands: generated 5 action(s) under .../actions/
generated
```

Edge cases

Case	Behaviour
Registry fails validation	`generate_agent_prefix_commands: registry failed validation; aborting`, **exit 1**. Nothing is written.
An action has no `expansion`	`WARN: no expansion for <NAME>` on stderr; that action is **skipped**; the rest are generated. (Validation normally catches this first.)
`summary:` absent	Falls back to `Action-prefix <NAME>: run the task with the registered expansion applied.`
`slash_conflicts:` non-empty	The bare command file gets an explicit `CONFLICT` comment naming the host command and the two safe invocations (`/helix:<name>` , `/default-<name>`), and the plugin README row is rendered as a **COLLIDES** warning. The plugin never silently shadows a host command.
A `summary` containing `|` (e.g. `{Bug | Feature | Task}`)	Escaped before it is placed in the markdown table cell, so the README table cannot break.
A `description` containing `"` or `\`	Escaped in the YAML frontmatter, so a stray quote cannot break the command file's frontmatter.
Re-run with no registry change	Deterministic — byte-identical files. Safe to re-run at any time; files are overwritten, never appended.
An action **removed** from the registry	Its command files are **not** deleted (the generator only writes). Remove the stale `<name>.md` / `<name>.toml` files by hand.

Honest boundary (§11.4.6): the generator only **writes** files. It writes Claude Code's commands straight into the plugin tree, and the Gemini / Qwen / Codex files into `actions/generated/<agent>/` — it does not install anything into `.gemini/commands/` , `.qwen/commands/` or `prompts/` . That wiring is `install_cli_agent_plugins.sh` 's `link_agent_commands()` step, which

symlinks them (never copies, never clobbers a hand-written file). Run the generator alone and the new command exists but is not yet linked into a newly-added agent directory; run the installer (which calls the generator first) and it is.

The generator also does not embed each action's `rules:` into the command files — `rules` are LAYER-1 material, read by the agent from the registry/carrier block. Only `expansion` (plus `summary` and `slash_conflicts` metadata) reaches the command files.

Internal behaviour

```
source scripts/action_prefix_lib.sh
apx_validate_registry || abort(1)

for NAME in $(apx_list_actions):
    expansion  = apx_lookup_expansion NAME          # library (python3 →
awk fallback)
    summary    = apx_gen_field NAME summary         # python3-only;
generic fallback
    conflicts  = apx_gen_field NAME slash_conflicts # python3-only; ""
fallback
    lc         = lowercase(NAME)

    # form 3 — the bare command
    apx_emit_claude_md  plugins/helix/commands/  $lc  NAME  $expansion
$summary $conflicts
    apx_emit_toml       actions/generated/gemini/ $lc …
    apx_emit_toml       actions/generated/qwen/   $lc …
    apx_emit_codex_md   actions/generated/codex/  $lc …

    # form 4 — the collision-free `default-` alias (identical expansion)
    apx_emit_*          …  default-$lc  "DEFAULT::NAME"  $expansion …

    accumulate a README row (COLLIDES variant when $conflicts non-empty)

rewrite plugins/helix/README.md        (command table + conflict rule +
install pointer)
rewrite actions/generated/README.md    (per-agent install-target table +
action count)
```

Emitters: `apx_emit_claude_md` (YAML frontmatter `description:` + `argument-hint:`, a `DO NOT EDIT` banner naming the source row, the optional `CONFLICT` comment, the expansion, then `$ARGUMENTS`); `apx_emit_toml` (a `description = …` key and a `prompt = """…{{args}}"""` block); `apx_emit_codex_md` (HTML-comment banner, the expansion, then `$ARGUMENTS`).

No network, no state, no side effects outside `plugins/helix/` and `actions/generated/`.

Related scripts

Script	Relationship
`scripts/action_prefix_lib.sh`	The engine: registry validation, action listing, expansion lookup. Sourced by this generator.
`install_cli_agent_plugins.md`	Calls this generator in its step 1, then wires the plugin + skills.
`scripts/install_action_prefix.sh`	Also calls this generator, and registers the `UserPromptSubmit` hook.
`scripts/post_update_hook.sh`	Reaches this generator indirectly, via `install_cli_agent_plugins.sh`, on every constitution pull.
`actions/registry.yaml`	The input — the single source of truth.

Last verified

2026-07-14 — read against `scripts/generate_agent_prefix_commands.sh` at constitution HEAD; emitters, fallbacks, README regeneration, conflict rendering and escaping confirmed line by line; output cross-checked against the generated `plugins/helix/commands/bug.md` and `actions/generated/gemini/bug.toml`.