`helix` — Claude Code plugin (action directives + commands)

GENERATED by `scripts/generate_agent_prefix_commands.sh` from `actions/registry.yaml`. DO NOT EDIT BY HAND — add a registry row and re-run the generator.

Every registered §11.4.140 action is exposed as a Claude Code slash command.

Invoke	Always-unambiguous form	What it does
`/background`	`/helix:background` · `/default-background`	Run the remainder of the prompt as a DURABLE (never-lost), background, subagent-driven work stream in parallel with all main work, producing rock-solid physical proof.
`/reminder`	`/helix:reminder` · `/default-reminder`	Re-surface previously-scheduled, critical, status-UNCERTAIN work; verify actual status from captured evidence before acting (never assume done).
`/critical`	`/helix:critical` · `/default-critical`	Tag the remainder of the prompt HIGHEST-PRIORITY / potentially release-blocking — address with maximum urgency + rigor, track it, and do not defer it behind lower-priority work.
`/important`	`/helix:important` · `/default-important`	Tag the remainder of the prompt HIGH-PRIORITY — prioritize it above routine work (but below a CRITICAL / release-blocking matter), track it, and apply full anti-bluff rigor.
`/note`	`/helix:note` · `/default-note`	Capture the remainder of the prompt as durable CONTEXT / a note to remember (request-history + persistent memory), applied when relevant — not an urgent action unless it contains an explicit action.
`/helix:bug`	`/bug` **COLLIDES** with host `bug` → use `/helix:bug` or `/default-bug`	Report a product DEFECT — create a fully-populated Type=Bug workable item and drive the full DB → docs → external-tracker sync.

Invoke	Always-unambiguous form	What it does
`/task`	`/helix:task` · `/default-task`	Report an internal WORKSTREAM item — create a fully-populated Type=Task workable item and drive the full DB → docs → external-tracker sync.
`/issue`	`/helix:issue` · `/default-issue`	Report ANYTHING trackable — classify into the §11.4.16 closed set {Bug | Feature | Task}, then create the fully-populated, fully-synced item.
`/feature`	`/helix:feature` · `/default-feature` 11 4 140	SCHEDULE (never synchronously run) a deep, enterprise-grade research + implementation-planning effort on a described feature as a tracked workable item — the multi-day research itself is performed later by the autonomous loop, not by this directive.

Conflict rule (§ . .)

A bare `/<name>` is honored ONLY when it does not collide with a host built-in (declared as data in the registry `slash_conflicts:` field). The plugin-namespaced `/helix:<name>` is ALWAYS unambiguous — Claude Code plugin namespacing IS the §11.4.140 form-4 `PREFIX::ACTION` escape. `/default-<name>` is a third, collision-free form that works identically on every supported CLI agent.

The plugin NEVER silently shadows a host command: on a collision Claude Code resolves the bare name to its own built-in, and the colliding command file says so.

Install: see `docs/actions/QUICKSTART_INSTALL.md` (one command, or fully automatic on every constitution pull via `scripts/post_update_hook.sh` per §11.4.164).