0 3 6

fixtures/dispatch_stamp/ — T self-validation fixtures

Fixture convention for `constitution/scripts/fastcycle/tokens/dispatch_stamp.sh` (§11.4.107(10) self-validation: golden-good / golden-bad / negative-control).

Each case directory holds:

File	Content
`input`	The raw stdin JSON payload (the Claude Code PreToolUse hook invocation shape), byte-for-byte as it would arrive on stdin. Matches the `input` / `expected` naming already used by the sibling `fixtures/build_deploy_qa/` set.
`expected`	The expected **GUARD mode** (default invocation, no CLI flag) exit code — `0` or `2` — on its own line.
`expected_extract`	The expected **EXTRACTION mode** (`--extract-item-id`) stdout — the bare `ATM-nnnn` token, the literal `?` , or **empty** (0 bytes, no trailing newline) when `item=` is genuinely absent. This file is deliberately a *separate* file from `expected` because this tool has two independent behaviours (a blocking guard decision and a non-blocking extraction) driven by the SAME input — one `expected` file could not hold both without an ad-hoc multi-field format.

Cases

- **`golden-good/`** — a well-formed `Agent` dispatch carrying `item=ATM-1041` alongside a real §11.4.182 label → GUARD mode `exit 0` ; EXTRACTION mode prints `ATM-1041` .

- **`golden-bad/`** — the identical shape (`Task` dispatch, real §11.4.182 label) but with the `item=` token missing entirely → GUARD mode `exit 2` (stderr names the fix); EXTRACTION mode prints nothing (empty).
- **`negative-control/`** — a `Bash` tool_name (never gated) with no `item=` anywhere → GUARD mode `exit 0` , proving the guard does not over-fire on tools it was never meant to gate. (This case exercises GUARD mode only; EXTRACTION mode is tool_name-agnostic by design — see dispatch_stamp.sh's own header — so its `expected_extract` is empty here simply because the fixture's description field itself never contains `item=` , not because of any tool_name check in extraction mode.)

Running a case by hand

```
TOOL="$REPO_ROOT/constitution/scripts/fastcycle/tokens/dispatch_stamp.sh"
CASE="$REPO_ROOT/constitution/scripts/fastcycle/tests/fixtures/dispatch_stamp/golden-good"

# GUARD mode
cat "$CASE/input" | bash "$TOOL"; echo "exit=$?"      # compare against $CASE/expected

# EXTRACTION mode
cat "$CASE/input" | bash "$TOOL" --extract-item-id      # compare against $CASE/expected_extract
```