0 2 0 0 6

Fixtures: transcript_ingest (T , plan T-A)

RED-set fixtures for `constitution/scripts/fastcycle/tests/test_token_attribution_red.sh` (T020). Guards T036 (`$FC/tokens/dispatch_stamp.sh`) and T038 (`$FC/tokens/transcript_ingest.py`) — neither exists yet; this test and its fixtures are written and observed to fail against that absence (§11.4.224, common-conventions.md C-005). Producer≠Verifier (§11.4.240): this directory and the test script are the RED artefact only; `dispatch_stamp.sh` and `transcript_ingest.py` are separate, later, implementation tasks owned by other agents.

Real-schema provenance (§ . . — nothing here is invented)

Every field shape below was read from this project's OWN live Claude Code transcripts on 2026-09-28 (session `8824e088-62a6-4d4f-9f6c-2320055ad033` and sibling sessions under `~/.claude-claude5/projects/-mnt-track1-atmosphere-t1/`), never assumed:

- Top-level (non-sidechain) transcript records: `parentUuid` , `isSidechain` , `type` (`user` | `assistant` |...), `uuid` , `timestamp` , `sessionId` , `message` . An `assistant` record's `message` carries `model` , `id` , `type` , `role` , `stop_reason` , `content` , and (when the API call actually returned) a `usage` object with `input_tokens` , `output_tokens` , `cache_creation_input_tokens` , `cache_read_input_tokens` (plus provider-internal fields such as `output_tokens_details` , `server_tool_use` , `cache_creation` , `service_tier` , `iterations` , `speed` — irrelevant to token attribution and omitted from these minimal fixtures).
- A rate-limited/rejected turn's `message.usage` is present with EVERY count explicitly `0` (captured verbatim: session `0099c079-62e3-4846-a2a6-eacb7d42a85c` , line 49, `error: "rate_limit"` , `isApiErrorMessage:`

`true`, `apiErrorStatus: 429`, all four usage counts `0`) — this is the REAL shape `missing_usage_block/usage_present_zero.jsonl` is modelled on: a genuinely-zero, fully-instrumented turn, never to be confused with a turn that carries no `usage` key at all.

- Async agent dispatch: the PARENT transcript's dispatching `assistant` turn contains a `tool_use` content block (`type: "tool_use"`, `name: "Agent"`, `input: {description, prompt}`); the immediately-following `user` turn (the tool result) carries `toolUseResult: {isAsync: true, status: "async_launched", agentId, description, resolvedModel, outputFile, ...}` (captured verbatim from a genuine live async dispatch, agentId `a3769936d2ace3124`, session `8824e088-62a6-4d4f-9f6c-2320055ad033`, 2026-09-28 — the SAME real payload shape `scripts/hooks/test_agent_registry_dispatch_writer_red.sh`'s own A8 case is built from, cited there as agentId `ac39c9d3e8933edd3`, 2026-09-27).
- **Real captured dispatch `description` today carries NO `item=<ATM-nnnn>` token anywhere** — verbatim captured example (session `8824e088-62a6-4d4f-9f6c-2320055ad033`, `toolUseResult.description`): `"(T1/main - claude5 - sonnet - high) T018 RED test review_record"`. This is the direct evidence behind property (a) in the test.
- Subagent transcript on-disk convention: `<CLAUDE_CONFIG_DIR>/projects/<project-slug>/<parent_session_id>.jsonl` (the parent/CLI transcript) alongside `<parent_session_id>/subagents/agent-<agentId>.jsonl` (the subagent's OWN transcript) — directly observed via `<repo>/../.../tasks/<agentId>.output` symlinks resolving to exactly that path. A subagent transcript record carries `agentId` directly (not only derivable from the file name) plus `isSidechain: true` and (for its first `user` record) `promptId`. This is the real join key `transcript_ingest.py` (T038)'s "session→agent→item" keying (plan.md T-A06) needs: `sessionId` (session) → `agentId` (agent, matching both the subagent record's own field AND the parent's `toolUseResult.agentId` AND the `agent-<agentId>.jsonl` filename) → the `item=<ATM-nnnn>` token embedded in the parent's stamped `description` (item, once T036/T037 land).

Fixture map

Path	Property under test	Shape
`cache_hits/session.jsonl`	cache-hit tokens are counted, not dropped	one `user` turn + two `assistant` turns: turn 1 is cache-cold (`cache_creation_input_tokens=1200` , `cache_read_input_tokens=0`), turn 2 is a genuine cache HIT reading the same 1200 tokens back (`cache_read_input_tokens=1200`)
`missing_usage_block/usage_absent.jsonl`	a turn with NO `usage` key MUST be reported missing/ `UNMEASURED` (common-conventions.md term), never coerced to 0	`assistant` `message` object has no `"usage"` key at all
`missing_usage_block/usage_present_zero.jsonl`	negative control (§11.4.201(6) false-null guard, C-004 control needle) — a genuinely-zero, fully-instrumented turn MUST NOT be reported missing	`assistant` `message.usage` present, all four counts explicitly `0` (modelled on the real rate-limited-turn shape above)
`subagent_attribution/parent_session.jsonl` + `subagent_attribution/parent_session/subagents/agent-fixturet020attr01.jsonl`	a subagent's token usage attributes to its parent dispatch's item	parent dispatches with `description` containing `item=ATM-9999` (the future T036-stamped tag) and `toolUseResult.agentId = "fixturet020attr01"` ; the subagent transcript (real on-disk path convention) carries the SAME `agentId` and its own real usage (`cache_read_input_tokens=500` , `cache_creation_input_tokens=8000`)

Path	Property under test	Shape
`fore-ground_attribution/par-ent_session.jsonl` + `fore-ground_attribution/parent_session/sub-agents/agent-fix-turefg01.{jsonl,meta.json}`	a FOREGROUND dispatch (round 8, F1): the parent's `toolUseResult` has the real fore-ground keys (`agentId` , `agentType` , `content` , `prompt` , `re-solvedModel` , `status` , `total-Tokens` , `usage`) and NO `description` ; the item comes from the subagent's sidecar `agent-<id>.meta.json` (`description` carries `item=ATM-9999`); `prompt` / `con-tent` carry decoy tags (`ATM-1111` , `ATM-2222`) that must never be read; the subagent records carry their OWN `sessionId` (`fixture-fg-sub-agent-own-ses-sion` , different from the parent's)	derived from the structure of this host's live subagent transcripts (their sidecars carry `agentType` , `description` , `toolUseId` , `requestShape` , `model`); every id and text is synthetic

Path	Property under test	Shape
`credential_leak/session.jsonl`	a planted secret-shaped string in message content never reaches the telemetry DB (§11.4.10)	`user` + `assistant` turns whose text embeds the literal marker `FASTCYCLE-T020-PLANTED-MARK-ER-7f3a9c2e1b8d4f6091ab34cd`, clearly labelled synthetic; a genuine `usage` block accompanies the assistant turn so the fixture also exercises normal ingest

Credential-scanner safety (verified, not assumed)

Every fixture file above was scanned with this repository's OWN `helix_cred_scan_file` (`constitution/scripts/hooks/credential_scan_lib.sh`) before being checked in, with a positive control run first (a synthetic `AKIA`-shaped AWS key, confirmed CAUGHT) proving the scanner instrument was alive for that run — all six fixture files scanned clean. The planted marker in `credential_leak/session.jsonl` deliberately avoids every keyword the scanner's `HELIX_CRED_VALUE_PATTERN` matches (`password|passwd|secret|api[_-]?key|access[_-]?token|auth[_-]?token|client[_-]?secret` adjacent to `:` / `=`) and every literal prefix it matches (`AKIA` , `ghp_` , `gho_` , `github_pat_` , `xox[baprs]-` , `sk-` , `AIza` , `-----BEGIN ... PRIVATE KEY-----`) — it is a synthetic marker STRING representing "sensitive message-body content that must never reach a metrics-only DB", not a credential-SHAPED assignment the scanner is designed to catch (that is a different, already-covered feature).