

fixtures/dispatch_stamp/ – T self-validation fixtures

Fixture convention for `constitution/scripts/fastcycle/tokens/dispatch_stamp.sh` (§11.4.107(10) self-validation: golden-good / golden-bad / negative-control).

Each case directory holds:

File	Content
<code>input</code>	The raw stdin JSON payload (the Claude Code PreToolUse hook invocation shape), byte-for-byte as it would arrive on stdin. Matches the <code>input / expected</code> naming already used by the sibling <code>fixtures/build_deploy_qa/</code> set.
<code>expected</code>	The expected GUARD mode (default invocation, no CLI flag) exit code — <code>0</code> or <code>2</code> — on its own line.
<code>expected_extract</code>	The expected EXTRACTION mode (<code>--extract-item-id</code>) stdout — the bare <code>ATM-nnnn</code> token, the literal <code>?</code> , or empty (0 bytes, no trailing newline) when <code>item=</code> is genuinely absent. This file is deliberately a <i>separate</i> file from <code>expected</code> because this tool has two independent behaviours (a blocking guard decision and a non-blocking extraction) driven by the SAME input — one <code>expected</code> file could not hold both without an ad-hoc multi-field format.

Cases

- **golden-good/** — a well-formed `Agent` dispatch carrying `item=ATM-1041` alongside a real §11.4.182 label → `GUARD mode` `exit 0` ; `EXTRACTION mode` prints `ATM-1041` .

- **golden-bad/** — the identical shape (`Task dispatch`, real §11.4.182 label) but with the `item=` token missing entirely → GUARD mode `exit 2` (stderr names the fix); EXTRACTION mode prints nothing (empty).
- **negative-control/** — a `Bash tool_name` (never gated) with no `item=` anywhere → GUARD mode `exit 0` , proving the guard does not over-fire on tools it was never meant to gate. (This case exercises GUARD mode only; EXTRACTION mode is `tool_name`-agnostic by design — see `dispatch_stamp.sh`'s own header — so its `expected_extract` is empty here simply because the fixture's description field itself never contains `item=` , not because of any `tool_name` check in extraction mode.)

Running a case by hand

```
TOOL="$REPO_ROOT/constitution/scripts/fastcycle/tokens/dispatch_stamp.sh"
CASE="$REPO_ROOT/constitution/scripts/fastcycle/tests/fixtures/dispatch_stamp/golden-good"

# GUARD mode
cat "$CASE/input" | bash "$TOOL"; echo "exit=$?"      # compare against $CASE/expected

# EXTRACTION mode
cat "$CASE/input" | bash "$TOOL" --extract-item-id    # compare against $CASE/expected_extract
```