

gate_order fixtures (T^{0 1 3} plan T-C, contract AS-)

RED-test fixtures for `constitution/scripts/fastcycle/tests/test_gate_order_red.sh`, covering ONLY the fail-fast ORDERING half of `gates/gate_runner.sh` (AS-013). The sibling BOUNDED-SHARDING half (AS-014, plan T-C05) is out of scope here — see `test_gate_shard_red.sh` (T055) for that.

`_shared/` — the common toy corpus

- `gates/` — 4 tiny real shell "gate" scripts (`gate_a_reliable.sh` always PASS, `gate_b_moderate.sh` always PASS but historically 1/5 FAIL, `gate_c_planted_fail.sh` genuinely FAILs on every invocation (the planted defect), `gate_d_new.sh` always PASS with zero history rows).
- `history/prebuild_sections.tsv` — a real T-A01-schema (`fc_timer.sh` header, see `constitution/scripts/fastcycle/timing/fc_timer.sh`) log with 5 historical runs each for gates a/b/c establishing their `historical_fail_rate / mean_cost` : a=0.0, b=0.0004, c=0.008 (highest). Gate d has no rows (tests DEC-10's median-rate default).
- `affected.json` — an Affected-Set entity (data-model.md §4) declaring all 4 gates as `members` in SECTION/DECLARED order `a, b, d, c` — the planted-failing gate `c` is declared **last**.
- `config.yaml` — the `--config` fixture (gate-site paths + history-log path).

Scenarios

Directory	Kind	Proves
<code>go_ordered_planted_fail_first/</code>	golden	<code>--order history-cost</code> executes/reports the planted-fail gate FIRST despite it being declared last (the literal task-text claim).
<code>go_negctrl_already_first/</code>	negative control	When the ranked-first gate is ALREADY declared first, ordering is a correct no-op, not a vacuous behaviour.
<code>go_determinism_identical_results/</code>	determinism	The final <code>results</code> verdict set (sorted by <code>gate_id</code>) is byte-identical whether <code>--order history-cost</code> is given or omitted — ordering changes only run/report SEQUENCE, never the substantive outcome.
<code>go_new_gate_median_rate/</code>	control needle	A gate with no historical entry (<code>gate_d_new</code>) ranks at the MEDIAN rate — neither 0 (would tie it with the lowest gate) nor the maximum (would rank it above the genuinely worst gate) — per contract DEC-10.

What this RED test does NOT cover

- AS-014 bounded sharding (`--order` 's sibling flag/mode for parallel execution) — T055's `test_gate_shard_red.sh` scope, not this file's.
- The `--no-cache` flag and verdict-cache interaction (T-C01, covered by T051's `test_verdict_cache_red.sh`).

- `affected_set.py` 's own selection/skip-list logic (T-C03, covered by T053's `test_affected_set_red.sh`).
- `io_trace.sh` 's observed-input tracing (T-C02, covered by T052's `test_io_trace_red.sh`).

See `PAIRED_MUTATION_NOTE.md` for the C-005 mutation obligation this fixture set hands to T070 (the real implementation task), not this RED test itself.