

fixtures/evidence_ref/ – T self-validation fixtures

Fixture convention for `constitution/scripts/fastcycle/context/evidence_ref.py` (contract `specs/004-fast-dev-cycles/contracts/evidence-reference-reverify.md`, clauses ER-000..ER-005; `data-model.md` §8 "Evidence Reference"; `plan.md` T-E05; `research.md` DEC-29). Task T108 (`tasks.md`) writes ONLY this RED test + these fixtures; the tool itself is T117, a later, separate task (Producer != Verifier, §11.4.240 — this file's author never implements `evidence_ref.py`).

Layout

Six self-contained scenario directories, one per contract RED-fixtures-table row. Each holds the CURRENT ("consume-time"/live) bytes of every file the scenario's `ref.json` cites, plus (only where the scenario's whole point is that a file changed after the reference was created) an `*_as_recorded.*` sibling holding the ORIGINAL ("create-time") bytes that `ref.json` 's stored content addresses were computed from. `ref.json` 's declared `inputs.paths` never change between create and consume — only the BYTES at those paths change, which is exactly what ER-002 ("recomputes every component from current bytes") exists to catch.

Directory	Kind	What changed between create and consume
er_unchanged/	golden-good	nothing — <code>input_a.txt</code> , <code>verifier.sh</code> , <code>evidence.txt</code> are byte-identical to what <code>ref.json</code> records
er_changed_input/	golden-bad	<code>input_a.txt</code> 's CURRENT bytes differ from <code>input_a_as_recorded.txt</code> (what <code>ref.json</code> 's <code>inputs.root</code> was computed from)
er_changed_verifier/	golden-bad	<code>verifier.sh</code> 's CURRENT bytes differ from <code>verifier_as_recorded.sh</code> (what <code>ref.json</code> 's <code>verifier_version</code> was computed from); the declared input is unaffected
er_changed_target/	golden-bad	nothing on disk — <code>ref.json</code> records <code>target_fingerprint: "DEVICE-SERIAL-AAA"</code> ; <code>scenario.json</code> names the DIFFERENT live serial (<code>DEVICE-SERIAL-BBB</code>) <code>consume</code> is invoked with — T108's own named scenario, "a reference whose on-target fingerprint differs is refused"
er_evidence_tampered/	golden-bad	<code>evidence.txt</code> 's CURRENT bytes differ from <code>evidence_as_recorded.txt</code> (what <code>ref.json</code> 's <code>evidence.content_address</code> was computed from); inputs + verifier unaffected
er_negctrl_unrelated_file/	negative-control	<code>unrelated.txt</code> 's CURRENT bytes differ from <code>unrelated_as_recorded.txt</code> — but <code>unrelated.txt</code> is NEVER named in <code>ref.json</code> 's <code>inputs.paths</code> , so ER-002 must never notice it

Every sha256 embedded in every `ref.json` is the REAL digest of the file it names, computed at fixture-authoring time by `hashlib.sha256` and independently RE-VERIFIED, live, by the already-landed `constitution/scripts/fastcycle/lib/fc_common.py body-hash --verify` (a control needle: the established tool, not this fixture author's own reimplementations, confirms every `ref.json`'s stored `body_hash` matches its canonical body — `bash test_evidence_ref_red.sh` reruns this check on every invocation, so a future hand-edit that desyncs a `ref.json` from its own `body_hash` is caught rather than silently poisoning the fixture).

117

`ref.json` / `consume.json` wire format (UNCONFIRMED, binding-if-adopted on T)

The contract's Invocation section names the CLI shape (`create --fact ... --verifier <id> --inputs <paths...> [--target <serial>] --verdict PASS|FAIL --evidence <path> --out <ref.json> ; consume --ref <ref.json> [--target <serial>] --out <consume.json>) and data-model.md §8 names the Evidence Reference entity's FIELDS, but neither pins the exact JSON shape those fields are serialized into, nor how --verifier <id> resolves to the bytes ER-001's verifier_version hashes. This fixture set — like the established precedent in fixtures/verdict_cache/ and test_governance_subset_red.sh's own "UNCONFIRMED... DEFINED here" section — DEFINES one concrete, defensible shape and flags it explicitly as binding-if-adopted, not as a claim the contract already specifies it:`

- `--verifier <id>` **IS the verifier script's own repo-relative path** (the simplest literal reading available — the contract offers no separate `--verifier-script` flag to distinguish an opaque id from a locator).
`verifier_version` = `content_address(that path's bytes at create time)` .
- `ref.json` **carries BOTH the Merkle root AND the declared path list** (`inputs: {paths: [...], root: "sha256:..."}`), never the root alone — a `consume` cannot recompute a Merkle root over an unknown path set, so the paths must travel with the reference.

- **Content addresses and Merkle roots are "sha256:<64 hex>" -prefixed** (data-model.md §0's own `ContentAddress / MerkleRoot` format); `body_hash` is the established `fc_common.py` convention's BARE 64-hex string (no prefix) — two different, independently-real established formats, each used exactly where its own convention already defines it, never conflated.
- **changed_components is a closed vocabulary:** `"inputs:<path>"` (that declared input's content changed), `"verifier_version"`, `"target_fingerprint"` (the live `--target` differs from the recorded one), and `"target_fingerprint_unobserved"` (ER-005: `--target` omitted for a non-hermetic reference) — DEFINED here; the contract names none of these literally, only "listing the changed components."
- **Merkle root canonicalization** reuses `fc_common.py` 's own `canon()` convention (`json.dumps(sort_keys=True, separators=(",", ":"), ensure_ascii=False)`) over the sorted `[path, content_address]` pair list — never a bespoke separator scheme — per §11.4.227 (extend, don't invent a second serialization convention alongside an already-established one). Pairs sort by the path string's raw UTF-8 BYTES (data-model.md §0's own "sorted bitwise by path"), never a locale-dependent string sort (C-003; the T105 GNU- `sort` -vs-Python lesson applies here too, though every path in this fixture set is plain ASCII so the two orderings happen to coincide — the bitwise construction is used anyway, on principle, not by luck).

What this RED test does NOT cover (honest, explicit gap)

ER-004 ("a ref whose verifier is an unrecorded LLM judgment is refused at `create` ") and exit code 4 ("target unreadable") are real contract clauses but are NOT among the six RED-fixtures-table rows this directory encodes — T108's own task line names only the two-step (unchanged/changed) `consume` fixture plus the named golden-bad target-mismatch scenario, and the contract's fixture table itself has no row for either. Left for T117 review time, exactly as `fixtures/governance_subset/` 's own `--item` resolution gap was left for T112.