

codegraph_safe.sh – Companion Guide

Revision: 1 Last modified: 2026-09-24T12:00:53Z

Source: `constitution/scripts/codegraph/codegraph_safe.sh` (561 lines).

Every statement below cites `codegraph_safe.sh:<line>` .

Overview

`codegraph_safe.sh` is the ONLY sanctioned entry point for CodeGraph `init` , `index` and `sync` (line 3). It exists to make the failure modes of the 2026-09-23 bulk-window incident impossible by construction (lines 5-32):

1. Stock `init` / `index` on a fresh DB drops the FK child-key indexes during the bulk window, so `INSERT OR REPLACE` cascades full-scan very large tables. Bulk ops run ONLY through the patched runner derived by `fk_index_patch.py` , or through stock AFTER `fk_cascade_probe.py` proves stock safe. A refused runner is NEVER silently replaced by stock (lines 7-11, 411-437).
2. `codegraph ... || true` masking — every failure is a non-zero exit (line 12).
3. A stall that looks alive — `index_watch.py` proves progress; a STALL is exit 7 (lines 13-14, 174-177).
4. Unbounded DB growth — `disk_tripwire.sh` SIGSTOPs the indexer below `--tripwire-min-gib` (exit 8), plus a host preflight (lines 15-16, 170-173, 297-329).
5. The fix vanishing after an upgrade — the runner is re-derived per stock version and its receipt/version checked on every bulk run (lines 17-18, 424-428).
6. The v1.6.0 stale-lock behaviour (a lock older than 2 minutes deleted regardless of holder liveness) — this wrapper checks the lock holder's real `/proc` `argv` and refuses while it lives, whatever the lock's age (lines 19-22, 331-378).

7. `sync` on any populated DB used to run stock + foreground with no patches, watcher or tripwire. `sync` is now classified BULK vs INCREMENTAL by the pending-refs backlog (lines 23-32, 467-487).

Hard rule: never run a writer against a project root whose lock holder is alive. The script enforces this itself (exit 3), but equally never run stock `codegraph init|index|sync|serve|unlock` by hand on such a root — that bypasses every check below. `codegraph_guard.sh` refuses tracked scripts that do so.

Prerequisites

- `bash` , `flock` , `setsid` , `nohup` , `df` , `python3` (line 102).
- Siblings in the same directory: `codegraph_safe_helper.py` , `index_watch.py` , `disk_tripwire.sh` , `fk_index_patch.py` , `fk_cascade_probe.py` (lines 102-103, 112-116).
- A stock CodeGraph CLI on `PATH` or in `CODEGRAPH_BIN` (line 117).
- For bulk ops: host headroom as measured by `preflight` (see below).

Usage examples

Host check only (no DB touched)

```
codegraph_safe.sh --project <project_root> preflight
```

First full index, detached, return immediately

```
codegraph_safe.sh --project <project_root> index
```

Same, block until the detached run finishes; exit = run result

```
codegraph_safe.sh --project <project_root> --wait --poll-s 30 index
```

Sync; classification decided by the pending-refs backlog

```
codegraph_safe.sh --project <project_root> sync
```

Force the supervised bulk path for sync

```
codegraph_safe.sh --project <project_root> --bulk sync
```

Read-only checks

```
codegraph_safe.sh --project <project_root> status
```

```
codegraph_safe.sh --project <project_root> --expected-count 580000 --tolerance-pct 2 verify
```

Remove a lock whose holder is provably dead (decision logged)

```
codegraph_safe.sh --project <project_root> --reap-dead-lock3 4 unlock3 6
```

4 4 0 5 6 1

Operations (lines - , -)

Exactly one op is allowed (line 262); missing or unknown op → exit 2 (lines 265-266).

Op	Kind	Behaviour
<code>init</code>	writer	Always bulk. Runner args <code>init -y -v <P></code> (line 515).
<code>index</code>	writer	Always bulk. Runner args <code>index -v <P></code> (line 516).
<code>sync</code>	writer	BULK or INCREMENTAL, see classification. Bulk runner args <code>sync <P></code> (line 517).
<code>status</code>	read- er	<code>lock_check reader</code> , <code>/proc scan</code> (3 tries), then <code>stock status <P></code> ; non-zero stock exit $\rightarrow$ 1 (lines 449-454).
<code>verify</code>	read- er	<code>lock_check reader</code> , <code>scan</code> , then <code>verify_now</code> (helper <code>verify + scope</code>) $\rightarrow$ <code>VERDICT PASS 0 / VERDICT FAIL 1</code> (lines 455-459, 398-407).
<code>pre-flight</code>	other	Prints measurements; <code>PREFLIGHT PASS 0</code> or exit 6 (lines 442-444).
<code>unlock</code>	other	Takes the wrapper flock, runs <code>lock_check unlock</code> (writer rules); exit 0 when no stale lock remains (lines 445-448).

Writers first take the wrapper flock, then `lock_check writer` , then the `/proc scan` (lines 462-464).

Options (lines - ,
-)

Option	Default	Validation / notes
<code>--project DIR</code>	git toplevel of <code>\$PWD</code> , else <code>\$PWD</code> (lines 284-286)	must exist (line 287); path containing whitespace → exit 2 for bulk ops (line 519)
<code>--bulk</code>	off	writer ops only, else exit 2 (lines 277-279); only changes behaviour for <code>sync</code>
<code>--pending-threshold N</code>	<code>\$CG_SAFE_PENDING_BULK_MIN</code> , else <code>150000</code> (line 240)	integer ≥ 1 (lines 271-272)
<code>--patches IDS</code>	<code>\$CG_SAFE_PATCHES</code> , else <code>fkidx1,resolve1</code> (line 240)	<code>all</code> or comma list <code>[a-z0-9]</code> , no leading/trailing/double commas (lines 273-276)
<code>--wait</code>	off	block until the detached bulk run writes its result (lines 543-561)
<code>--poll-s N</code>	10	integer (lines 267-269)
<code>--watch-interval N</code>	60	integer; passed to <code>index_watch.py</code>
<code>--stall-min M</code>	10	number, decimals allowed (line 270)
<code>--trip-wire-min-gib N</code>	20	integer in <code>[5, 500]</code> (line 280)
<code>--trip-wire-interval N</code>	30	integer

Option	Default	Validation / notes
<code>--reap-dead-lock</code>	off	allow removal of a provably dead lock
<code>--expected-count N</code>	—	integer (line 281); with <code>--tolerance-pct P</code> (number, line 282; default 0 when only N given, line 294)
<code>--status-doc FILE</code>	<code><P>/docs/codegraph/Status.md</code> (line 292)	absent file → ledger SKIP, run not failed (lines 221-224)
<code>--scope-baseline FILE</code>	<code>scope_baseline.txt</code> beside the script (line 241)	passed to helper <code>scope</code>
<code>--scope-exceptions FILE</code>	<code>scope_exceptions.txt</code> beside the script	narrow per-exact-path exceptions for the <code>secret_named / secrets_dir</code> heuristic classes ONLY (never the credential-CONTENT classes); passed as helper <code>scope</code> 's optional 3rd argument at every call-site, including inside <code>supervise()</code> via env <code>CG_SV_SCOPE_EXCEPTIONS</code> ; absent file ⇒ no exceptions (unchanged, strictest posture). See <code>docs/scripts/codegraph_safe_helper.md</code> 's <code>### scope</code> section for the full mechanism.
<code>-h , --help</code>	—	prints the header, exit 0 (line 260)

Any other `-...` option → exit 2 (line 261). An option missing its value → exit 2 (`need` , line 242).

Patch set (lines -)

Only `fkidx1` and `resolve1` have tests; `lockfix1` and `datafrag1` have none and are opt-in via `--patches / CG_SAFE_PATCHES`. `fkidx1` must be in the set — the receipt gate requires it, else exit 5 (lines 45-46). The default runner key is `<version>-fkidx1-resolve1`.

UNCONFIRMED: the receipt check itself (`python3 codegraph_safe_helper.py receipt` , line 425) was not read; the `fkidx1` requirement is stated in the header only.

Environment (lines -)

Variable	Default	Effect
<code>CODEGRAPH_BIN</code>	<code>codegraph</code>	stock CLI (line 117)
<code>CG_SAFE_PENDING_BULK_MIN</code>	150000	default sync BULK threshold
<code>CG_SAFE_PATCHES</code>	<code>fkidx1, resolve1</code>	default <code>--patches</code>
<code>CG_SAFE_PENDING_PROBE_BUDGET_S</code>	30	wall-clock budget of the pending probe (UNCONFIRMED: consumed inside the helper; not referenced in this script's code)
<code>CG_SAFE_PATCH_TOOL</code> / <code>CG_SAFE_PROBE_TOOL</code>	sibling <code>fk_index_patch.py</code> / <code>fk_cascode_probe.py</code>	lines 115-116
<code>CG_SAFE_MIN_THREAD_HEADROOM</code>	1024	preflight thread headroom (line 322)
<code>CG_SAFE_TEST_FREE_BYTES</code>	—	TEST-ONLY, can only lower free bytes (line 303)
<code>CG_SAFE_TEST_MEMAVAIL_KB</code>	—	TEST-ONLY, can only lower MemAvailable (line 314)
<code>CG_SAFE_TEST_THREADS_USED</code>	—	TEST-ONLY, can only raise threads used (line 320)

Sync classification: BULK vs INCREMENTAL (lines 467 – 487)

BULK=1 by default (line 471). For sync :

1. `--bulk` given → BULK (reason=`--bulk` requested , line 474).
2. Else helper `dbinfo` must report the DB exists, nodes present, no error (lines 476-477). If not → BULK (reason=database missing, empty or unreadable , line 485).
3. Else helper `pending <P> --threshold N` (line 478):
 - exit 0 → INCREMENTAL (`pending<threshold` , line 480);
 - exit 1 → BULK (`pending>=threshold` , line 481);
 - any other exit → BULK (`pending-probe UNKNOWN` , line 482). UNKNOWN is never read as "small".

Every sync prints `sync classification: BULK|INCREMENTAL (reason=...)` . The header states the pending probe is bounded (an index range read of at most `threshold+1` entries, never `COUNT(*)` , lines 29-31); UNCONFIRMED from this file — implemented in `codegraph_safe_helper.py` .

INCREMENTAL path (lines 489-503): stock `sync <P>` in the foreground under the held flock, output to `index_runs/sync_<UTC>.log` , last 5 lines echoed. Non-zero → exit 1. Then helper `verify_0s+scope ; ledger entry; VERDICT PASS 0 / VERDICT FAIL 1`. No preflight, no watcher, no tripwire.

Bulk path (lines 505 – 525)

1. `preflight` — FAIL → exit 6 (lines 505-507).
2. `resolve_runner` (lines 411-437): read stock `--version` (none → 5); run the patch tool with `--patches <IDS> --print-bin` (or `--print-bin` for `all`):
 - exit 0 → runner path must be executable, its parent dir must hold a valid `RUNNER_RECEIPT.json` for the stock version, and the runner's `--version` must equal stock's; any mismatch → 5;
 - exit 2 → 5 (stock is FORBIDDEN as fallback);

- exit 3 (patch not needed) → `fk_cascade_probe.py --work-dir index_runs/probe --json-out index_runs/probe_verdict.json` must exit 0, then the runner is stock; otherwise 5;
- any other exit → 5.

3. Launch detached: `setsid nohup bash <self> __supervise` with state in `CG_SV_*` environment variables (lines 525-529). The caller waits up to 600×0.1 s for the indexer to be identified (lines 533-541).

4. Without `--wait` : exit 0 after launch (lines 543-546). With `--wait` : poll every `--poll-s` seconds until `run_134<id>201.result` exists; exit with the `EXIT=` code it records (lines 547-561).

Supervisor (lines –)

- Starts the runner with the op args, logs to `index_<UTC>.log` , records PIDs.
- Waits up to 300×0.1 s for `.codegraph/codegraph.lock` to name a PID whose identity check passes; that PID (else the launched PID) is the indexer (lines 145-157).
- Arms `index_watch.py` and `disk_tripwire.sh` on the identified indexer (lines 158-163); if none identified, logs a WARN and arms neither (line 165).
- While the indexer runs: a `tripwire_<id>.log.TRIPPED` marker → result 8; a last watcher line containing `STALL_` → result 7, indexer left running for inspection (lines 167-179).
- On exit: helper `verify` (with the reported `Indexed N files` count and stock `status` Files count) + helper `scope` ; any non-zero among indexer, verify, `scope` → result 1; ledger append; result written atomically via `.tmp` + `mv` (lines 180-206).

Preflight thresholds (lines –)

Check	Pass condition
Disk	free on <code>.codegraph</code> (else project) $\geq \max(60 \text{ GiB}, 2 \times (\text{db} + \text{wal bytes}))$
Memory	<code>MemAvailable</code> $\geq 32 \text{ GiB}$
Threads	<code>ulimit -u</code> – threads used by this uid ≥ 1024 (skipped when unlimited)

331 396

Unreadable `df` or `MemAvailable` → FAIL (lines 301, 313).

Lock handling (lines –)

- No lock file → proceed (line 334).
- Numeric PID > 1 whose helper `identity` begins OK :
 - reader op → continue, unless the holder's op is `init|index|sync` → 3 (lines 345-349);
 - writer / unlock → 3, "whatever the lock's age, it is NOT stale" (line 351).
- Holder dead, non-numeric content, PID ≤ 1, or alive-but-not-codegraph → stale. Reader: WARN and continue (lines 357-360). Writer without `--reap-dead-lock` → 4 (line 363). With it: re-check immediately before removal (live → 3), then remove and append a `REAPED` line to `index_runs/lock_reap.log` (lines 365-377).
- `/proc` scan via helper `scan` (writer 1 try, reader 3 tries 0.5 s apart) → 3 on a live writer (lines 380-390).
- Wrapper flock `.codegraph/.helix_index.flock` taken non-blocking; held by another launcher → 3; cannot open → 2 (lines 392-396).

Exit codes (header lines verified against code)

– ,

Code	Meaning	Source
0	Success / verified / detached launch without <code>--wait</code> / <code>--help</code>	260, 443, 448, 454, 458, 499, 545
1	Indexer failed, verification FAILED, stock status failed, supervisor ended without result, unreadable result	453, 459, 496, 502, 554, 560; result 1 at 186-188
2	Usage error / unknown op / bad option / flock file unopenable / whitespace path	242-287, 394, 519
3	Live writer (lock holder or <code>/proc</code> scan) or wrapper flock held	348, 351, 369, 387, 395
4	Stale lock present, not reaped	363
5	Safe runner unavailable — stock NEVER used as fallback	415, 423, 426, 428, 430, 433, 436
6	Host preflight failed	444, 507
7	STALL detected (via <code>--wait</code>)	result written at 175
8	Disk tripwire tripped (via <code>--wait</code>)	result written at 171

Codes 7 and 8 (and a bulk-run 1) reach the caller only through `--wait` , which exits with the recorded `EXIT=` value (line 561).

Files written under `<P>/ .codegraph/` `index_runs/`

File	Written by
<code>index_<UTC>.log</code>	bulk runner output (line 522)
<code>sync_<UTC>.log</code>	incremental sync output (line 492) — not listed in the header
<code>run_<id>.pids</code>	<code>supervisor=</code> , <code>indexer_launch=</code> , <code>indexer=</code> , <code>watcher=</code> , <code>tripwire=</code> (lines 139-163, 524)
<code>run_<id>.result</code>	<code>EXIT=<n></code> + summary, atomic (lines 203-206)
<code>watch_<id>.log</code>	<code>index_watch.py</code> output (line 159)
<code>tripwire_<id>.log</code> (+ <code>.TRIPPED</code>)	<code>disk_tripwire.sh</code> (line 161)
<code>supervisor_<id>.log</code>	detached supervisor stdout/stderr (line 529)
<code>lock_reap.log</code>	reaped-lock decisions (line 375)
<code>probe/</code> , <code>probe_verdict.json</code>	only when the patch tool says NOT_NEEDED (line 432)

`<id>` is `<UTC>_<pid>` (line 521). `watch_state.json` is deleted before each bulk launch (line 523). Also created: `<P>/ .codegraph/ .helix_index.flock` (line 394).

Edge cases

- `--bulk` with `init / index` is accepted and changes nothing (always bulk).
- `unlock` with a stale lock and no `--reap-dead-lock` → exit 4.
- A missing Status doc is not a failure: `LEDGER: SKIP` (line 222).
- If no indexer identity is observed within 30 s, the run continues with no watcher and no tripwire (line 165).

Related scripts

Guide	Relation
codegraph_safe_helper	<code>identity</code> , <code>scan</code> , <code>dbinfo</code> , <code>pending</code> , <code>verify</code> , <code>scope</code> , <code>receipt</code> subcommands
disk_tripwire	Free-space watcher armed by the supervisor
index_watch	Progress-proven stall detector
fk_index_patch	Derives the patched runner
fk_cascade_probe	Proves stock safe when no patch is needed
code-graph_runner_patches	Registered runner patches
codegraph_guard	Gate that refuses bypasses of this script
codegraph_scope_guard	Scope proof
scope_render	Scope generator
codegraph_mcp_probe	MCP reachability probe
lumen_verify	Semantic-index health check
gen_lumenignore	Semantic-index scope generator
code-graph_lumen_overview	Overview

Last verified

2026-09-24 — read `codegraph_safe.sh` lines 1-561 in full (in slices); `bash -n codegraph_safe.sh` passed. The script was NOT executed (a live indexer holds the project DB). Helper subcommand internals were not read.