Multitrack

Multitrack

Automatic multi-track ruler orchestration (§11.4.187): a universal, automatic, out-of-the-box, inherited-by-reference engine. One conductor session spawns, drives, resumes, monitors and controls per-track headless workers (`claude -p --output-format stream-json`, session id taken from the `init` event, success read from `result.is_error` — never the exit code), with per-subscription authentication, rate-limit (429) rebind and fallback, and a crash-resilient self-supervisor over durable state. Bootstrap is idempotent and auto-invoked on every constitution pull through the §11.4.164 seam.

The consuming project supplies only per-host data: `config/multitrack/<hostname>.yaml`. The conductor stays home; tracks execute in their own checkouts.

Registration

`register.sh <project-root>` (defaults to `$PWD`) is the §11.4.164 auto-install trigger — it carries no wiring logic of its own and delegates entirely to `scripts/multitrack/multitrack_bootstrap.sh`, whose six idempotent steps are: install the cwd-hook symlink, check the CLI alias availability, validate the per-host config (fatal only here — host data is never invented), seed the orchestrator (`reconcile` + `status`), run the read-only drive-preparation probe, and leave the opt-in supervisor watchdog off by default.

Activation ceiling and similarity

Active-track count and worker fan-out are bounded by the host's measured budgets (§12.6 / §12.12); a second concurrent heavy build on one host is never scheduled (§11.4.96 UNSAFE catalogue).