

ARCHITECTURE_DIAGRAMS

Helix Cluster OS — Consolidated Architecture Diagrams

Field	Value
Revision	1
Created	2026-06-03
Status	active

Scope & honesty contract (CLAUDE-1 / CLAUDE-3, Constitution §11.4.106). This document collects the Helix Cluster OS architecture into a small set of **Mermaid** diagrams. It is a *visual companion* to the prose docs — it does not restate them. Every node in every diagram is labelled with a **real** package (`pkg/...`, `internal/...`) or binary (`cmd/...`) path that exists in this repository; the module path is `github.com/HelixDevelopment/helix_cluster`. Where an edge represents an integration that is **not yet wired in code**, it is drawn dashed and tagged **PLANNED**, matching `architecture/PHASE_8C_INTEGRATION.md`.

For the authoritative, lint-enforced component→package→origin mapping see `ARCHITECTURE.md` (enforced by `pkg/archlint`). **For runtime service prose, the registry schema, and foundation-package interfaces** see `MVP_ARCHITECTURE.md`. **For the full foundation-library catalogue** see `FOUNDATION_PACKAGES.md`. This file duplicates none of that prose; it diagrams it.

Legend for integration state: solid edge = runtime/coordination path grounded in code today; **dashed edge tagged PLANNED** = the interface/seam exists but the production wiring to the named package is not present yet (per `PHASE_8C_INTEGRATION.md`, verified `file:symbol`). Do not read dashed edges as live integration.

1. The L0–L7 layered stack

Helix is a seven-layer stack (L0–L7) over a hardware substrate, coordinated via **SWIM gossip** (`pkg/swim`) for membership and **Raft** consensus (`pkg/multiraft`, `pkg/kraft`) for strongly-consistent state, with an **Omega-model** two-level

scheduler ([pkg/scheduler](#)). Each layer consumes only the layers beneath it. Node labels below are representative real packages from the [ARCHITECTURE.md](#) Component Map; that table is the exhaustive, lint-checked source.

flowchart TB

```
    subgraph L7["L7 – Federation, multi-cluster & observability"]
        direction LR
        l7a["pkg/federation"]
        l7b["pkg/fedtopology"]
        l7c["pkg/metrics"]
        l7d["pkg/tracing"]
        l7e["pkg/grafanadash"]
    end
```

end

```
    subgraph L6["L6 – Control-plane services (cmd/helix-*)"]
        direction LR
        l6a["internal/gateway"]
        l6b["internal/session"]
        l6c["internal/health"]
        l6d["internal/policy"]
        l6e["internal/llm"]
        l6f["internal/scheduler"]
        l6g["internal/build"]
        l6h["internal/advisory"]
        l6i["internal/trust"]
    end
```

end

```
    subgraph L5["L5 – Secure transport & networking"]
        direction LR
        l5a["pkg/hybridkex<br/>(X25519+ML-KEM-768)"]
        l5b["cmd/e2ee-proxy"]
        l5c["internal/wireguard"]
        l5d["pkg/ice"]
        l5e["pkg/hashslot"]
    end
```

end

```
    subgraph L4["L4 – Scheduling, placement & economics"]
        direction LR
        l4a["pkg/scheduler<br/>(Omega)"]
        l4b["pkg/constraints"]
        l4c["pkg/preempt"]
        l4d["pkg/workloadrouter"]
        l4e["pkg/carbonsched"]
        l4f["pkg/economics"]
    end
```

end

```
    subgraph L3["L3 – Consensus & replicated state"]
        direction LR
        l3a["pkg/voting"]
        l3b["pkg/mvcc"]
        l3c["pkg/crdt"]
        l3d["pkg/deltacrdt"]
        l3e["pkg/antientropy"]
        l3f["pkg/hlc"]
    end
```

end

```
    subgraph L2["L2 – Membership & discovery"]
        direction LR
        l2a["pkg/swim"]
    end
```

```

    l2b["pkg/discovery"]
    l2c["pkg/scan"]
    l2d["pkg/nattraversal"]
    l2e["pkg/cellmesh"]
end
subgraph L1["L1 – Node lifecycle & boot"]
    direction LR
    l1a["internal/node"]
    l1b["internal/console"]
    l1c["cmd/helix-node"]
    l1d["pkg/local<br/>(TC0)"]
end
subgraph L0["L0 – Hardware / resource substrate"]
    direction LR
    l0a["pkg/resources<br/>(linux/darwin)"]
    l0b["pkg/gpuattest"]
    l0c["internal/gpu"]
    l0d["pkg/devicecatalog"]
    l0e["pkg/capability"]
    l0f["pkg/exportcontrol"]
end

L7 --> L6 --> L5 --> L4 --> L3 --> L2 --> L1 --> L0

```

Cross-cutting concerns (attestation, metrics, compliance) are surfaced as dedicated components rather than threaded implicitly through every layer — see the Component Map in [ARCHITECTURE.md](#) for the full per-component origin/HXC mapping.

2. Control-plane services & how they communicate

Each `cmd/helix-*` binary's `main.go` imports the correspondingly named `internal/*` package (verified: `cmd/helix-gateway/main.go` imports `internal/gateway`; `cmd/helix-node/main.go` imports `internal/node`). The operator drives the cluster through the gateway; the gateway fronts session, policy, LLM-router, health and scheduler; nodes register through discovery and gossip membership over SWIM.

This diagram is the visual form of [MVP_ARCHITECTURE.md §2](#); see that section for edge-by-edge verifiability notes.

```

graph TD
    operator([Operator / Client])

    subgraph cp ["Control plane (cmd/helix-*)"]
        gw["helix-gateway<br/>internal/gateway"]
        sess["helix-session<br/>internal/session"]
        pol["helix-policy<br/>internal/policy (OPA)"]
        llm["helix-llm<br/>internal/llm"]
        health["helix-health<br/>internal/health"]
        sched["helix-scheduler<br/>internal/scheduler + pkg/scheduler"]
    end

```

```

    sec["helix-security<br/>internal/security / internal/
trust"]
    build["helix-build<br/>internal/build"]
    adv["helix-advisory<br/>internal/advisory"]
end

subgraph coord["Coordination / state plane"]
    disc["pkg/discovery<br/>(etcd watch backend)"]
    swim["pkg/swim<br/>(SWIM gossip)"]
    raft["pkg/multiraft / pkg/kraft<br/>(Raft groups)"]
    bus["internal/messaging + pkg/events<br/>(NATS backend)"]
    reg["hxc-registry<br/>data/hxc_registry.db"]
end

subgraph nodes["Worker nodes (cmd/helix-node)"]
    node["internal/node + internal/console"]
    res["pkg/resources<br/>(linux/darwin probe)"]
end

operator -->|"HTTP / API"| gw
gw -->|"auth + route"| pol
gw -->|"PTY / streams"| sess
gw -->|"inference"| llm
gw -->|"liveness"| health
gw -->|"placement"| sched

sched -->|"resolve candidates"| disc
sched -->|"score by capacity"| res
sec -->|"attest / KYC gate"| sched
adv -->|"recommendations"| sched

disc -.->|"watch keyspace"| raft
cp -.->|"event pub/sub"| bus

node -->|"register instance"| disc
node -->|"gossip membership"| swim
node -->|"sample resources"| res
health -->|"probe"| node

reg -.->|"HXC work-item tracking (out-of-band)"| cp

```

Edge grounding. Discovery's etcd backend is [pkg/discovery/etcd_backend.go](#); the gateway routing surface is [internal/gateway/api.go](#) and [internal/gateway/inference.go](#); the NATS event path is [pkg/events/nats_backend.go](#) plus the in-process bus [internal/messaging/bus.go](#); Raft groups are [pkg/multiraft / pkg/kraft](#). The dotted hxc-registry edge is the development work-item registry ([cmd/hxc-registry](#) over [data/hxc_registry.db](#)), not a traffic-serving service.

Honest note. The [internal/messaging](#) [\[?\]](#) [pkg/events](#) bus and the [discovery](#) → [raft](#) [keyspace](#) edge are drawn dotted because they are coordination-plane substrates rather than a single fixed request path; the exact per-service NATS subjects/Raft groups a given binary uses are configuration-driven, not hard-wired in a way this diagram should overstate.

3. Request / data flow (workload → gateway → scheduler → session → node)

End-to-end placement of a workload, including the **attestation** and **E2EE** seams. Per `architecture/PHASE_8C_INTEGRATION.md`, the **attestation admission predicate itself is live** (the scheduler runs the AttestationGate plugin with an in-repo HMACAttestor), but **population of the node-trust flag from a real TEE/PoVW quote, and termination of an E2EE envelope inside an attested enclave, are PLANNED** (interface present, production backend not wired). Those seams are dashed below.

sequenceDiagram

autonumber

actor Client as Operator / Client

participant GW as helix-gateway
internal/gateway

participant POL as helix-policy
internal/policy

participant SCH as helix-scheduler
pkg/scheduler

participant GATE as AttestationGate
pkg/scheduler/

attestation.go

participant DISC as pkg/discovery (etcd)

participant SESS as helix-session
internal/session

participant NODE as cmd/helix-node
internal/node + pkg/

resources

Client->>GW: HTTP request (workload / inference)

GW->>POL: authorize + route (OPA)

POL-->>GW: allow

GW->>SCH: Schedule(workload)

SCH->>DISC: resolve candidate nodes

DISC-->>SCH: live instances

SCH->>NODE: score by capacity (pkg/resources snapshot)

SCH->>GATE: runFilters → AttestationGate.Filter(job, node)

Note over GATE: helix.attestation/required job admitted only
if
Attestor.Verify(node, token, now)==true (fail-closed)

GATE-->>SCH: admissible nodes [IMPLEMENTED: HMACAttestor]

SCH-->>GW: placement decision

GW->>SESS: open session / PTY + streams

SESS->>NODE: bind workload to node

NODE-->>SESS: stream stdout / results

SESS-->>GW: relay stream

GW-->>Client: response / live stream

rect rgb(245,240,230)

Note over Client,NODE: PLANNED seams (Phase 8C – interface exists, production wiring absent)

Client--xGW: PLANNED: e2ee.Session.Seal(prompt) PQ envelope (no router invokes it today)

GATE--xNODE: PLANNED: GPUInfo.Attested set from a verified TEE/PoVW quote (never driven by pipeline)

SESS--xNODE: PLANNED: envelope terminates inside attested

```
enclave (no e2ee/attestation ref in pkg/inference)
end
```

Grounding & honesty. The live admission path — Scheduler.Schedule → runFilters → AttestationGate.Filter → Attestor.Verify — is `pkg/scheduler/scheduler.go` + `pkg/scheduler/attestation.go`; the in-repo `HMACAttestor` does genuine constant-time HMAC-SHA256 token verification and fails closed when no `Attestor` is configured. The E2EE envelope itself is a complete PQ implementation in the `digital.vasic.security` submodule (`security/pkg/e2ee/package.go`: ML-KEM-768 + HKDF-SHA256 + AES-256-GCM), **but no main-repo router/inference package imports it yet** — hence the dashed PLANNED arrows. See `PHASE_8C_INTEGRATION.md` §5.1/§5.2 for the verified file:symbol index. The full multi-node distributed flow over a real deployed fleet is **not yet validated end-to-end** (tracked separately; requires a deployed cluster).

4. Tier matrix (high level)

Node capability tiers are defined as data in `pkg/tierdef/tierdef.yaml` (loaded by `pkg/tierdef/loader.go`), with each tier gated on minimum CPU cores, memory, GPU count/VRAM, network, and a power ceiling. The task focuses on **T1–T8**; the table below transcribes those rows verbatim from the YAML. (**Honest scope note:** the YAML actually defines a continuum **T1 through T15** — T9–T15 cover server+ through extreme multi-GPU flagship nodes; they are omitted here only for brevity, not because they are absent.) Edge-class tiers **T3–T8** are also the registration range of `pkg/edgeregistry`; device→tier resolution is via the device taxonomy in `pkg/devicecatalog` (a case-insensitive substring Lookup over the in-code catalog, which today ships **14 well-known device-family entries**, ordered most-specific-first; the broader “64-device” master taxonomy is a Phase-5 roadmap target tracked as queued issue HXC-1331, not yet authored in code).

```
graph LR
    subgraph tiers["pkg/tierdef/tierdef.yaml – T1..T8 (of T1..T15)"]
        direction TB
        T1["T1 micro<br/>1 core · 256MB · 0 GPU · ≤5W"]
        T2["T2 handheld<br/>2 core · 512MB · 0 GPU · ≤15W"]
        T3["T3 SBC/edge<br/>4 core · 2GB · 0 GPU · ≤25W"]
        T4["T4 workstation-lite<br/>8 core · 8GB · iGPU ok · ≤65W"]
        T5["T5 accelerated edge<br/>12 core · 16GB · 1 GPU/4GB · ≤150W"]
        T6["T6 workstation<br/>16 core · 32GB · 1 GPU/8GB · ≤300W"]
        T7["T7 pro workstation<br/>24 core · 64GB · 1 GPU/16GB · ≤500W"]
        T8["T8 server<br/>32 core · 128GB · 2 GPU/16GB · ≤700W"]
        T1 --> T2 --> T3 --> T4 --> T5 --> T6 --> T7 --> T8
    end

    cat["pkg/devicecatalog<br/>(14-entry device taxonomy Lookup)"]
    edge["pkg/edgeregistry<br/>(registers T3..T8 edge devices)"]
    res["pkg/resources<br/>(measured CPU/mem/GPU/power)"]
```

```
res -->|"measured capability"| tiers
cat -->|"resolve model → tier"| tiers
tiers -->|"T3..T8 edge subset"| edge
```

Grounding & honesty. The thresholds shown are the literal `min_cpu_cores / min_memory_mb / min_gpu / min_gpu_vram_mb / max_power_w` fields from `pkg/tierdef/tierdef.yaml` (schema version 1); memory is shown converted from MB to GB for readability. Resource measurement feeding tier assignment is the per-OS probe in `pkg/resources` (linux `sysfs` / darwin `system_profiler`, CLAUDE-2 cross-platform parity); device-model→tier resolution is `pkg/devicecatalog`. This diagram shows tier *definitions and their data sources*; it does not assert that every tier has been exercised on real hardware.

Maintenance

This document is a visual companion and is kept in sync under CLAUDE-3 / §11.4.106 alongside its sources: when the layer stack, control-plane service set, request flow, Phase 8C integration state, or the tier definitions change, update the corresponding diagram here in the same work unit. The canonical, lint-checked component map remains `ARCHITECTURE.md`; runtime prose and the registry schema remain `MVP_ARCHITECTURE.md`; the Phase 8C seam states (IMPLEMENTED vs PLANNED) remain `architecture/PHASE_8C_INTEGRATION.md`; the foundation-library catalogue remains `FOUNDATION_PACKAGES.md`. The `docs_chain` engine keeps this file's HTML/PDF/DOCX exports in sync (`docs_chain sync`) and gates them (`docs_chain verify`).