

Status

CodeGraph — Status

Revision: 1 Last modified: 2026-05-28T12:03:15Z

Field	Value
Revision	1
Created	2026-05-28
Last modified	2026-05-28T12:03:15Z
Status	active
Status summary	Append-only ledger of every CodeGraph-related event for HelixCode (config changes, index regenerations, sync runs, validation probes). Per §11.4.78 (CodeGraph parent), §11.4.79 (own-org submodule inclusion), §11.4.80 (regular-update + sync automation), §11.4.45 / §11.4.56 (Status-doc shape). The weekly update + sync automation is INHERITED BY REFERENCE from the constitution submodule — invoke <code>constitution/scripts/codegraph_update.sh</code> and <code>constitution/scripts/codegraph_sync.sh</code> (never copied).
Issues	none
Issues summary	—
Fixed	HXC-017 (own-org submodule inclusion in index)
Continuation	sibling <code>Status_Summary.md</code> carries the operator-readable digest per §11.4.56.

Table of contents

- [Cadence + automation \(§11.4.80\)](#)
- [Index configuration \(§11.4.79\)](#)
- [Event ledger](#)

Cadence + automation (§11.4.80)

Per §11.4.80, HelixCode MUST run the CodeGraph update + sync automation at least weekly (cadence floor per §11.4.45 status-digest cadence). The two canonical scripts are **inherited by**

reference from the constitution submodule (per §3 submodule inheritance) and **MUST** be invoked at their constitution-submodule paths — never copied into HelixCode:

- `constitution/scripts/codegraph_update.sh` — npm-installs the latest `@colbymchenry/codegraph`, verifies `codegraph --version` reflects the new version (anti-bluff: npm exit 0 is not proof of a working binary), and appends old/new version to this ledger.
- `constitution/scripts/codegraph_sync.sh` — after a successful update runs `codegraph status` → `codegraph sync` . → `codegraph status` → validation, appending every step's output to this ledger.

Regeneration mechanism (per §11.4.77): `.codegraph/codegraph.db` is gitignored; `codegraph index` . (full) or `codegraph sync` . (incremental) regenerates it from `.codegraph/config.json` (tracked).

Index configuration (§11.4.79)

`.codegraph/config.json` (tracked) controls which paths enter the index. Per §11.4.79 the `dependencies/ tree` is split by submodule ownership:

INCLUDED — own-org submodules (full CLI access via vasic-digital + HelixDevelopment):

- `dependencies/vasic-digital/**` — ~55 own-org submodules (EventBus, Concurrency, Observability, Auth, Storage, VectorDB, Embeddings, Database, Cache, Messaging, Formatters, MCP_Module, RAG, Memory, Optimization, Plugins, Agentic, LLMops, SelfImprove, Planning, Benchmark, ToolSchema, SkillRegistry, Models, LLMProvider, BackgroundTasks, DocProcessor, conversation, LLMOrchestrator, VisionEngine, Normalize, RedTeam, PliniusCommon, GandalfSolutions, AutoTemp, HyperTune, I-LLM, Streaming, Veritas, LeakHub, Claritas, Ouroborous, Config, Lazy, Watcher, Middleware, RateLimiter, I18n, Recovery, Document, Filesystem, TOON, ...).
- `dependencies/HelixDevelopment/**` — own-org submodules (DocProcessor, LLMOrchestrator, LLMProvider, VisionEngine, LLMsVerifier, Models, HelixMemory, HelixSpecifier, HelixLLM, DebateOrchestrator, ...).

EXCLUDED — third-party vendored submodules (per §11.4.74 no-match → vendor):

- `dependencies/LLama_CPP/**` — `git@github.com:ggml-org/llama.cpp.git`
- `dependencies/Ollama/**` — `git@github.com:ollama/ollama.git`
- `dependencies/HuggingFace_Hub/**` — `git@github.com:huggingface/huggingface_hub.git`

Credential/secret exclusions (per §11.4.10, belt-and-suspenders): the `include` list is code-extensions only (no `.env` / `.key` / `.pem`), and the `exclude` list additionally pins `**/.env`, `**/.env.*`, `**/*.key`, `**/*.pem`, `**/secrets/**` so no credential path can ever be indexed.

Event ledger

(events appended below by the automation; newest at the bottom)

2026-05-28T12:03:15Z — HXC-017 config fix: include own-org submodules, exclude only third-party (§11.4.79)

- **Defect:** `.codegraph/config.json` carried a blanket `dependencies/** exclude` that wrongly removed ALL own-org submodules (`dependencies/vasic-digital/** + dependencies/HelixDevelopment/**`) from the index — a §11.4.79 violation (own-org submodules MUST be INCLUDED; only third-party submodules excluded).
- **Fix:** replaced the blanket `dependencies/** exclude` with three specific third-party excludes (`dependencies/LLama_CPP/**`, `dependencies/Ollama/**`, `dependencies/HuggingFace_Hub/**`); added explicit credential excludes (`**/.env`, `**/.env.*`, `**/*.key`, `**/*.pem`, `**/secrets/**`) per §11.4.10.
- **Config JSON validity:** confirmed via `python3 -c "import json; json.load(open('.codegraph/config.json'))"` → VALID.
- **Index status BEFORE re-index:** Files 39,024 / Nodes 624,103 / Edges 1,643,200 / DB 1609.00 MB.
- **Index status AFTER re-index** (`codegraph index ., exit 0`): Files **76,044** / Nodes **1,255,974** / Edges **3,955,444** / DB 2617.24 MB. The +37,020 files / +631,871 nodes delta is the newly-included own-org submodule trees.
- **§11.4.79 anti-bluff probe (own-org symbol now resolves):**
 - `codegraph query EventBus` → `submodules/event_bus/pkg/bus/bus.go:85` ✅ (would NOT have resolved under the old blanket `dependencies/** exclude`).
 - `codegraph query helix_memory` → `submodules/helix_memory/pkg/config/config.go` (+more) ✅.
 - `codegraph query llama` filtered to `dependencies/LLama_CPP` → **empty** ✅ (third-party correctly excluded).
- **HXC-017 status:** fully done — config fixed, re-index complete, own-org inclusion proven, third-party exclusion proven.

2026-05-29T06:37:00Z — codegraph_sync.sh @ /run/media/milosvasic/DATA4TB/Projects/HelixCode

FAIL — `codegraph sync` exited non-zero. Tail of log: `` `└ Syncing CodeGraph [2m | [0m (raw progress-spinner log line removed — was 25387 chars of ANSI noise from `codegraph_sync.sh`; see `qa-results/ logs`) (raw progress-spinner log line removed — was 3007584 chars of ANSI noise from `codegraph_sync.sh`; see `qa-results/ logs`)

2026-05-29 — codegraph 0.9.7 update: index/sync FAIL + §11.4.79 own-org regression (HXC-033)

Event: operator installed `codegraph 0.9.7` on the host (`codegraph --version` → `0.9.7`).

§11.4.80 post-update sync — FAILED (honest ledger, no bluff): - The 0.9.7 install reset the gitignored index DB (was 76,044 files / 1,255,974 nodes at HXC-017; dropped to 39,203). - `constitution/scripts/codegraph_sync.sh` ran `codegraph sync .` → exited before completing its 4 steps (index reached 43,073 files). - Full re-index `codegraph index .` → process **KILLED mid-run, no diagnostic / no exit code** (terminated by signal); index left at 54,207 files. Reproduced. - `codegraph index . --force --quiet` → **KILLED again, no diagnostic**; `--force` wiped + left only 4,630 files. - `codegraph`

`sync . --quiet` → **exit 1** at 8,461 files. - Host memory ample (51 GiB free) — not an obvious §12.6 OOM.

§11.4.79 anti-bluff probe — FAILS: `codegraph_search BundleTranslator` (MCP) returns ONLY `helix_code/internal/tools/askuser/...` — the `own-org submodules/llm_orchestrator/pkg/i18n/bundle.go` symbol does NOT resolve. Own-org submodules are NOT reachable in the 0.9.7 index. **This is a §11.4.79 regression introduced by the 0.9.7 update.**

Not a config regression: tracked `.codegraph/config.json` is intact (git-clean) — `own-org` includes + §11.4.10 credential excludes (`**/.env`, `**/*.key`, `**/secrets/**`) all present.

Root cause: UNCONFIRMED (§11.4.6) — `codegraph 0.9.7 index/sync` terminate without an actionable diagnostic on this 76k-file repo. Not determinable from captured evidence whether it is a 0.9.7 stability bug, a submodule-traversal change, or a config-schema change. Filed as **HXC-033**; needs operator decision (downgrade to prior working version / upstream bug report / accept degraded index). Evidence: `qa-results/codegraph_index_*.log`, `codegraph_recover_*.log`.

2026-05-29 — codegraph 0.9.7 RESOLVED: wipe + init + re-index restored own-org index (HXC-033 → Fixed)

Resolution (operator-directed: “clear all indexed data fully and re-index — it MUST be a data-compatibility problem; ALWAYS index main + HelixDevelopment + vasic-digital”). Confirmed correct.

Root cause (now CONFIRMED, was UNCONFIRMED): `codegraph 0.9.7` requires an **explicit** `codegraph init` before `index` (behavioral change vs the prior version). The pre-0.9.7 index DB was incompatible; operating on it produced the failures. After a full wipe of the gitignored DB (`codegraph.db/-wal/-shm`; the 1.7 GB stale WAL was a tell) + `codegraph init` (tracked `config.json` preserved — `own-org` includes + §11.4.10 credential excludes intact) + `codegraph index .`, the index rebuilt cleanly.

Two earlier mis-diagnoses corrected (per §11.4.6 — stated here as the record): (1) “index crashes/killed mid-run” was a FAULTY `pgrep` pattern (`codegraph index` vs the real node ... `codegraph.js index .`) giving false “ENDED” reads — the process was simply slow (76k files); real `ps` showed it alive (~600 MB RSS, healthy, climbing). (2) “own-org symbols do not resolve” used the WRONG CLI verb (`codegraph search` — removed in 0.9.7; the verb is `codegraph query`) AND queried a stale MCP-server DB handle from before the re-index.

Result (CLI `codegraph status` on fresh 0.9.7 DB): Files **75,663** / Nodes **1,272,492** / Edges finalizing (1.7M→ toward ~3.95M; edge-enrichment phase runs async after node indexing).

§11.4.79 anti-bluff probe — PASS (`codegraph query`, fresh DB): - `NewBundleTranslator` → `submodules/llm_orchestrator/pkg/i18n/bundle.go:34` (+ `dependencies/vasic-digital/...`, `doc_processor`) — 10 own-org hits. ✅ `HelixDevelopment + vasic-digital` both reachable. - `EventBus` → resolves. ✅ - `llama_model_load` under `dependencies/LLama_CPP` → empty. ✅ third-party correctly excluded.

Status.md hygiene fix: this ledger had bloated to 3.66 MB — a single 3,007,584-char line of raw ANSI progress-spinner output that `constitution/scripts/codegraph_sync.sh` dumped verbatim on its earlier FAIL. Stripped to 8 KB (all 7 real ledger entries preserved).

FOLLOW-UP: `codegraph_sync.sh` should strip ANSI / not dump raw spinner logs into `Status.md` (constitution-submodule fix per §11.4.26).

Operational follow-up: the agent-facing codegraph **MCP server** (`tools/codegraph/. . . serve --mcp`, a separate install) holds the pre-wipe DB inode — it must be **restarted** to serve the fresh index to AI agents; the CLI query already reflects it.