

phased_implementation_plan

Ultimate Phased Implementation Plan: LLMsVerifier Integration into HelixCode

Document Version: 1.0.0
Date: 2026-07-01
Author: Master Implementation Planner
Status: AUTHORITATIVE — NO VAGUENESS PERMITTED
Constitutional Basis: CONST-036 through CONST-040, CONST-035 (Anti-Bluff),
CONST-017 (Zero-Bluff Testing), CONST-021 (No Mocks Above Unit)

EXECUTIVE SUMMARY

This plan specifies **every single action** required to integrate LLMsVerifier as the single source of truth for model provisioning in HelixCode. Every task includes exact file paths, line numbers, complete code, acceptance criteria, dependencies, and effort estimates. Nothing is left to interpretation.

Gaps in LLMsVerifier That Must Be Fixed During Implementation

Gap	Location	Impact	Fix Required
STUB-001	verification/ verification.go	Returns hardcoded 8.5 scores for ALL dimensions	Replace stub with real coding_capability integration
STUB-002	api/server.go	Only 5 endpoints wired; full CRUD missing	Wire all handlers: models, pricing, limits, events, sch
STUB-003	auth/ oauth_stub.go	OAuth flows are placeholder	Implement real OAuth tok OAuth providers from def
MISSING-001	providers/	Only 12 providers vs HelixCode's 35+	Add 23 additional provide Bedrock, VertexAI, Qwen
MISSING-002	External module	digital.vasic.llmprovider at ../../LLMProvider required	Decision: Use REST API o module import to avoid pa
MISSING-003	Real-time push	No webhooks, SSE, or push notifications	Use polling-only architect

Bluff Areas in HelixCode That This Integration Fixes

Bluff ID	File	Current State	Fix
BLUFF-002	cmd/cli/ main.go:101-128	Hardcoded 3-model list	Replace with verifier adapter fetch
BLUFF-001		Simulated LLM response	

Bluff ID	File	Current State	Fix
	cmd/cli/main.go.old		Route ALL generation through real provider via verifier-selected model
BLUFF-003	cmd/cli/main.go:237-250	Simulated command execution	Replace time.Sleep with actual command execution
BLUFF-004	internal/llm/model_discovery.go	Hardcoded external models in fetchExternalModels()	Replace with verifier adapter call
BLUFF-005	internal/llm/model_manager.go	Scoring ignores real verification data	Augment SelectOptimalModel() with verifier scores
BLUFF-006	internal/llm/factory.go	No verifier-aware provider validation	Add health/score validation before returning provider

ROLLBACK & VERIFICATION STRATEGY (Global)

Rollback Plan Template (Applied Per Phase)

For each phase, the rollback procedure is: 1. `git checkout -- <files-modified-in-this-phase>` 2. `git rm --cached <files-created-in-this-phase>` (then `rm` them) 3. Restore previous `go.mod` with `git checkout -- helix_code/go.mod` 4. Run `make test-unit` to verify baseline passes 5. Run `make build` to verify compilation succeeds

Phase Verification Steps (Applied Per Phase)

After completing each phase, run: 1. `cd HelixCode && go build ./...` — Must compile with zero errors 2. `make test-unit` — Must pass (short tests only) 3. `make test-verifier-hardcode` — Must show zero hardcoded models in modified files 4. `make build-cli && ./bin/cli --help` — CLI must show new flags 5. `grep -r "llama-3-8b" cmd/cli/main.go` — Must return zero matches (BLUFF-002 fixed)

PHASE 1: FOUNDATION — Configuration, Dependencies, Basic Integration

Phase Goal: Establish the infrastructure for LLMsVerifier integration. All config, types, client, and wiring must be in place before any feature code.

Phase Entry Criteria: None — this is the first phase. **Phase Exit Criteria:** 1. `go build ./...` compiles with zero errors 2. All new config structs are loaded and validated correctly 3. REST API client can connect to a mock verifier server 4. All 20+ env var bindings are tested

TASK 1.1: Add LLMsVerifier REST API Client Dependency

NOTE: We do NOT import LLMsVerifier as a Go module (it depends on `digital.vasic.llmprovider` at `../LLMProvider` which is incompatible with `dev.helix.code`). Instead, we use HTTP REST API calls. No new Go module dependency is needed — we only use `net/http` from `stdlib`.

TASK 1.1.1: Verify No Module Import Required

File(s): `helix_code/go.mod` **Line(s):** EOF — verify no `replace digital.vasic.llmsverifier` or `digital.vasic.llmprovider` entries **Action:** VERIFY

```
// Check that go.mod does NOT contain:  
// replace digital.vasic.llmsverifier => ...  
// require digital.vasic.llmprovider ...
```

Acceptance Criteria: 1. `grep -E "digital\.vasic|llmsverifier|llmprovider" helix_code/go.mod` returns zero matches 2. `go mod tidy` completes without adding LLMsVerifier as a dependency

Dependencies: None **Effort:** Small

TASK 1.2: Add VerifierConfig Struct to internal/config/config.go

TASK 1.2.1: Add VerifierConfig and Related Structs

File(s): `helix_code/internal/config/config.go` **Line(s):** After line 253 (after `Cognee *CogneeConfig` field) **Action:** MODIFY

```
// ... existing fields ...  
Cognee      *CogneeConfig      `mapstructure:"cognee"`  
Verifier    *VerifierConfig    `mapstructure:"verifier" // NEW — LLMsVerifier  
           integration`  
HelixAgent  *HelixAgentConfig  `mapstructure:"helix_agent" // NEW — HelixAgent  
           submodule sync`  
}
```

Append the following struct definitions at the end of `config.go` (after existing struct definitions, before function definitions):

```
// VerifierConfig controls LLMsVerifier integration.  
type VerifierConfig struct {  
    Enabled    bool  
    `mapstructure:"enabled"`  
    Mode       string  
    `mapstructure:"mode" // "remote" | "embedded"
```

```

Endpoint      string
    `mapstructure:"endpoint"`           // REST API URL
APIKey        string
    `mapstructure:"api_key"`           // Auth key for verifier
API
Timeout       time.Duration
    `mapstructure:"timeout"`
CacheTTL      time.Duration
    `mapstructure:"cache_ttl"`
PollingInterval time.Duration
    `mapstructure:"polling_interval"`
Scoring       VerifierScoringConfig
    `mapstructure:"scoring"`
Health       VerifierHealthConfig
    `mapstructure:"health"`
Events       VerifierEventsConfig
    `mapstructure:"events"`
Providers     map[string]VerifierProviderConfig
    `mapstructure:"providers"`
}

// VerifierScoringConfig mirrors HelixAgent's scoring weights.
type VerifierScoringConfig struct {
    Weights          ScoringWeights `mapstructure:"weights"`
    ModelsDevEnabled bool
    `mapstructure:"models_dev_enabled"`
    ModelsDevEndpoint string
    `mapstructure:"models_dev_endpoint"`
    MinAcceptableScore float64
    `mapstructure:"min_acceptable_score"`
}

// ScoringWeights defines the 5-component weight distribution.
// Weights MUST sum to exactly 1.0 (validated at startup).
type ScoringWeights struct {
    CodeCapability float64
    `mapstructure:"code_capability"` // default: 0.40
    Responsiveness float64
    `mapstructure:"responsiveness"` // default: 0.20
    Reliability    float64
    `mapstructure:"reliability"`    // default: 0.20
    FeatureRichness float64
    `mapstructure:"feature_richness"` // default: 0.15
    ValueProposition float64
    `mapstructure:"value_proposition"` // default: 0.05
}

```

```

// VerifierHealthConfig mirrors HelixAgent's circuit breaker
config.
type VerifierHealthConfig struct {
    CheckInterval    time.Duration
        `mapstructure:"check_interval"`
    Timeout          time.Duration
        `mapstructure:"timeout"`
    FailureThreshold int
        `mapstructure:"failure_threshold"`
    RecoveryThreshold int
        `mapstructure:"recovery_threshold"`
    CircuitBreaker    CircuitBreakerConfig
        `mapstructure:"circuit_breaker"`
}

// CircuitBreakerConfig controls automatic failover behavior.
type CircuitBreakerConfig struct {
    Enabled          bool        `mapstructure:"enabled"`
    HalfOpenTimeout time.Duration
        `mapstructure:"half_open_timeout"`
}

// VerifierEventsConfig controls event publishing.
type VerifierEventsConfig struct {
    Enabled          bool    `mapstructure:"enabled"`
    WebSocket        bool    `mapstructure:"websocket"`
    WebSocketPath    string `mapstructure:"websocket_path"`
}

// VerifierProviderConfig – per-provider override.
type VerifierProviderConfig struct {
    Enabled    bool    `mapstructure:"enabled"`
    APIKey     string `mapstructure:"api_key" json:"- "
        yaml:"api_key" // json:"- " prevents serialization
    BaseURL    string `mapstructure:"base_url"`
    Models     []string `mapstructure:"models"`
    Priority    int     `mapstructure:"priority"`
}

// HelixAgentConfig controls HelixAgent submodule integration.
type HelixAgentConfig struct {
    Enabled          bool        `mapstructure:"enabled"`
    Path            string      `mapstructure:"path" // submodule path`
    AutoStart        bool        `mapstructure:"auto_start"`
    VerifierSync     HelixAgentVerifierSync
        `mapstructure:"verifier_sync"`
}

```

```

}

// HelixAgentVerifierSync controls bidirectional score sharing.
type HelixAgentVerifierSync struct {
    Enabled      bool      `mapstructure:"enabled"`
    ShareScores  bool      `mapstructure:"share_scores"`
    ShareProviders bool    `mapstructure:"share_providers"`
    SyncInterval time.Duration `mapstructure:"sync_interval"`
}

```

Acceptance Criteria: 1. `go build ./internal/config/...` compiles with zero errors
 2. Config struct now has Verifier and HelixAgent fields
 3. VerifierConfig has all 9 top-level fields with correct mapstructure tags
 4. APIKey fields have `json: "-"` to prevent accidental serialization

Dependencies: None **Effort:** Medium

TASK 1.2.2: Add Viper Defaults for All Verifier Config Options

File(s): `helix_code/internal/config/config.go` **Line(s):** Inside `setDefault()` function, after existing defaults **Action:** MODIFY

Locate the existing `setDefault()` function (around line 300+). Append inside the function body:

```

func setDefaults() {
    // ... existing defaults ...

    // LLMsVerifier defaults
    v.SetDefault("verifier.enabled", false)
    v.SetDefault("verifier.mode", "remote")
    v.SetDefault("verifier.endpoint", "http://localhost:8081")
    v.SetDefault("verifier.timeout", "30s")
    v.SetDefault("verifier.cache_ttl", "5m")
    v.SetDefault("verifier.polling_interval", "60s")

    // Scoring defaults (match LLMsVerifier README weights)
    v.SetDefault("verifier.scoring.weights.code_capability",
        0.40)
    v.SetDefault("verifier.scoring.weights.responsiveness", 0.20)
    v.SetDefault("verifier.scoring.weights.reliability", 0.20)
    v.SetDefault("verifier.scoring.weights.feature_richness",
        0.15)
    v.SetDefault("verifier.scoring.weights.value_proposition",
        0.05)
    v.SetDefault("verifier.scoring.min_acceptable_score", 6.0)
    v.SetDefault("verifier.scoring.models_dev_enabled", true)
    v.SetDefault("verifier.scoring.models_dev_endpoint",
        "https://api.models.dev")
}

```

```

// Health defaults (match HelixAgent circuit breaker)
v.SetDefault("verifier.health.check_interval", "30s")
v.SetDefault("verifier.health.timeout", "10s")
v.SetDefault("verifier.health.failure_threshold", 5)
v.SetDefault("verifier.health.recovery_threshold", 3)
v.SetDefault("verifier.health.circuit_breaker.enabled", true)
v.SetDefault("verifier.health.circuit_breaker.half_open_timeout",
    "60s")

// Event defaults
v.SetDefault("verifier.events.enabled", true)
v.SetDefault("verifier.events.websocket", false)
v.SetDefault("verifier.events.websocket_path", "/ws/verifier/
    events")

// HelixAgent defaults
v.SetDefault("helix_agent.enabled", false)
v.SetDefault("helix_agent.path", "./HelixAgent")
v.SetDefault("helix_agent.auto_start", false)
v.SetDefault("helix_agent.verifier_sync.enabled", true)
v.SetDefault("helix_agent.verifier_sync.share_scores", true)
v.SetDefault("helix_agent.verifier_sync.sync_interval", "5m")
}

```

Acceptance Criteria: 1. `go test -short ./internal/config/...` passes 2. Loading config with empty file produces `verifier.enabled=false` and `verifier.endpoint="http://localhost:8081"` 3. Weight defaults sum to 1.0: $0.40+0.20+0.20+0.15+0.05 == 1.0$

Dependencies: TASK 1.2.1 **Effort:** Small

TASK 1.2.3: Add Environment Variable Bindings

File(s): `helix_code/internal/config/config.go` **Line(s):** After existing explicit env var bindings (after `HELIX_REDIS_PORT` binding) **Action:** MODIFY

```

// Explicitly bind critical env vars
_ = v.BindEnv("auth.jwt_secret", "HELIX_AUTH_JWT_SECRET")
_ = v.BindEnv("database.password", "HELIX_DATABASE_PASSWORD")
_ = v.BindEnv("database.host", "HELIX_DATABASE_HOST")
_ = v.BindEnv("redis.password", "HELIX_REDIS_PASSWORD")
_ = v.BindEnv("redis.host", "HELIX_REDIS_HOST")
_ = v.BindEnv("redis.port", "HELIX_REDIS_PORT")

// NEW: LLMsVerifier env var bindings
_ = v.BindEnv("verifier.enabled", "HELIX_VERIFIER_ENABLED")
_ = v.BindEnv("verifier.endpoint", "HELIX_VERIFIER_ENDPOINT")
_ = v.BindEnv("verifier.api_key", "HELIX_VERIFIER_API_KEY")

```

```

_ = v.BindEnv("verifier.timeout", "HELIX_VERIFIER_TIMEOUT")
_ = v.BindEnv("verifier.cache_ttl",
    "HELIX_VERIFIER_CACHE_TTL")
_ = v.BindEnv("verifier.polling_interval",
    "HELIX_VERIFIER_POLLING_INTERVAL")
_ = v.BindEnv("verifier.scoring.models_dev_endpoint",
    "HELIX_MODELS_DEV_ENDPOINT")
_ = v.BindEnv("verifier.scoring.min_acceptable_score",
    "HELIX_VERIFIER_MIN_SCORE")

// NEW: Per-provider API key bindings (dual-prefix support)
_ = v.BindEnv("verifier.providers.openai.api_key",
    "HELIX_OPENAI_API_KEY")
_ = v.BindEnv("verifier.providers.anthropic.api_key",
    "HELIX_ANTHROPIC_API_KEY")
_ = v.BindEnv("verifier.providers.gemini.api_key",
    "HELIX_GEMINI_API_KEY")
_ = v.BindEnv("verifier.providers.deepseek.api_key",
    "HELIX_DEEPSEEK_API_KEY")
_ = v.BindEnv("verifier.providers.groq.api_key",
    "HELIX_GROQ_API_KEY")
_ = v.BindEnv("verifier.providers.together.api_key",
    "HELIX_TOGETHER_API_KEY")
_ = v.BindEnv("verifier.providers.mistral.api_key",
    "HELIX_MISTRAL_API_KEY")
_ = v.BindEnv("verifier.providers.xai.api_key",
    "HELIX_XAI_API_KEY")
_ = v.BindEnv("verifier.providers.cerebras.api_key",
    "HELIX_CEREBRAS_API_KEY")
_ = v.BindEnv("verifier.providers.cloudflare.api_key",
    "HELIX_CLOUDFLARE_API_KEY")
_ = v.BindEnv("verifier.providers.cloudflare.account_id",
    "HELIX_CLOUDFLARE_ACCOUNT_ID")
_ = v.BindEnv("verifier.providers.siliconflow.api_key",
    "HELIX_SILICONFLOW_API_KEY")
_ = v.BindEnv("verifier.providers.replicate.api_token",
    "HELIX_REPLICATE_API_TOKEN")
_ = v.BindEnv("verifier.providers.openrouter.api_key",
    "HELIX_OPENROUTER_API_KEY")
_ = v.BindEnv("verifier.providers.qwen.api_key",
    "HELIX_QWEN_API_KEY")
_ = v.BindEnv("verifier.providers.cohere.api_key",
    "HELIX_COHERE_API_KEY")
_ = v.BindEnv("verifier.providers.ollama.host",
    "HELIX_OLLAMA_HOST")
_ = v.BindEnv("verifier.providers.llamacpp.host",
    "HELIX_LLAMA_CPP_HOST")

```


Acceptance Criteria: 1. `grep -c "BindEnv.*HELIX_" internal/config/config.go` returns ≥ 30 bindings 2. `go test -short ./internal/config/...` passes 3. Setting `HELIX_VERIFIER_ENABLED=true` in env causes `cfg.Verifier.Enabled == true` 4. Setting `HELIX_OPENAI_API_KEY=sk-test` causes `cfg.Verifier.Providers["openai"].APIKey == "sk-test"`

Dependencies: TASK 1.2.2 **Effort:** Small

TASK 1.2.4: Add Config Validation Rules

File(s): `helix_code/internal/config/config.go` **Line(s):** Inside `validateConfig()` function, before return `nil` **Action:** MODIFY

```
func (c *Config) validateConfig() error {
    // ... existing validation ...

    // NEW: Verifier config validation
    if c.Verifier != nil && c.Verifier.Enabled {
        if c.Verifier.Mode != "remote" && c.Verifier.Mode !=
            "embedded" {
            return fmt.Errorf("verifier.mode must be 'remote' or
            'embedded', got: %s", c.Verifier.Mode)
        }
        if c.Verifier.Endpoint == "" && c.Verifier.Mode ==
            "remote" {
            return
            fmt.Errorf("verifier.endpoint is required when mode is
            'remote'")
        }
        if c.Verifier.PollingInterval < 10*time.Second {
            return fmt.Errorf("verifier.polling_interval must be
            >= 10s, got: %s", c.Verifier.PollingInterval)
        }
        if c.Verifier.CacheTTL < 1*time.Second {
            return fmt.Errorf("verifier.cache_ttl must be >= 1s,
            got: %s", c.Verifier.CacheTTL)
        }

        // Validate scoring weights sum to 1.0
        totalWeight := c.Verifier.Scoring.Weights.CodeCapability
        +
            c.Verifier.Scoring.Weights.Responsiveness +
            c.Verifier.Scoring.Weights.Reliability +
            c.Verifier.Scoring.Weights.FeatureRichness +
            c.Verifier.Scoring.Weights.ValueProposition
        if math.Abs(totalWeight-1.0) > 0.001 {
            return fmt.Errorf("verifier scoring weights must sum
            to 1.0, got: %.3f", totalWeight)
        }
    }
}
```

```

// Validate min acceptable score range
if c.Verifier.Scoring.MinAcceptableScore < 0.0 ||
c.Verifier.Scoring.MinAcceptableScore > 10.0 {
    return
    fmt.Errorf("verifier.scoring.min_acceptable_score must be
0.0-10.0, got: %.1f",
        c.Verifier.Scoring.MinAcceptableScore)
}

// Validate provider configs
for name, pc := range c.Verifier.Providers {
    if pc.APIKey != "" && len(pc.APIKey) < 8 {
        return fmt.Errorf("verifier.providers.%s.api_key
is too short (minimum 8 chars)", name)
    }
}

return nil
}

```

Acceptance Criteria: 1. Config{Verifier: &VerifierConfig{Enabled: true, Mode: "invalid"}} returns error 2. Config with weights {0.3, 0.3, 0.3, 0.3, 0.3} (sum=1.5) returns error 3. Config with weights {0.40, 0.20, 0.20, 0.15, 0.05} (sum=1.0) passes 4. go test -short ./internal/config/... passes

Dependencies: TASK 1.2.3 **Effort:** Small

TASK 1.3: Create configs/verifier.yaml

TASK 1.3.1: Create Full Verifier Config Schema

File(s): helix_code/configs/verifier.yaml **Line(s):** CREATE new file **Action:** CREATE

```

# configs/verifier.yaml – LLMsVerifier Configuration Schema
# Version: 1.0.0
# Required by: CONST-036 (All Providers and Models Integration
Mandate)
# This file is loaded by Viper alongside config.yaml

```

verifier:

```

# -----
# SECTION 1: Master Enable/Disable
# -----
enabled: false                                # bool    – Master
switch for entire verifier subsystem

```

```

                                #           When false:
all verifier features bypassed,
                                #
ModelManager falls back to legacy behavior
                                # Default: false (safe
default)
                                # Env:
HELIX_VERIFIER_ENABLED

mode: "remote"                  # string – "remote"
                                (external service) or "embedded" (same-process)
                                # Default: remote
                                # Env:
HELIX_VERIFIER_MODE

endpoint: "http://
localhost:8081"                # string – Verifier REST API URL
                                # Default: http://
localhost:8081
                                # Env:
HELIX_VERIFIER_ENDPOINT

api_key: "${HELIX_VERIFIER_API_KEY}" # string – API key for
                                authenticating TO the verifier
                                # Default: ""
                                # Env:
HELIX_VERIFIER_API_KEY

timeout: "30s"                 # duration – HTTP
                                timeout for verifier API calls
                                # Default: 30s
                                # Env:
HELIX_VERIFIER_TIMEOUT

cache_ttl:
"5m"                          # duration – In-memory +
                                Redis cache TTL
                                # Default: 5m
                                # Env:
HELIX_VERIFIER_CACHE_TTL

polling_interval: "60s"        # duration – Background
                                polling interval
                                # Default: 60s
                                # Env:
HELIX_VERIFIER_POLLING_INTERVAL

```

SECTION 2: Scoring Configuration

```
scoring:
  weights:                                # map[string]float64 -
    MUST sum to 1.0
    code_capability: 0.40                  # Weight for coding
    task success rate
    responsiveness: 0.20                  # Weight for latency
    performance
    reliability: 0.20                     # Weight for uptime/
    error rate
    feature_richness: 0.15                # Weight for tool
    use, streaming, vision, etc.
    value_proposition: 0.05              # Weight for cost
    effectiveness

  models_dev_enabled: true                # bool    - Enable
    models.dev price fetch
  models_dev_endpoint: "https://api.models.dev" # string -
    Pricing data endpoint
  cache_ttl:
    "24h"                                # duration - Score cache TTL
  min_acceptable_score: 6.0               # float64 - Minimum
    score for auto-selection (0.0-10.0)
```

SECTION 3: Health Monitoring

```
health:
  check_interval: "30s"                   # duration - Health
    check interval
  timeout: "10s"                          # duration - Health
    check timeout
  failure_threshold: 5                     # int      - Consecutive
    failures before circuit opens
  recovery_threshold: 3                    # int      - Consecutive
    successes before circuit closes
  circuit_breaker:
    enabled: true                          # bool     - Enable
    circuit breaker
    half_open_timeout: "60s"              # duration - Time in
    half-open before retry
```

SECTION 4: Event System

```
events:
```

```

enabled: true                                # bool    – Enable event
    publishing
websocket: false                             # bool    – Enable
    WebSocket event stream
websocket_path: "/ws/verifier/events" # string – WebSocket
    endpoint path

# -----
# SECTION 5: Provider Configuration
# -----
providers:
  openai:
    enabled: true
    api_key: "${OPENAI_API_KEY}"
    base_url: "https://api.openai.com/v1"
    models:
      []                                     # empty = auto-discover all
    priority: 1

  anthropic:
    enabled: true
    api_key: "${ANTHROPIC_API_KEY}"
    base_url: "https://api.anthropic.com/v1"
    models: []
    priority: 2
    oauth_fallback: true

  gemini:
    enabled: true
    api_key: "${GEMINI_API_KEY}"
    base_url: "https://generativelanguage.googleapis.com/
      v1beta"
    models: []
    priority: 3

  deepseek:
    enabled: true
    api_key: "${DEEPSEEK_API_KEY}"
    base_url: "https://api.deepseek.com/v1"
    models: []
    priority: 4

  groq:
    enabled: true
    api_key: "${GROQ_API_KEY}"
    base_url: "https://api.groq.com/openai/v1"
    models: []
    priority: 5

```

```

mistral:
  enabled: true
  api_key: "${MISTRAL_API_KEY}"
  base_url: "https://api.mistral.ai/v1"
  models: []
  priority: 6

xai:
  enabled: false                                # Disabled by default
  api_key: "${XAI_API_KEY}"
  base_url: "https://api.x.ai/v1"
  models: []
  priority: 7

openrouter:
  enabled: true
  api_key: "${OPENROUTER_API_KEY}"
  base_url: "https://openrouter.ai/api/v1"
  models: []
  priority: 8
  free_models_only: false

ollama:
  enabled: true
  host: "http://localhost:11434"
  models: []
  priority: 100                                # Local providers
  lowest priority

llamacpp:
  enabled: true
  host: "http://localhost:8080"
  models: []
  priority: 101

```

Acceptance Criteria: 1. File exists at `helix_code/configs/verifier.yaml` 2. `go test -short ./internal/config/...` can load this file via Viper 3. All provider sections have `enabled`, `api_key` (or `host` for local), and `models` fields 4. Scoring weights sum to 1.0 in the file

Dependencies: TASK 1.2.1 **Effort:** Medium

TASK 1.4: Update `.env.example`

TASK 1.4.1: Add All Verifier and Provider Env Vars

File(s): `helix_code/.env.example` **Line(s):** After existing env vars, before any closing comments **Action:** MODIFY

```
# =====
# LLMsVerifier Configuration
# =====
HELIX_VERIFIER_ENABLED=false
HELIX_VERIFIER_ENDPOINT=http://localhost:8081
HELIX_VERIFIER_API_KEY=
HELIX_VERIFIER_TIMEOUT=30s
HELIX_VERIFIER_CACHE_TTL=5m
HELIX_VERIFIER_POLLING_INTERVAL=60s
HELIX_VERIFIER_MIN_SCORE=6.0
HELIX_MODELS_DEV_ENDPOINT=https://api.models.dev
```

```
# =====
# Provider API Keys (Cloud Providers)
# =====
```

```
HELIX_OPENAI_API_KEY=
HELIX_ANTHROPIC_API_KEY=
HELIX_GEMINI_API_KEY=
HELIX_DEEPSEEK_API_KEY=
HELIX_GROQ_API_KEY=
HELIX_TOGETHER_API_KEY=
HELIX_MISTRAL_API_KEY=
HELIX_XAI_API_KEY=
HELIX_CEREBRAS_API_KEY=
HELIX_CLOUDFLARE_API_KEY=
HELIX_CLOUDFLARE_ACCOUNT_ID=
HELIX_SILICONFLOW_API_KEY=
HELIX_REPLICATE_API_TOKEN=
HELIX_OPENROUTER_API_KEY=
HELIX_QWEN_API_KEY=
HELIX_COHERE_API_KEY=
```

```
# =====
# Local Provider Configuration
# =====
```

```
HELIX_OLLAMA_HOST=http://localhost:11434
HELIX_LLAMA_CPP_HOST=http://localhost:8080
```

Acceptance Criteria: 1. `grep -c "HELIX_" .env.example` returns ≥ 30 entries 2. All 16 provider API keys are documented 3. `grep "HELIX_VERIFIER_ENABLED" .env.example` returns exactly one line

Dependencies: TASK 1.2.3 **Effort:** Small

TASK 1.5: Create internal/verifier/types.go

TASK 1.5.1: Define All Shared Verifier Types

File(s): helix_code/internal/verifier/types.go **Line(s):** CREATE new file

Action: CREATE

```
// Package verifier provides the LLMsVerifier integration layer
// for HelixCode.
// It communicates with LLMsVerifier via REST API (not Go module
// import)
// to avoid the digital.vasic.llmprovider sibling-module
// dependency.
package verifier

import (
    "errors"
    "time"
)

// ErrVerifierDisabled is returned when the verifier is disabled
// in config.
var ErrVerifierDisabled = errors.New("verifier is disabled")

// ErrVerifierUnavailable is returned when the verifier service
// cannot be reached.
var ErrVerifierUnavailable = errors.New("verifier service is
    unavailable")

// ErrUsingStaleCache is returned when data comes from expired
// cache.
var ErrUsingStaleCache = errors.New("using stale cached verifier
    data")

// ErrUsingFallback is returned when data comes from hardcoded
// fallback list.
var ErrUsingFallback = errors.New("using fallback model list")

// VerifiedModel – unified model representation from
// LLMsVerifier.
type VerifiedModel struct {
    ID            string    `json:"id"`
    Name          string    `json:"name"`
    DisplayName   string    `json:"display_name"`
    Provider      string    `json:"provider"`
    ProviderType  string    `json:"provider_type"`
    Score         float64   `json:"score"`
    Verified      bool      `json:"verified"`
}
```



```

VerificationStatus      string
    `json:"verification_status"` // pending, verified,
    failed, rate_limited
ContextSize              int
    `json:"context_window_tokens"`
MaxOutputTokens          int    `json:"max_output_tokens"`
SupportsStreaming        bool    `json:"supports_streaming"`
SupportsTools            bool    `json:"supports_tool_use"`
SupportsFunctions        bool    `json:"supports_functions"`
SupportsCode             bool
    `json:"supports_code_generation"`
SupportsVision           bool    `json:"supports_vision"`
SupportsAudio            bool    `json:"supports_audio"`
SupportsVideo            bool    `json:"supports_video"`
SupportsReasoning        bool    `json:"supports_reasoning"`
SupportsEmbeddings       bool    `json:"supports_embeddings"`
SupportsJSONMode         bool    `json:"supports_json_mode"`
Latency                  time.Duration `json:"latency_ms"`
CostPerInputToken        float64 `json:"input_token_cost"`
CostPerOutputToken       float64 `json:"output_token_cost"`
OverallScore             float64 `json:"overall_score"`
CodeCapabilityScore      float64
    `json:"code_capability_score"`
ResponsivenessScore      float64 `json:"responsiveness_score"`
ReliabilityScore         float64 `json:"reliability_score"`
FeatureRichnessScore     float64
    `json:"feature_richness_score"`
ValuePropositionScore    float64
    `json:"value_proposition_score"`
LastVerified             time.Time `json:"last_verified"`
Source                   string    `json:"source"` //
    "verifier", "cache", "fallback"
OpenSource               bool    `json:"open_source"`
Deprecated               bool    `json:"deprecated"`
Tier                     int    `json:"tier"` // 1=Premium,
    2=High-quality, 3=Fast, 4=Aggregator, 5=Free
Capabilities             []string `json:"capabilities"`
Tags                     []string `json:"tags"`
}

```

// ProviderStatus – health and score of a provider.

```

type ProviderStatus struct {
    Name          string    `json:"name"`
    Type          string    `json:"type"`
    DisplayName    string    `json:"display_name"`
    Score         float64   `json:"score"`
    Verified      bool      `json:"verified"`
    Healthy       bool      `json:"healthy"`
}

```

```

    Status      string    `json:"status"` // unknown, healthy,
                                degraded, unhealthy, offline
    ModelCount  int        `json:"model_count"`
    Tier        int        `json:"tier"`
    Priority     int        `json:"priority"`
    LastChecked time.Time   `json:"last_checked"`
    UptimePct   float64    `json:"uptime_pct"`
    Latency     time.Duration `json:"latency"`
}

// VerificationResult – result of on-demand verification.
type VerificationResult struct {
    ModelID      string    `json:"model_id"`
    Status       string    `json:"status"` // started,
                                completed, failed
    OverallScore float64    `json:"overall_score"`
    CodeCapabilityScore float64    `json:"code_capability_score"`
    ResponsivenessScore float64    `json:"responsiveness_score"`
    ReliabilityScore float64    `json:"reliability_score"`
    FeatureRichnessScore float64    `json:"feature_richness_score"`
    ValuePropositionScore float64    `json:"value_proposition_score"`
    ModelExists   *bool     `json:"model_exists,omitempty"`
    Responsive    *bool     `json:"responsive,omitempty"`
    Overloaded    *bool     `json:"overloaded,omitempty"`
    SupportsToolUse bool      `json:"supports_tool_use"`
    SupportsCodeGeneration bool      `json:"supports_code_generation"`
    SupportsEmbeddings bool      `json:"supports_embeddings"`
    SupportsStreaming bool      `json:"supports_streaming"`
    SupportsJSONMode bool      `json:"supports_json_mode"`
    SupportsReasoning bool      `json:"supports_reasoning"`
    CodeDebugging bool      `json:"code_debugging"`
    CodeOptimization bool      `json:"code_optimization"`
    TestGeneration bool      `json:"test_generation"`
    DocumentationGeneration bool      `json:"documentation_generation"`
    ArchitectureDesign bool      `json:"architecture_design"`
    SecurityAssessment bool      `json:"security_assessment"`
    PatternRecognition bool      `json:"pattern_recognition"`
    Error         string    `json:"error,omitempty"`
    CompletedAt   time.Time `json:"completed_at"`
}

// HealthResponse – verifier service health.

```

```

type HealthResponse struct {
    Status      string    `json:"status"`
    Timestamp   time.Time `json:"timestamp"`
    Version     string    `json:"version"`
}

// RateLimitStatus – rate limit information for a model.
type RateLimitStatus struct {
    ModelID     string    `json:"model_id"`
    Limits      []LimitEntry `json:"limits"`
}

// LimitEntry – a single rate limit dimension.
type LimitEntry struct {
    Type        string    `json:"type"`
    Limit       int       `json:"limit"`
    Used        int       `json:"used"`
    Remaining   int       `json:"remaining"`
    ResetTime   time.Time `json:"reset_time"`
}

// CooldownInfo – cooldown state for a model or provider.
type CooldownInfo struct {
    ModelID     string    `json:"model_id"`
    Provider     string    `json:"provider"`
    Reason       string    `json:"reason"` // rate-limited,
                quota-exceeded, cooldown
    ResetTime   time.Time `json:"reset_time"`
    Duration    time.Duration `json:"duration"`
}

// ChangeEvent – emitted when verifier data changes.
type ChangeEvent struct {
    Type        string    `json:"type"` // model.discovered,
                model.score_changed, model.status_changed, model.removed
    Model       *VerifiedModel `json:"model,omitempty"`
    Provider    *ProviderStatus `json:"provider,omitempty"`
    OldScore    float64      `json:"old_score,omitempty"`
    OldStatus   string       `json:"old_status,omitempty"`
    Timestamp   time.Time    `json:"timestamp"`
}

// FallbackModels is the hardcoded fallback list used when
// verifier is unavailable.
// This is the ONLY permitted hardcoded model list (CONST-035
// compliance).
var FallbackModels = []*VerifiedModel{

```

```

{ID: "llama-3.2-3b", Name: "Llama 3.2 3B", DisplayName:
  "Llama 3.2 3B", Provider: "ollama", ContextSize: 131072,
  Source: "fallback", OverallScore: 6.0, Tier: 3,
  OpenSource: true},
{ID: "gpt-4o", Name: "GPT-4o", DisplayName: "GPT-4o",
  Provider: "openai", ContextSize: 128000, Source:
  "fallback", OverallScore: 9.1, Tier: 1},
{ID: "claude-3-5-sonnet", Name: "Claude 3.5 Sonnet",
  DisplayName: "Claude 3.5 Sonnet", Provider: "anthropic",
  ContextSize: 200000, Source: "fallback", OverallScore:
  8.9, Tier: 1},
{ID: "mistral-large", Name: "Mistral Large", DisplayName:
  "Mistral Large", Provider: "mistral", ContextSize:
  128000, Source: "fallback", OverallScore: 7.8, Tier: 2},
{ID: "gemini-2.5-pro", Name: "Gemini 2.5 Pro", DisplayName:
  "Gemini 2.5 Pro", Provider: "gemini", ContextSize:
  1000000, Source: "fallback", OverallScore: 8.7, Tier: 1},
{ID: "deepseek-chat", Name: "DeepSeek Chat", DisplayName:
  "DeepSeek Chat", Provider: "deepseek", ContextSize:
  64000, Source: "fallback", OverallScore: 8.3, Tier: 2,
  OpenSource: true},
{ID: "grok-3-fast-beta", Name: "Grok-3 Fast Beta",
  DisplayName: "Grok-3 Fast Beta", Provider: "xai",
  ContextSize: 131072, Source: "fallback", OverallScore:
  8.0, Tier: 1},
}

```

Acceptance Criteria: 1. go build ./internal/verifier/... compiles 2. FallbackModels has exactly 7 entries 3. All struct fields have json:"..." tags for every field 4. ErrVerifierDisabled, ErrVerifierUnavailable, ErrUsingStaleCache, ErrUsingFallback are defined

Dependencies: None **Effort:** Medium

TASK 1.6: Create internal/verifier/client.go

TASK 1.6.1: Implement REST API Client

File(s): helix_code/internal/verifier/client.go **Line(s):** CREATE new file
Action: CREATE

```

package verifier

import (
    "context"
    "encoding/json"
    "fmt"
    "net/http"
    "time"

```

```

)

// Client is the HTTP REST API client for LLMsVerifier.
// It mirrors HelixAgent's pkg/sdk/go/verifier/client.go pattern.
// Uses stdlib net/http – no external dependency needed.
type Client struct {
    baseURL    string
    apiKey     string
    httpClient *http.Client
    timeout    time.Duration
}

// NewClient creates a verifier API client.
// baseURL: verifier service URL (e.g., "http://localhost:8081")
// apiKey: optional bearer token for authenticated endpoints
// timeout: HTTP client timeout (0 = default 30s)
func NewClient(baseURL, apiKey string, timeout time.Duration)
    *Client {
    if baseURL == "" {
        baseURL = "http://localhost:8081"
    }
    if timeout == 0 {
        timeout = 30 * time.Second
    }
    return &Client{
        baseURL:    baseURL,
        apiKey:     apiKey,
        timeout:    timeout,
        httpClient: &http.Client{Timeout: timeout},
    }
}

// WithHTTPClient allows injecting a custom HTTP client (for
// testing).
func (c *Client) WithHTTPClient(hc *http.Client) *Client {
    c.httpClient = hc
    return c
}

// Health checks the verifier service health endpoint.
func (c *Client) Health(ctx context.Context) (*HealthResponse,
    error) {
    req, err := http.NewRequestWithContext(ctx, http.MethodGet,
        c.baseURL+"/api/health", nil)
    if err != nil {
        return nil, fmt.Errorf("verifier health: create request:
            %w", err)
    }
}

```

```

c.setAuthHeader(req)

resp, err := c.httpClient.Do(req)
if err != nil {
    return nil, fmt.Errorf("verifier health check failed: %w", err)
}
defer resp.Body.Close()

if resp.StatusCode != http.StatusOK {
    return nil, fmt.Errorf("verifier health: HTTP %d", resp.StatusCode)
}

var hr HealthResponse
if err := json.NewDecoder(resp.Body).Decode(&hr); err != nil {
    return nil, fmt.Errorf("verifier health: decode: %w", err)
}
return &hr, nil
}

// GetModels fetches all verified models from the verifier.
func (c *Client) GetModels(ctx context.Context) ([]*VerifiedModel, error) {
    req, err := http.NewRequestWithContext(ctx, http.MethodGet, c.baseURL+"/api/models", nil)
    if err != nil {
        return nil, err
    }
    c.setAuthHeader(req)

    resp, err := c.httpClient.Do(req)
    if err != nil {
        return nil, fmt.Errorf("failed to fetch models from verifier: %w", err)
    }
    defer resp.Body.Close()

    if resp.StatusCode != http.StatusOK {
        return nil, fmt.Errorf("verifier models: HTTP %d", resp.StatusCode)
    }

    var models []*VerifiedModel
    if err := json.NewDecoder(resp.Body).Decode(&models); err != nil {

```

```

        return nil, fmt.Errorf("failed to decode models: %w",
            err)
    }
    return models, nil
}

// GetModelByID fetches a single model by ID.
func (c *Client) GetModelByID(ctx context.Context, modelID
    string) (*VerifiedModel, error) {
    url := fmt.Sprintf("%s/api/models/%s", c.baseURL, modelID)
    req, err := http.NewRequestWithContext(ctx, http.MethodGet,
        url, nil)
    if err != nil {
        return nil, err
    }
    c.setAuthHeader(req)

    resp, err := c.httpClient.Do(req)
    if err != nil {
        return nil, fmt.Errorf("failed to fetch model %s: %w",
            modelID, err)
    }
    defer resp.Body.Close()

    if resp.StatusCode == http.StatusNotFound {
        return nil, fmt.Errorf("model %s not found", modelID)
    }
    if resp.StatusCode != http.StatusOK {
        return nil, fmt.Errorf("verifier model get: HTTP %d",
            resp.StatusCode)
    }

    var model VerifiedModel
    if err := json.NewDecoder(resp.Body).Decode(&model); err !=
        nil {
        return nil, fmt.Errorf("failed to decode model: %w", err)
    }
    return &model, nil
}

// GetProviderScores fetches all provider scores.
func (c *Client) GetProviderScores(ctx context.Context)
    (map[string]float64, error) {
    req, err := http.NewRequestWithContext(ctx, http.MethodGet,
        c.baseURL+"/api/scores", nil)
    if err != nil {
        return nil, err
    }

```

```

c.setAuthHeader(req)

resp, err := c.httpClient.Do(req)
if err != nil {
    return nil, fmt.Errorf("failed to fetch scores: %w", err)
}
defer resp.Body.Close()

if resp.StatusCode != http.StatusOK {
    return nil, fmt.Errorf("verifier scores: HTTP %d",
        resp.StatusCode)
}

var scores map[string]float64
if err := json.NewDecoder(resp.Body).Decode(&scores); err !=
    nil {
    return nil, fmt.Errorf("failed to decode scores: %w",
        err)
}
return scores, nil
}

// VerifyModel triggers on-demand verification for a model.
func (c *Client) VerifyModel(ctx context.Context, modelID
    string) (*VerificationResult, error) {
    url := fmt.Sprintf("%s/api/models/%s/verify", c.baseURL,
        modelID)
    req, err := http.NewRequestWithContext(ctx, http.MethodPost,
        url, nil)
    if err != nil {
        return nil, err
    }
    c.setAuthHeader(req)

    resp, err := c.httpClient.Do(req)
    if err != nil {
        return nil, fmt.Errorf("failed to verify model %s: %w",
            modelID, err)
    }
    defer resp.Body.Close()

    if resp.StatusCode != http.StatusOK && resp.StatusCode !=
        http.StatusAccepted {
        return nil, fmt.Errorf("verifier verify: HTTP %d",
            resp.StatusCode)
    }

    var result VerificationResult

```



```

    if err := json.NewDecoder(resp.Body).Decode(&result); err !=
        nil {
            return nil, fmt.Errorf("failed to decode verification
                result: %w", err)
        }
    return &result, nil
}

// GetPricing fetches token pricing data.
func (c *Client) GetPricing(ctx context.Context)
    ([]map[string]interface{}, error) {
    req, err := http.NewRequestWithContext(ctx, http.MethodGet,
        c.baseURL+"/api/pricing", nil)
    if err != nil {
        return nil, err
    }
    c.setAuthHeader(req)

    resp, err := c.httpClient.Do(req)
    if err != nil {
        return nil, fmt.Errorf("failed to fetch pricing: %w",
            err)
    }
    defer resp.Body.Close()

    if resp.StatusCode != http.StatusOK {
        return nil, fmt.Errorf("verifier pricing: HTTP %d",
            resp.StatusCode)
    }

    var pricing []map[string]interface{}
    if err := json.NewDecoder(resp.Body).Decode(&pricing); err !=
        nil {
        return nil, fmt.Errorf("failed to decode pricing: %w",
            err)
    }
    return pricing, nil
}

// GetLimits fetches rate limit data.
func (c *Client) GetLimits(ctx context.Context)
    ([]map[string]interface{}, error) {
    req, err := http.NewRequestWithContext(ctx, http.MethodGet,
        c.baseURL+"/api/limits", nil)
    if err != nil {
        return nil, err
    }
    c.setAuthHeader(req)

```

```

resp, err := c.httpClient.Do(req)
if err != nil {
    return nil, fmt.Errorf("failed to fetch limits: %w", err)
}
defer resp.Body.Close()

if resp.StatusCode != http.StatusOK {
    return nil, fmt.Errorf("verifier limits: HTTP %d",
        resp.StatusCode)
}

var limits []map[string]interface{}
if err := json.NewDecoder(resp.Body).Decode(&limits); err !=
    nil {
    return nil, fmt.Errorf("failed to decode limits: %w",
        err)
}
return limits, nil
}

// setAuthHeader adds the Authorization header if API key is
// configured.
func (c *Client) setAuthHeader(req *http.Request) {
    if c.apiKey != "" {
        req.Header.Set("Authorization", "Bearer "+c.apiKey)
    }
    req.Header.Set("Accept", "application/json")
    req.Header.Set("User-Agent", "HelixCode-VerifierClient/1.0")
}

```

Acceptance Criteria: 1. `go build ./internal/verifier/...` compiles with zero errors 2. `NewClient("", "", 0)` produces `baseUrl="http://localhost:8081"`, `timeout=30s` 3. `setAuthHeader` sets "Bearer" prefix and never logs the key 4. All methods accept `context.Context` for cancellation 5. Response body is always closed via `defer`

Dependencies: TASK 1.5.1 **Effort:** Large

TASK 1.7: Create `internal/verifier/config.go`

TASK 1.7.1: Create Verifier-Specific Config Types and Loader

File(s): `helix_code/internal/verifier/config.go` **Line(s):** CREATE new file
Action: CREATE

```

package verifier

import (
    "dev.helix.code/internal/config"

```

```

    "fmt"
    "time"
)

// AdapterConfig wraps the application-level VerifierConfig for
// use within
// the verifier package. This separates the Viper/mapstructure
// concerns from
// the runtime verifier concerns.
type AdapterConfig struct {
    Enabled          bool
    Endpoint         string
    APIKey           string
    Timeout          time.Duration
    CacheTTL         time.Duration
    PollingInterval time.Duration
    Scoring          ScoringAdapterConfig
    Health           HealthAdapterConfig
    Events           EventsAdapterConfig
    Providers        map[string]ProviderAdapterConfig
}

// ScoringAdapterConfig – runtime scoring configuration.
type ScoringAdapterConfig struct {
    Weights          config.ScoringWeights
    ModelsDevEnabled bool
    ModelsDevEndpoint string
    MinAcceptableScore float64
}

// HealthAdapterConfig – runtime health configuration.
type HealthAdapterConfig struct {
    CheckInterval    time.Duration
    Timeout          time.Duration
    FailureThreshold int
    RecoveryThreshold int
    CircuitBreaker   config.CircuitBreakerConfig
}

// EventsAdapterConfig – runtime events configuration.
type EventsAdapterConfig struct {
    Enabled          bool
    WebSocket        bool
    WebSocketPath    string
}

// ProviderAdapterConfig – runtime per-provider configuration.
type ProviderAdapterConfig struct {

```

```

    Enabled    bool
    APIKey     string
    BaseURL    string
    Models     []string
    Priority    int
}

// NewAdapterConfig translates the Viper-loaded Config into
// verifier-native config.
func NewAdapterConfig(cfg *config.VerifierConfig) *AdapterConfig
{
    if cfg == nil {
        return &AdapterConfig{Enabled: false}
    }
    ac := &AdapterConfig{
        Enabled:          cfg.Enabled,
        Endpoint:          cfg.Endpoint,
        APIKey:            cfg.APIKey,
        Timeout:           cfg.Timeout,
        CacheTTL:          cfg.CacheTTL,
        PollingInterval:  cfg.PollingInterval,
        Scoring: ScoringAdapterConfig{
            Weights:          cfg.Scoring.Weights,
            ModelsDevEnabled:  cfg.Scoring.ModelsDevEnabled,
            ModelsDevEndpoint: cfg.Scoring.ModelsDevEndpoint,
            MinAcceptableScore: cfg.Scoring.MinAcceptableScore,
        },
        Health: HealthAdapterConfig{
            CheckInterval:  cfg.Health.CheckInterval,
            Timeout:         cfg.Health.Timeout,
            FailureThreshold: cfg.Health.FailureThreshold,
            RecoveryThreshold: cfg.Health.RecoveryThreshold,
            CircuitBreaker:  cfg.Health.CircuitBreaker,
        },
        Events: EventsAdapterConfig{
            Enabled:          cfg.Events.Enabled,
            WebSocket:         cfg.Events.WebSocket,
            WebSocketPath:     cfg.Events.WebSocketPath,
        },
        Providers: make(map[string]ProviderAdapterConfig),
    }
    for name, pc := range cfg.Providers {
        ac.Providers[name] = ProviderAdapterConfig{
            Enabled:  pc.Enabled,
            APIKey:   pc.APIKey,
            BaseURL:  pc.BaseURL,
            Models:  pc.Models,
            Priority: pc.Priority,
        }
    }
}

```

```

    }
}
return ac
}

// Validate checks the adapter configuration for runtime
correctness.
func (ac *AdapterConfig) Validate() error {
    if !ac.Enabled {
        return nil
    }
    if ac.Endpoint == "" {
        return fmt.Errorf("verifier endpoint is required when
enabled")
    }
    if ac.Timeout < 1*time.Second {
        return fmt.Errorf("verifier timeout must be >= 1s")
    }
    if ac.PollingInterval < 10*time.Second {
        return fmt.Errorf("verifier polling_interval must be >=
10s")
    }
    total := ac.Scoring.Weights.CodeCapability +
        ac.Scoring.Weights.Responsiveness +
        ac.Scoring.Weights.Reliability +
        ac.Scoring.Weights.FeatureRichness +
        ac.Scoring.Weights.ValueProposition
    if total < 0.999 || total > 1.001 {
        return fmt.Errorf("scoring weights must sum to 1.0, got
%.3f", total)
    }
    return nil
}

```

Acceptance Criteria: 1. go build ./internal/verifier/... compiles 2. NewAdapterConfig(nil) returns Enabled: false 3. Validate() returns error when weights don't sum to 1.0 4. All nested configs are correctly translated from config.VerifierConfig

Dependencies: TASK 1.2.1, TASK 1.5.1 **Effort:** Medium

TASK 1.8: Create internal/verifier/doc.go

TASK 1.8.1: Package Documentation

File(s): helix_code/internal/verifier/doc.go **Line(s):** CREATE new file **Action:** CREATE

```

// Package verifier integrates LLMsVerifier as the single source
//   of truth
// for model metadata, provider health, verification status, and
//   scoring
// within HelixCode.
//
// Architecture:
//
//   HelixCode (cmd/cli, cmd/server, internal/llm)
//       |
//       | REST API calls (HTTP/json)
//       v
//   internal/verifier/Client -> LLMsVerifier service
//       (localhost:8081)
//       |
//       | SQLite DB read
//       v
//   LLMsVerifier (submodule) -> Provider APIs
//
// Key types:
//   - Client: HTTP REST client for verifier API
//   - Adapter: Bridges verifier scores to HelixCode's
//       ModelManager
//   - Cache: Two-tier cache (in-memory LRU + Redis)
//   - HealthMonitor: Circuit breaker for verifier availability
//   - Poller: Background goroutine for real-time updates
//   - EventPublisher: Publishes changes to HelixCode event bus
//
// The verifier is disabled by default (verifier.enabled=false).
//   When disabled,
// all model operations fall back to legacy behavior.
//
// Constitutional compliance:
//   - CONST-036: LLMsVerifier single source of truth
//   - CONST-037: Anti-bluff guarantee (no hardcoded models)
//   - CONST-038: Real-time status accuracy
//   - CONST-039: All providers integration
//   - CONST-040: MCP/LSP/ACP/Embedding/RAG/Skills/Plugins
package verifier

```

Acceptance Criteria: 1. `go doc ./internal/verifier` shows the package documentation 2. Documentation mentions all 6 key types 3. Constitutional rules CONST-036 through CONST-040 are referenced

Dependencies: None **Effort:** Small

TASK 1.9: Add Enable/Disable Truth Table

TASK 1.9.1: Document and Implement Verifier Enable/Disable Behavior

File(s): `helix_code/internal/verifier/adapter.go` (will be created in Phase 2, but the truth table is defined here) **Line(s):** N/A — truth table is enforced by nil-check in initialization **Action:** DOCUMENT

The enable/disable behavior is implemented via nil-check in `initializeVerifier()`:

<code>verifier.enabled</code>	<code>verifier.endpoint reachable</code>	System Behavior
false (default)	N/A	Verifier client is nil. All model operations use legacy local/heuristic logic. <code>handleListModel()</code> falls through to <code>modelManager.GetAvailableModels()</code> . No polling goroutine. No REST calls.
true	true	Verifier client initialized. Polling goroutine started. Model lists fetched from verifier first. Scores incorporated into <code>SelectOptimalModel()</code> . Events published on changes.
true	false	Verifier client initialized but health monitor marks circuit OPEN after <code>failure_threshold</code> failures. System falls back to stale cache, then to <code>FallbackModels</code> . Events published for degraded state.

Implementation location: `cmd/server/main.go` and `cmd/cli/main.go` — check `cfg.Verifier != nil && cfg.Verifier.Enabled` before initializing verifier subsystem.

Acceptance Criteria: 1. With `verifier.enabled=false`, `grep -r "llmsverifier\|verifier" cmd/cli/main.go` shows only the nil check 2. With `verifier.enabled=true`, the CLI shows verifier-specific columns in `--list-models`

Dependencies: TASK 1.6.1 **Effort:** Small

PHASE 1 ROLLBACK PLAN

If Phase 1 must be rolled back:

```
cd HelixCode
git checkout -- internal/config/config.go
git checkout -- .env.example
git rm --cached internal/verifier/types.go internal/verifier/
      client.go internal/verifier/config.go internal/verifier/
      doc.go
rm -f internal/verifier/types.go internal/verifier/client.go
      internal/verifier/config.go internal/verifier/doc.go
```

```
git rm --cached configs/verifier.yaml
rm -f configs/verifier.yaml
go mod tidy
make build
make test-unit
```

PHASE 1 VERIFICATION CHECKLIST

- ☐ go build ./... compiles with zero errors
 - ☐ make test-unit passes
 - ☐ go test -short ./internal/config/... passes with verifier defaults
 - ☐ grep -c "VerifierConfig" internal/config/config.go >= 1
 - ☐ grep -c "mapstructure:\"verifier\"" internal/config/config.go >= 1
 - ☐ grep -c "BindEnv.*HELIX_VERIFIER" internal/config/config.go >= 7
 - ☐ grep -c "BindEnv.*HELIX_.*API_KEY" internal/config/config.go >= 16
 - ☐ configs/verifier.yaml exists and is valid YAML
 - ☐ .env.example contains all HELIX_VERIFIER_* and provider keys
 - ☐ internal/verifier/types.go defines VerifiedModel, ProviderStatus, VerificationResult
 - ☐ internal/verifier/client.go implements GetModels, GetModelByID, GetProviderScores, VerifyModel
 - ☐ FallbackModels has exactly 7 entries
 - ☐ ErrVerifierDisabled and ErrVerifierUnavailable are defined
 - ☐ NewAdapterConfig(nil) returns Enabled: false
-

PHASE 2: MODEL MANAGEMENT — LLMsVerifier as Single Source of Truth

Phase Goal: Replace ALL hardcoded model sources with LLMsVerifier data. The verifier adapter becomes the bridge between LLMsVerifier and HelixCode's internal/llm/ package.

Phase Entry Criteria: Phase 1 verification checklist is complete. **Phase Exit Criteria:** 1. handleListModels() returns models from verifier, not hardcoded list 2. fetchExternalModels() returns verifier data, not hardcoded array 3. SelectOptimalModel() uses verifier scores for ranking 4. NewProvider() validates against verifier health/score thresholds 5. Background polling updates model data every N seconds

TASK 2.1: Create internal/verifier/adapter.go

TASK 2.1.1: Implement ScoreAdapter Bridge

File(s): helix_code/internal/verifier/adapter.go **Line(s):** CREATE new file
Action: CREATE

```
package verifier

import (
    "context"
    "dev.helix.code/internal/config"
    "fmt"
    "sync"
    "time"
)

// Adapter bridges LLMsVerifier scores to HelixCode's llm
// package.
// Replicates HelixAgent's internal/services/
// llmsverifier_score_adapter.go.
type Adapter struct {
    client      *Client
    cache       *Cache
    health      *HealthMonitor
    config      *AdapterConfig
    events      *EventPublisher

    providerScores map[string]float64
    modelScores    map[string]float64
    modelCodeScores map[string]float64
    modelRelScores map[string]float64
    mu             sync.RWMutex

    lastRefresh      time.Time
    refreshInterval time.Duration
}

// NewAdapter creates the verifier adapter.
func NewAdapter(client *Client, cache *Cache, health
    *HealthMonitor, cfg *config.VerifierConfig) *Adapter {
    ac := NewAdapterConfig(cfg)
```

```

    return &Adapter{
        client:      client,
        cache:        cache,
        health:       health,
        config:       ac,
        providerScores: make(map[string]float64),
        modelScores:   make(map[string]float64),
        modelCodeScores: make(map[string]float64),
        modelRelScores: make(map[string]float64),
        refreshInterval: ac.CacheTTL,
    }
}

// IsEnabled returns true if the verifier subsystem is enabled in
// config.
func (a *Adapter) IsEnabled() bool {
    return a.config != nil && a.config.Enabled
}

// IsReachable returns true if the verifier service is reachable
// (circuit not open).
func (a *Adapter) IsReachable() bool {
    return a.health.AllowRequest()
}

// GetModelScore returns the overall verifier score (0-10) for a
// model.
// Mirrors HelixAgent's
// llmsverifier_score_adapter.go:GetModelScore().
func (a *Adapter) GetModelScore(modelID string) (float64, bool) {
    a.mu.RLock()
    defer a.mu.RUnlock()

    score, ok := a.modelScores[modelID]
    if ok {
        if score > 10 {
            score = score / 10.0
        }
        return score, true
    }
    // Try cache
    if a.cache != nil {
        if cached, found := a.cache.GetModelScore(modelID);
        found {
            return cached, true
        }
    }
    return 0, false
}

```

```

}

// GetProviderScore returns the best score for any model of this
// provider.
// Mirrors HelixAgent's GetProviderScore().
func (a *Adapter) GetProviderScore(providerType string)
    (float64, bool) {
    a.mu.RLock()
    defer a.mu.RUnlock()

    score, ok := a.providerScores[providerType]
    if ok {
        if score > 10 {
            score = score / 10.0
        }
        return score, true
    }
    return 0, false
}

// GetModelCodeCapabilityScore returns the code capability score
// for a model.
func (a *Adapter) GetModelCodeCapabilityScore(modelID string)
    (float64, bool) {
    a.mu.RLock()
    defer a.mu.RUnlock()
    score, ok := a.modelCodeScores[modelID]
    return score, ok
}

// GetModelReliabilityScore returns the reliability score for a
// model.
func (a *Adapter) GetModelReliabilityScore(modelID string)
    (float64, bool) {
    a.mu.RLock()
    defer a.mu.RUnlock()
    score, ok := a.modelRelScores[modelID]
    return score, ok
}

// GetMinAcceptableScore returns the configured minimum score
// threshold.
func (a *Adapter) GetMinAcceptableScore() float64 {
    if a.config == nil {
        return 6.0
    }
    return a.config.Scoring.MinAcceptableScore
}

```

```

// GetVerifiedModels returns all models from verifier, filtered
// by provider config.
func (a *Adapter) GetVerifiedModels(ctx context.Context)
    ([]*VerifiedModel, error) {
    if !a.IsEnabled() {
        return nil, ErrVerifierDisabled
    }
    if !a.health.AllowRequest() {
        return a.getFallbackModels()
    }

    // Try cache first
    if a.cache != nil {
        if models, ok := a.cache.GetModels("all"); ok {
            return a.filterByProviderConfig(models), nil
        }
    }

    // Fetch from verifier
    models, err := a.client.GetModels(ctx)
    if err != nil {
        a.health.RecordFailure()
        // Try stale cache (up to 2x TTL)
        if a.cache != nil {
            if stale, ok := a.cache.GetModelsStale("all"); ok {
                return stale, ErrUsingStaleCache
            }
        }
        return a.getFallbackModels()
    }

    a.health.RecordSuccess()
    a.refreshScores(models)

    // Update cache
    if a.cache != nil {
        a.cache.SetModels("all", models)
    }

    return a.filterByProviderConfig(models), nil
}

// GetProviderStatus returns the health and score status for a
// provider.
func (a *Adapter) GetProviderStatus(providerType string)
    (*ProviderStatus, bool) {
    a.mu.RLock()

```

```

defer a.mu.RUnlock()

score, hasScore := a.providerScores[providerType]
healthy := a.health.AllowRequest() && hasScore

status := &ProviderStatus{
    Type:      providerType,
    Score:     score,
    Healthy:   healthy,
    LastChecked: a.lastRefresh,
}
if hasScore {
    return status, true
}
return status, false
}

// ForceRefresh invalidates cache and re-fetches from verifier.
func (a *Adapter) ForceRefresh(ctx context.Context) error {
    if a.cache != nil {
        a.cache.Invalidate("all")
    }
    _, err := a.GetVerifiedModels(ctx)
    return err
}

// refreshScores updates internal score maps from model list.
func (a *Adapter) refreshScores(models []*VerifiedModel) {
    a.mu.Lock()
    defer a.mu.Unlock()

    providerBest := make(map[string]float64)

    for _, m := range models {
        a.modelScores[m.ID] = m.OverallScore
        a.modelCodeScores[m.ID] = m.CodeCapabilityScore
        a.modelRelScores[m.ID] = m.ReliabilityScore

        if current, ok := providerBest[m.Provider]; !ok ||
            m.OverallScore > current {
            providerBest[m.Provider] = m.OverallScore
        }
    }

    a.providerScores = providerBest
    a.lastRefresh = time.Now()
}

// filterByProviderConfig removes models from disabled providers.

```

```

func (a *Adapter) filterByProviderConfig(models
    []*VerifiedModel) []*VerifiedModel {
    if len(a.config.Providers) == 0 {
        return models
    }
    filtered := make([]*VerifiedModel, 0, len(models))
    for _, m := range models {
        if pc, ok := a.config.Providers[m.Provider]; ok && !
            pc.Enabled {
            continue
        }
        filtered = append(filtered, m)
    }
    return filtered
}

// getFallbackModels returns the hardcoded fallback list.
func (a *Adapter) getFallbackModels() ([]*VerifiedModel, error) {
    result := make([]*VerifiedModel, len(FallbackModels))
    for i, m := range FallbackModels {
        copy := *m
        copy.Source = "fallback"
        result[i] = &copy
    }
    return result, ErrUsingFallback
}

```

Acceptance Criteria: 1. go build ./internal/verifier/... compiles 2. NewAdapter(nil, nil, nil, &config.VerifierConfig{Enabled: false}).IsEnabled() returns false 3. GetModelScore("gpt-4o") returns score and true after refreshScores() 4. filterByProviderConfig() removes models from providers with Enabled: false 5. getFallbackModels() returns 7 models with Source: "fallback"

Dependencies: TASK 1.5.1, TASK 1.6.1, TASK 1.7.1 **Effort:** Large

TASK 2.2: Create internal/verifier/discovery.go

TASK 2.2.1: Implement ModelDiscoveryService

File(s): helix_code/internal/verifier/discovery.go **Line(s):** CREATE new file
Action: CREATE

```
package verifier
```

```
import (
    "context"
    "fmt"
    "sort"

```

```

    "strings"
    "sync"
    "time"
)

// ModelDiscoveryService discovers and filters models from
// LLMsVerifier.
// Replicates HelixAgent's internal/verifier/discovery.go
// pattern.
type ModelDiscoveryService struct {
    adapter      *Adapter
    config        *DiscoveryConfig
    discovered    map[string]*VerifiedModel
    mu            sync.RWMutex
    lastDiscover time.Time
}

// DiscoveryConfig controls discovery behavior.
type DiscoveryConfig struct {
    Enabled                bool          `yaml:"enabled"`
    DiscoveryInterval       time.Duration `yaml:"discovery_interval"`
    MaxModelsForEnsemble    int           `yaml:"max_models_for_ensemble"`
    MinScore                float64       `yaml:"min_score"`
    RequireVerification     bool          `yaml:"require_verification"`
    RequireCodeVisibility   bool          `yaml:"require_code_visibility"`
    RequiredDiversity       bool          `yaml:"require_diversity"`
    ProviderPriority         []string      `yaml:"provider_priority"`
}

// NewModelDiscoveryService creates a discovery service.
func NewModelDiscoveryService(adapter *Adapter, cfg
    *DiscoveryConfig) *ModelDiscoveryService {
    return &ModelDiscoveryService{
        adapter:    adapter,
        config:     cfg,
        discovered: make(map[string]*VerifiedModel),
    }
}

// DiscoverModels fetches and filters models from verifier.
func (s *ModelDiscoveryService) DiscoverModels(ctx
    context.Context) ([]*VerifiedModel, error) {

```

```

    if s.adapter == nil || !s.adapter.IsEnabled() {
        return nil, ErrVerifierDisabled
    }

    models, err := s.adapter.GetVerifiedModels(ctx)
    if err != nil {
        return nil, err
    }

    filtered := s.applyFilters(models)
    sorted := s.applySorting(filtered)

    s.mu.Lock()
    s.discovered = make(map[string]*VerifiedModel, len(sorted))
    for _, m := range sorted {
        s.discovered[m.ID] = m
    }
    s.lastDiscover = time.Now()
    s.mu.Unlock()

    return sorted, nil
}

// GetDiscoveredModel returns a single model by ID.
func (s *ModelDiscoveryService) GetDiscoveredModel(modelID
    string) (*VerifiedModel, bool) {
    s.mu.RLock()
    defer s.mu.RUnlock()
    m, ok := s.discovered[modelID]
    return m, ok
}

// SelectOptimalModel selects the best model for a task using
// verifier scores.
func (s *ModelDiscoveryService) SelectOptimalModel(
    ctx context.Context,
    taskType string,
    requiredCapabilities []string,
    maxPrice float64,
    minScore float64,
) (*VerifiedModel, error) {
    models, err := s.DiscoverModels(ctx)
    if err != nil {
        return nil, err
    }

    candidates := make([]*VerifiedModel, 0, len(models))
    for _, m := range models {

```



```

        if minScore > 0 && m.OverallScore < minScore {
            continue
        }
        if maxPrice > 0 &&
            (m.CostPerInputToken+m.CostPerOutputToken)/2.0*1000 >
            maxPrice {
            continue
        }
        if s.config.RequireVerification && !m.Verified {
            continue
        }
        if !hasAllCapabilities(m, requiredCapabilities) {
            continue
        }
        candidates = append(candidates, m)
    }

    if len(candidates) == 0 {
        return nil, fmt.Errorf("no model matches criteria:
            task=%s, minScore=%.1f, maxPrice=%.2f",
            taskType, minScore, maxPrice)
    }

    // Sort by score descending, then by latency ascending
    sort.Slice(candidates, func(i, j int) bool {
        if candidates[i].OverallScore !=
            candidates[j].OverallScore {
            return candidates[i].OverallScore >
            candidates[j].OverallScore
        }
        return candidates[i].Latency < candidates[j].Latency
    })

    return candidates[0], nil
}

// applyFilters removes models that don't meet discovery config
// criteria.
func (s *ModelDiscoveryService) applyFilters(models
    []*VerifiedModel) []*VerifiedModel {
    if s.config == nil {
        return models
    }
    result := make([]*VerifiedModel, 0, len(models))
    for _, m := range models {
        if s.config.MinScore > 0 && m.OverallScore <
            s.config.MinScore {
            continue
        }
    }
}

```

```

    }
    if s.config.RequireVerification && !m.Verified {
        continue
    }
    result = append(result, m)
}
return result
}

// applySorting sorts models by provider priority, then score,
// then latency.
func (s *ModelDiscoveryService) applySorting(models
    []*VerifiedModel) []*VerifiedModel {
    if s.config == nil || len(s.config.ProviderPriority) == 0 {
        // Default: sort by score desc, tier asc, latency asc
        sort.Slice(models, func(i, j int) bool {
            if models[i].OverallScore != models[j].OverallScore {
                return models[i].OverallScore >
                    models[j].OverallScore
            }
            if models[i].Tier != models[j].Tier {
                return models[i].Tier < models[j].Tier
            }
            return models[i].Latency < models[j].Latency
        })
        return models
    }

    priorityMap := make(map[string]int)
    for i, p := range s.config.ProviderPriority {
        priorityMap[p] = i
    }

    sort.Slice(models, func(i, j int) bool {
        pi, oki := priorityMap[models[i].Provider]
        pj, okj := priorityMap[models[j].Provider]
        if oki && okj {
            return pi < pj
        }
        if oki {
            return true
        }
        if okj {
            return false
        }
        return models[i].OverallScore > models[j].OverallScore
    })
    return models
}

```

```

}

// hasAllCapabilities checks if a model has all required
// capabilities.
func hasAllCapabilities(m *VerifiedModel, required []string)
    bool {
    if len(required) == 0 {
        return true
    }
    capSet := make(map[string]bool)
    for _, c := range m.Capabilities {
        capSet[strings.ToLower(c)] = true
    }
    for _, req := range required {
        if !capSet[strings.ToLower(req)] {
            return false
        }
    }
    return true
}

```

Acceptance Criteria: 1. go build ./internal/verifier/... compiles 2. DiscoverModels() returns error when adapter is nil 3. SelectOptimalModel() filters by minScore, maxPrice, and capabilities 4. applySorting() sorts by score descending by default 5. hasAllCapabilities() returns false when required cap is missing

Dependencies: TASK 2.1.1 **Effort:** Large

TASK 2.3: Create internal/verifier/poller.go

TASK 2.3.1: Implement Background Polling for Real-Time Updates

File(s): helix_code/internal/verifier/poller.go **Line(s):** CREATE new file
Action: CREATE

```

package verifier

import (
    "context"
    "sync"
    "time"
)

// Poller runs a background goroutine that polls LLMsVerifier at
// a configurable interval.
// Since LLMsVerifier has no push/webhook support, polling is the
// only real-time mechanism.
type Poller struct {
    adapter      *Adapter

```

```

    interval      time.Duration
    ticker        *time.Ticker
    stopCh        chan struct{}
    wg            sync.WaitGroup
    lastModels    map[string]*VerifiedModel
    lastScores    map[string]float64
    mu            sync.RWMutex
    pollCount     int
}

// NewPoller creates a poller. Minimum interval is 10s
// (enforced).
func NewPoller(adapter *Adapter, interval time.Duration) *Poller
{
    if interval < 10*time.Second {
        interval = 10 * time.Second
    }
    return &Poller{
        adapter:    adapter,
        interval:    interval,
        stopCh:      make(chan struct{}),
        lastModels:  make(map[string]*VerifiedModel),
        lastScores:  make(map[string]float64),
    }
}

// Start begins the background polling goroutine.
func (p *Poller) Start() {
    p.wg.Add(1)
    go p.loop()
}

// Stop signals the poller to stop and waits for the goroutine to
// exit.
func (p *Poller) Stop() {
    close(p.stopCh)
    p.wg.Wait()
}

// IsRunning returns true if the poller goroutine is active.
func (p *Poller) IsRunning() bool {
    select {
    case <-p.stopCh:
        return false
    default:
        return true
    }
}

```

```

func (p *Poller) loop() {
    defer p.wg.Done()

    // Immediate first poll
    p.poll()

    p.ticker = time.NewTicker(p.interval)
    defer p.ticker.Stop()

    for {
        select {
        case <-p.ticker.C:
            p.poll()
        case <-p.stopCh:
            return
        }
    }
}

func (p *Poller) poll() {
    if p.adapter == nil || !p.adapter.IsEnabled() {
        return
    }

    ctx, cancel := context.WithTimeout(context.Background(),
        30*time.Second)
    defer cancel()

    // 1. Fetch all models
    models, err := p.adapter.client.GetModels(ctx)
    if err != nil {
        p.adapter.health.RecordFailure()
        return
    }

    // 2. Detect changes
    p.mu.Lock()
    changes := p.detectChanges(p.lastModels, models)
    p.lastModels = indexModels(models)
    p.mu.Unlock()

    // 3. Update adapter state
    p.adapter.health.RecordSuccess()
    p.adapter.refreshScores(models)

    // 4. Update cache
    if p.adapter.cache != nil {
        p.adapter.cache.SetModels("all", models)
    }
}

```

```

}

// 5. Publish events for changes
if p.adapter.events != nil {
    for _, change := range changes {
        _ = p.adapter.events.Publish(change)
    }
}

// 6. Fetch scores every 3rd poll (scores change slower than
    model lists)
p.pollCount++
if p.pollCount%3 == 0 {
    scores, _ := p.adapter.client.GetProviderScores(ctx)
    if p.adapter.cache != nil && scores != nil {
        p.adapter.cache.SetScores(scores)
    }
    p.mu.Lock()
    p.lastScores = scores
    p.mu.Unlock()
}
}

func (p *Poller) detectChanges(old, new []*VerifiedModel)
    []ChangeEvent {
changes := []ChangeEvent{}
newIndex := indexModels(new)

for id, model := range newIndex {
    if oldModel, ok := old[id]; !ok {
        changes = append(changes, ChangeEvent{
            Type:      "model.discovered",
            Model:      model,
            Timestamp: time.Now(),
        })
    } else {
        if oldModel.OverallScore != model.OverallScore {
            changes = append(changes, ChangeEvent{
                Type:      "model.score_changed",
                Model:      model,
                OldScore:  oldModel.OverallScore,
                Timestamp: time.Now(),
            })
        }
        if oldModel.VerificationStatus !=
model.VerificationStatus {
            changes = append(changes, ChangeEvent{
                Type:      "model.status_changed",

```

```

        Model:      model,
        OldStatus:  oldModel.VerificationStatus,
        Timestamp:  time.Now(),
    })
}
}

for id, model := range old {
    if _, ok := newIndex[id]; !ok {
        changes = append(changes, ChangeEvent{
            Type:      "model.removed",
            Model:      model,
            Timestamp:  time.Now(),
        })
    }
}

return changes
}

func indexModels(models []*VerifiedModel)
    map[string]*VerifiedModel {
    idx := make(map[string]*VerifiedModel, len(models))
    for _, m := range models {
        idx[m.ID] = m
    }
    return idx
}

```

Acceptance Criteria: 1. go build ./internal/verifier/... compiles 2. NewPoller(nil, 5*time.Second) enforces minimum 10s interval 3. Start() + Stop() sequence completes without deadlock 4. detectChanges() detects added, removed, score-changed, and status-changed models 5. pollCount%3 == 0 triggers score fetch every 3rd poll

Dependencies: TASK 2.1.1 **Effort:** Large

TASK 2.4: Create internal/verifier/cache.go

TASK 2.4.1: Implement Two-Tier Cache (LRU + Redis)

File(s): helix_code/internal/verifier/cache.go **Line(s):** CREATE new file

Action: CREATE

```
package verifier
```

```
import (
    "context"
```

```

"encoding/json"
"sync"
"time"

lru "github.com/hashicorp/golang-lru/v2"
"github.com/redis/go-redis/v9"
)

// Cache implements a two-tier cache: L1 in-memory LRU + L2
// Redis.
type Cache struct {
    l1      *lru.Cache[string, *CacheEntry]
    l2      *redis.Client // may be nil if Redis is not configured
    ttl     time.Duration
    mu      sync.RWMutex
}

// CacheEntry stores cached verifier data with timestamp.
type CacheEntry struct {
    Models      []*VerifiedModel `json:"models"`
    Scores      map[string]float64 `json:"scores"`
    FetchedAt   time.Time         `json:"fetched_at"`
    Source      string            `json:"source"` // "verifier",
                "fallback", "embedded"
}

// NewCache creates a two-tier cache.
// ttl: cache entry lifetime
// redisClient: optional Redis client (nil = memory-only)
func NewCache(ttl time.Duration, redisClient *redis.Client)
    *Cache {
    l1Cache, _ := lru.New[string, *CacheEntry](1024)
    return &Cache{
        l1:  l1Cache,
        l2:  redisClient,
        ttl: ttl,
    }
}

// GetModels retrieves cached models from L1 or L2.
func (c *Cache) GetModels(provider string) ([]*VerifiedModel,
    bool) {
    c.mu.RLock()
    defer c.mu.RUnlock()

    // Try L1
    if entry, ok := c.l1.Get(provider); ok {
        if time.Since(entry.FetchedAt) < c.ttl {

```



```

        return entry.Models, true
    }
}

// Try L2 (Redis)
if c.l2 != nil {
    ctx, cancel := context.WithTimeout(context.Background(),
        5*time.Second)
    defer cancel()
    data, err := c.l2.Get(ctx,
        "helix:verifier:models:"+provider).Result()
    if err == nil {
        var entry CacheEntry
        if json.Unmarshal([]byte(data), &entry) == nil {
            if time.Since(entry.FetchedAt) < c.ttl {
                // Backfill L1
                c.l1.Add(provider, &entry)
                return entry.Models, true
            }
        }
    }
}

return nil, false
}

// GetModelsStale retrieves models even if past TTL (for circuit
// breaker fallback).
func (c *Cache) GetModelsStale(provider string)
    ([]*VerifiedModel, bool) {
    c.mu.RLock()
    defer c.mu.RUnlock()

    // Try L1 (accept even if stale, up to 2x TTL)
    if entry, ok := c.l1.Get(provider); ok {
        if time.Since(entry.FetchedAt) < c.ttl*2 {
            return entry.Models, true
        }
    }

    // Try L2 (same relaxed TTL)
    if c.l2 != nil {
        ctx, cancel := context.WithTimeout(context.Background(),
            5*time.Second)
        defer cancel()
        data, err := c.l2.Get(ctx,
            "helix:verifier:models:"+provider).Result()
        if err == nil {
            var entry CacheEntry

```

```

        if json.Unmarshal([]byte(data), &entry) == nil {
            if time.Since(entry.FetchedAt) < c.ttl*2 {
                return entry.Models, true
            }
        }
    }
    return nil, false
}

// SetModels stores models in both L1 and L2.
func (c *Cache) SetModels(provider string, models
    []*VerifiedModel) {
    entry := &CacheEntry{
        Models:    models,
        FetchedAt:  time.Now(),
        Source:     "verifier",
    }

    c.mu.Lock()
    c.l1.Add(provider, entry)
    c.mu.Unlock()

    if c.l2 != nil {
        data, _ := json.Marshal(entry)
        ctx, cancel := context.WithTimeout(context.Background(),
            5*time.Second)
        defer cancel()
        c.l2.Set(ctx, "helix:verifier:models:"+provider, data,
            c.ttl)
    }
}

// GetModelScore retrieves a cached model score.
func (c *Cache) GetModelScore(modelID string) (float64, bool) {
    // Scores are stored with provider="scores" key
    c.mu.RLock()
    defer c.mu.RUnlock()
    if entry, ok := c.l1.Get("scores"); ok {
        if time.Since(entry.FetchedAt) < c.ttl {
            if score, ok := entry.Scores[modelID]; ok {
                return score, true
            }
        }
    }
    return 0, false
}

```

```
// SetScores stores provider/model scores.
func (c *Cache) SetScores(scores map[string]float64) {
    entry := &CacheEntry{
        Scores:    scores,
        FetchedAt: time.Now(),
        Source:     "verifier",
    }

    c.mu.Lock()
    c.l1.Add("scores", entry)
    c.mu.Unlock()

    if c.l2 != nil {
        data, _ := json.Marshal(entry)
        ctx, cancel := context.WithTimeout(context.Background(),
            5*time.Second)
        defer cancel()
        c.l2.Set(ctx, "helix:verifier:scores", data, c.ttl)
    }
}

// Invalidate removes a cache entry from both tiers.
func (c *Cache) Invalidate(provider string) {
    c.mu.Lock()
    c.l1.Remove(provider)
    c.mu.Unlock()

    if c.l2 != nil {
        ctx, cancel := context.WithTimeout(context.Background(),
            5*time.Second)
        defer cancel()
        c.l2.Del(ctx, "helix:verifier:models:"+provider)
    }
}
```

Acceptance Criteria: 1. go build ./internal/verifier/... compiles 2. NewCache(5*time.Minute, nil) creates memory-only cache 3. GetModels("all") returns hit after SetModels("all", ...) 4. GetModelsStale("all") returns hit up to 2x TTL after expiry 5. Invalidate("all") removes from both L1 and L2

Dependencies: TASK 1.5.1 **Effort:** Large

TASK 2.5: Create internal/verifier/health.go

TASK 2.5.1: Implement Circuit Breaker and Health Monitor

File(s): helix_code/internal/verifier/health.go **Line(s):** CREATE new file
Action: CREATE

```

package verifier

import (
    "sync"
    "time"

    "dev.helix.code/internal/config"
)

// CircuitState represents the circuit breaker state.
type CircuitState int

const (
    CircuitClosed CircuitState = iota
    CircuitOpen
    CircuitHalfOpen
)

// HealthMonitor tracks verifier service health with circuit
// breaker pattern.
type HealthMonitor struct {
    state          CircuitState
    failures        int
    successes       int
    lastFailureTime time.Time
    checkInterval   time.Duration
    timeout         time.Duration
    failureThreshold int
    recoveryThreshold int
    halfOpenTimeout time.Duration
    enabled         bool
    mu              sync.RWMutex
}

// NewHealthMonitor creates a health monitor from config.
func NewHealthMonitor(cfg config.VerifierHealthConfig)
    *HealthMonitor {
    return &HealthMonitor{
        checkInterval:    cfg.CheckInterval,
        timeout:          cfg.Timeout,
        failureThreshold:  cfg.FailureThreshold,
        recoveryThreshold: cfg.RecoveryThreshold,
        halfOpenTimeout:  cfg.CircuitBreaker.HalfOpenTimeout,
        enabled:          cfg.CircuitBreaker.Enabled,
        state:            CircuitClosed,
    }
}

```

```

// RecordFailure increments failure count and may open the
// circuit.
func (h *HealthMonitor) RecordFailure() {
    h.mu.Lock()
    defer h.mu.Unlock()

    h.failures++
    h.lastFailureTime = time.Now()

    if h.enabled && h.state != CircuitOpen && h.failures >=
        h.failureThreshold {
        h.state = CircuitOpen
    }
}

// RecordSuccess increments success count and may close the
// circuit.
func (h *HealthMonitor) RecordSuccess() {
    h.mu.Lock()
    defer h.mu.Unlock()

    switch h.state {
    case CircuitHalfOpen:
        h.successes++
        if h.successes >= h.recoveryThreshold {
            h.state = CircuitClosed
            h.failures = 0
            h.successes = 0
        }
    case CircuitClosed:
        h.failures = 0 // reset on success in closed state
    }
}

// AllowRequest returns true if the circuit allows a request
// through.
func (h *HealthMonitor) AllowRequest() bool {
    h.mu.RLock()
    defer h.mu.RUnlock()

    switch h.state {
    case CircuitClosed:
        return true
    case CircuitOpen:
        if time.Since(h.lastFailureTime) > h.halfOpenTimeout {
            // Transition to half-open (requires write lock)
            h.mu.RUnlock()
            h.mu.Lock()
        }
    }
}

```

```

        if h.state == CircuitOpen { // double-check
            h.state = CircuitHalfOpen
            h.successes = 0
        }
        h.mu.Unlock()
        h.mu.RLock()
        return true
    }
    return false
case CircuitHalfOpen:
    return true
}
return false
}

// IsCircuitOpen returns true if the circuit is open.
func (h *HealthMonitor) IsCircuitOpen() bool {
    h.mu.RLock()
    defer h.mu.RUnlock()
    return h.state == CircuitOpen
}

// GetState returns the current circuit state.
func (h *HealthMonitor) GetState() CircuitState {
    h.mu.RLock()
    defer h.mu.RUnlock()
    return h.state
}

// IsHealthy returns true if the circuit is closed.
func (h *HealthMonitor) IsHealthy() bool {
    return h.GetState() == CircuitClosed
}

```

Acceptance Criteria: 1. go build ./internal/verifier/... compiles 2. RecordFailure() x5 with failureThreshold=5 opens circuit 3. AllowRequest() returns false when circuit is open 4. After halfOpenTimeout, AllowRequest() returns true (half-open) 5. RecordSuccess() x3 in half-open closes circuit

Dependencies: TASK 1.2.1 **Effort:** Large

TASK 2.6: Create internal/verifier/events.go

TASK 2.6.1: Implement Event Publishing to HelixCode Event Bus

File(s): helix_code/internal/verifier/events.go **Line(s):** CREATE new file
Action: CREATE

```

package verifier

import (
    "encoding/json"
    "sync"

    "dev.helix.code/internal/event"
)

// Event topic constants for verifier events.
const (
    TopicVerifierModelDiscovered =
        "helix.verifier.model.discovered"
    TopicVerifierModelUpdated     = "helix.verifier.model.updated"
    TopicVerifierModelRemoved     = "helix.verifier.model.removed"
    TopicVerifierProviderHealth   =
        "helix.verifier.provider.health"
    TopicVerifierScoreChanged     = "helix.verifier.score.changed"
    TopicVerifierDegraded         = "helix.verifier.degraded"
    TopicVerifierRecovered        = "helix.verifier.recovered"
)

// EventPublisher publishes verifier changes to the HelixCode
// event bus.
type EventPublisher struct {
    bus      event.Bus
    enabled  bool
    websocket bool
    wsPath   string
    mu       sync.RWMutex
}

// NewEventPublisher creates an event publisher.
func NewEventPublisher(bus event.Bus, enabled, websocket bool,
    wsPath string) *EventPublisher {
    return &EventPublisher{
        bus:      bus,
        enabled:  enabled,
        websocket: websocket,
        wsPath:   wsPath,
    }
}

// Publish sends a change event to the event bus.
func (ep *EventPublisher) Publish(change ChangeEvent) error {
    ep.mu.RLock()
    if !ep.enabled {
        ep.mu.RUnlock()
    }
}

```

```

        return nil
    }
    ep.mu.RUnlock()

    var topic string
    switch change.Type {
    case "model.discovered":
        topic = TopicVerifierModelDiscovered
    case "model.score_changed":
        topic = TopicVerifierScoreChanged
    case "model.status_changed":
        topic = TopicVerifierModelUpdated
    case "model.removed":
        topic = TopicVerifierModelRemoved
    case "provider.health":
        topic = TopicVerifierProviderHealth
    case "degraded":
        topic = TopicVerifierDegraded
    case "recovered":
        topic = TopicVerifierRecovered
    default:
        topic = TopicVerifierModelUpdated
    }

    data, err := json.Marshal(change)
    if err != nil {
        return err
    }

    if ep.bus != nil {
        return ep.bus.Publish(topic, data)
    }
    return nil
}

// IsEnabled returns the current enabled state.
func (ep *EventPublisher) IsEnabled() bool {
    ep.mu.RLock()
    defer ep.mu.RUnlock()
    return ep.enabled
}

// SetEnabled updates the enabled state.
func (ep *EventPublisher) SetEnabled(enabled bool) {
    ep.mu.Lock()
    defer ep.mu.Unlock()
    ep.enabled = enabled
}

```


Acceptance Criteria: 1. `go build ./internal/verifier/...` compiles 2. `Publish()` with `enabled=false` returns `nil` without calling `bus` 3. `Publish()` maps all 6 change types to correct topics 4. `SetEnabled()` toggles publishing on/off

Dependencies: TASK 1.5.1 **Effort:** Medium

TASK 2.7: Modify `internal/llm/model_discovery.go`

TASK 2.7.1: Replace `fetchExternalModels()` Hardcoded List with Verifier Fetch

File(s): `helix_code/internal/llm/model_discovery.go` **Line(s):** Search for `func (e *ModelDiscoveryEngine) fetchExternalModels()` **Action:** MODIFY

Add new field to `ModelDiscoveryEngine` struct (search for struct definition):

```
type ModelDiscoveryEngine struct {
    // ... existing fields ...
    verifierAdapter *verifier.Adapter // NEW – LLMsVerifier
        bridge
    logger          *logrus.Logger    // NEW – structured logging
}
```

Replace the `fetchExternalModels()` function:

```
// fetchExternalModels retrieves external models from
// LLMsVerifier when enabled.
// Replaces the previous hardcoded list (BLUFF-002 fix).
func (e *ModelDiscoveryEngine) fetchExternalModels(ctx
    context.Context) []*ModelInfo {
    // If verifier adapter is available and enabled, use it as
    // the single source of truth
    if e.verifierAdapter != nil && e.verifierAdapter.IsEnabled()
    {
        verifiedModels, err :=
            e.verifierAdapter.GetVerifiedModels(ctx)
        if err == nil && len(verifiedModels) > 0 {
            return e.convertVerifiedToModelInfo(verifiedModels)
        }
        if err != nil && err != verifier.ErrVerifierDisabled {
            e.logger.Warnf("Verifier fetch failed for external
                models: %v", err)
        }
    }

    // Fallback: return empty – local providers (Ollama,
    // llama.cpp) will still be discovered
    // The hardcoded list has been REMOVED per CONST-036.
    return []*ModelInfo{}
}
```

```
// convertVerifiedToModelInfo transforms verifier models into  
HelixCode ModelInfo.
```

```
func (e *ModelDiscoveryEngine)  
    convertVerifiedToModelInfo(verified  
        []*verifier.VerifiedModel) []*ModelInfo {  
    result := make([]*ModelInfo, 0, len(verified))  
    for _, v := range verified {  
        mi := &ModelInfo{  
            ID:          v.ID,  
            Name:        v.DisplayName,  
            Format:      FormatUnknown, // Verifier doesn't  
            track GGUF vs HF  
            Size:        0,             // Not provided by  
            verifier  
            ContextSize: v.ContextSize,  
            MaxTokens:   v.MaxOutputTokens,  
            Provider:    v.Provider,  
            Verified:    v.Verified,  
            Score:       v.OverallScore,  
            Capabilities: e.mapCapabilities(v),  
            Source:      v.Source,  
        }  
        result = append(result, mi)  
    }  
    return result  
}
```

```
// mapCapabilities converts verifier capability flags to  
ModelCapability slice.
```

```
func (e *ModelDiscoveryEngine) mapCapabilities(v  
    *verifier.VerifiedModel) []ModelCapability {  
    caps := []ModelCapability{}  
    if v.SupportsCode {  
        caps = append(caps, CapabilityCodeGeneration)  
    }  
    if v.SupportsTools || v.SupportsFunctions {  
        caps = append(caps, CapabilityToolUse)  
    }  
    if v.SupportsStreaming {  
        caps = append(caps, CapabilityStreaming)  
    }  
    if v.SupportsVision {  
        caps = append(caps, CapabilityVision)  
    }  
    if v.SupportsReasoning {  
        caps = append(caps, CapabilityReasoning)  
    }  
}
```

```

    if v.SupportsEmbeddings {
        caps = append(caps, CapabilityEmbeddings)
    }
    return caps
}

```

Acceptance Criteria: 1. go build ./internal/llm/... compiles 2. fetchExternalModels() no longer contains hardcoded []*ModelInfo{{ID: "llama-3-8b-instruct"...}} 3. grep "llama-3-8b-instruct" internal/llm/model_discovery.go returns zero matches 4. convertVerifiedToModelInfo() maps all capability flags 5. mapCapabilities() returns CapabilityCodeGeneration when v.SupportsCode is true

Dependencies: TASK 2.1.1 **Effort:** Large

TASK 2.8: Modify internal/llm/model_manager.go

TASK 2.8.1: Augment SelectOptimalModel() with Verifier Scores

File(s): helix_code/internal/llm/model_manager.go **Line(s):** Inside SelectOptimalModel() method, after task type suitability filter **Action:** MODIFY

Add new field to ModelManager struct:

```

type ModelManager struct {
    // ... existing fields ...
    verifierAdapter *verifier.Adapter // NEW - LLMsVerifier bridge
}

```

Insert verifier score augmentation into SelectOptimalModel():

```

func (m *ModelManager) SelectOptimalModel(criteria
    ModelSelectionCriteria) (*ModelInfo, error) {
    candidates :=
        m.filterByCapabilities(criteria.RequiredCapabilities)
    candidates = m.filterByContextSize(candidates,
        criteria.MaxTokens)
    candidates = m.filterByTaskType(candidates,
        criteria.TaskType)

    // NEW: Incorporate LLMsVerifier scores into ranking
    if m.verifierAdapter != nil && m.verifierAdapter.IsEnabled()
    {
        candidates = m.rankByVerifierScores(candidates, criteria)
    }

    candidates = m.filterByHardwareCompatibility(candidates)
    candidates = m.applyQualityPreference(candidates,
        criteria.QualityPreference)
}

```

```

    if len(candidates) == 0 {
        return nil, ErrNoSuitableModel
    }
    return candidates[0], nil
}

// rankByVerifierScores blends verifier scores with local
// heuristic scores.
func (m *ModelManager) rankByVerifierScores(
    candidates []*ModelInfo,
    criteria ModelSelectionCriteria,
) []*ModelInfo {
    scored := make([]*struct {
        model *ModelInfo
        score float64
    }, 0, len(candidates))

    for _, c := range candidates {
        baseScore := c.Score // existing heuristic score (0-1)

        // Fetch verifier score for this specific model
        verifierScore, found :=
            m.verifierAdapter.GetModelScore(c.ID)
        if found {
            // Weighted blend: 60% verifier, 40% local heuristic
            // Verifier score is 0-10; normalize to 0-1
            normalizedVerifier := verifierScore / 10.0
            blendedScore := (normalizedVerifier * 0.6) +
                (baseScore * 0.4)

            // Apply task-specific boost from verifier dimensions
            switch criteria.TaskType {
            case "code_generation", "debugging", "refactoring",
                "testing":
                codeScore, hasCode :=
                    m.verifierAdapter.GetModelCodeCapabilityScore(c.ID)
                if hasCode {
                    blendedScore += (codeScore / 10.0) * 0.15 //
                    +15% code capability bonus
                }
            case "planning", "analysis", "architecture":
                relScore, hasRel :=
                    m.verifierAdapter.GetModelReliabilityScore(c.ID)
                if hasRel {
                    blendedScore += (relScore / 10.0) * 0.10 //
                    +10% reliability bonus
                }
            }
        }
    }
}

```

```

    }

    baseScore = blendedScore
}

scored = append(scored, struct {
    model *ModelInfo
    score float64
} {c, baseScore})
}

sort.Slice(scored, func(i, j int) bool {
    return scored[i].score > scored[j].score
})

result := make([]*ModelInfo, len(scored))
for i, s := range scored {
    result[i] = s.model
}
return result
}

```

Acceptance Criteria: 1. go build ./internal/llm/... compiles 2. SelectOptimalModel() calls rankByVerifierScores() when adapter is enabled 3. rankByVerifierScores() gives 60% weight to verifier score, 40% to local heuristic 4. Task type “code_generation” adds 15% code capability bonus 5. Task type “planning” adds 10% reliability bonus

Dependencies: TASK 2.1.1 **Effort:** Large

TASK 2.9: Modify cmd/cli/main.go

TASK 2.9.1: Replace handleListModels() Hardcoded Models with Dynamic Fetch

File(s): helix_code/cmd/cli/main.go **Line(s):** Lines 101-128 (the handleListModels method) **Action:** MODIFY

Replace the entire handleListModels() method:

```

func (c *CLI) handleListModels(ctx context.Context) error {
    // Use verifier adapter if enabled, otherwise fall through to
    model manager
    if c.verifierAdapter != nil && c.verifierAdapter.IsEnabled()
    {
        models, err := c.verifierAdapter.GetVerifiedModels(ctx)
        if err == nil && len(models) > 0 {
            return c.printVerifiedModels(models)
        }
        // Log warning but don't fail – try fallback
    }
}

```

```

        c.logger.Warnf("Verifier model fetch failed, using
        fallback: %v", err)
    }

    // Fallback to existing ModelManager (already initialized,
    // may have local models)
    if c.modelManager != nil {
        models := c.modelManager.GetAvailableModels()
        return c.printManagerModels(models)
    }

    // Ultimate fallback: static list (for bootstrapping before
    // any provider is ready)
    return c.printFallbackModels()
}

func (c *CLI) printVerifiedModels(models
    []*verifier.VerifiedModel) error {
    fmt.Println("Available Models (from LLMsVerifier):")
    fmt.Println(strings.Repeat("-", 80))
    fmt.Printf("%-24s %-20s %-10s %-12s %s\n", "ID", "Name",
        "Provider", "Score", "Status")
    for _, m := range models {
        status := "verified"
        if !m.Verified {
            status = "pending"
        }
        if m.VerificationStatus == "failed" {
            status = "failed"
        }
        if m.VerificationStatus == "rate_limited" {
            status = "rate-limited"
        }
        scoreStr := fmt.Sprintf("SC:%.1f", m.OverallScore)
        fmt.Printf("%-24s %-20s %-10s %-12s %s\n", m.ID, m.Name,
            m.Provider, scoreStr, status)
    }
    return nil
}

func (c *CLI) printManagerModels(models []*llm.ModelInfo) error {
    fmt.Println("Available Models (from providers):")
    fmt.Println(strings.Repeat("-", 80))
    fmt.Printf("%-24s %-20s %-10s %-12s %s\n", "ID", "Name",
        "Provider", "Context", "Status")
    for _, m := range models {
        status := "available"
        if !m.Verified {

```

```

        status = "unverified"
    }
    fmt.Printf("%-24s %-20s %-10s %-12d %s\n", m.ID, m.Name,
        m.Provider, m.ContextSize, status)
}
return nil
}

func (c *CLI) printFallbackModels() error {
    fmt.Println("Available Models (fallback list):")
    fmt.Println(strings.Repeat("-", 80))
    for _, m := range verifier.FallbackModels {
        fmt.Printf("%-24s %-20s %-10s %-12s %s\n", m.ID, m.Name,
            m.Provider, "fallback", "available")
    }
    return nil
}

```

Acceptance Criteria: 1. go build ./cmd/cli/... compiles 2. grep "llama-3-8b" cmd/cli/main.go returns zero matches (old hardcoded list removed) 3. handleListModels() calls verifierAdapter.GetVerifiedModels() first 4. printVerifiedModels() includes score suffix SC:X.X 5. All three print methods exist: printVerifiedModels, printManagerModels, printFallbackModels

Dependencies: TASK 2.1.1 **Effort:** Large

TASK 2.10: Modify internal/llm/factory.go

TASK 2.10.1: Add Verifier-Aware Provider Validation

File(s): helix_code/internal/llm/factory.go **Line(s):** After provider creation, before return provider, nil **Action:** MODIFY

```

func NewProvider(config ProviderConfigEntry) (Provider, error) {
    var provider Provider
    var err error

    switch config.Type {
    case ProviderTypeOpenAI:    provider, err =
        NewOpenAIProvider(config)
    case ProviderTypeAnthropic: provider, err =
        NewAnthropicProvider(config)
    case ProviderTypeGemini:    provider, err =
        NewGeminiProvider(config)
    case ProviderTypeOllama:    provider, err =
        NewOllamaProvider(config)
    case ProviderTypeLlamaCpp:  provider, err =
        NewLlamaCPPProvider(config)
    }
    return provider, err
}

```

```

case ProviderTypeQwen:      provider, err =
    NewQwenProvider(config)
case ProviderTypeXAI:      provider, err =
    NewXAIProvider(config)
case ProviderTypeOpenRouter: provider, err =
    NewOpenRouterProvider(config)
case ProviderTypeAzure:    provider, err =
    NewAzureProvider(config)
case ProviderTypeBedrock:  provider, err =
    NewBedrockProvider(config)
case ProviderTypeVertexAI: provider, err =
    NewVertexAIProvider(config)
case ProviderTypeGroq:     provider, err =
    NewGroqProvider(config)
case ProviderTypeVLLM:     provider, err =
    NewVLLMProvider(config)
case ProviderTypeLocalAI:  provider, err =
    NewLocalAIProvider(config)
// ... existing cases ...
default:
    return nil, fmt.Errorf("unsupported provider type: %s",
        config.Type)
}

if err != nil {
    return nil, err
}

// NEW: Validate provider against LLMsVerifier registry
if verifierAdapter != nil && verifierAdapter.IsEnabled() {
    status, found :=
        verifierAdapter.GetProviderStatus(string(config.Type))
    if found {
        if !status.Healthy {
            return nil, fmt.Errorf("provider %s is marked
unhealthy by verifier (score: %.1f)",
                config.Type, status.Score)
        }
        if status.Score <
            verifierAdapter.GetMinAcceptableScore() {
            return nil, fmt.Errorf("provider %s score %.1f
below minimum %.1f",
                config.Type, status.Score,
                verifierAdapter.GetMinAcceptableScore())
        }
    }
}
}

```



```
    return provider, nil
}
```

Acceptance Criteria: 1. `go build ./internal/llm/...` compiles 2. `NewProvider()` returns error when verifier marks provider unhealthy 3. `NewProvider()` returns error when provider score is below `min_acceptable_score` 4. When verifier is disabled, factory behavior is unchanged

Dependencies: TASK 2.1.1 **Effort:** Medium

TASK 2.11: Create `internal/llm/verifier_integration.go`

TASK 2.11.1: Create Bridge File Between `llm` and `verifier` Packages

File(s): `helix_code/internal/llm/verifier_integration.go` **Line(s):** CREATE new file **Action:** CREATE

```
package llm

import (
    "context"
    "dev.helix.code/internal/verifier"
)

// VerifierModelSource implements the model source interface for
// the discovery engine.
// It delegates to the verifier adapter to fetch real-time model
// data.
type VerifierModelSource struct {
    adapter *verifier.Adapter
}

// NewVerifierModelSource creates a verifier-backed model source.
func NewVerifierModelSource(adapter *verifier.Adapter)
    *VerifierModelSource {
    return &VerifierModelSource{adapter: adapter}
}

// IsAvailable returns true if the verifier adapter is enabled
// and reachable.
func (s *VerifierModelSource) IsAvailable() bool {
    return s.adapter != nil && s.adapter.IsEnabled() &&
        s.adapter.IsReachable()
}

// FetchModels retrieves models from the verifier.
func (s *VerifierModelSource) FetchModels(ctx context.Context)
    ([]*ModelInfo, error) {
    verified, err := s.adapter.GetVerifiedModels(ctx)
```

```

    if err != nil {
        return nil, err
    }
    return s.convert(verified), nil
}

// convert transforms VerifiedModel into HelixCode ModelInfo.
func (s *VerifierModelSource) convert(verified
    []*verifier.VerifiedModel) []*ModelInfo {
    result := make([]*ModelInfo, 0, len(verified))
    for _, v := range verified {
        mi := &ModelInfo{
            ID:          v.ID,
            Name:         v.DisplayName,
            Format:       FormatUnknown,
            Size:         0,
            ContextSize: v.ContextSize,
            MaxTokens:    v.MaxOutputTokens,
            Provider:     v.Provider,
            Verified:     v.Verified,
            Score:        v.OverallScore,
            Source:      v.Source,
        }
        // Map capabilities
        if v.SupportsCode {
            mi.Capabilities = append(mi.Capabilities,
                CapabilityCodeGeneration)
        }
        if v.SupportsTools || v.SupportsFunctions {
            mi.Capabilities = append(mi.Capabilities,
                CapabilityToolUse)
        }
        if v.SupportsStreaming {
            mi.Capabilities = append(mi.Capabilities,
                CapabilityStreaming)
        }
        if v.SupportsVision {
            mi.Capabilities = append(mi.Capabilities,
                CapabilityVision)
        }
        if v.SupportsReasoning {
            mi.Capabilities = append(mi.Capabilities,
                CapabilityReasoning)
        }
        if v.SupportsEmbeddings {
            mi.Capabilities = append(mi.Capabilities,
                CapabilityEmbeddings)
        }
    }
}

```

```

        result = append(result, mi)
    }
    return result
}

```

Acceptance Criteria: 1. `go build ./internal/llm/...` compiles 2. `IsAvailable()` returns false when adapter is nil 3. `FetchModels()` returns `[]*ModelInfo` with correct capability mapping 4. `convert()` handles all verifier capability flags

Dependencies: TASK 2.1.1, TASK 2.7.1 **Effort:** Medium

TASK 2.12: Add Provider-Specific Enable/Disable and Real-Time Updates

TASK 2.12.1: Implement Provider Enable Truth Table

File(s): `helix_code/internal/verifier/adapter.go` **Line(s):** Already implemented in `filterByProviderConfig()` — add truth table documentation **Action:** DOCUMENT

The truth table is enforced by `filterByProviderConfig()` in `adapter.go`:

```

// Provider Enable State Resolution:
//   verifier.providers.X.enabled  ×
//       helixcode.providers.X.enabled  =  Effective
//   _____
//   true                            ×
//       true                        =  ENABLED
//   true                            ×
//       false                       =  DISABLED
//   false                           ×
//       true                        =  DISABLED
//   false                           ×
//       false                       =  DISABLED
//   (not set)                       ×
//       true                        =  ENABLED (inherits)
//   (not set)                       ×
//       false                       =  DISABLED (inherits)

```

Acceptance Criteria: 1. Truth table is documented as comment in `adapter.go` 2. `filterByProviderConfig()` correctly implements the AND logic

Dependencies: TASK 2.1.1 **Effort:** Small

PHASE 2 ROLLBACK PLAN

```

cd HelixCode
git checkout -- internal/llm/model_discovery.go
git checkout -- internal/llm/model_manager.go
git checkout -- cmd/cli/main.go
git checkout -- internal/llm/factory.go

```

```
git rm --cached internal/verifier/adapter.go internal/verifier/
    discovery.go \
    internal/verifier/poller.go internal/verifier/cache.go \
    internal/verifier/health.go internal/verifier/events.go \
    internal/llm/verifier_integration.go
rm -f internal/verifier/adapter.go internal/verifier/
    discovery.go \
    internal/verifier/poller.go internal/verifier/cache.go \
    internal/verifier/health.go internal/verifier/events.go \
    internal/llm/verifier_integration.go
go mod tidy
make build
make test-unit
```

PHASE 2 VERIFICATION CHECKLIST

- ☐ go build ./... compiles with zero errors
 - ☐ make test-unit passes
 - ☐ grep "llama-3-8b" cmd/cli/main.go returns ZERO matches (BLUFF-002 fixed)
 - ☐ grep "llama-3-8b-instruct" internal/llm/model_discovery.go returns ZERO matches
 - ☐ Adapter.GetVerifiedModels() returns models with non-empty IDs
 - ☐ HealthMonitor.RecordFailure() x5 opens circuit breaker
 - ☐ Poller.Start() + Poller.Stop() completes without deadlock
 - ☐ Cache.GetModels("all") returns hit after SetModels()
 - ☐ ModelManager.SelectOptimalModel() uses verifier scores when adapter enabled
 - ☐ NewProvider() rejects unhealthy providers when verifier enabled
 - ☐ EventPublisher.Publish() maps all change types to correct topics
 - ☐ fallback_models.go contains exactly 7 fallback entries
-

PHASE 3: UX IMPLEMENTATION — Enterprise-Grade Model Display

Phase Goal: Implement the UX design spec across all platforms (CLI wide/standard/narrow/compact, JSON/YAML output, TUI interactive selector, real-time status bar, notifications, auto-suggest).

Phase Entry Criteria: Phase 2 verification checklist is complete. **Phase Exit Criteria:** 1. --list-models shows verification status, score, price, latency, capabilities 2. --model-info <id> shows full detail with all dimensions 3. All 6 width modes render correctly 4. TUI model selector works with keyboard navigation 5. Real-time status bar shows model counts 6. Notifications appear for cooldown/provider offline events 7. Auto-suggest displays when unavailable model is selected 8. Cross-platform symbol rendering works on Linux, macOS, Windows CMD, Windows Terminal

TASK 3.1: Create internal/cli/ux/symbols.go

TASK 3.1.1: Implement Cross-Platform Symbol Resolution

File(s): helix_code/internal/cli/ux/symbols.go **Line(s):** CREATE new file

Action: CREATE

```
package ux

// SymbolSet holds platform-appropriate symbols for UI rendering.
type SymbolSet struct {
    Diamond      string // Diamond/bullet
    SepHorizontal string
    SepVertical  string
    Verified     string
    Failed       string
    Healthy      string
    Degraded     string
    Cooldown     string
    Pending      string
    Bullet       string
    ArrowUp      string
    ArrowRight   string
    Dollar       string
    Vision       string
    Streaming    string
    Tools        string
    Code         string
    Reasoning    string
    Audio        string
    Video       string
    Embeddings   string
    OpenSource   string
}
```

```

    ProgressFull  string
    ProgressEmpty string
}

// DefaultSymbols uses Unicode symbols (best for modern
// terminals).
var DefaultSymbols = &SymbolSet{
    Diamond:      "◆",
    SepHorizontal: "—",
    SepVertical:   "│",
    Verified:      "✓",
    Failed:        "✗",
    Healthy:       "●",
    Degraded:      "◐",
    CoolDown:      "⏸",
    Pending:       "⌚",
    Bullet:        "•",
    ArrowUp:       "↑",
    ArrowRight:    "→",
    Dollar:        "$",
    Vision:        "🔮",
    Streaming:     "⚡",
    Tools:         "🔧",
    Code:          "</>",
    Reasoning:     "🧠",
    Audio:         "🎧",
    Video:         "🎬",
    Embeddings:    "📊",
    OpenSource:    "🔒",
    ProgressFull:  "▒",
    ProgressEmpty: "░",
}

// FallbackSymbols uses ASCII for Windows CMD and minimal
// terminals.
var FallbackSymbols = &SymbolSet{
    Diamond:      "*",
    SepHorizontal: "-",
    SepVertical:   "|",
    Verified:      "[OK]",
    Failed:        "[NO]",
    Healthy:       "[+]",
    Degraded:      "[~]",
    CoolDown:      "[CD]",
    Pending:       "[.]",
    Bullet:        "-",
    ArrowUp:       "^",
    ArrowRight:    ">",
}

```

```

Dollar:      "$",
Vision:     "[V]",
Streaming:   "[S]",
Tools:       "[T]",
Code:        "[C]",
Reasoning:   "[R]",
Audio:       "[A]",
Video:       "[M]",
Embeddings:  "[E]",
OpenSource:  "[O]",
ProgressFull: "#",
ProgressEmpty: "-",
}

// NewSymbolSet selects the appropriate symbol set based on
// terminal capabilities.
func NewSymbolSet(isWindowsCMD bool) *SymbolSet {
    if isWindowsCMD {
        return FallbackSymbols
    }
    return DefaultSymbols
}

```

Acceptance Criteria: 1. `go build ./internal/cli/ux/...` compiles 2. `NewSymbolSet(true)` returns `FallbackSymbols` 3. `NewSymbolSet(false)` returns `DefaultSymbols` 4. All 22 symbol fields are defined in both sets

Dependencies: None **Effort:** Small

TASK 3.2: Create `internal/cli/ux/badges.go`

TASK 3.2.1: Implement All Badge Types

File(s): `helix_code/internal/cli/ux/badges.go` **Line(s):** CREATE new file **Action:** CREATE

```

package ux

import (
    "fmt"
    "strings"
    "time"

    "github.com/fatih/color"
)

var (
    CVerified      = color.New(color.FgGreen, color.Bold)
    CFailed        = color.New(color.FgRed, color.Bold)

```

```

CDegraded      = color.New(color.FgYellow, color.Bold)
CCoolDown      = color.New(color.FgHiRed, color.Bold)
CScoreExcellent = color.New(color.FgHiGreen)
CScoreGood     = color.New(color.FgGreen)
CScoreAverage  = color.New(color.FgYellow)
CScorePoor     = color.New(color.FgRed)
CScoreBad      = color.New(color.FgHiRed, color.Bold)
CPriceFree     = color.New(color.FgHiGreen, color.Bold)
CPriceCheap    = color.New(color.FgGreen)
CPriceModerate = color.New(color.FgYellow)
CPriceExpensive = color.New(color.FgRed, color.Bold)
CBarGood       = color.New(color.FgGreen)
CBarAverage    = color.New(color.FgYellow)
CBarPoor       = color.New(color.FgRed)
CBarEmpty      = color.New(color.FgHiBlack)
)

```

```

// VerificationBadge renders a verification status indicator.
func VerificationBadge(status string, sym *SymbolSet) string {
    switch status {
    case "verified", "passed":
        return CVerified.Sprintf("%s Ready", sym.Verified)
    case "failed":
        return CFailed.Sprintf("%s Failed", sym.Failed)
    case "pending":
        return CDegraded.Sprintf("%s Pending", sym.Pending)
    case "rate_limited":
        return CCoolDown.Sprintf("%s Cooldown", sym.CoolDown)
    default:
        return CDegraded.Sprintf("%s Unknown", sym.Degraded)
    }
}

```

```

// ProviderHealthBadge renders provider health status.
func ProviderHealthBadge(status string, sym *SymbolSet) string {
    switch status {
    case "healthy":
        return CVerified.Sprintf("%s HEALTHY", sym.Healthy)
    case "degraded":
        return CDegraded.Sprintf("%s DEGRADED", sym.Degraded)
    case "unhealthy", "offline":
        return CFailed.Sprintf("%s OFFLINE", sym.Failed)
    default:
        return CDegraded.Sprintf("%s UNKNOWN", sym.Degraded)
    }
}

```

```

// CooldownBadge renders cooldown state.

```



```

func CooldownBadge(resetIn time.Duration, sym *SymbolSet) string
{
    return CCoolDown.Sprintf("%s Cooldown (%s)", sym.CoolDown,
        formatDuration(resetIn))
}

// ScoreBadge renders a score with color.
func ScoreBadge(score float64, sym *SymbolSet) string {
    switch {
    case score >= 9.0:
        return CScoreExcellent.Sprintf("%.1f", score)
    case score >= 7.0:
        return CScoreGood.Sprintf("%.1f", score)
    case score >= 5.0:
        return CScoreAverage.Sprintf("%.1f", score)
    case score >= 3.0:
        return CScorePoor.Sprintf("%.1f", score)
    default:
        return CScoreBad.Sprintf("%.1f", score)
    }
}

// PriceBadge renders a price indicator.
func PriceBadge(costIn, costOut float64, sym *SymbolSet, width
    int) string {
    avgPrice := (costIn + costOut) / 2.0 * 1000
    switch {
    case avgPrice == 0:
        return CPriceFree.Sprintf("%sFREE", sym.Dollar)
    case avgPrice < 0.5:
        return CPriceCheap.Sprintf("%s%.2f/1K", sym.Dollar,
            avgPrice)
    case avgPrice < 2.0:
        return CPriceModerate.Sprintf("%s%.2f/1K", sym.Dollar,
            avgPrice)
    default:
        return CPriceExpensive.Sprintf("%s%.2f/1K", sym.Dollar,
            avgPrice)
    }
}

// TierBadge renders a model tier indicator.
func TierBadge(tier int) string {
    switch tier {
    case 1:
        return CVerified.Sprintf("★★★★★ Premium")
    case 2:
        return CScoreGood.Sprintf("★★★★★ High")
    }
}

```

```

    case 3:
        return CScoreAverage.Sprintf("★★★ Fast")
    case 4:
        return CScoreAverage.Sprintf("★★ Aggregator")
    case 5:
        return CPriceFree.Sprintf("★ Free")
    default:
        return "Unknown"
    }
}

func formatDuration(d time.Duration) string {
    if d < 0 {
        return "now"
    }
    if d < time.Minute {
        return fmt.Sprintf("%ds", int(d.Seconds()))
    }
    if d < time.Hour {
        return fmt.Sprintf("%dm", int(d.Minutes()))
    }
    return fmt.Sprintf("%dh%dm", int(d.Hours()), int(d.Minutes())
        %60)
}

```

Acceptance Criteria: 1. go build ./internal/cli/ux/... compiles 2. VerificationBadge("verified", DefaultSymbols) contains "Ready" in green 3. ScoreBadge(9.5, nil) uses green color 4. ScoreBadge(2.5, nil) uses red bold 5. All 6 badge functions exist and are exported

Dependencies: TASK 3.1.1 **Effort:** Medium

TASK 3.3: Create internal/cli/ux/capabilities.go

TASK 3.3.1: Implement Capability Strip Rendering

File(s): helix_code/internal/cli/ux/capabilities.go **Line(s):** CREATE new file **Action:** CREATE

```

package ux

import (
    "fmt"
    "strings"

    "dev.helix.code/internal/verifier"
)

// CapabilityStrip renders a compact capability indicator.

```

```

func CapabilityStrip(m *verifier.VerifiedModel, sym *SymbolSet,
    width int) string {
    parts := []string{}
    if m.SupportsVision {
        parts = append(parts, sym.Vision)
    }
    if m.SupportsStreaming {
        parts = append(parts, sym.Streaming)
    }
    if m.SupportsTools || m.SupportsFunctions {
        parts = append(parts, sym.Tools)
    }
    if m.SupportsCode {
        parts = append(parts, sym.Code)
    }
    if m.SupportsReasoning {
        parts = append(parts, sym.Reasoning)
    }
    if m.SupportsAudio {
        parts = append(parts, sym.Audio)
    }
    if m.SupportsVideo {
        parts = append(parts, sym.Video)
    }
    if m.SupportsEmbeddings {
        parts = append(parts, sym.Embeddings)
    }
    if m.OpenSource {
        parts = append(parts, sym.OpenSource)
    }
    return strings.Join(parts, " ")
}

```

// CapabilityStripCompact renders a narrow-width capability strip.

```

func CapabilityStripCompact(m *verifier.VerifiedModel, sym
    *SymbolSet) string {
    count := 0
    if m.SupportsCode {
        count++
    }
    if m.SupportsStreaming {
        count++
    }
    if m.SupportsTools || m.SupportsFunctions {
        count++
    }
    if m.SupportsVision {

```

```

        count++
    }
    return fmt.Sprintf("%d caps", count)
}

// CapabilityDetails renders full capability grid with pass/fail.
func CapabilityDetails(m *verifier.VerifiedModel, v
    *verifier.VerificationResult, sym *SymbolSet, width int)
    string {
caps := []struct {
    label string
    val    bool
    s      string
}{}
    {"Vision", m.SupportsVision, sym.Vision},
    {"Streaming", m.SupportsStreaming, sym.Streaming},
    {"Tool Use", m.SupportsTools, sym.Tools},
    {"Code Gen", v != nil && v.SupportsCodeGeneration,
    sym.Code},
    {"Reasoning", v != nil && v.SupportsReasoning,
    sym.Reasoning},
    {"Audio", m.SupportsAudio, sym.Audio},
    {"Video", m.SupportsVideo, sym.Video},
    {"Embeddings", v != nil && v.SupportsEmbeddings,
    sym.Embeddings},
    {"Open Source", m.OpenSource, sym.OpenSource},
    {"JSON Mode", v != nil && v.SupportsJSONMode, "{ }"},
}

var b strings.Builder
cols := 4
if width < 80 {
    cols = 2
}

for i := 0; i < len(caps); i += cols {
    for j := 0; j < cols && i+j < len(caps); j++ {
        c := caps[i+j]
        status := CFailed.Sprintf("%s", sym.Failed)
        if c.val {
            status = CVerified.Sprintf("%s", sym.Verified)
        }
        b.WriteString(fmt.Sprintf("  %s %-18s", status,
        c.label))
    }
    b.WriteString("\n")
}

```

```
    return b.String()
}
```

Acceptance Criteria: 1. `go build ./internal/cli/ux/...` compiles 2. `CapabilityStrip()` returns non-empty for GPT-4o (has vision, streaming, tools, code) 3. `CapabilityStripCompact()` returns “4 caps” for a model with 4 capabilities 4. `CapabilityDetails()` uses 4 columns when width ≥ 80 , 2 columns when < 80

Dependencies: TASK 3.1.1 **Effort:** Medium

TASK 3.4: Create `internal/cli/ux/render.go`

TASK 3.4.1: Implement Model List Rendering (Wide/Standard/Narrow)

File(s): `helix_code/internal/cli/ux/render.go` **Line(s):** CREATE new file **Action:** CREATE

```
package ux

import (
    "encoding/json"
    "fmt"
    "strings"

    "dev.helix.code/internal/verifier"
    "gopkg.in/yaml.v3"
)

// ModelListRow holds all data needed to render one model row.
type ModelListRow struct {
    Model          *verifier.VerifiedModel
    Provider       *verifier.ProviderStatus
    Verification    *verifier.VerificationResult
    Limits         *verifier.RateLimitStatus
    Cooldown       *verifier.CooldownInfo
    Rank           int
}

// RenderModelList renders the model list based on terminal
// width.
func RenderModelList(rows []*ModelListRow, sym *SymbolSet, width
    int, opts *RenderOptions) string {
    if opts != nil && opts.Format == "json" {
        return renderJSON(rows)
    }
    if opts != nil && opts.Format == "yaml" {
        return renderYAML(rows)
    }
}
```

```

switch {
case width >= 140:
    return renderWide(rows, sym, width, opts)
case width >= 100:
    return renderStandard(rows, sym, width, opts)
case width >= 80:
    return renderNarrow(rows, sym, width, opts)
default:
    return renderCompact(rows, sym, width, opts)
}
}

// RenderOptions controls list rendering behavior.
type RenderOptions struct {
    Format      string // "table", "json", "yaml"
    NoColor     bool
    NoEmoji     bool
    ShowPrices  bool
    ShowLatency bool
    GroupBy     string // "provider", "tier", "none"
    SortBy      string // "score", "price", "name", "latency"
}

func renderWide(rows []*ModelListRow, sym *SymbolSet, width int,
    opts *RenderOptions) string {
    var b strings.Builder
    b.WriteString(fmt.Sprintf(" %s HelixCode — Available Models\n", sym.Diamond))
    b.WriteString(fmt.Sprintf(" %s\n",
        strings.Repeat(sym.SepHorizontal, width-2)))
    header := fmt.Sprintf(" %-4s %-26s %-14s %-8s %-12s %-10s\n",
        "%-10s %-10s %s",
        "Rank", "Model", "Provider", "Score", "Status",
        "Latency", "Price", "Tier", "Capabilities")
    b.WriteString(header + "\n")
    b.WriteString(fmt.Sprintf(" %s\n",
        strings.Repeat(sym.SepHorizontal, width-2)))

    for _, r := range rows {
        status := VerificationBadge(r.Model.VerificationStatus,
            sym)
        score := ScoreBadge(r.Model.OverallScore, sym)
        price := PriceBadge(r.Model.CostPerInputToken,
            r.Model.CostPerOutputToken, sym, width)
        caps := CapabilityStrip(r.Model, sym, width)
        tier := TierBadge(r.Model.Tier)
        latencyStr := formatLatency(r.Model.Latency)
    }
}

```

```

        line := fmt.Sprintf(" %-4d %-26s %-14s %-8s %-12s %-10s
%-10s %-10s %s",
            r.Rank, truncate(r.Model.DisplayName, 26),
            r.Model.Provider,
            score, status, latencyStr, price, tier, caps)
        b.WriteString(line + "\n")
    }
    b.WriteString(fmt.Sprintf(" %s\n",
        strings.Repeat(sym.SepHorizontal, width-2)))
    return b.String()
}

```

```

func renderStandard(rows []*ModelListRow, sym *SymbolSet, width
    int, opts *RenderOptions) string {
    var b strings.Builder
    b.WriteString(fmt.Sprintf(" %s HelixCode — Available
Models\n", sym.Diamond))
    b.WriteString(fmt.Sprintf(" %s\n",
        strings.Repeat(sym.SepHorizontal, width-2)))
    header := fmt.Sprintf(" %-4s %-28s %-12s %-8s %-12s %-10s
%s",
        "#", "Model", "Provider", "Score", "Status", "Latency",
        "Price")
    b.WriteString(header + "\n")

    for _, r := range rows {
        status := VerificationBadge(r.Model.VerificationStatus,
            sym)
        score := ScoreBadge(r.Model.OverallScore, sym)
        price := PriceBadge(r.Model.CostPerInputToken,
            r.Model.CostPerOutputToken, sym, width)
        latencyStr := formatLatency(r.Model.Latency)

        line := fmt.Sprintf(" %-4d %-28s %-12s %-8s %-12s %-10s
%s",
            r.Rank, truncate(r.Model.DisplayName, 28),
            r.Model.Provider,
            score, status, latencyStr, price)
        b.WriteString(line + "\n")
    }
    return b.String()
}

```

```

func renderNarrow(rows []*ModelListRow, sym *SymbolSet, width
    int, opts *RenderOptions) string {
    var b strings.Builder
    b.WriteString(fmt.Sprintf(" %s Models\n", sym.Diamond))

```

```

        b.WriteString(fmt.Sprintf(" %s\n",
            strings.Repeat(sym.SepHorizontal, width-2)))

    for _, r := range rows {
        status := VerificationBadge(r.Model.VerificationStatus,
            sym)
        score := ScoreBadge(r.Model.OverallScore, sym)
        line := fmt.Sprintf(" %d. %-24s %s %s %s",
            r.Rank, truncate(r.Model.DisplayName, 24),
            r.Model.Provider, score, status)
        b.WriteString(line + "\n")
    }
    return b.String()
}

func renderCompact(rows []*ModelListRow, sym *SymbolSet, width
    int, opts *RenderOptions) string {
    var b strings.Builder
    for _, r := range rows {
        status := "OK"
        if !r.Model.Verified {
            status = "?"
        }
        if r.Model.VerificationStatus == "failed" {
            status = "FAIL"
        }
        if r.Model.VerificationStatus == "rate_limited" {
            status = "CD"
        }
        line := fmt.Sprintf(" %d. %s (%s) %.1f [%s]",
            r.Rank, r.Model.DisplayName, r.Model.Provider,
            r.Model.OverallScore, status)
        b.WriteString(line + "\n")
    }
    return b.String()
}

func renderJSON(rows []*ModelListRow) string {
    type jsonRow struct {
        ID      string `json:"id"`
        Name    string `json:"name"`
        Provider string `json:"provider"`
        Score   float64 `json:"score"`
        Verified bool    `json:"verified"`
        Status  string `json:"status"`
        Latency string `json:"latency"`
        Price   string `json:"price"`
        Tier    int    `json:"tier"`
    }

```



```

    }
    out := make([]jsonRow, len(rows))
    for i, r := range rows {
        out[i] = jsonRow{
            ID:          r.Model.ID,
            Name:        r.Model.DisplayName,
            Provider:    r.Model.Provider,
            Score:       r.Model.OverallScore,
            Verified:    r.Model.Verified,
            Status:      r.Model.VerificationStatus,
            Latency:     formatLatency(r.Model.Latency),
            Price:       PriceBadge(r.Model.CostPerInputToken,
                r.Model.CostPerOutputToken, DefaultSymbols, 80),
            Tier:       r.Model.Tier,
        }
    }
    data, _ := json.MarshalIndent(out, "", " ")
    return string(data)
}

```

```

func renderYAML(rows []*ModelListRow) string {
    type yamlRow struct {
        ID          string `yaml:"id"`
        Name        string `yaml:"name"`
        Provider    string `yaml:"provider"`
        Score       float64 `yaml:"score"`
        Verified    bool   `yaml:"verified"`
    }
    out := make([]yamlRow, len(rows))
    for i, r := range rows {
        out[i] = yamlRow{
            ID:          r.Model.ID,
            Name:        r.Model.DisplayName,
            Provider:    r.Model.Provider,
            Score:       r.Model.OverallScore,
            Verified:    r.Model.Verified,
        }
    }
    data, _ := yaml.Marshal(out)
    return string(data)
}

```

```

func truncate(s string, maxlen int) string {
    if len(s) <= maxlen {
        return s
    }
    return s[:maxlen-3] + "..."
}

```

```

func formatLatency(d time.Duration) string {
    if d == 0 {
        return "unknown"
    }
    if d < time.Millisecond {
        return fmt.Sprintf("%dus", d.Microseconds())
    }
    if d < time.Second {
        return fmt.Sprintf("%dms", d.Milliseconds())
    }
    return fmt.Sprintf("%.1fs", d.Seconds())
}

```

Acceptance Criteria: 1. `go build ./internal/cli/ux/...` compiles 2. `RenderModelList()` dispatches to `renderWide` when `width >= 140` 3. `RenderModelList()` dispatches to `renderCompact` when `width < 80` 4. `renderJSON()` produces valid JSON with `id`, `name`, `provider`, `score`, `verified` fields 5. `truncate("hello world", 5)` returns "he..." 6. `formatLatency(234*time.Millisecond)` returns "234ms"

Dependencies: TASK 3.1.1, TASK 3.2.1, TASK 3.3.1 **Effort:** Large

TASK 3.5: Create `internal/cli/ux/detail.go`

TASK 3.5.1: Implement Model Detail Rendering

File(s): `helix_code/internal/cli/ux/detail.go` **Line(s):** CREATE new file **Action:** CREATE

```

package ux

import (
    "encoding/json"
    "fmt"
    "strings"
    "time"

    "dev.helix.code/internal/verifier"
    "github.com/fatih/color"
    "gopkg.in/yaml.v3"
)

// DetailDisplayOptions controls detail rendering.
type DetailDisplayOptions struct {
    Format          string // "rich", "json", "yaml"
    NoColor         bool
    NoEmoji         bool
    TerminalWidth  int
}

```

```

}

// RenderModelDetail renders a full model detail view.
func RenderModelDetail(
    model *verifier.VerifiedModel,
    provider *verifier.ProviderStatus,
    verification *verifier.VerificationResult,
    limits *verifier.RateLimitStatus,
    cooldown *verifier.CooldownInfo,
    alternatives []*verifier.VerifiedModel,
    opts *DetailDisplayOptions,
) string {
    sym := NewSymbolSet(opts.NoEmoji)
    if opts.NoColor {
        color.NoColor = true
    }

    switch opts.Format {
    case "json":
        return renderDetailJSON(model, provider, verification,
            limits, cooldown, alternatives)
    case "yaml":
        return renderDetailYAML(model, provider, verification,
            limits, cooldown, alternatives)
    default:
        if opts.TerminalWidth >= 100 {
            return renderDetailWide(model, provider,
                verification, limits, cooldown, alternatives, sym,
                opts.TerminalWidth)
        } else if opts.TerminalWidth >= 60 {
            return renderDetailCompact(model, provider,
                verification, limits, cooldown, alternatives, sym,
                opts.TerminalWidth)
        }
        return renderDetailNarrow(model, provider, verification,
            limits, cooldown, alternatives, sym, opts.TerminalWidth)
    }
}

func renderDetailWide(m *verifier.VerifiedModel, p
    *verifier.ProviderStatus, v *verifier.VerificationResult,
    limits *verifier.RateLimitStatus, cd *verifier.CooldownInfo,
    alts []*verifier.VerifiedModel,
    sym *SymbolSet, width int) string {
    var b strings.Builder
    b.WriteString(fmt.Sprintf(" %s HelixCode – Model Details\n",
        sym.Diamond))

```

```

b.WriteString(fmt.Sprintf(" %s\n",
    strings.Repeat(sym.SepHorizontal, width-2)))

// Header
healthBadge := ""
if p != nil {
    healthBadge = ProviderHealthBadge(p.Status, sym)
}
b.WriteString(fmt.Sprintf(" %-50s %s %s\n", m.DisplayName,
    m.Provider, healthBadge))
b.WriteString(fmt.Sprintf(" %s\n", strings.Repeat("=",
    width-4)))

// Score panel
b.WriteString(fmt.Sprintf(" Overall Score %s\n",
    ScoreBadge(m.OverallScore, sym)))
if v != nil {
    b.WriteString(fmt.Sprintf(" Code Capability %s\n",
        ScoreBadge(v.CodeCapabilityScore, sym)))
    b.WriteString(fmt.Sprintf(" Responsiveness %s\n",
        ScoreBadge(v.ResponsivenessScore, sym)))
    b.WriteString(fmt.Sprintf(" Reliability %s\n",
        ScoreBadge(v.ReliabilityScore, sym)))
}
b.WriteString("\n")

// Context

    b.WriteString(fmt.Sprintf(" Context Window: %d tokens
    Max Output: %d tokens\n", m.ContextSize,
    m.MaxOutputTokens))
b.WriteString("\n")

// Pricing
inPrice := m.CostPerInputToken * 1000
outPrice := m.CostPerOutputToken * 1000
b.WriteString(fmt.Sprintf(" Pricing (per 1K): Input
    %s%.2f Output %s%.2f\n", sym.Dollar, inPrice,
    sym.Dollar, outPrice))
b.WriteString("\n")

// Capabilities
b.WriteString(" Capabilities:\n")
b.WriteString(CapabilityDetails(m, v, sym, width))

// Verification dimensions
if v != nil {
    b.WriteString(" Verification Dimensions:\n")

```

```

checks := []struct{ name string; pass bool }{
    {"Model Exists", v.ModelExists != nil &&
*v.ModelExists},
    {"Responsive", v.Responsive != nil && *v.Responsive},
    {"Not Overloaded", v.Overloaded != nil && !
*v.Overloaded},
    {"Supports Tools", v.SupportsToolUse},
    {"Code Generation", v.SupportsCodeGeneration},
    {"Code Debugging", v.CodeDebugging},
    {"Code Optimization", v.CodeOptimization},
    {"Test Generation", v.TestGeneration},
    {"Documentation Gen.", v.DocumentationGeneration},
    {"Architecture", v.ArchitectureDesign},
    {"Security Assessment", v.SecurityAssessment},
    {"Pattern Recognition", v.PatternRecognition},
}
for _, c := range checks {
    status := CFailed.Sprintf("%s", sym.Failed)
    if c.pass {
        status = CVerified.Sprintf("%s", sym.Verified)
    }
    b.WriteString(fmt.Sprintf("    %s %s\n", status,
c.name))
}
b.WriteString("\n")
}

// Rate limits
if limits != nil && len(limits.Limits) > 0 {
    b.WriteString("  Rate Limits:\n")
    for _, l := range limits.Limits {
        b.WriteString(fmt.Sprintf("    %s: limit=%d used=%d
remaining=%d reset=%s\n",
l.Type, l.Limit, l.Used, l.Remaining,
l.ResetTime.Format("15:04:05")))
    }
    b.WriteString("\n")
}

// Alternatives
if len(alts) > 0 {
    b.WriteString("  Alternative Models:\n")
    for i, alt := range alts {
        if i >= 5 {
            break
        }
        price := (alt.CostPerInputToken +
alt.CostPerOutputToken) / 2.0 * 1000
    }
}

```

```

        b.WriteString(fmt.Sprintf("    %d. %s (%s) – Score:
%.1f – Price: $%.2f/1K\n",
            i+1, alt.DisplayName, alt.Provider,
            alt.OverallScore, price))
    }
}

return b.String()
}

func renderDetailCompact(m *verifier.VerifiedModel, p
    *verifier.ProviderStatus, v *verifier.VerificationResult,
    limits *verifier.RateLimitStatus, cd *verifier.CooldownInfo,
    alts []*verifier.VerifiedModel,
    sym *SymbolSet, width int) string {
    var b strings.Builder
    b.WriteString(fmt.Sprintf(" %s HelixCode – Model Details\n",
        sym.Diamond))
    b.WriteString(fmt.Sprintf(" %s\n",
        strings.Repeat(sym.SepHorizontal, width-2)))
    b.WriteString(fmt.Sprintf("  %-30s %s %s\n", m.DisplayName,
        m.Provider, ProviderHealthBadge(p.Status, sym)))
    b.WriteString(fmt.Sprintf("  Score: %s Tier: %s\n",
        ScoreBadge(m.OverallScore, sym), TierBadge(m.Tier)))
    b.WriteString(fmt.Sprintf("  Context: %dK MaxOut: %d\n",
        m.ContextSize/1000, m.MaxOutputTokens))
    b.WriteString(fmt.Sprintf("  Price: In $%.2f/1K Out $%.2f/
1K\n", sym.Dollar, m.CostPerInputToken*1000, sym.Dollar,
        m.CostPerOutputToken*1000))
    b.WriteString(fmt.Sprintf("  Capabilities: %s\n",
        CapabilityStrip(m, sym, width)))
    if len(alts) > 0 {
        b.WriteString(fmt.Sprintf("  Fallbacks: %d alternatives
available\n", len(alts)))
    }
    return b.String()
}

func renderDetailNarrow(m *verifier.VerifiedModel, p
    *verifier.ProviderStatus, v *verifier.VerificationResult,
    limits *verifier.RateLimitStatus, cd *verifier.CooldownInfo,
    alts []*verifier.VerifiedModel,
    sym *SymbolSet, width int) string {
    var b strings.Builder
    b.WriteString(fmt.Sprintf("Model: %s\n", m.DisplayName))
    b.WriteString(fmt.Sprintf("Provider: %s [%s]\n", m.Provider,
        p.Status))
    b.WriteString(fmt.Sprintf("Score: %.1f\n", m.OverallScore))

```

```

b.WriteString(fmt.Sprintf("Context: %dK / MaxOut: %d\n",
    m.ContextSize/1000, m.MaxOutputTokens))
b.WriteString(fmt.Sprintf("Price: In $%.2f/1K Out $%.2f/
    1K\n", m.CostPerInputToken*1000,
    m.CostPerOutputToken*1000))
b.WriteString(fmt.Sprintf("Status: %s\n",
    m.VerificationStatus))
if len(alts) > 0 {
    b.WriteString(fmt.Sprintf("Fallbacks: %d\n", len(alts)))
}
return b.String()
}

func renderDetailJSON(m *verifier.VerifiedModel, p
    *verifier.ProviderStatus, v *verifier.VerificationResult,
    limits *verifier.RateLimitStatus, cd *verifier.CooldownInfo,
    alts []*verifier.VerifiedModel) string {
data, _ := json.MarshalIndent(struct {
    Model          *verifier.VerifiedModel    `json:"model"`
    Provider       *verifier.ProviderStatus
    `json:"provider,omitempty"`
    Verification   *verifier.VerificationResult
    `json:"verification,omitempty"`
    Limits        *verifier.RateLimitStatus
    `json:"limits,omitempty"`
    Alternatives  []*verifier.VerifiedModel
    `json:"alternatives,omitempty"`
}{m, p, v, limits, alts}, "", " ")
return string(data)
}

func renderDetailYAML(m *verifier.VerifiedModel, p
    *verifier.ProviderStatus, v *verifier.VerificationResult,
    limits *verifier.RateLimitStatus, cd *verifier.CooldownInfo,
    alts []*verifier.VerifiedModel) string {
data, _ := yaml.Marshal(struct {
    Model          *verifier.VerifiedModel    `yaml:"model"`
    Provider       *verifier.ProviderStatus
    `yaml:"provider,omitempty"`
    Verification   *verifier.VerificationResult
    `yaml:"verification,omitempty"`
}{m, p, v})
return string(data)
}

```

Acceptance Criteria: 1. go build ./internal/cli/ux/... compiles 2. renderDetailWide() includes score panel, context, pricing, capabilities, verification, rate limits, alternatives 3. renderDetailCompact() fits in 60-99 columns 4.

renderDetailNarrow() fits in <60 columns 5. renderDetailJSON() produces valid JSON 6. renderDetailYAML() produces valid YAML

Dependencies: TASK 3.1.1, TASK 3.2.1, TASK 3.3.1 **Effort:** Large

TASK 3.6: Create internal/cli/tui/model_selector.go

TASK 3.6.1: Implement tview-Based Interactive Model Selector

File(s): helix_code/internal/cli/tui/model_selector.go **Line(s):** CREATE new file **Action:** CREATE

```
package tui

import (
    "context"
    "fmt"
    "strings"
    "time"

    "dev.helix.code/internal/cli/ux"
    "dev.helix.code/internal/verifier"
    "github.com/gdamore/tcell/v2"
    "github.com/rivo/tview"
)

// ModelSelectorApp is the interactive model selection TUI.
type ModelSelectorApp struct {
    app          *tview.Application
    modelList    *tview.List
    previewPane  *tview.TextView
    statusBar    *tview.TextView
    filterInput  *tview.InputField

    models        []*ux.ModelListRow
    filtered      []*ux.ModelListRow
    selectedIdx   int
    sym           *ux.SymbolSet
    refreshTicker *time.Ticker
    cancelFunc     context.CancelFunc
    onSelect      func(modelID string)
}

// NewModelSelectorApp creates a TUI model selector.
func NewModelSelectorApp(models []*ux.ModelListRow, sym
    *ux.SymbolSet) *ModelSelectorApp {
    m := &ModelSelectorApp{
        app:          tview.NewApplication(),
```



```

        models:    models,
        filtered:  models,
        sym:       sym,
    }
    m.buildUI()
    return m
}

func (m *ModelSelectorApp) buildUI() {
    // Model list (left pane)
    m.modelList = tview.NewList()
    m.modelList.SetBorder(true).SetTitle(" Model List ")
    m.modelList.SetMainTextColor(tview.ColorWhite)
    m.modelList.SetSecondaryTextColor(tview.ColorDarkGray)
    m.modelList.SetSelectedBackgroundColor(tview.ColorDarkCyan)
    m.populateModelList()

    m.modelList.SetSelectedFunc(func(idx int, mainText string,
        secondaryText string, shortcut rune) {
        if idx >= 0 && idx < len(m.filtered) {
            m.onSelect(m.filtered[idx].Model.ID)
            m.app.Stop()
        }
    })

    m.modelList.SetChangedFunc(func(idx int, mainText string,
        secondaryText string, shortcut rune) {
        if idx >= 0 && idx < len(m.filtered) {
            m.updatePreview(m.filtered[idx])
        }
    })

    // Preview pane (right pane)
    m.previewPane = tview.NewTextView()
    m.previewPane.SetBorder(true).SetTitle(" Preview ")
    m.previewPane.SetDynamicColors(true)
    m.previewPane.SetScrollable(true)

    // Status bar (bottom)
    m.statusBar = tview.NewTextView()
    m.statusBar.SetDynamicColors(true)
    m.statusBar.SetTextAlign(tview.AlignLeft)

    // Filter input
    m.filterInput = tview.NewInputField().SetLabel("Filter: ")
    m.filterInput.SetFieldBackgroundColor(tview.ColorBlack)
    m.filterInput.SetDoneFunc(func(key tcell.Key) {
        m.applyFilter(m.filterInput.GetText())
    })
}

```

```

// Layout: left list | right preview, stacked with filter +
// status bar
mainFlex := tview.NewFlex().
    AddItem(m.modelList, 0, 1, true).
    AddItem(m.previewPane, 0, 2, false)

fullLayout := tview.NewFlex().SetDirection(tview.FlexRow).
    AddItem(mainFlex, 0, 1, true).
    AddItem(m.filterInput, 1, 0, false).
    AddItem(m.statusBar, 1, 0, false)

m.app.SetRoot(fullLayout, true)

// Key bindings
m.app.SetInputCapture(func(event *tcell.EventKey)
    *tcell.EventKey {
        switch event.Rune() {
        case 'q', 'Q':
            m.app.Stop()
            return nil
        case 'r', 'R':
            m.triggerRefresh()
            return nil
        case 'f', 'F':
            m.app.SetFocus(m.filterInput)
            return nil
        }
        return event
    })

if len(m.filtered) > 0 {
    m.updatePreview(m.filtered[0])
}
m.updateStatusBar()
}

func (m *ModelSelectorApp) populateModelList() {
    m.modelList.Clear()
    for i, r := range m.filtered {
        tierPrefix := " "
        if r.Model.Tier == 1 {
            tierPrefix = "* "
        }
        mainText := fmt.Sprintf("%s%s", tierPrefix,
            r.Model.DisplayName)
        statusBadge :=
            ux.VerificationBadge(r.Model.VerificationStatus, m.sym)
    }
}

```

```

        scoreStr := fmt.Sprintf("%.1f", r.Model.OverallScore)
        priceStr := ux.PriceBadge(r.Model.CostPerInputToken,
            r.Model.CostPerOutputToken, m.sym, 80)
        secondaryText := fmt.Sprintf("  %s %s %s %s %s",
            statusBadge, scoreStr, priceStr, r.Model.Provider,
            ux.CapabilityStripCompact(r.Model, m.sym))
        m.modelList.AddItem(mainText, secondaryText, rune('0'+
            ((i+1)%10)), nil)
    }
}

func (m *ModelSelectorApp) updatePreview(r *ux.ModelListRow) {
    detail := ux.RenderModelDetail(r.Model, r.Provider,
        r.Verification, r.Limits, r.Cooldown, nil,
        &ux.DetailDisplayOptions{Format: "rich", TerminalWidth:
            80})
    m.previewPane.SetText(detail)
}

func (m *ModelSelectorApp) updateStatusBar() {
    counts := countStatuses(m.filtered)
    text := fmt.Sprintf(
        " [green]* %d healthy[-]  [yellow]* %d degraded[-]
        [red]* %d cooldown[-]  [gray]* %d offline[-]  |  [blue]
        [f]ilter [r]efresh [q]uit[-]",
        counts.Healthy, counts.Degraded, counts.Cooldown,
        counts.Offline)
    m.statusBar.SetText(text)
}

func (m *ModelSelectorApp) applyFilter(query string) {
    query = strings.ToLower(strings.TrimSpace(query))
    if query == "" {
        m.filtered = m.models
    } else {
        m.filtered = []*ux.ModelListRow{}
        for _, r := range m.models {
            if
                strings.Contains(strings.ToLower(r.Model.DisplayName),
                    query) ||

                strings.Contains(strings.ToLower(r.Model.Provider),
                    query) ||

                strings.Contains(strings.ToLower(r.Model.ID),
                    query) {
                m.filtered = append(m.filtered, r)
            }
        }
    }
}

```

```

    }
    m.populateModelList()
    if len(m.filtered) > 0 {
        m.updatePreview(m.filtered[0])
    }
    m.updateStatusBar()
}

func (m *ModelSelectorApp) triggerRefresh() {
    // Signal to background goroutine to refresh data
}

func (m *ModelSelectorApp) Run() error {
    return m.app.Run()
}

func (m *ModelSelectorApp) GetSelectedModel() string {
    if m.selectedIdx >= 0 && m.selectedIdx < len(m.filtered) {
        return m.filtered[m.selectedIdx].Model.ID
    }
    return ""
}

func (m *ModelSelectorApp) SetOnSelect(fn func(modelID string)) {
    m.onSelect = fn
}

type statusCounts struct {
    Healthy    int
    Degraded   int
    Cooldown   int
    Offline    int
}

func countStatuses(rows []*ux.ModelListRow) statusCounts {
    c := statusCounts{}
    for _, r := range rows {
        switch r.Model.VerificationStatus {
        case "verified", "passed":
            c.Healthy++
        case "pending":
            c.Degraded++
        case "rate_limited":
            c.Cooldown++
        case "failed", "offline":
            c.Offline++
        default:
            c.Degraded++
        }
    }
}

```

```

    }
}
return c
}

```

Acceptance Criteria: 1. `go build ./internal/cli/tui/...` compiles (requires `go get github.com/rivo/tview`) 2. `NewModelSelectorApp()` creates all `tview` widgets 3. `applyFilter()` filters by name, provider, and ID 4. `Run()` returns error if `tview` fails to initialize 5. `SetOnSelect()` callback is invoked when model is selected

Dependencies: TASK 3.1.1, TASK 3.2.1, TASK 3.3.1, TASK 3.4.1 **Effort:** Large

TASK 3.7: Modify `cmd/cli/main.go` — Add Enhanced CLI Flags

TASK 3.7.1: Add All New CLI Flags

File(s): `helix_code/cmd/cli/main.go` **Line(s):** After existing `flag.StringVar(&c.prompt, ...)` declarations **Action:** MODIFY

```

// Existing flags ...

// NEW: Model listing and filtering flags
var (
    listModels      = flag.Bool("list-models", false, "List
    all available models with verifier data")
    modelInfo       = flag.String("model-info", "", "Show
    detailed info for a specific model ID")
    providerFilter  = flag.String("provider", "", "Filter
    models by provider name")
    verifiedOnly    = flag.Bool("verified-only", false, "Show
    only verified models")
    maxPrice        = flag.Float64("max-price", 0, "Maximum
    price per 1K tokens (in USD)")
    minScore        = flag.Float64("min-score", 0, "Minimum
    verifier score (0-10)")
    capability      = flag.String("capability", "",
    "Filter by capability (comma-separated:
    code,vision,streaming,tools,reasoning)")
    sortBy          = flag.String("sort", "score", "Sort
    models by: score, price, name, latency, tier")
    groupBy         = flag.String("group-by", "none", "Group
    models by: provider, tier, none")
    format          = flag.String("format", "table", "Output
    format: table, json, yaml")
    interactive     = flag.Bool("models-interactive", false,
    "Interactive TUI model selector")
    refreshModels   = flag.Bool("refresh-models", false,
    "Force refresh model list from verifier")

```

```

        noColor      = flag.Bool("no-color", false, "Disable
        color output")
        noEmoji      = flag.Bool("no-emoji", false, "Disable
        emoji/special symbols (ASCII fallback)")
    )

```

Then in `handleListModel()`, integrate the new flags:

```

func (c *CLI) handleListModel(ctx context.Context) error {
    if *refreshModels && c.verifierAdapter != nil {
        _ = c.verifierAdapter.ForceRefresh(ctx)
    }

    // Determine symbol set
    sym := ux.NewSymbolSet(*noEmoji || isWindowsCMD())
    if *noColor {
        color.NoColor = true
    }

    // Fetch models
    var models []*verifier.VerifiedModel
    var err error
    if c.verifierAdapter != nil && c.verifierAdapter.IsEnabled()
    {
        models, err = c.verifierAdapter.GetVerifiedModels(ctx)
    } else {
        models = verifier.FallbackModels
    }

    // Apply filters
    models = c.filterModels(models, *providerFilter,
        *verifiedOnly, *maxPrice, *minScore, *capability)
    models = c.sortModels(models, *sortBy)

    // Build rows
    rows := make([]*ux.ModelListRow, len(models))
    for i, m := range models {
        rows[i] = &ux.ModelListRow{
            Model: m,
            Rank:  i + 1,
        }
    }

    // Render
    opts := &ux.RenderOptions{
        Format:      *format,
        NoColor:     *noColor,
        NoEmoji:     *noEmoji,
        ShowPrices:  true,
    }

```

```

        ShowLatency: true,
        GroupBy:     *groupBy,
        SortBy:      *sortBy,
    }

    width, _, _ := term.GetSize(int(os.Stdout.Fd()))
    if width <= 0 {
        width = 120
    }

    output := ux.RenderModelList(rows, sym, width, opts)
    fmt.Println(output)
    return nil
}

func (c *CLI) filterModels(models []*verifier.VerifiedModel,
    provider string, verifiedOnly bool, maxPrice, minScore
    float64, caps string) []*verifier.VerifiedModel {
    result := make([]*verifier.VerifiedModel, 0, len(models))
    for _, m := range models {
        if provider != "" && m.Provider != provider {
            continue
        }
        if verifiedOnly && !m.Verified {
            continue
        }
        if maxPrice > 0 &&
            (m.CostPerInputToken+m.CostPerOutputToken)/2.0*1000 >
            maxPrice {
            continue
        }
        if minScore > 0 && m.OverallScore < minScore {
            continue
        }
        if caps != "" {
            required := strings.Split(caps, ",")
            if !hasCapabilities(m, required) {
                continue
            }
        }
        result = append(result, m)
    }
    return result
}

func hasCapabilities(m *verifier.VerifiedModel, required
    []string) bool {
    for _, r := range required {

```

```

switch strings.ToLower(strings.TrimSpace(r)) {
case "code":
    if !m.SupportsCode {
        return false
    }
case "vision":
    if !m.SupportsVision {
        return false
    }
case "streaming":
    if !m.SupportsStreaming {
        return false
    }
case "tools":
    if !m.SupportsTools && !m.SupportsFunctions {
        return false
    }
case "reasoning":
    if !m.SupportsReasoning {
        return false
    }
case "embeddings":
    if !m.SupportsEmbeddings {
        return false
    }
case "audio":
    if !m.SupportsAudio {
        return false
    }
case "video":
    if !m.SupportsVideo {
        return false
    }
}
}
return true
}

func (c *CLI) sortModels(models []*verifier.VerifiedModel,
    sortBy string) []*verifier.VerifiedModel {
    result := make([]*verifier.VerifiedModel, len(models))
    copy(result, models)
    switch strings.ToLower(sortBy) {
case "score":
    sort.Slice(result, func(i, j int) bool { return
        result[i].OverallScore > result[j].OverallScore })
case "price":
    sort.Slice(result, func(i, j int) bool {

```



```

        pi := (result[i].CostPerInputToken +
result[i].CostPerOutputToken) / 2.0
        pj := (result[j].CostPerInputToken +
result[j].CostPerOutputToken) / 2.0
        return pi < pj
    })
case "name":
    sort.Slice(result, func(i, j int) bool { return
result[i].DisplayName < result[j].DisplayName })
case "latency":
    sort.Slice(result, func(i, j int) bool { return
result[i].Latency < result[j].Latency })
case "tier":
    sort.Slice(result, func(i, j int) bool { return
result[i].Tier < result[j].Tier })
}
return result
}

```

Acceptance Criteria: 1. `go build ./cmd/cli/...` compiles 2. `./cli --help` shows all new flags: `--list-models`, `--model-info`, `--provider`, `--verified-only`, `--max-price`, `--min-score`, `--capability`, `--sort`, `--group-by`, `--format`, `--models-interactive`, `--refresh-models`, `--no-color`, `--no-emoji` 3. `--format json` produces valid JSON with `id`, `name`, `provider`, `score`, `verified` 4. `--provider openai` filters to only OpenAI models 5. `--min-score 8.0` filters out models with `score < 8.0` 6. `--capability code,vision` filters to models supporting both

Dependencies: TASK 3.4.1 **Effort:** Large

TASK 3.8: Implement Real-Time Status Bar and Notifications

TASK 3.8.1: Create Status Bar Component

File(s): `helix_code/internal/cli/ux/status_bar.go` **Line(s):** CREATE new file
Action: CREATE

```

package ux

import (
    "fmt"
    "time"
)

// StatusBar renders the persistent bottom status line.
type StatusBar struct {
    sym          *SymbolSet
    totalModels  int
    activeModels int
    cooldownCount int
}

```

```

    degradedCount int
    offlineCount  int
    lastRefresh   time.Time
    isRefreshing  bool
    width         int
}

// Render returns the status bar string based on terminal width.
func (sb *StatusBar) Render() string {
    if sb.width >= 100 {
        refreshStr := fmt.Sprintf("%s last refresh: %s",
            sb.sym.Verified, sb.lastRefresh.Format("15:04:05"))
        if sb.isRefreshing {
            refreshStr = fmt.Sprintf("%s refreshing...",
                sb.sym.Pending)
        }
        return fmt.Sprintf(" %s %d models active  %s %s %d
cooldown %s %s %d degraded %s %s",
            sb.sym.Healthy, sb.activeModels,
            sb.sym.SepVertical,
            sb.sym.CoolDown, sb.cooldownCount,
            sb.sym.SepVertical,
            sb.sym.Degraded, sb.degradedCount,
            sb.sym.SepVertical,
            refreshStr)
    }
    refreshStr := sb.lastRefresh.Format("15:04")
    if sb.isRefreshing {
        refreshStr = "... "
    }
    return fmt.Sprintf(" %d OK | %d CD | %d ~ | %s",
        sb.activeModels, sb.cooldownCount, sb.degradedCount,
        refreshStr)
}

```

TASK 3.8.2: Create Alert/Notification System

File(s): helix_code/internal/cli/ux/alerts.go **Line(s):** CREATE new file **Action:** CREATE

```

package ux

import (
    "fmt"
    "strings"
    "time"
)

// AlertLevel defines the severity of an alert.

```

```

type AlertLevel int

const (
    AlertInfo AlertLevel = iota
    AlertWarning
    AlertError
    AlertSuccess
)

// Alert represents a notification to the user.
type Alert struct {
    Level           AlertLevel
    Title           string
    Message         string
    ModelID         string
    Provider        string
    SuggestedAlternative string
    Timestamp       time.Time
}

// Render formats the alert as a bordered message.
func (a *Alert) Render(sym *SymbolSet, width int) string {
    var b strings.Builder
    icon := ""
    titleColor := ""
    switch a.Level {
    case AlertInfo:
        icon = sym.Bullet
        titleColor = "[blue]"
    case AlertWarning:
        icon = sym.Degraded
        titleColor = "[yellow]"
    case AlertError:
        icon = sym.Failed
        titleColor = "[red]"
    case AlertSuccess:
        icon = sym.Verified
        titleColor = "[green]"
    }

    b.WriteString(fmt.Sprintf("%s\n",
        strings.Repeat(sym.SepHorizontal, width-1)))
    b.WriteString(fmt.Sprintf("  %s %s%s[-]\n", icon,
        titleColor, a.Title))
    b.WriteString(fmt.Sprintf("  %s\n", a.Message))
    if a.SuggestedAlternative != "" {
        b.WriteString(fmt.Sprintf("  %s Suggested alternative:
%s\n", sym.ArrowRight, a.SuggestedAlternative))
    }
}

```

```

    }
    b.WriteString(fmt.Sprintf("%s\n",
        strings.Repeat(sym.SepHorizontal, width-1)))
    return b.String()
}

```

TASK 3.8.3: Create Auto-Suggest Component

File(s): helix_code/internal/cli/ux/auto_suggest.go **Line(s):** CREATE new file **Action:** CREATE

```

package ux

import (
    "fmt"
    "sort"
    "strings"

    "dev.helix.code/internal/verifier"
)

// SuggestAlternatives returns up to N alternative models for an
// unavailable one.
func SuggestAlternatives(
    unavailable *verifier.VerifiedModel,
    allModels []*verifier.VerifiedModel,
    sym *SymbolSet,
    count int,
) string {
    var b strings.Builder
    b.WriteString(fmt.Sprintf("\n  %s SELECTED MODEL
        UNAVAILABLE\n", sym.Degraded))
    b.WriteString(fmt.Sprintf("  \"%s\" is currently %s.\n\n",
        unavailable.DisplayName, unavailable.VerificationStatus))
    b.WriteString("  Auto-switch to best available alternative?
        \n")

    // Filter and score alternatives
    candidates := make([]*verifier.VerifiedModel, 0,
        len(allModels))
    for _, m := range allModels {
        if m.ID == unavailable.ID {
            continue
        }
        if m.VerificationStatus == "failed" ||
            m.VerificationStatus == "rate_limited" {
            continue
        }
        candidates = append(candidates, m)
    }
}

```

```

    }

    sort.Slice(candidates, func(i, j int) bool {
        return candidates[i].OverallScore >
            candidates[j].OverallScore
    })

    for i, alt := range candidates {
        if i >= count {
            break
        }
        price := (alt.CostPerInputToken +
            alt.CostPerOutputToken) / 2.0 * 1000
        rec := ""
        if i == 0 {
            rec = " [RECOMMENDED]"
        }

        b.WriteString(fmt.Sprintf(" [%d] %s (%s) – Score: %.1f –
            $%.2f/1K%s\n",
                i+1, alt.DisplayName, alt.Provider,
                alt.OverallScore, price, rec))
    }

    b.WriteString(fmt.Sprintf(" [%d] Cancel and exit\n",
        len(candidates)+1))
    b.WriteString("\n Select number or press Enter for default
        [1]:\n")
    return b.String()
}

```

Acceptance Criteria: 1. go build ./internal/cli/ux/... compiles 2. StatusBar.Render() produces wide format when width >= 100, narrow when < 100 3. Alert.Render() produces bordered message with correct color codes 4. SuggestAlternatives() returns ranked alternatives excluding unavailable model 5. First alternative is marked “[RECOMMENDED]”

Dependencies: TASK 3.1.1, TASK 3.2.1 **Effort:** Medium

PHASE 3 ROLLBACK PLAN

```

cd HelixCode
git checkout -- cmd/cli/main.go
git rm --cached internal/cli/ux/*.go internal/cli/tui/*.go
rm -f internal/cli/ux/symbols.go internal/cli/ux/badges.go
    internal/cli/ux/capabilities.go \
    internal/cli/ux/render.go internal/cli/ux/detail.go
    internal/cli/ux/status_bar.go \

```

```
internal/cli/ux/alerts.go internal/cli/ux/auto_suggest.go \
internal/cli/tui/model_selector.go
go mod tidy
make build
make test-unit
```

PHASE 3 VERIFICATION CHECKLIST

- ☐ go build ./... compiles with zero errors
- ☐ ./cli --help shows --list-models, --model-info, --provider, --verified-only, --max-price, --min-score, --capability, --sort, --group-by, --format, --models-interactive, --refresh-models, --no-color, --no-emoji
- ☐ --list-models outputs table with Rank, Model, Provider, Score, Status columns
- ☐ --list-models --format json produces valid JSON with id, name, provider, score, verified
- ☐ --list-models --provider openai filters to OpenAI models only
- ☐ --list-models --min-score 8.0 shows only models with score >= 8.0
- ☐ --model-info gpt-4o shows full detail with capabilities, pricing, verification dimensions
- ☐ NewSymbolSet(true) returns ASCII-only symbols (no Unicode)
- ☐ VerificationBadge() returns correct color for each status
- ☐ ScoreBadge(9.5) uses green, ScoreBadge(2.0) uses red
- ☐ StatusBar.Render() fits in narrow terminals (<60 columns)
- ☐ SuggestAlternatives() returns at least 1 alternative for unavailable model

PHASE 4: ADVANCED FEATURES — MCPs, LSPs, ACPs, Embeddings, RAGs, Skills, Plugins

Phase Goal: Flawlessly incorporate all available capabilities from all supported providers, ensuring each capability respects verifier enable/disable state and has proper fallback behavior.

Phase Entry Criteria: Phase 3 verification checklist is complete. **Phase Exit Criteria:** 1. MCP transport works with verifier-selected models 2. LSP features query model capabilities from verifier 3. ACP agent discovery references verifier model data 4. Embedding model selection uses

verifier scores 5. RAG pipeline queries verified models 6. Skills system maps to model capability requirements 7. Plugins validate against verifier before activation

TASK 4.1: MCP (Model Context Protocol) Integration

TASK 4.1.1: Modify MCP Server to Use Verifier-Selected Models

File(s): helix_code/internal/mcp/server.go **Line(s):** Search for func (s *Server) handleListTools() or func (s *Server) HandleRequest()
Action: MODIFY

Add verifier adapter field to MCPServer struct:

```
type Server struct {
    // ... existing fields ...
    verifierAdapter *verifier.Adapter // NEW - LLMsVerifier bridge
}
```

Add method to get MCP-capable models from verifier:

```
// GetMCPCapableModels returns models that support MCP/tool_use.
func (s *Server) GetMCPCapableModels(ctx context.Context)
    ([]string, error) {
    if s.verifierAdapter == nil || !
        s.verifierAdapter.IsEnabled() {
        // Fallback: return hardcoded MCP-capable models
        return []string{"gpt-4o", "claude-3-5-sonnet",
            "gemini-2.5-pro"}, nil
    }
    models, err := s.verifierAdapter.GetVerifiedModels(ctx)
    if err != nil {
        return nil, err
    }
    result := []string{}
    for _, m := range models {
        if m.SupportsTools || m.SupportsFunctions {
            result = append(result, m.ID)
        }
    }
    return result, nil
}
```

Acceptance Criteria: 1. go build ./internal/mcp/... compiles 2. GetMCPCapableModels() returns only models with SupportsTools=true or SupportsFunctions=true 3. When verifier is disabled, falls back to 3 hardcoded MCP-capable models 4. When verifier is enabled, ALL returned models are from verifier DB

Dependencies: TASK 2.1.1 **Effort:** Medium

TASK 4.2: LSP (Language Server Protocol) Integration

TASK 4.2.1: Connect LSP Features to Model Capabilities

File(s): helix_code/internal/lsp/completion.go **Line(s):** Before completion request dispatch **Action:** MODIFY

```
// selectLSPModel chooses the best model for LSP completion based
// on verifier data.
func (s *LSPService) selectLSPModel(ctx context.Context)
(string, error) {
    if s.verifierAdapter != nil && s.verifierAdapter.IsEnabled()
    {
        models, err := s.verifierAdapter.GetVerifiedModels(ctx)
        if err == nil {
            // Prefer models with high code capability score
            for _, m := range models {
                if m.SupportsCode && m.Verified &&
                m.OverallScore >=
                s.verifierAdapter.GetMinAcceptableScore() {
                    return m.ID, nil
                }
            }
        }
        // Fallback: use config default
        return s.config.DefaultModel, nil
    }
}
```

Acceptance Criteria: 1. go build ./internal/lsp/... compiles 2. selectLSPModel() prefers models with SupportsCode=true when verifier is enabled 3. Falls back to config.DefaultModel when verifier is disabled or no suitable model

Dependencies: TASK 2.1.1 **Effort:** Small

TASK 4.3: ACP (Agent Communication Protocol) Integration

TASK 4.3.1: Reference Verifier in Agent Discovery

File(s): helix_code/internal/acp/discovery.go **Line(s):** Inside DiscoverAgents() function **Action:** MODIFY

```
func (d *DiscoveryService) DiscoverAgents(ctx context.Context)
([]*AgentInfo, error) {
    agents := []*AgentInfo{}

    // NEW: Include verifier-aware model agents
    if d.verifierAdapter != nil && d.verifierAdapter.IsEnabled()
    {

```



```

models, err := d.verifierAdapter.GetVerifiedModels(ctx)
if err == nil {
    for _, m := range models {
        if m.Verified && m.OverallScore >=
d.verifierAdapter.GetMinAcceptableScore() {
            agents = append(agents, &AgentInfo{
                ID:          "model:" + m.ID,
                Name:         m.DisplayName,
                Type:          "llm",
                Provider:     m.Provider,
                Capabilities: m.Capabilities,
                Score:        m.OverallScore,
                Source:       "verifier",
            })
        }
    }
}

// ... existing discovery logic ...
return agents, nil
}

```

Acceptance Criteria: 1. go build ./internal/acp/... compiles 2.
DiscoverAgents() includes agents with Source: "verifier" when verifier is enabled
3. Only verified models with score >= min_acceptable are included

Dependencies: TASK 2.1.1 **Effort:** Small

TASK 4.4: Embeddings Integration

TASK 4.4.1: Use Verifier to Select Optimal Embedding Models

File(s): helix_code/internal/embeddings/selector.go (or equivalent) **Line(s):**
Inside embedding model selection function **Action:** MODIFY

```

// SelectEmbeddingModel returns the best embedding-capable model
// from verifier.
func (s *EmbeddingService) SelectEmbeddingModel(ctx
context.Context) (string, error) {
    if s.verifierAdapter != nil && s.verifierAdapter.IsEnabled()
    {
        models, err := s.verifierAdapter.GetVerifiedModels(ctx)
        if err == nil {
            // Find highest-scored embedding model
            var best *verifier.VerifiedModel
            for _, m := range models {
                if m.SupportsEmbeddings && m.Verified {

```

```

        if best == nil || m.OverallScore >
best.OverallScore {
            best = m
        }
    }
    if best != nil {
        return best.ID, nil
    }
}
// Fallback: config default embedding model
return s.config.DefaultEmbeddingModel, nil
}

```

Acceptance Criteria: 1. go build ./internal/embeddings/... compiles 2. SelectEmbeddingModel() returns highest-scored model with SupportsEmbeddings=true 3. Falls back to config default when verifier is disabled

Dependencies: TASK 2.1.1 **Effort:** Small

TASK 4.5: RAG Integration

TASK 4.5.1: Connect RAG Pipeline to Verified Models

File(s): helix_code/internal/rag/pipeline.go **Line(s):** Before LLM query dispatch in pipeline **Action:** MODIFY

```

// selectRAGModel picks a model for RAG queries using verifier
data.
func (p *Pipeline) selectRAGModel(ctx context.Context) (string,
error) {
    if p.verifierAdapter != nil && p.verifierAdapter.IsEnabled()
    {
        models, err := p.verifierAdapter.GetVerifiedModels(ctx)
        if err == nil {
            // For RAG, prefer models with large context window +
reasoning
            var best *verifier.VerifiedModel
            for _, m := range models {
                if m.Verified && m.ContextSize >= 32000 {
                    score := m.OverallScore
                    if m.SupportsReasoning {
                        score += 0.5 // reasoning bonus for RAG
                    }
                    if best == nil || score > best.OverallScore+
(mapBoolFloat(best.SupportsReasoning)*0.5) {
                        best = m
                    }
                }
            }
        }
    }
    if best == nil {
        return s.config.DefaultEmbeddingModel, nil
    }
    return best.ID, nil
}

```

```

        }
    }
    if best != nil {
        return best.ID, nil
    }
}
return p.config.DefaultRAGModel, nil
}

func mapBoolFloat(b bool) float64 {
    if b {
        return 1.0
    }
    return 0.0
}

```

Acceptance Criteria: 1. go build ./internal/rag/... compiles 2. selectRAGModel() gives 0.5 bonus to models with SupportsReasoning=true 3. Only models with ContextSize >= 32000 are considered for RAG

Dependencies: TASK 2.1.1 **Effort:** Small

TASK 4.6: Skills Integration

TASK 4.6.1: Map Skills to Model Capability Requirements

File(s): helix_code/internal/skills/manager.go **Line(s):** Inside skill execution or validation function **Action:** MODIFY

```

// validateSkillRequirements checks if the selected model
// supports a skill's requirements.
func (m *SkillsManager) validateSkillRequirements(ctx
    context.Context, skillID string, modelID string) error {
    skill := m.registry.Get(skillID)
    if skill == nil {
        return fmt.Errorf("skill %s not found", skillID)
    }

    if m.verifierAdapter != nil && m.verifierAdapter.IsEnabled()
    {
        model, err := m.verifierAdapter.GetVerifiedModels(ctx)
        if err == nil {
            // Find the specific model
            for _, mod := range model {
                if mod.ID == modelID {
                    for _, req := range
                        skill.RequiredCapabilities {

```

```

        if !hasCapability(mod, req) {
            return fmt.Errorf("model %s lacks
required capability '%s' for skill '%s'",
                                modelID, req, skillID)
        }
    }
    return nil // all requirements met
}
}
}

// Fallback: skip validation if verifier is disabled
return nil
}

func hasCapability(m *verifier.VerifiedModel, cap string) bool {
    switch cap {
    case "code": return m.SupportsCode
    case "vision": return m.SupportsVision
    case "streaming": return m.SupportsStreaming
    case "tools": return m.SupportsTools || m.SupportsFunctions
    case "reasoning": return m.SupportsReasoning
    case "embeddings": return m.SupportsEmbeddings
    case "audio": return m.SupportsAudio
    case "video": return m.SupportsVideo
    default:
        for _, c := range m.Capabilities {
            if c == cap {
                return true
            }
        }
    }
    return false
}

```

Acceptance Criteria: 1. go build ./internal/skills/... compiles 2. validateSkillRequirements() returns error when model lacks required capability 3. hasCapability("code") returns true when SupportsCode=true 4. Falls back to nil error when verifier is disabled

Dependencies: TASK 2.1.1 **Effort:** Small

TASK 4.7: Plugins Integration

TASK 4.7.1: Verify Plugins Against Verifier Before Activation

File(s): helix_code/internal/plugins/manager.go **Line(s):** Inside plugin activation or validation **Action:** MODIFY

```
// validatePluginModelRequirements checks plugin model
// requirements against verifier.
func (m *PluginManager) validatePluginModelRequirements(ctx
    context.Context, plugin *Plugin) error {
    if m.verifierAdapter == nil || !
        m.verifierAdapter.IsEnabled() {
        return nil // skip when verifier disabled
    }

    models, err := m.verifierAdapter.GetVerifiedModels(ctx)
    if err != nil {
        return fmt.Errorf("cannot validate plugin: verifier
            unavailable: %w", err)
    }

    for _, req := range plugin.ModelRequirements {
        found := false
        for _, mod := range models {
            if mod.ID == req.ModelID || mod.Name == req.ModelID {
                if mod.Verified && mod.OverallScore >=
                    req.MinScore {
                    found = true
                    break
                }
            }
        }
        if !found {
            return fmt.Errorf("plugin '%s' requires model '%s'
                (score >= %.1f) which is not available",
                plugin.Name, req.ModelID, req.MinScore)
        }
    }
    return nil
}
```

Acceptance Criteria: 1. go build ./internal/plugins/... compiles 2. validatePluginModelRequirements() returns error when required model is unavailable 3. Returns nil when verifier is disabled (backward compatible)

Dependencies: TASK 2.1.1 **Effort:** Small

TASK 4.8: Token Usage Tracking Integration

TASK 4.8.1: Track Token Usage with Verifier Context

File(s): helix_code/internal/usage/tracker.go (or equivalent) **Line(s):** CREATE new file or modify existing **Action:** CREATE/MODIFY

```
package usage

import (
    "dev.helix.code/internal/verifier"
    "sync"
    "time"
)

// TokenUsageTracker tracks per-model token usage with verifier
// integration.
type TokenUsageTracker struct {
    mu      sync.RWMutex
    records map[string]*UsageRecord // key: model_id
    adapter *verifier.Adapter
}

type UsageRecord struct {
    ModelID      string `json:"model_id"`
    Provider     string `json:"provider"`
    InputTokens  int64  `json:"input_tokens"`
    OutputTokens int64  `json:"output_tokens"`
    CostUSD      float64 `json:"cost_usd"`
    RequestCount int64  `json:"request_count"`
    LastUsed     time.Time `json:"last_used"`
    ScoreAtUse   float64 `json:"score_at_use" // verifier
                score snapshot
}

// RecordUsage logs token usage and captures verifier score at
// time of use.
func (t *TokenUsageTracker) RecordUsage(modelID, provider
    string, inputTokens, outputTokens int64) {
    t.mu.Lock()
    defer t.mu.Unlock()

    var score float64
    if t.adapter != nil {
        if s, ok := t.adapter.GetModelScore(modelID); ok {
            score = s
        }
    }
}
```

```

    record := t.records[modelID]
    if record == nil {
        record = &UsageRecord{ModelID: modelID, Provider:
            provider}
        t.records[modelID] = record
    }
    record.InputTokens += inputTokens
    record.OutputTokens += outputTokens
    record.RequestCount++
    record.LastUsed = time.Now()
    record.ScoreAtUse = score
}

// GetUsageReport returns aggregated usage data.
func (t *TokenUsageTracker) GetUsageReport() []*UsageRecord {
    t.mu.RLock()
    defer t.mu.RUnlock()
    result := make([]*UsageRecord, 0, len(t.records))
    for _, r := range t.records {
        result = append(result, r)
    }
    return result
}

```

Acceptance Criteria: 1. go build ./internal/usage/... compiles 2. RecordUsage() captures verifier score at time of use 3. GetUsageReport() returns all recorded usage

Dependencies: TASK 2.1.1 **Effort:** Small

TASK 4.9: Pricing Update Integration

TASK 4.9.1: Integrate Real-Time Pricing from Verifier

File(s): helix_code/internal/pricing/monitor.go (or equivalent) **Line(s):** CREATE new file **Action:** CREATE

```

package pricing

import (
    "context"
    "dev.helix.code/internal/verifier"
    "time"
)

// Monitor watches for pricing changes from LLMsVerifier.
type Monitor struct {
    adapter    *verifier.Adapter
    interval   time.Duration
}

```

```

    lastHash string
}

// NewMonitor creates a pricing monitor.
func NewMonitor(adapter *verifier.Adapter, interval
    time.Duration) *Monitor {
    return &Monitor{adapter: adapter, interval: interval}
}

// CheckForChanges fetches current pricing and detects changes.
func (m *Monitor) CheckForChanges(ctx context.Context)
    (*PricingUpdate, error) {
    if m.adapter == nil || !m.adapter.IsEnabled() {
        return nil, verifier.ErrVerifierDisabled
    }
    pricing, err := m.adapter.client.GetPricing(ctx)
    if err != nil {
        return nil, err
    }
    return &PricingUpdate{Models: pricing, ChangedAt:
        time.Now()}, nil
}

type PricingUpdate struct {
    Models []map[string]interface{} `json:"models"`
    ChangedAt time.Time `json:"changed_at"`
}

```

Acceptance Criteria: 1. go build ./internal/pricing/... compiles 2. CheckForChanges() returns error when verifier is disabled 3. Pricing data structure is preserved as []map[string]interface{} for flexibility

Dependencies: TASK 2.1.1 **Effort:** Small

TASK 4.10: Rate Limiting Integration with Cooldown State

TASK 4.10.1: Integrate Rate Limit and Cooldown Awareness

File(s): helix_code/internal/ratelimit/verifier_integration.go (or equivalent) **Line(s):** CREATE new file **Action:** CREATE

```

package ratelimit

import (
    "context"
    "dev.helix.code/internal/verifier"
    "fmt"
    "time"
)

```



```

// VerifierRateLimiter wraps rate limit decisions with verifier
// cooldown data.
type VerifierRateLimiter struct {
    adapter *verifier.Adapter
    inner   *RateLimiter // existing rate limiter
}

// NewVerifierRateLimiter creates a verifier-aware rate limiter.
func NewVerifierRateLimiter(adapter *verifier.Adapter, inner
    *RateLimiter) *VerifierRateLimiter {
    return &VerifierRateLimiter{adapter: adapter, inner: inner}
}

// AllowRequest checks both local rate limiter AND verifier
// cooldown state.
func (r *VerifierRateLimiter) AllowRequest(ctx context.Context,
    modelID string) (bool, time.Duration, error) {
    // Check local rate limiter first
    allowed, retryAfter, err := r.inner.AllowRequest(modelID)
    if !allowed {
        return false, retryAfter, err
    }

    // Check verifier cooldown state
    if r.adapter != nil && r.adapter.IsEnabled() {
        model, err := r.adapter.client.GetModelByID(ctx, modelID)
        if err == nil && model != nil {
            if model.VerificationStatus == "rate_limited" {
                return false, 60 * time.Second,
                    fmt.Errorf("model %s is in cooldown", modelID)
            }
        }
    }

    return true, 0, nil
}

```

Acceptance Criteria: 1. go build ./internal/ratelimit/... compiles 2. AllowRequest() returns false when model is in rate_limited status 3. Falls back to local rate limiter when verifier is disabled

Dependencies: TASK 2.1.1 **Effort:** Small

TASK 4.11: Extend LLMsVerifier to Work with ALL Providers

TASK 4.11.1: Document Required Provider Adapter Additions

File(s): N/A — This is a gap in LLMsVerifier that must be fixed in the submodule **Line(s):** N/A
Action: DOCUMENT

LLMsVerifier currently supports only 12 providers. The following 23 additional provider adapters MUST be added to LLMsVerifier to achieve full HelixCode parity:

#	Provider	Status	Required Action
1	Azure	MISSING	Add providers/azure.go adapter
2	AWS Bedrock	MISSING	Add providers/bedrock.go adapter
3	Google Vertex AI	MISSING	Add providers/vertex.go adapter
4	Together AI	MISSING	Add providers/together.go adapter
5	Cerebras	MISSING	Add providers/cerebras.go adapter
6	Cloudflare Workers AI	MISSING	Add providers/cloudflare.go adapter
7	SiliconFlow	MISSING	Add providers/siliconflow.go adapter
8	Replicate	MISSING	Add providers/replicate.go adapter
9	Qwen (Alibaba)	MISSING	Add providers/qwen.go adapter
10	Cohere	MISSING	Add providers/cohere.go adapter
11	vLLM	MISSING	Add providers/vllm.go adapter
12	LocalAI	MISSING	Add providers/localai.go adapter
13	Hugging Face	MISSING	Add providers/huggingface.go adapter
14	Perplexity	MISSING	Add providers/perplexity.go adapter
15	AI21 Labs	MISSING	Add providers/ai21.go adapter
16	Aleph Alpha	MISSING	Add providers/alephalpha.go adapter
17	Fireworks AI	MISSING	Add providers/fireworks.go adapter
18	Anyscale	MISSING	Add providers/anyscale.go adapter
19	Predibase	MISSING	

#	Provider	Status	Required Action
			Add providers/predibase.go adapter
20	Lepton AI	MISSING	Add providers/lepton.go adapter
21	Nvidia NIM	MISSING	Add providers/nvidia.go adapter
22	Baseten	MISSING	Add providers/baseten.go adapter
23	OctoAI	MISSING	Add providers/octoai.go adapter

Each adapter must implement the Provider interface:

```
type Provider interface {
    Name() string
    ListModels(ctx context.Context) ([]*Model, error)
    VerifyModel(ctx context.Context, modelID string)
        (*VerificationResult, error)
    GetPricing(ctx context.Context) ([]PricingInfo, error)
    GetLimits(ctx context.Context) ([]RateLimitInfo, error)
}
```

Acceptance Criteria: 1. Document lists all 23 missing providers 2. Each entry specifies the required file path 3. Interface definition is provided

Dependencies: None **Effort:** Large (23 individual tasks in submodule)

TASK 4.12: Fix LLMsVerifier Stub Verification

TASK 4.12.1: Document and Plan Stub Fixes

File(s): N/A — LLMsVerifier submodule fix **Line(s):** LLMsVerifier/verification/verification.go:VerifyModel() **Action:** DOCUMENT

STUB-001 Fix Required: In LLMsVerifier/verification/verification.go, the VerifyModel() function returns hardcoded 8.5 for ALL dimensions. This MUST be replaced with real verification logic:

```
// BEFORE (stub):
func VerifyModel(modelID string) (*VerificationResult, error) {
    return &VerificationResult{
        OverallScore:      8.5,
        CodeCapabilityScore: 8.5,
        ResponsivenessScore: 8.5,
        // ... all hardcoded 8.5
    }, nil
}
```

```
// AFTER (real):
func VerifyModel(modelID string, adapter ProviderAdapter)
    (*VerificationResult, error) {
    result := &VerificationResult{ModelID: modelID}

    // 1. Existence check
    exists, err := adapter.HeadModel(modelID)
    result.ModelExists = &exists

    // 2. Responsiveness check
    respStart := time.Now()
    _, err = adapter.PingModel(modelID, "Say 'hello' and nothing
        else.")
    latency := time.Since(respStart)
    responsive := err == nil
    result.Responsive = &responsive

    // 3. Code capability check
    codeResp, err := adapter.TestCodeGeneration(modelID)
    result.SupportsCodeGeneration = err == nil &&
        codeResp.Contains("func")

    // 4. Calculate real scores from test results
    result.OverallScore = calculateOverallScore(result, latency)
    result.CodeCapabilityScore = calculateCodeScore(codeResp)
    result.ResponsivenessScore =
        calculateResponsivenessScore(latency)
    // ... etc.

    return result, nil
}
```

Acceptance Criteria: 1. Document clearly shows the before/after code 2. Real verification calls provider adapter methods 3. Scores are calculated from actual test results

Dependencies: None **Effort:** Large (submodule fix)

PHASE 4 ROLLBACK PLAN

```
cd HelixCode
git checkout -- internal/mcp/server.go
git checkout -- internal/lsp/completion.go
git checkout -- internal/acp/discovery.go
git rm --cached internal/embeddings/selector.go internal/rag/
    pipeline.go \
    internal/skills/manager.go internal/plugins/manager.go \
    internal/usage/tracker.go internal/pricing/monitor.go \
```

```
internal/ratelimit/verifier_integration.go
rm -f internal/embeddings/selector.go internal/rag/pipeline.go \
internal/skills/manager.go internal/plugins/manager.go \
internal/usage/tracker.go internal/pricing/monitor.go \
internal/ratelimit/verifier_integration.go
go mod tidy
make build
make test-unit
```

PHASE 4 VERIFICATION CHECKLIST

- ☐ go build ./... compiles with zero errors
 - ☐ MCP server includes verifier-aware models in tool list
 - ☐ LSP completion uses verifier-selected model with SupportsCode=true
 - ☐ ACP discovery includes agents with Source: "verifier"
 - ☐ Embedding selector returns model with SupportsEmbeddings=true
 - ☐ RAG selector prefers models with ContextSize >= 32000 and SupportsReasoning=true
 - ☐ Skills manager rejects skill execution when model lacks required capability
 - ☐ Plugin manager rejects activation when required model is unavailable
 - ☐ Token usage tracker captures verifier score at time of use
 - ☐ Pricing monitor fetches from verifier when enabled
 - ☐ Rate limiter rejects requests for models in rate_limited status
 - ☐ All capability integrations respect verifier.enabled flag (fallback when disabled)
-

PHASE 5: TESTING IMPLEMENTATION — Anti-Bluff Test Suite

Phase Goal: Implement all tests that guarantee every feature actually works. No simulated data, no hardcoded expectations, no bluff.

Phase Entry Criteria: Phase 4 verification checklist is complete. **Phase Exit Criteria:** 1. All 20+ unit test files compile and pass in -short mode 2. All 6+ contract test files pass against real verifier endpoints 3. All 6+ component test files pass with real subsystem wiring 4. All 8+ integration test files pass with real dependencies 5. All 12 challenge scripts pass 6. scripts/

enforce_coverage.sh passes (100% unit, 95% integration) 7. scripts/
no_mock_above_unit.sh passes (zero violations)

TASK 5.1: Create Unit Test Files

TASK 5.1.1: Create internal/verifier/client_test.go

File(s): helix_code/internal/verifier/client_test.go **Line(s):** CREATE new file **Action:** CREATE

```
package verifier

import (
    "context"
    "encoding/json"
    "net/http"
    "net/http/httptest"
    "testing"
    "time"
)

func TestNewClient_Defaults(t *testing.T) {
    c := NewClient("", "", 0)
    if c.baseURL != "http://localhost:8081" {
        t.Errorf("expected default baseURL, got %s", c.baseURL)
    }
    if c.timeout != 30*time.Second {
        t.Errorf("expected default timeout, got %s", c.timeout)
    }
}

func TestClient_Health(t *testing.T) {
    server := httptest.NewServer(http.HandlerFunc(func(w
        http.ResponseWriter, r *http.Request) {
        if r.URL.Path != "/api/health" {
            t.Errorf("unexpected path: %s", r.URL.Path)
        }
        if r.Header.Get("Authorization") != "Bearer test-key" {
            t.Errorf("missing auth header")
        }
        json.NewEncoder(w).Encode(HealthResponse{Status: "ok",
            Version: "1.0.0"})
        }))
    defer server.Close()

    client := NewClient(server.URL, "test-key", 5*time.Second)
    hr, err := client.Health(context.Background())
    if err != nil {
```

```

        t.Fatalf("health check failed: %v", err)
    }
    if hr.Status != "ok" {
        t.Errorf("expected status ok, got %s", hr.Status)
    }
}

func TestClient_GetModels(t *testing.T) {
    server := httptest.NewServer(http.HandlerFunc(func(w
        http.ResponseWriter, r *http.Request) {
            if r.URL.Path != "/api/models" {
                t.Errorf("unexpected path: %s", r.URL.Path)
            }
            json.NewEncoder(w).Encode([]*VerifiedModel{
                {ID: "gpt-4o", Name: "GPT-4o", Provider: "openai",
                OverallScore: 9.2},
                {ID: "claude-3-5-sonnet", Name: "Claude 3.5 Sonnet",
                Provider: "anthropic", OverallScore: 8.9},
            })
        }))
    defer server.Close()

    client := NewClient(server.URL, "test-key", 5*time.Second)
    models, err := client.GetModels(context.Background())
    if err != nil {
        t.Fatalf("get models failed: %v", err)
    }
    if len(models) != 2 {
        t.Errorf("expected 2 models, got %d", len(models))
    }
    if models[0].ID != "gpt-4o" {
        t.Errorf("expected gpt-4o, got %s", models[0].ID)
    }
    if models[0].OverallScore != 9.2 {
        t.Errorf("expected score 9.2, got %.1f",
            models[0].OverallScore)
    }
}

func TestClient_GetModelByID_NotFound(t *testing.T) {
    server := httptest.NewServer(http.HandlerFunc(func(w
        http.ResponseWriter, r *http.Request) {
            w.WriteHeader(http.StatusNotFound)
        }))
    defer server.Close()

    client := NewClient(server.URL, "", 5*time.Second)

```

```

_, err := client.GetModelByID(context.Background(),
    "nonexistent")
if err == nil {
    t.Fatalf("expected error for 404")
}
}

func TestClient_GetProviderScores(t *testing.T) {
    server := httptest.NewServer(http.HandlerFunc(func(w
        http.ResponseWriter, r *http.Request) {
            json.NewEncoder(w).Encode(map[string]float64{"openai":
                9.1, "anthropic": 8.9})
        }))
    defer server.Close()

    client := NewClient(server.URL, "", 5*time.Second)
    scores, err := client.GetProviderScores(context.Background())
    if err != nil {
        t.Fatalf("get scores failed: %v", err)
    }
    if scores["openai"] != 9.1 {
        t.Errorf("expected openai score 9.1, got %.1f",
            scores["openai"])
    }
}

func TestClient_AuthHeader_NoKey(t *testing.T) {
    server := httptest.NewServer(http.HandlerFunc(func(w
        http.ResponseWriter, r *http.Request) {
            if r.Header.Get("Authorization") != "" {
                t.Error("auth header should be empty when no key
                    configured")
            }
            json.NewEncoder(w).Encode(HealthResponse{Status: "ok"})
        }))
    defer server.Close()

    client := NewClient(server.URL, "", 5*time.Second)
    _, err := client.Health(context.Background())
    if err != nil {
        t.Fatalf("health check failed: %v", err)
    }
}

```

Acceptance Criteria: 1. `go test -short ./internal/verifier/...` passes 2. All 6 test functions compile and run 3. `TestNewClient_Defaults` verifies defaults without mocks 4. `TestClient_AuthHeader_NoKey` proves no auth sent when key is empty

Dependencies: TASK 1.6.1 **Effort:** Large

TASK 5.1.2: Create internal/verifier/cache_test.go

File(s): helix_code/internal/verifier/cache_test.go **Line(s):** CREATE new file **Action:** CREATE

```
package verifier

import (
    "testing"
    "time"
)

func TestCache_GetSet(t *testing.T) {
    cache := NewCache(5*time.Minute, nil)
    models := []*VerifiedModel{
        {ID: "gpt-4o", OverallScore: 9.2},
    }
    cache.SetModels("all", models)
    got, ok := cache.GetModels("all")
    if !ok {
        t.Fatal("expected cache hit")
    }
    if len(got) != 1 || got[0].ID != "gpt-4o" {
        t.Errorf("unexpected cached model: %v", got)
    }
}

func TestCache_TTLExpiry(t *testing.T) {
    cache := NewCache(1*time.Millisecond, nil)
    models := []*VerifiedModel{{ID: "test", OverallScore: 5.0}}
    cache.SetModels("all", models)
    time.Sleep(2 * time.Millisecond)
    _, ok := cache.GetModels("all")
    if ok {
        t.Error("expected cache miss after TTL expiry")
    }
}

func TestCache_StaleFallback(t *testing.T) {
    cache := NewCache(1*time.Millisecond, nil)
    models := []*VerifiedModel{{ID: "test", OverallScore: 5.0}}
    cache.SetModels("all", models)
    time.Sleep(2 * time.Millisecond)
    got, ok := cache.GetModelsStale("all")
    if !ok {
        t.Error("expected stale cache hit within 2x TTL")
    }
    if len(got) != 1 {
```

```

        t.Errorf("expected 1 model from stale cache, got %d",
            len(got))
    }
}

func TestCache_Invalidation(t *testing.T) {
    cache := NewCache(5*time.Minute, nil)
    cache.SetModels("all", []*VerifiedModel{{ID: "test"}})
    cache.Invalidate("all")
    _, ok := cache.GetModels("all")
    if ok {
        t.Error("expected cache miss after invalidation")
    }
}

func TestCache_ModelScore(t *testing.T) {
    cache := NewCache(5*time.Minute, nil)
    cache.SetScores(map[string]float64{"gpt-4o": 9.2})
    score, ok := cache.GetModelScore("gpt-4o")
    if !ok {
        t.Fatal("expected score cache hit")
    }
    if score != 9.2 {
        t.Errorf("expected score 9.2, got %.1f", score)
    }
}

```

Acceptance Criteria: 1. `go test -short ./internal/verifier/...` passes 2. All 5 cache test functions compile and run 3. `TestCache_TTLExpiry` proves TTL works (real time, not mock) 4. `TestCache_StaleFallback` proves stale cache works within 2x TTL

Dependencies: TASK 2.4.1 **Effort:** Medium

TASK 5.1.3: Create `internal/verifier/health_test.go`

File(s): `helix_code/internal/verifier/health_test.go` **Line(s):** CREATE new file **Action:** CREATE

```

package verifier

import (
    "dev.helix.code/internal/config"
    "testing"
    "time"
)

func TestHealthMonitor_CircuitBreaker(t *testing.T) {
    cfg := config.VerifierHealthConfig{
        FailureThreshold: 3,
    }
}

```

```

    RecoveryThreshold: 2,
    CircuitBreaker: config.CircuitBreakerConfig{
        Enabled: true,
        HalfOpenTimeout: 1 * time.Second,
    },
}
h := NewHealthMonitor(cfg)

// Record failures up to threshold
h.RecordFailure()
h.RecordFailure()
if h.IsCircuitOpen() {
    t.Error("circuit should not be open after 2 failures")
}
h.RecordFailure()
if !h.IsCircuitOpen() {
    t.Error("circuit should be open after 3 failures")
}
if h.AllowRequest() {
    t.Error("request should not be allowed when circuit
        open")
}

// Wait for half-open timeout
time.Sleep(1100 * time.Millisecond)
if !h.AllowRequest() {
    t.Error("request should be allowed in half-open state")
}

// Record successes to close circuit
h.RecordSuccess()
h.RecordSuccess()
if h.GetState() != CircuitClosed {
    t.Errorf("circuit should be closed, got state %d",
        h.GetState())
}
if !h.AllowRequest() {
    t.Error("request should be allowed when circuit closed")
}
}

func TestHealthMonitor_SuccessResetsFailures(t *testing.T) {
    cfg := config.VerifierHealthConfig{
        FailureThreshold: 5,
        CircuitBreaker: config.CircuitBreakerConfig{Enabled:
            true},
    }
    h := NewHealthMonitor(cfg)

```

```

    h.RecordFailure()
    h.RecordFailure()
    h.RecordSuccess() // should reset failures in closed state
    h.RecordFailure()
    h.RecordFailure()
    if h.IsCircuitOpen() {
        t.Error("circuit should not be open: only 2 failures
            after reset")
    }
}

func TestHealthMonitor_DisabledBreaker(t *testing.T) {
    cfg := config.VerifierHealthConfig{
        FailureThreshold: 1,
        CircuitBreaker:    config.CircuitBreakerConfig{Enabled:
            false},
    }
    h := NewHealthMonitor(cfg)
    h.RecordFailure()
    if h.IsCircuitOpen() {
        t.Error("circuit should NOT open when breaker is
            disabled")
    }
}

```

Acceptance Criteria: 1. `go test -short ./internal/verifier/...` passes 2. `TestHealthMonitor_CircuitBreaker` tests real state transitions with real time 3. `TestHealthMonitor_SuccessResetsFailures` proves reset behavior 4. `TestHealthMonitor_DisabledBreaker` proves circuit breaker can be disabled

Dependencies: TASK 2.5.1 **Effort:** Medium

TASK 5.1.4: Create `internal/verifier/adaptor_test.go`

File(s): `helix_code/internal/verifier/adaptor_test.go` **Line(s):** CREATE new file **Action:** CREATE

```

package verifier

import (
    "context"
    "dev.helix.code/internal/config"
    "testing"
)

func TestAdapter_IsEnabled(t *testing.T) {
    a := NewAdapter(nil, nil, nil,
        &config.VerifierConfig{Enabled: false})
    if a.IsEnabled() {

```

```

        t.Error("should be disabled")
    }
    a := NewAdapter(nil, nil, nil,
        &config.VerifierConfig{Enabled: true})
    if !a.IsEnabled() {
        t.Error("should be enabled")
    }
}

func TestAdapter_GetModelScore(t *testing.T) {
    a := NewAdapter(nil, nil, nil,
        &config.VerifierConfig{Enabled: true})
    a.refreshScores([]*VerifiedModel{
        {ID: "gpt-4o", OverallScore: 9.2},
    })
    score, ok := a.GetModelScore("gpt-4o")
    if !ok {
        t.Fatal("expected score found")
    }
    if score != 9.2 {
        t.Errorf("expected 9.2, got %.1f", score)
    }
}

func TestAdapter_GetModelScore_Normalization(t *testing.T) {
    a := NewAdapter(nil, nil, nil,
        &config.VerifierConfig{Enabled: true})
    a.refreshScores([]*VerifiedModel{
        {ID: "big-score", OverallScore: 95.0}, // >10, should
        normalize
    })
    score, ok := a.GetModelScore("big-score")
    if !ok {
        t.Fatal("expected score found")
    }
    if score != 9.5 {
        t.Errorf("expected normalized 9.5, got %.1f", score)
    }
}

func TestAdapter_FilterByProviderConfig(t *testing.T) {
    a := NewAdapter(nil, nil, nil, &config.VerifierConfig{
        Enabled: true,
        Providers: map[string]config.VerifierProviderConfig{
            "openai": {Enabled: true},
            "xai":    {Enabled: false},
        },
    })
}

```

```

models := []*VerifiedModel{
    {ID: "gpt-4o", Provider: "openai"},
    {ID: "grok-3", Provider: "xai"},
}
filtered := a.filterByProviderConfig(models)
if len(filtered) != 1 || filtered[0].Provider != "openai" {
    t.Errorf("expected only openai model, got %v", filtered)
}
}

func TestAdapter_GetFallbackModels(t *testing.T) {
    a := NewAdapter(nil, nil, nil,
        &config.VerifierConfig{Enabled: true})
    models, err := a.getFallbackModels()
    if err != ErrUsingFallback {
        t.Errorf("expected ErrUsingFallback, got %v", err)
    }
    if len(models) != 7 {
        t.Errorf("expected 7 fallback models, got %d",
            len(models))
    }
    for _, m := range models {
        if m.Source != "fallback" {
            t.Errorf("expected source fallback, got %s",
                m.Source)
        }
    }
}

```

Acceptance Criteria: 1. `go test -short ./internal/verifier/...` passes 2. `TestAdapter_GetModelScore_Normalization` proves score >10 is divided by 10 3. `TestAdapter_FilterByProviderConfig` proves disabled providers are filtered out 4. `TestAdapter_GetFallbackModels` proves exactly 7 fallback models with source="fallback"

Dependencies: TASK 2.1.1 **Effort:** Medium

TASK 5.1.5: Create `internal/verifier/polling_test.go`

File(s): `helix_code/internal/verifier/polling_test.go` **Line(s):** CREATE new file **Action:** CREATE

```

package verifier

import (
    "dev.helix.code/internal/config"
    "testing"
    "time"
)

```

```

func TestPoller_MinimumInterval(t *testing.T) {
    p := NewPoller(nil, 1*time.Second)
    if p.interval != 10*time.Second {
        t.Errorf("minimum interval should be 10s, got %s",
            p.interval)
    }
}

func TestPoller_StartStop(t *testing.T) {
    cfg := &config.VerifierConfig{Enabled: true}
    adapter := NewAdapter(nil, nil, nil, cfg)
    p := NewPoller(adapter, 1*time.Hour) // long interval so no
        actual polls
    p.Start()
    if !p.IsRunning() {
        t.Error("poller should be running after Start()")
    }
    p.Stop()
    if p.IsRunning() {
        t.Error("poller should not be running after Stop()")
    }
}

func TestPoller_DetectChanges(t *testing.T) {
    p := &Poller{lastModels: make(map[string]*VerifiedModel)}
    old := []*VerifiedModel{
        {ID: "gpt-4o", OverallScore: 9.0, VerificationStatus:
            "verified"},
    }
    new := []*VerifiedModel{
        {ID: "gpt-4o", OverallScore: 9.2, VerificationStatus:
            "verified"},
        {ID: "claude-3", OverallScore: 8.9, VerificationStatus:
            "verified"},
    }
    p.lastModels = indexModels(old)
    changes := p.detectChanges(old, new)
    if len(changes) != 2 {
        t.Errorf("expected 2 changes (score + discovered), got
            %d", len(changes))
    }
    hasScoreChange := false
    hasDiscovered := false
    for _, c := range changes {
        if c.Type == "model.score_changed" {
            hasScoreChange = true
        }
    }
}

```

```

        if c.Type == "model.discovered" && c.Model.ID ==
            "claude-3" {
            hasDiscovered = true
        }
    }
    if !hasScoreChange {
        t.Error("expected score change event")
    }
    if !hasDiscovered {
        t.Error("expected discovered event for claude-3")
    }
}

```

Acceptance Criteria: 1. `go test -short ./internal/verifier/...` passes 2. `TestPoller_MinimumInterval` proves 10s floor 3. `TestPoller_StartStop` proves no deadlock 4. `TestPoller_DetectChanges` proves change detection works

Dependencies: TASK 2.3.1 **Effort:** Medium

TASK 5.1.6: Create `internal/llm/verifier_integration_test.go`

File(s): `helix_code/internal/llm/verifier_integration_test.go` **Line(s):**
 CREATE new file **Action:** CREATE

```

package llm

import (
    "dev.helix.code/internal/verifier"
    "testing"
)

func TestVerifierModelSource_IsAvailable(t *testing.T) {
    src := NewVerifierModelSource(nil)
    if src.IsAvailable() {
        t.Error("should not be available with nil adapter")
    }
}

func TestVerifierModelSource_FetchModels(t *testing.T) {
    models := []*verifier.VerifiedModel{
        {ID: "gpt-4o", DisplayName: "GPT-4o", Provider: "openai",
            SupportsCode: true, SupportsStreaming: true,
            SupportsTools: true,
            OverallScore: 9.2},
    }
    src := &VerifierModelSource{}
    converted := src.convert(models)
    if len(converted) != 1 {
        t.Fatalf("expected 1 model, got %d", len(converted))
    }
}

```



```

    }
    if converted[0].ID != "gpt-4o" {
        t.Errorf("expected gpt-4o, got %s", converted[0].ID)
    }
    // Verify capabilities mapped
    hasCode := false
    for _, c := range converted[0].Capabilities {
        if c == CapabilityCodeGeneration {
            hasCode = true
        }
    }
    if !hasCode {
        t.Error("expected CapabilityCodeGeneration mapped from SupportsCode")
    }
}

```

Acceptance Criteria: 1. `go test -short ./internal/llm/...` passes 2. `TestVerifierModelSource_FetchModels` proves conversion from verifier to `ModelInfo` 3. Capabilities are correctly mapped

Dependencies: TASK 2.11.1 **Effort:** Small

TASK 5.1.7: Create `internal/cli/ux/render_test.go`

File(s): `helix_code/internal/cli/ux/render_test.go` **Line(s):** CREATE new file
Action: CREATE

```

package ux

import (
    "dev.helix.code/internal/verifier"
    "encoding/json"
    "strings"
    "testing"
)

func TestRenderModelList_Wide(t *testing.T) {
    rows := []*ModelListRow{
        {Model: &verifier.VerifiedModel{ID: "gpt-4o",
            DisplayName: "GPT-4o", Provider: "openai", OverallScore:
            9.2, VerificationStatus: "verified"}, Rank: 1},
    }
    sym := NewSymbolSet(false)
    out := RenderModelList(rows, sym, 150,
        &RenderOptions{Format: "table"})
    if !strings.Contains(out, "GPT-4o") {
        t.Error("output should contain model name")
    }
}

```

```

    if !strings.Contains(out, "9.2") {
        t.Error("output should contain score")
    }
}

func TestRenderModelList_JSON(t *testing.T) {
    rows := []*ModelListRow{
        {Model: &verifier.VerifiedModel{ID: "gpt-4o",
            DisplayName: "GPT-4o", Provider: "openai", OverallScore:
            9.2, Verified: true}, Rank: 1},
    }
    sym := NewSymbolSet(false)
    out := RenderModelList(rows, sym, 150,
        &RenderOptions{Format: "json"})
    var data []map[string]interface{}
    if err := json.Unmarshal([]byte(out), &data); err != nil {
        t.Fatalf("invalid JSON: %v", err)
    }
    if len(data) != 1 {
        t.Fatalf("expected 1 JSON object, got %d", len(data))
    }
    if data[0]["id"] != "gpt-4o" {
        t.Errorf("expected id gpt-4o, got %v", data[0]["id"])
    }
}

func TestRenderModelList_Compact(t *testing.T) {
    rows := []*ModelListRow{
        {Model: &verifier.VerifiedModel{ID: "gpt-4o",
            DisplayName: "GPT-4o", Provider: "openai", OverallScore:
            9.2, VerificationStatus: "verified"}, Rank: 1},
    }
    sym := NewSymbolSet(false)
    out := RenderModelList(rows, sym, 40, &RenderOptions{Format:
        "table"})
    if strings.Contains(out, "Capabilities") {
        t.Error("compact view should not show capabilities
            header")
    }
}

func TestTruncate(t *testing.T) {
    if truncate("hello world", 5) != "he..." {
        t.Errorf("unexpected truncate result: %s",
            truncate("hello world", 5))
    }
    if truncate("hi", 5) != "hi" {
        t.Errorf("short string should not be truncated")
    }
}

```

```
}  
}
```

Acceptance Criteria: 1. `go test -short ./internal/cli/ux/...` passes 2.
TestRenderModelList_JSON proves valid JSON output 3.
TestRenderModelList_Compact proves narrow rendering

Dependencies: TASK 3.4.1 **Effort:** Small

TASK 5.2: Create Contract Test Files

TASK 5.2.1: Create `tests/contract/verifier_schema_contract_test.go`

File(s): `helix_code/tests/contract/verifier_schema_contract_test.go`

Line(s): CREATE new file **Action:** CREATE

```
package contract  
  
import (  
    "context"  
    "dev.helix.code/internal/verifier"  
    "encoding/json"  
    "net/http"  
    "net/http/httptest"  
    "testing"  
    "time"  
)  
  
// ContractTest verifies that the verifier API schema matches  
// expectations.  
func ContractTest_VerifierSchema(t *testing.T) {  
    server := httptest.NewServer(http.HandlerFunc(func(w  
        http.ResponseWriter, r *http.Request) {  
            switch r.URL.Path {  
            case "/api/models":  
                data := []map[string]interface{}{  
                    {  
                        "id": "test-gpt-4o",  
                        "name": "Test GPT-4o",  
                        "display_name": "Test GPT-4o",  
                        "provider": "openai",  
                        "score": 9.2,  
                        "verified": true,  
                        "verification_status": "verified",  
                        "context_window_tokens": 128000,  
                        "max_output_tokens": 4096,  
                        "supports_streaming": true,  
                        "supports_tool_use": true,  
                        "supports_functions": true,  
                    },  
                }  
                w.WriteHeader(http.StatusOK)  
                json.NewEncoder(w).Encode(data)  
            }  
        })  
    })  
    t.Run("ContractTest_VerifierSchema", func(t *testing.T) {  
        // Test logic here  
    })  
}
```

```

        "supports_code_generation": true,
        "supports_vision": true,
        "overall_score": 9.2,
        "code_capability_score": 9.5,
        "responsiveness_score": 8.8,
        "reliability_score": 9.0,
        "feature_richness_score": 9.1,
        "value_proposition_score": 8.0,
        "input_token_cost": 0.005,
        "output_token_cost": 0.015,
        "latency_ms": 250,
    },
}
_ = json.NewEncoder(w).Encode(data)
default:
    w.WriteHeader(http.StatusNotFound)
}
}))
defer server.Close()

client := verifier.NewClient(server.URL, "", 5*time.Second)
models, err := client.GetModels(context.Background())
if err != nil {
    t.Fatalf("contract test failed: %v", err)
}
if len(models) == 0 {
    t.Fatal("expected at least one model")
}

// Schema validation: all required fields must be present
m := models[0]
if m.ID == "" {
    t.Error("contract violation: id is empty")
}
if m.DisplayName == "" {
    t.Error("contract violation: display_name is empty")
}
if m.Provider == "" {
    t.Error("contract violation: provider is empty")
}
if m.OverallScore == 0 {
    t.Error("contract violation: overall_score is 0")
}
}

```

Acceptance Criteria: 1. `go test -v -run Contract ./tests/contract/...` passes 2. Schema validation checks all required fields 3. Uses real `http` test server (not mocks above unit level)

Dependencies: TASK 1.6.1 **Effort:** Medium

TASK 5.2.2: Create tests/contract/error_response_contract_test.go

File(s): helix_code/tests/contract/error_response_contract_test.go

Line(s): CREATE new file **Action:** CREATE

```
package contract

import (
    "context"
    "dev.helix.code/internal/verifier"
    "encoding/json"
    "net/http"
    "net/http/httptest"
    "testing"
    "time"
)

// ContractTest_ErrorResponseFormat verifies error JSON
// structure.
func ContractTest_ErrorResponseFormat(t *testing.T) {
    server := httptest.NewServer(http.HandlerFunc(func(w
        http.ResponseWriter, r *http.Request) {
            w.WriteHeader(http.StatusBadRequest)
            json.NewEncoder(w).Encode(map[string]interface{}{
                "error":    "invalid_request",
                "message":  "Model ID is required",
                "code":     400,
            })
        }))
    defer server.Close()

    client := verifier.NewClient(server.URL, "", 5*time.Second)
    _, err := client.GetModelByID(context.Background(), "")
    if err == nil {
        t.Fatal("expected error")
    }
    // Verify error contains expected fields
    errStr := err.Error()
    if errStr == "" {
        t.Error("error should not be empty")
    }
}
```

Acceptance Criteria: 1. go test -v -run Contract ./tests/contract/...
passes 2. Error response has error, message, code fields

Dependencies: TASK 1.6.1 **Effort:** Small

TASK 5.3: Create Component Test Files

TASK 5.3.1: Create tests/component/model_manager_verifier_component_test.go

File(s): helix_code/tests/component/
model_manager_verifier_component_test.go **Line(s):** CREATE new file **Action:**
CREATE

```
package component

import (
    "context"
    "dev.helix.code/internal/config"
    "dev.helix.code/internal/llm"
    "dev.helix.code/internal/verifier"
    "encoding/json"
    "net/http"
    "net/http/httptest"
    "testing"
    "time"
)

// ComponentTest_ModelManagerSelectModel_UsesVerifierScores
// proves that
// SelectOptimalModel incorporates verifier scores.
func ComponentTest_ModelManagerSelectModel_UsesVerifierScores(t
    *testing.T) {
    server := httptest.NewServer(http.HandlerFunc(func(w
        http.ResponseWriter, r *http.Request) {
        if r.URL.Path == "/api/models" {
            data := []map[string]interface{}{
                {
                    "id": "high-score-model", "display_name":
                    "High Score", "provider": "openai",
                    "overall_score": 9.5,
                    "supports_code_generation": true,
                    "verification_status": "verified",
                    "context_window_tokens": 128000,
                },
                {
                    "id": "low-score-model", "display_name":
                    "Low Score", "provider": "openai",
                    "overall_score": 4.0,
                    "supports_code_generation": true,
                    "verification_status": "verified",
                    "context_window_tokens": 128000,
                },
            }
        }
    })
}
```

```

        _ = json.NewEncoder(w).Encode(data)
    }
}))
defer server.Close()

client := verifier.NewClient(server.URL, "", 5*time.Second)
cfg := &config.VerifierConfig{Enabled: true, Endpoint:
    server.URL, CacheTTL: 1 * time.Hour}
cache := verifier.NewCache(1*time.Hour, nil)
health :=
    verifier.NewHealthMonitor(config.VerifierHealthConfig{
        CircuitBreaker: config.CircuitBreakerConfig{Enabled:
            true},
    })
adapter := verifier.NewAdapter(client, cache, health, cfg)

mm := llm.NewModelManager(/* ... setup ... */)
mm.SetVerifierAdapter(adapter)

criteria := llm.ModelSelectionCriteria{
    TaskType: "code_generation",
    RequiredCapabilities:
        []llm.ModelCapability{llm.CapabilityCodeGeneration},
}
selected, err := mm.SelectOptimalModel(criteria)
if err != nil {
    t.Fatalf("selection failed: %v", err)
}
if selected.ID != "high-score-model" {
    t.Errorf("expected high-score-model (9.5), got %s",
        selected.ID)
}
}

```

Acceptance Criteria: 1. go test -v -run Component ./tests/component/... passes 2. Test proves higher-scored model is selected over lower-scored 3. Uses real http test server (no mocks)

Dependencies: TASK 2.8.1 **Effort:** Large

TASK 5.4: Create Integration Test Files

TASK 5.4.1: Create tests/integration/helixcode_full_stack_test.go

File(s): helix_code/tests/integration/helixcode_full_stack_test.go

Line(s): CREATE new file **Action:** CREATE

```
package integration
```

```

import (
    "context"
    "dev.helix.code/internal/verifier"
    "os"
    "testing"
    "time"
)

// IntegrationTest_FullStack_APIModels_ReturnsVerifierData proves
// the full stack
// from config -> verifier adapter -> model manager -> API
// returns verifier data.
func IntegrationTest_FullStack_APIModels_ReturnsVerifierData(t
    *testing.T) {
    if testing.Short() {
        t.Skip("skipping integration test in short mode")
    }

    ctx, cancel := context.WithTimeout(context.Background(),
        30*time.Second)
    defer cancel()

    endpoint := os.Getenv("HELIX_VERIFIER_ENDPOINT")
    if endpoint == "" {
        endpoint = "http://localhost:8081"
    }

    client := verifier.NewClient(endpoint, "", 30*time.Second)
    models, err := client.GetModels(ctx)
    if err != nil {
        t.Fatalf("full stack integration failed: %v", err)
    }
    if len(models) == 0 {
        t.Fatal("no models returned from verifier – integration
            failure")
    }

    // ANTI-BLUFF: Verify the response is NOT a hardcoded list
    if len(models) <= 3 {
        t.Logf("WARNING: only %d models returned – may be
            fallback list", len(models))
    }

    for _, m := range models {
        if m.ID == "" {
            t.Error("model has empty ID")
        }
        if m.Provider == "" {

```



```

        t.Error("model has empty provider")
    }
}
}

```

Acceptance Criteria: 1. `go test -v -run Integration ./tests/integration/...` passes (when run with real verifier) 2. Test connects to real verifier endpoint 3. Returns error if no models are returned 4. Warns if only ≤ 3 models returned (hardcoded list detection)

Dependencies: TASK 1.6.1 **Effort:** Large

TASK 5.5: Create Challenge Scripts

TASK 5.5.1: Create All 12 Challenge Shell Scripts

Challenge 1: `challenges/scripts/verifier_model_list_challenge.sh`

```

#!/usr/bin/env bash
set -euo pipefail
SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
PROJECT_ROOT="$(cd "${SCRIPT_DIR}/../.." && pwd)"
CLI_BIN="${PROJECT_ROOT}/helix_code/bin/cli"
OUTPUT_FILE="/tmp/verifier_model_list_output.txt"

echo "[CHALLENGE] verifier_model_list_challenge: START"
"${CLI_BIN}" --list-models > "${OUTPUT_FILE}" 2>&1 || true
if grep -q "llama-3-8b.*mistral-7b.*phi-3-mini" "$
    {OUTPUT_FILE}"; then
    echo "[FAIL] Output contains only hardcoded 3-model list
        (BLUFF-002)"
    exit 1
fi
if ! grep -q "Score" "${OUTPUT_FILE}"; then
    echo "[FAIL] Missing Score column"
    exit 1
fi
echo "[CHALLENGE] verifier_model_list_challenge: PASS"

```

Challenge 2: `challenges/scripts/verifier_model_select_challenge.sh`

```

#!/usr/bin/env bash
set -euo pipefail
SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
PROJECT_ROOT="$(cd "${SCRIPT_DIR}/../.." && pwd)"
CLI_BIN="${PROJECT_ROOT}/helix_code/bin/cli"
OUTPUT_FILE="/tmp/verifier_select_output.txt"

echo "[CHALLENGE] verifier_model_select_challenge: START"

```

```

"${CLI_BIN}" --prompt "Write a Go function named AntiBluff" --
    model gpt-4o > "${OUTPUT_FILE}" 2>&1 || true
if grep -q "Generated response for:" "${OUTPUT_FILE}"; then
    echo "[FAIL] Simulated response detected (BLUFF-001)"
    exit 1
fi
if grep -q "func AntiBluff" "${OUTPUT_FILE}"; then
    echo "[CHALLENGE] verifier_model_select_challenge: PASS"
else
    echo "[FAIL] No real code generated"
    exit 1
fi

```

Challenge 3: challenges/scripts/
verifier_disable_fallback_challenge.sh

```

#!/usr/bin/env bash
set -euo pipefail
SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
PROJECT_ROOT="$(cd "${SCRIPT_DIR}/../.." && pwd)"
CLI_BIN="${PROJECT_ROOT}/helix_code/bin/cli"
OUTPUT_FILE="/tmp/verifier_disable_output.txt"

echo "[CHALLENGE] verifier_disable_fallback_challenge: START"
HELIX_VERIFIER_ENABLED=false "${CLI_BIN}" --list-models > "${
    OUTPUT_FILE}" 2>&1 || true
MODEL_COUNT=$(grep -c "openai\|anthropic\|ollama\|llama" "${
    OUTPUT_FILE}" || true)
if [[ "${MODEL_COUNT}" -lt 1 ]]; then
    echo "[FAIL] No models returned when verifier disabled"
    exit 1
fi
echo "[CHALLENGE] verifier_disable_fallback_challenge: PASS"

```

Challenge 4: challenges/scripts/
verifier_api_key_provision_challenge.sh

```

#!/usr/bin/env bash
set -euo pipefail
SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
PROJECT_ROOT="$(cd "${SCRIPT_DIR}/../.." && pwd)"
CONFIG_FILE="${PROJECT_ROOT}/helix_code/configs/config.yaml"

echo "[CHALLENGE] verifier_api_key_provision_challenge: START"
if grep -rP 'api_key:\s*sk-[a-zA-Z0-9]+' "${CONFIG_FILE}" 2>/dev/
    null; then
    echo "[FAIL] Literal API key found in config (security
        violation)"
    exit 1

```

```

fi
ENV_FILE="${PROJECT_ROOT}/helix_code/.env.example"
KEY_COUNT=$(grep -c "HELIX_.*API_KEY\|HELIX_.*API_TOKEN" "$
    {ENV_FILE}" || true)
if [[ "${KEY_COUNT}" -lt 10 ]]; then
    echo "[FAIL] Only ${KEY_COUNT} API keys documented
        in .env.example (expected >= 10)"
    exit 1
fi
echo "[CHALLENGE] verifier_api_key_provision_challenge: PASS"

```

Challenge 5: challenges/scripts/
verifier_rate_limit_display_challenge.sh

```

#!/usr/bin/env bash
set -euo pipefail
SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
PROJECT_ROOT="$(cd "${SCRIPT_DIR}/../../.." && pwd)"

echo "[CHALLENGE] verifier_rate_limit_display_challenge: START"
curl -sf "http://localhost:8081/api/models" > /tmp/
    verifier_rate_models.json 2>&1 || true
if ! grep -q "rate_limited\|cooldown" /tmp/
    verifier_rate_models.json 2>/dev/null; then
    echo "[WARN] No rate-limited models in verifier DB – test
        inconclusive"
fi
echo "[CHALLENGE] verifier_rate_limit_display_challenge: PASS"

```

Challenge 6: challenges/scripts/verifier_realtime_update_challenge.sh

```

#!/usr/bin/env bash
set -euo pipefail
SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
PROJECT_ROOT="$(cd "${SCRIPT_DIR}/../../.." && pwd)"

echo "[CHALLENGE] verifier_realtime_update_challenge: START"
MAX_WAIT=300
for i in $(seq 1 ${MAX_WAIT}); do
    curl -sf "http://localhost:8081/api/models" > "/tmp/
        verifier_poll_${i}.json" 2>&1 || true
    sleep 1
done
if [[ ! -f "/tmp/verifier_poll_1.json" ]]; then
    echo "[FAIL] No verifier data received"
    exit 1
fi
echo "[CHALLENGE] verifier_realtime_update_challenge: PASS"

```

Challenge 7: challenges/scripts/verifier_mcp_lsp_acp_challenge.sh

```
#!/usr/bin/env bash
set -euo pipefail
SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
PROJECT_ROOT="$(cd "${SCRIPT_DIR}/../.." && pwd)"
SERVER_URL="http://localhost:8080"

echo "[CHALLENGE] verifier_mcp_lsp_acp_challenge: START"
curl -sf "${SERVER_URL}/api/v1/mcp/models" > /tmp/
    verifier_mcp_output.json 2>&1 || true
if ! grep -q "gpt-4o\|claude" /tmp/verifier_mcp_output.json 2>/
    dev/null; then
    echo "[FAIL] MCP endpoint does not return verifier models"
    exit 1
fi
curl -sf "${SERVER_URL}/api/v1/lsp/completion" \
    -H "Content-Type: application/json" \
    -d '{"model": "gpt-4o", "prompt": "func AntiBluff"}' > /tmp/
    verifier_lsp_output.json 2>&1 || true
if ! grep -q "AntiBluff" /tmp/verifier_lsp_output.json 2>/dev/
    null; then
    echo "[FAIL] LSP endpoint does not return completions with
    verifier model"
    exit 1
fi
curl -sf "${SERVER_URL}/api/v1/acp/agents/discover" > /tmp/
    verifier_acp_output.json 2>&1 || true
if ! grep -q "verifier\|model:" /tmp/verifier_acp_output.json 2>/
    dev/null; then
    echo "[FAIL] ACP endpoint does not reference verifier"
    exit 1
fi
curl -sf "${SERVER_URL}/api/v1/embeddings" \
    -H "Content-Type: application/json" \
    -d '{"model": "text-embedding-3-small", "input": "anti-bluff
    test"}' > /tmp/verifier_embed_output.json 2>&1 || true
if ! grep -q "embedding" /tmp/verifier_embed_output.json 2>/dev/
    null; then
    echo "[FAIL] Embedding endpoint does not return embeddings"
    exit 1
fi
echo "[CHALLENGE] verifier_mcp_lsp_acp_challenge: PASS"
```

Challenge 8: challenges/scripts/
 verifier_cross_platform_cli_challenge.sh

```
#!/usr/bin/env bash
set -euo pipefail
SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
PROJECT_ROOT="$(cd "${SCRIPT_DIR}/../.." && pwd)"
```

```

CLI_BIN="${PROJECT_ROOT}/helix_code/bin/cli"

echo "[CHALLENGE] verifier_cross_platform_cli_challenge: START"
PLATFORM=$(uname -s)
ARCH=$(uname -m)
OUTPUT_FILE="/tmp/verifier_cross_platform_${PLATFORM}_${ARCH}.txt"
JSON_FILE="/tmp/verifier_cross_platform_${PLATFORM}_${ARCH}.json"

"${CLI_BIN}" --list-models > "${OUTPUT_FILE}" 2>&1 || true
"${CLI_BIN}" --list-models --format json > "${JSON_FILE}" 2>&1
|| true

if [[ "${PLATFORM}" != "MINGW*" && "${PLATFORM}" !=
    "CYGWIN*" ]]; then
    if grep -q $'\r' "${OUTPUT_FILE}"; then
        echo "[FAIL] Table output contains CRLF on non-Windows"
        exit 1
    fi
fi
if ! python3 -m json.tool "${JSON_FILE}" > /dev/null 2>&1; then
    echo "[FAIL] JSON output is invalid on ${PLATFORM}"
    exit 1
fi
for KEY in "id" "name" "provider" "score" "verified"; do
    if ! python3 -c "import json; d=json.load(open('${JSON_FILE}')); print('${KEY}' in d[0])" | grep -q
        "True"; then
        echo "[FAIL] JSON missing required key '${KEY}'"
        exit 1
    fi
done
MODEL_COUNT=$(python3 -c "import json; d=json.load(open('${JSON_FILE}')); print(len(d))")
if [[ "${MODEL_COUNT}" -lt 1 ]]; then
    echo "[FAIL] No models in JSON output"
    exit 1
fi
echo "[CHALLENGE] verifier_cross_platform_cli_challenge: PASS ($
    {PLATFORM} ${ARCH}, ${MODEL_COUNT} models)"

```

Challenge 9: challenges/scripts/
verifier_startup_pipeline_challenge.sh

```

#!/usr/bin/env bash
set -euo pipefail
SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
PROJECT_ROOT="$(cd "${SCRIPT_DIR}/../.." && pwd)"
SERVER_BIN="${PROJECT_ROOT}/helix_code/bin/server"

```

```

LOG_FILE="/tmp/verifier_startup_pipeline.log"

echo "[CHALLENGE] verifier_startup_pipeline_challenge: START"
timeout 60 "${SERVER_BIN}" > "${LOG_FILE}" 2>&1 &
SERVER_PID=$!
sleep 10

if ! grep -qi "discover" "${LOG_FILE}"; then
    echo "[FAIL] Phase 1 (Discover) not logged"
    kill "${SERVER_PID}" 2>/dev/null || true; exit 1
fi
if ! grep -qi "verif" "${LOG_FILE}"; then
    echo "[FAIL] Phase 2 (Verify) not logged"
    kill "${SERVER_PID}" 2>/dev/null || true; exit 1
fi
if ! grep -qi "score" "${LOG_FILE}"; then
    echo "[FAIL] Phase 3 (Score) not logged"
    kill "${SERVER_PID}" 2>/dev/null || true; exit 1
fi
if ! grep -qi "debate\|team\|selected" "${LOG_FILE}"; then
    echo "[FAIL] Phase 5 (Debate Team) not logged"
    kill "${SERVER_PID}" 2>/dev/null || true; exit 1
fi
if ! curl -sf "http://localhost:8080/health" > /dev/null 2>&1;
then
    echo "[FAIL] Server health check failed"
    kill "${SERVER_PID}" 2>/dev/null || true; exit 1
fi
kill "${SERVER_PID}" 2>/dev/null || true
echo "[CHALLENGE] verifier_startup_pipeline_challenge: PASS"

```

Challenge 10: challenges/scripts/
verifier_canned_detection_challenge.sh

```

#!/usr/bin/env bash
set -euo pipefail
SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
PROJECT_ROOT="$(cd "${SCRIPT_DIR}/../../.." && pwd)"

echo "[CHALLENGE] verifier_canned_detection_challenge: START"
API_OUTPUT="/tmp/verifier_canned_api.json"
curl -sf "http://localhost:8081/api/models/test-canned-model" >
    "${API_OUTPUT}" 2>&1 || true

STATUS=$(python3 -c "
import json, sys
try:
    d=json.load(open('${API_OUTPUT}'))
    print(d.get('verification_status', 'UNKNOWN'))

```

```

except:
    print('UNKNOWN')
")

if [[ "${STATUS}" != "failed" && "${STATUS}" != "unverified" ]];
then
    echo "[FAIL] Canned-response model has status '${STATUS}'
        instead of failed"
    exit 1
fi

SCORE=$(python3 -c "
import json, sys
try:
    d=json.load(open('${API_OUTPUT}'))
    print(d.get('overall_score', 999))
except:
    print(999)")

if (( $(echo "${SCORE} > 3.0" | bc -l) )); then
    echo "[FAIL] Canned-response model has score ${SCORE} (>
        3.0)"
    exit 1
fi
echo "[CHALLENGE] verifier_canned_detection_challenge: PASS"

```

Challenge 11: challenges/scripts/
verifier_security_redaction_challenge.sh

```

#!/usr/bin/env bash
set -euo pipefail
SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
PROJECT_ROOT="$(cd "${SCRIPT_DIR}/../.." && pwd)"
CLI_BIN="${PROJECT_ROOT}/helix_code/bin/cli"
CLI_LOG="/tmp/verifier_security_cli.log"

echo "[CHALLENGE] verifier_security_redaction_challenge: START"
FAKE_KEY="sk-antibluff-test-key-9876543210abcdef"
export HELIX_OPENAI_API_KEY="${FAKE_KEY}"

"${CLI_BIN}" --list-models > "${CLI_LOG}" 2>&1 || true

if grep -q "${FAKE_KEY}" "${CLI_LOG}"; then
    echo "[FAIL] API key found in CLI output"
    exit 1
fi
if grep -r "${FAKE_KEY}" "${PROJECT_ROOT}/helix_code/" > /dev/
    null 2>&1; then
    echo "[FAIL] API key found in HelixCode directory"

```

```

        exit 1
    fi

    KEY_FRAGMENT="${FAKE_KEY:0:8}"
    if grep -q "${KEY_FRAGMENT}" "${CLI_LOG}"; then
        echo "[FAIL] API key fragment found in CLI output"
        exit 1
    fi
    echo "[CHALLENGE] verifier_security_redaction_challenge: PASS"

```

Challenge 12: challenges/scripts/
verifier_scoring_accuracy_challenge.sh

```

#!/usr/bin/env bash
set -euo pipefail
SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
PROJECT_ROOT="$(cd "${SCRIPT_DIR}/../.." && pwd)"

echo "[CHALLENGE] verifier_scoring_accuracy_challenge: START"
HIGH_OUTPUT="/tmp/verifier_score_high.json"
LOW_OUTPUT="/tmp/verifier_score_low.json"

curl -sf "http://localhost:8081/api/models/test-high-score" > "${HIGH_OUTPUT}" 2>&1 || true
curl -sf "http://localhost:8081/api/models/test-low-score" > "${LOW_OUTPUT}" 2>&1 || true

HIGH_SCORE=$(python3 -c "import json; d=json.load(open('${HIGH_OUTPUT}')); print(d.get('overall_score', 0))")
LOW_SCORE=$(python3 -c "import json; d=json.load(open('${LOW_OUTPUT}')); print(d.get('overall_score', 10))")

if (( $(echo "${HIGH_SCORE} < 9.0" | bc -l) )); then
    echo "[FAIL] High-score model has score ${HIGH_SCORE} (< 9.0)"
    exit 1
fi
if (( $(echo "${LOW_SCORE} > 5.0" | bc -l) )); then
    echo "[FAIL] Low-score model has score ${LOW_SCORE} (> 5.0)"
    exit 1
fi
if (( $(echo "${HIGH_SCORE} == ${LOW_SCORE}" | bc -l) )); then
    echo "[FAIL] Scores are identical – hardcoded score detected"
    exit 1
fi
if (( $(echo "${HIGH_SCORE} == 8.5" | bc -l) )) || (( $(echo "${LOW_SCORE} == 8.5" | bc -l) )); then
    echo "[FAIL] Score is exactly 8.5 – likely stub value"
    exit 1

```



```
fi
echo "[CHALLENGE] verifier_scoring_accuracy_challenge: PASS"
```

Acceptance Criteria: 1. All 12 scripts are executable (chmod +x) 2. Each script has set -euo pipefail 3. Each script outputs [CHALLENGE] name: START and [CHALLENGE] name: PASS 4. Each script includes at least one anti-bluff assertion

Dependencies: All previous phases **Effort:** Large

TASK 5.6: Create Coverage and Quality Scripts

TASK 5.6.1: Create scripts/enforce_coverage.sh

File(s): helix_code/scripts/enforce_coverage.sh **Line(s):** CREATE new file
Action: CREATE

```
#!/usr/bin/env bash
set -euo pipefail

UNIT_THRESHOLD=100
INTEGRATION_THRESHOLD=95
CONTRACT_THRESHOLD=100

UNIT_COVER=$(go test -short ./internal/verifier/... ./internal/
    llm/... ./cmd/cli/... ./internal/services/... -cover 2>/
    dev/null | grep -oP '\d+\.\d+%' | tail -1 | tr -d '%')
if (( $(echo "${UNIT_COVER} < ${UNIT_THRESHOLD}" | bc -l) ));
then
    echo "[FAIL] Unit coverage ${UNIT_COVER}% < ${UNIT_THRESHOLD}
    %"
    exit 1
fi

INTEGRATION_COVER=$(go test -run Integration ./tests/
    integration/... -cover 2>/dev/null | grep -oP '\d+\.\d+
    %' | tail -1 | tr -d '%')
if (( $(echo "${INTEGRATION_COVER} < ${INTEGRATION_THRESHOLD}" |
    bc -l) )); then
    echo "[FAIL] Integration coverage ${INTEGRATION_COVER}% < $
    {INTEGRATION_THRESHOLD}%"
    exit 1
fi

echo "[PASS] Coverage check passed: Unit=${UNIT_COVER}%,
    Integration=${INTEGRATION_COVER}%"
```

TASK 5.6.2: Create scripts/no_mock_abeve_unit.sh

File(s): helix_code/scripts/no_mock_abeve_unit.sh **Line(s):** CREATE new file **Action:** CREATE

```
#!/usr/bin/env bash
set -euo pipefail

VIOLATIONS=0

for FILE in $(find tests/ internal/ -name "*_test.go" | grep -v
    "^internal/verifier/*_test.go" | grep -v "^internal/
    llm/*_test.go" | grep -v "^cmd/cli/*_test.go"); do
    if grep -qE "(mock|Mock|gomock|mockery|httpptest)" "${FILE}";
    then
        echo "[VIOLATION] Mock usage found in non-unit test: $
        {FILE}"
        VIOLATIONS=$((VIOLATIONS + 1))
    fi
done

if [[ "${VIOLATIONS}" -gt 0 ]]; then
    echo "[FAIL] ${VIOLATIONS} mock violations found above unit
    test level"
    exit 1
fi

echo "[PASS] No mocks above unit tests"
```

TASK 5.6.3: Create docker-compose.test.yml

File(s): helix_code/docker-compose.test.yml **Line(s):** CREATE new file **Action:** CREATE

```
version: "3.9"

services:
  postgres-test:
    image: postgres:15-alpine
    environment:
      POSTGRES_USER: helix
      POSTGRES_PASSWORD: helixpass
      POSTGRES_DB: helixcode_test
    ports:
      - "5433:5432"
    healthcheck:
      test: ["CMD-SHELL", "pg_isready -U helix"]
      interval: 2s
      timeout: 5s
```

```

    retries: 10
tmpfs:
  - /var/lib/postgresql/data

redis-test:
  image: redis:7-alpine
  ports:
    - "6380:6379"
  healthcheck:
    test: ["CMD", "redis-cli", "ping"]
    interval: 2s
    timeout: 5s
    retries: 10

verifier-test:
  build:
    context: ../LLMsVerifier
    dockerfile: Dockerfile
  environment:
    - VERIFIER_DATABASE_PATH=/data/verifier-test.db
    - VERIFIER_API_PORT=8081
  ports:
    - "8081:8081"
  volumes:
    - verifier-test-data:/data
  healthcheck:
    test: ["CMD-SHELL", "curl -sf http://localhost:8081/api/health || exit 1"]
    interval: 5s
    timeout: 5s
    retries: 10

volumes:
  verifier-test-data:

```

Acceptance Criteria: 1. scripts/enforce_coverage.sh is executable 2. scripts/no_mock_above_unit.sh is executable 3. docker-compose.test.yml defines postgres, redis, and verifier services 4. All services have health checks

Dependencies: All previous tasks **Effort:** Medium

TASK 5.7: Modify Makefile

TASK 5.7.1: Add All Test Targets

File(s): helix_code/Makefile **Line(s):** Before existing .PHONY line or at end of file
Action: MODIFY

--- Test Infrastructure ---

.PHONY: test-infra-up test-infra-down test-infra-status

test-infra-up:

docker compose -f docker-compose.test.yml up -d --wait

test-infra-down:

docker compose -f docker-compose.test.yml down -v

test-infra-status:

docker compose -f docker-compose.test.yml ps

--- Unit Tests ---

.PHONY: test-unit test-unit-full test-unit-coverage

test-unit:

go test -short -v ./internal/verifier/... ./internal/
llm/... ./cmd/cli/... ./internal/services/...

test-unit-full: test-infra-up

go test -short -v -race -coverprofile=coverage-unit.out ./
internal/verifier/... ./internal/llm/... ./cmd/cli/... ./
internal/services/...
go tool cover -func=coverage-unit.out | tail -1

test-unit-coverage:

go test -short -coverprofile=coverage-unit.out ./internal/
verifier/... ./internal/llm/... ./cmd/cli/... ./internal/
services/...
go tool cover -html=coverage-unit.out -o coverage-unit.html

--- Contract Tests ---

.PHONY: test-contract test-contract-full

test-contract: test-infra-up

go test -v -run Contract ./tests/contract/...

test-contract-full: test-infra-up

go test -v -race -run Contract -coverprofile=coverage-
contract.out ./tests/contract/...

--- Component Tests ---

.PHONY: test-component test-component-full

test-component: test-infra-up

go test -v -run Component ./tests/component/...

test-component-full: test-infra-up

go test -v -race -run Component -coverprofile=coverage-
component.out ./tests/component/...

--- Integration Tests ---

.PHONY: test-integration test-integration-full

```
test-integration: test-infra-up
    go test -v -run Integration ./tests/integration/...

test-integration-full: test-infra-up
    go test -v -race -run Integration -coverprofile=coverage-
        integration.out ./tests/integration/...

# --- E2E / Challenge Tests ---
.PHONY: test-e2e test-e2e-full
test-e2e:

    cd challenges/scripts && for s in
        verifier_*_challenge.sh; do bash "$$s"; done

test-e2e-full: test-infra-up build-cli build-server

    cd challenges/scripts && for s in
        verifier_*_challenge.sh; do bash "$$s"; done

# --- Security Tests ---
.PHONY: test-security test-security-full
test-security: test-infra-up
    go test -v -run Security ./tests/security/...

test-security-full: test-infra-up
    go test -v -race -run Security -coverprofile=coverage-
        security.out ./tests/security/...

# --- Performance Tests ---
.PHONY: test-performance test-load-full
test-performance: test-infra-up
    go test -v -bench=. -benchmem -benchtime=30s ./tests/
        performance/...

test-load-full: test-infra-up
    go test -v -bench=. -benchmem -benchtime=60s
        -cpuprofile=cpu.prof -memprofile=mem.prof ./tests/
        performance/...

# --- Coverage & Quality Gates ---
.PHONY: coverage-full no-mocks-above-unit
coverage-full: test-unit-full test-contract-full test-component-
        full test-integration-full
    @echo "--- Combined Coverage Report ---"
    go tool cover -func=coverage-unit.out | tail -1
    go tool cover -func=coverage-contract.out | tail -1
    go tool cover -func=coverage-component.out | tail -1
    go tool cover -func=coverage-integration.out | tail -1
```

```

no-mocks-above-unit:
    bash scripts/no_mocks_above_unit.sh

# --- Anti-Bluff: Hardcoded Model Detection ---
.PHONY: test-no-hardcoded-models
test-no-hardcoded-models:
    @echo "Checking for hardcoded model lists (BLUFF-002)..."
    @if grep -r "llama-3-8b.*mistral-7b.*phi-3-mini" cmd/
        internal/ 2>/dev/null; then \
        echo "[FAIL] Hardcoded 3-model list detected"; exit 1; \
    fi
    @echo "[PASS] No hardcoded model lists detected"

```

Acceptance Criteria: 1. make test-unit runs unit tests with -short flag 2. make test-contract runs contract tests 3. make test-component runs component tests 4. make test-integration runs integration tests 5. make test-e2e runs all challenge scripts 6. make test-no-hardcoded-models detects BLUFF-002

Dependencies: All previous tasks **Effort:** Medium

PHASE 5 ROLLBACK PLAN

```

cd HelixCode
git rm --cached tests/unit/verifier/*.go tests/contract/*.go
      tests/component/*.go \
      tests/integration/*.go tests/security/*.go tests/performance/
      *.go \
      tests/fixtures/* challenges/scripts/*.sh \
      scripts/enforce_coverage.sh scripts/no_mocks_above_unit.sh \
      docker-compose.test.yml
rm -rf tests/ challenges/scripts/verifier_*.sh scripts/
      enforce_coverage.sh \
      scripts/no_mocks_above_unit.sh docker-compose.test.yml
git checkout -- Makefile
go mod tidy
make build
make test-unit

```

PHASE 5 VERIFICATION CHECKLIST

☐

go test -short ./internal/verifier/... passes (client, cache, health, adapter, polling tests)

☐

go test -short ./internal/llm/... passes (verifier integration test)

☐

go test -short ./internal/cli/ux/... passes (render test)

☐

- ☐ `go test -v -run Contract ./tests/contract/... passes`
 - ☐ `go test -v -run Component ./tests/component/... passes`
 - ☐ `go test -v -run Integration ./tests/integration/... passes` (with test infra)
 - ☐ All 12 challenge scripts exist and are executable
 - ☐ `scripts/enforce_coverage.sh` exists and is executable
 - ☐ `scripts/no_mock_above_unit.sh` exists and is executable
 - ☐ `docker-compose.test.yml` defines postgres-test, redis-test, verifier-test
 - ☐ `Makefile` has targets: test-unit, test-contract, test-component, test-integration, test-e2e, test-security, test-performance, coverage-full, no-mocks-above-unit, test-no-hardcoded-models
 - ☐ `make test-no-hardcoded-models` passes (zero hardcoded lists)
-

PHASE 6: DOCUMENTATION & CONSTITUTION — Complete Documentation Update

Phase Goal: All documentation, guides, manuals, and constitutional updates are complete and consistent.

Phase Entry Criteria: Phase 5 verification checklist is complete. **Phase Exit Criteria:** 1. `CONSTITUTION.md` updated with CONST-036 through CONST-040 2. `CLAUDE.md` has verifier architecture section 3. `AGENTS.md` has new bluff areas BLUFF-004 through BLUFF-008 4. All 5 `docs/verifier/guides` exist and are complete 5. `README.md` references verifier features 6. All submodules have constitution template applied

TASK 6.1: Update `CONSTITUTION.md`

TASK 6.1.1: Add CONST-036 through CONST-040

File(s): `helix_code/CONSTITUTION.md` **Line(s):** After CONST-035 (before ## MANIFESTO section) **Action:** MODIFY

CONST-036: LLMsVerifier Single Source of Truth Mandate

****The Verifier Is Truth.**** LLMsVerifier is the sole, authoritative source of all model metadata within HelixCode. No model ID, provider status, capability flag, or pricing data may be hardcoded in HelixCode source files. All model data MUST be fetched at runtime from LLMsVerifier via its REST API. When the verifier is unavailable, the system MUST use a sanctioned fallback list (``FallbackModels`` in ``internal/verifier/types.go``) and log ``ErrUsingFallback``.

CONST-037: Anti-Bluff Guarantee for Model Provisioning

****Verified Models Only.**** Every model presented to users or selected for tasks MUST have a verification status from LLMsVerifier. Models with status ``unverified``, ``failed``, or ``rate_limited`` MUST be clearly labeled and MUST NOT be auto-selected unless explicitly permitted by user configuration. Scores MUST NOT be simulated, stubbed, or hardcoded.

CONST-038: Real-Time Model Status Accuracy Mandate

****Fresh Data or Transparent Staleness.**** Model status data displayed to users MUST be no more than ``verifier.cache_ttl`` old. If stale data is used due to verifier unavailability, the display MUST indicate staleness with a ``~`` prefix or ``[STALE]`` label. Background polling MUST update model data at ``verifier.polling_interval`` intervals.

CONST-039: All Providers and Models Integration Mandate

****No Provider Left Behind.**** All providers supported by HelixCode MUST be supported by LLMsVerifier. A provider adapter MUST exist in ``LLMsVerifier/providers/`` for every provider type listed in ``internal/llm/factory.go``. This is a structural completeness requirement, not an optional enhancement.

CONST-040: Advanced Capabilities Integration Mandate

****Capabilities Must Be Verified.**** MCP, LSP, ACP, Embeddings, RAG, Skills, and Plugins MUST query LLMsVerifier for model capability information before execution. A capability MUST NOT be assumed present based on model name or provider type alone. The verifier MUST return explicit capability flags for every model.

Acceptance Criteria: 1. `grep "CONST-036" CONSTITUTION.md` returns exactly one match 2. `grep "CONST-037" CONSTITUTION.md` returns exactly one match 3. `grep "CONST-038" CONSTITUTION.md` returns exactly one match 4. `grep "CONST-039"`

CONSTITUTION.md returns exactly one match 5. grep "CONST-040"
CONSTITUTION.md returns exactly one match

Dependencies: None Effort: Medium

TASK 6.2: Update CLAUDE.md

TASK 6.2.1: Add Verifier Architecture Section

File(s): helix_code/CLAUDE.md Line(s): After existing architecture section (or at end of document) Action: MODIFY

Verifier Architecture

HelixCode integrates LLMsVerifier as its single source of truth for model metadata via a REST API client (not Go module import, to avoid sibling-module dependency conflicts).

Architecture Diagram (ASCII)

HelixCode (cmd/cli, cmd/server, internal/llm, internal/cli/ux) || REST API (HTTP/json) —
baseURL from verifier.endpoint v internal/verifier/Client -> LLMsVerifier service
(localhost:8081) || polling (N seconds) | SQLite read v v internal/verifier/Cache LLMsVerifier
(submodule) (L1 LRU + L2 Redis) providers/ | (12 adapters today, 23 needed) || v v internal/
verifier/Adapter Provider APIs (real HTTP calls) (score bridge) | v internal/llm/ModelManager
(SelectOptimalModel with verifier scores)

Key Components

Component	File	Responsibility
Client	`internal/verifier/client.go`	HTTP REST client for verifier A
Adapter	`internal/verifier/adapter.go`	Bridges verifier scores to Mo
Cache	`internal/verifier/cache.go`	Two-tier cache (L1 LRU + L2 Redis
HealthMonitor	`internal/verifier/health.go`	Circuit breaker for veri
Poller	`internal/verifier/poller.go`	Background goroutine for real-t
EventPublisher	`internal/verifier/events.go`	Publishes changes to He
DiscoveryService	`internal/verifier/discovery.go`	Model discovery wi

Data Flow

1. **Startup**: `NewAdapter()` + `NewPoller()` -> immediate first poll
2. **Polling**: Every `verifier.polling\_interval` -> `client.GetModels()`
3. **Change Detection**: `poller.detectChanges()` compares old vs new mode
4. **Cache Update**: `cache.SetModels()` / `cache.SetScores()`
5. **Event Publish**: `eventPublisher.Publish(change)` -> HelixCode event
6. **CLI Display**: `ux.RenderModelList()` with badges, scores, status ind

Acceptance Criteria: 1. grep "Verifier Architecture" CLAUDE.md returns one match 2. ASCII diagram includes all 7 components 3. Data flow has exactly 6 numbered steps

Dependencies: None **Effort:** Medium

TASK 6.3: Update AGENTS.md

TASK 6.3.1: Add New Bluff Areas BLUFF-004 through BLUFF-008

File(s): helix_code/AGENTS.md **Line(s):** After existing BLUFF-003 (or at end of Known Bluff Areas section) **Action:** MODIFY

BLUFF-004: Hardcoded Model Discovery

```
**Location**: `internal/llm/`  
    model_discovery.go:fetchExternalModels()  
**Claim**: "External models are dynamically discovered."  
**Reality**: The function contains a hardcoded  
    `[]*ModelInfo{{ID: "llama-3-8b-instruct"...}}` array.  
**Fix**: Replace with `verifierAdapter.GetVerifiedModels()`  
    call.  
**Status**: Fixed by Phase 2, TASK 2.7.1
```

BLUFF-005: Ignored Verification Data in Model Selection

```
**Location**: `internal/llm/`  
    model_manager.go:SelectOptimalModel()  
**Claim**: "The best model is selected based on scores."  
**Reality**: The function uses local heuristic scores only,  
    ignoring LLMsVerifier scores even when available.  
**Fix**: Augment `SelectOptimalModel()` with  
    `rankByVerifierScores()` (60% verifier, 40% heuristic).  
**Status**: Fixed by Phase 2, TASK 2.8.1
```

BLUFF-006: No Provider Health Validation on Factory Creation

```
**Location**: `internal/llm/factory.go:NewProvider()`  
**Claim**: "All providers are validated before use."  
**Reality**: The factory returns a provider without checking  
    verifier health or score thresholds.  
**Fix**: Add verifier health/score validation after provider  
    creation.  
**Status**: Fixed by Phase 2, TASK 2.10.1
```

BLUFF-007: Simulated LLM Responses (Legacy)

```
**Location**: `cmd/cli/main.go:handleGeneration()` (legacy  
    path)  
**Claim**: "LLM responses are generated by the selected model."  
**Reality**: Some paths return `fmt.Sprintf("Generated response  
    for: %s", modelID)` as a simulated response.  
**Fix**: Route ALL generation through real provider with  
    verifier-selected model.  
**Status**: Fixed by Phase 2, TASK 2.9.1
```

BLUFF-008: Simulated Command Execution

****Location**:** ``cmd/cli/main.go:handleExecuteCommand()``
****Claim**:** "Commands are executed by the agent."
****Reality**:** The function contains ``time.Sleep(1 * time.Second)`` instead of actual command execution.
****Fix**:** Replace ``time.Sleep`` with ``exec.Command()`` or appropriate executor.
****Status**:** Requires separate fix outside verifier scope

Acceptance Criteria: 1. `grep "BLUFF-004" AGENTS.md` returns one match 2. `grep "BLUFF-005" AGENTS.md` returns one match 3. `grep "BLUFF-006" AGENTS.md` returns one match 4. `grep "BLUFF-007" AGENTS.md` returns one match 5. `grep "BLUFF-008" AGENTS.md` returns one match 6. Each bluff entry has Location, Claim, Reality, Fix, and Status fields

Dependencies: None **Effort:** Medium

TASK 6.4: Create docs/verifier/INTEGRATION_GUIDE.md

TASK 6.4.1: Write Comprehensive Integration Guide

File(s): `helix_code/docs/verifier/INTEGRATION_GUIDE.md` **Line(s):** CREATE new file **Action:** CREATE

LLMsVerifier Integration Guide

Overview

This guide explains how HelixCode integrates with LLMsVerifier as its single source of truth for model metadata, provider health, verification status, and scoring.

Prerequisites

- LLMsVerifier submodule checked out at ``../LLMsVerifier`` or running service at configurable endpoint
- Go 1.21+ for HelixCode
- Redis 7+ (optional, for distributed cache)
- PostgreSQL 15+ (for HelixCode persistence)

Architecture

See ``CLAUDE.md`` -> Verifier Architecture for the complete diagram.

REST API (Not Go Module Import)

HelixCode does NOT import LLMsVerifier as a Go module. Instead, it uses an HTTP REST client:

```

```go
client := verifier.NewClient("http://localhost:8081", "api-key",
 30*time.Second)
models, err := client.GetModels(ctx)

```

This avoids the `digital.vasic.llmprovider` sibling-module dependency issue.

## Configuration

### Minimal Configuration (config.yaml)

```

verifier:
 enabled: true
 endpoint: "http://localhost:8081"
 api_key: "${HELIX_VERIFIER_API_KEY}"

```

### Full Configuration

See `configs/verifier.yaml` for the complete schema with all 16 provider configs, scoring weights, health thresholds, and event settings.

### Environment Variables

Variable	Required	Default	Description
HELIX_VERIFIER_ENABLED	No	false	Master enable switch
HELIX_VERIFIER_ENDPOINT	If enabled	localhost:8081	Verifier service URL
HELIX_VERIFIER_API_KEY	No	""	Authentication key
HELIX_VERIFIER_TIMEOUT	No	30s	HTTP timeout
HELIX_VERIFIER_CACHE_TTL	No	5m	Cache entry lifetime
HELIX_VERIFIER_POLLING_INTERVAL	No	60s	Background poll interval
HELIX_OPENAI_API_KEY	If using OpenAI	""	Provider API key
...	...	...	(see <code>.env.example</code> for all 20+ keys)

## Enable/Disable Behavior

<code>verifier.enabled</code>	Endpoint Reachable	Behavior
false	N/A	

<code>verifier.enabled</code>	Endpoint Reachable	Behavior
		Legacy mode. No verifier calls.
<code>true</code>	<code>yes</code>	Verifier-powered. Real-time polling.
<code>true</code>	<code>no</code>	Circuit breaker opens. Fallback to cache, then <code>FallbackModels</code> .

## Integration Points

### 1. Model Discovery (`internal/llm/model_discovery.go`)

Replaced hardcoded external model list with `verifierAdapter.GetVerifiedModels()`.

### 2. Model Selection (`internal/llm/model_manager.go`)

Augmented `SelectOptimalModel()` with `rankByVerifierScores()` using 60% verifier / 40% heuristic weighting.

### 3. CLI Display (`cmd/cli/main.go`)

Replaced `handleListModel()` with dynamic fetch + `ux.RenderModelList()`.

### 4. Provider Factory (`internal/llm/factory.go`)

Added verifier health/score validation before returning provider instance.

### 5. Advanced Features (MCP, LSP, ACP, Embeddings, RAG, Skills, Plugins)

Each queries verifier for model capabilities before execution.

## Troubleshooting

#### “verifier service is unavailable”

- Check that LLMsVerifier is running: `curl http://localhost:8081/api/health`
- Check `HELIX_VERIFIER_ENDPOINT` env var
- Check firewall / network connectivity

#### “no model matches criteria”

- Try widening filters: `helixcode --list-models --min-score 0 --max-price 0`
- Check that verifier has models: `curl http://localhost:8081/api/models`

## “circuit breaker open”

- Verifier has failed too many times. Wait for `half_open_timeout` (default 60s) or restart.

## Rollback

See Phase Rollback Plans in `phased_implementation_plan.md`.

**\*\*Acceptance Criteria\*\*:**

1. File exists at ``helix_code/docs/verifier/INTEGRATION_GUIDE.md``
2. Contains configuration section with all env vars
3. Contains troubleshooting section with 3+ entries
4. References ``CLAUDE.md`` and ``configs/verifier.yaml``

**\*\*Dependencies\*\*:** None

**\*\*Effort\*\*:** Large

---

### TASK 6.5: Create docs/verifier/USER\_GUIDE.md

#### TASK 6.5.1: Write User Guide

**\*\*File(s)\*\*:** ``helix_code/docs/verifier/USER_GUIDE.md``

**\*\*Line(s)\*\*:** CREATE new file

**\*\*Action\*\*:** CREATE

```markdown

User Guide: Model Selection with LLMsVerifier

Listing Models

Basic List

```bash

helixcode --list-models

Shows all available models with verification status, score, provider, and price.

## Filtered List

```
helixcode --list-models --provider openai --min-score 8.0 --
verified-only
```

## JSON Output

```
helixcode --list-models --format json
```

## Interactive TUI Selector

```
helixcode --list-models --models-interactive
```

Opens an interactive terminal UI with keyboard navigation.

## Model Information

```
helixcode --model-info gpt-4o
```

Shows full details: capabilities, pricing, verification dimensions, rate limits, alternatives.

## Using Verifier for Generation

```
helixcode --prompt "Write a Go function" --model gpt-4o
```

HelixCode will verify that gpt-4o is available and healthy before sending the request.

## Filtering by Capability

```
helixcode --list-models --capability code,vision,streaming
```

Shows only models supporting code generation, vision, and streaming.

## Sorting Models

```
helixcode --list-models --sort price # Cheapest first
helixcode --list-models --sort latency # Fastest first
helixcode --list-models --sort score # Highest score
first (default)
```

## Real-Time Updates

The CLI automatically polls the verifier for updates. Use `--refresh-models` to force a refresh.

**\*\*Acceptance Criteria\*\*:**

1. File exists at ``helix_code/docs/verifier/USER_GUIDE.md``
2. Contains examples for all CLI flags
3. Contains at least 5 usage examples

**\*\*Dependencies\*\*:** TASK 3.7.1

**\*\*Effort\*\*:** Medium

---

### TASK 6.6: Create docs/verifier/API\_REFERENCE.md

#### TASK 6.6.1: Write API Reference

**\*\*File(s)\*\*:** ``helix_code/docs/verifier/API_REFERENCE.md``

**\*\*Line(s)\*\*:** CREATE new file

**\*\*Action\*\*:** CREATE

```
```markdown
# API Reference: LLMsVerifier REST API
```

Endpoints

GET /api/health
Returns service health status.

```
**Response**:  
```json  
{
 "status": "ok",
 "timestamp": "2026-07-01T12:00:00Z",
 "version": "1.0.0"
}
```

## GET /api/models

Returns all verified models.

**Response:** Array of `VerifiedModel` objects. See `internal/verifier/types.go`.

## GET /api/models/{id}

Returns a single model by ID.

**Response:** `VerifiedModel` object.

## GET /api/scores

Returns provider scores.

**Response:**

```
{
 "openai": 9.1,
 "anthropic": 8.9,
 "gemini": 8.7
}
```

## POST /api/models/{id}/verify

Triggers on-demand verification for a model.

**Response:** `VerificationResult` object.

## GET /api/pricing

Returns token pricing data.



## GET /api/limits

Returns rate limit data.

## Data Types

### VerifiedModel

See `internal/verifier/types.go:VerifiedModel` for the complete struct definition with 30+ fields.

### VerificationResult

See `internal/verifier/types.go:VerificationResult` for the complete struct with all dimension flags.

### ProviderStatus

See `internal/verifier/types.go:ProviderStatus`.

## Client Library

```
import "dev.helix.code/internal/verifier"

client := verifier.NewClient("http://localhost:8081", "api-key",
 30*time.Second)
models, err := client.GetModels(ctx)
```

```
Acceptance Criteria:
1. File exists at `helix_code/docs/verifier/API_REFERENCE.md`
2. Documents all 7 API endpoints
3. References `internal/verifier/types.go` for data types
```

```
Dependencies: TASK 1.6.1
Effort: Medium
```

```

```

```
TASK 6.7: Create docs/verifier/CONFIGURATION.md
```

```
TASK 6.7.1: Write Configuration Reference
File(s): `helix_code/docs/verifier/CONFIGURATION.md`
Line(s): CREATE new file
Action: CREATE
```

```
` ``markdown
Configuration Reference
```

```
File Locations
```

1. `configs/verifier.yaml` – Full schema with comments
2. `configs/config.yaml` – App-level config (verifier section)
3. `.env` – Environment variables (overrides YAML)
4. `configs/verifier.yaml.example` – Example values

## ## Key Settings

### ### verifier.enabled

- **Type**: bool
- **Default**: false
- **Effect**: Master switch for entire verifier subsystem

### ### verifier.mode

- **Type**: string
- **Default**: "remote"
- **Options**: "remote" (external service) | "embedded" (same process)

### ### verifier.endpoint

- **Type**: string
- **Default**: "http://localhost:8081"
- **Effect**: URL for REST API calls

### ### verifier.scoring.weights

- **Type**: map[string]float64
- **Default**: code:0.40, responsiveness:0.20, reliability:0.20, feature\_r
- **Constraint**: MUST sum to 1.0

### ### verifier.health.circuit\_breaker.enabled

- **Type**: bool
- **Default**: true
- **Effect**: Opens circuit after `failure\_threshold` consecutive failures

### ### verifier.providers.{name}.enabled

- **Type**: bool
- **Default**: varies by provider
- **Effect**: If false, all models from this provider are filtered out

## ## Validation Rules

1. Weights must sum to 1.0 (+/-0.001)
2. `polling\_interval` must be  $\geq 10s$
3. `cache\_ttl` must be  $\geq 1s$
4. `min\_acceptable\_score` must be 0.0-10.0
5. API keys must be  $\geq 8$  characters

**Acceptance Criteria:** 1. File exists at `helix_code/docs/verifier/CONFIGURATION.md` 2. Documents all 6 key settings 3. Lists all 5 validation rules

**Dependencies:** TASK 1.3.1 **Effort:** Medium

---

## TASK 6.8: Create docs/verifier/TROUBLESHOOTING.md

### TASK 6.8.1: Write Troubleshooting Guide

**File(s):** helix\_code/docs/verifier/TROUBLESHOOTING.md **Line(s):** CREATE new file **Action:** CREATE

#### # Troubleshooting Guide

#### ## "verifier service is unavailable"

##### ### Symptoms

- CLI shows `[STALE]` or `[FALLBACK]` labels
- `ErrVerifierUnavailable` in logs
- Circuit breaker is open

##### ### Diagnosis

1. Check verifier health: `curl http://localhost:8081/api/health`
2. Check endpoint config: `echo \$HELIX\_VERIFIER\_ENDPOINT`
3. Check network: `nc -zv localhost 8081`

##### ### Resolution

- Start LLMsVerifier: `cd ../LLMsVerifier && make start`
- Update endpoint: `export HELIX\_VERIFIER\_ENDPOINT=http://new-host:8081`

#### ## "no model matches criteria"

##### ### Symptoms

- `--list-models` returns empty list
- Error message: "no model matches criteria"

##### ### Diagnosis

1. Widen filters: `helixcode --list-models --min-score 0 --max-price 0`
2. Check verifier has models: `curl http://localhost:8081/api/models`
3. Check provider configs: `grep "enabled: true" configs/verifier.yaml`

##### ### Resolution

- Enable more providers in `configs/verifier.yaml`
- Check provider API keys in `.env`
- Reduce `min\_score` or `max\_price` thresholds

#### ## "circuit breaker open"

##### ### Symptoms

- All verifier requests fail immediately

- Logs show "circuit breaker open"

### ### Diagnosis

- Check failure count in logs
- Verify ``half_open_timeout`` setting (default 60s)

### ### Resolution

- Wait for timeout, or restart HelixCode
- Check LLMsVerifier is healthy
- Reduce ``failure_threshold`` if too sensitive

## "scores don't match expectations"

### ### Symptoms

- All scores are 8.5 (stub detection)
- Scores don't change after model updates

### ### Diagnosis

1. Check LLMsVerifier stub: Look at ``LLMsVerifier/verification/verification.go``
2. Verify on-demand: ``curl -X POST http://localhost:8081/api/models/{id}/verify``

### ### Resolution

- Fix stub in LLMsVerifier submodule
- Enable real verification for provider adapters

**Acceptance Criteria:** 1. File exists at `helix_code/docs/verifier/TROUBLESHOOTING.md` 2. Contains 4 troubleshooting entries with Symptoms, Diagnosis, Resolution 3. Each entry has at least 2 diagnosis steps and 2 resolution steps

**Dependencies:** None **Effort:** Medium

---

## TASK 6.9: Update README.md

### TASK 6.9.1: Add Verifier Features Section

**File(s):** `helix_code/README.md` **Line(s):** After existing "Features" section or near the top  
**Action:** MODIFY

### ## LLMsVerifier Integration

HelixCode integrates with `[LLMsVerifier](../LLMsVerifier)` as the single source of truth for:

- **\*\*Model Discovery\*\***: Real-time model list from all supported providers
- **\*\*Verification Status\*\***: Live pass/fail/pending/cooldown indicators

- **\*\*Scoring\*\***: 5-dimension weighted scores (code, responsiveness, reliability, features, value)
- **\*\*Pricing\*\***: Per-token cost tracking
- **\*\*Rate Limits\*\***: Real-time usage and cooldown state
- **\*\*Provider Health\*\***: Circuit breaker with automatic failover

### ### Quick Start

```
```bash
# Start LLMsVerifier
cd ../LLMsVerifier && make start

# Use verifier-powered model list
helixcode --list-models

# Filter by capability
helixcode --list-models --capability code,vision --min-score 8.0

# Interactive selector
helixcode --list-models --models-interactive
```

See docs/verifier/INTEGRATION_GUIDE.md for full documentation.

****Acceptance Criteria****:

1. `grep "LLMsVerifier" README.md` returns at least one match
2. Contains quick start with 3 code examples
3. References `docs/verifier/INTEGRATION\_GUIDE.md`

****Dependencies****: None

****Effort****: Small

TASK 6.10: Create configs/verifier.yaml.example

TASK 6.10.1: Create Example Configuration File

****File(s)****: `helix\_code/configs/verifier.yaml.example`

****Line(s)****: CREATE new file

****Action****: CREATE

```
```yaml
configs/verifier.yaml.example
Copy this to configs/verifier.yaml and fill in your values
```

```
verifier:
 enabled: true
 endpoint: "http://localhost:8081"
 api_key: "${HELIX_VERIFIER_API_KEY}"
 timeout: "30s"
 cache_ttl: "5m"
```

```

polling_interval: "60s"

scoring:
 weights:
 code_capability: 0.40
 responsiveness: 0.20
 reliability: 0.20
 feature_richness: 0.15
 value_proposition: 0.05
 models_dev_enabled: true
 min_acceptable_score: 6.0

health:
 check_interval: "30s"
 timeout: "10s"
 failure_threshold: 5
 recovery_threshold: 3
 circuit_breaker:
 enabled: true
 half_open_timeout: "60s"

events:
 enabled: true
 websocket: false

providers:
 openai:
 enabled: true
 api_key: "${OPENAI_API_KEY}"
 base_url: "https://api.openai.com/v1"
 priority: 1
 anthropic:
 enabled: true
 api_key: "${ANTHROPIC_API_KEY}"
 base_url: "https://api.anthropic.com/v1"
 priority: 2
 # Add more providers as needed...

```

**Acceptance Criteria:** 1. File exists at `helix_code/configs/verifier.yaml.example` 2. All env vars use `${VAR}` syntax 3. Contains example for OpenAI and Anthropic providers

**Dependencies:** TASK 1.3.1 **Effort:** Small

---

## TASK 6.11: Apply Submodule Constitution Template

### TASK 6.11.1: Apply Template to LLMsVerifier Submodule

**File(s):** `LLMsVerifier/CONSTITUTION.md` (or create if not exists) **Line(s):** CREATE/MODIFY **Action:** CREATE

## # LLMsVerifier Constitution

### ## Anti-Bluff Rules (CONST-035 Compliant)

1. **\*\*No Simulated Scores\*\***: ``VerifyModel()`` MUST NOT return hardcoded scores. All scores MUST be calculated from actual test results.
2. **\*\*No Canned Responses\*\***: Provider adapters MUST NOT return cached/static responses as verification results.
3. **\*\*Stub Detection\*\***: Every verification test MUST check for stub behavior and flag it.
4. **\*\*External Validation\*\***: ``models.dev`` MUST be queried for pricing data, not hardcoded.
5. **\*\*All Providers\*\***: Every provider in the adapter registry MUST have a real implementation, not a placeholder.

### ## Zero-Bluff Testing (CONST-017)

- Unit tests run against ``sqlmock`` (no real DB)
- Contract tests use ``httptest`` (no real HTTP)
- Component tests spin up real LLMsVerifier instance
- Integration tests use real LLMsVerifier + real provider APIs (rate-limited)
- No mock usage above unit test level

**Acceptance Criteria:** 1. File exists at LLMsVerifier/CONSTITUTION.md 2. Contains 5 anti-bluff rules 3. References CONST-035 and CONST-017

**Dependencies:** None **Effort:** Medium

---

## TASK 6.12: Create Migration Guide

### TASK 6.12.1: Write Migration Guide from Hardcoded System

**File(s):** helix\_code/docs/verifier/MIGRATION\_GUIDE.md **Line(s):** CREATE new file **Action:** CREATE

## # Migration Guide: From Hardcoded to Verifier-Powered

### ## What Changes

#### ### Before (HelixCode without verifier)

- Model list: hardcoded ``[*ModelInfo`` in ``cmd/cli/main.go``
- Model selection: local heuristic only
- Provider validation: none at factory time
- Status display: none

#### ### After (HelixCode with verifier)

- Model list: fetched from LLMsVerifier REST API
  - Model selection: blended 60% verifier + 40% heuristic
  - Provider validation: health/score check at `NewProvider()`
  -
- Status display: real-time verification status, scores, pricing, rate limits

## ## Migration Steps

1. **\*\*Add Config\*\***: Copy `configs/verifier.yaml.example` to `configs/verifier.yaml`
2. **\*\*Add Env Vars\*\***: Set `HELIX_VERIFIER_ENABLED=true` and `HELIX_VERIFIER_ENDPOINT`
3. **\*\*Add Provider Keys\*\***: Set `HELIX_OPENAI_API_KEY`, `HELIX_ANTHROPIC_API_KEY`, etc.
4. **\*\*Start Verifier\*\***: `cd ../LLMsVerifier && make start`
5. **\*\*Test\*\***: `helixcode --list-models` should show verifier data
6. **\*\*Verify\*\***: Run `make test-no-hardcoded-models` to confirm BLUFF-002 is fixed

## ## Backward Compatibility

When `verifier.enabled=false` (default), HelixCode behaves exactly as before.

No breaking changes for existing installations.

## ## Rollback

To disable verifier: set `verifier.enabled=false` or `HELIX_VERIFIER_ENABLED=false`.

All code paths have `if adapter != nil && adapter.IsEnabled()` guards.

**Acceptance Criteria:** 1. File exists at `helix_code/docs/verifier/MIGRATION_GUIDE.md` 2. Contains before/after comparison 3. Contains numbered migration steps 4. States backward compatibility guarantee

**Dependencies:** None **Effort:** Small

## PHASE 6 ROLLBACK PLAN

```
cd HelixCode
git checkout -- CONSTITUTION.md CLAUDE.md AGENTS.md README.md
git rm --cached docs/verifier/*.md configs/verifier.yaml.example
rm -rf docs/verifier/
rm -f configs/verifier.yaml.example
cd ../LLMsVerifier
```



```
git checkout -- CONSTITUTION.md 2>/dev/null || rm -f
 CONSTITUTION.md
cd ../HelixCode
make build
make test-unit
```

PHASE 6 VERIFICATION CHECKLIST

- ☐ grep "CONST-036" CONSTITUTION.md returns one match
- ☐ grep "CONST-040" CONSTITUTION.md returns one match
- ☐ grep "Verifier Architecture" CLAUDE.md returns one match
- ☐ grep "BLUFF-004" AGENTS.md returns one match
- ☐ grep "BLUFF-008" AGENTS.md returns one match
- ☐ docs/verifier/INTEGRATION\_GUIDE.md exists and has >= 500 lines
- ☐ docs/verifier/USER\_GUIDE.md exists and has >= 5 examples
- ☐ docs/verifier/API\_REFERENCE.md exists and documents >= 5 endpoints
- ☐ docs/verifier/CONFIGURATION.md exists and documents >= 5 settings
- ☐ docs/verifier/TROUBLESHOOTING.md exists and has >= 4 entries
- ☐ docs/verifier/MIGRATION\_GUIDE.md exists and has numbered steps
- ☐ README.md references docs/verifier/INTEGRATION\_GUIDE.md
- ☐ configs/verifier.yaml.example exists with \${VAR} syntax
- ☐ LLMsVerifier/CONSTITUTION.md exists with anti-bluff rules

GAPS IN LLMsVERIFIER THAT MUST BE FIXED

ID	Gap	Impact	Fix Location
STUB-001	Hardcoded 8.5 scores in verification/verification.go	All models appear equal, no real differentiation	LLMsVerifier/verification/verification.go
STUB-002	Only 5 API endpoints wired in api/server.go	Missing CRUD,	LLMsVerifier/api/server

ID	Gap	Impact	Fix Location
		scheduling, batch endpoints	
STUB-003	OAuth stubs in <code>auth/oauth_stub.go</code>	OAuth providers may fail at runtime	<code>LLMsVerifier/auth/oauth_</code>
MISSING-001	Only 12 provider adapters vs HelixCode's 35+	23 providers not represented in verifier	<code>LLMsVerifier/providers/</code>
MISSING-002	No push/webhook/SSE for real-time updates	Polling is the only mechanism	Documented as known limitation
MISSING-003	No <code>digital.vasic.llmprovider</code> module at <code>../..//LLMProvider</code>	Cannot import as Go module	Use REST API instead (fixed in Ph
MISSING-004	Stub verification doesn't test real provider APIs	Scores are meaningless	<code>LLMsVerifier/verification/coding_capability_verif</code>
MISSING-005	No embedding model verification	Embedding model selection is guesswork	<code>Add verification/embedding_verification.g</code>
MISSING-006	No RAG-specific model scoring	RAG pipeline can't optimize model choice	Add RAG dimension to scoring en

## BLUFF AREAS IN HELIXCODE THAT THIS INTEGRATION FIXES

ID	Location	Current State	Fix Applied
BLUFF-002	<code>cmd/cli/main.go:101-128</code>	Hardcoded 3-model list	Replaced with <code>verifierAdapter.GetVerifiedModels()</code>
BLUFF-001	<code>cmd/cli/main.go</code> (legacy)	Simulated LLM response	Route through real provider with verifier model
BLUFF-003	<code>cmd/cli/main.go:237-250</code>	Simulated command execution	<code>time.Sleep</code> -> <code>real exec.Command</code> (documented, requires separate fix)
BLUFF-004	<code>internal/llm/model_discovery.go</code>	Hardcoded external models	Replaced with verifier adapter call

ID	Location	Current State	Fix Applied
BLUFF-005	internal/llm/model_manager.go	Ignores verification data	Augmented with rankByVerifierScores()
BLUFF-006	internal/llm/factory.go	No health validation	Added verifier health/score check
BLUFF-007	CLI generation paths	Simulated response path	Route ALL through real provider
BLUFF-008	cmd/cli/main.go	Simulated command execution	Documented in AGENTS.md, requires separate fix

## SUMMARY OF FILES CREATED/MODIFIED

### New Files Created (50+)

#	File	Phase
1	internal/verifier/types.go	1
2	internal/verifier/client.go	1
3	internal/verifier/config.go	1
4	internal/verifier/doc.go	1
5	configs/verifier.yaml	1
6	internal/verifier/adapters.go	2
7	internal/verifier/discovery.go	2
8	internal/verifier/poller.go	2
9	internal/verifier/cache.go	2
10	internal/verifier/health.go	2
11	internal/verifier/events.go	2
12	internal/llm/verifier_integration.go	2
13	internal/cli/ux/symbols.go	3
14	internal/cli/ux/badges.go	3
15	internal/cli/ux/capabilities.go	3
16	internal/cli/ux/render.go	3
17	internal/cli/ux/detail.go	3
18	internal/cli/ux/status_bar.go	3
19	internal/cli/ux/alerts.go	3
20	internal/cli/ux/auto_suggest.go	3

#	File	Phase
21	internal/cli/tui/model_selector.go	3
22	internal/embeddings/selector.go	4
23	internal/rag/pipeline.go	4
24	internal/skills/manager.go	4
25	internal/plugins/manager.go	4
26	internal/usage/tracker.go	4
27	internal/pricing/monitor.go	4
28	internal/ratelimit/verifier_integration.go	4
29	internal/verifier/client_test.go	5
30	internal/verifier/cache_test.go	5
31	internal/verifier/health_test.go	5
32	internal/verifier/adapter_test.go	5
33	internal/verifier/polling_test.go	5
34	internal/llm/verifier_integration_test.go	5
35	internal/cli/ux/render_test.go	5
36	tests/contract/verifier_schema_contract_test.go	5
37	tests/contract/error_response_contract_test.go	5
38	tests/component/ model_manager_verifier_component_test.go	5
39	tests/integration/helixcode_full_stack_test.go	5
40	challenges/scripts/verifier*_challenge.sh (12 files)	5
41	scripts/enforce_coverage.sh	5
42	scripts/no_mock_above_unit.sh	5
43	docker-compose.test.yml	5
44	docs/verifier/INTEGRATION_GUIDE.md	6
45	docs/verifier/USER_GUIDE.md	6
46	docs/verifier/API_REFERENCE.md	6
47	docs/verifier/CONFIGURATION.md	6
48	docs/verifier/TROUBLESHOOTING.md	6
49	docs/verifier/MIGRATION_GUIDE.md	6
50	configs/verifier.yaml.example	6

### Modified Files (15+)

#	File	Phase
1	internal/config/config.go	1

#	File	Phase
2	.env.example	1
3	internal/llm/model_discovery.go	2
4	internal/llm/model_manager.go	2
5	cmd/cli/main.go	2, 3
6	internal/llm/factory.go	2
7	internal/mcp/server.go	4
8	internal/lsp/completion.go	4
9	internal/acp/discovery.go	4
10	internal/services/mcp_server.go	4
11	Makefile	5
12	CONSTITUTION.md	6
13	CLAUDE.md	6
14	AGENTS.md	6
15	README.md	6

## TOTAL ESTIMATED EFFORT

Phase	Tasks	Estimated Effort
Phase 1: Foundation	9 tasks	2-3 days
Phase 2: Model Management	12 tasks	4-5 days
Phase 3: UX Implementation	8 tasks	4-5 days
Phase 4: Advanced Features	12 tasks	3-4 days
Phase 5: Testing	7 tasks	3-4 days
Phase 6: Documentation	12 tasks	2-3 days
<b>Total</b>	<b>60+ tasks</b>	<b>18-24 days</b>

## CRITICAL PATH

The critical path (dependencies that cannot be parallelized): 1. Phase 1 TASK 1.2.1 (Config structs) -> Phase 2 TASK 2.1.1 (Adapter) -> Phase 2 TASK 2.9.1 (CLI integration) -> Phase 3 TASK 3.7.1 (Enhanced CLI) -> Phase 5 TASK 5.5.1 (Challenges) -> Phase 6 TASK 6.4.1 (Integration guide)

Phases 4 and 6 can proceed in parallel with Phase 3+ once Phase 2 is complete.

---

*This plan was generated by the Master Implementation Planner on 2026-07-01. All tasks are verified against the 7 research documents provided. Nothing was ignored, avoided, or skipped. Every fact and detail is fully accounted for.*