

bank-classification

HXC-029 — HelixQA Bank manual - review-required Deep-Classification

Field	Value
Revision	1
Created	2026-05-29
Last modified	2026-05-29
Status	active
Tracked item	HXC-029 (§11.4.98 full-automation anti-bluff forward sweep)
Pass type	Static source-read + JSON action-type analysis. NO tests executed. NO bank/test source modified.
Predecessor	docs/qa/HXC-029/compliance-ledger.md (flagged these 19 banks NEEDS-MANUAL-REVIEW)

Method

§11.4.98(C) requires live tests to be self-driving (no human action during execution). §11.4.98(F): manual-dependency tests not rewritten within 30 days graduate to §11.4.90 Obsolete. The prior ledger flagged 19 HelixQA banks under `helix_qa/banks/` carrying `_conversion_note: "manual-review-required"` steps as NEEDS-MANUAL-REVIEW (not confirmed violations).

This pass classifies each bank by (1) the **action content** of every `manual-review-required` step — what action type it carries (`playwright:`, `http:`, `adb_shell:`, `prose-with-no-prefix`) and what the prose describes (API call / CLI run / UI tap / browser action), to decide whether it COULD be driven programmatically; and (2) the **executor's runtime behaviour** for those steps, to decide whether any false PASS occurs today.

Executor semantics established (anti-bluff, cited)

- `helix_qa/pkg/testbank/schema.go:285-320` — `ParseAction` recognises a step as executable only when it carries a known type: prefix (`adb_shell:`, `shell:`, `http:`, `playwright:`, `tap:`, etc.); everything else falls through to `ActionTypeDescription` (`schema.go:319-320`).
- `helix_qa/pkg/autonomous/structured_executor.go:575-587` — an `ActionTypeDescription` step that begins `# CONVERT: Convert to executable is SKIPPED`; **any other prose returns** `Success:false` → **FAILS** (lines 586-587: `"Text-only action - not executable!"`). So `prose-with-no-prefix`

does NOT silently SKIP in the structured executor — it FAILS. (Correction to the prior ledger’s “executor SKIPs unrecognised prose” for the structured-executor path.)

- `structured_executor.go:551-573` — `ActionTypePlaywright` steps SKIP with SKIP-OK: `#PLAYWRIGHT-RUNTIME-PENDING` when no CDP URL is configured (honest skip).
- **Across all 19 banks:** `# CONVERT : -prefixed actions = 0` (grep, this pass). So none of the prose steps hit the SKIP branch — they would FAIL if the structured executor ran them.

Why no false PASS occurs today (load-path analysis, cited)

- Default executor banks dir is `challenges/helixqa-banks` (`helix_qa/cmd/helixqa/main.go:655-657`), and the structured-executor fallback alt-dir is the SAME path (`structured_executor.go:99-102`). `challenges/helixqa-banks` **does not exist / is empty** (verified this pass) — so the autonomous structured executor loads ZERO of these 19 banks by default.
- The 19 banks under `helix_qa/banks/` are loaded ONLY on an explicit `-banks` flag (`main.go:112,258`) / `config.Banks` (`pkg/config/config.go:69`), or by the one Go test that targets a single bank file directly.
- That test — `helix_qa/pkg/autonomous/bank_realbinary_test.go:74` — loads ONLY `full-qa-api.json`, evaluates ONLY `ActionTypeHTTP` steps (continues past all prose/playwright at lines 99-101), runs against a REAL server, and SKIPs honestly when the server is unreachable (`bank_realbinary_test.go:62,67` → SKIP-OK: `#BLUFF-HELIXQA-BANKS-REWRITE-001`). The prose manual-review-required steps are simply not executed by it.

Net: today these prose steps produce NO false PASS — they are either not loaded (default path) or skipped-by-action-type (realbinary test). They are a “looks-covered-but-doesn’t-run” surface (a §11.4 coverage gap), not a live §11.4.98(C) manual-intervention-during-execution violation. The existing tracker ticket for the rewrite is `#BLUFF-HELIXQA-BANKS-REWRITE-001`.

Classification rubric

- **AUTO-EXECUTABLE-WITH-WORK** — the steps describe actions drivable programmatically (server API call, shell/CLI run, headless browser, adb/uiauto) with reasonable effort. Candidate for rewrite to `http://assert:/shell:/playwright:/adb_shell:actions`.
- **GENUINELY-MANUAL** — a step intrinsically needs a human decision/observation no automation can supply. Candidate for §11.4.90 Obsolete citing §11.4.98(F).
- **ALREADY-SKIPPED-HONESTLY** — executor skips with a clear reason, no false PASS, low priority.

Classification table

Bank (path)	#manual-review steps	Action-type mix	Classification	Evidence (file:line)
<code>helix_qa/banks/full-qa-web.json</code>	572	prose=413, playwright=159	AUTO-EXECUTABLE-WITH-WORK	<code>full-qa-web.json:24</code> <code>playwright: navigate</code> <code>localhost:3000/login</code> “Check for Catalogizer logo” DOM assertion

Bank (path)	#manual-review steps	Action-type mix	Classification	Evidence (file:line)
helix_qa/banks/atmosphere.json	423	prose=366, playwright=42, adb_shell=15	AUTO-EXECUTABLE-WITH-WORK	atmosphere.json carries adb_shell:+playwright; prose are UI/device steps
helix_qa/banks/full-qa-android.json	318	prose=289, playwright=24, adb_shell=3, keypress=2	AUTO-EXECUTABLE-WITH-WORK	full-qa-android.json; adb_shell;; prose are Android
helix_qa/banks/performance-validation.json	116	prose=110, playwright=6	AUTO-EXECUTABLE-WITH-WORK	performance-validation.json:10 “Send 3 GET /api/v1/health r “Ensure at least 500 entities r
helix_qa/banks/storage-configuration.json	88	prose=88	AUTO-EXECUTABLE-WITH-WORK	storage-configuration.json:1 “Tap/click ‘Add WebDAV se username ‘testuser’...”
helix_qa/banks/cli-agents-comprehensive.json	79	prose=79	AUTO-EXECUTABLE-WITH-WORK	cli-agents-comprehensive.json:1 registry.GetStats()”, “Iterate AllAgentTypes()”
helix_qa/banks/edge-cases-stress.json	78	prose=78	AUTO-EXECUTABLE-WITH-WORK	edge-cases-stress.json:1 10 different text files in separ “Click/tap tabs 1,10,20”
helix_qa/banks/aichat-bash-tools-comprehensive.json	72	prose=72	AUTO-EXECUTABLE-WITH-WORK	aichat-bash-tools-comprehensive.json:1 helixagent –generate-agent-c
helix_qa/banks/cli-agents-test-helixagent.json	71	prose=71	AUTO-EXECUTABLE-WITH-WORK	cli-agents-test-helixagent.json:158 helixagent/ensemble –archite
helix_qa/banks/editor-operations.json	63	prose=63	AUTO-EXECUTABLE-WITH-WORK	editor-operations.json:1 “Create a new .txt file”, “Typ Yole!...””
helix_qa/banks/cloud-storage-operations.json	63	prose=63	AUTO-EXECUTABLE-WITH-WORK	cloud-storage-operations.json:4 “O selector, choose WebDAV se
helix_qa/banks/file-browser.json	61	prose=61		file-browser.json:2 browser icon or Files tab”

Bank (path)	#manual-review steps	Action-type mix	Classification	Evidence (file:line)
			AUTO-EXECUTABLE-WITH-WORK	
helix_qa/banks/app-navigation.json	54	prose=54	AUTO-EXECUTABLE-WITH-WORK	app-navigation.json Yole application”, “Tap/click bottom navigation”
helix_qa/banks/security-validation.json	41	prose=41	AUTO-EXECUTABLE-WITH-WORK	security-validation “Use a JWT token with exp o past”; “Sign a JWT with a di key”
helix_qa/banks/all-formats.json	40	prose=40	AUTO-EXECUTABLE-WITH-WORK	all-formats.json:31 new .md file”, “Type ‘# Title
helix_qa/banks/entity-management.json	38	prose=34, playwright=4	AUTO-EXECUTABLE-WITH-WORK	entity-management.j “POST 5 episodes with paren ID”
helix_qa/banks/full-qa-cross-platform.json	37	prose=37	AUTO-EXECUTABLE-WITH-WORK	full-qa-cross-platfo “Navigate to login page, ente admin123, click Login”
helix_qa/banks/admin-operations.json	29	prose=29	AUTO-EXECUTABLE-WITH-WORK	admin-operations.js scan status until complete”, “ backup file exists and has no
helix_qa/banks/full-qa-api.json	27	prose=26, http=1	ALREADY-SKIPPED-HONESTLY (+ AUTO-EXECUTABLE-WITH-WORK remainder)	71_skip:true w/ reasons api.json e.g. #BLUFF-H LOGOUT-CASCADE-001); runs HTTP steps only + skips (bank_realbinary_tes

Counts by classification

Classification	#banks	Banks
AUTO-EXECUTABLE-WITH-WORK	18	full-qa-web, atmosphere, full-qa-android, performance- validation, storage- configuration, cli-agents- comprehensive, edge-cases- stress, aichat-bash-tools- comprehensive, cli-agents-

Classification	#banks	Banks
		test-helixagent, editor-operations, cloud-storage-operations, file-browser, app-navigation, security-validation, all-formats, entity-management, full-qa-cross-platform, admin-operations
GENUINELY-MANUAL	0	— (no sampled step intrinsically requires a human decision; all are API/CLI/UI/browser actions drivable programmatically)
ALREADY-SKIPPED-HONESTLY	1 (primary)	full-qa-api (HTTP path verified + skipped honestly; also has the most explicit <code>_skip</code> markers). Note: ALL 19 banks are currently NOT in the default executor load path, so none produce a false PASS today.

Sub-grouping of the 18 AUTO-EXECUTABLE banks by drive mechanism (rewrite cost):

- **Server-API** (`http:assert:`) — **lowest cost, no GUI/device needed (5)**: full-qa-api, performance-validation, security-validation, entity-management, admin-operations.
- **CLI/shell** (`shell:`) — **low cost, needs a running endpoint (3)**: cli-agents-comprehensive, aichat-bash-tools-comprehensive, cli-agents-test-helixagent.
- **Web browser** (`playwright:`) — **needs Playwright CDP runtime (3)**: full-qa-web, full-qa-cross-platform, (web portion of) atmosphere/entity-management.
- **Desktop/Android GUI** (`adb_shell:/tap:/text: +uiauto`) — **highest cost (7)**: atmosphere, full-qa-android, storage-configuration, edge-cases-stress, editor-operations, cloud-storage-operations, file-browser, app-navigation, all-formats (overlap across topologies).

Anti-bluff caveat (§11.4.6)

- **No GENUINELY-MANUAL bank was found**, but this is a static action-content judgement. It is **UNCONFIRMED** whether every GUI step has a reachable uiautomator node (empty hierarchies force the §11.4.48/§11.4.52 APK/intent fallback) — provable only by running against a real device/emulator, which this pass did not do. None is classified GENUINELY-MANUAL on that uncertainty; the GUI banks are AUTO-EXECUTABLE-WITH-WORK with this caveat recorded.
- The “no false PASS today” finding is grounded in the load-path analysis above (default dir empty + realbinary test skips honestly). If a future runner is pointed at `helix_qa/banks/` directly via `-banks`, the structured executor would FAIL the prose steps (`structured_executor.go: 586-587`), not silently PASS them — still anti-bluff-safe, but noisy. Wiring them to a real runner before converting prose would manufacture failures; convert first.

Prioritized worklist (rewrite, not obsolete)

Because **0 banks are GENUINELY-MANUAL**, the §11.4.90 Obsolete path does NOT apply to any of the 19 — every bank is a rewrite candidate, not an obsolete candidate. Rewrite order favours lowest cost + highest coverage value first:

1. `full-qa-api.json (27)` + `entity-management.json (38 skips)` + `admin-operations.json (29)` + `security-validation.json (41)` + `performance-validation.json (116)` — pure server-API. Convert prose to `http:assert:` (no GUI/device). `full-qa-api` already half-verified by `bank_realbinary_test.go`; extend that pattern. Closes #BLUFF-HELIXQA-BANKS-REWRITE-001.
2. `**cli-agents-comprehensive.json (79)` + `aichat-bash-tools-comprehensive.json`
 1. `cli-agents-test-helixagent.json (71)**` — CLI/Go-API. Convert to `shell:` (or fold Go-API steps into `helix_code` integration tests). High step-count, deterministic, no GUI.
3. `full-qa-web.json (572)` + `full-qa-cross-platform.json (37)` — wire the Playwright CDP runtime (`structured_executor.go:551-573`), then convert the 413 prose web steps to `playwright:assert:`. Largest single coverage block.
4. `full-qa-android.json (318)` + `atmosphere.json (423)` — Android GUI. Convert prose to `adb_shell:/tap:/keypress:` with §11.4.48 `uiautomator` dispatch + §11.4.3 topology gating; real device/emulator.
5. **Desktop/Yole-GUI banks:** `storage-configuration (88)`, `edge-cases-stress (78)`, `editor-operations (63)`, `cloud-storage-operations (63)`, `file-browser (61)`, `app-navigation (54)`, `all-formats (40)` — convert GUI prose to `tap:/text:/adb_shell:` (or backend `http:` where a UI step has a server equivalent). Highest per-step cost; batch by shared Yole UI surface.

Sources verified

Internal source-of-truth files read during this audit (static code audit — no external web sources):
- `helix_qa/pkg/testbank/schema.go` (ActionType taxonomy, ParseAction, _skip/_skip_reason) - `helix_qa/pkg/autonomous/structured_executor.go` (step dispatch: Playwright SKIP, prose FAIL, placeholder-skip)
- `helix_qa/pkg/autonomous/pipeline.go` (BanksDir wiring) - `helix_qa/cmd/helixqa/main.go` (default BanksDir = `challenges/helixqa-banks`) - `helix_qa/pkg/autonomous/bank_realbinary_test.go` (only HTTP steps run; honest skip) - all 19 `helix_qa/banks/*.json` (JSON action-type distribution of manual-review-required steps) - `docs/qa/HXC-029/compliance-ledger.md` (predecessor ledger)