

ledger

HXC-029 §11.4.98 — Integration-Test Manual-Dependency Classification Ledger

Metadata	Value
Revision	1
Created	2026-05-29
Last modified	2026-05-29
Status	active
Ticket	HXC-029 (§11.4.98(F) full-automation anti-bluff — integration-test half)
Scope	helix_code/tests/integration/ ** (31 *_test.go files)
Live infra	http://localhost:8080 (health=200, register reachable), PostgreSQL :5432, Redis :6379 — all confirmed listening
Go	go1.26.2 (inner module dev.helix.code)

Summary

Classification	Count
Self-driving (no human action during execution)	31 / 31 files
Converted (manual → programmatic)	0 (none needed)
Obsolete-candidate (genuinely undriveable headless)	0

Headline result: ZERO of the 31 integration test files require any human action during execution. Every file was previously flagged NEEDS-MANUAL-REVIEW but on inspection none meets a §11.4.98(C) manual-dependency criterion (typing, clicking, hand-triggered webhook, manual file attach, hard-coded session UUID, 60 s human-response window). They are all already self-driving — gated only by build tags / testing.Short / env-var infra presence.

Test-execution evidence (real captured runs)

Real commands run from helix_code/:

```
go vet -tags=integration ./tests/integration/ # E
go test -tags=integration -count=1 -v ./tests/integration/ # 1
go test -tags='integration testing_export' -count=1 -run Telemetry ... # 6
```

Captured logs (in this directory): - `full_integration_run.log` — full -v run (110 PASS / 20 SKIP / 3 FAIL) - `telemetry_run.log` — double-tagged telemetry suite (6 PASS / 2 SKIP) - `askuser_run.log`, `approval_run.log` — focused FAIL captures - `i18n-regression-evidence.txt` — the 3 real FAILs (NOT manual-dependency; see below)

The 3 FAILs are a real i18n-render regression, NOT a manual dependency

All 3 failing tests are fully self-driving (deterministic bytes . Buffer I/O, no human action). They FAIL because the prompter render path now emits **raw i18n translation keys** instead of resolved+interpolated user-facing text:

- `TestAskUser_PreviewVisibleInOutput` — output contains `askuser_prompt_choice_preview_label` but NOT the actual preview value `RGB(255,0,0)` — bright crimson.
- `TestAskUser_InvalidInputThenValid` — output contains `askuser_prompt_invalid_choice_hint` but NOT the valid-range hint 1-3.
- `TestApproval_AutoEdit_PromptsRun_UserAllows` — output is `internal_approval_prompt_allow_toolinternal_approval_prompt_args_suffi` instead of containing the tool name `stub_run_for_approval`.

This is a genuine §11.9 usability defect (the user is shown raw i18n keys instead of text) that the self-driving tests correctly catch. Per §11.4.6 (no-guessing) it is reported honestly here, NOT papered over with a PASS. **Fix is OUT of this task’s scope** (production i18n render path in `internal/tools/askuser` + approval prompter, not a manual-dependency conversion). Flagged for the main stream as a §11.4.15 Bug.

The 20 SKIPs are honest infra/credential-unavailable skips (not manual deps)

All cite concrete infra reasons — Anthropic key absent, gopls not on PATH, cloud creds absent, Ollama/VLLM/LocalAI/Cognee not running, test admin user not configured, OTLP exporter not running, `RUN_CONVERSION_TESTS` unset. These are legitimate §11.4.3 SKIP-with-reason, NOT human-in-the-loop dependencies.

Per-file classification

File	Build gate	Classification	Driving mechanism	
<code>api_integration_test.go</code>	<code>testing.Short</code>	self-driving	real HTTP to :8080 + httptest	I (7 S a
<code>approval_test.go</code>	<code>//go:build integration</code>	self-driving	in-memory approval engine, deterministic	7 r
<code>askuser_test.go</code>	<code>//go:build integration</code>	self-driving	<code>bytes.Buffer</code> Reader/Writer (NOT <code>os.Stdin</code>), <code>ISTTY</code> closure	4 r
<code>autocommit_test.go</code>	<code>//go:build integration</code>	self-driving	real git in <code>t.TempDir()</code>	5
<code>auto_compaction_integration_test.go</code>		self-driving		S

File	Build gate	Classification	Driving mechanism	
	//go:build integration		real Anthropic (SKIP w/o key)	
background_shell_test.go	//go:build integration	self-driving	real os/exec shell, POSIX-gated	3
browser_test.go	//go:build integration	self-driving	chromedp programmatic click/type/screenshot vs httptest.Server fixture (the “click” is a chromedp DOM action, NOT human)	7
cognee_integration_test.go	none (default-skip)	self-driving	real Cognee HTTP (env URL, SKIP if down)	6
cognee_real_llm_test.go	none (suite, SKIP guard)	self-driving	real LLM (SKIP w/o config)	5
integration_test.go	testing.Short	self-driving	real HTTP to :8080	2
lsp_test.go	//go:build integration	self-driving	real LSP subprocess + fake-server fixture; gopls-gated	3
markdown_commands_test.go	//go:build integration	self-driving	real FS + fsnotify watcher	3
mcp_stdio_test.go	//go:build integration	self-driving	real MCP stdio subprocess handshake	2
memory_providers_integration_test.go	none	self-driving	real provider constructors	4
memory_test.go	//go:build integration	self-driving	real FS + hot-reload	3
multi_provider_test.go	//go:build integration	self-driving	config/env/flag resolution; cloud-call SKIP w/o creds	7
planmode_gating_test.go	//go:build integration	self-driving	in-memory plan-mode gate, POSIX-gated	3
provider_integration_test.go	//go:build integration	self-driving	real provider HTTP (SKIP if backend down); testTimeout=60s is an HTTP-client deadline, NOT a human-response window	2
sandbox_test.go	//go:build integration	self-driving	real bubblewrap (gated), CONST-033 reject	6
sessions_resume_test.go		self-driving		2

File	Build gate	Classification	Driving mechanism	
	//go:build integration		real session persistence across restart	
simple_test.go	testing.Short	self-driving	real os/exec + FS + net dial	6
skills_test.go	//go:build integration	self-driving	real FS + watcher	3
smartedit_test.go	//go:build integration	self-driving	real FS edits + git commit	I
subagent_test.go	//go:build integration	self-driving	real subagent subprocess via testhelper	I
telemetry_test.go	//go:build integration && testing_export	self-driving	OTel stdout/in-memory exporter; OTLP SKIP if no collector	6
theme_test.go	//go:build integration	self-driving	real theme load/render	I
workflow_tools_integration_test.go	testing.Short	self-driving	real workflow tools	I
(cmd/, hooks/, permissions/, persistence/, worktree/ subdirs)	challenge runners / sub-suites	self-driving	httptest fixtures, generated uuid.NewString() (NOT hard-coded), real FS/git	c

§11.4.98(C) criterion-by-criterion negative findings

- **Typing during execution:** NONE — askuser_test.go feeds input via bytes.NewBufferString("1\n"), never os.Stdin.
- **Clicking:** the only “click” is browser_test.go / cmd/p2f23 chromedp programmatic click.Execute({selector: "#b"}) against a fixture — machine-driven, asserts UNCLICKED→CLICKED_42.
- **Hand-triggered webhook:** NONE.
- **Manual file attach:** NONE — all file ops use t.TempDir() + os.WriteFile.
- **Hard-coded session UUID** (Herald lesson): NONE — cmd/p1f11_challenge uses uuid.NewString() (freshly generated); no claude --resume collision risk.
- **60 s human-response window:** NONE — the only 60 * time.Second literals are HTTP-client timeouts (provider_integration_test.go:25, cognee_integration_test.go:31), not human-input deadlines.

Anti-bluff statement (§11.4 / §11.4.98 / §11.9)

Every “self-driving + PASS” claim above is backed by a real captured go test invocation in full_integration_run.log / telemetry_run.log — not “looks self-driving”. The 3 FAILs and 20 SKIPs are reported honestly (no fabricated PASS). No test file was modified. No file changes were staged or committed by this task.