

QA evidence — pgx PostgreSQL Repository (containerized integration)

Field	Value
Run id	20260608-pgx-postgres-integration
Feature	store.PostgresRepository (pgx) implementing store.Repository, the production persistence seam
Date	2026-06-08
Evidence	<u>run.log</u> — real go test -tags integration -count=1 output

What this proves (anti-bluff, Constitution §11.4)

- A **real PostgreSQL** is booted on-demand through the containers submodule (digital.vasic.containers → pkg/boot + pkg/compose + pkg/health) on the **podman** runtime — not a manual podman/compose step, not a fake/mock (boot summary: started=1 ... failed=0).
- The pgx PostgresRepository passes the **exact same** behavioural contract (runRepositoryContract) that the in-memory repository passes — proving parity across both implementations (devices incl. hardware-id conflict, artifacts incl. payload-properties round-trip, releases incl. dotted-version LatestRelease + offset paging, deployments incl. group-narrowed ActiveDeploymentForTarget, telemetry ordering, first-write-wins idempotency).
- The booted container is torn down on test cleanup (mgr.Shutdown); no leftover containers remain after the run.

Reproduce

```
cd server
go test -tags integration -count=1 ./internal/store/ \
  -run TestPostgresRepositoryContract_Integration -v
```

Requires a container runtime (podman or docker) with a running machine and podman compose / docker compose. The compose file is server/deploy/postgres.compose.yml (Postgres 16, host port 55432).