

QA — OTA recall (forward-fix) lifecycle challenge

Revision: 1 **Last modified:** 2026-06-10T11:40:37Z

What this covers

A new e2e/Challenge layer covering the Helix OTA **server-driven recall (forward-fix rollback)** lifecycle:

- New script: `tests/e2e/recall_lifecycle.sh` (self-hosting, anti-bluff).
- New companion doc: `docs/scripts/recall_lifecycle.md` (§11.4.18).
- New HelixQA challenge: `HOTA-RECALL-LIFECYCLE` in `tools/helixqa/banks/helix_ota.yaml` (bank revision bumped 3 → 4).

The challenge dispatches to the real script and scores PASS only on its real exit 0 + captured evidence (`tests/e2e/RECALL_EVIDENCE.txt`). It is fully self-driving (§11.4.98): it builds + boots its own `ota-server` with an ephemeral `ed25519` key on a free-probed unique port, signs real artifacts, stages release `v1.1.0` + all-targets deployment `D1`, drives the operator recall to forward-fix release `v1.2.0`, and tears the server down on every exit path.

Authored-state validation (this parallel phase)

- `bash -n tests/e2e/recall_lifecycle.sh` → OK
- `sh -n tests/e2e/recall_lifecycle.sh` → OK
- `tools/helixqa/banks/helix_ota.yaml` parses as YAML; new entry present; existing entries undisturbed; bank revision = 4.
- Contract dry-run trace against `server/internal/api/handlers_recall.go` + `server.go` + `wire.go` + `ota-protocol/enums.go` confirms every asserted field/status/JSON-key matches the live handler (`kind="rollback"`, `from_release_id/to_release_id/recall_deployment_id/triggered_by, details.mode="forward-fix"`, recall 201, superseded `.status="superseded"`, recall deployment `.status="active"` = `DeploymentActive`, the 400/404 negative controls).

The live run was intentionally NOT executed during this parallel phase because the `server/` source may be mid-edit by another agent (§11.4.119 single-resource-owner). **The conductor MUST run it live against the clean merged tree to capture the PASS evidence.**

How the conductor runs it (capture live PASS evidence)

From the repo root, against the clean merged tree:

```
bash tests/e2e/recall_lifecycle.sh
```

Expected: RESULT: PASS with 0 failed, and the full run captured to tests/e2e/RECALL_EVIDENCE.txt. The script self-hosts the server (no manual server start, no admin password input) on a free probed port and cleans up on exit. To pin a port: `bash tests/e2e/recall_lifecycle.sh --port 8097`.

A SKIP (exit 3) occurs only if a prerequisite tool (go, openssl, ed25519, xxd, base64, curl, jq, python3) is unavailable — never a false PASS.

After the live run, the conductor should commit tests/e2e/RECALL_EVIDENCE.txt as the captured PASS evidence for HOTA-RECALL-LIFECYCLE and may update the challenge's asserted_lines summary counts to match the observed run.