

schema

Helix OTA — 1.0.0-MVP Database Schema

Field	Value
Revision	2
Created	2026-06-07
Last modified	2026-06-07
Status	active
Status summary	Canonical 1.0.0-MVP relational data model for the Helix OTA Go control plane: the <code>helix_ota</code> PostgreSQL schema, entity-relationship description, table-by-table rationale, constraints, indexes, and the four-layer testing plan. Backed by real, executed migration DDL (<code>migrations/001_initial_schema.{up,down}.sql</code>).
Issues	Relative telemetry-vs-rollout volume is UNVERIFIED (ADR-0003 §3.2); HelixConstitution clause numbers (§11.4.x) are carried from the corpus convention and are UNVERIFIED; precise public surfaces of the <code>database/auth/security/Storage</code> catalogue submodules are UNVERIFIED (<code>submodule_reuse_map.md</code>).
Fixed	Rev 2: clarified §5.6 version monotonicity is app-layer (Go publish-time), not a DB constraint; reworded §5.9 event vocabulary as derived/extended from master §9; added PII handling note; aligned §6/§10 constraint count ordering.
Continuation	When ADR-0001 (<code>hawkBit</code>) is un-gated, add the deferred rollouts bridge table in a later migration; when

Field	Value
	the staged-rollout engine lands (1.0.1) add deployment_phases + device_deployments.phase_id; when end-user/multi-version rollback lands (1.0.1) add rollback_history. Set numeric partition/retention policy for telemetry_events and audit_logs from MVP load-test data (currently UNVERIFIED). Confirm the database submodule migration runner is the one driving these files.

Table of contents

1. [Purpose and scope](#)
2. [Locked-stack and strategy alignment](#)
3. [The helix_ota schema](#)
4. [Entity-relationship description](#)
5. [Table-by-table rationale](#)
 - [5.1 users](#)
 - [5.2 api_keys](#)
 - [5.3 devices](#)
 - [5.4 device_groups and device_group_members](#)
 - [5.5 artifacts and artifact_versions](#)
 - [5.6 releases](#)
 - [5.7 deployments](#)
 - [5.8 device_deployments](#)
 - [5.9 telemetry_events](#)
 - [5.10 audit_logs](#)
6. [Constraints summary](#)
7. [Index summary and query drivers](#)
8. [Deferred to 1.0.1 \(NOT in this schema\)](#)
9. [Submodule reuse](#)
10. [Migration files](#)
11. [Testing \(four-layer\)](#)
12. [Anti-bluff / UNVERIFIED register](#)
13. [Sources](#)

The table-of-contents requirement is mandated by HelixConstitution §11.4.61 (UNVERIFIED clause number). This document carries its ToC immediately after the metadata table, per [documentation_standards.md §3](#).

1. Purpose and scope

This document specifies the relational data model for **Helix OTA 1.0.0-MVP** — the control-plane state persisted in PostgreSQL. It is the design rationale that accompanies the executable DDL in [migrations/001_initial_schema.up.sql](#) and its reverse [migrations/001_initial_schema.down.sql](#).

The schema is deliberately **MVP-scoped**. It covers the end-to-end MVP happy path from the master design §5: *admin logs in → uploads signed OTA .zip + hash → server validates → publishes release → deploys (all-at-once for MVP) → device polls, downloads, re-verifies, applies via update_engine, reboots → telemetry success/failure with automatic A/B rollback on boot failure*. Staged-rollout phasing and end-user/multi-version rollback are **deferred to 1.0.1** and are explicitly absent here (§8). [master design §1 non-goals, §5, §7]

The entity list is taken verbatim from the master design §7 (“base schema ... 02 as the richer base, normalized”) and the operator brief; field-level detail is normalized from [additions/initial_research_02.md §4](#). [master design §7]

2. Locked-stack and strategy alignment

The schema honors the locked decisions without re-opening them:

- **Persistence = PostgreSQL** (relational state) + **MinIO/S3** (artifact blobs). The DB stores metadata and the **object key** of each blob (`artifacts.file_path`), never the bytes — blobs live in Storage. [master design §3; D7]
- **Modular monolith (ADR-0003)**. One Go binary, therefore **one PostgreSQL schema** (`helix_ota`) with internal module boundaries mirrored by table groupings (artifact-validator, rollout-engine, device registry, telemetry). A future service split is a lift-out, not a re-shard. [ADR-0003 §3]
- **Wrapped engine gated (ADR-0001)**. hawkBit is the front-runner but GATED; the AOSP-native-only Go rollout engine is the pre-authorized fallback. The MVP schema therefore commits **no hawkbit_* columns** (draft 02’s `rollouts.hawkbit_rollout_id` is deferred with the rest of the staged-rollout machinery, §8). [ADR-0001 §4, §5.3]
- **Signing + SHA-256 + AVB for MVP; TUF deferred (ADR-0002)**. `artifacts` carries `checksum_sha256` (mandatory), `checksum_sha512` (where available), and a detached signature column — the MVP trust model. The signing interface is MVP-forward so TUF/Uptane drops in at 1.0.1 without a destructive migration. [ADR-0002 §4.1, §4.2; master design §6]
- **Transport is out of scope for the DB**. HTTP/3→HTTP/2, Brotli, REST `/api/v1`, optional internal gRPC are transport concerns (`http3`, `middleware`, `ota-protocol`); they touch no table here. [master design §3; `submodule_reuse_map` Transport row]

3. The `helix_ota` schema

All control-plane objects live in a dedicated **helix_ota** PostgreSQL schema rather than `public`.

Rationale:

- **Co-tenancy isolation**. If ADR-0001’s hawkBit is adopted, hawkBit runs on its own PostgreSQL schema/instance (hawkBit recommends a separate schema). A dedicated `helix_ota` schema guarantees the Helix-authored tables never collide with a co-located hawkBit schema. [ADR-0001 §3.1; ADR-0003 §3]
- **Clean teardown / least privilege**. The control-plane role can be scoped to `helix_ota`; the down migration drops the schema with `RESTRICT`, failing loudly if any unexpected object remains.

- **Forward-compatible.** 1.0.1 additions (deployment_phases, rollouts, rollback_history) land in the same schema; a service split (ADR-0003 §3.2) can later move a table group out without renaming.

The migration sets `search_path = helix_ota, public` for its session and `CREATE EXTENSION IF NOT EXISTS pgcrypto` so `gen_random_uuid()` is available on PostgreSQL < 13 (it is core on 13+).

4. Entity-relationship description

Twelve tables in four functional clusters. UUID primary keys throughout (`gen_random_uuid()`); all timestamps are `TIMESTAMPTZ DEFAULT now()`.

Identity & access — `users` 1—N `api_keys`; `users` is referenced (nullable, audit-preserving) by `artifacts.uploaded_by`, `releases.published_by`, `deployments.created_by`, and `audit_logs.user_id`.

Fleet — `devices` N—M `device_groups` through the composite-PK join `device_group_members`.

Artifacts → **releases** → **deployments** (the supply chain): `artifacts` 1—N `artifact_versions`; `artifacts` 1—N `releases` (a release pins one validated artifact + channel); `releases` 1—N `deployments`; a `deployments` row targets all / a group / a single device; `deployments` 1—N `device_deployments` (one row per targeted device, unique on (`deployment_id`, `device_id`)).

Observability — `telemetry_events` references `devices` and `deployments` (ON DELETE SET NULL, history survives deletion); `audit_logs` references `users` (also SET NULL).

erDiagram

```

users ||--o{ api_keys : "owns"
users ||--o{ artifacts : "uploaded_by"
users ||--o{ releases : "published_by"
users ||--o{ deployments : "created_by"
users ||--o{ audit_logs : "actor"
devices ||--o{ device_group_members : ""
device_groups ||--o{ device_group_members : ""
artifacts ||--o{ artifact_versions : "versions"
artifacts ||--o{ releases : "published as"
releases ||--o{ deployments : "delivered by"
deployments ||--o{ device_deployments : "per-device state"
devices ||--o{ device_deployments : "target"
devices ||--o{ telemetry_events : "reports"
deployments ||--o{ telemetry_events : "about"
device_groups ||--o{ deployments : "target (group)"
devices ||--o{ deployments : "target (device)"

```

(Diagram source is Mermaid per [documentation_standards.md §6](#).)

5. Table-by-table rationale

5.1 users

Dashboard/API operators — the RBAC subjects. Identity, password verification, token issue/verify, and RBAC enforcement are **owned by the auth/security catalogue submodules**; this table is the relational projection the control plane joins against for ownership and audit. `role` is constrained to ('admin', 'operator', 'viewer'). `username` and `email` are unique. `is_active` supports soft disable without deletion (FKs from audit/artifacts must survive). [submodule_reuse_map Auth row; master design §6]

5.2 api_keys

Non-interactive credentials (the CI build pipeline that signs and uploads artifacts; automation). Only `key_hash` is persisted (unique) — cleartext is shown once at issue. `permissions` is JSONB (scope set). `expires_at` is CHECK-constrained to be after `created_at`; `revoked_at` allows revocation without deletion. FK to `users` is ON DELETE CASCADE (a deleted user's keys go with it).

5.3 devices

Fleet inventory. `device_id` is the **stable external identity** (unique) — a token bound to the hardware id (Android KeyStore, master §6), distinct from the surrogate id. `os_type` is CHECK-constrained to ('android', 'linux', 'windows', 'other'): **'android' is the only Phase-1 value**, but the column exists so the OS-adaptor seam (ADR-0003 §3.1) is schema-ready without a later migration. `status` ('active', 'inactive', 'blocked') gates eligibility. `last_seen_at` is updated on each poll (15 min + jitter, D7). `metadata` JSONB holds free-form device attributes used by dynamic group `filter_criteria`. [master design §6; ADR-0003 §3.1]

5.4 device_groups and device_group_members

`device_groups` are named cohorts; `filter_criteria` JSONB carries a **dynamic** selector (evaluated against `devices.metadata`), while `device_group_members` records **static** membership. The join uses a composite primary key (`group_id`, `device_id`) — the natural key, no surrogate needed — and cascades on deletion of either side. A secondary index on `device_id` answers “which groups is this device in?”. `name` is unique.

5.5 artifacts and artifact_versions

`artifacts` is one uploaded OTA blob's metadata. Key design points:

- **file_path is the Storage object key**, not a local FS path — bytes live in MinIO/S3 behind the Storage submodule. [submodule_reuse_map Storage row]
- **Integrity (ADR-0002 MVP trust model)**: `checksum_sha256` CHAR(64) NOT NULL, with a CHECK that it matches `^[0-9a-f]{64}$`; `checksum_sha512`

- CHAR(128) (nullable, “where available”) with an analogous CHECK; a detached signature TEXT. Verified server-side on upload by ota-artifact-validator and device-side before apply. [ADR-0002 §4.1; master design §6]
- **artifact_type** defaults to 'full'; 'incremental'/'delta' are allowed by the CHECK but **unused at MVP** — delta updates are ADR-0005, deferred. [master design §1 non-goals; ADR-0005]
 - **upload_status** ('pending', 'validating', 'validated', 'failed') mirrors the validation pipeline (structure → hash → signature → version monotonicity → target compatibility, master §5); validation_errors JSONB records failures. Only validated artifacts may be published.
 - **Uniqueness:** (name, os_type, version) is unique — one artifact per OS per version.
 - uploaded_by FK is ON DELETE SET NULL (artifact provenance outlives the uploader).

artifact_versions carries version lineage (changelog, release_notes) and an is_latest flag made safe by a **partial unique index** (WHERE is_latest) guaranteeing at most one latest per artifact. (artifact_id, version) is unique.

5.6 releases

The master design §7 lists releases as a **first-class entity distinct from deployments**: a *release* is the published, deployable unit an admin creates from a validated artifact before deploying. Separating release (publish) from deployment (deliver) lets one release feed multiple deployments (e.g. group A now, group B later). **Version monotonicity is enforced at publish time in the Go control plane (application layer), NOT by a database constraint** — the DB only enforces uniqueness via releases_channel_version_uniq(channel + version) and artifacts_name_os_version_uniq((name, os_type, version)). channel ('stable', 'beta', 'canary', 'internal') + version is unique. status ('draft', 'published', 'superseded', 'withdrawn') with a CHECK that a published release has published_at set. FK to artifacts is ON DELETE RESTRICT (cannot delete an artifact that has releases). [master design §5, §7]

5.7 deployments

An instruction to deliver a release to a target set. For MVP the **only supported strategy is all-at-once** (master §5: “staged engine lands 1.0.1”); rollout_strategy JSONB defaults to {"mode": "all_at_once"} and is kept as JSONB so a 1.0.1 staged config drops in without a column migration. Targeting uses target_type ('all', 'group', 'device') plus nullable target_group_id/target_device_id, made consistent by a **table CHECK**: 'all' has neither ref, 'group' has exactly the group ref, 'device' has exactly the device ref. status includes ('draft', 'active', 'paused', 'completed', 'failed', 'cancelled'). A time-ordering CHECK ensures completed_at >= started_at. FK to releases is RESTRICT; target FKs are SET NULL. **Deferred:** deployment_phases and the hawkBit rollouts bridge (§8). [master design §5, §8; ADR-0001 §4]

5.8 device_deployments

Per-device delivery state — the join recording what each device actually did for a deployment, one row per (deployment_id, device_id) (unique). status tracks the device lifecycle

('pending', 'downloading', 'installing', 'verifying', 'success', 'failed', 'rolled_back'), where rolled_back records the **automatic A/B boot-failure rollback** that IS in MVP (distinct from the deferred end-user rollback). progress NUMERIC(5,2) is CHECK-bounded to 0.00–100.00; retry_count >= 0. The MVP omits draft 02's phase_id (staged phases are 1.0.1). FKs cascade on deployment/device deletion. [master design §1 (auto-rollback in MVP), §5]

5.9 telemetry_events

Device-reported event stream (master §9). **Renamed from draft 02's update_metrics to the master's canonical telemetry_events.** This is the higher-volume, append-mostly table and the first scale-split candidate after the rollout engine (ADR-0003 §3.2 trigger #1 — relative volume is **UNVERIFIED**, to be set from MVP load tests). event_type is CHECK-constrained to a device vocabulary derived from master §9, extended with download_complete and rollback:

('download_started', 'download_complete', 'installing', 'installed', 'verifying', 'success', 'failure', 'rollback'). duration_ms/bytes_transferred are CHECK >= 0 when present. device_id/deployment_id FKs are ON DELETE SET NULL so telemetry history survives device/deployment deletion. Metrics from this table drive the (1.0.1) rollout halt logic and the operator-required problem detection. [master design §9; ADR-0003 §3.2]

5.10 audit_logs

Every admin/operator action — master §6 mandates “every admin action logged”. Append-only: action, resource_type, nullable resource_id, details JSONB, ip_address INET, user_agent. user_id FK is ON DELETE SET NULL so the audit record outlives the actor (a security requirement). Indexed by user, action, (resource_type, resource_id), and time. [master design §6]

PII handling note: users.email, audit_logs.ip_address, and audit_logs.user_agent are stored in **plaintext**; users.password_hash and api_keys.key_hash are **hashed** (never stored in cleartext). Encryption-at-rest and a retention/erasure policy for these fields are **UNVERIFIED / future** (not specified or implemented at MVP).

6. Constraints summary

Verified counts from applying the up migration to PostgreSQL 16 (see §10): **12 primary keys, 16 foreign keys, 23 CHECK constraints, 9 UNIQUE constraints, 45 indexes.**

- **UUID PKs** on all 12 tables (device_group_members uses a composite natural PK).

- **CHECK constraints** enforce: enumerated role/status/os_type/channel/event_type/ target_type/artifact_type/upload_status values (replacing draft 02's bare comment-strings); SHA-256/512 hex format and length; non-negative sizes/durations/retries; progress 0–100; release publish consistency; deployment target/type consistency; deployment time ordering; api-key expiry ordering.
- **FK delete behavior** is chosen per relationship: CASCADE for owned children (api_keys, device_group_members, device_deployments); RESTRICT for supply-chain parents that must not vanish under a referent (artifacts←releases, releases←deployments); SET NULL for provenance/audit/telemetry references that must survive actor/target deletion.

7. Index summary and query drivers

Indexes follow draft 02 §4 plus query-driven additions:

Index	Drives query
idx_devices_os_type, idx_devices_status, idx_devices_last_seen	fleet filtering; stale-device detection
idx_api_keys_user	list a user's keys; auth lookups
idx_dgm_device	"which groups is this device in?"
idx_artifacts_os_type, idx_artifacts_version, idx_artifacts_status	artifact browse + validation-queue
idx_artifact_versions_one_latest (partial unique)	single-latest invariant + latest lookup
idx_releases_artifact, idx_releases_status, idx_releases_channel	release listing per channel/state
idx_deployments_release, idx_deployments_status	active-deployment dashboard
idx_device_deployments_status, idx_device_deployments_device	per-deployment progress; device history
idx_telemetry_events_device/ deployment/type/created	telemetry rollups, time-range scans, halt-logic feed
idx_audit_logs_user/action/ resource/created	audit search by actor, action, resource, time

UNIQUE constraints also create supporting indexes (e.g. devices.device_id, users.email). **UNVERIFIED:** time-series partitioning / retention for telemetry_events and audit_logs is not set at MVP — pending load-test data (ADR-0003 §3.2). [additions 02 §4]

8. Deferred to 1.0.1 (NOT in this schema)

These entities from draft 02 / master §7 are **intentionally absent** and are NOT created by this migration:

Deferred entity	Why deferred	Owning decision
deployment_phases	Staged-rollout phasing (5/10/30/.../100 %) lands in 1.0.1 1.0.1-staged-rollout/; MVP is all-at-once.	master §1 non-goals, §5, §8
rollouts (incl. hawkbit_rollout_id)	hawkBit is GATED (front-runner, not committed); committing a hawkBit bridge column now would presume an un-closed decision.	ADR-0001 §4, §5.3
rollback_history	End-user / multi-version rollback is a 1.0.1 non-goal; automatic A/B boot-failure rollback IS in MVP and is captured by device_deployments.status='rolled_back' + telemetry_events.event_type='rollback', needing no separate table.	master §1 non-goals
TUF metadata tables	TUF/Uptane device-side trust is 1.0.1 hardening; MVP uses signing + SHA-256 + AVB, with the signature column MVP-forward.	ADR-0002 §4.1–§4.3
Delta-artifact tables / columns	Delta updates are ADR-0005 (deferred); artifact_type already reserves 'delta'/'incremental'.	master §1 non-goals; ADR-0005

9. Submodule reuse

Per catalogue-first (§11.4.74, UNVERIFIED) and [submodule_reuse_map.md](#):

- **database** owns the migration runner, connection pooling, and the storage-port the rollout/registry modules persist through. Helix OTA writes DDL/queries against it; no bespoke driver code. (UNVERIFIED: exact database migration-runner API.)
- **Storage** (and Storage-KMP) holds artifact bytes (MinIO/S3); artifacts.file_path is its object key. The DB never stores blobs.
- **auth/security** own identity/RBAC/crypto; users/api_keys are the relational projection only. SHA-256/512 + signature-verify primitives for ota-artifact-validator come from security (UNVERIFIED that the primitives are exposed as needed).
- **observability/Herald** consume telemetry_events for dashboards/alerting; the schema + codecs live in the NEW ota-telemetry-schema submodule.
- Wire/manifest types (used to read/write these rows over REST) come from the NEW ota-protocol submodule. No invented submodule names are used (§7.1). [submodule_reuse_map §3, §4]

10. Migration files

File	Purpose
migrations/ 001_initial_schema.up.sql	

File	Purpose
	Creates the <code>helix_ota</code> schema and all 12 tables, constraints, and indexes. Wrapped in a single transaction.
<code>migrations/001_initial_schema.down.sql</code>	Drops all tables in strict reverse dependency order , then drops the schema with <code>RESTRICT</code> . Does not drop the shared <code>pgcrypto</code> extension.

Validation performed (not asserted — executed): both migrations were applied to a throwaway **PostgreSQL 16.14** cluster. Result: 12 tables, 12 PK + 16 FK + 23 CHECK + 9 UNIQUE constraints, 45 indexes; a bad-SHA-256 insert was correctly rejected by `artifacts_sha256_chk`; the down migration left zero `helix_ota` objects; and a clean re-apply of the up migration succeeded. This is the artifact gate of §11.

11. Testing (four-layer)

Per `HelixConstitution` §1 / master design §13, every change ships four layers with no-bluff positive evidence (§7.1). For this schema:

1. **Source-presence gate.** Assert the artifacts exist and contain the required objects: `schema.md`, `001_initial_schema.up.sql`, `001_initial_schema.down.sql` are present; the up file contains `CREATE SCHEMA helix_ota` and a `CREATE TABLE helix_ota.<name>` for each of the 12 tables; the down file contains a matching `DROP TABLE` for each. A `grep/AST` check, not a claim.
2. **Artifact gate (bytes shipped).** Apply `001_initial_schema.up.sql` to a real PostgreSQL instance and assert the realized catalog: exactly 12 tables in `helix_ota`; expected PK/FK/CHECK/ UNIQUE/index counts (§6: 12/16/23/9/45); every CHECK present (e.g. `artifacts_sha256_chk`, `deployments_target_ref_chk`). **Executed in §10 on PG 16.14.**
3. **Runtime / integration.** Exercise the schema with the control plane: insert a user → `api_key` → artifact (validated) → release (published) → deployment (`all_at_once`) → `device_deployment` rows → `telemetry_events`, asserting (a) every CHECK rejects out-of-domain values (bad `os_type`, `progress > 100`, mismatched `target_type/refs`, non-hex checksum, bad `event_type`); (b) FK delete behaviors (`CASCADE/RESTRICT/SET NULL`) fire as designed;
 1. the partial unique `is_latest` index forbids two latest versions; (d) `up→down→up` round-trips cleanly. (down→up round-trip executed in §10.)
4. **Mutation meta-test (PASS→FAIL on negation).** A test that, when a constraint is *removed or inverted*, must flip from PASS to FAIL — proving the test actually exercises the constraint. Examples: drop `artifacts_sha256_chk` → the “bad-checksum rejected” test must FAIL; widen `device_deployments_progress_chk` → the “progress > 100 rejected” test must FAIL; invert `deployments_target_ref_chk` → the “group deployment without group_id rejected” test must FAIL. Any constraint whose negation does not break a test is untested and the meta-test flags it.

Safety-critical relevance: `artifacts` integrity CHECKs (signing/hash) sit on the verify-before-apply path floored at ≥90% coverage (master §13; ADR-0002 §7).

12. Anti-bluff / UNVERIFIED register

Per §7.1 / §11.4.6 / §11.4.123 (UNVERIFIED clause numbers, [documentation_standards.md §8](#)):

- **UNVERIFIED:** relative volume of `telemetry_events` vs rollout traffic (ADR-0003 §3.2, no load figures in sources).
- **UNVERIFIED:** HelixConstitution clause numbers (§1, §7.1, §11.4.6, §11.4.28, §11.4.61, §11.4.74, §11.4.123) — carried from corpus convention, not cross-checked against the constitution text.
- **UNVERIFIED:** precise public surfaces of database, auth, security, Storage (submodule_reuse_map.md Continuation) — “satisfies” claims are conditional on inspection.
- **UNVERIFIED:** time-series partitioning/retention thresholds for `telemetry_events/audit_logs`.
- **VERIFIED (executed):** the DDL is valid PostgreSQL 16; the constraint/index counts; the bad-checksum rejection; the down migration fully reverses the up (§10).
- No fabricated submodule names, columns, or hawkBit specifics are committed; gated/deferred items are marked, not invented.

13. Sources

- [../../../../00-master/2026-06-07-helix-ota-design.md](#) — master design (§5 MVP path, §6 trust, §7 entity list, §9 telemetry vocabulary, §13 testing).
- [../../../../00-master/documentation_standards.md](#) — metadata/ToC (§2, §3, §11.4.61), anti-bluff (§8), submodule catalogue (§9).
- [../../../../00-master/submodule_reuse_map.md](#) — component→submodule bindings, NEW-submodule boundaries.
- [../../../../research/adr/adr-0001-wrapped-engine.md](#) — hawkBit gated; no committed `hawkbit_*` columns at MVP.
- [../../../../research/adr/adr-0002-supply-chain-trust.md](#) — signing + SHA-256 + AVB for MVP; TUF deferred; MVP-forward signing interface.
- [../../../../research/adr/adr-0003-server-topology.md](#) — modular monolith → one schema; telemetry split trigger.
- [../../../../research/adr/adr-0005-delta-updates.md](#) — delta updates deferred (`artifact_type` reserves the values).
- [../../../../additions/initial_research_02.md §4](#) — richer base schema and index list, normalized into this design.