

scripts/commit_all.sh — user guide

Revision: 1 Last modified: 2026-07-10T22:10:00Z

Overview

The official commit wrapper for the **main repo** (per the project MANDATORY COMMIT & PUSH CONSTRAINTS — never `git add/commit/push` the main repo directly). It stages, runs the pre-build gate, commits, and fans the push out to all four upstreams (github/gitlab/gitflic/gitverse) in the background (§11.4.88).

Prerequisites

- Run from anywhere inside the repo; it resolves `PROJECT_ROOT` itself.
- All four upstream remotes configured (`install_upstreams`).
- A clean-ish working tree you understand — see **--paths isolation** below.

Usage

```
# Full commit (stages everything: git add -A), prompts for message
if -m absent:
bash scripts/commit_all.sh -m "feat(x): ..."

# Explicit-paths commit – stage + commit ONLY the listed paths
# (space-separated):
bash scripts/commit_all.sh --paths "docs/A.md docs/A.html server/
x.go" -m "..."

# Docs-only variant (§11.4.22) – the canonical doc-set:
bash scripts/commit_all.sh --docs-only -m "docs: sync"

# Synchronous push (force-push audit paths / §11.4.41 – NOTE
force-push itself is
```

```
# forbidden §11.4.113; --sync-push only makes the push foreground,
    never forces):
bash scripts/commit_all.sh --sync-push -m "..."
```

```
# Dry run:
bash scripts/commit_all.sh --dry-run --paths "..."
```

Inputs

Flag	Effect
-m <msg>	Commit message (prompted if omitted).
--paths "<p1 p2 ...>"	Stage + commit ONLY these paths (index-isolated — see below).
--docs-only	Commit the canonical tracked doc set only (§11.4.22).
--sync-push	Push in the foreground (default is background/detached, §11.4.88).
--auto-cascade	Also git add -A + commit + push each dirty owned submodule first.
--dry-run	Show what would happen; no commit/push.

Outputs / Side-effects

- One commit on the current branch of the main repo.
- A **detached background push** to all four upstreams (§11.4.88); failures land in qa-results/push_failures/<ts>_push.log. Exit code reports COMMIT success, not push.
- Exit 3 = nothing to commit (informational).

--paths index isolation (item E fix, 2026-07-10) — IMPORTANT

--paths commits **exactly** the listed paths and nothing else. Internally the commit is a bare git commit, which snapshots the *entire* index; so the wrapper first runs git reset -q (clears the parent index to HEAD,

working tree untouched) and then `git add -- <listed paths>`. This guarantees that anything another actor pre-staged in the shared checkout (e.g. a subagent's `git rm` deletions) does **not** leak into a `--paths` commit — it stays as an uncommitted working-tree change for its proper commit.

Forensic origin: on 2026-07-10 a docs-only `--paths` commit swept in 3 subagent-staged `clients/` deletions because the bare commit snapshotted the whole index (incident `docs/research/incident_1184_paths_leak_20260710/`). The `git reset -q` line closes this. Belt-and-braces: the conductor still runs a `git diff --cached --name-only` clean-precheck before every `--paths` commit, and subagents must never run any `git` command (§11.4.20/§11.4.70).

Edge cases

- `--paths` never affects submodule indexes (separate `.git`); submodule pointer bumps must be listed explicitly if intended.
- The `git reset -q` unstages ALL parent staging before staging the listed paths — intended: in `--paths` mode, anything not listed is by definition not for this commit.

Related scripts

- `scripts/push_all.sh` — the per-remote background pusher (§11.4.88).
- `scripts/export_docs.sh` — regenerates HTML/PDF/DOCX siblings (§11.4.65).
- `scripts/pre_build_verification.sh` — the pre-build gate invoked before commit.

Test

`tests/test_commit_all_paths_isolation.sh` — hermetic regression guard for the `--paths` index isolation (reproduces the leak in a temp repo, proves the fix excludes actor-staged changes) + a structural assertion that the `git reset -q` line is present in the `--paths` branch.

Last verified: 2026-07-10.