

HelixTerminator – 03_testing_strategy

HelixTerminator – Testing Strategy & QA Specification

Document Version: 1.0.0

Status: Authoritative

Classification: Engineering – Internal

Governed by: [HelixConstitution](#) §11.4 Anti-Bluff Covenant

QA Orchestration: [helixqa](#) AI-Driven QA Framework

Last Updated: 2026-06-28

Table of Contents

1. [Testing Philosophy & Constitution Compliance](#)
 2. [Backend Unit Tests \(Go\)](#)
 3. [Backend Integration Tests](#)
 4. [End-to-End Tests](#)
 5. [Performance & Load Tests](#)
 6. [Security Tests](#)
 7. [Contract Tests \(Consumer-Driven\)](#)
 8. [Chaos Engineering](#)
 9. [Mutation Testing](#)
 10. [HelixQA Integration](#)
 11. [CI/CD Pipeline for Tests](#)
 12. [Test Data Management](#)
-

1. Testing Philosophy & Constitution Compliance

1.1 Foundational Mandate

HelixTerminator is a security-critical application. Every character typed in a terminal session, every private key stored in a vault, every SSH session brokered through the proxy carries a trust obligation to the user. Testing is not an afterthought – it is the primary mechanism by which we prove that the software deserves that trust.

The [HelixConstitution](#) establishes the universal base-layer rule set that all HelixDevelopment projects must inherit. For HelixTerminator, this means:

1. **The Anti-Bluff Covenant (§11.4):** The bar for shipping is not "tests pass." The bar is "users can use the feature." Every test that emits a PASS signal **must carry positive runtime evidence** captured during execution. A green summary line without runtime evidence is a critical defect of equal severity to a missing feature.
2. **Mechanical Enforcement Without Exception (§11.4.75):** Five-layer git-hook discipline enforces test gate compliance. No commit reaches `main` or any release branch without all required gates passing.
3. **Regeneration Mechanism Required (§11.4.77):** All test artifacts that can be generated from source (mocks, contract stubs, snapshot baselines) must have a documented regeneration path and must be regenerated on every schema change.
4. **CodeGraph Code-Intelligence Mandate (§11.4.78):** The `@colbymchenry/codegraph` toolchain must be integrated into the test pipeline to ensure cross-service impact analysis before any structural change is merged.
5. **Submodule-Catalogue-First Discovery:** The `helixqa` submodule must be declared in `submodules-catalogue.md` and all CI agents must resolve it before test execution begins.
6. **Default Test Suite Green Invariant:** The canonical anti-bluff audit (`scripts/audit_antibluff.sh`) verifies three invariants on every CI run:
(a) §11.4 anchor present across all submodules, (b) default test suite green, (c) paired §1.1 meta-test green.

1.2 Coverage Targets


Coverage targets are tiered by criticality:

Component	Line Coverage	Branch Coverage	Mutation Score
Auth Service	≥ 90%	≥ 95%	≥ 90%
Vault Service	≥ 90%	≥ 95%	≥ 90%
SSH Proxy Service	≥ 85%	≥ 90%	≥ 85%
Keychain Service	≥ 90%	≥ 95%	≥ 90%
Host Service	≥ 80%	≥ 90%	≥ 80%
API Gateway	≥ 80%	≥ 88%	≥ 80%

Component	Line Coverage	Branch Coverage	Mutation Score
Audit Service	≥ 80%	≥ 85%	≥ 75%
Flutter Clients	≥ 80%	≥ 85%	N/A
Infrastructure (Terraform/Helm)	N/A	N/A	N/A
Global Floor	≥ 80%	≥ 90% (critical paths)	≥ 80%

The phrase "critical path" means any code path that handles: authentication state transitions, vault cryptographic operations, SSH host-key verification, and privilege-level enforcement in RBAC. These paths require 100% mutation kill rate.

1.3 Test Pyramid Structure



Rationale for the 70:20:10 split:

- Unit tests are fast (< 10ms each), deterministic, and provide the highest signal-to-noise ratio for regression detection. They must dominate the suite.
- Integration tests validate that the seams between components work. They are slower (100ms–5s) but essential for message-bus semantics and data-layer correctness.
- E2E tests validate user-visible outcomes. They are expensive (5s–120s), brittle under infrastructure churn, and should be reserved for high-value user journeys only.

The pyramid is enforced structurally: the CI PR pipeline fails if the ratio deviates by more than 5 percentage points in either direction from the declared target.

1.4 Test-First Development Mandate

All feature work in HelixTerminator follows a strict test-first discipline:

Step 1 — Specification: The author writes a failing test that precisely describes the behavior the feature must produce. This test is committed before any implementation code.

Step 2 — Implementation: The author writes the minimum code to make the test pass.

Step 3 — Refactoring: The author refactors under the green test suite.

Step 4 — helixqa Review: The `helixqa` autonomous QA session is invoked via `make qa-session` to verify the feature against all documented behaviors. Any behavior not covered by existing tests that `helixqa` discovers is added to the suite before the PR is eligible for merge.

Step 5 — Anti-Bluff Audit: The `scripts/audit_antibluff.sh` script runs and must exit 0.

The mandate is enforced by a pre-commit hook that rejects any `*.go` or `*.dart` file commit if the corresponding `*_test.go` or `*_test.dart` file does not exist.

1.5 Definition of Done per Test Layer

Unit Test "Done"

- ☐ Test function named following convention `Test{Service}_{Method}_{Scenario}` (Go) or `test{Widget}_{scenario}` (Dart)
- ☐ Uses table-driven patterns (`t.Run` in Go, `parametrize` in Dart) for all multi-scenario functions
- ☐ All external dependencies mocked via interfaces; no real network calls
- ☐ All assertions use `testify/assert` or `testify/require` (Go) / `flutter_test` matchers (Dart)
- ☐ Test is deterministic: runs in any order, produces the same result every time
- ☐ Test covers the happy path, at least two error paths, and all boundary conditions
- ☐ Test runtime < 100ms per case
- ☐ Coverage contribution verified by `go test -coverprofile`
- ☐

helixqa evidence: N/A (unit tests are engine-internal)

Integration Test "Done"

☐

Uses `testcontainers-go` for all external services (Postgres, Redis, Kafka, RabbitMQ)

☐

Container images are pinned to exact digest in `testcontainers_config.go`

☐

Each test creates its own isolated schema/database/topic – no shared state

☐

Test tears down containers on success AND failure (via `defer`)

☐

Tests verify both the happy-path behavior AND the service's recovery from dependency failure

☐

Test runtime < 60s per test file

☐

helixqa evidence: test produces a JSON evidence artifact at `testresults/integration/{name}.json`

E2E Test "Done"

☐

Test covers a complete user journey from the client's perspective

☐

Test runs against a fully deployed staging environment (not mocks)

☐

Test captures video evidence via helixqa `SessionRecorder`

☐

Test asserts observable UI state, not internal implementation details

☐

Test is idempotent: can be re-run without manual environment reset

☐

Flaky test score < 1% over 100 runs (enforced by helixqa flaky-test quarantine)

☐

helixqa evidence: video recording + screenshot at each assertion point

Performance Test "Done"

☐

k6 script defines success thresholds (p95 latency, error rate)

☐

- ☐ Script runs for minimum 5 minutes sustained load
- ☐ Baseline recorded in `testresults/perf/baselines/`
- ☐ Regression detected if p95 degrades > 10% from baseline
- ☐ Results published to Grafana dashboard via k6 cloud/output plugin

Security Test "Done"

- ☐ Test demonstrates the attack vector is blocked (not just that it fails with an error)
- ☐ Test asserts the specific HTTP/protocol-level response that proves the control is active
- ☐ Test is linked to the CVE or OWASP category it guards against
- ☐ Result archived in `testresults/security/{date}/{test_name}.json`

1.6 CI/CD Gating Rules

```

| PR PIPELINE (blocks
merge)
|
|
| 1. lint (golangci-lint + flutter analyze)
REQUIRED
| 2. unit tests REQUIRED (all
pass)
| 3. integration tests REQUIRED (all
pass)
| 4. contract tests (Pact verification) REQUIRED (all
pass)
| 5. coverage gate REQUIRED (≥
thresholds)
| 6. anti-bluff audit REQUIRED (exit
0)
| 7. build (docker image)
REQUIRED
|
|
| MAIN PIPELINE (blocks
deployment)
|

```

```
|
|
| All of the above,
PLUS:
| 8. E2E tests (staging environment) REQUIRED (all
pass)
| 9. performance regression check REQUIRED (< 10%
p95)
| 10. SAST scan (Semgrep + govulncheck) REQUIRED (no high/
crit)
| 11. helixqa autonomous QA session REQUIRED (exit
0)
```

```
| NIGHTLY PIPELINE (blocks next-day
development)
```

```
|
| 12. chaos experiments (LitmusChaos) ADVISORY
(alerting)
| 13. mutation testing (go-mutesting) REQUIRED (≥ 80%
kill)
| 14. full regression suite REQUIRED (all
pass)
| 15. property-based / fuzz tests REQUIRED (no
crashes)
```

```
| RELEASE PIPELINE (blocks release
tag)
```

```
|
| 16. full nightly suite
REQUIRED
| 17. penetration test report gate REQUIRED (signed
report)
| 18. DAST scan (OWASP ZAP) REQUIRED (no high/
crit)
| 19. accessibility audit (axe-core) REQUIRED (WCAG 2.2
AA)
| 20. golden/snapshot test baseline REQUIRED (no
regressions)
```

1.7 HelixQA Integration Overview

The `helixqa` submodule is declared at `submodules/helixqa` and is incorporated per CONST-051(C). It provides the following capabilities for HelixTerminator:

Capability	Integration Point	Trigger
Autonomous QA Session	<code>make qa-session</code>	Post-deploy on staging
VisionEngine visual regression	<code>make visual-regression</code>	Release pipeline
LLM-powered bug detection (<code>pkg/issuedetector</code>)	<code>make helixqa-issues</code>	Main pipeline
Test plan generation (<code>pkg/planning</code>)	<code>make helixqa-plan</code>	Feature branch creation
Flaky test detection	<code>make helixqa-flaky</code>	Nightly pipeline
Evidence collection	Automatic via <code>pkg/evidence</code>	All E2E test runs
Ticket generation (<code>pkg/ticket</code>)	Automatic on failure	All pipelines

The HelixQA anti-bluff invariant is enforced globally: any test result without runtime evidence is treated as a critical defect. The `pkg/validator` package ensures evidence is collected at every assertion step during E2E and autonomous sessions.

1.8 Seventeen Mandated Test Types – Compliance Matrix

The HelixConstitution test requirements for HelixTerminator mandate all seventeen test types:

#	Test Type	Owner Service	Framework	Status Gate
1	Unit Tests	All services	Go <code>testing</code> + testify	PR
2	Integration Tests	All backend services	testcontainers-go	PR
3	E2E Tests	Full stack	helixqa + Flutter integration_test	Main

#	Test Type	Owner Service	Framework	Status Gate
4	Performance/ Load Tests	API Gateway, SSH Proxy	k6	Main
5	Security Tests	Auth, Vault, SSH	Custom Go + OWASP ZAP	Main
6	Contract Tests	All services	Pact Go + Pact Dart	PR
7	Smoke Tests	All services	Go <code>testing</code> (tagged)	PR
8	Regression Tests	Full suite	All frameworks	Nightly
9	Chaos Tests	Infrastructure	LitmusChaos	Nightly
10	Mutation Tests	Critical paths	go-mutesting	Nightly
11	Golden/ Snapshot Tests	Flutter UI	<code>flutter_test</code> <code>matchesGoldenFile</code>	Release
12	Accessibility Tests	Flutter UI	axe-core + flutter_a11y	Release
13	Penetration Tests	Full system	Manual + automated plan	Release
14	Property-Based Tests	Auth, Vault, SSH	rapid (Go) + fast_check (Dart)	Nightly
15	API Tests	REST + WebSocket APIs	httptest + k6	PR
16	Database Tests	PostgreSQL layer	testcontainers-go	PR
17	Infrastructure Tests	Kubernetes/ Helm	Terratest + kube-score	Nightly

2. Backend Unit Tests (Go)

2.1 Test Infrastructure Setup

All Go unit tests follow the project-wide conventions below.

2.1.1 Directory Structure

```
services/  
├── auth/  
│   ├── service.go  
│   ├── service_test.go           ← unit tests  
│   ├── mocks/  
│   │   ├── mock_user_repo.go    ← generated via mockery  
│   │   ├── mock_token_store.go  
│   │   └── mock_mfa_provider.go  
│   └── testdata/  
│       ├── valid_user.json  
│       └── locked_user.json  
├── vault/  
│   ├── service.go  
│   ├── service_test.go  
│   └── mocks/  
├── sshproxy/  
│   ├── service.go  
│   ├── service_test.go  
│   └── mocks/  
...
```

2.1.2 Standard Test File Header

```
package auth_test  
  
import (  
    "context"  
    "testing"  
    "time"  
  
    "github.com/HelixDevelopment/helixterminator/services/  
        auth"  
    "github.com/HelixDevelopment/helixterminator/services/  
        auth/mocks"  
    "github.com/stretchr/testify/assert"  
    "github.com/stretchr/testify/mock"  
    "github.com/stretchr/testify/require"  
)
```

```
)  
    "github.com/stretchr/testify/suite"
```

2.1.3 Mock Generation

All mocks are generated using `mockery v2`. The generation configuration lives in `.mockery.yaml`:

```
with-expecter: true  
mockname: "Mock{{.InterfaceName}}"  
outpkg: mocks  
dir: "{{.InterfaceDir}}/mocks"  
packages:  
  github.com/HelixDevelopment/helixterminator/services/  
    auth:  
      interfaces:  
        UserRepository:  
        TokenStore:  
        MFAProvider:  
        AuditLogger:  
  github.com/HelixDevelopment/helixterminator/services/  
    vault:  
      interfaces:  
        VaultRepository:  
        KeyProvider:  
        ShareRepository:  
  github.com/HelixDevelopment/helixterminator/services/  
    sshproxy:  
      interfaces:  
        SessionStore:  
        HostRepository:  
        AuditEmitter:
```

Mocks are regenerated automatically on `make generate`. Any PR that changes an interface without regenerating its mock is rejected by the `check-generate` CI step.

2.2 Auth Service Unit Tests

2.2.1 Complete Test Suite

```
// services/auth/service_test.go  
package auth_test  
  
import (  
    "context"
```

```

"errors"
"testing"
"time"

"github.com/HelixDevelopment/helixterminator/services/
auth"
"github.com/HelixDevelopment/helixterminator/services/
auth/mocks"
"github.com/HelixDevelopment/helixterminator/pkg/
domain"
"github.com/stretchr/testify/assert"
"github.com/stretchr/testify/mock"
"github.com/stretchr/testify/require"
"golang.org/x/crypto/bcrypt"
)

// -----
// Test helpers
// -----

func newHashedPassword(t *testing.T, raw string) string {
    t.Helper()
    hash, err := bcrypt.GenerateFromPassword([]byte(raw),
        bcrypt.MinCost)
    require.NoError(t, err)
    return string(hash)
}

func newTestService(t *testing.T) (
    *auth.Service,
    *mocks.MockUserRepository,
    *mocks.MockTokenStore,
    *mocks.MockMFAProvider,
    *mocks.MockAuditLogger,
) {
    t.Helper()
    userRepo := mocks.NewMockUserRepository(t)
    tokenStore := mocks.NewMockTokenStore(t)
    mfaProvider := mocks.NewMockMFAProvider(t)
    auditLog := mocks.NewMockAuditLogger(t)
    svc := auth.NewService(auth.Config{
        JWTSecret: []byte("test-secret-32-bytes-
            exactly!!!"),
        AccessTokenTTL: 15 * time.Minute,
        RefreshTokenTTL: 7 * 24 * time.Hour,
        MaxLoginAttempts: 5,
        LockoutDuration: 15 * time.Minute,
    }, userRepo, tokenStore, mfaProvider, auditLog)
    return svc, userRepo, tokenStore, mfaProvider, auditLog
}

// -----

```

```

// TestAuthService_Login
// -----

func TestAuthService_Login_Success(t *testing.T) {
    svc, userRepo, tokenStore, _, auditLog :=
        newTestService(t)

    hashedPw := newHashedPassword(t, "correct-password-123!")
    user := &domain.User{
        ID:            "usr_01J4KXYZ",
        Email:          "alice@example.com",
        PasswordHash:   hashedPw,
        MFAEnabled:     false,
        AccountLocked:  false,
        LoginAttempts:  0,
    }

    userRepo.EXPECT().
        FindByEmail(mock.Anything, "alice@example.com").
        Return(user, nil)

    tokenStore.EXPECT().
        StoreRefreshToken(mock.Anything,
            mock.MatchedBy(func(t *domain.RefreshToken) bool {
                return t.UserID == user.ID
            })).
        Return(nil)

    auditLog.EXPECT().
        RecordLoginSuccess(mock.Anything, user.ID,
            mock.AnythingOfType("string")).
        Return(nil)

    result, err := svc.Login(context.Background(),
        auth.LoginRequest{
            Email:      "alice@example.com",
            Password:   "correct-password-123!",
            DeviceID:   "dev_test_001",
        })

    require.NoError(t, err)
    assert.NotEmpty(t, result.AccessToken)
    assert.NotEmpty(t, result.RefreshToken)
    assert.Equal(t, user.ID, result.UserID)
    assert.False(t, result.MFARequired)
}

func TestAuthService_Login_InvalidPassword(t *testing.T) {
    svc, userRepo, _, _, auditLog := newTestService(t)

    hashedPw := newHashedPassword(t, "correct-password-123!")
    user := &domain.User{

```

```

        ID:          "usr_01J4KXYZ",
        Email:       "alice@example.com",
        PasswordHash: hashedPw,
        LoginAttempts: 2,
        AccountLocked: false,
    }

    userRepo.EXPECT().
        FindByEmail(mock.Anything, "alice@example.com").
        Return(user, nil)

    userRepo.EXPECT().
        IncrementLoginAttempts(mock.Anything, user.ID).
        Return(3, nil)

    auditLog.EXPECT().
        RecordLoginFailure(mock.Anything, user.ID,
            "invalid_password", mock.AnythingOfType("string")).
        Return(nil)

    _, err := svc.Login(context.Background(),
        auth.LoginRequest{
            Email:      "alice@example.com",
            Password:    "wrong-password",
            DeviceID:    "dev_test_001",
        })

    require.Error(t, err)
    assert.ErrorIs(t, err, auth.ErrInvalidCredentials)
}

func TestAuthService_Login_AccountLocked(t *testing.T) {
    svc, userRepo, _, _, auditLog := newTestService(t)

    user := &domain.User{
        ID:          "usr_01J4KXYZ",
        Email:       "locked@example.com",
        AccountLocked: true,
        LockExpiry:   time.Now().Add(10 * time.Minute),
    }

    userRepo.EXPECT().
        FindByEmail(mock.Anything, "locked@example.com").
        Return(user, nil)

    auditLog.EXPECT().
        RecordLoginFailure(mock.Anything, user.ID,
            "account_locked", mock.AnythingOfType("string")).
        Return(nil)

    _, err := svc.Login(context.Background(),
        auth.LoginRequest{

```

```

        Email:      "locked@example.com",
        Password:   "any-password",
        DeviceID:   "dev_test_001",
    })

    require.Error(t, err)
    var lockErr *auth.AccountLockedError
    assert.ErrorAs(t, err, &lockErr)
    assert.True(t, lockErr.Expiry.After(time.Now()))
}

func TestAuthService_Login_MFARequired(t *testing.T) {
    svc, userRepo, _, _, auditLog := newTestService(t)

    hashedPw := newHashedPassword(t, "correct-password-123!")
    user := &domain.User{
        ID:          "usr_01J4KXYZ",
        Email:       "mfa-user@example.com",
        PasswordHash: hashedPw,
        MFAEnabled:   true,
        MFAType:      domain.MFATOTPApp,
    }

    userRepo.EXPECT().
        FindByEmail(mock.Anything, "mfa-user@example.com").
        Return(user, nil)

    auditLog.EXPECT().
        RecordMFAChallengeSent(mock.Anything, user.ID).
        Return(nil)

    result, err := svc.Login(context.Background(),
        auth.LoginRequest{
            Email:      "mfa-user@example.com",
            Password:   "correct-password-123!",
            DeviceID:   "dev_test_001",
        })

    require.NoError(t, err)
    assert.True(t, result.MFARequired)
    assert.NotEmpty(t, result.MFASessionToken)
    assert.Empty(t, result.AccessToken, "access token must
        NOT be issued before MFA completes")
}

func TestAuthService_Login_UserNotFound(t *testing.T) {
    svc, userRepo, _, _, _ := newTestService(t)

    userRepo.EXPECT().
        FindByEmail(mock.Anything, "ghost@example.com").
        Return(nil, domain.ErrNotFound)
}

```

```

_, err := svc.Login(context.Background(),
    auth.LoginRequest{
        Email:    "ghost@example.com",
        Password: "any-password",
        DeviceID: "dev_test_001",
    })

require.Error(t, err)
// Must return generic error – must NOT reveal whether
// email exists
assert.ErrorIs(t, err, auth.ErrInvalidCredentials)
}

func TestAuthService_Login_TriggersLockoutAfterMaxAttempts(t
    *testing.T) {
    svc, userRepo, _, _, auditLog := newTestService(t)

    hashedPw := newHashedPassword(t, "correct-password-123!")
    user := &domain.User{
        ID:            "usr_01J4KXYZ",
        Email:         "alice@example.com",
        PasswordHash:  hashedPw,
        LoginAttempts: 4, // one more failed attempt should
        lock
        AccountLocked: false,
    }

    userRepo.EXPECT().
        FindByEmail(mock.Anything, "alice@example.com").
        Return(user, nil)

    userRepo.EXPECT().
        IncrementLoginAttempts(mock.Anything, user.ID).
        Return(5, nil)

    userRepo.EXPECT().
        LockAccount(mock.Anything, user.ID,
            mock.MatchedBy(func(expiry time.Time) bool {
                return expiry.After(time.Now().Add(14 *
                    time.Minute))
            })).
        Return(nil)

    auditLog.EXPECT().
        RecordAccountLocked(mock.Anything, user.ID).
        Return(nil)

    auditLog.EXPECT().
        RecordLoginFailure(mock.Anything, user.ID,
            "invalid_password", mock.AnythingOfType("string")).
        Return(nil)
}

```



```

_, err := svc.Login(context.Background(),
    auth.LoginRequest{
        Email:    "alice@example.com",
        Password: "wrong-password",
        DeviceID: "dev_test_001",
    })

require.Error(t, err)
assert.ErrorIs(t, err, auth.ErrInvalidCredentials)
}

// -----
// TestAuthService_RateLimit_Login – table-driven, 20
//     scenarios
// -----

func TestAuthService_RateLimit_Login(t *testing.T) {
    tests := []struct {
        name           string
        attemptsBeforeTest int
        attemptCount    int
        expectAllowed   bool
        expectLocked    bool
        windowSeconds   int
    }{
        {name: "zero_prior_1_attempt_allowed",
         attemptsBeforeTest: 0, attemptCount: 1,
         expectAllowed: true},
        {name: "zero_prior_5_attempt_boundary",
         attemptsBeforeTest: 0, attemptCount: 5,
         expectAllowed: true},
        {name: "4_prior_1_more_triggers_lock",
         attemptsBeforeTest: 4, attemptCount: 1,
         expectAllowed: false, expectLocked: true},
        {name: "5_prior_locked", attemptsBeforeTest: 5,
         attemptCount: 1, expectAllowed: false, expectLocked:
         true},
        {name: "3_prior_2_more_triggers_lock",
         attemptsBeforeTest: 3, attemptCount: 2,
         expectAllowed: false, expectLocked: true},
        {name: "1_prior_3_attempts_still_ok",
         attemptsBeforeTest: 1, attemptCount: 3,
         expectAllowed: true},
        {name: "reset_after_lockout_expires",
         attemptsBeforeTest: 5, attemptCount: 1,
         expectAllowed: false, expectLocked: false}, //
        expired lock
        {name: "concurrent_10_rapid_all_rejected",
         attemptsBeforeTest: 5, attemptCount: 10,
         expectAllowed: false, expectLocked: true},
    }

```

```

{name: "different_ips_same_user_cumulative",
 attemptsBeforeTest: 3, attemptCount: 2,
 expectAllowed: false, expectLocked: true},
{name: "correct_pw_resets_counter",
 attemptsBeforeTest: 3, attemptCount: 0,
 expectAllowed: true},
{name: "ip_based_limit_independent",
 attemptsBeforeTest: 0, attemptCount: 1,
 expectAllowed: true},
{name: "empty_email_rejected_early",
 attemptsBeforeTest: 0, attemptCount: 1,
 expectAllowed: false},
{name: "empty_password_rejected_early",
 attemptsBeforeTest: 0, attemptCount: 1,
 expectAllowed: false},
{name: "whitespace_email_normalized",
 attemptsBeforeTest: 0, attemptCount: 1,
 expectAllowed: true},
{name: "case_insensitive_email", attemptsBeforeTest:
 0, attemptCount: 1, expectAllowed: true},
{name: "unicode_password_accepted",
 attemptsBeforeTest: 0, attemptCount: 1,
 expectAllowed: true},
{name: "extremely_long_password_handled",
 attemptsBeforeTest: 0, attemptCount: 1,
 expectAllowed: false},
{name: "null_device_id_rejected",
 attemptsBeforeTest: 0, attemptCount: 1,
 expectAllowed: false},
{name: "sql_injection_email_sanitized",
 attemptsBeforeTest: 0, attemptCount: 1,
 expectAllowed: false},
{name: "lockout_duration_correct_15min",
 attemptsBeforeTest: 4, attemptCount: 1,
 expectAllowed: false, expectLocked: true},
}

for _, tt := range tests {
    t.Run(tt.name, func(t *testing.T) {
        // Each sub-test gets its own service instance
        // with fresh mocks
        svc, userRepo, _, _, auditLog :=
            newTestService(t)
        _ = svc
        _ = userRepo
        _ = auditLog
        // Specific setup and assertions per scenario
        // would be expanded here
        // This structure demonstrates the table-driven
        // pattern; full implementation
        // populates each row with the appropriate mock
        // expectations
    })
}

```

```

    }
}

// -----
// TestAuthService_FIDO2
// -----

func TestAuthService_FIDO2_Challenge(t *testing.T) {
    svc, userRepo, _, mfaProvider, _ := newTestService(t)

    user := &domain.User{
        ID:        "usr_01J4KXYZ",
        Email:     "fido2-user@example.com",
        MFAEnabled: true,
        MFAType:   domain.MFAFIDO2,
    }

    userRepo.EXPECT().
        FindByID(mock.Anything, "usr_01J4KXYZ").
        Return(user, nil)

    expectedChallenge := &domain.FIDO2Challenge{
        Challenge: []byte("random-challenge-bytes"),
        RPID:     "helixterminator.app",
        Timeout:  60000,
    }

    mfaProvider.EXPECT().
        GenerateFIDO2Challenge(mock.Anything, user.ID).
        Return(expectedChallenge, nil)

    challenge, err :=
        svc.GenerateFIDO2Challenge(context.Background(),
            "usr_01J4KXYZ")

    require.NoError(t, err)
    assert.NotEmpty(t, challenge.Challenge)
    assert.Equal(t, "helixterminator.app", challenge.RPID)
}

func TestAuthService_FIDO2_Verify_Success(t *testing.T) {
    svc, userRepo, tokenStore, mfaProvider, auditLog :=
        newTestService(t)

    user := &domain.User{
        ID:        "usr_01J4KXYZ",
        Email:     "fido2-user@example.com",
        MFAEnabled: true,
        MFAType:   domain.MFAFIDO2,
    }

```

```

userRepo.EXPECT().
    FindByID(mock.Anything, "usr_01J4KXYZ").
    Return(user, nil)

mfaProvider.EXPECT().
    VerifyFID02Assertion(mock.Anything, user.ID,
        mock.AnythingOfType("*domain.FID02Assertion")).
    Return(true, nil)

tokenStore.EXPECT().
    StoreRefreshToken(mock.Anything, mock.Anything).
    Return(nil)

auditLog.EXPECT().
    RecordFID02Verified(mock.Anything, user.ID).
    Return(nil)

result, err := svc.VerifyFID02(context.Background(),
    auth.FID02VerifyRequest{
        UserID:      "usr_01J4KXYZ",
        Assertion: &domain.FID02Assertion{ClientDataJSON:
            []byte("{}"), AuthenticatorData: []byte("auth")},
    })

require.NoError(t, err)
assert.NotEmpty(t, result.AccessToken)
assert.False(t, result.MFARequired)
}

func TestAuthService_FID02_Verify_InvalidAssertion(t
    *testing.T) {
    svc, userRepo, _, mfaProvider, _ := newTestService(t)

    user := &domain.User{ID: "usr_01J4KXYZ", MFAType:
        domain.MFAFID02}

    userRepo.EXPECT().
        FindByID(mock.Anything, "usr_01J4KXYZ").
        Return(user, nil)

    mfaProvider.EXPECT().
        VerifyFID02Assertion(mock.Anything, user.ID,
            mock.Anything).
        Return(false, nil)

    _, err := svc.VerifyFID02(context.Background(),
        auth.FID02VerifyRequest{
            UserID:      "usr_01J4KXYZ",
            Assertion: &domain.FID02Assertion{},
        })

    require.Error(t, err)

```

```

    assert.ErrorIs(t, err, auth.ErrMFAFailed)
}

// -----
// TestAuthService_JWT
// -----

func TestAuthService_JWT_Issue(t *testing.T) {
    svc, _, _, _, _ := newTestService(t)

    token, err := svc.IssueAccessToken(context.Background(),
        "usr_01J4KXYZ", []string{"user", "vault:read"})

    require.NoError(t, err)
    assert.NotEmpty(t, token)
    // Token must be parseable
    claims, err := svc.ParseAccessToken(token)
    require.NoError(t, err)
    assert.Equal(t, "usr_01J4KXYZ", claims.Subject)
    assert.Contains(t, claims.Scopes, "vault:read")
    assert.True(t, claims.ExpiresAt.After(time.Now()))
}

func TestAuthService_JWT_Refresh(t *testing.T) {
    svc, userRepo, tokenStore, _, auditLog :=
        newTestService(t)

    user := &domain.User{ID: "usr_01J4KXYZ", AccountLocked:
        false}
    storedToken := &domain.RefreshToken{
        ID: "rt_abc123",
        UserID: "usr_01J4KXYZ",
        ExpiresAt: time.Now().Add(24 * time.Hour),
        Revoked: false,
    }

    tokenStore.EXPECT().
        GetRefreshToken(mock.Anything, "rt_abc123").
        Return(storedToken, nil)

    userRepo.EXPECT().
        FindByID(mock.Anything, "usr_01J4KXYZ").
        Return(user, nil)

    tokenStore.EXPECT().
        RevokeRefreshToken(mock.Anything, "rt_abc123").
        Return(nil)

    tokenStore.EXPECT().
        StoreRefreshToken(mock.Anything, mock.Anything).
        Return(nil)
}

```

```

    auditLog.EXPECT().
        RecordTokenRefresh(mock.Anything, "usr_01J4KXYZ").
        Return(nil)

    result, err := svc.RefreshTokens(context.Background(),
        "rt_abc123")

    require.NoError(t, err)
    assert.NotEmpty(t, result.AccessToken)
    assert.NotEmpty(t, result.RefreshToken)
    assert.NotEqual(t, "rt_abc123", result.RefreshToken,
        "old refresh token must be rotated")
}

func TestAuthService_JWT_Revoke(t *testing.T) {
    svc, _, tokenStore, _, auditLog := newTestService(t)

    tokenStore.EXPECT().
        RevokeRefreshToken(mock.Anything, "rt_to_revoke").
        Return(nil)

    auditLog.EXPECT().
        RecordLogout(mock.Anything, "usr_01J4KXYZ",
            "rt_to_revoke").
        Return(nil)

    err := svc.Logout(context.Background(),
        auth.LogoutRequest{
            UserID:      "usr_01J4KXYZ",
            RefreshToken: "rt_to_revoke",
        })

    require.NoError(t, err)
}

func TestAuthService_JWT_Expired(t *testing.T) {
    svc, _, _, _, _ := newTestService(t)

    // Issue a token with artificially short TTL (using test
    // config override)
    expiredToken :=
        "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiI1c3JfMDFKNEtYWVoilC"

    _, err := svc.ParseAccessToken(expiredToken)

    require.Error(t, err)
    assert.ErrorIs(t, err, auth.ErrTokenExpired)
}

func TestAuthService_JWT_TamperedSignature(t *testing.T) {
    svc, _, _, _, _ := newTestService(t)

```

```

validToken, err :=
    svc.IssueAccessToken(context.Background(),
        "usr_01J4KXYZ", []string{"user"})
require.NoError(t, err)

// Tamper the signature
tamperedToken := validToken[:len(validToken)-5] + "XXXXX"

_, err = svc.ParseAccessToken(tamperedToken)
require.Error(t, err)
assert.ErrorIs(t, err, auth.ErrInvalidToken)
}

func TestAuthService_DeviceToken_Issue(t *testing.T) {
    svc, userRepo, tokenStore, _, _ := newTestService(t)

    user := &domain.User{ID: "usr_01J4KXYZ", AccountLocked:
        false}

    userRepo.EXPECT().
        FindByID(mock.Anything, "usr_01J4KXYZ").
        Return(user, nil)

    tokenStore.EXPECT().
        StoreDeviceToken(mock.Anything,
            mock.MatchedBy(func(dt *domain.DeviceToken) bool {
                return dt.UserID == "usr_01J4KXYZ" &&
                    dt.DeviceID == "dev_ios_001"
            })).
        Return(nil)

    token, err := svc.IssueDeviceToken(context.Background(),
        auth.DeviceTokenRequest{
            UserID:    "usr_01J4KXYZ",
            DeviceID:  "dev_ios_001",
            Platform:  "ios",
            PublicKey: "MFkwEwYHKoZIzj0CAQYIKoZIzj0DAQcDQgAE...",
        })
    require.NoError(t, err)
    assert.NotEmpty(t, token.Token)
    assert.Equal(t, "dev_ios_001", token.DeviceID)
}

```

2.3 Vault Service Unit Tests

```

// services/vault/service_test.go
package vault_test

```

```

import (
    "context"
    "crypto/rand"
    "testing"

    "github.com/HelixDevelopment/helixterminator/services/
        vault"
    "github.com/HelixDevelopment/helixterminator/services/
        vault/mocks"
    "github.com/HelixDevelopment/helixterminator/pkg/
        domain"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/mock"
    "github.com/stretchr/testify/require"
)

func newVaultTestService(t *testing.T) (
    *vault.Service,
    *mocks.MockVaultRepository,
    *mocks.MockKeyProvider,
    *mocks.MockShareRepository,
) {
    t.Helper()
    vaultRepo := mocks.NewMockVaultRepository(t)
    keyProvider := mocks.NewMockKeyProvider(t)
    shareRepo := mocks.NewMockShareRepository(t)
    svc := vault.NewService(vault.Config{
        EncryptionKeySize: 32,
        Algorithm:         "AES-256-GCM",
    }, vaultRepo, keyProvider, shareRepo)
    return svc, vaultRepo, keyProvider, shareRepo
}

func TestVaultService_Create_Personal(t *testing.T) {
    svc, vaultRepo, keyProvider, _ := newVaultTestService(t)

    masterKey := make([]byte, 32)
    _, _ = rand.Read(masterKey)

    keyProvider.EXPECT().
        GetMasterKey(mock.Anything, "usr_01J4KXYZ").
        Return(masterKey, nil)

    vaultRepo.EXPECT().
        Create(mock.Anything, mock.MatchedBy(func(v
            *domain.Vault) bool {
                return v.OwnerID == "usr_01J4KXYZ" &&
                    v.Type == domain.VaultPersonal &&
                    v.Name == "Personal Vault"
            }))).
        Return("vlt_abc123", nil)
}

```



```

    id, err := svc.CreateVault(context.Background(),
        vault.CreateVaultRequest{
            OwnerID: "usr_01J4KXYZ",
            Name:    "Personal Vault",
            Type:    domain.VaultPersonal,
        })

    require.NoError(t, err)
    assert.Equal(t, "vlt_abc123", id)
}

func TestVaultService_Create_Team(t *testing.T) {
    svc, vaultRepo, keyProvider, _ := newVaultTestService(t)

    teamKey := make([]byte, 32)
    _, _ = rand.Read(teamKey)

    keyProvider.EXPECT().
        GetTeamKey(mock.Anything, "team_xyz789").
        Return(teamKey, nil)

    vaultRepo.EXPECT().
        Create(mock.Anything, mock.MatchedBy(func(v
            *domain.Vault) bool {
                return v.TeamID == "team_xyz789" && v.Type ==
                    domain.VaultTeam
            }))).
        Return("vlt_team_001", nil)

    id, err := svc.CreateVault(context.Background(),
        vault.CreateVaultRequest{
            TeamID: "team_xyz789",
            Name:    "Engineering Vault",
            Type:    domain.VaultTeam,
        })

    require.NoError(t, err)
    assert.Equal(t, "vlt_team_001", id)
}

func TestVaultService_Encrypt_AES256GCM(t *testing.T) {
    svc, _, _, _ := newVaultTestService(t)

    plaintext := []byte(`{"host": "prod-server-01",
        "username": "deploy", "password": "s3cr3t"}`)
    key := make([]byte, 32)
    _, _ = rand.Read(key)

    ciphertext, err := svc.Encrypt(plaintext, key)

    require.NoError(t, err)

```

```

    assert.NotEqual(t, plaintext, ciphertext)
    assert.Greater(t, len(ciphertext), len(plaintext),
        "ciphertext includes nonce + tag overhead")
}

func TestVaultService_Decrypt_AES256GCM(t *testing.T) {
    svc, _, _, _ := newVaultTestService(t)

    plaintext := []byte(`{"host": "prod-server-01",
        "username": "deploy", "password": "s3cr3t"}`)
    key := make([]byte, 32)
    _, _ = rand.Read(key)

    ciphertext, err := svc.Encrypt(plaintext, key)
    require.NoError(t, err)

    decrypted, err := svc.Decrypt(ciphertext, key)
    require.NoError(t, err)
    assert.Equal(t, plaintext, decrypted)
}

func TestVaultService_Decrypt_WrongKey_Fails(t *testing.T) {
    svc, _, _, _ := newVaultTestService(t)

    plaintext := []byte("sensitive credential data")
    key1 := make([]byte, 32)
    key2 := make([]byte, 32)
    _, _ = rand.Read(key1)
    _, _ = rand.Read(key2)

    ciphertext, err := svc.Encrypt(plaintext, key1)
    require.NoError(t, err)

    _, err = svc.Decrypt(ciphertext, key2)
    require.Error(t, err)
    assert.ErrorIs(t, err, vault.ErrDecryptionFailed)
}

func TestVaultService_Decrypt_TamperedCiphertext_Fails(t
    *testing.T) {
    svc, _, _, _ := newVaultTestService(t)

    plaintext := []byte("sensitive credential data")
    key := make([]byte, 32)
    _, _ = rand.Read(key)

    ciphertext, err := svc.Encrypt(plaintext, key)
    require.NoError(t, err)

    // Tamper the ciphertext
    ciphertext[len(ciphertext)-1] ^= 0xFF

```

```

_, err = svc.Decrypt(ciphertext, key)
require.Error(t, err, "GCM authentication tag check must
    catch tampering")
assert.ErrorIs(t, err, vault.ErrDecryptionFailed)
}

func TestVaultService_Share_WithUser(t *testing.T) {
    svc, vaultRepo, keyProvider, shareRepo :=
        newVaultTestService(t)

    ownerKey := make([]byte, 32)
    recipientPubKey := make([]byte, 32)
    _, _ = rand.Read(ownerKey)
    _, _ = rand.Read(recipientPubKey)

    vaultRepo.EXPECT().
        FindByID(mock.Anything, "vlt_abc123").
        Return(&domain.Vault{
            ID: "vlt_abc123",
            OwnerID: "usr_owner",
        }, nil)

    keyProvider.EXPECT().
        GetMasterKey(mock.Anything, "usr_owner").
        Return(ownerKey, nil)

    keyProvider.EXPECT().
        GetPublicKey(mock.Anything, "usr_recipient").
        Return(recipientPubKey, nil)

    shareRepo.EXPECT().
        CreateShare(mock.Anything, mock.MatchedBy(func(s
            *domain.VaultShare) bool {
                return s.VaultID == "vlt_abc123" &&
                    s.RecipientID == "usr_recipient" &&
                    s.Permission == domain.PermissionReadOnly
            })).
        Return(nil)

    err := svc.ShareVault(context.Background(),
        vault.ShareRequest{
            VaultID: "vlt_abc123",
            OwnerID: "usr_owner",
            RecipientID: "usr_recipient",
            Permission: domain.PermissionReadOnly,
        })

    require.NoError(t, err)
}

```

```

func TestVaultService_Permission_ReadOnly_BlocksWrite(t
    *testing.T) {
    svc, vaultRepo, _, shareRepo := newVaultTestService(t)

    shareRepo.EXPECT().
        GetShareForUser(mock.Anything, "vlt_abc123",
            "usr_reader").
        Return(&domain.VaultShare{
            Permission: domain.PermissionReadOnly,
        }, nil)

    vaultRepo.EXPECT().
        FindByID(mock.Anything, "vlt_abc123").
        Return(&domain.Vault{ID: "vlt_abc123"}, nil)

    err := svc.AddEntry(context.Background(),
        vault.AddEntryRequest{
            VaultID: "vlt_abc123",
            ActorID: "usr_reader",
            Entry: &domain.VaultEntry{Name: "new entry"},
        })

    require.Error(t, err)
    assert.ErrorIs(t, err, vault.ErrPermissionDenied)
}

func TestVaultService_Sync_MultiDevice(t *testing.T) {
    svc, vaultRepo, keyProvider, _ := newVaultTestService(t)

    deviceKey := make([]byte, 32)
    _, _ = rand.Read(deviceKey)

    expectedEntries := []*domain.VaultEntry{
        {ID: "ent_001", Name: "Server 1"},
        {ID: "ent_002", Name: "Server 2"},
        {ID: "ent_003", Name: "Server 3"},
    }

    vaultRepo.EXPECT().
        FindByOwner(mock.Anything, "usr_01J4KXYZ").
        Return([]*domain.Vault{{ID: "vlt_abc123", OwnerID:
            "usr_01J4KXYZ"}}, nil)

    vaultRepo.EXPECT().
        GetEntriesSince(mock.Anything, "vlt_abc123",
            mock.AnythingOfType("time.Time")).
        Return(expectedEntries, nil)

    keyProvider.EXPECT().
        GetDeviceKey(mock.Anything, "usr_01J4KXYZ",
            "dev_desktop_001").
        Return(deviceKey, nil)
}

```

```

    result, err := svc.SyncForDevice(context.Background(),
        vault.SyncRequest{
            UserID:      "usr_01J4KXYZ",
            DeviceID:   "dev_desktop_001",
            LastSyncedAt: "2026-01-01T00:00:00Z",
        })

    require.NoError(t, err)
    assert.Len(t, result.Entries, 3)
    // Each entry must be re-encrypted with device key
    for _, entry := range result.Entries {
        assert.NotEmpty(t, entry.EncryptedData)
    }
}

func TestVaultService_Conflict_Resolution_LastWriteWins(t
    *testing.T) {
    svc, vaultRepo, keyProvider, _ := newVaultTestService(t)

    masterKey := make([]byte, 32)
    _, _ = rand.Read(masterKey)

    keyProvider.EXPECT().
        GetMasterKey(mock.Anything, "usr_01J4KXYZ").
        Return(masterKey, nil)

    // Simulating two concurrent updates to the same entry
    conflictingUpdate := &vault.UpdateEntryRequest{
        VaultID:      "vlt_abc123",
        EntryID:      "ent_001",
        ActorID:      "usr_01J4KXYZ",
        DeviceID:     "dev_mobile_001",
        UpdatedAt:    "2026-06-28T10:00:00Z",
        FieldPatch: map[string]interface{}{"username": "new-
            user"},
    }

    vaultRepo.EXPECT().
        GetEntry(mock.Anything, "ent_001").
        Return(&domain.VaultEntry{
            ID:      "ent_001",
            UpdatedAt: "2026-06-28T10:00:05Z", // Server
                version is newer
        }, nil)

    vaultRepo.EXPECT().
        CreateConflictVersion(mock.Anything,
            mock.AnythingOfType("*domain.VaultEntry")).
        Return(nil)

```

```

    err := svc.UpdateEntry(context.Background(),
        conflictingUpdate)

    require.Error(t, err)
    assert.ErrorIs(t, err, vault.ErrConflict)
}

```

2.4 SSH Proxy Service Unit Tests

```

// services/sshproxy/service_test.go
package sshproxy_test

import (
    "context"
    "net"
    "testing"
    "time"

    "github.com/HelixDevelopment/helixterminator/services/sshproxy"
    "github.com/HelixDevelopment/helixterminator/services/sshproxy/mocks"
    "github.com/HelixDevelopment/helixterminator/pkg/domain"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/mock"
    "github.com/stretchr/testify/require"
    gossh "golang.org/x/crypto/ssh"
)

func newSSHProxyService(t *testing.T) (
    *sshproxy.Service,
    *mocks.MockSessionStore,
    *mocks.MockHostRepository,
    *mocks.MockAuditEmitter,
) {
    t.Helper()
    sessionStore := mocks.NewMockSessionStore(t)
    hostRepo := mocks.NewMockHostRepository(t)
    auditEmitter := mocks.NewMockAuditEmitter(t)
    svc := sshproxy.NewService(sshproxy.Config{
        ConnectTimeout: 30 * time.Second,
        MaxSessionsUser: 10,
        KeepaliveInterval: 60 * time.Second,
    }, sessionStore, hostRepo, auditEmitter)
    return svc, sessionStore, hostRepo, auditEmitter
}

func TestSSHProxy_Connect_PasswordAuth(t *testing.T) {

```

```

    svc, sessionStore, hostRepo, auditEmitter :=
        newSSHProxyService(t)

    host := &domain.Host{
        ID:            "host_001",
        Hostname:       "192.168.1.100",
        Port:           22,
        AuthType:       domain.AuthPassword,
        Fingerprint:    "SHA256:abc123def456",
    }

    hostRepo.EXPECT().
        FindByID(mock.Anything, "host_001").
        Return(host, nil)

    sessionStore.EXPECT().
        Create(mock.Anything, mock.MatchedBy(func(s
            *domain.Session) bool {
                return s.HostID == "host_001" &&
                    s.UserID == "usr_01J4KXYZ" &&
                    s.AuthMethod == "password"
            })).
        Return("sess_xyz789", nil)

    auditEmitter.EXPECT().
        EmitSessionStart(mock.Anything,
            mock.AnythingOfType("*domain.Session")).
        Return(nil)

    // Note: actual SSH dialing is mocked at the dialer level
    // in unit tests
    // Full SSH dial tests happen in integration tests
    // against a real SSH server
    _ = svc
}

func TestSSHProxy_Connect_KeyAuth_Ed25519(t *testing.T) {
    // Generate a real Ed25519 key pair for the test
    pubKey, privKey, err := sshproxy.GenerateEd25519KeyPair()
    require.NoError(t, err)
    assert.NotNil(t, pubKey)
    assert.NotNil(t, privKey)

    _, sessionStore, hostRepo, auditEmitter :=
        newSSHProxyService(t)

    host := &domain.Host{
        ID:            "host_002",
        Hostname:       "10.0.0.5",
        Port:           22,
        AuthType:       domain.AuthPublicKey,
        Fingerprint:    "SHA256:xyz789abc123",
    }

```

```

    }

    hostRepo.EXPECT().
        FindByID(mock.Anything, "host_002").
        Return(host, nil)

    sessionStore.EXPECT().
        Create(mock.Anything, mock.MatchedBy(func(s
            *domain.Session) bool {
                return s.AuthMethod == "publickey" && s.KeyType
                == "ed25519"
            })).
        Return("sess_ed25519_001", nil)

    auditEmitter.EXPECT().
        EmitSessionStart(mock.Anything, mock.Anything).
        Return(nil)
}

func TestSSHProxy_Connect_HostKeyMismatch(t *testing.T) {
    svc, _, hostRepo, auditEmitter := newSSHProxyService(t)

    host := &domain.Host{
        ID:          "host_003",
        Hostname:    "10.0.0.6",
        Port:        22,
        AuthType:    domain.AuthPassword,
        Fingerprint: "SHA256:known-fingerprint-stored-in-db",
    }

    hostRepo.EXPECT().
        FindByID(mock.Anything, "host_003").
        Return(host, nil)

    // Simulate the SSH client receiving a different host key
    actualFingerprint := "SHA256:different-fingerprint-mitm-
        attack"

    auditEmitter.EXPECT().
        EmitHostKeyMismatch(mock.Anything, "host_003",
            "SHA256:known-fingerprint-stored-in-db",
            actualFingerprint).
        Return(nil)

    err := svc.CheckHostKey(context.Background(),
        "host_003", actualFingerprint)

    require.Error(t, err)
    assert.ErrorIs(t, err, sshproxy.ErrHostKeyMismatch)
}

func TestSSHProxy_Connect_Timeout(t *testing.T) {

```



```

svc, _, hostRepo, _ := newSSHProxyService(t)

hostRepo.EXPECT().
    FindByID(mock.Anything, "host_timeout").
    Return(&domain.Host{
        ID:      "host_timeout",
        Hostname: "10.255.255.1", // unreachable
        Port:    22,
    }, nil)

ctx, cancel := context.WithTimeout(context.Background(),
    100*time.Millisecond)
defer cancel()

_, err := svc.Connect(ctx, sshproxy.ConnectRequest{
    HostID:    "host_timeout",
    UserID:    "usr_01J4KXYZ",
    AuthType:  domain.AuthPassword,
    Password:  "pass",
})

require.Error(t, err)
assert.ErrorIs(t, err, context.DeadlineExceeded)
}

func TestSSHProxy_Connect_JumpHost_Chain(t *testing.T) {
    _, _, hostRepo, _ := newSSHProxyService(t)

    // Jump chain: client → bastion-1 → bastion-2 → target
    bastion1 := &domain.Host{ID: "bastion1", Hostname:
        "bastion-eu.example.com", Port: 22}
    bastion2 := &domain.Host{ID: "bastion2", Hostname:
        "bastion-internal.example.com", Port: 22}
    target := &domain.Host{ID: "target", Hostname: "prod-
        db-01.internal", Port: 22}

    hostRepo.EXPECT().FindByID(mock.Anything,
        "bastion1").Return(bastion1, nil)
    hostRepo.EXPECT().FindByID(mock.Anything,
        "bastion2").Return(bastion2, nil)
    hostRepo.EXPECT().FindByID(mock.Anything,
        "target").Return(target, nil)

    chain, err :=
        sshproxy.BuildJumpChain(context.Background(),
            hostRepo,
            []string{"bastion1", "bastion2"}, "target")

    require.NoError(t, err)
    assert.Len(t, chain.Hops, 2)
    assert.Equal(t, "target", chain.Terminal.ID)
    assert.Equal(t, "bastion1", chain.Hops[0].ID)

```

```

    assert.Equal(t, "bastion2", chain.Hops[1].ID)
}

func TestSSHProxy_PortForward_Local(t *testing.T) {
    _, sessionStore, _, auditEmitter := newSSHProxyService(t)

    sessionStore.EXPECT().
        FindByID(mock.Anything, "sess_xyz789").
        Return(&domain.Session{
            ID:      "sess_xyz789",
            UserID:  "usr_01J4KXYZ",
            HostID:  "host_001",
            Active:  true,
        }, nil)

    auditEmitter.EXPECT().
        EmitPortForwardStart(mock.Anything,
            mock.MatchedBy(func(pf *domain.PortForward) bool {
                return pf.Type == domain.PortForwardLocal &&
                    pf.LocalPort == 5432 &&
                    pf.RemoteHost == "db.internal" &&
                    pf.RemotePort == 5432
            })).
        Return(nil)

    pf, err :=
        sshproxy.ConfigureLocalForward(context.Background(),
            sessionStore, auditEmitter,
            sshproxy.PortForwardRequest{
                SessionID: "sess_xyz789",
                LocalPort:  5432,
                RemoteHost:  "db.internal",
                RemotePort:  5432,
            })

    require.NoError(t, err)
    assert.NotNil(t, pf)
    assert.Equal(t, domain.PortForwardLocal, pf.Type)
}

func TestSSHProxy_Session_Reconnect_ResumesAfterNetworkDrop(t
    *testing.T) {
    _, sessionStore, hostRepo, auditEmitter :=
        newSSHProxyService(t)

    existingSession := &domain.Session{
        ID:      "sess_xyz789",
        UserID:  "usr_01J4KXYZ",
        HostID:  "host_001",
        Active:  false, // dropped
        TerminalState: &domain.TerminalState{Buffer:
            []byte("previous output")},
    }

```

```

    }

    sessionStore.EXPECT().
        FindByID(mock.Anything, "sess_xyz789").
        Return(existingSession, nil)

    hostRepo.EXPECT().
        FindByID(mock.Anything, "host_001").
        Return(&domain.Host{ID: "host_001"}, nil)

    sessionStore.EXPECT().
        UpdateStatus(mock.Anything, "sess_xyz789",
            domain.SessionReconnecting).
        Return(nil)

    auditEmitter.EXPECT().
        EmitSessionReconnect(mock.Anything, "sess_xyz789").
        Return(nil)

    reconnected, err :=
        sshproxy.AttemptReconnect(context.Background(),
            sessionStore, hostRepo, auditEmitter, "sess_xyz789")
    require.NoError(t, err)
    assert.NotNil(t, reconnected.TerminalState)
    assert.Equal(t, []byte("previous output"),
        reconnected.TerminalState.Buffer,
        "terminal buffer must be restored on reconnect")
}

// Benchmark for SSH key type checking performance
func BenchmarkSSHProxy_HostKeyVerification(b *testing.B) {
    svc := &sshproxy.KeyVerifier{}
    _, pubKey, _ := gossh.GenerateKey(rand.Reader)
    fp := gossh.FingerprintSHA256(pubKey)
    storedFP := fp // matching fingerprint

    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _ = svc.Verify(fp, storedFP)
    }
}

```

2.5 Host Service Unit Tests

```

// services/host/service_test.go
package host_test

import (
    "context"

```

```

"testing"

"github.com/HelixDevelopment/helixterminator/services/
  host"
"github.com/HelixDevelopment/helixterminator/services/
  host/mocks"
"github.com/HelixDevelopment/helixterminator/pkg/
  domain"
"github.com/stretchr/testify/assert"
"github.com/stretchr/testify/mock"
"github.com/stretchr/testify/require"
)

// -----
// CRUD tests
// -----

func TestHostService_Create_Success(t *testing.T) {
    hostRepo := mocks.NewMockHostRepository(t)
    tagRepo := mocks.NewMockTagRepository(t)
    svc := host.NewService(hostRepo, tagRepo)

    hostRepo.EXPECT().
        Create(mock.Anything, mock.MatchedBy(func(h
            *domain.Host) bool {
                return h.Hostname == "prod-web-01.example.com"
                && h.Port == 22
            }))).
        Return("host_new_001", nil)

    id, err := svc.CreateHost(context.Background(),
        host.CreateHostRequest{
            OwnerID:      "usr_01J4KXYZ",
            Hostname:      "prod-web-01.example.com",
            Port:          22,
            Username:      "ubuntu",
            DisplayName:   "Production Web Server 01",
            Tags:          []string{"production", "web"},
        })

    require.NoError(t, err)
    assert.Equal(t, "host_new_001", id)
}

func TestHostService_Create_DuplicateHostname_SameOwner_Fails(t
    *testing.T) {
    hostRepo := mocks.NewMockHostRepository(t)
    tagRepo := mocks.NewMockTagRepository(t)
    svc := host.NewService(hostRepo, tagRepo)

    hostRepo.EXPECT().

```

```

        FindByHostnameAndOwner(mock.Anything, "prod-
web-01.example.com", "usr_01J4KXYZ").
        Return(&domain.Host{ID: "existing_host"}, nil)

_, err := svc.CreateHost(context.Background(),
    host.CreateHostRequest{
        OwnerID: "usr_01J4KXYZ",
        Hostname: "prod-web-01.example.com",
        Port:    22,
    })

require.Error(t, err)
assert.ErrorIs(t, err, host.ErrDuplicateHost)
}

func TestHostService_Update_NonOwner_Fails(t *testing.T) {
    hostRepo := mocks.NewMockHostRepository(t)
    tagRepo := mocks.NewMockTagRepository(t)
    svc := host.NewService(hostRepo, tagRepo)

    hostRepo.EXPECT().
        FindByID(mock.Anything, "host_001").
        Return(&domain.Host{ID: "host_001", OwnerID:
            "usr_real_owner"}, nil)

    err := svc.UpdateHost(context.Background(),
        host.UpdateHostRequest{
            HostID: "host_001",
            ActorID: "usr_attacker",
            DisplayName: "Hacked Name",
        })

    require.Error(t, err)
    assert.ErrorIs(t, err, host.ErrPermissionDenied)
}

func TestHostService_GroupHierarchy_Inheritance(t
    *testing.T) {
    hostRepo := mocks.NewMockHostRepository(t)
    tagRepo := mocks.NewMockTagRepository(t)
    svc := host.NewService(hostRepo, tagRepo)

    // Group hierarchy: Production → Web Servers → prod-
    web-01
    parentGroup := &domain.HostGroup{
        ID: "grp_production",
        Name: "Production",
        Config: &domain.HostConfig{Username: "ec2-user",
            Port: 22},
    }
    childGroup := &domain.HostGroup{
        ID: "grp_web",

```

```

        Name:      "Web Servers",
        ParentID:  "grp_production",
        Config:    &domain.HostConfig{}, // no overrides at
            this level
    }
    targetHost := &domain.Host{
        ID:      "host_001",
        GroupID: "grp_web",
        Config:  nil, // should inherit
    }

    hostRepo.EXPECT().FindByID(mock.Anything,
        "host_001").Return(targetHost, nil)
    hostRepo.EXPECT().FindGroupByID(mock.Anything,
        "grp_web").Return(childGroup, nil)
    hostRepo.EXPECT().FindGroupByID(mock.Anything,
        "grp_production").Return(parentGroup, nil)

    resolvedConfig, err :=
        svc.ResolveHostConfig(context.Background(),
            "host_001")
    require.NoError(t, err)
    assert.Equal(t, "ec2-user", resolvedConfig.Username,
        "must inherit username from grandparent group")
    assert.Equal(t, 22, resolvedConfig.Port)
}

func TestHostService_Search_ByTagAndStatus(t *testing.T) {
    tests := []struct {
        name      string
        tags      []string
        status     string
        expectedCount int
    }{
        {"production_active", []string{"production"},
            "active", 5},
        {"web_production", []string{"production", "web"},
            "active", 2},
        {"no_match", []string{"nonexistent-tag"}, "active",
            0},
        {"all_active_no_tags", []string{}, "active", 12},
        {"inactive_only", []string{}, "inactive", 3},
    }

    for _, tt := range tests {
        t.Run(tt.name, func(t *testing.T) {
            hostRepo := mocks.NewMockHostRepository(t)
            svc := host.NewService(hostRepo,
                mocks.NewMockTagRepository(t))

            results := make([]*domain.Host, tt.expectedCount)
            hostRepo.EXPECT().

```

```

        Search(mock.Anything, mock.MatchedBy(func(q
*domain.HostSearchQuery) bool {
            return q.Status == tt.status
        })).
        Return(results, nil)

        found, err :=
svc.SearchHosts(context.Background(),
host.SearchRequest{
    OwnerID: "usr_01J4KXYZ",
    Tags:    tt.tags,
    Status:  tt.status,
})

        require.NoError(t, err)
        assert.Len(t, found, tt.expectedCount)
    })
}

```

2.6 Keychain Service Unit Tests

```

// services/keychain/service_test.go
package keychain_test

import (
    "context"
    "crypto/ed25519"
    "crypto/rand"
    "testing"

    "github.com/HelixDevelopment/helixterminator/services/
    keychain"
    "github.com/HelixDevelopment/helixterminator/services/
    keychain/mocks"
    "github.com/HelixDevelopment/helixterminator/pkg/
    domain"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/mock"
    "github.com/stretchr/testify/require"
)

func TestKeychainService_StoreKey_Ed25519(t *testing.T) {
    keyRepo := mocks.NewMockKeyRepository(t)
    encryptor := mocks.NewMockKeyEncryptor(t)
    svc := keychain.NewService(keyRepo, encryptor)

    pubKey, privKey, err := ed25519.GenerateKey(rand.Reader)
    require.NoError(t, err)
}

```

```

    encryptedPrivKey := []byte("encrypted-private-key-bytes")
    encryptor.EXPECT().
        EncryptPrivateKey(mock.Anything, privKey,
            "usr_01J4KXYZ").
        Return(encryptedPrivKey, nil)

    keyRepo.EXPECT().
        Store(mock.Anything, mock.MatchedBy(func(k
            *domain.SSHKey) bool {
                return k.OwnerID == "usr_01J4KXYZ" &&
                    k.KeyType == "ed25519" &&
                    k.PublicKeyData != nil
            }))).
        Return("key_ed25519_001", nil)

    id, err := svc.StoreKey(context.Background(),
        keychain.StoreKeyRequest{
            OwnerID:    "usr_01J4KXYZ",
            PrivateKey: privKey,
            PublicKey:   pubKey,
            Name:        "Personal Ed25519 Key",
            Comment:    "alice@workstation",
        })

    require.NoError(t, err)
    assert.Equal(t, "key_ed25519_001", id)
}

func TestKeychainService_RetrieveKey_WrongOwner_Fails(t
    *testing.T) {
    keyRepo := mocks.NewMockKeyRepository(t)
    svc := keychain.NewService(keyRepo,
        mocks.NewMockKeyEncryptor(t))

    keyRepo.EXPECT().
        FindByID(mock.Anything, "key_001").
        Return(&domain.SSHKey{
            ID:        "key_001",
            OwnerID:   "usr_real_owner",
        }, nil)

    _, err := svc.RetrieveKey(context.Background(),
        keychain.RetrieveKeyRequest{
            ActorID: "usr_attacker",
            KeyID:   "key_001",
        })

    require.Error(t, err)
    assert.ErrorIs(t, err, keychain.ErrPermissionDenied)
}

```



```

func TestKeychainService_FIDO2Key_Registration(t *testing.T)
{
    keyRepo := mocks.NewMockKeyRepository(t)
    encryptor := mocks.NewMockKeyEncryptor(t)
    svc := keychain.NewService(keyRepo, encryptor)

    credential := &domain.FIDO2Credential{
        CredentialID: []byte("credential-id-bytes"),
        PublicKey:    []byte("cose-encoded-public-key"),
        AAGUID:       []byte("aaguid-bytes"),
        Counter:      0,
    }

    keyRepo.EXPECT().
        StoreFIDO2Credential(mock.Anything,
            mock.MatchedBy(func(c *domain.FIDO2Credential) bool {
                return c.OwnerID == "usr_01J4KXYZ"
            }))).
        Return("fido2_cred_001", nil)

    id, err :=
        svc.RegisterFIDO2Credential(context.Background(),
            keychain.RegisterFIDO2Request{
                OwnerID:    "usr_01J4KXYZ",
                Credential: credential,
                DeviceName: "YubiKey 5C NFC",
            })

    require.NoError(t, err)
    assert.Equal(t, "fido2_cred_001", id)
}

func TestKeychainService_PassphraseProtected_Key(t
    *testing.T) {
    keyRepo := mocks.NewMockKeyRepository(t)
    encryptor := mocks.NewMockKeyEncryptor(t)
    svc := keychain.NewService(keyRepo, encryptor)

    _, privKey, _ := ed25519.GenerateKey(rand.Reader)
    passphrase := "my-super-secret-passphrase-2026!"
    encryptedKey := []byte("passphrase-encrypted-key")

    encryptor.EXPECT().
        EncryptWithPassphrase(mock.Anything, privKey,
            passphrase).
        Return(encryptedKey, nil)

    keyRepo.EXPECT().
        Store(mock.Anything, mock.MatchedBy(func(k
            *domain.SSHKey) bool {
                return k.PassphraseProtected == true
            }))).

```

```

        Return("key_pp_001", nil)

    id, err :=
        svc.StoreKeyWithPassphrase(context.Background(),
            keychain.StoreKeyWithPassphraseRequest{
                OwnerID:      "usr_01J4KXYZ",
                PrivateKey: privKey,
                Passphrase: passphrase,
                Name:          "Passphrase Protected Key",
            })

    require.NoError(t, err)
    assert.Equal(t, "key_pp_001", id)
}

```

2.7 Go Benchmark Tests

```

// services/vault/bench_test.go
package vault_test

import (
    "crypto/rand"
    "testing"

    "github.com/HelixDevelopment/helixterminator/services/
    vault"
)

func BenchmarkVault_Encrypt_AES256GCM_1KB(b *testing.B) {
    svc := vault.NewBenchmarkService()
    key := make([]byte, 32)
    _, _ = rand.Read(key)
    plaintext := make([]byte, 1024) // 1KB
    _, _ = rand.Read(plaintext)

    b.ResetTimer()
    b.SetBytes(int64(len(plaintext)))
    for i := 0; i < b.N; i++ {
        _, _ = svc.Encrypt(plaintext, key)
    }
}

func BenchmarkVault_Encrypt_AES256GCM_1MB(b *testing.B) {
    svc := vault.NewBenchmarkService()
    key := make([]byte, 32)
    _, _ = rand.Read(key)
    plaintext := make([]byte, 1024*1024) // 1MB
    _, _ = rand.Read(plaintext)
}

```

```

        b.ResetTimer()
        b.SetBytes(int64(len(plaintext)))
        for i := 0; i < b.N; i++ {
            _, _ = svc.Encrypt(plaintext, key)
        }
    }

func BenchmarkVault_Decrypt_AES256GCM_1KB(b *testing.B) {
    svc := vault.NewBenchmarkService()
    key := make([]byte, 32)
    _, _ = rand.Read(key)
    plaintext := make([]byte, 1024)
    _, _ = rand.Read(plaintext)
    ciphertext, _ := svc.Encrypt(plaintext, key)

    b.ResetTimer()
    b.SetBytes(int64(len(plaintext)))
    for i := 0; i < b.N; i++ {
        _, _ = svc.Decrypt(ciphertext, key)
    }
}

// services/auth/bench_test.go
package auth_test

import (
    "context"
    "testing"

    "github.com/HelixDevelopment/helixterminator/services/auth"
)

func BenchmarkAuth_JWT_Issue(b *testing.B) {
    svc := auth.NewBenchmarkService()
    ctx := context.Background()

    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _, _ = svc.IssueAccessToken(ctx, "usr_bench_001",
            []string{"user", "vault:read", "ssh:connect"})
    }
}

func BenchmarkAuth_JWT_Parse(b *testing.B) {
    svc := auth.NewBenchmarkService()
    token, _ := svc.IssueAccessToken(context.Background(),
        "usr_bench_001", []string{"user"})

    b.ResetTimer()
    for i := 0; i < b.N; i++ {

```

```

        _, _ = svc.ParseAccessToken(token)
    }
}

func BenchmarkAuth_BcryptVerify(b *testing.B) {
    svc := auth.NewBenchmarkService()
    hash := svc.HashPassword("test-password-benchmark-123!")

    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _ = svc.VerifyPassword("test-password-benchmark-123!", hash)
    }
}

```

2.8 Property-Based Tests (Fuzzing)

```

// services/vault/fuzz_test.go
package vault_test

import (
    "testing"

    "github.com/HelixDevelopment/helixterminator/services/vault"
)

// FuzzVaultEncryptDecrypt verifies that any plaintext
// encrypted then decrypted
// returns the original plaintext – no matter the content.
func FuzzVaultEncryptDecrypt(f *testing.F) {
    svc := vault.NewBenchmarkService()

    // Seed corpus
    f.Add([]byte("hello world"))
    f.Add([]byte(""))
    f.Add([]byte("\x00\x01\x02\x03"))
    f.Add([]byte("特殊文字テスト"))
    f.Add(make([]byte, 65536)) // 64KB

    f.Fuzz(func(t *testing.T, plaintext []byte) {
        key := make([]byte, 32)
        // Use deterministic key for reproducibility in
        // corpus minimization
        for i := range key {
            key[i] = byte(i)
        }

        ciphertext, err := svc.Encrypt(plaintext, key)
    })
}

```

```

        if err != nil {
            t.Skip() // Some inputs may be legitimately
            rejected
        }

        decrypted, err := svc.Decrypt(ciphertext, key)
        if err != nil {
            t.Fatalf("Decrypt failed on ciphertext produced
            by Encrypt: %v", err)
        }

        if len(plaintext) != len(decrypted) {
            t.Fatalf("Length mismatch: got %d, want %d",
            len(decrypted), len(plaintext))
        }

        for i := range plaintext {
            if plaintext[i] != decrypted[i] {
                t.Fatalf("Byte mismatch at position %d", i)
            }
        }
    })
}

// FuzzJWTRoundtrip verifies JWT issue/parse round-trip for
// any user ID
func FuzzJWTRoundtrip(f *testing.F) {
    svc := auth.NewBenchmarkService()

    f.Add("usr_normal")
    f.Add("")
    f.Add("usr_with_special_chars_!@#$")
    f.Add("very-long-user-id-" + strings.Repeat("x", 1000))

    f.Fuzz(func(t *testing.T, userID string) {
        token, err :=
        svc.IssueAccessToken(context.Background(), userID,
        []string{"user"})
        if err != nil {
            t.Skip()
        }
        claims, err := svc.ParseAccessToken(token)
        if err != nil {
            t.Fatalf("Parse failed on token issued by
            IssueAccessToken: %v", err)
        }
        if claims.Subject != userID {
            t.Fatalf("Subject mismatch: got %q, want %q",
            claims.Subject, userID)
        }
    })
}

```

```
}  
})  
}
```

3. Backend Integration Tests

3.1 Integration Test Infrastructure

Integration tests use `testcontainers-go` to spin up real dependency containers. This eliminates test doubles at the infrastructure boundary and catches real serialization, schema, and protocol issues.

3.1.1 Container Configuration

```
// testinfra/containers.go  
package testinfra  
  
import (  
    "context"  
    "fmt"  
    "testing"  
    "time"  
  
    "github.com/testcontainers/testcontainers-go"  
    "github.com/testcontainers/testcontainers-go/modules/  
        kafka"  
    "github.com/testcontainers/testcontainers-go/modules/  
        postgres"  
    "github.com/testcontainers/testcontainers-go/modules/  
        rabbitmq"  
    "github.com/testcontainers/testcontainers-go/modules/  
        redis"  
    "github.com/testcontainers/testcontainers-go/wait"  
)  
  
// Pinned image digests – must match submodules-catalogue.md  
const (  
    PostgresImage = "postgres:16.3-  
        alpine3.20@sha256:a2282ad0db623c27f03bab803975c9e2f7eb50f33eb0db9db2"  
    RedisImage    = "redis:7.2.5-  
        alpine3.20@sha256:3134997edb04277814aa51a4175a588d45eb4299272f8eff23"  
    KafkaImage     = "confluentinc/cp-  
        kafka:7.6.1@sha256:abcdef1234567890abcdef1234567890abcdef1234567890a"  
    RabbitMQImage  = "rabbitmq:3.13.3-management-  
        alpine@sha256:fedcba0987654321fedcba0987654321fedcba0987654321fedcba"  
    OpenSSHImage   = "linuxserver/openssh-  
        server:latest@sha256:1234abcd5678efgh1234abcd5678efgh1234abcd5678efg"  
)
```

```

// TestPostgres starts a PostgreSQL container and returns the
// DSN.
// The container is automatically stopped when the test ends.
func TestPostgres(ctx context.Context, t *testing.T) string {
    t.Helper()
    container, err := postgres.RunContainer(ctx,
        testcontainers.WithImage(PostgresImage),
        postgres.WithDatabase("helixterm_test"),
        postgres.WithUsername("helixterm"),
        postgres.WithPassword("helixterm_test_pw"),
        testcontainers.WithWaitStrategy(
            wait.ForLog("database system is ready to accept
connections").
                WithOccurrence(2).
                WithStartupTimeout(30*time.Second),
        ),
    )
    if err != nil {
        t.Fatalf("failed to start postgres: %v", err)
    }
    t.Cleanup(func() {
        if err := container.Terminate(ctx); err != nil {
            t.Logf("warning: failed to terminate postgres
container: %v", err)
        }
    })
    dsn, err := container.ConnectionString(ctx,
        "sslmode=disable")
    if err != nil {
        t.Fatalf("failed to get postgres DSN: %v", err)
    }
    return dsn
}

// TestRedis starts a Redis container and returns the
// address.
func TestRedis(ctx context.Context, t *testing.T) string {
    t.Helper()
    container, err := redis.RunContainer(ctx,
        testcontainers.WithImage(RedisImage),
        testcontainers.WithWaitStrategy(
            wait.ForLog("Ready to accept connections tcp").
                WithStartupTimeout(20*time.Second),
        ),
    )
    if err != nil {
        t.Fatalf("failed to start redis: %v", err)
    }
    t.Cleanup(func() { _ = container.Terminate(ctx) })
    addr, err := container.ConnectionString(ctx)
    if err != nil {

```

```

        t.Fatalf("failed to get redis address: %v", err)
    }
    return addr
}

// TestKafka starts a Kafka container and returns the broker
// list.
func TestKafka(ctx context.Context, t *testing.T) []string {
    t.Helper()
    container, err := kafka.RunContainer(ctx,
        testcontainers.WithImage(KafkaImage),
        kafka.WithClusterID("test-cluster"),
        testcontainers.WithWaitStrategy(
            wait.ForLog("Kafka Server started").
                WithStartupTimeout(60*time.Second),
        ),
    )
    if err != nil {
        t.Fatalf("failed to start kafka: %v", err)
    }
    t.Cleanup(func() { _ = container.Terminate(ctx) })
    brokers, err := container.Brokers(ctx)
    if err != nil {
        t.Fatalf("failed to get kafka brokers: %v", err)
    }
    return brokers
}

// TestRabbitMQ starts a RabbitMQ container and returns the
// AMQP URL.
func TestRabbitMQ(ctx context.Context, t *testing.T) string {
    t.Helper()
    container, err := rabbitmq.RunContainer(ctx,
        testcontainers.WithImage(RabbitMQImage),
        rabbitmq.WithAdminUsername("guest"),
        rabbitmq.WithAdminPassword("guest"),
        testcontainers.WithWaitStrategy(
            wait.ForLog("Server startup complete").
                WithStartupTimeout(30*time.Second),
        ),
    )
    if err != nil {
        t.Fatalf("failed to start rabbitmq: %v", err)
    }
    t.Cleanup(func() { _ = container.Terminate(ctx) })
    url, err := container.AmqpURL(ctx)
    if err != nil {
        t.Fatalf("failed to get rabbitmq url: %v", err)
    }
}

```



```
    return url
}
```

3.2 Database Integration Tests

```
// services/auth/repository_integration_test.go
//go:build integration

package auth_integration_test

import (
    "context"
    "database/sql"
    "testing"
    "time"

    _ "github.com/lib/pq"
    "github.com/HelixDevelopment/helixterminator/services/auth/repository"
    "github.com/HelixDevelopment/helixterminator/testinfra"
    "github.com/HelixDevelopment/helixterminator/pkg/domain"
    "github.com/HelixDevelopment/helixterminator/db/migrations"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

func setupTestDB(t *testing.T) *sql.DB {
    t.Helper()
    ctx := context.Background()
    dsn := testinfra.TestPostgres(ctx, t)
    db, err := sql.Open("postgres", dsn)
    require.NoError(t, err)
    // Run all migrations against the fresh test database
    err = migrations.RunAll(db)
    require.NoError(t, err, "DB migration must succeed on clean database")
    t.Cleanup(func() { _ = db.Close() })
    return db
}

func TestUserRepository_CreateAndFind_Integration(t *testing.T) {
    db := setupTestDB(t)
    repo := repository.NewUserRepository(db)
    ctx := context.Background()

    user := &domain.User{
```

```

        Email:      "integration-test@example.com",
        PasswordHash:
            "$2a$10$abcdefghijklmnopqrstuvwxyzabcdefghijklmnopqrstuvwxyz",
        DisplayName: "Integration Test User",
        CreatedAt:
            time.Now().UTC().Truncate(time.Microsecond),
    }

    id, err := repo.Create(ctx, user)
    require.NoError(t, err)
    assert.NotEmpty(t, id)

    found, err := repo.FindByEmail(ctx, "integration-
        test@example.com")
    require.NoError(t, err)
    require.NotNil(t, found)
    assert.Equal(t, id, found.ID)
    assert.Equal(t, user.Email, found.Email)
    assert.Equal(t, user.DisplayName, found.DisplayName)
}

func TestUserRepository_LoginAttempts_Integration(t
    *testing.T) {
    db := setupTestDB(t)
    repo := repository.NewUserRepository(db)
    ctx := context.Background()

    // Create user
    user := &domain.User{Email: "lockout-test@example.com",
        PasswordHash: "hash"}
    id, err := repo.Create(ctx, user)
    require.NoError(t, err)

    // Increment attempts multiple times
    for i := 1; i <= 5; i++ {
        count, err := repo.IncrementLoginAttempts(ctx, id)
        require.NoError(t, err)
        assert.Equal(t, i, count)
    }

    // Lock account
    lockExpiry := time.Now().Add(15 * time.Minute)
    err = repo.LockAccount(ctx, id, lockExpiry)
    require.NoError(t, err)

    // Verify lock is persisted
    locked, err := repo.FindByID(ctx, id)
    require.NoError(t, err)
    assert.True(t, locked.AccountLocked)
    assert.True(t, locked.LockExpiry.After(time.Now()))
}

```

```

func TestUserRepository_UniqueEmail_Constraint(t *testing.T)
{
    db := setupTestDB(t)
    repo := repository.NewUserRepository(db)
    ctx := context.Background()

    user1 := &domain.User{Email: "unique@example.com",
        PasswordHash: "hash"}
    _, err := repo.Create(ctx, user1)
    require.NoError(t, err)

    user2 := &domain.User{Email: "unique@example.com",
        PasswordHash: "hash2"}
    _, err = repo.Create(ctx, user2)
    require.Error(t, err)
    assert.ErrorIs(t, err, domain.ErrDuplicate)
}

func TestDBMigration_IdempotentRerun(t *testing.T) {
    db := setupTestDB(t) // already runs migrations once
    // Running migrations again must be a no-op
    err := migrations.RunAll(db)
    require.NoError(t, err, "migrations must be idempotent")
}

func TestDBMigration_RollbackAndReapply(t *testing.T) {
    db := setupTestDB(t)

    // Roll back the last 3 migrations
    err := migrations.RollbackN(db, 3)
    require.NoError(t, err)

    // Re-apply them
    err = migrations.RunAll(db)
    require.NoError(t, err, "re-applying rolled-back
        migrations must succeed")
}

func TestTransaction_Rollback_OnError(t *testing.T) {
    db := setupTestDB(t)
    ctx := context.Background()

    tx, err := db.BeginTx(ctx, nil)
    require.NoError(t, err)

    // Insert a user
    _, err = tx.ExecContext(ctx,
        `INSERT INTO users (id, email, password_hash) VALUES
        ($1, $2, $3)`,
        "tx_test_user", "tx-test@example.com", "hash")
    require.NoError(t, err)
}

```

```

    // Roll back
    err = tx.Rollback()
    require.NoError(t, err)

    // Verify the user was NOT persisted
    var count int
    err = db.QueryRowContext(ctx,
        `SELECT COUNT(*) FROM users WHERE email = $1`, "tx-
        test@example.com").Scan(&count)
    require.NoError(t, err)
    assert.Equal(t, 0, count, "rolled-back transaction must
        not persist data")
}

```

3.3 Kafka Integration Tests

```

// services/audit/kafka_integration_test.go
//go:build integration

package audit_integration_test

import (
    "context"
    "encoding/json"
    "testing"
    "time"

    "github.com/IBM/sarama"
    "github.com/HelixDevelopment/helixterminator/services/
        audit"
    "github.com/HelixDevelopment/helixterminator/testinfra"
    "github.com/HelixDevelopment/helixterminator/pkg/
        domain"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

func TestAuditService_KafkaProducer_Integration(t
    *testing.T) {
    ctx := context.Background()
    brokers := testinfra.TestKafka(ctx, t)

    // Create topic for test
    topicName := "audit-events-test-" + t.Name()
    admin, err := sarama.NewClusterAdmin(brokers,
        sarama.NewConfig())
    require.NoError(t, err)
    defer admin.Close()
}

```

```

err = admin.CreateTopic(topicName, &sarama.TopicDetail{
    NumPartitions:    3,
    ReplicationFactor: 1,
}, false)
require.NoError(t, err)

svc := audit.NewService(audit.Config{
    KafkaBrokers: brokers,
    Topic:        topicName,
})

// Emit an audit event
event := &domain.AuditEvent{
    EventType: "session.start",
    ActorID:   "usr_01J4KXYZ",
    TargetID:  "host_001",
    Timestamp: time.Now().UTC(),
    IPAddress: "192.168.1.50",
    SessionID: "sess_xyz789",
}

err = svc.Emit(ctx, event)
require.NoError(t, err)

// Consume the event from Kafka and verify
config := sarama.NewConfig()
config.Consumer.Offsets.Initial = sarama.OffsetOldest
consumer, err := sarama.NewConsumer(brokers, config)
require.NoError(t, err)
defer consumer.Close()

partConsumer, err :=
    consumer.ConsumePartition(topicName, 0,
        sarama.OffsetOldest)
require.NoError(t, err)
defer partConsumer.Close()

select {
case msg := <-partConsumer.Messages():
    var received domain.AuditEvent
    err = json.Unmarshal(msg.Value, &received)
    require.NoError(t, err)
    assert.Equal(t, event.EventType, received.EventType)
    assert.Equal(t, event.ActorID, received.ActorID)
    assert.Equal(t, event.SessionID, received.SessionID)
case <-time.After(10 * time.Second):
    t.Fatal("timed out waiting for Kafka message")
}
}

```

```

func TestAuditService_KafkaConsumer_EventOrdering(t
    *testing.T) {
    ctx := context.Background()
    brokers := testinfra.TestKafka(ctx, t)
    topicName := "audit-ordering-" + t.Name()

    // Produce 100 events in sequence
    svc := audit.NewService(audit.Config{
        KafkaBrokers: brokers,
        Topic:        topicName,
    })

    for i := 0; i < 100; i++ {
        err := svc.Emit(ctx, &domain.AuditEvent{
            EventType: "test.event",
            Sequence:  i,
            SessionID: "sess_ordering_test",
        })
        require.NoError(t, err)
    }

    // Consume all events and verify they arrive in order per
    // partition key
    received := audit.ConsumeAll(ctx, t, brokers, topicName,
        100, 15*time.Second)
    assert.Len(t, received, 100)
    for i, event := range received {
        assert.Equal(t, i, event.Sequence,
            "events with same partition key must arrive in
            order")
    }
}

```

3.4 Redis Integration Tests

```

// services/auth/token_store_integration_test.go
//go:build integration

package auth_integration_test

import (
    "context"
    "testing"
    "time"

    "github.com/HelixDevelopment/helixterminator/services/
        auth/tokenstore"
    "github.com/HelixDevelopment/helixterminator/testinfra"

```

```

    "github.com/HelixDevelopment/helixterminator/pkg/
        domain"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

func TestRedisTokenStore_StoreAndGet_Integration(t
    *testing.T) {
    ctx := context.Background()
    redisAddr := testinfra.TestRedis(ctx, t)
    store := tokenstore.NewRedisTokenStore(redisAddr, "")

    token := &domain.RefreshToken{
        ID:        "rt_integration_001",
        UserID:    "usr_01J4KXYZ",
        ExpiresAt: time.Now().Add(7 * 24 * time.Hour),
        Revoked:   false,
    }

    err := store.StoreRefreshToken(ctx, token)
    require.NoError(t, err)

    retrieved, err := store.GetRefreshToken(ctx,
        "rt_integration_001")
    require.NoError(t, err)
    require.NotNil(t, retrieved)
    assert.Equal(t, token.UserID, retrieved.UserID)
    assert.False(t, retrieved.Revoked)
}

func TestRedisTokenStore_TTLExpiry_Integration(t *testing.T)
{
    ctx := context.Background()
    redisAddr := testinfra.TestRedis(ctx, t)
    store := tokenstore.NewRedisTokenStore(redisAddr, "")

    token := &domain.RefreshToken{
        ID:        "rt_short_ttl",
        UserID:    "usr_01J4KXYZ",
        ExpiresAt: time.Now().Add(2 * time.Second), //
        expires very soon
    }

    err := store.StoreRefreshToken(ctx, token)
    require.NoError(t, err)

    // Verify it exists
    retrieved, err := store.GetRefreshToken(ctx,
        "rt_short_ttl")
    require.NoError(t, err)
    assert.NotNil(t, retrieved)
}

```

```

// Wait for expiry
time.Sleep(3 * time.Second)

// Verify it's gone
expired, err := store.GetRefreshToken(ctx,
    "rt_short_ttl")
require.Error(t, err)
assert.Nil(t, expired)
assert.ErrorIs(t, err, tokenstore.ErrTokenNotFound)
}

func TestRedisTokenStore_Revoke_Integration(t *testing.T) {
    ctx := context.Background()
    redisAddr := testinfra.TestRedis(ctx, t)
    store := tokenstore.NewRedisTokenStore(redisAddr, "")

    token := &domain.RefreshToken{
        ID:      "rt_to_revoke",
        UserID:   "usr_01J4KXYZ",
        ExpiresAt: time.Now().Add(1 * time.Hour),
    }

    err := store.StoreRefreshToken(ctx, token)
    require.NoError(t, err)

    err = store.RevokeRefreshToken(ctx, "rt_to_revoke")
    require.NoError(t, err)

    revoked, err := store.GetRefreshToken(ctx,
        "rt_to_revoke")
    require.NoError(t, err)
    assert.True(t, revoked.Revoked, "revoked token must have
        Revoked=true flag in Redis")
}

func TestRedisTokenStore_CacheMiss_Integration(t *testing.T) {
    ctx := context.Background()
    redisAddr := testinfra.TestRedis(ctx, t)
    store := tokenstore.NewRedisTokenStore(redisAddr, "")

    _, err := store.GetRefreshToken(ctx,
        "rt_nonexistent_key")
    require.Error(t, err)
    assert.ErrorIs(t, err, tokenstore.ErrTokenNotFound)
}

```


3.5 RabbitMQ Integration Tests

```
// services/sshproxy/command_routing_integration_test.go
//go:build integration

package sshproxy_integration_test

import (
    "context"
    "testing"
    "time"

    amqp "github.com/rabbitmq/amqp091-go"
    "github.com/HelixDevelopment/helixterminator/services/sshproxy/commands"
    "github.com/HelixDevelopment/helixterminator/testinfra"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

func TestRabbitMQ_SSHCommand_Routing_Integration(t
    *testing.T) {
    ctx := context.Background()
    amqpURL := testinfra.TestRabbitMQ(ctx, t)

    router := commands.NewCommandRouter(commands.Config{
        AMQPURL:      amqpURL,
        Exchange:     "helix.ssh.commands",
        ConnectQueue: "ssh.connect",
        DisconnectQueue: "ssh.disconnect",
    })

    err := router.Setup(ctx)
    require.NoError(t, err)

    // Publish a connect command
    cmd := &commands.SSHConnectCommand{
        SessionID: "sess_amqp_test",
        UserID:    "usr_01J4KXYZ",
        HostID:    "host_001",
        RequestedAt: time.Now().UTC(),
    }

    err = router.PublishConnect(ctx, cmd)
    require.NoError(t, err)

    // Consume and verify
    received := make(chan *commands.SSHConnectCommand, 1)
    err = router.ConsumeConnect(ctx, func(c
        *commands.SSHConnectCommand) error {
```

```

        received <- c
        return nil
    })
    require.NoError(t, err)

    select {
    case msg := <-received:
        assert.Equal(t, "sess_amqp_test", msg.SessionID)
        assert.Equal(t, "usr_01J4KXYZ", msg.UserID)
    case <-time.After(10 * time.Second):
        t.Fatal("timed out waiting for RabbitMQ message")
    }
}

func TestRabbitMQ_DeadLetterQueue_OnProcessingError(t
    *testing.T) {
    ctx := context.Background()
    amqpURL := testinfra.TestRabbitMQ(ctx, t)

    router := commands.NewCommandRouter(commands.Config{
        AMQPURL:      amqpURL,
        Exchange:      "helix.ssh.commands",
        ConnectQueue: "ssh.connect.dlq-test",
        DLQEnabled:    true,
        DLQName:       "ssh.connect.dlq",
        MaxRetries:    3,
    })

    err := router.Setup(ctx)
    require.NoError(t, err)

    cmd := &commands.SSHConnectCommand{SessionID:
        "sess_dlq_test", HostID: "host_bad"}

    err = router.PublishConnect(ctx, cmd)
    require.NoError(t, err)

    // Consumer that always fails – should trigger DLQ after
    // MaxRetries
    err = router.ConsumeConnect(ctx, func(c
        *commands.SSHConnectCommand) error {
        return assert.AnError // always fail
    })
    require.NoError(t, err)

    // Give retry loop time to exhaust attempts
    time.Sleep(5 * time.Second)

    // Verify message landed in DLQ
    dlqCount := router.GetDLQMessageCount(ctx,
        "ssh.connect.dlq")

```

```
    assert.Equal(t, 1, dlqCount, "message must be in DLQ
        after MaxRetries exhausted")
}
```

3.6 Service-to-Service Integration Tests

```
// integration/auth_vault_chain_test.go
//go:build integration

package integration_test

import (
    "context"
    "net/http"
    "net/http/httptest"
    "testing"
    "time"

    "github.com/HelixDevelopment/helixterminator/services/auth"
    "github.com/HelixDevelopment/helixterminator/services/vault"
    "github.com/HelixDevelopment/helixterminator/testinfra"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

// TestAuthVaultChain_Integration tests the full
// authentication → vault access chain
// using real database and Redis containers.
func TestAuthVaultChain_Integration(t *testing.T) {
    ctx := context.Background()

    // Start real containers
    pgDSN := testinfra.TestPostgres(ctx, t)
    redisAddr := testinfra.TestRedis(ctx, t)

    // Initialize real services with real dependencies
    authSvc := auth.NewServiceFromDSN(pgDSN, redisAddr)
    vaultSvc := vault.NewServiceFromDSN(pgDSN)

    // Register a user
    userID, err := authSvc.RegisterUser(ctx,
        auth.RegisterRequest{
            Email:      "chain-test@example.com",
            Password: "ValidPassword123!@#",
        })
    require.NoError(t, err)
```

```
// Verify email (skip in integration test via test
    helper)
err = authSvc.ForceVerifyEmail(ctx, userID)
require.NoError(t, err)

// Login
loginResult, err := authSvc.Login(ctx, auth.LoginRequest{
    Email:    "chain-test@example.com",
    Password: "ValidPassword123!@#",
    DeviceID: "dev_integration_001",
})
require.NoError(t, err)
assert.NotEmpty(t, loginResult.AccessToken)

// Use access token to create a vault
vaultID, err := vaultSvc.CreateVaultWithToken(ctx,
    loginResult.AccessToken, vault.CreateVaultRequest{
    Name: "Integration Test Vault",
})
require.NoError(t, err)
assert.NotEmpty(t, vaultID)

// Add an entry to the vault
entryID, err := vaultSvc.AddEntryWithToken(ctx,
    loginResult.AccessToken, vault.AddEntryRequest{
    VaultID: vaultID,
    Entry: &domain.VaultEntry{
        Name:    "Test Server",
        Hostname: "10.0.0.1",
        Username: "admin",
        Password: "server-password-encrypted",
    },
})
require.NoError(t, err)
assert.NotEmpty(t, entryID)

// Retrieve the entry and verify
retrieved, err := vaultSvc.GetEntryWithToken(ctx,
    loginResult.AccessToken, vaultID, entryID)
require.NoError(t, err)
assert.Equal(t, "Test Server", retrieved.Name)
assert.Equal(t, "10.0.0.1", retrieved.Hostname)
}
```

4. End-to-End Tests

4.1 Backend E2E Test: Complete User Journey

The backend E2E tests run against a full staging deployment and exercise the complete user-visible flows via the API Gateway.

```
// e2e/user_journey_test.go
//go:build e2e

package e2e_test

import (
    "bytes"
    "context"
    "encoding/json"
    "fmt"
    "io"
    "net/http"
    "testing"
    "time"

    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

const (
    E2EBaseURL    = "https://staging-
        api.helixterminator.app"
    E2EWSBaseURL = "wss://staging-ws.helixterminator.app"
)

type E2EClient struct {
    http      *http.Client
    baseURL   string
    accessToken string
}

func newE2EClient() *E2EClient {
    return &E2EClient{
        http:      &http.Client{Timeout: 30 * time.Second},
        baseURL:   E2EBaseURL,
    }
}

func (c *E2EClient) POST(t *testing.T, path string, body
    interface{}) *http.Response {
    t.Helper()
    data, err := json.Marshal(body)
    require.NoError(t, err)
```

```

    req, err := http.NewRequest("POST", c.baseURL+path,
        bytes.NewBuffer(data))
    require.NoError(t, err)
    req.Header.Set("Content-Type", "application/json")
    if c.accessToken != "" {
        req.Header.Set("Authorization", "Bearer "+c.accessToken)
    }
    resp, err := c.http.Do(req)
    require.NoError(t, err)
    return resp
}

// TestE2E_CompleteUserJourney exercises the full flow:
// registration → email verify → login → vault create → host
// add → SSH connect →
// session → disconnect
func TestE2E_CompleteUserJourney(t *testing.T) {
    client := newE2EClient()
    ctx := context.Background()
    _ = ctx

    // Unique test email to avoid conflicts
    email := fmt.Sprintf("e2e-test-%d@helixterminator-
        test.app", time.Now().UnixNano())
    password := "E2ETestPassword!2026"

    // — Step 1: Register
    t.Run("Register", func(t *testing.T) {
        resp := client.POST(t, "/v1/auth/register",
            map[string]string{
                "email": email,
                "password": password,
            })
        defer resp.Body.Close()
        require.Equal(t, http.StatusCreated, resp.StatusCode)

        var body map[string]interface{}
        require.NoError(t,
            json.NewDecoder(resp.Body).Decode(&body))
        assert.NotEmpty(t, body["user_id"])
    })

    // — Step 2: Email verification (staging uses magic
    // token) —
    t.Run("VerifyEmail", func(t *testing.T) {
        // In E2E tests, use the staging test API to get the
        // verification token
        token := getTestVerificationToken(t, email)
        resp := client.POST(t, "/v1/auth/verify-email",
            map[string]string{

```

```

        "token": token,
    })
    defer resp.Body.Close()
    require.Equal(t, http.StatusOK, resp.StatusCode)
})

// — Step 3: Login


---


t.Run("Login", func(t *testing.T) {
    resp := client.POST(t, "/v1/auth/login",
        map[string]string{
            "email": email,
            "password": password,
            "device_id": "e2e-test-device",
        })
    defer resp.Body.Close()
    require.Equal(t, http.StatusOK, resp.StatusCode)

    var body map[string]interface{}
    require.NoError(t,
        json.NewDecoder(resp.Body).Decode(&body))
    require.NotEmpty(t, body["access_token"])
    client.accessToken = body["access_token"].(string)
})

// — Step 4: Create Vault


---


var vaultID string
t.Run("CreateVault", func(t *testing.T) {
    resp := client.POST(t, "/v1/vaults",
        map[string]string{
            "name": "E2E Test Vault",
            "type": "personal",
        })
    defer resp.Body.Close()
    require.Equal(t, http.StatusCreated, resp.StatusCode)

    var body map[string]interface{}
    require.NoError(t,
        json.NewDecoder(resp.Body).Decode(&body))
    require.NotEmpty(t, body["vault_id"])
    vaultID = body["vault_id"].(string)
})

// — Step 5: Add Host


---


var hostID string
t.Run("AddHost", func(t *testing.T) {
    resp := client.POST(t, "/v1/hosts",
        map[string]interface{}{
            "vault_id": vaultID,
            "hostname": "e2e-test-server.internal",
        })
})

```

```

        "port":      22,
        "username":  "test-user",
        "auth_type": "password",
        "display_name": "E2E Test Server",
    })
    defer resp.Body.Close()
    require.Equal(t, http.StatusCreated, resp.StatusCode)

    var body map[string]interface{}
    require.NoError(t,
        json.NewDecoder(resp.Body).Decode(&body))
    require.NotEmpty(t, body["host_id"])
    hostID = body["host_id"].(string)
})

// — Step 6: SSH Connect


---


var sessionID string
t.Run("SSHConnect", func(t *testing.T) {
    resp := client.POST(t, "/v1/sessions",
        map[string]interface{}{
            "host_id":  hostID,
            "auth_type": "password",
            "password": "test-server-password",
        })
    defer resp.Body.Close()
    require.Equal(t, http.StatusCreated, resp.StatusCode)

    var body map[string]interface{}
    require.NoError(t,
        json.NewDecoder(resp.Body).Decode(&body))
    require.NotEmpty(t, body["session_id"])
    require.NotEmpty(t, body["websocket_url"])
    sessionID = body["session_id"].(string)
})

// — Step 7: Interact with Terminal via WebSocket


---


t.Run("TerminalInteraction", func(t *testing.T) {
    ws := connectE2EWebSocket(t, sessionID,
        client.accessToken)
    defer ws.Close()

    // Send a command
    sendTerminalInput(t, ws, "echo 'helix-e2e-test'\n")

    // Verify output appears within 5 seconds
    output := readTerminalOutput(t, ws, "helix-e2e-
test", 5*time.Second)
    assert.Contains(t, output, "helix-e2e-test")
})

```



```
// — Step 8: Disconnect

t.Run("Disconnect", func(t *testing.T) {
    resp := client.POST(t, fmt.Sprintf("/v1/sessions/%s/disconnect", sessionID), nil)
    defer resp.Body.Close()
    require.Equal(t, http.StatusNoContent, resp.StatusCode)

    // Verify session is marked inactive
    getResp, err := http.NewRequest("GET", E2EBaseURL+fmt.Sprintf("/v1/sessions/%s", sessionID), nil)
    require.NoError(t, err)
    getResp.Header.Set("Authorization", "Bearer "+client.accessToken)
    statusResp, err := client.http.Do(getResp)
    require.NoError(t, err)
    defer statusResp.Body.Close()

    var sessionBody map[string]interface{}
    require.NoError(t, json.NewDecoder(statusResp.Body).Decode(&sessionBody))
    assert.Equal(t, "inactive", sessionBody["status"])
})
}
```

4.2 Flutter Integration Tests

Flutter integration tests use `flutter_test` and the `integration_test` package. Tests run on real devices or simulators via `flutter drive`.

```
// integration_test/app_launch_test.dart
import 'package:flutter_test/flutter_test.dart';
import 'package:integration_test/integration_test.dart';
import 'package:helixterminator/main.dart' as app;
import 'package:helixterminator/pages/host_list_page.dart';
import 'package:helixterminator/pages/terminal_page.dart';

void main() {
    IntegrationTestWidgetsFlutterBinding.ensureInitialized();

    group('App Launch and Authentication E2E', () {
        testWidgets('App launches, biometric login, host list visible', (tester) async {
            // Start the app
            app.main();
            await tester.pumpAndSettle(const Duration(seconds: 3));
        });
    });
}
```

```
// Verify splash screen appears
expect(find.byKey(const Key('splash_screen')),
  findsOneWidget);

// Simulate biometric authentication approval
await tester.tap(find.byKey(const
  Key('biometric_login_button')));
await tester.pumpAndSettle(const Duration(seconds: 2));

// After auth, host list should be visible
expect(find.byType(HostListPage), findsOneWidget);
expect(find.byKey(const Key('host_list_view')),
  findsOneWidget);
});

testWidgets('Connect to host, type command, verify
  output, disconnect', (tester) async {
  app.main();
  await tester.pumpAndSettle(const Duration(seconds: 3));

  // Authenticate
  await authenticateWithBiometrics(tester);
  await tester.pumpAndSettle();

  // Find and tap the first host
  await tester.tap(find.byKey(const
    Key('host_list_item_0')));
  await tester.pumpAndSettle(const Duration(seconds: 2));

  // Terminal page should be active
  expect(find.byType(TerminalPage), findsOneWidget);

  // Wait for SSH connection
  await tester.pumpAndSettle(const Duration(seconds: 5));
  expect(find.byKey(const
    Key('terminal_connected_indicator')),
    findsOneWidget);

  // Type a command
  final terminalInput = find.byKey(const
    Key('terminal_input_field'));
  await tester.enterText(terminalInput, 'echo "flutter-
    e2e-test"');
  await
    tester.testTextInput.receiveAction(TextInputAction.done);
  await tester.pumpAndSettle(const Duration(seconds: 3));

  // Verify output in terminal
  expect(find.textContaining('flutter-e2e-test'),
    findsAtLeastNWidgets(1));

  // Disconnect
```

```

        await tester.tap(find.byKey(const
            Key('disconnect_button')));
        await tester.pumpAndSettle(const Duration(seconds: 2));

        // Back to host list
        expect(find.byType(HostListPage), findsOneWidget);
    });
});

group('SFTP Transfer E2E', () {

    testWidgets('SFTP: connect → browse → upload →
        download → verify', (tester) async {
        app.main();
        await tester.pumpAndSettle(const Duration(seconds: 3));
        await authenticateWithBiometrics(tester);

        // Open SFTP browser for host
        await tester.tap(find.byKey(const
            Key('host_sftp_button_0')));
        await tester.pumpAndSettle(const Duration(seconds: 3));

        // Verify directory listing is shown
        expect(find.byKey(const Key('sftp_file_browser')),
            findsOneWidget);

        // Upload a test file
        await tester.tap(find.byKey(const
            Key('sftp_upload_button')));
        await tester.pumpAndSettle();

        // Select test file from mock picker
        await tester.tap(find.byKey(const
            Key('file_picker_test_file')));
        await tester.pumpAndSettle(const Duration(seconds: 5));

        // Verify upload success
        expect(find.byKey(const
            Key('sftp_upload_success_indicator')),
            findsOneWidget);

        // Download the uploaded file
        await tester.tap(find.textContaining('test_file.txt'));
        await tester.pumpAndSettle();
        await tester.tap(find.byKey(const
            Key('sftp_download_button')));
        await tester.pumpAndSettle(const Duration(seconds: 5));

        // Verify download
        expect(find.byKey(const
            Key('sftp_download_success_indicator')),
            findsOneWidget);
    });
});

```

```

    });
  });

group('Workspace Management E2E', () {
  testWidgets('Create workspace, add sessions, split view,
    save template, restore', (tester) async {
    app.main();
    await tester.pumpAndSettle(const Duration(seconds: 3));
    await authenticateWithBiometrics(tester);

    // Navigate to Workspaces
    await tester.tap(find.byKey(const
      Key('nav_workspaces')));
    await tester.pumpAndSettle();

    // Create a new workspace
    await tester.tap(find.byKey(const
      Key('create_workspace_button')));
    await tester.pumpAndSettle();

    final workspaceNameField = find.byKey(const
      Key('workspace_name_field'));
    await tester.enterText(workspaceNameField, 'E2E Test
      Workspace');
    await tester.tap(find.byKey(const
      Key('workspace_save_button')));
    await tester.pumpAndSettle();

    expect(find.textContaining('E2E Test Workspace'),
      findsOneWidget);

    // Add two sessions
    for (int i = 0; i < 2; i++) {
      await tester.tap(find.byKey(const
        Key('workspace_add_session_button')));
      await tester.pumpAndSettle();
      await
        tester.tap(find.byKey(Key('workspace_host_selector_$i')));
      await tester.pumpAndSettle(const Duration(seconds:
        3));
    }

    // Enable split view
    await tester.tap(find.byKey(const
      Key('workspace_split_view_toggle')));
    await tester.pumpAndSettle();

    // Verify both terminal panes are visible
    expect(find.byKey(const Key('terminal_pane_0')),
      findsOneWidget);
    expect(find.byKey(const Key('terminal_pane_1')),
      findsOneWidget);
  });
});

```

```

    // Save as template
    await tester.tap(find.byKey(const
      Key('workspace_save_template_button')));
    await tester.pumpAndSettle();
    await tester.enterText(
      find.byKey(const Key('template_name_field')), 'E2E
      Template');
    await tester.tap(find.byKey(const
      Key('template_save_confirm')));
    await tester.pumpAndSettle();

    // Close workspace and restore from template
    await tester.tap(find.byKey(const
      Key('close_workspace_button')));
    await tester.pumpAndSettle();

    await tester.tap(find.textContaining('E2E Template'));
    await tester.pumpAndSettle(const Duration(seconds: 5));

    // Verify workspace was restored with split view
    expect(find.byKey(const Key('terminal_pane_0')),
      findsOneWidget);
    expect(find.byKey(const Key('terminal_pane_1')),
      findsOneWidget);
  });
});
}

Future<void> authenticateWithBiometrics(WidgetTester tester)
  async {
    await tester.tap(find.byKey(const
      Key('biometric_login_button')));
    await tester.pumpAndSettle(const Duration(seconds: 2));
  }

```

4.3 MFA Setup and Use Flow (E2E)

```

// e2e/mfa_flow_test.go
//go:build e2e

package e2e_test

import (
    "encoding/base64"
    "testing"
    "time"

    "github.com/pquerna/otp/totp"

```

```

    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

func TestE2E_MFASetupAndUse(t *testing.T) {
    client := newE2EClient()

    // Create and login as test user (no MFA yet)
    email, password := createAndLoginTestUser(t, client)
    _ = email
    _ = password

    // — Setup TOTP MFA
    

---


    var totpSecret string
    t.Run("SetupTOTP", func(t *testing.T) {
        resp := client.POST(t, "/v1/auth/mfa/totp/setup",
            nil)
        defer resp.Body.Close()
        require.Equal(t, 200, resp.StatusCode)

        var body map[string]interface{}
        require.NoError(t, jsonDecode(resp.Body, &body))
        require.NotEmpty(t, body["secret"])
        require.NotEmpty(t, body["qr_url"])
        totpSecret = body["secret"].(string)
    })

    t.Run("VerifyTOTPSetup", func(t *testing.T) {
        code, err := totp.GenerateCode(totpSecret,
            time.Now())
        require.NoError(t, err)

        resp := client.POST(t, "/v1/auth/mfa/totp/verify",
            map[string]string{
                "code": code,
            })
        defer resp.Body.Close()
        require.Equal(t, 200, resp.StatusCode)

        var body map[string]interface{}
        require.NoError(t, jsonDecode(resp.Body, &body))
        assert.True(t, body["mfa_enabled"].(bool))
        // Backup codes must be provided
        assert.NotEmpty(t, body["backup_codes"])
    })

    t.Run("LoginWithMFA", func(t *testing.T) {
        // Logout first
        logoutTestUser(t, client)

        // Login – should get MFA challenge
    })
}

```

```

resp := client.POST(t, "/v1/auth/login",
map[string]string{
    "email":      email,
    "password":   password,
    "device_id":  "e2e-mfa-device",
})
defer resp.Body.Close()
require.Equal(t, 200, resp.StatusCode)

var loginBody map[string]interface{}
require.NoError(t, jsonDecode(resp.Body, &loginBody))
require.True(t, loginBody["mfa_required"].(bool))
require.NotEmpty(t, loginBody["mfa_session_token"])
mfaToken := loginBody["mfa_session_token"].(string)

// Complete MFA
code, err := totp.GenerateCode(totpSecret,
time.Now())
require.NoError(t, err)

mfaResp := client.POST(t, "/v1/auth/mfa/verify",
map[string]string{
    "mfa_session_token": mfaToken,
    "code":              code,
})
defer mfaResp.Body.Close()
require.Equal(t, 200, mfaResp.StatusCode)

var mfaBody map[string]interface{}
require.NoError(t, jsonDecode(mfaResp.Body,
&mfaBody))
assert.NotEmpty(t, mfaBody["access_token"])
client.accessToken = mfaBody["access_token"].(string)
})
}

```

5. Performance & Load Tests

5.1 k6 Test Scripts

5.1.1 SSH Connection Establishment — 10,000 Concurrent

```

// k6/ssh_connection_load.js
import http from 'k6/http';
import ws from 'k6/ws';
import { check, sleep } from 'k6';
import { Counter, Gauge, Rate, Trend } from 'k6/metrics';

```

```

// Custom metrics
const sshConnectionDuration = new
    Trend('ssh_connection_duration_ms', true);
const sshConnectionErrors = new
    Counter('ssh_connection_errors_total');
const activeSSHSessions = new Gauge('ssh_active_sessions');
const sshAuthSuccessRate = new Rate('ssh_auth_success_rate');

export const options = {
  stages: [
    { duration: '2m', target: 1000 }, // Ramp up to 1,000
    { duration: '5m', target: 5000 }, // Ramp up to 5,000
    { duration: '10m', target: 10000 }, // Ramp up to 10,000
    { duration: '15m', target: 10000 }, // Hold at 10,000
    { duration: '3m', target: 0 }, // Ramp down
  ],
  thresholds: {
    'ssh_connection_duration_ms': [
      'p(50)<500', // 50th percentile < 500ms
      'p(95)<2000', // 95th percentile < 2 seconds
      'p(99)<5000', // 99th percentile < 5 seconds
    ],
    'ssh_auth_success_rate': ['rate>0.99'], // 99%+
      success
    'ssh_connection_errors_total': ['count<100'], // < 100
      errors total
    'http_req_failed': ['rate<0.01'], // API
      error rate < 1%
  },
};

const BASE_URL = __ENV.API_BASE_URL || 'https://staging-
  api.helixterminator.app';
const WS_URL = __ENV.WS_BASE_URL || 'wss://staging-
  ws.helixterminator.app';

// Pre-seeded test users and hosts for load test
const TEST_USERS = JSON.parse(open('./fixtures/
  load_test_users.json'));
const TEST_HOSTS = JSON.parse(open('./fixtures/
  load_test_hosts.json'));

function getTestUser(vu) {
  return TEST_USERS[vu % TEST_USERS.length];
}

function getTestHost(vu) {
  return TEST_HOSTS[vu % TEST_HOSTS.length];
}

export function setup() {

```



```

    // Warm up the API and pre-authenticate test users
    console.log('Load test setup: pre-authenticating test
        users');
    return { startTime: Date.now() };
}

export default function () {
    const user = getTestUser(__VU);
    const host = getTestHost(__VU);

    // Step 1: Authenticate
    const loginStart = Date.now();
    const loginResp = http.post(
        `${BASE_URL}/v1/auth/login`,
        JSON.stringify({
            email: user.email,
            password: user.password,
            device_id: `k6-vu-${__VU}-iter-${__ITER}`,
        }),
        { headers: { 'Content-Type': 'application/json' } }
    );

    const loginOK = check(loginResp, {
        'login status 200': (r) => r.status === 200,
        'access token present': (r) =>
            JSON.parse(r.body).access_token !== undefined,
    });

    if (!loginOK) {
        sshConnectionErrors.add(1);
        return;
    }

    const { access_token } = JSON.parse(loginResp.body);

    // Step 2: Create SSH session
    const sessionStart = Date.now();
    const sessionResp = http.post(
        `${BASE_URL}/v1/sessions`,
        JSON.stringify({
            host_id: host.id,
            auth_type: 'password',
            password: host.password,
        }),
        {
            headers: {
                'Content-Type': 'application/json',
                'Authorization': `Bearer ${access_token}`,
            },
        },
    );
};

```

```

const sessionOK = check(sessionResp, {
  'session created 201': (r) => r.status === 201,
  'session_id present': (r) =>
    JSON.parse(r.body).session_id !== undefined,
  'websocket_url present': (r) =>
    JSON.parse(r.body).websocket_url !== undefined,
});

if (!sessionOK) {
  sshConnectionErrors.add(1);
  sshAuthSuccessRate.add(false);
  return;
}

const { session_id, websocket_url } =
  JSON.parse(sessionResp.body);
const connectionTime = Date.now() - sessionStart;
sshConnectionDuration.add(connectionTime);
sshAuthSuccessRate.add(true);
activeSSHSessions.add(1);

// Step 3: Open WebSocket and interact
const wsResp = ws.connect(
  `${WS_URL}/v1/sessions/${session_id}/terminal`,
  { headers: { 'Authorization': `Bearer ${access_token}` } },
  function (socket) {
    socket.on('open', () => {
      // Send a simple command
      socket.send(JSON.stringify({ type: 'input', data:
        'echo "k6-load-test"\n' }));
    });

    socket.on('message', (data) => {
      const msg = JSON.parse(data);
      if (msg.type === 'output' && msg.data.includes('k6-
        load-test')) {
        socket.close();
      }
    });

    socket.on('error', (e) => {
      sshConnectionErrors.add(1);
    });

    socket.setTimeout(() => { socket.close(); }, 10000);
  }
);

check(wsResp, {
  'websocket connected': (r) => r && r.status === 101,

```

```

});

// Disconnect session
http.post(
  `${BASE_URL}/v1/sessions/${session_id}/disconnect`,
  null,
  { headers: { 'Authorization': `Bearer ${access_token}` } }
);

activeSSHSessions.add(-1);
sleep(Math.random() * 2 + 1); // Random think time: 1-3
seconds
}

export function teardown(data) {
  console.log(`Load test completed. Duration: ${Date.now() -
    data.startTime}ms`);
}

```

5.1.2 Vault Sync — 100,000 Items Across 1,000 Users

```

// k6/vault_sync_load.js
import http from 'k6/http';
import { check, sleep } from 'k6';
import { Trend, Counter, Rate } from 'k6/metrics';

const vaultSyncDuration = new
  Trend('vault_sync_duration_ms', true);
const vaultSyncErrors = new
  Counter('vault_sync_errors_total');
const vaultSyncItemsPerSec = new
  Counter('vault_sync_items_total');

export const options = {
  scenarios: {
    vault_sync_ramp: {
      executor: 'ramping-vus',
      stages: [
        { duration: '1m', target: 100 },
        { duration: '5m', target: 1000 },
        { duration: '10m', target: 1000 },
        { duration: '2m', target: 0 },
      ],
    },
  },
  thresholds: {
    'vault_sync_duration_ms': [

```

```

        'p(95)<3000', // 95% of syncs complete within 3
                      seconds
        'p(99)<8000', // 99% within 8 seconds
    ],
    'vault_sync_errors_total': ['count<50'],
    'http_req_failed': ['rate<0.005'],
  },
};

const BASE_URL = __ENV.API_BASE_URL || 'https://staging-
  api.helixterminator.app';
const TEST_USERS = JSON.parse(open('./fixtures/
  vault_load_test_users.json'));

export default function () {
  const user = TEST_USERS[__VU % TEST_USERS.length];

  // Authenticate
  const loginResp = http.post(
    `${BASE_URL}/v1/auth/login`,
    JSON.stringify({ email: user.email, password:
      user.password, device_id: `k6-${__VU}` }),
    { headers: { 'Content-Type': 'application/json' } }
  );
  if (!check(loginResp, { 'login ok': (r) => r.status ===
    200 })) {
    vaultSyncErrors.add(1);
    return;
  }
  const { access_token } = JSON.parse(loginResp.body);

  // Sync vault – simulate device requesting delta since last
  sync
  const syncStart = Date.now();
  const syncResp = http.get(
    `${BASE_URL}/v1/vaults/sync?
      last_synced_at=2026-01-01T00:00:00Z`,
    {
      headers: {
        'Authorization': `Bearer ${access_token}`,
        'Accept': 'application/json',
      },
    },
  );

  const syncDuration = Date.now() - syncStart;

  const syncOK = check(syncResp, {
    'sync status 200': (r) => r.status === 200,
    'entries array present': (r) =>
      Array.isArray(JSON.parse(r.body).entries),
  });
};

```

```

    if (!syncOK) {
        vaultSyncErrors.add(1);
        return;
    }

    const { entries } = JSON.parse(syncResp.body);
    vaultSyncDuration.add(syncDuration);
    vaultSyncItemsPerSec.add(entries.length);

    sleep(0.5);
}

```

5.1.3 API Gateway – High Throughput Test

```

// k6/api_gateway_throughput.js
import http from 'k6/http';
import { check } from 'k6';
import { Rate, Counter, Trend } from 'k6/metrics';

const requestRate = new Counter('total_requests');
const errorRate = new Rate('error_rate');
const apiLatency = new Trend('api_latency_ms', true);

export const options = {
  scenarios: {
    constant_arrival_rate: {
      executor: 'constant-arrival-rate',
      rate: 10000,           // 10,000 requests per second
      timeUnit: '1s',
      duration: '10m',
      preAllocatedVUs: 500,
      maxVUs: 2000,
    },
  },
  thresholds: {
    'api_latency_ms': [
      'p(50)<20',    // Median latency < 20ms
      'p(95)<100',   // 95th percentile < 100ms
      'p(99)<500',   // 99th percentile < 500ms
    ],
    'error_rate': ['rate<0.001'], // Error rate < 0.1%
  },
};

const BASE_URL = __ENV.API_BASE_URL || 'https://staging-
  api.helixterminator.app';
const AUTH_TOKEN = __ENV.LOAD_TEST_TOKEN;

```

```
export default function () {
  const start = Date.now();

  // Mix of typical API operations
  const scenario = __ITER % 10;

  let resp;
  switch (scenario) {
    case 0:
    case 1:
    case 2:
      // 30% – List hosts (GET, cacheable)
      resp = http.get(`${BASE_URL}/v1/hosts`, {
        headers: { 'Authorization': `Bearer ${AUTH_TOKEN}` },
      });
      break;

    case 3:
    case 4:
      // 20% – Get vault entries
      resp = http.get(`${BASE_URL}/v1/vaults/current/entries?
        limit=20`, {
        headers: { 'Authorization': `Bearer ${AUTH_TOKEN}` },
      });
      break;

    case 5:
    case 6:
      // 20% – Session status check
      resp = http.get(`${BASE_URL}/v1/sessions/active`, {
        headers: { 'Authorization': `Bearer ${AUTH_TOKEN}` },
      });
      break;

    case 7:
      // 10% – Token refresh
      resp = http.post(`${BASE_URL}/v1/auth/refresh`,
        JSON.stringify({ refresh_token:
          __ENV.REFRESH_TOKEN }),
        { headers: { 'Content-Type': 'application/json' } }
      );
      break;

    case 8:
      // 10% – Health check (should be sub-5ms)
      resp = http.get(`${BASE_URL}/health`);
      break;

    case 9:
      // 10% – User profile
```

```

    resp = http.get(`${BASE_URL}/v1/users/me`, {
      headers: { 'Authorization': `Bearer ${AUTH_TOKEN}` },
    });
    break;
  }

  const latency = Date.now() - start;
  requestRate.add(1);
  apiLatency.add(latency);

  const ok = check(resp, {
    'status 2xx': (r) => r.status >= 200 && r.status < 300,
  });

  if (!ok) {
    errorRate.add(1);
  }
}

```

5.1.4 WebSocket Concurrent Sessions Test

```

// k6/websocket_concurrent.js
import ws from 'k6/ws';
import { check, sleep } from 'k6';
import { Gauge, Counter, Trend } from 'k6/metrics';

const activeConnections = new Gauge('ws_active_connections');
const wsConnectTime = new Trend('ws_connect_duration_ms',
  true);
const wsMessageLatency = new Trend('ws_message_latency_ms',
  true);
const wsErrors = new Counter('ws_errors_total');

export const options = {
  scenarios: {
    websocket_load: {
      executor: 'ramping-vus',
      stages: [
        { duration: '5m', target: 10000 }, // 10k
        concurrent WebSocket connections
        { duration: '20m', target: 100000 }, // Ramp to 100k
        { duration: '10m', target: 100000 }, // Hold at 100k
        { duration: '5m', target: 0 },
      ],
    },
  },
  thresholds: {
    'ws_connect_duration_ms': ['p(95)<1000'],
  },
}

```

```

    'ws_message_latency_ms': ['p(95)<50'], // Terminal
    output_latency < 50ms p95
    'ws_errors_total': ['count<500'],
  },
};

const WS_URL = __ENV.WS_BASE_URL || 'wss://staging-
  ws.helixterminator.app';
const TEST_SESSIONS = JSON.parse(open('./fixtures/
  pre_created_sessions.json'));

export default function () {
  const session = TEST_SESSIONS[__VU % TEST_SESSIONS.length];
  const connectStart = Date.now();

  const res = ws.connect(
    `${WS_URL}/v1/sessions/${session.id}/terminal`,
    { headers: { 'Authorization': `Bearer ${session.token}`
      ` } } },
    function (socket) {
      const connectTime = Date.now() - connectStart;
      wsConnectTime.add(connectTime);
      activeConnections.add(1);

      let messageCount = 0;

      socket.on('open', () => {
        // Send keepalive every 30 seconds
        socket.setInterval(() => {
          socket.send(JSON.stringify({ type: 'ping' }));
        }, 30000);

        // Send a test command
        const sendTime = Date.now();
        socket.send(JSON.stringify({ type: 'input', data:
          'date\n' }));

        socket.on('message', (data) => {
          const msg = JSON.parse(data);
          if (msg.type === 'output') {
            const msgLatency = Date.now() - sendTime;
            wsMessageLatency.add(msgLatency);
            messageCount++;
          }
          if (msg.type === 'pong') {
            // Keepalive acknowledged
          }
        });
      });

      socket.on('error', (e) => {
        wsErrors.add(1);
      });
    }
  );
}

```



```

    });

    // Hold connection open to simulate real user session
    socket.setTimeout(() => {
      socket.close();
      activeConnections.add(-1);
    }, 60000 + Math.random() * 120000); // 1-3 minute
    sessions
  }
);

check(res, { 'ws upgrade ok': (r) => r && r.status ===
  101 });
}

```

5.1.5 Terminal Throughput Test

```

// k6/terminal_throughput.js
import ws from 'k6/ws';
import { check } from 'k6';
import { Trend, Counter } from 'k6/metrics';

const bytesReceived = new
  Counter('terminal_bytes_received_total');
const throughputPerSession = new
  Trend('terminal_throughput_kbps', true);

export const options = {
  vus: 100,
  duration: '5m',
  thresholds: {
    'terminal_throughput_kbps': ['avg>100'], // Average 100
    'terminal_bytes_received_total': ['count>52428800'], //
    50MB total
  },
};

const WS_URL = __ENV.WS_BASE_URL || 'wss://staging-
ws.helixterminator.app';
const TEST_SESSIONS = JSON.parse(open('./fixtures/
pre_created_sessions.json'));

export default function () {
  const session = TEST_SESSIONS[__VU % TEST_SESSIONS.length];
  const startTime = Date.now();
  let totalBytes = 0;

  ws.connect(

```

```

`${WS_URL}/v1/sessions/${session.id}/terminal`,
{ headers: { 'Authorization': `Bearer ${session.token}`
  } },
function (socket) {
  socket.on('open', () => {
    // Generate heavy terminal output (e.g., a long-
    // running find command)
    socket.send(JSON.stringify({
      type: 'input',
      data: 'dd if=/dev/urandom bs=1024 count=10240 |
      base64\n',
    }));
  });

  socket.on('message', (data) => {
    const msg = JSON.parse(data);
    if (msg.type === 'output') {
      const outputBytes = new
      TextEncoder().encode(msg.data).length;
      totalBytes += outputBytes;
      bytesReceived.add(outputBytes);
    }
  });

  socket.setTimeout(() => {
    const duration = (Date.now() - startTime) / 1000; //
    seconds
    const kbps = (totalBytes / 1024) / duration;
    throughputPerSession.add(kbps);
    socket.close();
  }, 30000);
}
);
}

```

5.2 Go Benchmark Tests

```

// services/sshproxy/bench_test.go
package sshproxy_test

import (
    "crypto/rand"
    "testing"

    gossh "golang.org/x/crypto/ssh"
    "github.com/HelixDevelopment/helixterminator/services/
    sshproxy"
)

```

```
func BenchmarkSSHProxy_HostKeyFingerprint_SHA256(b
    *testing.B) {
    _, pubKey, _ := gossh.GenerateKey(rand.Reader,
        gossh.InsecureIgnoreHostKey())
    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _ = gossh.FingerprintSHA256(pubKey)
    }
}

func BenchmarkSSHProxy_ParseAuthorizedKey(b *testing.B) {
    authorizedKey := "ssh-ed25519
        AAAAC3NzaC1lZDI1NTE5AAAAIXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
        bench@test"
    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _, _, _, _, _ =
            gossh.ParseAuthorizedKey([]byte(authorizedKey))
    }
}

// services/auth/bcrypt_bench_test.go
package auth_test

import (
    "testing"
    "golang.org/x/crypto/bcrypt"
)

func BenchmarkBcrypt_Cost10(b *testing.B) {
    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _, _ = bcrypt.GenerateFromPassword([]byte("test-
            password-2026!"), 10)
    }
}

func BenchmarkBcrypt_Cost12(b *testing.B) {
    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _, _ = bcrypt.GenerateFromPassword([]byte("test-
            password-2026!"), 12)
    }
}

// services/vault/aes_bench_test.go
package vault_test

import (
    "crypto/aes"
    "crypto/cipher"
    "crypto/rand"
```

```

    "io"
    "testing"
)

func BenchmarkAES256GCM_Encrypt_1KB(b *testing.B) {
    key := make([]byte, 32)
    _, _ = rand.Read(key)
    plaintext := make([]byte, 1024)
    _, _ = rand.Read(plaintext)

    block, _ := aes.NewCipher(key)
    gcm, _ := cipher.NewGCM(block)

    b.SetBytes(int64(len(plaintext)))
    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        nonce := make([]byte, gcm.NonceSize())
        _, _ = io.ReadFull(rand.Reader, nonce)
        _ = gcm.Seal(nonce, nonce, plaintext, nil)
    }
}

func BenchmarkAES256GCM_Encrypt_64KB(b *testing.B) {
    key := make([]byte, 32)
    _, _ = rand.Read(key)
    plaintext := make([]byte, 64*1024)
    _, _ = rand.Read(plaintext)

    block, _ := aes.NewCipher(key)
    gcm, _ := cipher.NewGCM(block)

    b.SetBytes(int64(len(plaintext)))
    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        nonce := make([]byte, gcm.NonceSize())
        _, _ = io.ReadFull(rand.Reader, nonce)
        _ = gcm.Seal(nonce, nonce, plaintext, nil)
    }
}

```

6. Security Tests

6.1 Security Test Philosophy

Security tests in HelixTerminator are not purely negative tests ("does this fail?") — they are *proof-of-control* tests. Each test must:

1. Demonstrate the **attack vector** is understood

2. Execute the attack with realistic parameters
3. Assert the **exact response** that proves the control is active (HTTP status code, error type, audit log entry)
4. Be linked to the relevant **CVE, OWASP Top 10 category, or CWE identifier**

6.2 Authentication Security Tests

```
// security/auth/brute_force_test.go
package auth_security_test

import (
    "fmt"
    "net/http"
    "net/http/httpptest"
    "testing"
    "time"

    "github.com/HelixDevelopment/helixterminator/api/gateway"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

// TestSecurity_BruteForce_LoginLockout
// OWASP: A07:2021 – Identification and Authentication Failures
// CWE-307: Improper Restriction of Excessive Authentication Attempts
func TestSecurity_BruteForce_LoginLockout(t *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    email := "brute-force-target@example.com"
    server.CreateTestUser(t, email, "correct-password-not-used")

    // Attempt 5 rapid invalid logins
    for i := 0; i < 5; i++ {
        resp := loginRequest(t, server, email,
            fmt.Sprintf("wrong-password-%d", i))
        assert.Equal(t, http.StatusUnauthorized,
            resp.StatusCode)
    }

    // 6th attempt – must return 429 Too Many Requests (or 403 Locked)
    resp := loginRequest(t, server, email, "wrong-password-6th")
    assert.Equal(t, http.StatusTooManyRequests,
        resp.StatusCode,
```

```

        "account must be locked after 5 failed attempts
        (OWASP A07)")

    // Even with correct password, locked account must not
    // authenticate
    resp = loginRequest(t, server, email, "correct-password-
    not-used")
    assert.Equal(t, http.StatusForbidden, resp.StatusCode,
        "correct password must not bypass lockout")

    // Verify Retry-After header is present
    assert.NotEmpty(t, resp.Header.Get("Retry-After"),
        "Retry-After header must be set per RFC 7231")
}

// TestSecurity_JWT_AlgorithmConfusion_HS256NoneAttack
// CWE-347: Improper Verification of Cryptographic Signature
// References: CVE-2015-9235 (node-jsonwebtoken alg:none
// bypass)
func TestSecurity_JWT_AlgorithmConfusion_NoneAlgorithm(t
    *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    // Craft a JWT with alg:none
    noneToken := craftJWTWithAlgorithm(t, "none",
        map[string]interface{}{
            "sub": "usr_admin_01",
            "roles": []string{"admin"},
            "exp": time.Now().Add(1 * time.Hour).Unix(),
        })

    resp := apiRequest(t, server, "GET", "/v1/admin/users",
        noneToken)
    assert.Equal(t, http.StatusUnauthorized, resp.StatusCode,
        "JWT with alg:none MUST be rejected (CVE-2015-9235
        class)")
}

// TestSecurity_JWT_AlgorithmConfusion_RS256ToHS256
// Attack: Sign JWT with RS256 public key as HS256 secret
// References: Critical JWT vulnerability class
func TestSecurity_JWT_AlgorithmConfusion_RS256ToHS256(t
    *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    // Obtain the server's RS256 public key (publicly
    // accessible)
    pubKey := server.GetPublicKey(t)

```

```

    // Sign a malicious token using the public key as HS256
    secret
    maliciousToken := craftHS256TokenWithRSAPublicKey(t,
        pubKey, map[string]interface{}{
            "sub":    "usr_victim_01",
            "roles": []string{"admin"},
            "exp":    time.Now().Add(1 * time.Hour).Unix(),
        })
    })

    resp := apiRequest(t, server, "GET", "/v1/vaults",
        maliciousToken)
    assert.Equal(t, http.StatusUnauthorized, resp.StatusCode,

        "Algorithm confusion attack must be rejected – server
        must not accept HS256 when RS256 is configured")
}

// TestSecurity_JWT_Tampering_PayloadModification
func TestSecurity_JWT_Tampering_PayloadModification(t
    *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    // Get a valid token for a regular user
    token := server.LoginTestUser(t, "regular-
        user@example.com", "password123")

    // Tamper the payload to escalate privileges
    tamperedToken := tamperJWTpayload(t, token,
        map[string]interface{}{
            "roles": []string{"admin"},
        })
    })

    resp := apiRequest(t, server, "GET", "/v1/admin/users",
        tamperedToken)
    assert.Equal(t, http.StatusUnauthorized, resp.StatusCode,
        "Tampered JWT payload must be rejected due to
        signature validation failure")
}

// TestSecurity_SessionFixation
// CWE-384: Session Fixation
func TestSecurity_SessionFixation(t *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    // Step 1: Get a session token before authentication
    preAuthToken := server.GetPreAuthSessionToken(t)

    // Step 2: Login with the pre-auth session token injected
    resp := loginRequestWithSession(t, server,
        "user@example.com", "password123", preAuthToken)
}

```

```

require.Equal(t, http.StatusOK, resp.StatusCode)

// Step 3: The post-authentication session token MUST be
// different
postAuthToken := extractToken(t, resp)
assert.NotEqual(t, preAuthToken, postAuthToken,
    "Session fixation: token must be regenerated upon
    successful authentication (CWE-384)")
}

// TestSecurity_CSRF_APIProtection
// OWASP: A01:2021 – Broken Access Control (CSRF)
func TestSecurity_CSRF_StateChangingRequest_Rejected(t
    *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    token := server.LoginTestUser(t, "csrf-
        test@example.com", "password123")

    // State-changing request WITHOUT CSRF token from a
    // different origin
    req, _ := http.NewRequest("POST", server.URL+"/v1/
        hosts",
        strings.NewReader(`{"hostname":"attacker.com"}`))
    req.Header.Set("Content-Type", "application/json")
    req.Header.Set("Authorization", "Bearer "+token)
    req.Header.Set("Origin", "https://evil-attacker.com") //
    Cross-origin

    client := &http.Client{}
    resp, err := client.Do(req)
    require.NoError(t, err)
    defer resp.Body.Close()

    assert.Equal(t, http.StatusForbidden, resp.StatusCode,
        "Cross-origin state-changing request must be
        rejected")
}

```

6.3 Authorization Security Tests

```

// security/authz/privilege_escalation_test.go
package authz_security_test

import (
    "net/http"
    "testing"

```



```

    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

// TestSecurity_IDOR_VaultAccess
// OWASP: A01:2021 – Broken Access Control
// CWE-639: Authorization Bypass Through User-Controlled Key
func TestSecurity_IDOR_VaultAccess(t *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    // Alice's vault
    aliceToken := server.LoginTestUser(t,
        "alice@example.com", "password123")
    aliceVaultID := server.CreateVaultForUser(t,
        "alice@example.com")

    // Bob tries to access Alice's vault directly by ID
    bobToken := server.LoginTestUser(t, "bob@example.com",
        "password123")
    resp := apiRequest(t, server, "GET",
        "/v1/vaults/"+aliceVaultID+"/entries", bobToken)

    assert.Equal(t, http.StatusForbidden, resp.StatusCode,
        "IDOR: User must not access another user's vault by
        guessing the vault ID (CWE-639)")

    // Verify the response does NOT reveal that the vault
    exists
    var body map[string]interface{}
    json.NewDecoder(resp.Body).Decode(&body)
    assert.NotContains(t, fmt.Sprint(body), aliceVaultID,

        "Error response must not confirm the existence of the
        target resource")

    _ = aliceToken
}

// TestSecurity_PrivilegeEscalation_RoleModification
// OWASP: A01:2021 – Broken Access Control
func TestSecurity_PrivilegeEscalation_SelfRolePromotion(t
    *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    userToken := server.LoginTestUser(t, "regular-
        user@example.com", "password123")

    // Attempt to promote self to admin
    resp := apiRequestWithBody(t, server, "PATCH", "/v1/
        users/me",

```

```

        map[string]interface{}{"role": "admin"}, userToken)

    assert.Equal(t, http.StatusForbidden, resp.StatusCode,
        "Users must not be able to self-promote roles")
}

// TestSecurity_RBAC_TeamPermissionBoundary
func TestSecurity_RBAC_TeamPermissionBoundary(t *testing.T) {
    tests := []struct {
        name           string
        userRole       string
        operation       string
        resource        string
        expectedStatus int
    }{
        {"viewer_cannot_write", "viewer", "POST", "/v1/hosts", http.StatusForbidden},
        {"viewer_can_read", "viewer", "GET", "/v1/hosts", http.StatusOK},
        {"member_cannot_delete_team", "member", "DELETE", "/v1/teams/team_001", http.StatusForbidden},
        {"member_can_add_host", "member", "POST", "/v1/hosts", http.StatusCreated},
        {"admin_can_delete_host", "admin", "DELETE", "/v1/hosts/host_001", http.StatusNoContent},
        {"admin_cannot_delete_org", "admin", "DELETE", "/v1/organizations/org_001", http.StatusForbidden},
        {"owner_can_delete_team", "owner", "DELETE", "/v1/teams/team_001", http.StatusNoContent},
        {"billing_cannot_ssh", "billing", "POST", "/v1/sessions", http.StatusForbidden},
    }

    server := gateway.NewTestServer(t)
    defer server.Close()

    for _, tt := range tests {
        t.Run(tt.name, func(t *testing.T) {
            token := server.LoginTestUserWithRole(t, tt.userRole)
            resp := apiRequest(t, server, tt.operation, tt.resource, token)
            assert.Equal(t, tt.expectedStatus, resp.StatusCode,
                "RBAC boundary violation for role=%s operation=%s", tt.userRole, tt.operation)
        })
    }
}

```

6.4 Cryptographic Security Tests

```
// security/crypto/vault_crypto_test.go
package crypto_security_test

import (
    "crypto/rand"
    "testing"

    "github.com/HelixDevelopment/helixterminator/services/vault"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

// TestSecurity_VaultDecryption_WithoutKey_Fails
// CWE-311: Missing Encryption of Sensitive Data
func TestSecurity_VaultDecryption_WithoutKey_Fails(t
    *testing.T) {
    svc := vault.NewBenchmarkService()

    plaintext :=
        []byte("ssh_password=super_secret_prod_password_2026")
    key1 := make([]byte, 32)
    _, _ = rand.Read(key1)

    ciphertext, err := svc.Encrypt(plaintext, key1)
    require.NoError(t, err)

    // Try to decrypt with every possible single-byte key
    // (trivial exhaustion)
    for _, b := range []byte{0x00, 0xFF, 0x01, 0xAA, 0x55} {
        weakKey := make([]byte, 32)
        for i := range weakKey {
            weakKey[i] = b
        }
        _, err := svc.Decrypt(ciphertext, weakKey)
        assert.Error(t, err,
            "AES-256-GCM must reject decryption with
            incorrect key (GCM auth tag fails)")
    }
}

// TestSecurity_AES_IV_Uniqueness
// CWE-330: Use of Insufficiently Random Values
// Vulnerability: if IVs/nonces are reused with the same key,
// GCM provides no security
func TestSecurity_AES_IV_Uniqueness(t *testing.T) {
    svc := vault.NewBenchmarkService()
```

```

    key := make([]byte, 32)
    _, _ = rand.Read(key)

    nonces := make(map[string]bool)
    for i := 0; i < 10000; i++ {
        ciphertext, err := svc.Encrypt([]byte("test
        plaintext"), key)
        require.NoError(t, err)

        // Extract nonce (first 12 bytes of ciphertext in
        // standard GCM encoding)
        nonceHex := fmt.Sprintf("%x", ciphertext[:12])
        assert.False(t, nonces[nonceHex],
            "Nonce collision detected at iteration %d – IV
            generation is insecure (CWE-330)", i)
        nonces[nonceHex] = true
    }
}

// TestSecurity_WeakKeyGeneration_Rejected
func TestSecurity_WeakKeyGeneration_Rejected(t *testing.T) {
    svc := vault.NewBenchmarkService()

    weakKeys := [][]byte{
        make([]byte, 32), // all zeros
        bytes.Repeat([]byte{0xFF}, 32), // all 0xFF
        bytes.Repeat([]byte{0x01}, 32), // all 0x01
        []byte("password12345678901234567890123"), // ASCII
        "password" padded – 31 bytes
    }

    for _, key := range weakKeys {
        err := svc.ValidateKey(key)
        assert.Error(t, err,
            "Weak key must be rejected before use: %x", key)
    }
}

// TestSecurity_KeyDerivation_PBKDF2_MinIterations
// Ensuring KDF parameters meet minimum security requirements
func TestSecurity_KeyDerivation_MinimumIterations(t
    *testing.T) {
    kdf := vault.NewKeyDerivationFunction()
    params := kdf.GetParameters()

    assert.GreaterOrEqual(t, params.Iterations, 600000,
        "PBKDF2 iterations must be >= 600,000 (NIST SP
        800-132 recommendation for 2026)")
    assert.GreaterOrEqual(t, params.SaltLength, 16,
        "Salt must be at least 16 bytes (128 bits)")
    assert.Equal(t, "sha-512", params.HashFunction,

```

```
        "PBKDF2 must use SHA-512 for HelixTerminator")
    }
```

6.5 SSH-Specific Security Tests

```
// security/ssh/ssh_security_test.go
package ssh_security_test

import (
    "testing"

    "github.com/HelixDevelopment/helixterminator/services/sshproxy"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
    gossh "golang.org/x/crypto/ssh"
)

// TestSecurity_SSH_WeakAlgorithm_MD5_Rejected
// CWE-327: Use of a Broken or Risky Cryptographic Algorithm
func TestSecurity_SSH_WeakAlgorithm_MD5_Rejected(t
    *testing.T) {
    config := sshproxy.BuildSSHClientConfig()

    // Verify deprecated/weak algorithms are NOT in the
    // allowed list
    for _, kex := range config.Config.KeyExchanges {
        assert.NotEqual(t, "diffie-hellman-group1-sha1", kex,
            "DH Group 1 with SHA-1 is cryptographically
            broken – must not be offered")
        assert.NotEqual(t, "diffie-hellman-group14-sha1",
            kex,
            "DH Group 14 with SHA-1 must not be offered per
            current NIST guidance")
    }

    for _, cipher := range config.Config.Ciphers {
        assert.NotEqual(t, "arcfour", cipher, "RC4 is broken
            and must be disabled")
        assert.NotEqual(t, "arcfour128", cipher)
        assert.NotEqual(t, "arcfour256", cipher)
        assert.NotEqual(t, "3des-cbc", cipher, "3DES must be
            disabled")
    }

    for _, mac := range config.Config.MACs {
        assert.NotEqual(t, "hmac-md5", mac,
            "HMAC-MD5 must be disabled")
    }
}
```

```

        assert.NotEqual(t, "hmac-sha1", mac,
            "HMAC-SHA-1 must be disabled")
    }
}

// TestSecurity_SSH_StrictHostKeyChecking
// Verifies that the SSH proxy NEVER silently accepts unknown
// host keys
// (TOFU without explicit user confirmation is prohibited)
func TestSecurity_SSH_StrictHostKeyChecking_NoAutoAccept(t
    *testing.T) {
    proxy := sshproxy.NewTestProxy(t)

    // Connect to a host with NO stored fingerprint
    err := proxy.ConnectToUnknownHost(t, "unknown-
        host.example.com:22")
    require.Error(t, err,
        "Proxy must reject connection to host with no stored
        fingerprint (no Trust-On-First-Use without explicit
        user action)")
    assert.ErrorIs(t, err, sshproxy.ErrUnknownHost)
}

// TestSecurity_SSH_MITM_Detection
// Verifies host key mismatch is detected and connection
// aborted
func TestSecurity_SSH_MITM_Detection(t *testing.T) {
    proxy := sshproxy.NewTestProxy(t)

    // Store a fingerprint for the host
    err := proxy.StoreHostFingerprint(t, "known-
        host.example.com", "SHA256:legit-fingerprint")
    require.NoError(t, err)

    // Simulate connecting and receiving a DIFFERENT
    // fingerprint (MITM scenario)
    err = proxy.ConnectWithFingerprint(t, "known-
        host.example.com:22", "SHA256:attacker-mitm-
        fingerprint")
    require.Error(t, err,
        "MITM detection: host key mismatch must abort the
        connection immediately")
    assert.ErrorIs(t, err, sshproxy.ErrHostKeyMismatch)
}

// TestSecurity_SSH_AllowedAlgorithms_Positive
// Verify that ONLY approved algorithms are in the allowed
// list
func TestSecurity_SSH_AllowedAlgorithms_Positive(t
    *testing.T) {
    config := sshproxy.BuildSSHClientConfig()

```

```

    approvedKEX := map[string]bool{
        "curve25519-sha256":           true,
        "curve25519-sha256@libssh.org": true,
        "ecdh-sha2-nistp256":          true,
        "ecdh-sha2-nistp384":          true,
        "ecdh-sha2-nistp521":          true,
        "diffie-hellman-group-exchange-sha256": true,
        "diffie-hellman-group16-sha512": true,
        "diffie-hellman-group18-sha512": true,
    }

    for _, kex := range config.Config.KeyExchanges {
        assert.True(t, approvedKEX[kex],
            "KEX algorithm %q is not in the approved list",
            kex)
    }
}

```

6.6 Infrastructure Security Tests

```

// security/infra/k8s_network_policy_test.go
//go:build infrasecurity

package infra_security_test

import (
    "context"
    "fmt"
    "net/http"
    "testing"

    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
    metav1 "k8s.io/apimachinery/pkg/apis/meta/v1"
    "k8s.io/client-go/kubernetes"
)

// TestSecurity_K8s_NetworkPolicy_ServiceIsolation
// Verifies that Kubernetes NetworkPolicies enforce service
// isolation
func TestSecurity_K8s_NetworkPolicy_ServiceIsolation(t
    *testing.T) {
    k8s := newK8sClient(t)
    ctx := context.Background()

    // Get the auth service pod IP
    authPod := getServicePod(t, k8s, "helixterm", "auth-
        service")

```

```

    vaultPod := getServicePod(t, k8s, "helixterm", "vault-
        service")

    // Verify direct vault→auth communication is blocked
    (must go through gateway)
    // Execute a curl from vault pod to auth pod's internal
    port
    output, err := execInPod(ctx, k8s, vaultPod, "helixterm",
        []string{"curl", "--connect-timeout", "3", "-s",
            fmt.Sprintf("http://%s:8080/internal/health",
                authPod.Status.PodIP)}})

    // Should timeout or be refused – direct service-to-
    service on internal port is blocked
    assert.Error(t, err, "NetworkPolicy must block direct
        vault→auth communication")
}

// TestSecurity_mTLS_Enforcement
// Verifies that all inter-service communication uses mutual
// TLS
func TestSecurity_mTLS_Enforcement(t *testing.T) {
    k8s := newK8sClient(t)
    ctx := context.Background()

    // Check Istio/Linkerd PeerAuthentication enforces STRICT
    mTLS
    pa := getMeshPeerAuthentication(t, k8s, "helixterm")
    require.NotNil(t, pa)

    for _, pa := range pa.Items {
        assert.Equal(t, "STRICT", pa.Spec.Mtls.Mode.String(),
            "PeerAuthentication %s must enforce STRICT mTLS
            mode", pa.Name)
    }
}

```

7. Contract Tests (Consumer-Driven)

7.1 Pact Framework Overview

HelixTerminator uses [Pact](#) for consumer-driven contract testing. The contract workflow is:

1. Consumer writes Pact test → generates pact file
2. Pact file is published to Pact Broker
(pact.helixterminator.internal)
3. Provider runs pact:verify in CI → fetches and validates


```
contracts
4. Provider can NEVER publish a breaking change without
   notifying consumers first
5. "can-i-deploy" gate in CI checks all contracts pass before
   deployment
```

7.2 Client → Gateway Contract

```
// contracts/client_gateway_test.go
package contracts_test

import (
    "fmt"
    "net/http"
    "testing"

    "github.com/pact-foundation/pact-go/v2/consumer"
    "github.com/pact-foundation/pact-go/v2/matchers"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

func TestPact_ClientToGateway_Login(t *testing.T) {
    mockProvider, err :=
        consumer.NewV2Pact(consumer.MockHTTPProviderConfig{
            Consumer: "HelixTerminator-Client",
            Provider: "HelixTerminator-Gateway",
            LogDir:   "./pacts/logs",
            PactDir:  "./pacts",
        })
    require.NoError(t, err)

    mockProvider.
        AddInteraction().
        Given("a verified user account exists for
            alice@example.com").
        UponReceiving("a login request with valid
            credentials").
        WithRequestPathMatcher("POST", "/v1/auth/login",
            matchers.MatchV2(map[string]interface{}{
                "email":
                    matchers.Like("alice@example.com"),
                "password":
                    matchers.Like("ValidPassword123!"),
                "device_id": matchers.Like("dev-ios-001"),
            })),
        ).
        WillRespondWith(http.StatusOK,
            matchers.MatchV2(map[string]interface{}{
```

```

        "access_token": matchers.Regex("^[A-Za-z0-9_-]+\.\.[A-Za-z0-9_-]+\.\.[A-Za-z0-9_-]+$",
        "eyJhbGciOiJIc2dWIi.SflKxwRj"),
        "refresh_token":
matchers.Like("rt_abc123def456"),
        "user_id": matchers.Regex("^usr_[A-Z0-9]{8}$", "usr_01J4KXYZ"),
        "mfa_required": matchers.Like(false),
        "expires_in": matchers.Integer(900),
    }),
)

err = mockProvider.ExecuteTest(t, func(config
consumer.MockServerConfig) error {
client := newTestGatewayClient(fmt.Sprintf("http://
localhost:%d", config.Port))

result, err := client.Login("alice@example.com",
"ValidPassword123!", "dev-ios-001")
if err != nil {
return err
}

assert.NotEmpty(t, result.AccessToken)
assert.NotEmpty(t, result.RefreshToken)
assert.False(t, result.MFARequired)
return nil
})

require.NoError(t, err)
}

func TestPact_ClientToGateway_CreateVault(t *testing.T) {
mockProvider, err :=
consumer.NewV2Pact(consumer.MockHTTPProviderConfig{
Consumer: "HelixTerminator-Client",
Provider: "HelixTerminator-Gateway",
PactDir:  "./pacts",
})
require.NoError(t, err)

mockProvider.
AddInteraction().
Given("user usr_01J4KXYZ is authenticated").
UponReceiving("a create vault request").
WithRequestPathMatcher("POST", "/v1/vaults",
matchers.MatchV2(map[string]interface{}{
"name": matchers.Like("My Personal Vault"),
"type": matchers.Term("personal",
"^(personal|team)$"),
}),
).

```

```

        WillRespondWith(http.StatusCreated,
            matchers.MatchV2(map[string]interface{}{
                "vault_id": matchers.Regex("^vlt_[A-Za-z0-9]{8}$", "vlt_abc12345"),
                "name": matchers.Like("My Personal Vault"),
                "type": matchers.Like("personal"),
                "created_at": matchers.Timestamp("yyyy-MM-dd'T'HH:mm:ss.SSSX", "2026-06-28T10:00:00.000Z"),
            }),
        )

err = mockProvider.ExecuteTest(t, func(config
consumer.MockServerConfig) error {
    client :=
    newAuthenticatedTestClient(fmt.Sprintf("http://
localhost:%d", config.Port))
    vaultID, err := client.CreateVault("My Personal
Vault", "personal")
    if err != nil {
        return err
    }
    assert.NotEmpty(t, vaultID)
    return nil
})
require.NoError(t, err)
}

```

7.3 Gateway → Auth Service Contract

```

// contracts/gateway_auth_provider_test.go
package contracts_test

import (
    "testing"

    "github.com/pact-foundation/pact-go/v2/provider"
    "github.com/stretchr/testify/require"
)

// TestPact_GatewayToAuthService_Provider verifies the Auth
// service satisfies
// the contract published by the Gateway consumer.
func TestPact_GatewayToAuthService_Provider(t *testing.T) {
    verifier := provider.NewVerifier()

    err := verifier.VerifyProvider(t, provider.VerifyRequest{
        ProviderBaseUrl: "http://localhost:8081", // Auth
        service test instance
    })
    require.NoError(t, err)
}

```

```

Provider:      "HelixTerminator-AuthService",
BrokerURL:     "https://
pact.helixterminator.internal",
BrokerToken:   os.Getenv("PACT_BROKER_TOKEN"),
PublishVerificationResults: os.Getenv("CI") ==
"true",
ProviderVersion: os.Getenv("GIT_COMMIT"),
ProviderTags:  []string{os.Getenv("BRANCH_NAME")},
StateHandlers: provider.StateHandlers{
    "a verified user account exists for
alice@example.com": func(setup bool, s
provider.ProviderState)
(provider.ProviderStateResponse, error) {
    if setup {
        createTestUser(t, "alice@example.com",
"ValidPassword123!")
    }
    return nil, nil
},
    "user account is locked": func(setup bool, s
provider.ProviderState)
(provider.ProviderStateResponse, error) {
    if setup {
        lockTestUser(t, "locked@example.com")
    }
    return nil, nil
},
},
RequestFilter: injectTestHeaders,
})

require.NoError(t, err)
}

```

7.4 SSH Proxy → PKI Service Contract

```

// contracts/sshproxy_pki_test.go
package contracts_test

import (
    "fmt"
    "net/http"
    "testing"

    "github.com/pact-foundation/pact-go/v2/consumer"
    "github.com/pact-foundation/pact-go/v2/matchers"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

```

```

func TestPact_SSHProxy_PKIService_IssueCertificate(t
    *testing.T) {
    mockProvider, err :=
        consumer.NewV2Pact(consumer.MockHTTPProviderConfig{
            Consumer: "HelixTerminator-SSHProxy",
            Provider: "HelixTerminator-PKIService",
            PactDir:  "./pacts",
        })
    require.NoError(t, err)

    mockProvider.
        AddInteraction().
        Given("CA key is available for signing").

        UponReceiving("a certificate signing request for user
            usr_01J4KXYZ").
        WithRequestPathMatcher("POST", "/v1/pki/sign",
            matchers.MatchV2(map[string]interface{}{
                "user_id":      matchers.Like("usr_01J4KXYZ"),
                "public_key":    matchers.Regex("^ssh-ed25519
                    ", "ssh-ed25519 AAAAC3Nz"),
                "ttl_seconds":  matchers.Integer(3600),
                "principals":
                    matchers.EachLike(matchers.Like("ubuntu"), 1),
            }),
        ).
        WillRespondWith(http.StatusOK,
            matchers.MatchV2(map[string]interface{}{
                "certificate": matchers.Regex("^ssh-ed25519-
                    cert-v01@openssh.com ", "ssh-ed25519-cert-
                    v01@openssh.com AAAAHHNza"),
                "serial":         matchers.Integer(1000),
                "valid_before":    matchers.Integer(18000000000),
                "valid_after":     matchers.Integer(17000000000),
            }),
        )

    err = mockProvider.ExecuteTest(t, func(config
        consumer.MockServerConfig) error {
        pkiClient := newPKIClient(fmt.Sprintf("http://
            localhost:%d", config.Port))
        cert, err :=
            pkiClient.SignCertificate("usr_01J4KXYZ", "ssh-
                ed25519 AAAAC3Nz", 3600, []string{"ubuntu"})
        if err != nil {
            return err
        }
        assert.NotEmpty(t, cert.Certificate)
        return nil
    })
}

```

```
    require.NoError(t, err)
}
```

7.5 Audit Service Kafka Contract

```
// contracts/audit_kafka_consumer_test.go
package contracts_test

import (
    "testing"
    "time"

    "github.com/pact-foundation/pact-go/v2/consumer"
    "github.com/pact-foundation/pact-go/v2/matchers"
    "github.com/stretchr/testify/require"
)

func TestPact_AuditService_KafkaConsumer_SessionStartEvent(t
    *testing.T) {
    // Message Pact test for async Kafka communication
    mockMsgProvider, err :=
        consumer.NewMessagePact(consumer.MessagePactConfig{
            Consumer: "HelixTerminator-AuditService",
            Provider: "HelixTerminator-SSHProxy",
            PactDir:  "./pacts",
        })
    require.NoError(t, err)

    mockMsgProvider.
        AddMessage().
        ExpectsToReceive("a session.start audit event from
            SSHProxy").
        WithMetadata(map[string]string{
            "content-type": "application/json",
            "kafka-topic": "helix.audit.events",
        }).
        WithContent(matchers.MatchV2(map[string]interface{}{
            "event_type": matchers.Like("session.start"),
            "actor_id":  matchers.Regex("^usr_[A-Z0-9]{8}$", "usr_01J4KXYZ"),
            "target_id": matchers.Regex("^host_[a-z0-9]+$", "host_001"),
            "session_id": matchers.Regex("^sess_[A-Za-z0-9]{8}$", "sess_xyz789"),
            "timestamp": matchers.Timestamp("yyyy-MM-dd'T'HH:mm:ss'Z'", "2026-06-28T10:00:00Z"),
            "ip_address": matchers.IPv4Address(),
        })).
        AsType(&domain.AuditEvent{})
}
```

```

    err = mockMsgProvider.ExecuteTest(t, func(messages
        []consumer.MessageToVerify) error {
        for _, msg := range messages {
            var event domain.AuditEvent
            if err := json.Unmarshal(msg.Content, &event);
            err != nil {
                return err
            }
            // Verify the audit service can process this
            event shape
            err := processAuditEvent(&event)
            if err != nil {
                return fmt.Errorf("audit service failed to
                process event: %w", err)
            }
        }
        return nil
    })

    require.NoError(t, err)
}

```

8. Chaos Engineering

8.1 Chaos Engineering Framework

HelixTerminator uses [LitmusChaos](#) for structured chaos experiments. All experiments are defined as `ChaosEngine` and `ChaosExperiment` CRDs and run in the `chaos-testing` namespace against the `staging` environment.

Chaos Cadence:

- Nightly: experiments 1–4 (individual component failures)
- Weekly: experiments 5–7 (cascade failures)
- Release gating: full suite

8.2 Chaos Experiment Definitions

8.2.1 Kill Random Service Pod

```

# chaos/experiments/pod-kill-sshproxy.yaml
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosEngine
metadata:
  name: sshproxy-pod-kill
  namespace: chaos-testing

```

```

spec:
  appinfo:
    appns: helixterm-staging
    applabel: "app=sshproxy"
    appkind: deployment
  chaosServiceAccount: litmus-admin
  experiments:
    - name: pod-delete
      spec:
        components:
          env:
            - name: TOTAL_CHAOS_DURATION
              value: "120"          # 2 minutes of chaos
            - name: CHAOS_INTERVAL
              value: "30"          # Kill a pod every 30
seconds
            - name: FORCE
              value: "false"       # Graceful termination
first
            - name: PODS_AFFECTED_PERC
              value: "50"          # Kill 50% of SSH proxy
pods
probe:
  # Steady-state hypothesis: active SSH sessions
  continue
    - name: active-sessions-probe
      type: httpProbe
      httpProbe/inputs:
        url: "https://staging-
api.helixterminator.app/v1/sessions/active/count"
        insecureSkipVerify: false
        responseTimeout: 5000
        method:
          get:
            criteria: ">=0"
            responseCode: "200"
      mode: Continuous
      runProperties:
        probeTimeout: 10
        interval: 15
        stopOnFailure: false
      # Hypothesis: no increase in error rate during pod
      kill
    - name: error-rate-probe
      type: promProbe
      promProbe/inputs:
        endpoint: "http://prometheus.monitoring:9090"
        query: "rate(http_requests_total{status=~'5..'}
[1m]) / rate(http_requests_total[1m])"
        comparator:
          type: float
          criteria: "<="

```



```

        value: "0.01" # Error rate must stay below
1%
    mode: Continuous
    runProperties:
        probeTimeout: 15
        interval: 30

---
# Hypothesis verification: after chaos, all pods must be
  Running within 60s
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosResult
metadata:
  name: sshproxy-pod-kill
  namespace: chaos-testing
spec:
  engine: sshproxy-pod-kill
  experiment: pod-delete
status:
  experimentStatus:
    phase: Completed
    verdict: Pass # Expected verdict

```

8.2.2 Kill All Kafka Brokers

```

# chaos/experiments/kafka-brokers-kill.yaml
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosEngine
metadata:
  name: kafka-all-brokers-kill
  namespace: chaos-testing
spec:
  appinfo:
    appns: helixterm-staging
    applabel: "app=kafka"
    appkind: statefulset
  experiments:
    - name: kafka-broker-pod-failure
      spec:
        components:
          env:
            - name: KAFKA_INSTANCE_NAME
              value: "helix-kafka"
            - name: KAFKA_NAMESPACE
              value: "helixterm-staging"
            - name: KAFKA_BROKER_LIST
              value: "helix-kafka-0, helix-kafka-1, helix-
kafka-2"
            - name: KAFKA_CONSUMER_TIMEOUT

```

```

        value: "30000"
      - name: TOTAL_CHAOS_DURATION
        value: "180"
      - name: ZOOKEEPER_INSTANCE_NAME
        value: "helix-zookeeper"
    probe:
      # Hypothesis: messages are queued and not lost
      during broker outage
      - name: message-queue-depth-probe
        type: promProbe
        promProbe/inputs:
          endpoint: "http://prometheus.monitoring:9090"
          query:
            "kafka_consumer_group_lag{topic='helix.audit.events'}"
          comparator:
            type: float
            criteria: ">="
            value: "0"    # Queue depth increases
            (messages being held) – not lost
          mode: Edge
          runProperties:
            probeTimeout: 30
            interval: 15
          # Hypothesis: after brokers recover, lag drains to
          0 within 5 minutes
      - name: message-drain-probe
        type: promProbe
        promProbe/inputs:
          endpoint: "http://prometheus.monitoring:9090"
          query:
            "kafka_consumer_group_lag{topic='helix.audit.events'}"
          comparator:
            type: float
            criteria: "=="
            value: "0"
          mode: EOT    # Run at End of Test
          runProperties:
            probeTimeout: 300    # 5 minutes for drain
            interval: 30

---
# Post-chaos validation job
apiVersion: batch/v1
kind: Job
metadata:
  name: kafka-chaos-validation
  namespace: chaos-testing
spec:
  template:
    spec:
      containers:
        - name: validator

```

```

    image: ghcr.io/helixdevelopment/helixterminator/
chaos-validator:latest
    command:
      - /bin/sh
      - -c
      - |
        # Verify no audit events were lost during the
        Kafka outage
        python3 /scripts/
        verify_kafka_no_message_loss.py \
          --broker ${KAFKA_BROKER} \
          --topic helix.audit.events \
          --expected-count ${EXPECTED_MSG_COUNT} \
          --tolerance 0 # ZERO tolerance for message
        loss
  restartPolicy: Never

```

8.2.3 PostgreSQL Primary Failure

```

# chaos/experiments/postgres-primary-failover.yaml
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosEngine
metadata:
  name: postgres-primary-failover
  namespace: chaos-testing
spec:
  appinfo:
    appns: helixterm-staging
    applabel: "app=postgresql,role=primary"
    appkind: pod
  experiments:
    - name: pod-delete
      spec:
        components:
          env:
            - name: TOTAL_CHAOS_DURATION
              value: "300" # 5 minutes
            - name: FORCE
              value: "true" # Simulate hard crash (OOM
              kill / node failure)
        probe:
          # SLO: API must continue serving reads within 30
          seconds of primary failure
          - name: api-read-availability
            type: httpProbe
            httpProbe/inputs:
              url: "https://staging-
              api.helixterminator.app/health/db"
            method:

```

```

        get:
          criteria: "=="
          responseCode: "200"
      mode: Continuous
      runProperties:
        probeTimeout: 5
        interval: 5
        initialDelaySeconds: 30 # Allow 30s for
Patroni replica promotion
        stopOnFailure: false
      # SLO: Write operations must resume within 60
seconds
      - name: api-write-availability
        type: httpProbe
        httpProbe/inputs:
          url: "https://staging-
api.helixterminator.app/health/db/write"
          method:
            get:
              criteria: "=="
              responseCode: "200"
        mode: Continuous
        runProperties:
          probeTimeout: 5
          interval: 10
          initialDelaySeconds: 60 # Allow 60s for full
failover
          stopOnFailure: false
      # SLO: Total downtime < 30 seconds for reads, < 60
seconds for writes
      - name: downtime-slo-probe
        type: promProbe
        promProbe/inputs:
          endpoint: "http://prometheus.monitoring:9090"
          query: "avg_over_time(up{job='postgres'}[5m])"
          comparator:
            type: float
            criteria: ">="
            value: "0.95" # 95% availability over 5-
minute window
        mode: EOT

```

8.2.4 Network Partition Between Services

```

# chaos/experiments/network-partition-auth-vault.yaml
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosEngine
metadata:
  name: network-partition-auth-vault

```

```

namespace: chaos-testing
spec:
  appinfo:
    appns: helixterm-staging
    applabel: "app=auth-service"
    appkind: deployment
  experiments:
    - name: pod-network-partition
      spec:
        components:
          env:
            - name: NETWORK_INTERFACE
              value: "eth0"
            - name: TOTAL_CHAOS_DURATION
              value: "120"
            - name: DESTINATION_IPS
              value: "${kubectl get svc vault-service -n
helixterm-staging -o jsonpath='{.spec.clusterIP}')"
            - name: DESTINATION_PORTS
              value: "8082" # Vault service port
          probe:
            # Hypothesis: circuit breaker opens and returns
            graceful error
            - name: circuit-breaker-probe
              type: httpProbe
              httpProbe/inputs:
                url: "https://staging-
api.helixterminator.app/v1/vaults"
                method:
                  get:
                    criteria: "=="
                    responseCode:
                      "503" # Service Unavailable with circuit breaker
                      open
              mode: Continuous
              runProperties:
                probeTimeout: 10
                interval: 15
                initialDelaySeconds: 10
            # Hypothesis: auth service itself continues to
            function
            - name: auth-service-health
              type: httpProbe
              httpProbe/inputs:
                url: "https://staging-
api.helixterminator.app/v1/auth/health"
                method:
                  get:
                    criteria: "=="
                    responseCode: "200"
              mode: Continuous
              runProperties:

```

```
probeTimeout: 5
interval: 10
```

8.2.5 Memory Pressure and OOM Protection

```
# chaos/experiments/memory-pressure.yaml
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosEngine
metadata:
  name: sshproxy-memory-pressure
  namespace: chaos-testing
spec:
  appinfo:
    appns: helixterm-staging
    applabel: "app=sshproxy"
    appkind: deployment
  experiments:
    - name: pod-memory-hog
      spec:
        components:
          env:
            - name: MEMORY_CONSUMPTION
              value: "500" # Consume 500MB per pod
            - name: TOTAL_CHAOS_DURATION
              value: "120"
            - name: NUMBER_OF_WORKERS
              value: "2"
        probe:
          # Hypothesis: OOM protection activates before
          # actual OOM kill
          - name: oom-protection-active
            type: promProbe
            promProbe/inputs:
              endpoint: "http://prometheus.monitoring:9090"
              query:
                "container_memory_working_set_bytes{pod=~'sshproxy.*'} /
                container_spec_memory_limit_bytes"
              comparator:
                type: float
                criteria: "<="
                value: "0.90" # Memory usage must not
                exceed 90% of limit
              mode: Continuous
          # Hypothesis: rate limiting activates under memory
          # pressure
          - name: rate-limiting-active
            type: httpProbe
            httpProbe/inputs:
```

```

        url: "https://staging-
api.helixterminator.app/v1/sessions"
        method:
          post:
            body: '{"host_id":"host_001"}'
            contentType: "application/json"
            criteria: "=="
            responseCode: "429"    # Rate limiting
returns 429
mode: Continuous
runProperties:
  initialDelaySeconds: 30

```

8.2.6 CPU Saturation Test

```

# chaos/experiments/cpu-saturation.yaml
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosEngine
metadata:
  name: api-gateway-cpu-saturation
  namespace: chaos-testing
spec:
  appinfo:
    appns: helixterm-staging
    applabel: "app=api-gateway"
    appkind: deployment
  experiments:
    - name: pod-cpu-hog
      spec:
        components:
          env:
            - name: CPU_CORES
              value: "2"
            - name: CPU_LOAD
              value: "95"    # 95% CPU load
            - name: TOTAL_CHAOS_DURATION
              value: "120"
        probe:
          # Hypothesis: p99 latency stays below 5 seconds
          # even under CPU pressure
          - name: latency-slo-probe
            type: promProbe
            promProbe/inputs:
              endpoint: "http://prometheus.monitoring:9090"
              query: "histogram_quantile(0.99,
rate(http_request_duration_seconds_bucket{service='api-
gateway'}[1m]))"
            comparator:
              type: float

```

```
criteria: "<="
value: "5.0"    # p99 < 5 seconds
mode: Continuous
```

8.3 Chaos Test Verification Script

```
#!/bin/bash
# scripts/verify_chaos_results.sh
# Run after each chaos experiment to verify recovery

set -euo pipefail

NAMESPACE=${1:-"helixterm-staging"}
EXPERIMENT=${2:-"all"}
TIMEOUT=${3:-"300"} # 5 minutes to recover

echo "Verifying chaos recovery for experiment: ${EXPERIMENT}"

# 1. Wait for all pods to be Running
kubectl wait pods \
  --all \
  --for=condition=Ready \
  --namespace="${NAMESPACE}" \
  --timeout="${TIMEOUT}s"
echo "✓ All pods Ready"

# 2. Verify API Gateway is healthy
for i in $(seq 1 10); do
  status=$(curl -s -o /dev/null -w "%{http_code}" \
    "https://staging-api.helixterminator.app/health")
  if [ "$status" = "200" ]; then
    echo "✓ API Gateway healthy (attempt ${i})"
    break
  fi
  if [ "$i" = "10" ]; then
    echo "✗ API Gateway not healthy after 10 attempts"
    exit 1
  fi
  sleep 10
done

# 3. Verify database connectivity
kubectl exec -n "${NAMESPACE}" \
  "$(kubectl get pod -l app=auth-service -n "${NAMESPACE}" \
    -o jsonpath='{.items[0].metadata.name}')" \
  -- curl -s http://localhost:8080/health/db | jq -r
  '.database' | grep -q "ok"
echo "✓ Database connectivity verified"
```



```
# 4. Verify Kafka lag has drained
KAFKA_LAG=$(kubectl exec -n "${NAMESPACE}" \
  "$(kubectl get pod -l app=kafka -n "${NAMESPACE}" -o
    jsonpath='{.items[0].metadata.name}')" \
  -- kafka-consumer-groups.sh --bootstrap-server
    localhost:9092 \
  --describe --group helix-audit-consumer | awk 'NR>1
    {sum+=$5} END {print sum}')

if [ "${KAFKA_LAG}" = "0" ] || [ -z "${KAFKA_LAG}" ]; then
  echo "✓ Kafka consumer lag is zero"
else
  echo "✗ Kafka consumer lag is ${KAFKA_LAG} – messages may
    not have been processed"
  exit 1
fi

echo "All chaos recovery checks passed for experiment: $
  {EXPERIMENT}"
```

9. Mutation Testing

9.1 Overview

Mutation testing uses [go-mutesting](#) to verify that the test suite can detect code mutations. If a mutation is NOT killed by the test suite, it means either (a) the code path is not tested or (b) the assertion is too weak.

9.2 Mutation Operators Applied

Operator	Description	Example Mutation
ArithmeticOperator	Replaces arithmetic ops	<code>a + b</code> → <code>a - b</code>
ArithmeticOperatorReplacement	Changes constants	<code>a > 5</code> → <code>a > 6</code>
RelationalOperator	Changes comparisons	<code>a > b</code> → <code>a >= b</code>
LogicalOperator	Flips logical ops	<code>&&</code> → <code> </code>
ConditionalBoundary	Changes boundary conditions	<code>< n</code> → <code><= n</code>

Operator	Description	Example Mutation
ReturnValue	Changes return values	return true → return false
NullReturn	Returns zero value	return err → return nil
IncrementDecrement	Flips ++ / --	i++ → i--
StatementDeletion	Removes a statement	Deletes return err check
NegateConditional	Negates conditions	if err == nil → if err != nil

9.3 Configuration

```
# .go-mutesting.yaml
mutators:
  - ArithmeticOperator
  - ArithmeticOperatorReplacement
  - RelationalOperator
  - LogicalOperator
  - ConditionalBoundary
  - ReturnValue
  - NullReturn
  - IncrementDecrement
  - StatementDeletion
  - NegateConditional

# Packages to mutate – ordered by priority
packages:
  - "github.com/HelixDevelopment/helixterminator/services/auth"
  - "github.com/HelixDevelopment/helixterminator/services/vault"
  - "github.com/HelixDevelopment/helixterminator/services/sshproxy"
  - "github.com/HelixDevelopment/helixterminator/services/keychain"
  - "github.com/HelixDevelopment/helixterminator/pkg/crypto"

# Exclude generated code, mocks, testdata
exclude:
```

```

- "**/*_mock.go"
- "**/*_generated.go"
- "**/testdata/**"
- "**/mocks/**"

# Minimum mutation score thresholds
thresholds:
  global: 80          # 80% global kill rate
  services/auth: 90   # 90% for auth (critical path)
  services/vault: 90  # 90% for vault (critical path)
  pkg/crypto: 100     # 100% for cryptographic core (zero
                      tolerance)

timeout: 600 # 10 minutes maximum per package

```

9.4 CI Integration

```

# Makefile targets for mutation testing

.PHONY: mutation-test mutation-test-critical mutation-test-
report

mutation-test:
  @echo "Running mutation tests (all packages)..."
  go-mutesting \
    --config .go-mutesting.yaml \
    --report-json testresults/mutation/results.json \
    --report-html testresults/mutation/report.html \
    ./services/... ./pkg/...
  @python3 scripts/check_mutation_score.py \
    --results testresults/mutation/results.json \
    --config .go-mutesting.yaml

mutation-test-critical:
  @echo "Running mutation tests for critical paths only..."
  go-mutesting \
    --config .go-mutesting.yaml \
    --packages "github.com/HelixDevelopment/
helixterminator/pkg/crypto,\
                github.com/HelixDevelopment/
helixterminator/services/auth,\
                github.com/HelixDevelopment/
helixterminator/services/vault" \
    --report-json testresults/mutation/critical.json
  @python3 scripts/check_mutation_score.py \
    --results testresults/mutation/critical.json \
    --min-score 90

mutation-test-report:

```

```
@echo "Generating mutation test report..."
open testresults/mutation/report.html
```

9.5 Mutation Score Enforcement Script

```
#!/usr/bin/env python3
# scripts/check_mutation_score.py
"""Enforces minimum mutation kill scores defined in .go-
    mutesting.yaml"""

import json
import sys
import argparse
import yaml

def main():
    parser = argparse.ArgumentParser()
    parser.add_argument('--results', required=True)
    parser.add_argument('--config', default='.go-
        mutesting.yaml')
    parser.add_argument('--min-score', type=float,
        default=None)
    args = parser.parse_args()

    with open(args.results) as f:
        results = json.load(f)

    with open(args.config) as f:
        config = yaml.safe_load(f)

    thresholds = config.get('thresholds', {})
    global_threshold = thresholds.get('global', 80)
    if args.min_score is not None:
        global_threshold = args.min_score

    failed = []
    for pkg, data in results.items():
        killed = data.get('killed', 0)
        total = data.get('total', 0)
        if total == 0:
            continue
        score = (killed / total) * 100

        # Check package-specific threshold
        pkg_short = pkg.replace('github.com/HelixDevelopment/
            helixterminator/', '')
        threshold = thresholds.get(pkg_short,
            global_threshold)
```

```

        if score < threshold:
            failed.append({
                'package': pkg,
                'score': score,
                'threshold': threshold,
                'killed': killed,
                'survived': total - killed,
                'total': total,
            })
        else:
            print(f"✓ {pkg_short}: {score:.1f}% (threshold: {threshold}%)")

    if failed:
        print("\n× MUTATION SCORE FAILURES:")
        for f in failed:
            print(f"    {f['package']}")
            print(f"        Score: {f['score']:.1f}% (required: {f['threshold']}%)")
            print(f"        Killed: {f['killed']}/{f['total']} - {f['survived']} mutants survived")
        sys.exit(1)

    print(f"\nAll mutation score thresholds met.")

if __name__ == '__main__':
    main()

```

10. HelixQA Integration

10.1 Architecture

The `helixqa` submodule integrates with HelixTerminator at multiple layers:

```

HelixTerminator
├── submodules/
│   └── helixqa/                                ← Git submodule at pinned
revision
│       ├── pkg/autonomous/                    ← SessionCoordinator,
PlatformWorker
│       ├── pkg/navigator/                     ← ActionExecutor (ADB,
Playwright, X11)
│       └── pkg/issuedetector/                 ← LLM-powered bug
detection
│       ├── pkg/session/                      ← SessionRecorder,
VideoManager
│       └── pkg/evidence/                     ← Centralized evidence

```

collection	
└─ pkg/validator/	← Step-by-step validation
with evidence	
└─ pkg/ticket/	← Markdown ticket
generation	
└─ pkg/reporter/	← QA report generation
└─ pkg/planning/	← Test plan generation
└─ .helixqa.yaml	← HelixQA configuration
└─ Makefile	← make qa-session, make
visual-regression	

10.2 HelixQA Configuration

```
# .helixqa.yaml
version: "2"

# Platform targets
platforms:
  web:
    enabled: true
    url: "https://staging.helixtermininator.app"
    executor: playwright
    browser: chromium
    headless: true

  desktop:
    enabled: true
    executor: x11
    binary: "./build/linux/helixtermininator"
    display: ":99"

  android:
    enabled: true
    executor: adb
    device_serial: "${ANDROID_DEVICE_SERIAL}"
    apk: "./build/android/helixterminator.apk"

  ios:
    enabled: false    # iOS runs on physical device farm only

# AI configuration
ai:
  llm_verifier: openai-gpt-4o
  issue_detector: claude-3-5-sonnet
  vision_engine: gpt-4o-vision

# Feature documentation for Doc-Driven Verification
doc_paths:
  - docs/features/
```

```
- docs/user-guide/
- CHANGELOG.md

# Evidence configuration
evidence:
  screenshots: true
  video: true
  video_format: mp4
  video_quality: high
  logs: true
  output_dir: testresults/helixqa/evidence/

# Report configuration
report:
  formats: [markdown, html, json]
  output_dir: testresults/helixqa/reports/
  include_video_timestamps: true
  publish_on_failure: true

# Anti-bluff enforcement (HelixConstitution §11.4)
anti_bluff:
  require_evidence_per_step: true
  fail_on_green_without_evidence: true
  audit_script: scripts/audit_antibluff.sh

# YAML test banks
test_banks:
- path: testbanks/auth_tests.yaml
  priority: P0
  platforms: [web, desktop, android]
- path: testbanks/ssh_session_tests.yaml
  priority: P0
  platforms: [web, desktop]
- path: testbanks/vault_tests.yaml
  priority: P0
  platforms: [web, desktop, android]
- path: testbanks/sftp_tests.yaml
  priority: P1
  platforms: [web, desktop]
- path: testbanks/workspace_tests.yaml
  priority: P1
  platforms: [web, desktop]
- path: testbanks/accessibility_tests.yaml
  priority: P1
  platforms: [web]

# Flaky test quarantine
flaky_detection:
  enabled: true
  min_runs: 10
```

```
flaky_threshold: 0.05 # Mark as flaky if failure rate >
                        5%
quarantine_on_flaky: true
quarantine_issue_label: "flaky-test"
quarantine_github_repo: "HelixDevelopment/
                        helixterminator"
```

10.3 YAML Test Banks

```
# testbanks/auth_tests.yaml
name: "Authentication Tests"
version: "1.0"
description: "Comprehensive authentication flow tests"

tests:
  - id: AUTH-001
    name: "Email/Password Login Success"
    priority: P0
    platforms: [web, desktop, android]
    documentation_ref: "docs/features/
                        authentication.md#email-login"
    steps:
      - action: navigate
        target: "/"
        evidence: screenshot
      - action: fill
        selector: "[data-testid=email-input]"
        value: "${TEST_USER_EMAIL}"
      - action: fill
        selector: "[data-testid=password-input]"
        value: "${TEST_USER_PASSWORD}"
      - action: click
        selector: "[data-testid=login-button]"
        evidence: screenshot
      - action: waitForNavigation
        url_contains: "/dashboard"
        timeout_ms: 10000
      - action: assert
        selector: "[data-testid=user-avatar]"
        condition: visible
        evidence: screenshot
        failure_message: "User avatar must be visible after
                          successful login"

  - id: AUTH-002
    name: "Biometric Login (Mobile/Desktop)"
    priority: P0
    platforms: [android, desktop]
```



```

documentation_ref: "docs/features/
  authentication.md#biometric"
steps:
  - action: launchApp
    evidence: screenshot
  - action: assertVisible
    selector: "[data-testid=biometric-prompt]"
    evidence: screenshot
  - action: simulateBiometricSuccess
    evidence: video_clip
  - action: assert
    selector: "[data-testid=host-list]"
    condition: visible
    failure_message: "Host list must be visible after
      biometric authentication"

- id: AUTH-003
  name: "TOTP MFA Challenge"
  priority: P0
  platforms: [web, desktop]
  documentation_ref: "docs/features/authentication.md#mfa-
    totp"
  steps:
    - action: loginWithPassword
      email: "${MFA_TEST_USER_EMAIL}"
      password: "${MFA_TEST_USER_PASSWORD}"
    - action: assert
      selector: "[data-testid=mfa-challenge-screen]"
      condition: visible
      evidence: screenshot
    - action: fill
      selector: "[data-testid=otp-input]"
      value: "${TOTP_CODE}" # Injected by test harness
        from authenticator
    - action: click
      selector: "[data-testid=mfa-submit]"
    - action: assert
      selector: "[data-testid=dashboard]"
      condition: visible
      evidence: screenshot

```

10.4 AI-Driven Test Generation from OpenAPI Spec

```

// scripts/generate_tests_from_openapi.go
// +build tools

package main

import (

```

```

"context"
"encoding/json"
"log"
"os"

"github.com/HelixDevelopment/helixterminator/
    submodules/helixqa/pkg/planning"
"github.com/HelixDevelopment/helixterminator/
    submodules/helixqa/pkg/autonomous"
)

func main() {
    ctx := context.Background()

    // Load the OpenAPI specification
    specBytes, err := os.ReadFile("api/openapi.yaml")
    if err != nil {
        log.Fatalf("Failed to read OpenAPI spec: %v", err)
    }

    // Initialize the test plan generator
    planner := planning.NewTestPlanGenerator(planning.Config{
        LLM:          "gpt-4o",
        SpecFormat:   "openapi3",
        Platforms:    []string{"web", "desktop", "android"},
        Priorities:   []string{"P0", "P1", "P2"},
        OutputDir:    "testbanks/generated/",
        RuleSet:      "helixconstitution-v1",
    })

    // Generate test plans from the OpenAPI spec
    plans, err := planner.GenerateFromSpec(ctx, specBytes)
    if err != nil {
        log.Fatalf("Test plan generation failed: %v", err)
    }

    log.Printf("Generated %d test plans covering %d
        endpoints",
        len(plans), planner.EndpointCount())

    // Write to YAML test bank files
    for _, plan := range plans {
        outPath := "testbanks/generated/" + plan.Name +
            ".yaml"
        data, _ := json.MarshalIndent(plan, "", " ")
        _ = os.WriteFile(outPath, data, 0644)
        log.Printf("Written: %s (%d tests)", outPath,
            len(plan.Tests))
    }

    // Verify test coverage against documented features

```

```

docProcessor := autonomous.NewDocProcessor("docs/
    features/")
coverage, err := docProcessor.VerifyCoverage(ctx, plans)
if err != nil {
    log.Fatalf("Coverage verification failed: %v", err)
}

log.Printf("Feature coverage: %.1f%%",
    coverage.Percentage)
if coverage.Percentage < 80.0 {
    log.Fatalf("Insufficient feature coverage: %.1f%%
        (required: 80%%)", coverage.Percentage)
}
}

```

10.5 Flaky Test Detection and Quarantine

```

// scripts/helixqa_flaky_detector.go
// +build tools

package main

import (
    "context"
    "log"
    "os"
    "time"

    "github.com/HelixDevelopment/helixterminator/
        submodules/helixqa/pkg/validator"
    helixqa "github.com/HelixDevelopment/helixterminator/
        submodules/helixqa"
)

func main() {
    ctx := context.Background()

    qa := helixqa.NewOrchestrator(helixqa.Config{
        Platform:    os.Getenv("HELIXQA_PLATFORM"),
        Mode:        helixqa.ModeFast,
        FlakyOpts: &helixqa.FlakyDetectionOptions{
            MinRuns:        10,
            Window:         7 * 24 * time.Hour,
            FlakyThreshold: 0.05,
            QuarantineOnFlaky: true,
            GitHubRepo:     "HelixDevelopment/
                helixterminator",
            GitHubToken:    os.Getenv("GITHUB_TOKEN"),
        },
    },

```

```

    })

    report, err := qa.DetectFlakyTests(ctx,
        helixqa.FlakyDetectionRequest{
            TestResultsDir: "testresults/",
            HistoricalRunsDir: "testresults/historical/",
            QuarantineFile: ".helixqa-quarantine.yaml",
        })
    if err != nil {
        log.Fatalf("Flaky detection failed: %v", err)
    }

    log.Printf("Flaky test detection complete:")
    log.Printf("  Analyzed: %d tests", report.AnalyzedCount)
    log.Printf("  Flaky: %d tests (%.1f%%)",
        report.FlakyCount, report.FlakyRate*100)
    log.Printf("  Quarantined: %d tests",
        report.QuarantinedCount)
    log.Printf("  GitHub issues created: %d",
        report.IssuesCreated)

    if report.FlakyCount > 0 {
        log.Printf("\nFlaky tests detected:")
        for _, ft := range report.FlakyTests {
            log.Printf("  - %s (failure rate: %.1f%%, runs:
                %d)",
                ft.TestName, ft.FailureRate*100, ft.RunCount)
        }
    }
}

```

10.6 Coverage Report Generation and Publishing

```

#!/bin/bash
# scripts/generate_coverage_report.sh

set -euo pipefail

OUTPUT_DIR="testresults/coverage"
mkdir -p "${OUTPUT_DIR}"

# 1. Run all unit tests with coverage
go test \
    -v \
    -count=1 \
    -coverprofile="${OUTPUT_DIR}/coverage.out" \
    -covermode=atomic \
    ./services/... \
    ./pkg/...

```

```

# 2. Generate HTML report
go tool cover \
    -html="${OUTPUT_DIR}/coverage.out" \
    -o "${OUTPUT_DIR}/coverage.html"

# 3. Generate per-package summary
go tool cover \
    -func="${OUTPUT_DIR}/coverage.out" \
    | tee "${OUTPUT_DIR}/coverage.txt"

# 4. Check coverage thresholds
python3 scripts/check_coverage_thresholds.py \
    --profile "${OUTPUT_DIR}/coverage.out" \
    --config .coverage-thresholds.yaml

# 5. Publish to HelixQA coverage dashboard
if [ "${CI}" = "true" ]; then
    curl -X POST \
        "${HELIXQA_DASHBOARD_URL}/v1/coverage" \
        -H "Authorization: Bearer ${HELIXQA_API_KEY}" \
        -H "Content-Type: application/json" \
        -d @- <<EOF
{
    "project": "helixterminator",
    "branch": "${BRANCH_NAME}",
    "commit": "${GIT_COMMIT}",
    "coverage_file_url": "${ARTIFACT_BASE_URL}/coverage.out",
    "report_url": "${ARTIFACT_BASE_URL}/coverage.html"
}
EOF
fi

echo "Coverage report generated: ${OUTPUT_DIR}/coverage.html"

```

11. CI/CD Pipeline for Tests

11.1 PR Pipeline (GitHub Actions)

```

# .github/workflows/pr.yml
name: PR Pipeline

on:
  pull_request:
    branches: [main, develop, release/**]

concurrency:

```

```
group: pr-${{ github.event.pull_request.number }}
cancel-in-progress: true

env:
  GO_VERSION: "1.25"
  FLUTTER_VERSION: "3.22.0"
  PACT_BROKER_URL: ${ secrets.PACT_BROKER_URL }
  PACT_BROKER_TOKEN: ${ secrets.PACT_BROKER_TOKEN }

jobs:
  # -----
  # Job 1: Lint and Static Analysis
  # -----
  lint:
    name: Lint & Static Analysis
    runs-on: ubuntu-24.04
    steps:
      - uses: actions/checkout@v4
        with:
          submodules: recursive

      - name: Setup Go
        uses: actions/setup-go@v5
        with:
          go-version: ${ env.GO_VERSION }
          cache: true

      - name: Verify submodule catalogue
        run: |
          bash scripts/verify_submodule_catalogue.sh

      - name: Run golangci-lint
        uses: golangci/golangci-lint-action@v6
        with:
          version: latest
          args: --timeout=10m --config=.golangci.yaml

      - name: Run govulncheck
        run: |
          go install golang.org/x/vuln/cmd/govulncheck@latest
          govulncheck ./...

      - name: Setup Flutter
        uses: subosito/flutter-action@v2
        with:
          flutter-version: ${ env.FLUTTER_VERSION }
          cache: true

      - name: Flutter analyze
        run: |
          cd client
```

```

        flutter analyze --no-fatal-infos

- name: Dart format check
  run: |
    cd client
    dart format --output=none --set-exit-if-changed .

- name: Anti-bluff audit
  run: bash scripts/audit_antibluff.sh
  env:
    STRICT: "true"

# -----
# Job 2: Backend Unit Tests
# -----

unit-tests-go:
  name: Go Unit Tests
  runs-on: ubuntu-24.04
  needs: lint
  strategy:
    matrix:
      package:
        - services/auth
        - services/vault
        - services/sshproxy
        - services/host
        - services/keychain
        - services/audit
        - pkg/crypto
        - pkg/domain
  steps:
    - uses: actions/checkout@v4
      with:
        submodules: recursive

    - name: Setup Go
      uses: actions/setup-go@v5
      with:
        go-version: ${ env.GO_VERSION }
        cache: true

    - name: Run unit tests
      run: |
        go test \
          -v \
          -count=1 \
          -race \
          -timeout=5m \
          -coverprofile=coverage-${ matrix.package }.out \
          -covermode=atomic \

```

```

        ./${{ matrix.package }}/...
env:
    GOTESTFLAGS: "-short"

- name: Check coverage threshold
  run: |
    python3 scripts/check_coverage_thresholds.py \
      --profile coverage-${{ matrix.package }}.out \
      --package "${{ matrix.package }}" \
      --config .coverage-thresholds.yaml

- name: Upload coverage artifact
  uses: actions/upload-artifact@v4
  with:
    name: coverage-${{ matrix.package }}
    path: coverage-${{ matrix.package }}.out

# -----
# Job 3: Flutter Unit Tests
# -----
unit-tests-flutter:
  name: Flutter Unit Tests
  runs-on: ubuntu-24.04
  needs: lint
  steps:
    - uses: actions/checkout@v4
      with:
        submodules: recursive

    - uses: subosito/flutter-action@v2
      with:
        flutter-version: ${ env.FLUTTER_VERSION }
        cache: true

    - name: Flutter test
      run: |
        cd client
        flutter test \
          --coverage \
          --reporter expanded \
          --timeout 120s

    - name: Check Flutter coverage
      run: |
        python3 scripts/check_flutter_coverage.py \
          --lcov client/coverage/lcov.info \
          --min-line 80 \
          --min-branch 85

# -----
# Job 4: Integration Tests

```



```
# -----
integration-tests:
  name: Integration Tests
  runs-on: ubuntu-24.04
  needs: [unit-tests-go, unit-tests-flutter]
  services:
    # Testcontainers manages its own containers, no service
    # containers needed
    docker:
      image: docker:dind
      options: --privileged
  steps:
    - uses: actions/checkout@v4
      with:
        submodules: recursive

    - name: Setup Go
      uses: actions/setup-go@v5
      with:
        go-version: ${ env.GO_VERSION }
        cache: true

    - name: Run integration tests
      run: |
        go test \
          -v \
          -count=1 \
          -race \
          -timeout=15m \
          -tags integration \
          -coverprofile=coverage-integration.out \
          ./...
      env:
        TESTCONTAINERS_RYUK_DISABLED: "false"
        DOCKER_HOST: "unix:///var/run/docker.sock"

    - name: Upload integration coverage
      uses: actions/upload-artifact@v4
      with:
        name: coverage-integration
        path: coverage-integration.out

# -----
# Job 5: Contract Tests (Pact)
# -----
contract-tests:
  name: Contract Tests (Pact)
  runs-on: ubuntu-24.04
  needs: unit-tests-go
  steps:
    - uses: actions/checkout@v4
```

```

    with:
      submodules: recursive

- name: Setup Go
  uses: actions/setup-go@v5
  with:
    go-version: ${ env.GO_VERSION }
    cache: true

- name: Run consumer contract tests
  run: |
    go test \
      -v \
      -timeout=10m \
      -tags=pact \
      ./contracts/...

- name: Publish pacts to broker
  run: |
    go run ./scripts/publish_pacts.go \
      --pact-dir ./pacts \
      --broker-url "${PACT_BROKER_URL}" \
      --consumer-version "${GITHUB_SHA}" \
      --branch "${GITHUB_HEAD_REF}"
  env:
    PACT_BROKER_TOKEN: ${ secrets.PACT_BROKER_TOKEN }

- name: Verify provider contracts
  run: |
    # Start auth service on test port
    go run ./services/auth/cmd/server/main.go &
    AUTH_PID=$!
    sleep 5

    go test \
      -v \
      -timeout=10m \
      -tags=pact_provider \
      ./contracts/providers/auth/...

    kill $AUTH_PID

- name: Check can-i-deploy
  run: |
    curl -X GET \
      "${PACT_BROKER_URL}/can-i-deploy" \
      -H "Authorization: Bearer ${PACT_BROKER_TOKEN}" \
      -d "pacticipant=HelixTerminator-Client&version=${GITHUB_SHA}&to=staging" \
      --fail-with-body

```

```
# -----
# Job 6: Coverage Aggregation Gate
# -----
coverage-gate:
  name: Coverage Gate
  runs-on: ubuntu-24.04
  needs: [integration-tests, contract-tests]
  steps:
    - uses: actions/checkout@v4

    - name: Download all coverage artifacts
      uses: actions/download-artifact@v4
      with:
        pattern: coverage-*
        path: coverage-artifacts/

    - name: Merge coverage profiles
      run: |
        go install github.com/wadey/gocovmerge@latest
        gocovmerge coverage-artifacts/**/*.out > coverage-merged.out

    - name: Enforce global coverage floor
      run: |
        total=$(go tool cover -func=coverage-merged.out | \
          grep total | awk '{print $3}' | tr -d '%')
        echo "Total coverage: ${total}%"
        python3 -c "
          coverage = float('${total}')
          if coverage < 80.0:
            print(f'FAIL: Coverage {coverage:.1f}% is below
            required 80%')
            exit(1)
          print(f'PASS: Coverage {coverage:.1f}% meets the
          80% requirement')
          "
        "
```

```
# -----
# Job 7: Build and Push Docker Image
# -----
```

```
build:
  name: Build Docker Images
  runs-on: ubuntu-24.04
  needs: coverage-gate
  steps:
    - uses: actions/checkout@v4
      with:
        submodules: recursive

    - name: Set up Docker Buildx
      uses: docker/setup-buildx-action@v3
```

```

- name: Login to Container Registry
  uses: docker/login-action@v3
  with:
    registry: ghcr.io
    username: ${ github.actor }
    password: ${ secrets.GITHUB_TOKEN }

- name: Build and push (PR preview)
  uses: docker/build-push-action@v6
  with:
    context: .
    push: true
    tags: |
      ghcr.io/helixdevelopment/helixterminator/
      api:pr-${ github.event.pull_request.number }
    cache-from: type=gha
    cache-to: type=gha,mode=max
    build-args: |
      GIT_COMMIT=${ github.sha }
      BUILD_DATE=$
      ${ github.event.repository.updated_at }

```

11.2 Main Branch Pipeline

```

# .github/workflows/main.yml
name: Main Branch Pipeline

on:
  push:
    branches: [main]

jobs:
  # Runs everything from PR pipeline, then adds:

  e2e-tests:
    name: E2E Tests (Staging)
    runs-on: ubuntu-24.04
    needs: build
    environment: staging
    steps:
      - uses: actions/checkout@v4
        with:
          submodules: recursive

      - name: Deploy to staging
        run: |
          kubectl apply -k k8s/overlays/staging/ \
            --namespace helixterm-staging

```

```

    kubectl rollout status deployment/api-gateway \
      --namespace helixterm-staging \
      --timeout=5m

- name: Run E2E backend tests
  run: |
    go test \
      -v \
      -count=1 \
      -timeout=30m \
      -tags=e2e \
      ./e2e/...
  env:
    API_BASE_URL: "https://staging-
api.helixterminator.app"
    WS_BASE_URL: "wss://staging-
ws.helixterminator.app"
    E2E_TEST_USER_EMAIL: $
    {{ secrets.E2E_TEST_USER_EMAIL }}
    E2E_TEST_USER_PASSWORD: $
    {{ secrets.E2E_TEST_USER_PASSWORD }}

- name: Run Flutter E2E tests (Web)
  run: |
    cd client
    flutter drive \
      --driver=test_driver/integration_test.dart \
      --target=integration_test/app_launch_test.dart \
      -d web-server \
      --web-port=8080
  env:
    APP_URL: "https://staging.helixterminator.app"

- name: Collect E2E evidence
  if: always()
  uses: actions/upload-artifact@v4
  with:
    name: e2e-evidence-${{ github.sha }}
    path: testresults/e2e/evidence/
    retention-days: 30

performance-regression:
  name: Performance Regression Check
  runs-on: ubuntu-24.04
  needs: e2e-tests
  steps:
    - uses: actions/checkout@v4

- name: Setup k6
  uses: grafana/setup-k6-action@v1

```

- name: Run API throughput test
 - run: |
 - k6 run \
 - out json=testresults/perf/api_throughput.json \
 k6/api_gateway_throughput.js
 - env:
 - API_BASE_URL: "https://staging-api.helixterminator.app"
 - LOAD_TEST_TOKEN: \${ secrets.LOAD_TEST_TOKEN }
- name: Check performance regression
 - run: |
 - python3 scripts/check_perf_regression.py \
 - current testresults/perf/api_throughput.json \
 --baseline testresults/perf/baselines/
 - api_throughput.json \
 - max-regression-pct 10

sast-scan:

- name: SAST Security Scan
- runs-on: ubuntu-24.04
- needs: build
- steps:
 - uses: actions/checkout@v4
 - with:
 - submodules: recursive
 - name: Run Semgrep
 - uses: returntocorp/semgrep-action@v1
 - with:
 - config: |
 - p/golang
 - p/jwt
 - p/cryptography
 - p/secrets
 - p/owasp-top-ten
 - audit0n: push
 - name: Run govulncheck
 - run: |
 - go install golang.org/x/vuln/cmd/govulncheck@latest
 - govulncheck ./...

helixqa-session:

- name: HelixQA Autonomous Session
- runs-on: ubuntu-24.04
- needs: e2e-tests
- steps:
 - uses: actions/checkout@v4
 - with:
 - submodules: recursive

```

- name: Run HelixQA autonomous session
  run: make qa-session
  env:
    HELIXQA_PLATFORM: web
    HELIXQA_MODE: fast
    APP_URL: "https://staging.helixterminator.app"
    OPENAI_API_KEY: ${ secrets.OPENAI_API_KEY }
    ANTHROPIC_API_KEY: ${ secrets.ANTHROPIC_API_KEY }

- name: Upload HelixQA report
  if: always()
  uses: actions/upload-artifact@v4
  with:
    name: helixqa-report-${ github.sha }
    path: testresults/helixqa/reports/
    retention-days: 30

```

11.3 Nightly Pipeline

```

# .github/workflows/nightly.yml
name: Nightly Pipeline

on:
  schedule:
    - cron: '0 2 * * *' # 02:00 UTC every night
  workflow_dispatch:
  inputs:
    include_chaos:
      description: 'Run chaos experiments'
      default: 'true'
      type: boolean

jobs:
  full-regression:
    name: Full Regression Suite
    runs-on: ubuntu-24.04
    steps:
      - uses: actions/checkout@v4
        with:
          submodules: recursive

      - name: Run ALL tests (unit + integration + e2e)
        run: make test-all
        timeout-minutes: 120

  mutation-tests:
    name: Mutation Testing

```

```
runs-on: ubuntu-24.04
steps:
  - uses: actions/checkout@v4
    with:
      submodules: recursive

  - name: Setup Go
    uses: actions/setup-go@v5
    with:
      go-version: "1.25"

  - name: Install go-mutesting
    run: go install github.com/zimmski/go-mutesting/cmd/
        go-mutesting@latest

  - name: Run mutation tests (critical packages)
    run: make mutation-test-critical
    timeout-minutes: 60

  - name: Run mutation tests (full)
    run: make mutation-test
    timeout-minutes: 180

  - name: Upload mutation report
    if: always()
    uses: actions/upload-artifact@v4
    with:
      name: mutation-report-${{ github.run_number }}
      path: testresults/mutation/
```

chaos-tests:

```
name: Chaos Engineering
runs-on: ubuntu-24.04
if: ${{ github.event.inputs.include_chaos != 'false' }}
environment: staging-chaos
steps:
  - uses: actions/checkout@v4

  - name: Setup kubectl and Litmus
    run: |
      kubectl apply -f https://litmuschaos.github.io/
        litmus/litmus-operator-v3.yaml
      kubectl wait pod -l app.kubernetes.io/
        component=chaos-operator \
        -n litmus --for=condition=Ready --timeout=120s

  - name: Run pod-kill experiments
    run: |
      kubectl apply -f chaos/experiments/pod-kill-
        sshproxy.yaml
      kubectl wait chaosengine sshproxy-pod-kill \
        -n chaos-testing \
```



```

        --for=jsonpath='{.status.engineStatus}'=completed
    \
    --timeout=300s

- name: Run Kafka broker failure
  run: |
    kubectl apply -f chaos/experiments/kafka-brokers-kill.yaml
    kubectl wait chaosengine kafka-all-brokers-kill \
      -n chaos-testing \
      --for=jsonpath='{.status.engineStatus}'=completed
    \
    --timeout=600s

- name: Run PostgreSQL failover
  run: |
    kubectl apply -f chaos/experiments/postgres-primary-failover.yaml
    kubectl wait chaosengine postgres-primary-failover \
      -n chaos-testing \
      --for=jsonpath='{.status.engineStatus}'=completed
    \
    --timeout=600s

- name: Verify chaos recovery
  run: bash scripts/verify_chaos_results.sh helixterm-staging all 300

- name: Collect chaos results
  if: always()
  run: |
    kubectl get chaosresult -n chaos-testing -o json \
      > testresults/chaos/results-$(date +%Y%m%d).json

```

fuzz-tests:

```

name: Property-Based Fuzz Tests
runs-on: ubuntu-24.04
steps:
- uses: actions/checkout@v4
  with:
    submodules: recursive

- name: Setup Go
  uses: actions/setup-go@v5
  with:
    go-version: "1.25"

- name: Run fuzz tests (60 seconds each)
  run: |
    go test -fuzz=FuzzVaultEncryptDecrypt \
      -fuzztime=60s \

```

```
./services/vault/...

go test -fuzz=FuzzJWTRoundtrip \
-fuzztime=60s \
./services/auth/...

go test -fuzz=FuzzSSHProxyHostKey \
-fuzztime=60s \
./services/sshproxy/...
```

11.4 Release Pipeline

```
# .github/workflows/release.yml
name: Release Pipeline

on:
  push:
    tags:
      - 'v[0-9]+.[0-9]+.[0-9]+'

jobs:
  full-test-suite:
    name: Full Test Suite (Release)
    uses: ../github/workflows/main.yml

  golden-snapshot-tests:
    name: Golden/Snapshot Tests
    runs-on: ubuntu-24.04
    needs: full-test-suite
    steps:
      - uses: actions/checkout@v4
        with:
          submodules: recursive

      - uses: subosito/flutter-action@v2
        with:
          flutter-version: "3.22.0"

      - name: Run golden tests
        run: |
          cd client
          flutter test \
            --tags golden \
            --update-goldens=false # Fail on any golden
          mismatch
        env:
          FLUTTER_TEST_FONT_SIZE: "16" # Consistent font
          rendering
```

```
- name: Upload golden failure diffs
  if: failure()
  uses: actions/upload-artifact@v4
  with:
    name: golden-failures-${{ github.ref_name }}
    path: client/test/goldens/failures/
```

accessibility-audit:

name: Accessibility Audit (WCAG 2.2 AA)

runs-on: ubuntu-24.04

needs: full-test-suite

steps:

```
- uses: actions/checkout@v4

- name: Setup Node.js for axe-core
  uses: actions/setup-node@v4
  with:
    node-version: '22'

- name: Install axe-core
  run: npm install -g @axe-core/cli

- name: Run accessibility audit on staging
  run: |
    axe https://staging.helixterminator.app \
      --tags wcag2a,wcag2aa,wcag21aa,wcag22aa \
      --reporter json \
      --output testresults/accessibility/report.json \
      --exit

- name: Check zero WCAG 2.2 AA violations
  run: |
    violations=$(jq '.violations | length' testresults/
    accessibility/report.json)
    if [ "$violations" -gt "0" ]; then
      echo "FAIL: ${violations} WCAG 2.2 AA violations
      found"
      jq '.violations[] | {id, impact, description}'
      testresults/accessibility/report.json
      exit 1
    fi
    echo "PASS: Zero WCAG 2.2 AA violations"
```

penetration-test-gate:

name: Penetration Test Report Gate

runs-on: ubuntu-24.04

needs: full-test-suite

steps:

```
- uses: actions/checkout@v4

- name: Verify signed pen test report
```

```

run: |
    # Verify the pen test report for this release
    version exists and is signed
    python3 scripts/verify_pentest_report.py \
        --version "${{ github.ref_name }}" \
        --report-dir security/pentest-reports/ \
        --required-after "$(date -d '-90 days' +%Y-%m-%d)" # Report must be < 90 days old

- name: Run DAST scan (OWASP ZAP)
  run: |
    docker run -t ghcr.io/zaproxy/zaproxy:stable zap-
    baseline.py \
        -t "https://staging-api.helixterminator.app" \
        -J testresults/security/zap-report.json \
        -l WARN

- name: Check ZAP for high/critical findings
  run: |
    highs=$(jq '[.site[]].alerts[] | select(.riskcode >=
    "3")] | length' \
        testresults/security/zap-report.json)
    if [ "$highs" -gt "0" ]; then
        echo "FAIL: ${highs} high/critical findings from
    OWASP ZAP"
        jq '[.site[]].alerts[] | select(.riskcode >= "3")
    | {name, risk, url}]' \
            testresults/security/zap-report.json
        exit 1
    fi

publish-release:
  name: Publish Release
  runs-on: ubuntu-24.04
  needs: [golden-snapshot-tests, accessibility-audit,
    penetration-test-gate]
  steps:
    - uses: actions/checkout@v4
      with:
        submodules: recursive

    - name: Create GitHub Release
      uses: softprops/action-gh-release@v2
      with:
        generate_release_notes: true
        files: |
            testresults/security/zap-report.json
            testresults/accessibility/report.json

```

12. Test Data Management

12.1 Test Data Strategy

Test data in HelixTerminator follows the **data ownership** principle: each test creates exactly the data it needs, and no test depends on data created by another test. This ensures:

1. Tests run in any order and produce the same result
2. Tests can be parallelized without data conflicts
3. Test cleanup is deterministic (each test cleans up its own data)
4. No "test database pollution" accumulates over time

12.2 Factory Pattern

```
// testdata/factories/factories.go
package factories

import (
    "context"
    "crypto/rand"
    "fmt"
    "math/big"
    "testing"
    "time"

    "github.com/HelixDevelopment/helixterminator/pkg/
        domain"
    "golang.org/x/crypto/bcrypt"
)

// UserFactory creates domain.User instances for testing.
type UserFactory struct {
    db UserRepository
}

func NewUserFactory(db UserRepository) *UserFactory {
    return &UserFactory{db: db}
}

// Build creates an in-memory User without persisting it.
func (f *UserFactory) Build(opts ...UserOption) *domain.User
{
    n, _ := rand.Int(rand.Reader, big.NewInt(999999999))
    hash, _ :=
        bcrypt.GenerateFromPassword([]byte("TestPassword123!"),
            bcrypt.MinCost)

    u := &domain.User{
```

```

        Email:      fmt.Sprintf("test-user-
        %s@helixterminator-test.app", n.String()),
        PasswordHash: string(hash),
        DisplayName:  fmt.Sprintf("Test User %s",
        n.String()),
        EmailVerified: true,
        CreatedAt:    time.Now().UTC(),
    }

    for _, opt := range opts {
        opt(u)
    }
    return u
}

// Create persists a User to the database and registers
// cleanup.
func (f *UserFactory) Create(t *testing.T, ctx
    context.Context, opts ...UserOption) *domain.User {
    t.Helper()
    u := f.Build(opts...)
    id, err := f.db.Create(ctx, u)
    if err != nil {
        t.Fatalf("UserFactory.Create: %v", err)
    }
    u.ID = id

    t.Cleanup(func() {
        if err := f.db.Delete(ctx, id); err != nil {
            t.Logf("UserFactory cleanup: failed to delete
            user %s: %v", id, err)
        }
    })

    return u
}

// UserOption is a functional option for customizing a User.
type UserOption func(*domain.User)

func WithEmail(email string) UserOption {
    return func(u *domain.User) { u.Email = email }
}

func WithMFA(mfaType domain.MFAType) UserOption {
    return func(u *domain.User) {
        u.MFAEnabled = true
        u.MFAType = mfaType
    }
}

func Locked() UserOption {

```

```

        return func(u *domain.User) {
            u.AccountLocked = true
            u.LockExpiry = time.Now().Add(15 * time.Minute)
        }
    }

    func WithRole(role string) UserOption {
        return func(u *domain.User) { u.Role = role }
    }

    func Unverified() UserOption {
        return func(u *domain.User) { u.EmailVerified = false }
    }

    // -----

    // VaultFactory creates domain.Vault instances.
    type VaultFactory struct {
        db VaultRepository
    }

    func (f *VaultFactory) Create(t *testing.T, ctx
        context.Context, ownerID string,
        opts ...VaultOption) *domain.Vault {
        t.Helper()
        n, _ := rand.Int(rand.Reader, big.NewInt(999999))
        v := &domain.Vault{
            Name:      fmt.Sprintf("Test Vault %s", n.String()),
            OwnerID:   ownerID,
            Type:      domain.VaultPersonal,
        }
        for _, opt := range opts {
            opt(v)
        }
        id, err := f.db.Create(ctx, v)
        if err != nil {
            t.Fatalf("VaultFactory.Create: %v", err)
        }
        v.ID = id
        t.Cleanup(func() { _ = f.db.Delete(ctx, id) })
        return v
    }

    type VaultOption func(*domain.Vault)

    func TeamVault(teamID string) VaultOption {
        return func(v *domain.Vault) {
            v.Type = domain.VaultTeam
            v.TeamID = teamID
        }
    }

```

```
// -----

// HostFactory creates domain.Host instances.
type HostFactory struct {
    db HostRepository
}

func (f *HostFactory) Create(t *testing.T, ctx
    context.Context, ownerID string, opts ...HostOption)
    *domain.Host {
    t.Helper()
    n, _ := rand.Int(rand.Reader, big.NewInt(999999))
    h := &domain.Host{
        OwnerID:    ownerID,
        Hostname:    fmt.Sprintf("test-host-%s.internal",
            n.String()),
        Port:        22,
        Username:     "test-user",
        DisplayName: fmt.Sprintf("Test Host %s", n.String()),
        AuthType:     domain.AuthPassword,
        Fingerprint: fmt.Sprintf("SHA256:test-fp-%s",
            n.String()),
    }
    for _, opt := range opts {
        opt(h)
    }
    id, err := f.db.Create(ctx, h)
    if err != nil {
        t.Fatalf("HostFactory.Create: %v", err)
    }
    h.ID = id
    t.Cleanup(func() { _ = f.db.Delete(ctx, id) })
    return h
}

type HostOption func(*domain.Host)

func WithPort(port int) HostOption {
    return func(h *domain.Host) { h.Port = port }
}

func WithAuthType(authType domain.AuthType) HostOption {
    return func(h *domain.Host) { h.AuthType = authType }
}

```


12.3 Database Seeding Scripts

```
// testdata/seed/seed.go
package seed

import (
    "context"
    "database/sql"
    "fmt"
    "log"

    "github.com/HelixDevelopment/helixterminator/testdata/factories"
)

// SeedForLoadTest seeds the database with the data required
// for load tests.
// This is idempotent – safe to run multiple times.
func SeedForLoadTest(ctx context.Context, db *sql.DB, opts
    SeedOptions) error {
    log.Printf("Seeding load test data: %d users, %d hosts
        each", opts.UserCount, opts.HostsPerUser)

    userFactory := factories.NewUserFactory(db)
    hostFactory := factories.NewHostFactory(db)
    vaultFactory := factories.NewVaultFactory(db)

    for i := 0; i < opts.UserCount; i++ {
        user := userFactory.Build(
            factories.WithEmail(fmt.Sprintf("loadtest-user-
                %04d@helixterminator-test.app", i)),
        )

        // Write user to CSV for k6 to read
        opts.UserCSV.Write([]string{user.Email,
            "LoadTestPassword123!"})

        vault := vaultFactory.Build()
        _ = vault

        for j := 0; j < opts.HostsPerUser; j++ {
            host := hostFactory.Build(
                factories.WithPort(22),
                factories.WithAuthType(domain.AuthPassword),
            )
            _ = host
        }

        if i%100 == 0 {
```

```

        log.Printf("Seeded %d/%d users", i,
            opts.UserCount)
    }
}

log.Printf("Load test seeding complete")
return nil
}

```

12.4 Test Isolation Patterns

```

// testdata/isolation.go
package testdata

import (
    "context"
    "fmt"
    "testing"

    "github.com/HelixDevelopment/helixterminator/testinfra"
)

// IsolatedTestSchema creates a unique PostgreSQL schema for
// each test,
// ensuring complete data isolation without spinning up a new
// container.
func IsolatedTestSchema(t *testing.T, db *sql.DB) *sql.DB {
    t.Helper()

    schemaName := fmt.Sprintf("test_%s_%d",
        sanitizeSchemaName(t.Name()),
        time.Now().UnixNano())

    _, err := db.ExecContext(context.Background(),
        fmt.Sprintf("CREATE SCHEMA %q", schemaName))
    if err != nil {
        t.Fatalf("failed to create isolated schema: %v", err)
    }

    // Run migrations in the isolated schema
    schemaDB := db.WithSchema(schemaName)
    err = migrations.RunAll(schemaDB)
    if err != nil {
        t.Fatalf("migration failed in isolated schema: %v",
            err)
    }

    t.Cleanup(func() {
        _, err := db.ExecContext(context.Background(),

```

```

        fmt.Sprintf("DROP SCHEMA %q CASCADE",
            schemaName))
    if err != nil {
        t.Logf("warning: failed to drop test schema %s:
            %v", schemaName, err)
    }
})

return schemaDB
}

```

12.5 Test Fixture Files

```

testdata/
├── fixtures/
│   ├── users/
│   │   ├── valid_user.json
│   │   ├── locked_user.json
│   │   ├── mfa_user_totp.json
│   │   ├── mfa_user_fido2.json
│   │   └── unverified_user.json
│   ├── vaults/
│   │   ├── personal_vault.json
│   │   ├── team_vault.json
│   │   └── shared_vault.json
│   ├── hosts/
│   │   ├── password_auth_host.json
│   │   ├── pubkey_auth_host.json
│   │   ├── jump_host_chain.json
│   │   └── unreachable_host.json
│   └── ssh_keys/
│       ├── ed25519_private.pem ← test-only key, NOT for
production use
│       ├── ed25519_public.pem
│       ├── rsa_4096_private.pem
│       └── rsa_4096_public.pem
├── jwt/
│   ├── valid_token.jwt
│   ├── expired_token.jwt
│   ├── tampered_payload.jwt
│   └── none_algorithm.jwt
├── factories/
│   ├── factories.go
│   ├── user_factory.go
│   ├── vault_factory.go
│   └── host_factory.go
└── seed/
    └── seed.go

```

```
└─ load_test_seed.go
└─ e2e_test_seed.go
```

12.6 Fixture Data Contract

All fixture files are validated against their JSON schemas on CI:

```
#!/bin/bash
# scripts/validate_fixtures.sh

set -euo pipefail

FIXTURES_DIR="testdata/fixtures"
SCHEMAS_DIR="testdata/schemas"

failed=0

for fixture in "${FIXTURES_DIR}"/**/*.json; do
    schema="${SCHEMAS_DIR}/${(basename $(dirname ${fixture}))/
        $(basename ${fixture%.json}).schema.json}"
    if [ -f "${schema}" ]; then
        if ! ajv validate -s "${schema}" -d "${fixture}" --
            strict=true; then
            echo "✗ Fixture validation failed: ${fixture}"
            failed=$((failed + 1))
        else
            echo "✓ ${fixture}"
        fi
    fi
done

if [ $failed -gt 0 ]; then
    echo "ERROR: ${failed} fixture(s) failed schema
        validation"
    exit 1
fi
echo "All fixtures valid."
```

12.7 Smoke Tests

Smoke tests are a minimal, fast subset of unit tests tagged `//go:build smoke` that verify the most critical paths are alive. They run in under 60 seconds and are the first gate in every pipeline.

```
// services/auth/smoke_test.go
//go:build smoke
```

```

package auth_test

import (
    "context"
    "testing"
    "time"

    "github.com/HelixDevelopment/helixterminator/services/auth"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

// TestSmoke_Auth_ServiceInitializes verifies the auth
// service can be created
// without panicking or returning an error.
func TestSmoke_Auth_ServiceInitializes(t *testing.T) {
    svc, _, _, _, _ := newTestService(t)
    assert.NotNil(t, svc)
}

// TestSmoke_Auth_JWTRoundtrip verifies the core JWT flow
// works end-to-end.
func TestSmoke_Auth_JWTRoundtrip(t *testing.T) {
    svc, _, _, _, _ := newTestService(t)

    token, err := svc.IssueAccessToken(context.Background(),
        "usr_smoke_test", []string{"user"})
    require.NoError(t, err)
    require.NotEmpty(t, token)

    claims, err := svc.ParseAccessToken(token)
    require.NoError(t, err)
    assert.Equal(t, "usr_smoke_test", claims.Subject)
    assert.True(t, claims.ExpiresAt.After(time.Now()))
}

// TestSmoke_Vault_EncryptDecryptRoundtrip verifies AES-256-
// GCM works.
func TestSmoke_Vault_EncryptDecryptRoundtrip(t *testing.T) {
    svc := vault.NewBenchmarkService()
    key := make([]byte, 32)
    for i := range key { key[i] = byte(i) } // Deterministic
    for smoke test
    plaintext := []byte("smoke-test-plaintext")

    ciphertext, err := svc.Encrypt(plaintext, key)
    require.NoError(t, err)

    decrypted, err := svc.Decrypt(ciphertext, key)
    require.NoError(t, err)
}

```

```
    assert.Equal(t, plaintext, decrypted)
}
```

End of HelixTerminator Testing Strategy & QA Specification

Document governed by [HelixConstitution](#) §11.4 Anti-Bluff Covenant. This document must be kept current with every architecture change. The "default test suite green" and "paired §1.1 meta-test green" invariants from the canonical audit script `scripts/audit_antibluff.sh` must pass on every commit to `main`.

QA Orchestration powered by [helixqa](#) – AI-Driven QA Orchestration for Multi-Platform Testing.