

HelixTerminator — Testing Strategy & QA Specification

Document Version: 1.0.0

Status: Authoritative

Classification: Engineering — Internal

Governed by: [HelixConstitution](#) §11.4 Anti-Bluff Covenant

QA Orchestration: [helixqa](#) AI-Driven QA Framework

Last Updated: 2026-06-28

Table of Contents

1. [Testing Philosophy & Constitution Compliance](#)
 2. [Backend Unit Tests \(Go\)](#)
 3. [Backend Integration Tests](#)
 4. [End-to-End Tests](#)
 5. [Performance & Load Tests](#)
 6. [Security Tests](#)
 7. [Contract Tests \(Consumer-Driven\)](#)
 8. [Chaos Engineering](#)
 9. [Mutation Testing](#)
 10. [HelixQA Integration](#)
 11. [CI/CD Pipeline for Tests](#)
 12. [Test Data Management](#)
-

1. Testing Philosophy & Constitution Compliance

1.1 Foundational Mandate

HelixTerminator is a security-critical application. Every character typed in a terminal session, every private key stored in a vault, every SSH session brokered through the proxy carries a trust obligation to the user. Testing is not an afterthought — it is the primary mechanism by which we prove that the software deserves that trust.

The HelixConstitution establishes the universal base-layer rule set that all HelixDevelopment projects must inherit. For HelixTerminator, this means:

1. **The Anti-Bluff Covenant (§11.4):** The bar for shipping is not “tests pass.” The bar is “users can use the feature.” Every test that emits a PASS signal **must carry positive runtime evidence** captured during execution. A green summary line without runtime evidence is a critical defect of equal severity to a missing feature.
2. **Mechanical Enforcement Without Exception (§11.4.75):** Five-layer git-hook discipline enforces test gate compliance. No commit reaches main or any release branch without all required gates passing.
3. **Regeneration Mechanism Required (§11.4.77):** All test artifacts that can be generated from source (mocks, contract stubs, snapshot baselines) must have a documented regeneration path and must be regenerated on every schema change.
4. **CodeGraph Code-Intelligence Mandate (§11.4.78):** The @colbymchenry/codegraph toolchain must be integrated into the test pipeline to ensure cross-service impact analysis before any structural change is merged.
5. **Submodule-Catalogue-First Discovery:** The helixqa submodule must be declared in submodules-catalogue.md and all CI agents must resolve it before test execution begins.
6. **Default Test Suite Green Invariant:** The canonical anti-bluff audit (scripts/audit_antibluff.sh) verifies three invariants on every CI run: (a) §11.4 anchor present across all submodules, (b) default test suite green, (c) paired §1.1 meta-test green.


1.2 Coverage Targets

Coverage targets are tiered by criticality:

Component	Line Coverage	Branch Coverage	Mutation Score
Auth Service	≥ 90%	≥ 95%	≥ 90%
Vault Service	≥ 90%	≥ 95%	≥ 90%
SSH Proxy Service	≥ 85%	≥ 90%	≥ 85%
Keychain Service	≥ 90%	≥ 95%	≥ 90%
Host Service	≥ 80%	≥ 90%	≥ 80%
API Gateway	≥ 80%	≥ 88%	≥ 80%
Audit Service	≥ 80%	≥ 85%	≥ 75%
Flutter Clients	≥ 80%	≥ 85%	N/A
Infrastructure (Terraform/Helm)	N/A	N/A	N/A
Global Floor	≥ 80%	≥ 90% (critical paths)	≥ 80%

The phrase “critical path” means any code path that handles: authentication state transitions, vault cryptographic operations, SSH host-key verification, and privilege-level enforcement in RBAC. These paths require 100% mutation kill rate.

1.3 Test Pyramid Structure



```
| widgets, repositories) |
```

Rationale for the 70:20:10 split:

- Unit tests are fast (< 10ms each), deterministic, and provide the highest signal-to-noise ratio for regression detection. They must dominate the suite.
- Integration tests validate that the seams between components work. They are slower (100ms–5s) but essential for message-bus semantics and data-layer correctness.
- E2E tests validate user-visible outcomes. They are expensive (5s–120s), brittle under infrastructure churn, and should be reserved for high-value user journeys only.

The pyramid is enforced structurally: the CI PR pipeline fails if the ratio deviates by more than 5 percentage points in either direction from the declared target.

1.4 Test-First Development Mandate

All feature work in HelixTerminator follows a strict test-first discipline:

Step 1 — Specification: The author writes a failing test that precisely describes the behavior the feature must produce. This test is committed before any implementation code.

Step 2 — Implementation: The author writes the minimum code to make the test pass.

Step 3 — Refactoring: The author refactors under the green test suite.

Step 4 — helixqa Review: The helixqa autonomous QA session is invoked via `make qa-session` to verify the feature against all documented behaviors. Any behavior not covered by existing tests that helixqa discovers is added to the suite before the PR is eligible for merge.

Step 5 — Anti-Bluff Audit: The `scripts/audit_antibluff.sh` script runs and must exit 0.

The mandate is enforced by a pre-commit hook that rejects any `*.go` or `*.dart` file commit if the corresponding `*_test.go` or `*_test.dart` file does not exist.

1.5 Definition of Done per Test Layer

Unit Test “Done”

- ☐ Test function named following convention `Test{Service}_{Method}_{Scenario}` (Go) or `test{Widget}_{scenario}` (Dart)
- ☐ Uses table-driven patterns (`t.Run` in Go, `parametrize` in Dart) for all multi-scenario functions
- ☐ All external dependencies mocked via interfaces; no real network calls
- ☐ All assertions use `testify/assert` or `testify/require` (Go) / `flutter_test` matchers (Dart)
- ☐ Test is deterministic: runs in any order, produces the same result every time
- ☐ Test covers the happy path, at least two error paths, and all boundary conditions
- ☐ Test runtime < 100ms per case
- ☐ Coverage contribution verified by `go test -coverprofile`
- ☐ helixqa evidence: N/A (unit tests are engine-internal)

Integration Test “Done”

- ☐ Uses `testcontainers-go` for all external services (Postgres, Redis, Kafka, RabbitMQ)
- ☐ Container images are pinned to exact digest in `testcontainers_config.go`
- ☐ Each test creates its own isolated schema/database/topic — no shared state
- ☐ Test tears down containers on success AND failure (via `defer`)
- ☐

Tests verify both the happy-path behavior AND the service's recovery from dependency failure

☐

Test runtime < 60s per test file

☐

helixqa evidence: test produces a JSON evidence artifact at `testresults/integration/{name}.json`

E2E Test “Done”

☐

Test covers a complete user journey from the client's perspective

☐

Test runs against a fully deployed staging environment (not mocks)

☐

Test captures video evidence via helixqa `SessionRecorder`

☐

Test asserts observable UI state, not internal implementation details

☐

Test is idempotent: can be re-run without manual environment reset

☐

Flaky test score < 1% over 100 runs (enforced by helixqa flaky-test quarantine)

☐

helixqa evidence: video recording + screenshot at each assertion point

Performance Test “Done”

☐

k6 script defines success thresholds (p95 latency, error rate)

☐

Script runs for minimum 5 minutes sustained load

☐

Baseline recorded in `testresults/perf/baselines/`

☐

Regression detected if p95 degrades > 10% from baseline

☐

Results published to Grafana dashboard via k6 cloud/output plugin

Security Test “Done”

☐

Test demonstrates the attack vector is blocked (not just that it fails with an error)

☐

Test asserts the specific HTTP/protocol-level response that proves the control is active

☐

Test is linked to the CVE or OWASP category it guards against

☐

Result archived in `testresults/security/{date}/{test_name}.json`

1.6 CI/CD Gating Rules

PR PIPELINE (blocks merge)

- | | |
|---|-------------------------------|
| 1. lint (golangci-lint + flutter analyze) | REQUIRED |
| 2. unit tests | REQUIRED (all pass) |
| 3. integration tests | REQUIRED (all pass) |
| 4. contract tests (Pact verification) | REQUIRED (all pass) |
| 5. coverage gate | REQUIRED ($\geq$ thresholds) |
| 6. anti-bluff audit | REQUIRED (exit 0) |
| 7. Dart/Flutter SBOM + vuln gate
(<code>\$11.5 pub audit + OSV-Scanner</code>) | REQUIRED (no high/crit) |
| 8. build (docker image) | REQUIRED |

MAIN PIPELINE (blocks deployment)

All of the above, PLUS:

- | | |
|---------------------------------------|--|
| 9. E2E tests (staging environment) | REQUIRED (all pass) |
| 10. device/topology matrix subset | REQUIRED (Tier-1 rows,
§4.4 – one physical/virtual per platform family) |
| 11. performance regression check | REQUIRED (< 10% p95) |
| 12. SAST scan (Semgrep + govulncheck) | REQUIRED (no high/crit) |
| 13. helixqa autonomous QA session | REQUIRED (exit 0) |

NIGHTLY PIPELINE (blocks next-day development)

- | | |
|-------------------------------------|------------------------------|
| 14. chaos experiments (LitmusChaos) | ADVISORY (alerting) |
| 15. mutation testing (go-mutesting) | REQUIRED ($\geq 80\%$ kill) |
| 16. full regression suite | REQUIRED (all pass) |
| 17. property-based / fuzz tests | REQUIRED (no crashes) |
| 18. terminal-render perf suite | REQUIRED (§5.3 budgets) |

RELEASE PIPELINE (blocks release tag)

- | | |
|----------------------------------|--------------------------|
| 19. full nightly suite | REQUIRED |
| 20. penetration test report gate | REQUIRED (signed report) |
| 21. DAST scan (OWASP ZAP) | REQUIRED (no high/crit) |

22. accessibility audit (axe-core, web + §10.7 native)	REQUIRED (WCAG 2.2 AA + native SR pass)
23. golden/snapshot test baseline	REQUIRED (no regressions)
24. full device/topology matrix	REQUIRED (§4.4, all Tier-1 + Tier-2 rows green)

The box diagram above is retained as a quick terminal-readable index. The authoritative gate graph — including blocking edges between pipelines and the fail-closed behavior on any REQUIRED gate — is the following flowchart:

flowchart TD

```

    subgraph PR["PR Pipeline – blocks merge"]
        direction TB
        PR1["1. Lint\ngolangci-lint + flutter analyze"]
        PR2["2. Unit tests"]
        PR3["3. Integration tests"]
        PR4["4. Contract tests\nPact verification"]
        PR5["5. Coverage gate"]
        PR6["6. Anti-bluff audit"]
        PR7["7. Dart/Flutter SBOM + vuln gate\n§11.5"]
        PR8["8. Build docker image"]
        PR1 --> PR2 --> PR3 --> PR4 --> PR5 --> PR6 --> PR7 -->
    
```

PR8

end

```

    PRGate{"All PR gates GREEN?"}
    PR8 --> PRGate
    PRGate -- "No – any REQUIRED gate red" --> PRBlock["Merge
BLOCKED"]
    PRGate -- "Yes" --> MergeToMain["Merge to main"]
    
```

```

    subgraph MAIN["Main Pipeline – blocks deployment"]
        direction TB
        M1["9. E2E tests\nstaging environment"]
        M2["10. Device/topology matrix subset\n§4.4 Tier-1"]
        M3["11. Performance regression check\n< 10% p95"]
        M4["12. SAST scan\nSemgrep + govulncheck"]
        M5["13. HelixQA autonomous QA session"]
    
```

```

    M1 --> M2 --> M3 --> M4 --> M5
end

MergeToMain --> M1
MainGate{"All Main gates GREEN?"}
M5 --> MainGate
MainGate -- "No" --> MainBlock["Deployment BLOCKED"]
MainGate -- "Yes" --> Deploy["Deploy to staging"]

subgraph NIGHTLY["Nightly Pipeline – blocks next-day
development"]
    direction TB
    N1["14. Chaos experiments\nLitmusChaos – ADVISORY"]
    N2["15. Mutation testing\n≥ 80% kill"]
    N3["16. Full regression suite"]
    N4["17. Property-based / fuzz tests"]
    N5["18. Terminal-render perf suite\n$5.3 budgets"]
    N1 -.-> N2 --> N3 --> N4 --> N5
end

Deploy --> N1
NightlyGate{"All REQUIRED nightly gates GREEN?"}
N5 --> NightlyGate
NightlyGate -- "No" --> NightlyBlock["Next-day dev
BLOCKED\n(chaos is advisory-only)"]
NightlyGate -- "Yes" --> ReleaseReady["Eligible for release
tag"]

subgraph RELEASE["Release Pipeline – blocks release tag"]
    direction TB
    R1["19. Full nightly suite"]
    R2["20. Penetration test report gate\nsigned report < 90
days"]
    R3["21. DAST scan\nOWASP ZAP"]
    R4["22. Accessibility audit\naxe-core web + $10.7 native
SR"]
    R5["23. Golden/snapshot baseline"]
    R6["24. Full device/topology matrix\n$4.4 Tier-1 +
Tier-2"]
    R1 --> R2 --> R3 --> R4 --> R5 --> R6
end

ReleaseReady --> R1
ReleaseGate{"All release gates GREEN?"}

```

```

R6 --> ReleaseGate
ReleaseGate -- "No" --> ReleaseBlock["Release tag BLOCKED"]
ReleaseGate -- "Yes" --> Tag["Release tag published\n(all
owned submodules + main, $11.4.113)"]

```

1.7 HelixQA Integration Overview

The helixqa submodule is declared at submodules/helixqa and is incorporated per CONST-051(C). It provides the following capabilities for HelixTerminator:

Capability	Integration Point	Trigger
Autonomous QA Session	make qa-session	Post-deploy on staging
VisionEngine visual regression	make visual-regression	Release pipeline
LLM-powered bug detection (pkg/issuedetector)	make helixqa-issues	Main pipeline
Test plan generation (pkg/planning)	make helixqa-plan	Feature branch creation
Flaky test detection	make helixqa-flaky	Nightly pipeline
Evidence collection	Automatic via pkg/evidence	All E2E test runs
Ticket generation (pkg/ticket)	Automatic on failure	All pipelines

The HelixQA anti-bluff invariant is enforced globally: any test result without runtime evidence is treated as a critical defect. The pkg/validator package ensures evidence is collected at every assertion step during E2E and autonomous sessions.

1.8 Twelve Mandated Test Types (+ 5 Extended Sub-Categories) — Compliance Matrix

Per the canonical test-type count (CD-12), the HelixConstitution mandates **twelve** core test types for HelixTerminator — rows 1-12 below. Rows 13-17 are **not** additional top-level mandates; they are extended sub-categories that specialize one of the twelve core types (mapping noted in the “Sub-Category Of” column) and are retained here because each already has a distinct owner, framework, and gate

worth tracking separately. This reconciles the doc’s prior “seventeen mandated test types” framing, which silently contradicted the canonical count.

#	Test Type	Owner Service	Framework	Status Gate	Sub-Category Of
1	Unit Tests	All services	Go testing + testify	PR	— (core)
2	Integration Tests	All backend services	testcontainers-go	PR	— (core)
3	E2E Tests	Full stack	helixqa + Flutter integration_test	Main	— (core)
4	Performance/ Load Tests	API Gateway, SSH Proxy	k6	Main	— (core)
5	Security Tests	Auth, Vault, SSH	Custom Go + OWASP ZAP	Main	— (core)
6	Contract Tests	All services	Pact Go + Pact Dart	PR	— (core)
7	Smoke Tests	All services	Go testing (tagged)	PR	— (core)
8	Regression Tests	Full suite	All frameworks	Nightly	— (core)
9	Chaos Tests	Infrastructure	LitmusChaos	Nightly	— (core)
10	Mutation Tests	Critical paths	go-mutesting	Nightly	— (core)
11	Golden/ Snapshot Tests	Flutter UI	flutter_test matchesGoldenFile	Release	— (core)
12	Accessibility Tests	Flutter UI	axe-core + flutter_a11y	Release	— (core)
13	Penetration Tests	Full system	Manual + automated plan	Release	Security Tests (#5)
14	Property-Based Tests	Auth, Vault, SSH	rapid (Go) + fast_check (Dart)	Nightly	Unit Tests (#1)
15	API Tests	REST + WebSocket APIs	httptest + k6	PR	Integration Tests (#2)
16	Database Tests	PostgreSQL layer	testcontainers-go	PR	Integration Tests (#2)

#	Test Type	Owner Service	Framework	Status Gate	Sub-Category Of
17	Infrastructure Tests	Kubernetes/ Helm	Terratest + kube-score	Nightly	Chaos Tests (#9)

2. Backend Unit Tests (Go)

2.1 Test Infrastructure Setup

All Go unit tests follow the project-wide conventions below.

2.1.1 Directory Structure

```

services/
├── auth/
│   ├── service.go
│   ├── service_test.go           ← unit tests
│   ├── mocks/
│   │   ├── mock_user_repo.go    ← generated via mockery
│   │   ├── mock_token_store.go
│   │   └── mock_mfa_provider.go
│   └── testdata/
│       ├── valid_user.json
│       └── locked_user.json
├── vault/
│   ├── service.go
│   ├── service_test.go
│   └── mocks/
├── sshproxy/
│   ├── service.go
│   ├── service_test.go
│   └── mocks/
...

```

2.1.2 Standard Test File Header

```
package auth_test
```

```
import (
    "context"
```

```

"testing"
"time"

"github.com/HelixDevelopment/helixtermininator/services/auth"
"github.com/HelixDevelopment/helixterminator/services/auth/
mocks"
"github.com/stretchr/testify/assert"
"github.com/stretchr/testify/mock"
"github.com/stretchr/testify/require"
"github.com/stretchr/testify/suite"
)

```

2.1.3 Mock Generation

All mocks are generated using mockery v2. The generation configuration lives in `.mockery.yaml`:

```

with-expecter: true
mockname: "Mock{{.InterfaceName}}"
outpkg: mocks
dir: "{{.InterfaceDir}}/mocks"
packages:
  github.com/HelixDevelopment/helixterminator/services/auth:
    interfaces:
      UserRepository:
      TokenStore:
      MFAProvider:
      AuditLogger:
  github.com/HelixDevelopment/helixterminator/services/vault:
    interfaces:
      VaultRepository:
      KeyProvider:
      ShareRepository:
  github.com/HelixDevelopment/helixterminator/services/sshproxy:
    interfaces:
      SessionStore:
      HostRepository:
      AuditEmitter:

```

Mocks are regenerated automatically on `make generate`. Any PR that changes an interface without regenerating its mock is rejected by the `check-generate` CI step.

2.2 Auth Service Unit Tests

2.2.1 Complete Test Suite

```
// services/auth/service_test.go
package auth_test

import (
    "context"
    "errors"
    "testing"
    "time"

    "github.com/HelixDevelopment/helixterminator/services/auth"
    "github.com/HelixDevelopment/helixterminator/services/auth/
        mocks"
    "github.com/HelixDevelopment/helixterminator/pkg/domain"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/mock"
    "github.com/stretchr/testify/require"
    "golang.org/x/crypto/bcrypt"
)

// -----
// Test helpers
// -----

func newHashedPassword(t *testing.T, raw string) string {
    t.Helper()
    hash, err := bcrypt.GenerateFromPassword([]byte(raw),
        bcrypt.MinCost)
    require.NoError(t, err)
    return string(hash)
}

func newTestService(t *testing.T) (
    *auth.Service,
    *mocks.MockUserRepository,
    *mocks.MockTokenStore,
    *mocks.MockMFAProvider,
    *mocks.MockAuditLogger,
) {
    t.Helper()
    userRepo := mocks.NewMockUserRepository(t)
    tokenStore := mocks.NewMockTokenStore(t)
```

```

mfaProvider := mocks.NewMockMFAProvider(t)
auditLog := mocks.NewMockAuditLogger(t)
svc := auth.NewService(auth.Config{
    JWTSecret:      []byte("test-secret-32-bytes-
    exactly!!!"),
    AccessTokenTTL: 15 * time.Minute,
    RefreshTokenTTL: 7 * 24 * time.Hour,
    MaxLoginAttempts: 5,
    LockoutDuration: 15 * time.Minute,
}, userRepo, tokenStore, mfaProvider, auditLog)
return svc, userRepo, tokenStore, mfaProvider, auditLog
}

// -----
// TestAuthService_Login
// -----

func TestAuthService_Login_Success(t *testing.T) {
    svc, userRepo, tokenStore, _, auditLog := newTestService(t)

    hashedPw := newHashedPassword(t, "correct-password-123!")
    user := &domain.User{
        ID:          "usr_01J4KXYZ",
        Email:       "alice@example.com",
        PasswordHash: hashedPw,
        MFAEnabled:  false,
        AccountLocked: false,
        LoginAttempts: 0,
    }

    userRepo.EXPECT().
        FindByEmail(mock.Anything, "alice@example.com").
        Return(user, nil)

    tokenStore.EXPECT().
        StoreRefreshToken(mock.Anything, mock.MatchedBy(func(t
        *domain.RefreshToken) bool {
            return t.UserID == user.ID
        }))).
        Return(nil)

    auditLog.EXPECT().
        RecordLoginSuccess(mock.Anything, user.ID,
        mock.AnythingOfType("string")).
        Return(nil)

```



```

    result, err := svc.Login(context.Background(),
        auth.LoginRequest{
            Email:      "alice@example.com",
            Password:    "correct-password-123!",
            DeviceID:    "dev_test_001",
        })

    require.NoError(t, err)
    assert.NotEmpty(t, result.AccessToken)
    assert.NotEmpty(t, result.RefreshToken)
    assert.Equal(t, user.ID, result.UserID)
    assert.False(t, result.MFARequired)
}

func TestAuthService_Login_InvalidPassword(t *testing.T) {
    svc, userRepo, _, _, auditLog := newTestService(t)

    hashedPw := newHashedPassword(t, "correct-password-123!")
    user := &domain.User{
        ID:            "usr_01J4KXYZ",
        Email:         "alice@example.com",
        PasswordHash:  hashedPw,
        LoginAttempts: 2,
        AccountLocked: false,
    }

    userRepo.EXPECT().
        FindByEmail(mock.Anything, "alice@example.com").
        Return(user, nil)

    userRepo.EXPECT().
        IncrementLoginAttempts(mock.Anything, user.ID).
        Return(3, nil)

    auditLog.EXPECT().
        RecordLoginFailure(mock.Anything, user.ID,
            "invalid_password", mock.AnythingOfType("string")).
        Return(nil)

    _, err := svc.Login(context.Background(), auth.LoginRequest{
        Email:      "alice@example.com",
        Password:    "wrong-password",
        DeviceID:    "dev_test_001",
    })

```

```

require.Error(t, err)
assert.ErrorIs(t, err, auth.ErrInvalidCredentials)
}

func TestAuthService_Login_AccountLocked(t *testing.T) {
    svc, userRepo, _, _, auditLog := newTestService(t)

    user := &domain.User{
        ID:            "usr_01J4KXYZ",
        Email:         "locked@example.com",
        AccountLocked: true,
        LockExpiry:    time.Now().Add(10 * time.Minute),
    }

    userRepo.EXPECT().
        FindByEmail(mock.Anything, "locked@example.com").
        Return(user, nil)

    auditLog.EXPECT().
        RecordLoginFailure(mock.Anything, user.ID,
            "account_locked", mock.AnythingOfType("string")).
        Return(nil)

    _, err := svc.Login(context.Background(), auth.LoginRequest{
        Email:      "locked@example.com",
        Password:   "any-password",
        DeviceID:   "dev_test_001",
    })

    require.Error(t, err)
    var lockErr *auth.AccountLockedError
    assert.ErrorAs(t, err, &lockErr)
    assert.True(t, lockErr.Expiry.After(time.Now()))
}

func TestAuthService_Login_MFARequired(t *testing.T) {
    svc, userRepo, _, _, auditLog := newTestService(t)

    hashedPw := newHashedPassword(t, "correct-password-123!")
    user := &domain.User{
        ID:            "usr_01J4KXYZ",
        Email:         "mfa-user@example.com",
        PasswordHash: hashedPw,
    }

```

```

        MFAEnabled:    true,
        MFAType:       domain.MFATOTPApp,
    }

    userRepo.EXPECT().
        FindByEmail(mock.Anything, "mfa-user@example.com").
        Return(user, nil)

    auditLog.EXPECT().
        RecordMFAChallengeSent(mock.Anything, user.ID).
        Return(nil)

    result, err := svc.Login(context.Background(),
        auth.LoginRequest{
            Email:    "mfa-user@example.com",
            Password: "correct-password-123!",
            DeviceID: "dev_test_001",
        })

    require.NoError(t, err)
    assert.True(t, result.MFARequired)
    assert.NotEmpty(t, result.MFASessionToken)
    assert.Empty(t, result.AccessToken, "access token must NOT be
        issued before MFA completes")
}

func TestAuthService_Login_UserNotFound(t *testing.T) {
    svc, userRepo, _, _, _ := newTestService(t)

    userRepo.EXPECT().
        FindByEmail(mock.Anything, "ghost@example.com").
        Return(nil, domain.ErrNotFound)

    _, err := svc.Login(context.Background(), auth.LoginRequest{
        Email:    "ghost@example.com",
        Password: "any-password",
        DeviceID: "dev_test_001",
    })

    require.Error(t, err)
    // Must return generic error – must NOT reveal whether email
    // exists
    assert.ErrorIs(t, err, auth.ErrInvalidCredentials)
}

```

```

func TestAuthService_Login_TriggersLockoutAfterMaxAttempts(t
    *testing.T) {
    svc, userRepo, _, _, auditLog := newTestService(t)

    hashedPw := newHashedPassword(t, "correct-password-123!")
    user := &domain.User{
        ID:            "usr_01J4KXYZ",
        Email:         "alice@example.com",
        PasswordHash:  hashedPw,
        LoginAttempts: 4, // one more failed attempt should lock
        AccountLocked: false,
    }

    userRepo.EXPECT().
        FindByEmail(mock.Anything, "alice@example.com").
        Return(user, nil)

    userRepo.EXPECT().
        IncrementLoginAttempts(mock.Anything, user.ID).
        Return(5, nil)

    userRepo.EXPECT().
        LockAccount(mock.Anything, user.ID,
            mock.MatchedBy(func(expiry time.Time) bool {
                return expiry.After(time.Now().Add(14 * time.Minute))
            })).
        Return(nil)

    auditLog.EXPECT().
        RecordAccountLocked(mock.Anything, user.ID).
        Return(nil)

    auditLog.EXPECT().
        RecordLoginFailure(mock.Anything, user.ID,
            "invalid_password", mock.AnythingOfType("string")).
        Return(nil)

    _, err := svc.Login(context.Background(), auth.LoginRequest{
        Email:      "alice@example.com",
        Password:   "wrong-password",
        DeviceID:   "dev_test_001",
    })

    require.Error(t, err)
    assert.ErrorIs(t, err, auth.ErrInvalidCredentials)
}

```

```

}

// -----
// TestAuthService_RateLimit_Login – table-driven, 4 scenarios.
// Drives the real Service.Login rate-limit path
//     (MaxLoginAttempts=5,
// see newTestService) attempt-by-attempt and asserts, per row,
// the
// exact point at which the Nth login is rejected as locked – the
// domain-level counterpart to the HTTP-level 429 assertion in
// TestSecurity_BruteForce_LoginLockout (§6.2, security/auth/
// brute_force_test.go).
// -----

func TestAuthService_RateLimit_Login(t *testing.T) {
    const maxAttempts = 5 // matches newTestService's
                          Config.MaxLoginAttempts

    tests := []struct {
        name                string
        priorFailedAttempts int // LoginAttempts already recorded before this call
        wantLocked          bool // true => this attempt must be
                               rejected as locked (429-equivalent)
    }{
        {name: "1st_failure_after_0_prior_stays_open",
         priorFailedAttempts: 0, wantLocked: false},
        {name: "4th_failure_after_3_prior_stays_open",
         priorFailedAttempts: 3, wantLocked: false},
        {name: "5th_failure_after_4_prior_triggers_lock",
         priorFailedAttempts: 4, wantLocked: true},
        {name: "6th_attempt_while_already_locked_is_rejected",
         priorFailedAttempts: 5, wantLocked: true},
    }

    for _, tt := range tests {
        t.Run(tt.name, func(t *testing.T) {
            svc, userRepo, _, _, auditLog := newTestService(t)

            hashedPw := newHashedPassword(t, "correct-
password-123!")
            alreadyLocked := tt.priorFailedAttempts >= maxAttempts
            user := &domain.User{
                ID:                "usr_ratelimit_test",
                Email:              "ratelimit@example.com",
                PasswordHash:      hashedPw,
                LoginAttempts:      tt.priorFailedAttempts,
                AccountLocked:      alreadyLocked,
            }

```

```

    }
    if alreadyLocked {
        user.LockExpiry = time.Now().Add(15 * time.Minute)
    }

    userRepo.EXPECT().
        FindByEmail(mock.Anything,
            "ratelimit@example.com").
        Return(user, nil)

    if alreadyLocked {
        // Already locked before this call: the service
        must reject
        // immediately, without incrementing the counter
        again.
        auditLog.EXPECT().
            RecordLoginFailure(mock.Anything, user.ID,
                "account_locked", mock.AnythingOfType("string")).
            Return(nil)
    } else {
        newAttemptCount := tt.priorFailedAttempts + 1
        userRepo.EXPECT().
            IncrementLoginAttempts(mock.Anything,
                user.ID).
            Return(newAttemptCount, nil)

        if newAttemptCount >= maxAttempts {
            userRepo.EXPECT().
                LockAccount(mock.Anything, user.ID,
                    mock.MatchedBy(func(expiry time.Time) bool {
                        return expiry.After(time.Now().Add(14
                            * time.Minute))
                    }))).
                Return(nil)
            auditLog.EXPECT().
                RecordAccountLocked(mock.Anything,
                    user.ID).
                Return(nil)
        }

        auditLog.EXPECT().
            RecordLoginFailure(mock.Anything, user.ID,
                "invalid_password", mock.AnythingOfType("string")).
            Return(nil)
    }

    _, err := svc.Login(context.Background(),
        auth.LoginRequest{

```

```

        Email:      "ratelimit@example.com",
        Password:   "wrong-password",
        DeviceID:   "dev_test_ratelimit",
    })

    require.Error(t, err, "an incorrect password must
never succeed")

    var lockErr *auth.AccountLockedError
    if tt.wantLocked {
        assert.ErrorAsf(t, err, &lockErr,
            "attempt %d (prior=%d) must be rejected as
locked (429-equivalent), got: %v",
            tt.priorFailedAttempts+1,
            tt.priorFailedAttempts, err)
    } else {
        assert.ErrorIs(t, err, auth.ErrInvalidCredentials,
            "attempt %d must fail on bad credentials but
NOT yet be locked", tt.priorFailedAttempts+1)
        assert.False(t, errors.As(err, &lockErr), "must
not be locked before max attempts reached")
    }
})
}

// -----
// TestAuthService_FIDO2
// -----

func TestAuthService_FIDO2_Challenge(t *testing.T) {
    svc, userRepo, _, mfaProvider, _ := newTestService(t)

    user := &domain.User{
        ID:      "usr_01J4KXYZ",
        Email:   "fido2-user@example.com",
        MFAEnabled: true,
        MFAType: domain.MFAFIDO2,
    }

    userRepo.EXPECT().
        FindByID(mock.Anything, "usr_01J4KXYZ").
        Return(user, nil)

    expectedChallenge := &domain.FIDO2Challenge{
        Challenge: []byte("random-challenge-bytes"),
    }

```

```

        RPID:      "helixterminator.app",
        Timeout:   60000,
    }

    mfaProvider.EXPECT().
        GenerateFIDO2Challenge(mock.Anything, user.ID).
        Return(expectedChallenge, nil)

    challenge, err :=
        svc.GenerateFIDO2Challenge(context.Background(),
            "usr_01J4KXYZ")

    require.NoError(t, err)
    assert.NotEmpty(t, challenge.Challenge)
    assert.Equal(t, "helixterminator.app", challenge.RPID)
}

func TestAuthService_FIDO2_Verify_Success(t *testing.T) {
    svc, userRepo, tokenStore, mfaProvider, auditLog :=
        newTestService(t)

    user := &domain.User{
        ID:      "usr_01J4KXYZ",
        Email:    "fido2-user@example.com",
        MFAEnabled: true,
        MFAType:  domain.MFAFIDO2,
    }

    userRepo.EXPECT().
        FindByID(mock.Anything, "usr_01J4KXYZ").
        Return(user, nil)

    mfaProvider.EXPECT().
        VerifyFIDO2Assertion(mock.Anything, user.ID,
            mock.AnythingOfType("*domain.FIDO2Assertion")).
        Return(true, nil)

    tokenStore.EXPECT().
        StoreRefreshToken(mock.Anything, mock.Anything).
        Return(nil)

    auditLog.EXPECT().
        RecordFIDO2Verified(mock.Anything, user.ID).
        Return(nil)
}

```



```

    result, err := svc.VerifyFIDO2(context.Background(),
        auth.FIDO2VerifyRequest{
            UserID:      "usr_01J4KXYZ",
            Assertion: &domain.FIDO2Assertion{ClientDataJSON:
                []byte("{}"), AuthenticatorData: []byte("auth")},
        })

    require.NoError(t, err)
    assert.NotEmpty(t, result.AccessToken)
    assert.False(t, result.MFARequired)
}

func TestAuthService_FIDO2_Verify_InvalidAssertion(t *testing.T) {
    svc, userRepo, _, mfaProvider, _ := newTestService(t)

    user := &domain.User{ID: "usr_01J4KXYZ", MFAType:
        domain.MFAFIDO2}

    userRepo.EXPECT().
        FindByID(mock.Anything, "usr_01J4KXYZ").
        Return(user, nil)

    mfaProvider.EXPECT().
        VerifyFIDO2Assertion(mock.Anything, user.ID,
            mock.Anything).
        Return(false, nil)

    _, err := svc.VerifyFIDO2(context.Background(),
        auth.FIDO2VerifyRequest{
            UserID:      "usr_01J4KXYZ",
            Assertion: &domain.FIDO2Assertion{},
        })

    require.Error(t, err)
    assert.ErrorIs(t, err, auth.ErrMFAFailed)
}

// -----
// TestAuthService_JWT
// -----

func TestAuthService_JWT_Issue(t *testing.T) {
    svc, _, _, _, _ := newTestService(t)

    token, err := svc.IssueAccessToken(context.Background(),
        "usr_01J4KXYZ", []string{"user", "vault:read"})

```

```

require.NoError(t, err)
assert.NotEmpty(t, token)
// Token must be parseable
claims, err := svc.ParseAccessToken(token)
require.NoError(t, err)
assert.Equal(t, "usr_01J4KXYZ", claims.Subject)
assert.Contains(t, claims.Scopes, "vault:read")
assert.True(t, claims.ExpiresAt.After(time.Now()))
}

func TestAuthService_JWT_Refresh(t *testing.T) {
    svc, userRepo, tokenStore, _, auditLog := newTestService(t)

    user := &domain.User{ID: "usr_01J4KXYZ", AccountLocked: false}
    storedToken := &domain.RefreshToken{
        ID:          "rt_abc123",
        UserID:      "usr_01J4KXYZ",
        ExpiresAt:   time.Now().Add(24 * time.Hour),
        Revoked:     false,
    }

    tokenStore.EXPECT().
        GetRefreshToken(mock.Anything, "rt_abc123").
        Return(storedToken, nil)

    userRepo.EXPECT().
        FindByID(mock.Anything, "usr_01J4KXYZ").
        Return(user, nil)

    tokenStore.EXPECT().
        RevokeRefreshToken(mock.Anything, "rt_abc123").
        Return(nil)

    tokenStore.EXPECT().
        StoreRefreshToken(mock.Anything, mock.Anything).
        Return(nil)

    auditLog.EXPECT().
        RecordTokenRefresh(mock.Anything, "usr_01J4KXYZ").
        Return(nil)

    result, err := svc.RefreshTokens(context.Background(),
        "rt_abc123")

```



```

validToken, err := svc.IssueAccessToken(context.Background(),
    "usr_01J4KXYZ", []string{"user"})
require.NoError(t, err)

// Tamper the signature
tamperedToken := validToken[:len(validToken)-5] + "XXXXX"

_, err = svc.ParseAccessToken(tamperedToken)
require.Error(t, err)
assert.ErrorIs(t, err, auth.ErrInvalidToken)
}

func TestAuthService_DeviceToken_Issue(t *testing.T) {
    svc, userRepo, tokenStore, _, _ := newTestService(t)

    user := &domain.User{ID: "usr_01J4KXYZ", AccountLocked: false}

    userRepo.EXPECT().
        FindByID(mock.Anything, "usr_01J4KXYZ").
        Return(user, nil)

    tokenStore.EXPECT().
        StoreDeviceToken(mock.Anything, mock.MatchedBy(func(dt
            *domain.DeviceToken) bool {
                return dt.UserID == "usr_01J4KXYZ" && dt.DeviceID ==
                "dev_ios_001"
            }))).
        Return(nil)

    token, err := svc.IssueDeviceToken(context.Background(),
        auth.DeviceTokenRequest{
            UserID:    "usr_01J4KXYZ",
            DeviceID:  "dev_ios_001",
            Platform:  "ios",
            PublicKey: "MFkwEwYHKoZIzj0CAQYIKoZIzj0DAQcDQgAE...",
        })
    require.NoError(t, err)
    assert.NotEmpty(t, token.Token)
    assert.Equal(t, "dev_ios_001", token.DeviceID)
}

```

2.3 Vault Service Unit Tests

```
// services/vault/service_test.go
package vault_test

import (
    "context"
    "crypto/rand"
    "testing"

    "github.com/HelixDevelopment/helixterminator/services/vault"
    "github.com/HelixDevelopment/helixterminator/services/vault/mocks"
    "github.com/HelixDevelopment/helixterminator/pkg/domain"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/mock"
    "github.com/stretchr/testify/require"
)

func newVaultTestService(t *testing.T) (
    *vault.Service,
    *mocks.MockVaultRepository,
    *mocks.MockKeyProvider,
    *mocks.MockShareRepository,
) {
    t.Helper()
    vaultRepo := mocks.NewMockVaultRepository(t)
    keyProvider := mocks.NewMockKeyProvider(t)
    shareRepo := mocks.NewMockShareRepository(t)
    svc := vault.NewService(vault.Config{
        EncryptionKeySize: 32,
        Algorithm:         "AES-256-GCM",
    }, vaultRepo, keyProvider, shareRepo)
    return svc, vaultRepo, keyProvider, shareRepo
}

func TestVaultService_Create_Personal(t *testing.T) {
    svc, vaultRepo, keyProvider, _ := newVaultTestService(t)

    masterKey := make([]byte, 32)
    _, _ = rand.Read(masterKey)

    keyProvider.EXPECT().
        GetMasterKey(mock.Anything, "usr_01J4KXYZ").
```

```

        Return(masterKey, nil)

vaultRepo.EXPECT().
    Create(mock.Anything, mock.MatchedBy(func(v
        *domain.Vault) bool {
            return v.OwnerID == "usr_01J4KXYZ" &&
                v.Type == domain.VaultPersonal &&
                v.Name == "Personal Vault"
        })).
    Return("vlt_abc123", nil)

id, err := svc.CreateVault(context.Background(),
    vault.CreateVaultRequest{
        OwnerID: "usr_01J4KXYZ",
        Name:     "Personal Vault",
        Type:     domain.VaultPersonal,
    })

require.NoError(t, err)
assert.Equal(t, "vlt_abc123", id)
}

func TestVaultService_Create_Team(t *testing.T) {
    svc, vaultRepo, keyProvider, _ := newVaultTestService(t)

    teamKey := make([]byte, 32)
    _, _ = rand.Read(teamKey)

    keyProvider.EXPECT().
        GetTeamKey(mock.Anything, "team_xyz789").
        Return(teamKey, nil)

    vaultRepo.EXPECT().
        Create(mock.Anything, mock.MatchedBy(func(v
            *domain.Vault) bool {
                return v.TeamID == "team_xyz789" && v.Type ==
                    domain.VaultTeam
            })).
        Return("vlt_team_001", nil)

    id, err := svc.CreateVault(context.Background(),
        vault.CreateVaultRequest{
            TeamID: "team_xyz789",
            Name:    "Engineering Vault",
            Type:   domain.VaultTeam,
        })

```

```

    require.NoError(t, err)
    assert.Equal(t, "vlt_team_001", id)
}

func TestVaultService_Encrypt_AES256GCM(t *testing.T) {
    svc, _, _, _ := newVaultTestService(t)

    plaintext := []byte(`{"host": "prod-server-01", "username":
        "deploy", "password": "s3cr3t"}`)
    key := make([]byte, 32)
    _, _ = rand.Read(key)

    ciphertext, err := svc.Encrypt(plaintext, key)

    require.NoError(t, err)
    assert.NotEqual(t, plaintext, ciphertext)
    assert.Greater(t, len(ciphertext), len(plaintext),
        "ciphertext includes nonce + tag overhead")
}

func TestVaultService_Decrypt_AES256GCM(t *testing.T) {
    svc, _, _, _ := newVaultTestService(t)

    plaintext := []byte(`{"host": "prod-server-01", "username":
        "deploy", "password": "s3cr3t"}`)
    key := make([]byte, 32)
    _, _ = rand.Read(key)

    ciphertext, err := svc.Encrypt(plaintext, key)
    require.NoError(t, err)

    decrypted, err := svc.Decrypt(ciphertext, key)
    require.NoError(t, err)
    assert.Equal(t, plaintext, decrypted)
}

func TestVaultService_Decrypt_WrongKey_Fails(t *testing.T) {
    svc, _, _, _ := newVaultTestService(t)

    plaintext := []byte("sensitive credential data")
    key1 := make([]byte, 32)
    key2 := make([]byte, 32)
    _, _ = rand.Read(key1)
    _, _ = rand.Read(key2)

```

```

    ciphertext, err := svc.Encrypt(plaintext, key1)
    require.NoError(t, err)

    _, err = svc.Decrypt(ciphertext, key2)
    require.Error(t, err)
    assert.ErrorIs(t, err, vault.ErrDecryptionFailed)
}

func TestVaultService_Decrypt_TamperedCiphertext_Fails(t
    *testing.T) {
    svc, _, _, _ := newVaultTestService(t)

    plaintext := []byte("sensitive credential data")
    key := make([]byte, 32)
    _, _ = rand.Read(key)

    ciphertext, err := svc.Encrypt(plaintext, key)
    require.NoError(t, err)

    // Tamper the ciphertext
    ciphertext[len(ciphertext)-1] ^= 0xFF

    _, err = svc.Decrypt(ciphertext, key)
    require.Error(t, err,
        "GCM authentication tag check must catch tampering")
    assert.ErrorIs(t, err, vault.ErrDecryptionFailed)
}

func TestVaultService_Share_WithUser(t *testing.T) {
    svc, vaultRepo, keyProvider, shareRepo :=
        newVaultTestService(t)

    ownerKey := make([]byte, 32)
    recipientPubKey := make([]byte, 32)
    _, _ = rand.Read(ownerKey)
    _, _ = rand.Read(recipientPubKey)

    vaultRepo.EXPECT().
        FindByID(mock.Anything, "vlt_abc123").
        Return(&domain.Vault{
            ID: "vlt_abc123",
            OwnerID: "usr_owner",
        }, nil)
}

```



```

keyProvider.EXPECT().
    GetMasterKey(mock.Anything, "usr_owner").
    Return(ownerKey, nil)

keyProvider.EXPECT().
    GetPublicKey(mock.Anything, "usr_recipient").
    Return(recipientPubKey, nil)

shareRepo.EXPECT().
    CreateShare(mock.Anything, mock.MatchedBy(func(s
        *domain.VaultShare) bool {
            return s.VaultID == "vlt_abc123" &&
                s.RecipientID == "usr_recipient" &&
                s.Permission == domain.PermissionReadOnly
        })).
    Return(nil)

err := svc.ShareVault(context.Background(),
    vault.ShareRequest{
        VaultID:      "vlt_abc123",
        OwnerID:       "usr_owner",
        RecipientID:  "usr_recipient",
        Permission:    domain.PermissionReadOnly,
    })

require.NoError(t, err)
}

func TestVaultService_Permission_ReadOnly_BlocksWrite(t
    *testing.T) {
    svc, vaultRepo, _, shareRepo := newVaultTestService(t)

    shareRepo.EXPECT().
        GetShareForUser(mock.Anything, "vlt_abc123",
            "usr_reader").
        Return(&domain.VaultShare{
            Permission: domain.PermissionReadOnly,
        }, nil)

    vaultRepo.EXPECT().
        FindByID(mock.Anything, "vlt_abc123").
        Return(&domain.Vault{ID: "vlt_abc123"}, nil)

    err := svc.AddEntry(context.Background(),
        vault.AddEntryRequest{
            VaultID: "vlt_abc123",

```

```

        ActorID: "usr_reader",
        Entry:    &domain.VaultEntry{Name: "new entry"},
    })

    require.Error(t, err)
    assert.ErrorIs(t, err, vault.ErrPermissionDenied)
}

func TestVaultService_Sync_MultiDevice(t *testing.T) {
    svc, vaultRepo, keyProvider, _ := newVaultTestService(t)

    deviceKey := make([]byte, 32)
    _, _ = rand.Read(deviceKey)

    expectedEntries := []*domain.VaultEntry{
        {ID: "ent_001", Name: "Server 1"},
        {ID: "ent_002", Name: "Server 2"},
        {ID: "ent_003", Name: "Server 3"},
    }

    vaultRepo.EXPECT().
        FindByOwner(mock.Anything, "usr_01J4KXYZ").
        Return([]*domain.Vault{{ID: "vlt_abc123", OwnerID:
            "usr_01J4KXYZ"}}, nil)

    vaultRepo.EXPECT().
        GetEntriesSince(mock.Anything, "vlt_abc123",
            mock.AnythingOfType("time.Time")).
        Return(expectedEntries, nil)

    keyProvider.EXPECT().
        GetDeviceKey(mock.Anything, "usr_01J4KXYZ",
            "dev_desktop_001").
        Return(deviceKey, nil)

    result, err := svc.SyncForDevice(context.Background(),
        vault.SyncRequest{
            UserID:      "usr_01J4KXYZ",
            DeviceID:    "dev_desktop_001",
            LastSyncedAt: "2026-01-01T00:00:00Z",
        })

    require.NoError(t, err)
    assert.Len(t, result.Entries, 3)
    // Each entry must be re-encrypted with device key
    for _, entry := range result.Entries {

```

```

        assert.NotEmpty(t, entry.EncryptedData)
    }
}

func TestVaultService_Conflict_Resolution_LastWriteWins(t
    *testing.T) {
    svc, vaultRepo, keyProvider, _ := newVaultTestService(t)

    masterKey := make([]byte, 32)
    _, _ = rand.Read(masterKey)

    keyProvider.EXPECT().
        GetMasterKey(mock.Anything, "usr_01J4KXYZ").
        Return(masterKey, nil)

    // Simulating two concurrent updates to the same entry
    conflictingUpdate := &vault.UpdateEntryRequest{
        VaultID:    "vlt_abc123",
        EntryID:    "ent_001",
        ActorID:    "usr_01J4KXYZ",
        DeviceID:   "dev_mobile_001",
        UpdatedAt:  "2026-06-28T10:00:00Z",
        FieldPatch: map[string]interface{}{"username": "new-
            user"},
    }

    vaultRepo.EXPECT().
        GetEntry(mock.Anything, "ent_001").
        Return(&domain.VaultEntry{
            ID:         "ent_001",
            UpdatedAt:  "2026-06-28T10:00:05Z", // Server version
            is newer
        }, nil)

    vaultRepo.EXPECT().
        CreateConflictVersion(mock.Anything,
            mock.AnythingOfType("*domain.VaultEntry")).
        Return(nil)

    err := svc.UpdateEntry(context.Background(),
        conflictingUpdate)

    require.Error(t, err)
    assert.ErrorIs(t, err, vault.ErrConflict)
}

```

2.4 SSH Proxy Service Unit Tests

```
// services/sshproxy/service_test.go
package sshproxy_test

import (
    "context"
    "net"
    "testing"
    "time"

    "github.com/HelixDevelopment/helixterminator/services/sshproxy"
    "github.com/HelixDevelopment/helixterminator/services/sshproxy/mocks"
    "github.com/HelixDevelopment/helixterminator/pkg/domain"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/mock"
    "github.com/stretchr/testify/require"
    gossh "golang.org/x/crypto/ssh"
)

func newSSHProxyService(t *testing.T) (
    *sshproxy.Service,
    *mocks.MockSessionStore,
    *mocks.MockHostRepository,
    *mocks.MockAuditEmitter,
) {
    t.Helper()
    sessionStore := mocks.NewMockSessionStore(t)
    hostRepo := mocks.NewMockHostRepository(t)
    auditEmitter := mocks.NewMockAuditEmitter(t)
    svc := sshproxy.NewService(sshproxy.Config{
        ConnectTimeout: 30 * time.Second,
        MaxSessionsUser: 10,
        KeepaliveInterval: 60 * time.Second,
    }, sessionStore, hostRepo, auditEmitter)
    return svc, sessionStore, hostRepo, auditEmitter
}

func TestSSHProxy_Connect_PasswordAuth(t *testing.T) {
    svc, sessionStore, hostRepo, auditEmitter :=
        newSSHProxyService(t)

    host := &domain.Host{
```

```

        ID:          "host_001",
        Hostname:    "192.168.1.100",
        Port:        22,
        AuthType:    domain.AuthPassword,
        Fingerprint: "SHA256:abc123def456",
    }

    hostRepo.EXPECT().
        FindByID(mock.Anything, "host_001").
        Return(host, nil)

    sessionStore.EXPECT().
        Create(mock.Anything, mock.MatchedBy(func(s
            *domain.Session) bool {
                return s.HostID == "host_001" &&
                    s.UserID == "usr_01J4KXYZ" &&
                    s.AuthMethod == "password"
            })).
        Return("sess_xyz789", nil)

    auditEmitter.EXPECT().
        EmitSessionStart(mock.Anything,
            mock.AnythingOfType("*domain.Session")).
        Return(nil)

    // Note: actual SSH dialing is mocked at the dialer level in
    // unit tests
    // Full SSH dial tests happen in integration tests against a
    // real SSH server
    _ = svc
}

func TestSSHProxy_Connect_KeyAuth_Ed25519(t *testing.T) {
    // Generate a real Ed25519 key pair for the test
    pubKey, privKey, err := sshproxy.GenerateEd25519KeyPair()
    require.NoError(t, err)
    assert.NotNil(t, pubKey)
    assert.NotNil(t, privKey)

    _, sessionStore, hostRepo, auditEmitter :=
        newSSHProxyService(t)

    host := &domain.Host{
        ID:          "host_002",
        Hostname:    "10.0.0.5",
        Port:        22,
    }

```

```

        AuthType:    domain.AuthPublicKey,
        Fingerprint: "SHA256:xyz789abc123",
    }

    hostRepo.EXPECT().
        FindByID(mock.Anything, "host_002").
        Return(host, nil)

    sessionStore.EXPECT().
        Create(mock.Anything, mock.MatchedBy(func(s
            *domain.Session) bool {
                return s.AuthMethod == "publickey" && s.KeyType ==
                "ed25519"
            })).
        Return("sess_ed25519_001", nil)

    auditEmitter.EXPECT().
        EmitSessionStart(mock.Anything, mock.Anything).
        Return(nil)
}

func TestSSHProxy_Connect_HostKeyMismatch(t *testing.T) {
    svc, _, hostRepo, auditEmitter := newSSHProxyService(t)

    host := &domain.Host{
        ID:            "host_003",
        Hostname:      "10.0.0.6",
        Port:          22,
        AuthType:      domain.AuthPassword,
        Fingerprint:   "SHA256:known-fingerprint-stored-in-db",
    }

    hostRepo.EXPECT().
        FindByID(mock.Anything, "host_003").
        Return(host, nil)

    // Simulate the SSH client receiving a different host key
    actualFingerprint := "SHA256:different-fingerprint-mitm-
        attack"

    auditEmitter.EXPECT().
        EmitHostKeyMismatch(mock.Anything, "host_003",
            "SHA256:known-fingerprint-stored-in-db",
            actualFingerprint).
        Return(nil)
}

```

```

    err := svc.CheckHostKey(context.Background(), "host_003",
        actualFingerprint)

    require.Error(t, err)
    assert.ErrorIs(t, err, sshproxy.ErrHostKeyMismatch)
}

func TestSSHProxy_Connect_Timeout(t *testing.T) {
    svc, _, hostRepo, _ := newSSHProxyService(t)

    hostRepo.EXPECT().
        FindByID(mock.Anything, "host_timeout").
        Return(&domain.Host{
            ID:        "host_timeout",
            Hostname:  "10.255.255.1", // unreachable
            Port:     22,
        }, nil)

    ctx, cancel := context.WithTimeout(context.Background(),
        100*time.Millisecond)
    defer cancel()

    _, err := svc.Connect(ctx, sshproxy.ConnectRequest{
        HostID:    "host_timeout",
        UserID:    "usr_01J4KXYZ",
        AuthType:  domain.AuthPassword,
        Password:  "pass",
    })

    require.Error(t, err)
    assert.ErrorIs(t, err, context.DeadlineExceeded)
}

func TestSSHProxy_Connect_JumpHost_Chain(t *testing.T) {
    _, _, hostRepo, _ := newSSHProxyService(t)

    // Jump chain: client → bastion-1 → bastion-2 → target
    bastion1 := &domain.Host{ID: "bastion1", Hostname: "bastion-
        eu.example.com", Port: 22}
    bastion2 := &domain.Host{ID: "bastion2", Hostname: "bastion-
        internal.example.com", Port: 22}
    target := &domain.Host{ID: "target", Hostname: "prod-
        db-01.internal", Port: 22}

    hostRepo.EXPECT().FindByID(mock.Anything,
        "bastion1").Return(bastion1, nil)

```

```

hostRepo.EXPECT().FindByID(mock.Anything,
    "bastion2").Return(bastion2, nil)
hostRepo.EXPECT().FindByID(mock.Anything,
    "target").Return(target, nil)

chain, err := sshproxy.BuildJumpChain(context.Background(),
    hostRepo,
    []string{"bastion1", "bastion2"}, "target")

require.NoError(t, err)
assert.Len(t, chain.Hops, 2)
assert.Equal(t, "target", chain.Terminal.ID)
assert.Equal(t, "bastion1", chain.Hops[0].ID)
assert.Equal(t, "bastion2", chain.Hops[1].ID)
}

func TestSSHProxy_PortForward_Local(t *testing.T) {
    _, sessionStore, _, auditEmitter := newSSHProxyService(t)

    sessionStore.EXPECT().
        FindByID(mock.Anything, "sess_xyz789").
        Return(&domain.Session{
            ID:      "sess_xyz789",
            UserID:  "usr_01J4KXYZ",
            HostID:  "host_001",
            Active:  true,
        }, nil)

    auditEmitter.EXPECT().
        EmitPortForwardStart(mock.Anything,
            mock.MatchedBy(func(pf *domain.PortForward) bool {
                return pf.Type == domain.PortForwardLocal &&
                    pf.LocalPort == 5432 &&
                    pf.RemoteHost == "db.internal" &&
                    pf.RemotePort == 5432
            }))).
        Return(nil)

    pf, err :=
        sshproxy.ConfigureLocalForward(context.Background(),
            sessionStore, auditEmitter, sshproxy.PortForwardRequest{
                SessionID: "sess_xyz789",
                LocalPort:  5432,
                RemoteHost:  "db.internal",
                RemotePort:  5432,
            })
}

```



```

require.NoError(t, err)
assert.NotNil(t, pf)
assert.Equal(t, domain.PortForwardLocal, pf.Type)
}

func TestSSHProxy_Session_Reconnect_ResumesAfterNetworkDrop(t
    *testing.T) {
    _, sessionStore, hostRepo, auditEmitter :=
        newSSHProxyService(t)

    existingSession := &domain.Session{
        ID:            "sess_xyz789",
        UserID:        "usr_01J4KXYZ",
        HostID:        "host_001",
        Active:        false, // dropped
        TerminalState: &domain.TerminalState{Buffer:
            []byte("previous output")},
    }

    sessionStore.EXPECT().
        FindByID(mock.Anything, "sess_xyz789").
        Return(existingSession, nil)

    hostRepo.EXPECT().
        FindByID(mock.Anything, "host_001").
        Return(&domain.Host{ID: "host_001"}, nil)

    sessionStore.EXPECT().
        UpdateStatus(mock.Anything, "sess_xyz789",
            domain.SessionReconnecting).
        Return(nil)

    auditEmitter.EXPECT().
        EmitSessionReconnect(mock.Anything, "sess_xyz789").
        Return(nil)

    reconnected, err :=
        sshproxy.AttemptReconnect(context.Background(),
            sessionStore, hostRepo, auditEmitter, "sess_xyz789")
    require.NoError(t, err)
    assert.NotNil(t, reconnected.TerminalState)
    assert.Equal(t, []byte("previous output"),
        reconnected.TerminalState.Buffer,
        "terminal buffer must be restored on reconnect")
}

```

```
// Benchmark for SSH key type checking performance
func BenchmarkSSHProxy_HostKeyVerification(b *testing.B) {
    svc := &sshproxy.KeyVerifier{}
    _, pubKey, _ := gossh.GenerateKey(rand.Reader)
    fp := gossh.FingerprintSHA256(pubKey)
    storedFP := fp // matching fingerprint

    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _ = svc.Verify(fp, storedFP)
    }
}
```

2.5 Host Service Unit Tests

```
// services/host/service_test.go
package host_test

import (
    "context"
    "testing"

    "github.com/HelixDevelopment/helixtermininator/services/host"
    "github.com/HelixDevelopment/helixterminator/services/host/
        mocks"
    "github.com/HelixDevelopment/helixterminator/pkg/domain"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/mock"
    "github.com/stretchr/testify/require"
)

// -----
// CRUD tests
// -----

func TestHostService_Create_Success(t *testing.T) {
    hostRepo := mocks.NewMockHostRepository(t)
    tagRepo := mocks.NewMockTagRepository(t)
    svc := host.NewService(hostRepo, tagRepo)

    hostRepo.EXPECT().
        Create(mock.Anything, mock.MatchedBy(func(h *domain.Host)
            bool {
                return h.Hostname == "prod-web-01.example.com" &&
                h.Port == 22
            }
        ))
}
```

```

    })).
    Return("host_new_001", nil)

id, err := svc.CreateHost(context.Background(),
    host.CreateHostRequest{
        OwnerID:      "usr_01J4KXYZ",
        Hostname:     "prod-web-01.example.com",
        Port:         22,
        Username:     "ubuntu",
        DisplayName:  "Production Web Server 01",
        Tags:         []string{"production", "web"},
    })

require.NoError(t, err)
assert.Equal(t, "host_new_001", id)
}

func TestHostService_Create_DuplicateHostname_SameOwner_Fails(t
    *testing.T) {
    hostRepo := mocks.NewMockHostRepository(t)
    tagRepo := mocks.NewMockTagRepository(t)
    svc := host.NewService(hostRepo, tagRepo)

    hostRepo.EXPECT().
        FindByHostnameAndOwner(mock.Anything, "prod-
            web-01.example.com", "usr_01J4KXYZ").
        Return(&domain.Host{ID: "existing_host"}, nil)

    _, err := svc.CreateHost(context.Background(),
        host.CreateHostRequest{
            OwnerID:  "usr_01J4KXYZ",
            Hostname: "prod-web-01.example.com",
            Port:    22,
        })

    require.Error(t, err)
    assert.ErrorIs(t, err, host.ErrDuplicateHost)
}

func TestHostService_Update_NonOwner_Fails(t *testing.T) {
    hostRepo := mocks.NewMockHostRepository(t)
    tagRepo := mocks.NewMockTagRepository(t)
    svc := host.NewService(hostRepo, tagRepo)

    hostRepo.EXPECT().
        FindByID(mock.Anything, "host_001").

```

```

        Return(&domain.Host{ID: "host_001", OwnerID:
            "usr_real_owner"}, nil)

err := svc.UpdateHost(context.Background(),
    host.UpdateHostRequest{
        HostID:      "host_001",
        ActorID:     "usr_attacker",
        DisplayName: "Hacked Name",
    })

require.Error(t, err)
assert.ErrorIs(t, err, host.ErrPermissionDenied)
}

func TestHostService_GroupHierarchy_Inheritance(t *testing.T) {
    hostRepo := mocks.NewMockHostRepository(t)
    tagRepo := mocks.NewMockTagRepository(t)
    svc := host.NewService(hostRepo, tagRepo)

    // Group hierarchy: Production → Web Servers → prod-web-01
    parentGroup := &domain.HostGroup{
        ID:      "grp_production",
        Name:    "Production",
        Config: &domain.HostConfig{Username: "ec2-user", Port:
            22},
    }
    childGroup := &domain.HostGroup{
        ID:      "grp_web",
        Name:    "Web Servers",
        ParentID: "grp_production",
        Config:  &domain.HostConfig{}, // no overrides at this
            level
    }
    targetHost := &domain.Host{
        ID:      "host_001",
        GroupID: "grp_web",
        Config:  nil, // should inherit
    }

    hostRepo.EXPECT().FindByID(mock.Anything,
        "host_001").Return(targetHost, nil)
    hostRepo.EXPECT().FindGroupByID(mock.Anything,
        "grp_web").Return(childGroup, nil)
    hostRepo.EXPECT().FindGroupByID(mock.Anything,
        "grp_production").Return(parentGroup, nil)

```

```

resolvedConfig, err :=
    svc.ResolveHostConfig(context.Background(), "host_001")
require.NoError(t, err)
assert.Equal(t, "ec2-user", resolvedConfig.Username, "must
    inherit username from grandparent group")
assert.Equal(t, 22, resolvedConfig.Port)
}

```

```

func TestHostService_Search_ByTagAndStatus(t *testing.T) {
    tests := []struct {
        name          string
        tags          []string
        status        string
        expectedCount int
    }{
        {"production_active", []string{"production"}, "active",
            5},
        {"web_production", []string{"production", "web"},
            "active", 2},
        {"no_match", []string{"nonexistent-tag"}, "active", 0},
        {"all_active_no_tags", []string{}, "active", 12},
        {"inactive_only", []string{}, "inactive", 3},
    }

    for _, tt := range tests {
        t.Run(tt.name, func(t *testing.T) {
            hostRepo := mocks.NewMockHostRepository(t)
            svc := host.NewService(hostRepo,
                mocks.NewMockTagRepository(t))

            results := make([]*domain.Host, tt.expectedCount)
            hostRepo.EXPECT().
                Search(mock.Anything, mock.MatchedBy(func(q
                    *domain.HostSearchQuery) bool {
                    return q.Status == tt.status
                })).
                Return(results, nil)

            found, err := svc.SearchHosts(context.Background(),
                host.SearchRequest{
                    OwnerID: "usr_01J4KXYZ",
                    Tags:    tt.tags,
                    Status:  tt.status,
                })

            require.NoError(t, err)
            assert.Len(t, found, tt.expectedCount)
        })
    }
}

```

```

    })
  }
}

```

2.6 Keychain Service Unit Tests

```

// services/keychain/service_test.go
package keychain_test

import (
    "context"
    "crypto/ed25519"
    "crypto/rand"
    "testing"

    "github.com/HelixDevelopment/helixterminator/services/
        keychain"
    "github.com/HelixDevelopment/helixterminator/services/
        keychain/mocks"
    "github.com/HelixDevelopment/helixterminator/pkg/domain"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/mock"
    "github.com/stretchr/testify/require"
)

func TestKeychainService_StoreKey_Ed25519(t *testing.T) {
    keyRepo := mocks.NewMockKeyRepository(t)
    encryptor := mocks.NewMockKeyEncryptor(t)
    svc := keychain.NewService(keyRepo, encryptor)

    pubKey, privKey, err := ed25519.GenerateKey(rand.Reader)
    require.NoError(t, err)

    encryptedPrivKey := []byte("encrypted-private-key-bytes")
    encryptor.EXPECT().
        EncryptPrivateKey(mock.Anything, privKey, "usr_01J4KXYZ").
        Return(encryptedPrivKey, nil)

    keyRepo.EXPECT().
        Store(mock.Anything, mock.MatchedBy(func(k
            *domain.SSHKey) bool {
                return k.OwnerID == "usr_01J4KXYZ" &&
                    k.KeyType == "ed25519" &&
                    k.PublicKeyData != nil
            }))).

```

```

        Return("key_ed25519_001", nil)

id, err := svc.StoreKey(context.Background(),
    keychain.StoreKeyRequest{
        OwnerID:      "usr_01J4KXYZ",
        PrivateKey:    privKey,
        PublicKey:     pubKey,
        Name:          "Personal Ed25519 Key",
        Comment:       "alice@workstation",
    })

require.NoError(t, err)
assert.Equal(t, "key_ed25519_001", id)
}

func TestKeychainService_RetrieveKey_WrongOwner_Fails(t
    *testing.T) {
    keyRepo := mocks.NewMockKeyRepository(t)
    svc := keychain.NewService(keyRepo,
        mocks.NewMockKeyEncryptor(t))

    keyRepo.EXPECT().
        FindByID(mock.Anything, "key_001").
        Return(&domain.SSHKey{
            ID:          "key_001",
            OwnerID:     "usr_real_owner",
        }, nil)

    _, err := svc.RetrieveKey(context.Background(),
        keychain.RetrieveKeyRequest{
            ActorID: "usr_attacker",
            KeyID:   "key_001",
        })

    require.Error(t, err)
    assert.ErrorIs(t, err, keychain.ErrPermissionDenied)
}

func TestKeychainService_FIDO2Key_Registration(t *testing.T) {
    keyRepo := mocks.NewMockKeyRepository(t)
    encryptor := mocks.NewMockKeyEncryptor(t)
    svc := keychain.NewService(keyRepo, encryptor)

    credential := &domain.FIDO2Credential{
        CredentialID: []byte("credential-id-bytes"),
        PublicKey:    []byte("cose-encoded-public-key"),
    }

```

```

        AAGUID:      []byte("aaguid-bytes"),
        Counter:    0,
    }

    keyRepo.EXPECT().
        StoreFIDO2Credential(mock.Anything, mock.MatchedBy(func(c
            *domain.FIDO2Credential) bool {
                return c.OwnerID == "usr_01J4KXYZ"
            })).
        Return("fido2_cred_001", nil)

    id, err := svc.RegisterFIDO2Credential(context.Background(),
        keychain.RegisterFIDO2Request{
            OwnerID:      "usr_01J4KXYZ",
            Credential:    credential,
            DeviceName:    "YubiKey 5C NFC",
        })

    require.NoError(t, err)
    assert.Equal(t, "fido2_cred_001", id)
}

func TestKeychainService_PassphraseProtected_Key(t *testing.T) {
    keyRepo := mocks.NewMockKeyRepository(t)
    encryptor := mocks.NewMockKeyEncryptor(t)
    svc := keychain.NewService(keyRepo, encryptor)

    _, privKey, _ := ed25519.GenerateKey(rand.Reader)
    passphrase := "my-super-secret-passphrase-2026!"
    encryptedKey := []byte("passphrase-encrypted-key")

    encryptor.EXPECT().
        EncryptWithPassphrase(mock.Anything, privKey, passphrase).
        Return(encryptedKey, nil)

    keyRepo.EXPECT().
        Store(mock.Anything, mock.MatchedBy(func(k
            *domain.SSHKey) bool {
                return k.PassphraseProtected == true
            })).
        Return("key_pp_001", nil)

    id, err := svc.StoreKeyWithPassphrase(context.Background(),
        keychain.StoreKeyWithPassphraseRequest{
            OwnerID:      "usr_01J4KXYZ",
            PrivateKey:    privKey,

```



```

        Passphrase: passphrase,
        Name:         "Passphrase Protected Key",
    })

    require.NoError(t, err)
    assert.Equal(t, "key_pp_001", id)
}

```

2.7 Go Benchmark Tests

```

// services/vault/bench_test.go
package vault_test

import (
    "crypto/rand"
    "testing"

    "github.com/HelixDevelopment/helixterminator/services/vault"
)

func BenchmarkVault_Encrypt_AES256GCM_1KB(b *testing.B) {
    svc := vault.NewBenchmarkService()
    key := make([]byte, 32)
    _, _ = rand.Read(key)
    plaintext := make([]byte, 1024) // 1KB
    _, _ = rand.Read(plaintext)

    b.ResetTimer()
    b.SetBytes(int64(len(plaintext)))
    for i := 0; i < b.N; i++ {
        _, _ = svc.Encrypt(plaintext, key)
    }
}

func BenchmarkVault_Encrypt_AES256GCM_1MB(b *testing.B) {
    svc := vault.NewBenchmarkService()
    key := make([]byte, 32)
    _, _ = rand.Read(key)
    plaintext := make([]byte, 1024*1024) // 1MB
    _, _ = rand.Read(plaintext)

    b.ResetTimer()
    b.SetBytes(int64(len(plaintext)))
    for i := 0; i < b.N; i++ {

```

```

        _, _ = svc.Encrypt(plaintext, key)
    }
}

func BenchmarkVault_Decrypt_AES256GCM_1KB(b *testing.B) {
    svc := vault.NewBenchmarkService()
    key := make([]byte, 32)
    _, _ = rand.Read(key)
    plaintext := make([]byte, 1024)
    _, _ = rand.Read(plaintext)
    ciphertext, _ := svc.Encrypt(plaintext, key)

    b.ResetTimer()
    b.SetBytes(int64(len(plaintext)))
    for i := 0; i < b.N; i++ {
        _, _ = svc.Decrypt(ciphertext, key)
    }
}

```

// services/auth/bench_test.go

package auth_test

```

import (
    "context"
    "testing"

    "github.com/HelixDevelopment/helixterminator/services/auth"
)

```

```

func BenchmarkAuth_JWT_Issue(b *testing.B) {
    svc := auth.NewBenchmarkService()
    ctx := context.Background()

    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _, _ = svc.IssueAccessToken(ctx, "usr_bench_001",
            []string{"user", "vault:read", "ssh:connect"})
    }
}

```

```

func BenchmarkAuth_JWT_Parse(b *testing.B) {
    svc := auth.NewBenchmarkService()
    token, _ := svc.IssueAccessToken(context.Background(),
        "usr_bench_001", []string{"user"})
}

```

```

    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _, _ = svc.ParseAccessToken(token)
    }
}

func BenchmarkAuth_BcryptVerify(b *testing.B) {
    svc := auth.NewBenchmarkService()
    hash := svc.HashPassword("test-password-benchmark-123!")

    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _ = svc.VerifyPassword("test-password-benchmark-123!",
            hash)
    }
}

```

2.8 Property-Based Tests (Fuzzing)

```

// services/vault/fuzz_test.go
package vault_test

import (
    "testing"

    "github.com/HelixDevelopment/helixterminator/services/vault"
)

// FuzzVaultEncryptDecrypt verifies that any plaintext encrypted
// then decrypted
// returns the original plaintext – no matter the content.
func FuzzVaultEncryptDecrypt(f *testing.F) {
    svc := vault.NewBenchmarkService()

    // Seed corpus
    f.Add([]byte("hello world"))
    f.Add([]byte(""))
    f.Add([]byte("\x00\x01\x02\x03"))
    f.Add([]byte("特殊文字テスト"))
    f.Add(make([]byte, 65536)) // 64KB

    f.Fuzz(func(t *testing.T, plaintext []byte) {
        key := make([]byte, 32)
        // Use deterministic key for reproducibility in corpus
        // minimization
    })
}

```

```

    for i := range key {
        key[i] = byte(i)
    }

    ciphertext, err := svc.Encrypt(plaintext, key)
    if err != nil {
        t.Skip() // Some inputs may be legitimately rejected
    }

    decrypted, err := svc.Decrypt(ciphertext, key)
    if err != nil {
        t.Fatalf("Decrypt failed on ciphertext produced by
Encrypt: %v", err)
    }

    if len(plaintext) != len(decrypted) {
        t.Fatalf("Length mismatch: got %d, want %d",
len(decrypted), len(plaintext))
    }

    for i := range plaintext {
        if plaintext[i] != decrypted[i] {
            t.Fatalf("Byte mismatch at position %d", i)
        }
    }
})
}

// FuzzJWTRoundtrip verifies JWT issue/parse round-trip for any
// user ID
func FuzzJWTRoundtrip(f *testing.F) {
    svc := auth.NewBenchmarkService()

    f.Add("usr_normal")
    f.Add("")
    f.Add("usr_with_special_chars_!@#$")
    f.Add("very-long-user-id-" + strings.Repeat("x", 1000))

    f.Fuzz(func(t *testing.T, userID string) {
        token, err := svc.IssueAccessToken(context.Background(),
userID, []string{"user"})
        if err != nil {
            t.Skip()
        }
        claims, err := svc.ParseAccessToken(token)
        if err != nil {

```

```

        t.Fatalf("Parse failed on token issued by
IssueAccessToken: %v", err)
    }
    if claims.Subject != userID {
        t.Fatalf("Subject mismatch: got %q, want %q",
claims.Subject, userID)
    }
})
}

```

3. Backend Integration Tests

3.1 Integration Test Infrastructure

Integration tests use `testcontainers-go` to spin up real dependency containers. This eliminates test doubles at the infrastructure boundary and catches real serialization, schema, and protocol issues.

3.1.1 Container Configuration

```

// testinfra/containers.go
package testinfra

import (
    "context"
    "fmt"
    "testing"
    "time"

    "github.com/testcontainers/testcontainers-go"
    "github.com/testcontainers/testcontainers-go/modules/kafka"
    "github.com/testcontainers/testcontainers-go/modules/postgres"
    "github.com/testcontainers/testcontainers-go/modules/rabbitmq"
    "github.com/testcontainers/testcontainers-go/modules/redis"
    "github.com/testcontainers/testcontainers-go/wait"
)

// Pinned image digests – must match submodules-catalogue.md
const (
    PostgresImage = "postgres:17.2-alpine3.20@sha256:a2282ad0db623c27f03bab803975c9e2f7eb50f33eb0db9db29abe74"
    RedisImage    = "redis:8.0.1-alpine3.20@sha256:3134997edb04277814aa51a4175a588d45eb4299272f8eff2307bbf8"
)

```

```

KafkaImage      = "confluentinc/cp-
    kafka:7.9.0@sha256:abcdef1234567890abcdef1234567890abcdef1234567890abcdef1234567890abcdef1234567890"
RabbitMQImage   = "rabbitmq:3.13.3-management-
    alpine@sha256:fedcba0987654321fedcba0987654321fedcba0987654321fedcba0987654321fedcba0987654321"
OpenSSHImage    = "linuxserver/openssh-
    server:9.9_p2@sha256:1234abcd5678efgh1234abcd5678efgh1234abcd5678efgh1234abcd5678efgh1234abcd5678efgh"
)

// TestPostgres starts a PostgreSQL container and returns the DSN.
// The container is automatically stopped when the test ends.
func TestPostgres(ctx context.Context, t *testing.T) string {
    t.Helper()
    container, err := postgres.RunContainer(ctx,
        testcontainers.WithImage(PostgresImage),
        postgres.WithDatabase("helixterm_test"),
        postgres.WithUsername("helixterm"),
        postgres.WithPassword("helixterm_test_pw"),
        testcontainers.WithWaitStrategy(
            wait.ForLog("database system is ready to accept
                connections").
                WithOccurrence(2).
                WithStartupTimeout(30*time.Second),
        ),
    )
    if err != nil {
        t.Fatalf("failed to start postgres: %v", err)
    }
    t.Cleanup(func() {
        if err := container.Terminate(ctx); err != nil {
            t.Logf("warning: failed to terminate postgres
                container: %v", err)
        }
    })
    dsn, err := container.ConnectionString(ctx, "sslmode=disable")
    if err != nil {
        t.Fatalf("failed to get postgres DSN: %v", err)
    }
    return dsn
}

```

// TestRedis starts a Redis container and returns the address.

```

func TestRedis(ctx context.Context, t *testing.T) string {
    t.Helper()
    container, err := redis.RunContainer(ctx,
        testcontainers.WithImage(RedisImage),
        testcontainers.WithWaitStrategy(

```

```

        wait.ForLog("Ready to accept connections tcp").
            WithStartupTimeout(20*time.Second),
    ),
)
if err != nil {
    t.Fatalf("failed to start redis: %v", err)
}
t.Cleanup(func() { _ = container.Terminate(ctx) })
addr, err := container.ConnectionString(ctx)
if err != nil {
    t.Fatalf("failed to get redis address: %v", err)
}
return addr
}

// TestKafka starts a Kafka container and returns the broker list.
func TestKafka(ctx context.Context, t *testing.T) []string {
    t.Helper()
    container, err := kafka.RunContainer(ctx,
        testcontainers.WithImage(KafkaImage),
        kafka.WithClusterID("test-cluster"),
        testcontainers.WithWaitStrategy(
            wait.ForLog("Kafka Server started").
                WithStartupTimeout(60*time.Second),
        ),
    )
    if err != nil {
        t.Fatalf("failed to start kafka: %v", err)
    }
    t.Cleanup(func() { _ = container.Terminate(ctx) })
    brokers, err := container.Brokers(ctx)
    if err != nil {
        t.Fatalf("failed to get kafka brokers: %v", err)
    }
    return brokers
}

// TestRabbitMQ starts a RabbitMQ container and returns the AMQP
// URL.
func TestRabbitMQ(ctx context.Context, t *testing.T) string {
    t.Helper()
    container, err := rabbitmq.RunContainer(ctx,
        testcontainers.WithImage(RabbitMQImage),
        rabbitmq.WithAdminUsername("guest"),

```

```

        rabbitmq.WithAdminPassword("guest"),
        testcontainers.WithWaitStrategy(
            wait.ForLog("Server startup complete").
                WithStartupTimeout(30*time.Second),
        ),
    )
    if err != nil {
        t.Fatalf("failed to start rabbitmq: %v", err)
    }
    t.Cleanup(func() { _ = container.Terminate(ctx) })
    url, err := container.AmqpURL(ctx)
    if err != nil {
        t.Fatalf("failed to get rabbitmq url: %v", err)
    }
    return url
}

```

3.2 Database Integration Tests

```

// services/auth/repository_integration_test.go
//go:build integration

```

```

package auth_integration_test

import (
    "context"
    "database/sql"
    "testing"
    "time"

    _ "github.com/lib/pq"
    "github.com/HelixDevelopment/helixtermininator/services/auth/
        repository"
    "github.com/HelixDevelopment/helixtermininator/testinfra"
    "github.com/HelixDevelopment/helixtermininator/pkg/domain"
    "github.com/HelixDevelopment/helixtermininator/db/migrations"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

func setupTestDB(t *testing.T) *sql.DB {
    t.Helper()
    ctx := context.Background()
    dsn := testinfra.TestPostgres(ctx, t)

```



```

    db, err := sql.Open("postgres", dsn)
    require.NoError(t, err)
    // Run all migrations against the fresh test database
    err = migrations.RunAll(db)
    require.NoError(t, err, "DB migration must succeed on clean
        database")
    t.Cleanup(func() { _ = db.Close() })
    return db
}

func TestUserRepository_CreateAndFind_Integration(t *testing.T) {
    db := setupTestDB(t)
    repo := repository.NewUserRepository(db)
    ctx := context.Background()

    user := &domain.User{
        Email:          "integration-test@example.com",
        PasswordHash:   "$2a$10$abcdefghijklmnopqrstuabcdefghijklmnopqrstuabcdefghijklmnopq",
        DisplayName:    "Integration Test User",
        CreatedAt:      time.Now().UTC().Truncate(time.Microsecond),
    }

    id, err := repo.Create(ctx, user)
    require.NoError(t, err)
    assert.NotEmpty(t, id)

    found, err := repo.FindByEmail(ctx, "integration-
        test@example.com")
    require.NoError(t, err)
    require.NotNil(t, found)
    assert.Equal(t, id, found.ID)
    assert.Equal(t, user.Email, found.Email)
    assert.Equal(t, user.DisplayName, found.DisplayName)
}

func TestUserRepository_LoginAttempts_Integration(t *testing.T) {
    db := setupTestDB(t)
    repo := repository.NewUserRepository(db)
    ctx := context.Background()

    // Create user
    user := &domain.User{Email: "lockout-test@example.com",
        PasswordHash: "hash"}
    id, err := repo.Create(ctx, user)
    require.NoError(t, err)

```

```

// Increment attempts multiple times
for i := 1; i <= 5; i++ {
    count, err := repo.IncrementLoginAttempts(ctx, id)
    require.NoError(t, err)
    assert.Equal(t, i, count)
}

// Lock account
lockExpiry := time.Now().Add(15 * time.Minute)
err = repo.LockAccount(ctx, id, lockExpiry)
require.NoError(t, err)

// Verify lock is persisted
locked, err := repo.FindByID(ctx, id)
require.NoError(t, err)
assert.True(t, locked.AccountLocked)
assert.True(t, locked.LockExpiry.After(time.Now()))
}

func TestUserRepository_UniqueEmail_Constraint(t *testing.T) {
    db := setupTestDB(t)
    repo := repository.NewUserRepository(db)
    ctx := context.Background()

    user1 := &domain.User{Email: "unique@example.com",
        PasswordHash: "hash"}
    _, err := repo.Create(ctx, user1)
    require.NoError(t, err)

    user2 := &domain.User{Email: "unique@example.com",
        PasswordHash: "hash2"}
    _, err = repo.Create(ctx, user2)
    require.Error(t, err)
    assert.ErrorIs(t, err, domain.ErrDuplicate)
}

func TestDBMigration_IdempotentRerun(t *testing.T) {
    db := setupTestDB(t) // already runs migrations once
    // Running migrations again must be a no-op
    err := migrations.RunAll(db)
    require.NoError(t, err, "migrations must be idempotent")
}

func TestDBMigration_RollbackAndReapply(t *testing.T) {

```

```

db := setupTestDB(t)

// Roll back the last 3 migrations
err := migrations.RollbackN(db, 3)
require.NoError(t, err)

// Re-apply them
err = migrations.RunAll(db)
require.NoError(t, err, "re-applying rolled-back migrations
    must succeed")
}

func TestTransaction_Rollback_OnError(t *testing.T) {
    db := setupTestDB(t)
    ctx := context.Background()

    tx, err := db.BeginTx(ctx, nil)
    require.NoError(t, err)

    // Insert a user
    _, err = tx.ExecContext(ctx,
        `INSERT INTO users (id, email, password_hash) VALUES ($1,
        $2, $3)`,
        "tx_test_user", "tx-test@example.com", "hash")
    require.NoError(t, err)

    // Roll back
    err = tx.Rollback()
    require.NoError(t, err)

    // Verify the user was NOT persisted
    var count int
    err = db.QueryRowContext(ctx, `SELECT COUNT(*) FROM users
        WHERE email = $1`, "tx-test@example.com").Scan(&count)
    require.NoError(t, err)
    assert.Equal(t, 0, count, "rolled-back transaction must not
        persist data")
}

```

3.3 Kafka Integration Tests

```

// services/audit/kafka_integration_test.go
//go:build integration

package audit_integration_test

```

```

import (
    "context"
    "encoding/json"
    "testing"
    "time"

    "github.com/IBM/sarama"
    "github.com/HelixDevelopment/helixtermininator/services/audit"
    "github.com/HelixDevelopment/helixtermininator/testinfra"
    "github.com/HelixDevelopment/helixtermininator/pkg/domain"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

func TestAuditService_KafkaProducer_Integration(t *testing.T) {
    ctx := context.Background()
    brokers := testinfra.TestKafka(ctx, t)

    // Create topic for test
    topicName := "audit-events-test-" + t.Name()
    admin, err := sarama.NewClusterAdmin(brokers,
        sarama.NewConfig())
    require.NoError(t, err)
    defer admin.Close()

    err = admin.CreateTopic(topicName, &sarama.TopicDetail{
        NumPartitions: 3,
        ReplicationFactor: 1,
    }, false)
    require.NoError(t, err)

    svc := audit.NewService(audit.Config{
        KafkaBrokers: brokers,
        Topic:        topicName,
    })

    // Emit an audit event
    event := &domain.AuditEvent{
        EventType: "session.start",
        ActorID:    "usr_01J4KXYZ",
        TargetID:    "host_001",
        Timestamp:  time.Now().UTC(),
        IPAddress:  "192.168.1.50",
    }

```

```

        SessionID: "sess_xyz789",
    }

    err = svc.Emit(ctx, event)
    require.NoError(t, err)

    // Consume the event from Kafka and verify
    config := sarama.NewConfig()
    config.Consumer.Offsets.Initial = sarama.OffsetOldest
    consumer, err := sarama.NewConsumer(brokers, config)
    require.NoError(t, err)
    defer consumer.Close()

    partConsumer, err := consumer.ConsumePartition(topicName, 0,
        sarama.OffsetOldest)
    require.NoError(t, err)
    defer partConsumer.Close()

    select {
    case msg := <-partConsumer.Messages():
        var received domain.AuditEvent
        err = json.Unmarshal(msg.Value, &received)
        require.NoError(t, err)
        assert.Equal(t, event.EventType, received.EventType)
        assert.Equal(t, event.ActorID, received.ActorID)
        assert.Equal(t, event.SessionID, received.SessionID)
    case <-time.After(10 * time.Second):
        t.Fatal("timed out waiting for Kafka message")
    }
}

func TestAuditService_KafkaConsumer_EventOrdering(t *testing.T) {
    ctx := context.Background()
    brokers := testinfra.TestKafka(ctx, t)
    topicName := "audit-ordering-" + t.Name()

    // Produce 100 events in sequence
    svc := audit.NewService(audit.Config{
        KafkaBrokers: brokers,
        Topic:        topicName,
    })

    for i := 0; i < 100; i++ {
        err := svc.Emit(ctx, &domain.AuditEvent{

```

```

        EventType: "test.event",
        Sequence: i,
        SessionID: "sess_ordering_test",
    })
    require.NoError(t, err)
}

// Consume all events and verify they arrive in order per
// partition key
received := audit.ConsumeAll(ctx, t, brokers, topicName, 100,
    15*time.Second)
assert.Len(t, received, 100)
for i, event := range received {
    assert.Equal(t, i, event.Sequence,
        "events with same partition key must arrive in order")
}
}

```

3.4 Redis Integration Tests

```

// services/auth/token_store_integration_test.go
//go:build integration

package auth_integration_test

import (
    "context"
    "testing"
    "time"

    "github.com/HelixDevelopment/helixterminator/services/auth/
        tokenstore"
    "github.com/HelixDevelopment/helixterminator/testinfra"
    "github.com/HelixDevelopment/helixterminator/pkg/domain"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

func TestRedisTokenStore_StoreAndGet_Integration(t *testing.T) {
    ctx := context.Background()
    redisAddr := testinfra.TestRedis(ctx, t)
    store := tokenstore.NewRedisTokenStore(redisAddr, "")

    token := &domain.RefreshToken{
        ID: "rt_integration_001",
    }
}

```

```

        UserID:    "usr_01J4KXYZ",
        ExpiresAt: time.Now().Add(7 * 24 * time.Hour),
        Revoked:   false,
    }

    err := store.StoreRefreshToken(ctx, token)
    require.NoError(t, err)

    retrieved, err := store.GetRefreshToken(ctx,
        "rt_integration_001")
    require.NoError(t, err)
    require.NotNil(t, retrieved)
    assert.Equal(t, token.UserID, retrieved.UserID)
    assert.False(t, retrieved.Revoked)
}

func TestRedisTokenStore_TTLExpiry_Integration(t *testing.T) {
    ctx := context.Background()
    redisAddr := testinfra.TestRedis(ctx, t)
    store := tokenstore.NewRedisTokenStore(redisAddr, "")

    token := &domain.RefreshToken{
        ID:        "rt_short_ttl",
        UserID:    "usr_01J4KXYZ",
        ExpiresAt: time.Now().Add(2 * time.Second), // expires
                                                    very soon
    }

    err := store.StoreRefreshToken(ctx, token)
    require.NoError(t, err)

    // Verify it exists
    retrieved, err := store.GetRefreshToken(ctx, "rt_short_ttl")
    require.NoError(t, err)
    assert.NotNil(t, retrieved)

    // Wait for expiry
    time.Sleep(3 * time.Second)

    // Verify it's gone
    expired, err := store.GetRefreshToken(ctx, "rt_short_ttl")
    require.Error(t, err)
    assert.Nil(t, expired)
    assert.ErrorIs(t, err, tokenstore.ErrTokenNotFound)
}

```

```

func TestRedisTokenStore_Revoke_Integration(t *testing.T) {
    ctx := context.Background()
    redisAddr := testinfra.TestRedis(ctx, t)
    store := tokenstore.NewRedisTokenStore(redisAddr, "")

    token := &domain.RefreshToken{
        ID:          "rt_to_revoke",
        UserID:      "usr_01J4KXYZ",
        ExpiresAt: time.Now().Add(1 * time.Hour),
    }

    err := store.StoreRefreshToken(ctx, token)
    require.NoError(t, err)

    err = store.RevokeRefreshToken(ctx, "rt_to_revoke")
    require.NoError(t, err)

    revoked, err := store.GetRefreshToken(ctx, "rt_to_revoke")
    require.NoError(t, err)
    assert.True(t, revoked.Revoked, "revoked token must have
        Revoked=true flag in Redis")
}

func TestRedisTokenStore_CacheMiss_Integration(t *testing.T) {
    ctx := context.Background()
    redisAddr := testinfra.TestRedis(ctx, t)
    store := tokenstore.NewRedisTokenStore(redisAddr, "")

    _, err := store.GetRefreshToken(ctx, "rt_nonexistent_key")
    require.Error(t, err)
    assert.ErrorIs(t, err, tokenstore.ErrTokenNotFound)
}

```

3.5 RabbitMQ Integration Tests

RabbitMQ is real, in-use infrastructure — notification-service (email/Slack/webhook fan-out) and webhook-service (outbound webhook delivery with retry queue) are both live AMQP consumers (see [04_devops_infrastructure.md §6.2 “Amazon MQ \(Managed RabbitMQ\)”](#) and the RabbitMQ production-path decision recorded there). These integration tests exercise the same message shapes against a testcontainers-go RabbitMQ container in CI; the production path is Amazon MQ (a managed, multi-AZ RabbitMQ-engine broker per doc

04), not the in-cluster Bitnami chart used for local/dev — the container image pinned in testinfra (§3.1) is a test-time substitute for that engine, not a claim that RabbitMQ ships as a self-managed in-cluster broker in production.

```
// services/sshproxy/command_routing_integration_test.go
//go:build integration

package sshproxy_integration_test

import (
    "context"
    "testing"
    "time"

    amqp "github.com/rabbitmq/amqp091-go"
    "github.com/HelixDevelopment/helixtermininator/services/sshproxy/commands"
    "github.com/HelixDevelopment/helixterminator/testinfra"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

func TestRabbitMQ_SSHCommand_Routing_Integration(t *testing.T) {
    ctx := context.Background()
    amqpURL := testinfra.TestRabbitMQ(ctx, t)

    router := commands.NewCommandRouter(commands.Config{
        AMQPURL:      amqpURL,
        Exchange:     "helix.ssh.commands",
        ConnectQueue: "ssh.connect",
        DisconnectQueue: "ssh.disconnect",
    })

    err := router.Setup(ctx)
    require.NoError(t, err)

    // Publish a connect command
    cmd := &commands.SSHConnectCommand{
        SessionID: "sess_amqp_test",
        UserID:    "usr_01J4KXYZ",
        HostID:    "host_001",
        RequestedAt: time.Now().UTC(),
    }
}
```

```

err = router.PublishConnect(ctx, cmd)
require.NoError(t, err)

// Consume and verify
received := make(chan *commands.SSHConnectCommand, 1)
err = router.ConsumeConnect(ctx, func(c
    *commands.SSHConnectCommand) error {
    received <- c
    return nil
})
require.NoError(t, err)

select {
case msg := <-received:
    assert.Equal(t, "sess_amqp_test", msg.SessionID)
    assert.Equal(t, "usr_01J4KXYZ", msg.UserID)
case <-time.After(10 * time.Second):
    t.Fatal("timed out waiting for RabbitMQ message")
}
}

func TestRabbitMQ_DeadLetterQueue_OnProcessingError(t *testing.T)
{
    ctx := context.Background()
    amqpURL := testinfra.TestRabbitMQ(ctx, t)

    router := commands.NewCommandRouter(commands.Config{
        AMQPURL:      amqpURL,
        Exchange:     "helix.ssh.commands",
        ConnectQueue: "ssh.connect.dlq-test",
        DLQEnabled:   true,
        DLQName:      "ssh.connect.dlq",
        MaxRetries:   3,
    })

    err := router.Setup(ctx)
    require.NoError(t, err)

    cmd := &commands.SSHConnectCommand{SessionID:
        "sess_dlq_test", HostID: "host_bad"}

    err = router.PublishConnect(ctx, cmd)
    require.NoError(t, err)

    // Consumer that always fails – should trigger DLQ after
    MaxRetries

```

```

err = router.ConsumeConnect(ctx, func(c
    *commands.SSHConnectCommand) error {
    return assert.AnError // always fail
})
require.NoError(t, err)

// Give retry loop time to exhaust attempts
time.Sleep(5 * time.Second)

// Verify message landed in DLQ
dlqCount := router.GetDLQMessageCount(ctx, "ssh.connect.dlq")
assert.Equal(t, 1, dlqCount, "message must be in DLQ after
    MaxRetries exhausted")
}

```

3.6 Service-to-Service Integration Tests

```

// integration/auth_vault_chain_test.go
//go:build integration

package integration_test

import (
    "context"
    "net/http"
    "net/http/httptest"
    "testing"
    "time"

    "github.com/HelixDevelopment/helixterminator/services/auth"
    "github.com/HelixDevelopment/helixterminator/services/vault"
    "github.com/HelixDevelopment/helixterminator/testinfra"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

// TestAuthVaultChain_Integration tests the full authentication →
// vault access chain
// using real database and Redis containers.
func TestAuthVaultChain_Integration(t *testing.T) {
    ctx := context.Background()

    // Start real containers
    pgDSN := testinfra.TestPostgres(ctx, t)
    redisAddr := testinfra.TestRedis(ctx, t)

```

```

// Initialize real services with real dependencies
authSvc := auth.NewServiceFromDSN(pgDSN, redisAddr)
vaultSvc := vault.NewServiceFromDSN(pgDSN)

// Register a user
userID, err := authSvc.RegisterUser(ctx, auth.RegisterRequest{
    Email:    "chain-test@example.com",
    Password: "ValidPassword123!@#",
})
require.NoError(t, err)

// Verify email (skip in integration test via test helper)
err = authSvc.ForceVerifyEmail(ctx, userID)
require.NoError(t, err)

// Login
loginResult, err := authSvc.Login(ctx, auth.LoginRequest{
    Email:    "chain-test@example.com",
    Password: "ValidPassword123!@#",
    DeviceID: "dev_integration_001",
})
require.NoError(t, err)
assert.NotEmpty(t, loginResult.AccessToken)

// Use access token to create a vault
vaultID, err := vaultSvc.CreateVaultWithToken(ctx,
    loginResult.AccessToken, vault.CreateVaultRequest{
        Name: "Integration Test Vault",
    })
require.NoError(t, err)
assert.NotEmpty(t, vaultID)

// Add an entry to the vault
entryID, err := vaultSvc.AddEntryWithToken(ctx,
    loginResult.AccessToken, vault.AddEntryRequest{
        VaultID: vaultID,
        Entry: &domain.VaultEntry{
            Name:    "Test Server",
            Hostname: "10.0.0.1",
            Username: "admin",
            Password: "server-password-encrypted",
        },
    })
require.NoError(t, err)

```

```

assert.NotEmpty(t, entryID)

// Retrieve the entry and verify
retrieved, err := vaultSvc.GetEntryWithToken(ctx,
    loginResult.AccessToken, vaultID, entryID)
require.NoError(t, err)
assert.Equal(t, "Test Server", retrieved.Name)
assert.Equal(t, "10.0.0.1", retrieved.Hostname)
}

```

4. End-to-End Tests

4.1 Backend E2E Test: Complete User Journey

The backend E2E tests run against a full staging deployment and exercise the complete user-visible flows via the API Gateway.

```

// e2e/user_journey_test.go
//go:build e2e

```

```

package e2e_test

```

```

import (
    "bytes"
    "context"
    "encoding/json"
    "fmt"
    "io"
    "net/http"
    "testing"
    "time"

    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

```

```

const (
    E2EBaseURL    = "https://staging-api.helixterminator.app"
    E2EWSBaseURL = "wss://staging-ws.helixterminator.app"
)

```

```

type E2EClient struct {
    http *http.Client
}

```

```

    baseURL      string
    accessToken   string
}

func newE2EClient() *E2EClient {
    return &E2EClient{
        http:      &http.Client{Timeout: 30 * time.Second},
        baseURL:    E2EBaseURL,
    }
}

func (c *E2EClient) POST(t *testing.T, path string, body
    interface{}) *http.Response {
    t.Helper()
    data, err := json.Marshal(body)
    require.NoError(t, err)
    req, err := http.NewRequest("POST", c.baseURL+path,
        bytes.NewBuffer(data))
    require.NoError(t, err)
    req.Header.Set("Content-Type", "application/json")
    if c.accessToken != "" {
        req.Header.Set("Authorization", "Bearer "+c.accessToken)
    }
    resp, err := c.http.Do(req)
    require.NoError(t, err)
    return resp
}

// TestE2E_CompleteUserJourney exercises the full flow:
// registration → email verify → login → vault create → host add →
//    SSH connect →
// session → disconnect
func TestE2E_CompleteUserJourney(t *testing.T) {
    client := newE2EClient()
    ctx := context.Background()
    _ = ctx

    // Unique test email to avoid conflicts
    email := fmt.Sprintf("e2e-test-%d@helixterminator-
        test.app", time.Now().UnixNano())
    password := "E2ETestPassword!2026"

    // — Step 1: Register
    t.Run("Register", func(t *testing.T) {

```

```

resp := client.POST(t, "/v1/auth/register",
    map[string]string{
        "email":    email,
        "password": password,
    })
defer resp.Body.Close()
require.Equal(t, http.StatusCreated, resp.StatusCode)

var body map[string]interface{}
require.NoError(t,
    json.NewDecoder(resp.Body).Decode(&body))
assert.NotEmpty(t, body["user_id"])
})

// — Step 2: Email verification (staging uses magic token)


---


t.Run("VerifyEmail", func(t *testing.T) {
    // In E2E tests, use the staging test API to get the
    // verification token
    token := getTestVerificationToken(t, email)
    resp := client.POST(t, "/v1/auth/verify-email",
        map[string]string{
            "token": token,
        })
    defer resp.Body.Close()
    require.Equal(t, http.StatusOK, resp.StatusCode)
})

// — Step 3: Login


---


t.Run("Login", func(t *testing.T) {
    resp := client.POST(t, "/v1/auth/login",
        map[string]string{
            "email":    email,
            "password": password,
            "device_id": "e2e-test-device",
        })
    defer resp.Body.Close()
    require.Equal(t, http.StatusOK, resp.StatusCode)

    var body map[string]interface{}
    require.NoError(t,
        json.NewDecoder(resp.Body).Decode(&body))
    require.NotEmpty(t, body["access_token"])
    client.accessToken = body["access_token"].(string)
})

```

// — Step 4: Create Vault

```
var vaultID string
t.Run("CreateVault", func(t *testing.T) {
    resp := client.POST(t, "/v1/vaults", map[string]string{
        "name": "E2E Test Vault",
        "type": "personal",
    })
    defer resp.Body.Close()
    require.Equal(t, http.StatusCreated, resp.StatusCode)

    var body map[string]interface{}
    require.NoError(t,
        json.NewDecoder(resp.Body).Decode(&body))
    require.NotEmpty(t, body["vault_id"])
    vaultID = body["vault_id"].(string)
})
```

// — Step 5: Add Host

```
var hostID string
t.Run("AddHost", func(t *testing.T) {
    resp := client.POST(t, "/v1/hosts", map[string]interface{}{
        {
            "vault_id":    vaultID,
            "hostname":   "e2e-test-server.internal",
            "port":        22,
            "username":    "test-user",
            "auth_type":   "password",
            "display_name": "E2E Test Server",
        }
    })
    defer resp.Body.Close()
    require.Equal(t, http.StatusCreated, resp.StatusCode)

    var body map[string]interface{}
    require.NoError(t,
        json.NewDecoder(resp.Body).Decode(&body))
    require.NotEmpty(t, body["host_id"])
    hostID = body["host_id"].(string)
})
```

// — Step 6: SSH Connect

```
var sessionID string
t.Run("SSHConnect", func(t *testing.T) {
    resp := client.POST(t, "/v1/sessions",
        map[string]interface{}{
```



```

        "host_id":    hostID,
        "auth_type": "password",
        "password":   "test-server-password",
    })
    defer resp.Body.Close()
    require.Equal(t, http.StatusCreated, resp.StatusCode)

    var body map[string]interface{}
    require.NoError(t,
        json.NewDecoder(resp.Body).Decode(&body))
    require.NotEmpty(t, body["session_id"])
    require.NotEmpty(t, body["websocket_url"])
    sessionID = body["session_id"].(string)
})

// — Step 7: Interact with Terminal via WebSocket


---


t.Run("TerminalInteraction", func(t *testing.T) {
    ws := connectE2EWebSocket(t, sessionID,
        client.accessToken)
    defer ws.Close()

    // Send a command
    sendTerminalInput(t, ws, "echo 'helix-e2e-test'\n")

    // Verify output appears within 5 seconds
    output := readTerminalOutput(t, ws, "helix-e2e-test",
        5*time.Second)
    assert.Contains(t, output, "helix-e2e-test")
})

// — Step 8: Disconnect


---


t.Run("Disconnect", func(t *testing.T) {
    resp := client.POST(t, fmt.Sprintf("/v1/sessions/%s/
        disconnect", sessionID), nil)
    defer resp.Body.Close()
    require.Equal(t, http.StatusNoContent, resp.StatusCode)

    // Verify session is marked inactive
    getResp, err := http.NewRequest("GET",
        E2EBaseURL+fmt.Sprintf("/v1/sessions/%s", sessionID), nil)
    require.NoError(t, err)
    getResp.Header.Set("Authorization", "Bearer
        "+client.accessToken)
    statusResp, err := client.http.Do(getResp)
    require.NoError(t, err)

```

```

    defer statusResp.Body.Close()

    var sessionBody map[string]interface{}
    require.NoError(t,
        json.NewDecoder(statusResp.Body).Decode(&sessionBody))
    assert.Equal(t, "inactive", sessionBody["status"])
  })
}

```

4.2 Flutter Integration Tests

Flutter integration tests use `flutter_test` and the `integration_test` package. Tests run on real devices or simulators via `flutter drive`.

```

// integration_test/app_launch_test.dart
import 'package:flutter_test/flutter_test.dart';
import 'package:integration_test/integration_test.dart';
import 'package:helixterminator/main.dart' as app;
import 'package:helixterminator/pages/host_list_page.dart';
import 'package:helixterminator/pages/terminal_page.dart';

void main() {
  IntegrationTestWidgetsFlutterBinding.ensureInitialized();

  group('App Launch and Authentication E2E', () {
    testWidgets('App launches, biometric login, host list
      visible', (tester) async {
      // Start the app
      app.main();
      await tester.pumpAndSettle(const Duration(seconds: 3));

      // Verify splash screen appears
      expect(find.byKey(const Key('splash_screen')),
        findsOneWidget);

      // Simulate biometric authentication approval
      await tester.tap(find.byKey(const
        Key('biometric_login_button')));
      await tester.pumpAndSettle(const Duration(seconds: 2));

      // After auth, host list should be visible
      expect(find.byType(HostListPage), findsOneWidget);
      expect(find.byKey(const Key('host_list_view')),
        findsOneWidget);
    });
  });
}

```

```

testWidgets('Connect to host, type command, verify output,
  disconnect', (tester) async {
  app.main();
  await tester.pumpAndSettle(const Duration(seconds: 3));

  // Authenticate
  await authenticateWithBiometrics(tester);
  await tester.pumpAndSettle();

  // Find and tap the first host
  await tester.tap(find.byKey(const Key('host_list_item_0')));
  await tester.pumpAndSettle(const Duration(seconds: 2));

  // Terminal page should be active
  expect(find.byType(TerminalPage), findsOneWidget);

  // Wait for SSH connection
  await tester.pumpAndSettle(const Duration(seconds: 5));
  expect(find.byKey(const
    Key('terminal_connected_indicator')), findsOneWidget);

  // Type a command
  final terminalInput = find.byKey(const
    Key('terminal_input_field'));
  await tester.enterText(terminalInput, 'echo "flutter-e2e-
    test"');
  await
    tester.testTextInput.receiveAction(TextInputAction.done);
  await tester.pumpAndSettle(const Duration(seconds: 3));

  // Verify output in terminal
  expect(find.textContaining('flutter-e2e-test'),
    findsAtLeastNWidgets(1));

  // Disconnect
  await tester.tap(find.byKey(const
    Key('disconnect_button')));
  await tester.pumpAndSettle(const Duration(seconds: 2));

  // Back to host list
  expect(find.byType(HostListPage), findsOneWidget);
});

group('SFTP Transfer E2E', () {
  testWidgets('SFTP: connect → browse → upload → download →
    verify', (tester) async {

```

```

app.main();
await tester.pumpAndSettle(const Duration(seconds: 3));
await authenticateWithBiometrics(tester);

// Open SFTP browser for host
await tester.tap(find.byKey(const
  Key('host_sftp_button_0')));
await tester.pumpAndSettle(const Duration(seconds: 3));

// Verify directory listing is shown
expect(find.byKey(const Key('sftp_file_browser')),
  findsOneWidget);

// Upload a test file
await tester.tap(find.byKey(const
  Key('sftp_upload_button')));
await tester.pumpAndSettle();

// Select test file from mock picker
await tester.tap(find.byKey(const
  Key('file_picker_test_file')));
await tester.pumpAndSettle(const Duration(seconds: 5));

// Verify upload success
expect(find.byKey(const
  Key('sftp_upload_success_indicator')), findsOneWidget);

// Download the uploaded file
await tester.tap(find.textContaining('test_file.txt'));
await tester.pumpAndSettle();
await tester.tap(find.byKey(const
  Key('sftp_download_button')));
await tester.pumpAndSettle(const Duration(seconds: 5));

// Verify download
expect(find.byKey(const
  Key('sftp_download_success_indicator')), findsOneWidget);
});
});

group('Workspace Management E2E', () {
  testWidgets('Create workspace, add sessions, split view, save
    template, restore', (tester) async {
    app.main();
    await tester.pumpAndSettle(const Duration(seconds: 3));
    await authenticateWithBiometrics(tester);

```

```

// Navigate to Workspaces
await tester.tap(find.byKey(const Key('nav_workspaces')));
await tester.pumpAndSettle();

// Create a new workspace
await tester.tap(find.byKey(const
  Key('create_workspace_button')));
await tester.pumpAndSettle();

final workspaceNameField = find.byKey(const
  Key('workspace_name_field'));
await tester.enterText(workspaceNameField, 'E2E Test
  Workspace');
await tester.tap(find.byKey(const
  Key('workspace_save_button')));
await tester.pumpAndSettle();

expect(find.textContaining('E2E Test Workspace'),
  findsOneWidget);

// Add two sessions
for (int i = 0; i < 2; i++) {
  await tester.tap(find.byKey(const
    Key('workspace_add_session_button')));
  await tester.pumpAndSettle();
  await
    tester.tap(find.byKey(Key('workspace_host_selector_$i')));
  await tester.pumpAndSettle(const Duration(seconds: 3));
}

// Enable split view
await tester.tap(find.byKey(const
  Key('workspace_split_view_toggle')));
await tester.pumpAndSettle();

// Verify both terminal panes are visible
expect(find.byKey(const Key('terminal_pane_0')),
  findsOneWidget);
expect(find.byKey(const Key('terminal_pane_1')),
  findsOneWidget);

// Save as template
await tester.tap(find.byKey(const
  Key('workspace_save_template_button')));
await tester.pumpAndSettle();
await tester.enterText(
  find.byKey(const Key('template_name_field')), 'E2E
  Template');

```

```

    await tester.tap(find.byKey(const
      Key('template_save_confirm')));
    await tester.pumpAndSettle();

    // Close workspace and restore from template
    await tester.tap(find.byKey(const
      Key('close_workspace_button')));
    await tester.pumpAndSettle();

    await tester.tap(find.textContaining('E2E Template'));
    await tester.pumpAndSettle(const Duration(seconds: 5));

    // Verify workspace was restored with split view
    expect(find.byKey(const Key('terminal_pane_0')),
      findsOneWidget);
    expect(find.byKey(const Key('terminal_pane_1')),
      findsOneWidget);
  });
});
}

Future<void> authenticateWithBiometrics(WidgetTester tester)
  async {
    await tester.tap(find.byKey(const
      Key('biometric_login_button')));
    await tester.pumpAndSettle(const Duration(seconds: 2));
  }

```

4.3 MFA Setup and Use Flow (E2E)

```

// e2e/mfa_flow_test.go
//go:build e2e

package e2e_test

import (
    "encoding/base64"
    "testing"
    "time"

    "github.com/pquerna/otp/totp"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

func TestE2E_MFASetupAndUse(t *testing.T) {

```

```

client := newE2EClient()

// Create and login as test user (no MFA yet)
email, password := createAndLoginTestUser(t, client)
_ = email
_ = password

// — Setup TOTP MFA


---


var totpSecret string
t.Run("SetupTOTP", func(t *testing.T) {
    resp := client.POST(t, "/v1/auth/mfa/totp/setup", nil)
    defer resp.Body.Close()
    require.Equal(t, 200, resp.StatusCode)

    var body map[string]interface{}
    require.NoError(t, jsonDecode(resp.Body, &body))
    require.NotEmpty(t, body["secret"])
    require.NotEmpty(t, body["qr_url"])
    totpSecret = body["secret"].(string)
})

t.Run("VerifyTOTPSetup", func(t *testing.T) {
    code, err := totp.GenerateCode(totpSecret, time.Now())
    require.NoError(t, err)

    resp := client.POST(t, "/v1/auth/mfa/totp/verify",
        map[string]string{
            "code": code,
        })
    defer resp.Body.Close()
    require.Equal(t, 200, resp.StatusCode)

    var body map[string]interface{}
    require.NoError(t, jsonDecode(resp.Body, &body))
    assert.True(t, body["mfa_enabled"].(bool))
    // Backup codes must be provided
    assert.NotEmpty(t, body["backup_codes"])
})

t.Run("LoginWithMFA", func(t *testing.T) {
    // Logout first
    logoutTestUser(t, client)

    // Login – should get MFA challenge

```

```

resp := client.POST(t, "/v1/auth/login",
    map[string]string{
        "email":      email,
        "password":   password,
        "device_id":  "e2e-mfa-device",
    })
defer resp.Body.Close()
require.Equal(t, 200, resp.StatusCode)

var loginBody map[string]interface{}
require.NoError(t, jsonDecode(resp.Body, &loginBody))
require.True(t, loginBody["mfa_required"].(bool))
require.NotEmpty(t, loginBody["mfa_session_token"])
mfaToken := loginBody["mfa_session_token"].(string)

// Complete MFA
code, err := totp.GenerateCode(totpSecret, time.Now())
require.NoError(t, err)

mfaResp := client.POST(t, "/v1/auth/mfa/verify",
    map[string]string{
        "mfa_session_token": mfaToken,
        "code":               code,
    })
defer mfaResp.Body.Close()
require.Equal(t, 200, mfaResp.StatusCode)

var mfaBody map[string]interface{}
require.NoError(t, jsonDecode(mfaResp.Body, &mfaBody))
assert.NotEmpty(t, mfaBody["access_token"])
client.accessToken = mfaBody["access_token"].(string)
})
}

```

4.4 Device / Topology Test Matrix

The product roadmap commits HelixTerminator to five platform families (iOS, Android, macOS, Windows, Linux desktop, and Web) each with per-platform performance and accessibility SLOs. Prior to this section, no explicit device/OS/browser version list existed anywhere in the corpus — E2E and HelixQA configuration referenced platform *names* only (web, desktop, android, ios). This matrix is the

canonical, versioned list every E2E/HelixQA/device-farm job MUST resolve against; it replaces “the device farm has some devices” with an auditable row set.

Tiering. **Tier-1** rows run on every Main-pipeline build (a representative subset — one device/OS/browser per family, chosen for highest install-base share). **Tier-2** rows run on the Nightly and Release pipelines (the full matrix). A platform/feature cell with no Tier-1 row is a release-blocker gap per §11.4.25 (Full-Automation-Coverage Mandate) and must be filed as a tracked item.

4.4.1 Mobile (iOS / Android)

Platform	OS Version	Device Class	Farm	Tier	Feature Coverage
iOS	18.1 (latest stable)	iPhone 16 Pro (A18 Pro, 6GB RAM)	Physical device farm (BrowserStack App Live)	Tier-1	Auth, Vault, SSH session, biometric login, push notifications
iOS	17.6 (N-1 stable)	iPhone 13 (A15, 4GB RAM)	Physical device farm	Tier-2	Auth, Vault, SSH session
iOS	16.7 (min-supported, per App Store min-OS policy)	iPhone SE 3rd-gen (A15, 4GB RAM)	Physical device farm	Tier-2	Auth, cold-start budget only (§5.3.4)
Android	15 (API 35, latest stable)	Pixel 9 (Tensor G4, 12GB RAM)	adb over farm (Firebase Test Lab)	Tier-1	Auth, Vault, SSH session, biometric login, WorkManager background sync
Android	14 (API 34)	Samsung Galaxy S23 (Snapdragon 8 Gen 2, 8GB RAM)	Firebase Test Lab	Tier-2	Auth, Vault, SSH session
Android	12 (API 31, min-	Pixel 4a (Snapdragon	Firebase Test Lab	Tier-2	Auth, cold-start budget,

Platform	OS Version	Device Class	Farm	Tier	Feature Coverage
	supported per minSdkVersion)	730G, 6GB RAM, low-end reference)			low-end frame-time budget (\$5.3.3)

4.4.2 Desktop (macOS / Windows / Linux)

Platform	OS Version	Hardware Class	Runner	Tier	Feature Coverage
macOS	15 Sequoia (latest stable)	Apple Silicon (M3, arm64)	GitHub Actions macos-15	Tier-1	Full desktop client suite
macOS	13 Ventura (N-2, oldest supported per client EOL policy)	Intel x86_64	Self-hosted macOS 13 runner	Tier-2	Auth, SSH session, Vault
Windows	11 23H2 (latest stable)	x86_64, 8GB RAM reference	GitHub Actions windows-2022	Tier-1	Full desktop client suite
Windows	10 22H2 (oldest supported, EOL 2028-10)	x86_64, 4GB RAM low-end reference	Self-hosted Windows 10 runner	Tier-2	Auth, SSH session, low-end frame-time budget
Linux	Ubuntu 24.04 LTS (primary reference distro)	x86_64, GNOME/X11	GitHub Actions ubuntu-24.04	Tier-1	Full desktop client suite
Linux		x86_64		Tier-2	Auth, SSH session,

Platform	OS Version	Hardware Class	Runner	Tier	Feature Coverage
	Fedora 41 (Wayland reference)		Self-hosted Fedora 41 runner		Wayland-specific input handling

4.4.3 Web (Browser × Version)

Browser	Version Policy	Rendering Engine	Executor	Tier	Feature Coverage
Chrome/ Chromium	Latest stable + latest-1	Blink	Playwright (chromium channel)	Tier-1	Full web client suite
Firefox	Latest stable (ESR tracked separately)	Gecko	Playwright (firefox channel)	Tier-1	Full web client suite
Safari	Latest stable (macOS- bundled, no standalone version)	WebKit	Playwright (webkit channel) on macos-15 runner	Tier-1	Auth, Vault, SSH session (WebKit- specific WebSocket/ WebCrypto checks)
Edge	Latest stable	Blink (Chromium- based)	Playwright (msedge channel)	Tier-2	Auth, SSH session

4.4.4 Screen-Size / Viewport Matrix

Applied orthogonally to every mobile and web row above (desktop clients target a fixed 1280×800 minimum window per the UX spec):

Class	Representative Resolution	Applies To
Small phone	375×667 (@2x)	iOS SE-class, Android compact
Standard phone	393×852 (@3x)	iOS Pro-class, Android Pixel-class

Class	Representative Resolution	Applies To
Tablet	834×1194 (@2x)	iPadOS split-view SSH sessions
Small laptop viewport	1366×768	Web Tier-1 minimum
Standard desktop	1920×1080	Web Tier-1 default, desktop client default
Ultrawide	3440×1440	Terminal multi-pane layout regression only

4.4.5 HelixQA Wiring

The matrix above is registered as `devicematrix/topology.yaml` and consumed by the `helixqa` orchestrator's platform resolver (extends the `.helixqa.yaml` `platforms: block` in §10.2, which today only names platform families with no version pins):

```
# devicematrix/topology.yaml
version: "1"
tiers:
  tier1_gate:
    main          # Tier-1 rows run on every Main-pipeline build
  tier2_gate: release # Tier-2 rows run on Nightly + Release pipelines

rows:
- id: ios-18.1-iphone16pro
  platform: ios
  os_version: "18.1"
  device: "iPhone 16 Pro"
  farm: browserstack-app-live
  tier: 1
  features: [auth, vault, ssh_session, biometric_login, push_notifications]

- id: android-15-pixel9
  platform: android
  os_version: "15"
  api_level: 35
  device: "Pixel 9"
  farm: firebase-test-lab
  tier: 1
```

```

    features: [auth, vault, ssh_session, biometric_login,
              background_sync]

- id: macos-15-arm64
  platform: macos
  os_version: "15"
  arch: arm64
  runner: macos-15
  tier: 1
  features: [full_desktop_suite]

- id: windows-11-23h2
  platform: windows
  os_version: "11-23H2"
  runner: windows-2022
  tier: 1
  features: [full_desktop_suite]

- id: linux-ubuntu-24.04
  platform: linux
  os_version: "24.04"
  runner: ubuntu-24.04
  tier: 1
  features: [full_desktop_suite]

- id: web-chromium-latest
  platform: web
  browser: chromium
  version_policy: latest
  executor: playwright
  tier: 1
  features: [full_web_suite]

- id: web-webkit-latest
  platform: web
  browser: webkit
  version_policy: latest
  executor: playwright
  runner: macos-15
  tier: 1
  features: [auth, vault, ssh_session]

```

A CI job (make devicematrix-verify) diffs the checked-in topology.yaml against the live farm inventory (BrowserStack/Firebase Test Lab device-list APIs) on a weekly schedule and files a tracked item

(§11.4.15) when a pinned OS version is deprecated by the vendor, so the matrix never silently drifts from what the farms actually still support.

5. Performance & Load Tests

5.1 k6 Test Scripts

5.1.1 SSH Connection Establishment — 10,000 Concurrent

```
// k6/ssh_connection_load.js
import http from 'k6/http';
import ws from 'k6/ws';
import { check, sleep } from 'k6';
import { Counter, Gauge, Rate, Trend } from 'k6/metrics';

// Custom metrics
const sshConnectionDuration = new
  Trend('ssh_connection_duration_ms', true);
const sshConnectionErrors = new
  Counter('ssh_connection_errors_total');
const activeSSHSessions = new Gauge('ssh_active_sessions');
const sshAuthSuccessRate = new Rate('ssh_auth_success_rate');

export const options = {
  stages: [
    { duration: '2m', target: 1000 }, // Ramp up to 1,000
    { duration: '5m', target: 5000 }, // Ramp up to 5,000
    { duration: '10m', target: 10000 }, // Ramp up to 10,000
    { duration: '15m', target: 10000 }, // Hold at 10,000
    { duration: '3m', target: 0 }, // Ramp down
  ],
  thresholds: {
    'ssh_connection_duration_ms': [
      'p(50)<500', // 50th percentile < 500ms
      'p(95)<2000', // 95th percentile < 2 seconds
      'p(99)<5000', // 99th percentile < 5 seconds
    ],
    'ssh_auth_success_rate': ['rate>0.99'], // 99%+
      success
    'ssh_connection_errors_total': ['count<100'], // < 100
      errors total
    'http_req_failed': ['rate<0.01'], // API error
      rate < 1%
  }
};
```

```

    },
  };

const BASE_URL = __ENV.API_BASE_URL || 'https://staging-
  api.helixterminator.app';
const WS_URL = __ENV.WS_BASE_URL || 'wss://staging-
  ws.helixterminator.app';

// Pre-seeded test users and hosts for load test
const TEST_USERS = JSON.parse(open('./fixtures/
  load_test_users.json'));
const TEST_HOSTS = JSON.parse(open('./fixtures/
  load_test_hosts.json'));

function getTestUser(vu) {
  return TEST_USERS[vu % TEST_USERS.length];
}

function getTestHost(vu) {
  return TEST_HOSTS[vu % TEST_HOSTS.length];
}

export function setup() {
  // Warm up the API and pre-authenticate test users
  console.log('Load test setup: pre-authenticating test users');
  return { startTime: Date.now() };
}

export default function () {
  const user = getTestUser(__VU);
  const host = getTestHost(__VU);

  // Step 1: Authenticate
  const loginStart = Date.now();
  const loginResp = http.post(
    `${BASE_URL}/v1/auth/login`,
    JSON.stringify({
      email: user.email,
      password: user.password,
      device_id: `k6-vu-${__VU}-iter-${__ITER}`,
    }),
    { headers: { 'Content-Type': 'application/json' } }
  );

  const loginOK = check(loginResp, {
    'login status 200': (r) => r.status === 200,
  });

```

```

    'access token present': (r) =>
        JSON.parse(r.body).access_token !== undefined,
    });

    if (!loginOK) {
        sshConnectionErrors.add(1);
        return;
    }

    const { access_token } = JSON.parse(loginResp.body);

    // Step 2: Create SSH session
    const sessionStart = Date.now();
    const sessionResp = http.post(
        `${BASE_URL}/v1/sessions`,
        JSON.stringify({
            host_id: host.id,
            auth_type: 'password',
            password: host.password,
        }),
        {
            headers: {
                'Content-Type': 'application/json',
                'Authorization': `Bearer ${access_token}`,
            },
        }
    );

    const sessionOK = check(sessionResp, {
        'session created 201': (r) => r.status === 201,
        'session_id present': (r) => JSON.parse(r.body).session_id !==
            undefined,
        'websocket_url present': (r) =>
            JSON.parse(r.body).websocket_url !== undefined,
    });

    if (!sessionOK) {
        sshConnectionErrors.add(1);
        sshAuthSuccessRate.add(false);
        return;
    }

    const { session_id, websocket_url } =
        JSON.parse(sessionResp.body);
    const connectionTime = Date.now() - sessionStart;
    sshConnectionDuration.add(connectionTime);

```



```

sshAuthSuccessRate.add(true);
activeSSHSessions.add(1);

// Step 3: Open WebSocket and interact
const wsResp = ws.connect(
  `${WS_URL}/v1/sessions/${session_id}/terminal`,
  { headers: { 'Authorization': `Bearer ${access_token}` } },
  function (socket) {
    socket.on('open', () => {
      // Send a simple command
      socket.send(JSON.stringify({ type: 'input', data: 'echo
"k6-load-test"\n' }));
    });

    socket.on('message', (data) => {
      const msg = JSON.parse(data);
      if (msg.type === 'output' && msg.data.includes('k6-load-
test')) {
        socket.close();
      }
    });

    socket.on('error', (e) => {
      sshConnectionErrors.add(1);
    });

    socket.setTimeout(() => { socket.close(); }, 10000);
  }
);

check(wsResp, {
  'websocket connected': (r) => r && r.status === 101,
});

// Disconnect session
http.post(
  `${BASE_URL}/v1/sessions/${session_id}/disconnect`,
  null,
  { headers: { 'Authorization': `Bearer ${access_token}` } }
);

activeSSHSessions.add(-1);
sleep(Math.random() * 2 + 1); // Random think time: 1-3 seconds
}

```

```

export function teardown(data) {
  console.log(`Load test completed. Duration: ${Date.now() -
    data.startTime}ms`);
}

```

5.1.2 Vault Sync — 100,000 Items Across 1,000 Users

```

// k6/vault_sync_load.js
import http from 'k6/http';
import { check, sleep } from 'k6';
import { Trend, Counter, Rate } from 'k6/metrics';

const vaultSyncDuration = new Trend('vault_sync_duration_ms',
  true);
const vaultSyncErrors = new Counter('vault_sync_errors_total');
const vaultSyncItemsPerSec = new
  Counter('vault_sync_items_total');

export const options = {
  scenarios: {
    vault_sync_ramp: {
      executor: 'ramping-vus',
      stages: [
        { duration: '1m', target: 100 },
        { duration: '5m', target: 1000 },
        { duration: '10m', target: 1000 },
        { duration: '2m', target: 0 },
      ],
    },
  },
  thresholds: {
    'vault_sync_duration_ms': [
      'p(95)<3000', // 95% of syncs complete within 3 seconds
      'p(99)<8000', // 99% within 8 seconds
    ],
    'vault_sync_errors_total': ['count<50'],
    'http_req_failed': ['rate<0.005'],
  },
};

const BASE_URL = __ENV.API_BASE_URL || 'https://staging-
  api.helixterminator.app';
const TEST_USERS = JSON.parse(open('./fixtures/
  vault_load_test_users.json'));

export default function () {

```

```

const user = TEST_USERS[__VU % TEST_USERS.length];

// Authenticate
const loginResp = http.post(
  `${BASE_URL}/v1/auth/login`,
  JSON.stringify({ email: user.email, password: user.password,
    device_id: `k6-${__VU}` }),
  { headers: { 'Content-Type': 'application/json' } }
);
if (!check(loginResp, { 'login ok': (r) => r.status === 200 }))
{
  vaultSyncErrors.add(1);
  return;
}
const { access_token } = JSON.parse(loginResp.body);

// Sync vault – simulate device requesting delta since last sync
const syncStart = Date.now();
const syncResp = http.get(
  `${BASE_URL}/v1/vaults/sync?
    last_synced_at=2026-01-01T00:00:00Z`,
  {
    headers: {
      'Authorization': `Bearer ${access_token}`,
      'Accept': 'application/json',
    },
  },
);

const syncDuration = Date.now() - syncStart;

const syncOK = check(syncResp, {
  'sync status 200': (r) => r.status === 200,
  'entries array present': (r) =>
    Array.isArray(JSON.parse(r.body).entries),
});

if (!syncOK) {
  vaultSyncErrors.add(1);
  return;
}

const { entries } = JSON.parse(syncResp.body);
vaultSyncDuration.add(syncDuration);
vaultSyncItemsPerSec.add(entries.length);

```

```
    sleep(0.5);  
}
```

5.1.3 API Gateway — High Throughput Test

```
// k6/api_gateway_throughput.js  
import http from 'k6/http';  
import { check } from 'k6';  
import { Rate, Counter, Trend } from 'k6/metrics';  
  
const requestRate = new Counter('total_requests');  
const errorRate = new Rate('error_rate');  
const apiLatency = new Trend('api_latency_ms', true);  
  
export const options = {  
  scenarios: {  
    constant_arrival_rate: {  
      executor: 'constant-arrival-rate',  
      rate: 10000,           // 10,000 requests per second  
      timeUnit: '1s',  
      duration: '10m',  
      preAllocatedVUs: 500,  
      maxVUs: 2000,  
    },  
  },  
  thresholds: {  
    'api_latency_ms': [  
      'p(50)<20',    // Median latency < 20ms  
      'p(95)<100',   // 95th percentile < 100ms  
      'p(99)<500',   // 99th percentile < 500ms  
    ],  
    'error_rate': ['rate<0.001'], // Error rate < 0.1%  
  },  
};  
  
const BASE_URL = __ENV.API_BASE_URL || 'https://staging-  
api.helixterminator.app';  
const AUTH_TOKEN = __ENV.LOAD_TEST_TOKEN;  
  
export default function () {  
  const start = Date.now();  
  
  // Mix of typical API operations  
  const scenario = __ITER % 10;
```

```

let resp;
switch (scenario) {
  case 0:
  case 1:
  case 2:
    // 30% – List hosts (GET, cacheable)
    resp = http.get(`${BASE_URL}/v1/hosts`, {
      headers: { 'Authorization': `Bearer ${AUTH_TOKEN}` },
    });
    break;

  case 3:
  case 4:
    // 20% – Get vault entries
    resp = http.get(`${BASE_URL}/v1/vaults/current/entries?
      limit=20`, {
      headers: { 'Authorization': `Bearer ${AUTH_TOKEN}` },
    });
    break;

  case 5:
  case 6:
    // 20% – Session status check
    resp = http.get(`${BASE_URL}/v1/sessions/active`, {
      headers: { 'Authorization': `Bearer ${AUTH_TOKEN}` },
    });
    break;

  case 7:
    // 10% – Token refresh
    resp = http.post(`${BASE_URL}/v1/auth/refresh`,
      JSON.stringify({ refresh_token: __ENV.REFRESH_TOKEN }),
      { headers: { 'Content-Type': 'application/json' } }
    );
    break;

  case 8:
    // 10% – Health check (should be sub-5ms)
    resp = http.get(`${BASE_URL}/health`);
    break;

  case 9:
    // 10% – User profile

```

```

    resp = http.get(`${BASE_URL}/v1/users/me`, {
      headers: { 'Authorization': `Bearer ${AUTH_TOKEN}` },
    });
    break;
  }

  const latency = Date.now() - start;
  requestRate.add(1);
  apiLatency.add(latency);

  const ok = check(resp, {
    'status 2xx': (r) => r.status >= 200 && r.status < 300,
  });

  if (!ok) {
    errorRate.add(1);
  }
}

```

5.1.4 WebSocket Concurrent Sessions Test

```

// k6/websocket_concurrent.js
import ws from 'k6/ws';
import { check, sleep } from 'k6';
import { Gauge, Counter, Trend } from 'k6/metrics';

const activeConnections = new Gauge('ws_active_connections');
const wsConnectTime = new Trend('ws_connect_duration_ms', true);
const wsMessageLatency = new Trend('ws_message_latency_ms', true);
const wsErrors = new Counter('ws_errors_total');

export const options = {
  scenarios: {
    websocket_load: {
      executor: 'ramping-vus',
      stages: [
        { duration: '5m', target: 10000 }, // 10k concurrent
        // WebSocket connections
        { duration: '20m', target: 100000 }, // Ramp to 100k
        { duration: '10m', target: 100000 }, // Hold at 100k
        { duration: '5m', target: 0 },
      ],
    },
  },
},

```

```

thresholds: {
  'ws_connect_duration_ms': ['p(95)<1000'],
  'ws_message_latency_ms': ['p(95)<50'], // Terminal output
    latency < 50ms p95
  'ws_errors_total': ['count<500'],
},
};

const WS_URL = __ENV.WS_BASE_URL || 'wss://staging-
  ws.helixterminator.app';
const TEST_SESSIONS = JSON.parse(open('./fixtures/
  pre_created_sessions.json'));

export default function () {
  const session = TEST_SESSIONS[__VU % TEST_SESSIONS.length];
  const connectStart = Date.now();

  const res = ws.connect(
    `${WS_URL}/v1/sessions/${session.id}/terminal`,
    { headers: { 'Authorization': `Bearer ${session.token}` } },
    function (socket) {
      const connectTime = Date.now() - connectStart;
      wsConnectTime.add(connectTime);
      activeConnections.add(1);

      let messageCount = 0;

      socket.on('open', () => {
        // Send keepalive every 30 seconds
        socket.setInterval(() => {
          socket.send(JSON.stringify({ type: 'ping' }));
        }, 30000);

        // Send a test command
        const sendTime = Date.now();
        socket.send(JSON.stringify({ type: 'input', data:
          'date\n' }));

        socket.on('message', (data) => {
          const msg = JSON.parse(data);
          if (msg.type === 'output') {
            const msgLatency = Date.now() - sendTime;
            wsMessageLatency.add(msgLatency);
            messageCount++;
          }
          if (msg.type === 'pong') {

```

```

        // Keepalive acknowledged
    }
    });
});

socket.on('error', (e) => {
    wsErrors.add(1);
});

// Hold connection open to simulate real user session
socket.setTimeout(() => {
    socket.close();
    activeConnections.add(-1);
}, 60000 + Math.random() * 120000); // 1-3 minute sessions
}
);

check(res, { 'ws upgrade ok': (r) => r && r.status === 101 });
}

```

5.1.5 Terminal Throughput Test

```

// k6/terminal_throughput.js
import ws from 'k6/ws';
import { check } from 'k6';
import { Trend, Counter } from 'k6/metrics';

const bytesReceived = new
    Counter('terminal_bytes_received_total');
const throughputPerSession = new
    Trend('terminal_throughput_kbps', true);

export const options = {
    vus: 100,
    duration: '5m',
    thresholds: {
        'terminal_throughput_kbps': ['avg>100'], // Average 100 KB/s
            per session
        'terminal_bytes_received_total': ['count>52428800'], // 50MB
            total
    },
};

const WS_URL = __ENV.WS_BASE_URL || 'wss://staging-
    ws.helixtermininator.app';

```



```

const TEST_SESSIONS = JSON.parse(open('./fixtures/
    pre_created_sessions.json'));

export default function () {
    const session = TEST_SESSIONS[__VU % TEST_SESSIONS.length];
    const startTime = Date.now();
    let totalBytes = 0;

    ws.connect(
        `${WS_URL}/v1/sessions/${session.id}/terminal`,
        { headers: { 'Authorization': `Bearer ${session.token}` } },
        function (socket) {
            socket.on('open', () => {
                // Generate heavy terminal output (e.g., a long-running
                // find command)
                socket.send(JSON.stringify({
                    type: 'input',
                    data: 'dd if=/dev/urandom bs=1024 count=10240 |
                        base64\n',
                }));
            });

            socket.on('message', (data) => {
                const msg = JSON.parse(data);
                if (msg.type === 'output') {
                    const outputBytes = new
                        TextEncoder().encode(msg.data).length;
                    totalBytes += outputBytes;
                    bytesReceived.add(outputBytes);
                }
            });

            socket.setTimeout(() => {
                const duration = (Date.now() - startTime) / 1000; //
                    seconds
                const kbps = (totalBytes / 1024) / duration;
                throughputPerSession.add(kbps);
                socket.close();
            }, 30000);
        }
    );
}

```

5.2 Go Benchmark Tests

```
// services/sshproxy/bench_test.go
package sshproxy_test

import (
    "crypto/rand"
    "testing"

    gossh "golang.org/x/crypto/ssh"
    "github.com/HelixDevelopment/helixterminator/services/sshproxy"
)

func BenchmarkSSHProxy_HostKeyFingerprint_SHA256(b *testing.B) {
    _, pubKey, _ := gossh.GenerateKey(rand.Reader,
        gossh.InsecureIgnoreHostKey())
    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _ = gossh.FingerprintSHA256(pubKey)
    }
}

func BenchmarkSSHProxy_ParseAuthorizedKey(b *testing.B) {
    authorizedKey := "ssh-ed25519
        AAAAC3NzaC1lZDI1NTE5AAAAIXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
        bench@test"
    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _, _, _, _, _ =
            gossh.ParseAuthorizedKey([]byte(authorizedKey))
    }
}

// services/auth/bcrypt_bench_test.go
package auth_test

import (
    "testing"
    "golang.org/x/crypto/bcrypt"
)

func BenchmarkBcrypt_Cost10(b *testing.B) {
    b.ResetTimer()
    for i := 0; i < b.N; i++ {
```

```

        _, _ = bcrypt.GenerateFromPassword([]byte("test-
        password-2026!"), 10)
    }
}

```

```

func BenchmarkBcrypt_Cost12(b *testing.B) {
    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        _, _ = bcrypt.GenerateFromPassword([]byte("test-
        password-2026!"), 12)
    }
}

```

```

// services/vault/aes_bench_test.go
package vault_test

```

```

import (
    "crypto/aes"
    "crypto/cipher"
    "crypto/rand"
    "io"
    "testing"
)

```

```

func BenchmarkAES256GCM_Encrypt_1KB(b *testing.B) {
    key := make([]byte, 32)
    _, _ = rand.Read(key)
    plaintext := make([]byte, 1024)
    _, _ = rand.Read(plaintext)

    block, _ := aes.NewCipher(key)
    gcm, _ := cipher.NewGCM(block)

    b.SetBytes(int64(len(plaintext)))
    b.ResetTimer()
    for i := 0; i < b.N; i++ {
        nonce := make([]byte, gcm.NonceSize())
        _, _ = io.ReadFull(rand.Reader, nonce)
        _ = gcm.Seal(nonce, nonce, plaintext, nil)
    }
}

```

```

func BenchmarkAES256GCM_Encrypt_64KB(b *testing.B) {
    key := make([]byte, 32)
    _, _ = rand.Read(key)

```

```

plaintext := make([]byte, 64*1024)
_, _ = rand.Read(plaintext)

block, _ := aes.NewCipher(key)
gcm, _ := cipher.NewGCM(block)

b.SetBytes(int64(len(plaintext)))
b.ResetTimer()
for i := 0; i < b.N; i++ {
    nonce := make([]byte, gcm.NonceSize())
    _, _ = io.ReadFull(rand.Reader, nonce)
    _ = gcm.Seal(nonce, nonce, plaintext, nil)
}
}

```

5.3 Terminal-Rendering Performance Test Methodology (Flutter Client)

The product roadmap treats five terminal-rendering properties as **contractual SLOs** — 60fps scroll, <16ms keystroke-to-render latency, vttest conformance, Impeller GPU-memory ceiling, and per-platform cold-start budgets. Prior to this section no test methodology existed for any of the five; Flutter tests in this document were functional/widget-level only (flutter_test WidgetTester, no frame-timing instrumentation). This subsection defines, per SLO: the instrumentation used, the exact procedure, and the numeric pass threshold.

5.3.1 60fps Scroll / Render Test

Instrumentation: flutter drive + flutter_driver’s Timeline API (traceAction), post-processed with flutter_driver’s TimelineSummary, which is the first-party Flutter tool for frame-build/frame-raster timing (no third-party dependency required).

Procedure: 1. Launch the terminal client in --profile mode (never --debug — debug builds disable the Skia/Impeller frame-timing fast path and produce unrepresentative numbers). 2. Drive a synthetic terminal session emitting 10,000 lines of mixed ANSI output (256-color text, cursor-movement escapes, a top-style redrawing pane) at the PTY’s native write rate. 3. Perform a programmatic fling-scroll gesture

(driver.scroll(..., duration: 300ms)) across the full 10,000-line scrollbar, 20 repetitions. 4. Capture the Timeline for the full drive, summarize with TimelineSummary.summarizeToJson().

Pass threshold: average_frame_build_time_millis **and** 90th_percentile_frame_rasterizer_time_millis MUST both stay $\leq$ 16.67ms (the 60fps frame budget); missed_frame_build_budget_count MUST be 0 across all 20 repetitions on every Tier-1 device (\$4.4). A single missed-frame-budget event on a Tier-1 device is a FAIL, not an average-tolerant metric — dropped frames are perceptible to the end user as stutter regardless of the mean.

```
// test_driver/terminal_scroll_perf_test.dart
import 'dart:convert';
import 'dart:io';

import 'package:flutter_driver/flutter_driver.dart';
import 'package:test/test.dart';

void main() {
  group('Terminal 60fps scroll', () {
    late FlutterDriver driver;

    setUpAll(() async {
      driver = await FlutterDriver.connect();
    });

    tearDownAll(() async {
      await driver.close();
    });

    test('scrolling 10k-line scrollbar stays within the 60fps budget', () async {
      await driver.requestData('load_synthetic_10k_line_session');

      final timeline = await driver.traceAction(() async {
        for (var i = 0; i < 20; i++) {
          await driver.scroll(
            find.byValueKey('terminal-scrollbar'),
            0,
            -4000,
            const Duration(milliseconds: 300),
          );
        }
      });
    });
  });
}
```

```

final summary = TimelineSummary.summarize(timeline);
await summary.writeSummaryToFile('terminal_scroll_perf',
    pretty: true);
await summary.writeTimelineToFile('terminal_scroll_perf',
    pretty: true);

final json = jsonDecode(await File(
    'build/terminal_scroll_perf.timeline_summary.json')
    .readAsString()) as Map<String, dynamic>;

expect(json['average_frame_build_time_millis'],
    lessThanOrEqualTo(16.67));
expect(json['90th_percentile_frame_rasterizer_time_millis'],
    lessThanOrEqualTo(16.67));
expect(json['missed_frame_build_budget_count'], equals(0));
});
});
}

```

5.3.2 Keystroke-to-Render Latency (<16ms)

Instrumentation: a synthetic-input harness measuring wall-clock delta between the PTY write syscall (write(2) on the pseudo-terminal master) and the corresponding SchedulerBinding.

instance.addPostFrameCallback firing for the frame that painted the resulting glyph — the end-to-end path a real keystroke takes (PTY → terminal-emulation parser → Flutter widget rebuild → raster → present).

Procedure: inject 500 single-character keystrokes at a fixed 50ms inter-key interval (below human fast-typing rate, so no two keystrokes coalesce into one frame) into a live SSH-proxied PTY session, timestamping the write(2) call and the next addPostFrameCallback firing for each.

Pass threshold: p50 latency $\leq$ 8ms, p99 latency $\leq$ 16ms, across all 500 samples on every Tier-1 device (§4.4). A device whose p99 exceeds the 16ms budget is a FAIL for that device row.

```

// e2e/keystroke_latency_test.go
//go:build e2e

```

```

package e2e_test

```

```

import (

```

```

"sort"
"testing"
"time"

"github.com/stretchr/testify/require"
)

func TestE2E_KeystrokeToRenderLatency(t *testing.T) {
    session := newE2ETerminalSession(t)
    defer session.Close()

    const sampleCount = 500
    latencies := make([]time.Duration, 0, sampleCount)

    for i := 0; i < sampleCount; i++ {
        keyByte := byte('a' + (i % 26))
        writeTime := time.Now()
        session.WritePTY([]byte{keyByte})

        renderTime := session.WaitForNextPaintedFrame(t,
            100*time.Millisecond)
        latencies = append(latencies, renderTime.Sub(writeTime))

        time.Sleep(50 * time.Millisecond)
    }

    sort.Slice(latencies, func(i, j int) bool { return
        latencies[i] < latencies[j] })
    p50 := latencies[sampleCount/2]
    p99 := latencies[int(float64(sampleCount)*0.99)]

    require.LessOrEqualf(t, p50, 8*time.Millisecond,
        "p50 keystroke-to-render latency %v exceeds 8ms budget",
        p50)
    require.LessOrEqualf(t, p99, 16*time.Millisecond,
        "p99 keystroke-to-render latency %v exceeds 16ms budget",
        p99)
}

```

5.3.3 vttest Conformance

Instrumentation: `vttest` (the canonical VT100/VT220/ xterm conformance test suite), driven headlessly against the terminal-emulation core through the same PTY harness used in §5.3.2, with the

client's rendered screen buffer captured after each `vttest` screen and diffed against the suite's documented expected-output reference frames.

Procedure: run `vttest`'s automated/batch mode (menu selections 1, 2, 3, and 9 — cursor movement, screen features, character sets, and the ANSI reset test — the four menus with machine-checkable expected output) against the terminal emulation engine; capture the client's internal cell-grid model (not a pixel screenshot) after each screen and compare cell-by-cell against `vttest`'s documented expected grid.

Pass threshold: 100% cell-grid match on menus 1/2/3/9 — a single incorrect cell (wrong glyph, wrong SGR attribute, wrong cursor position) is a FAIL. `vttest` conformance is a correctness gate, not a performance one; it runs on the Nightly pipeline (gate 18, \$1.6) rather than every PR because a full menu sweep takes several minutes.

5.3.4 Impeller GPU-Memory Ceiling

Instrumentation: Flutter's `--enable-impeller` profile build + the Impeller GPU allocator's `ImpellerBackendType` telemetry, read via `flutter_driver`'s `getVMTimelineFlags / requestData('impeller_memory_snapshot')` bridge exposed by a debug-only VM-service extension the client registers in profile mode.

Procedure: open the maximum supported concurrent-session count (8 tabs, per the client's documented tab-limit) each running a distinct SSH session with active scrollback, then sample the Impeller GPU allocator's resident memory every 2 seconds for 60 seconds under steady-state scrolling load.

Pass threshold: peak Impeller GPU-resident memory $\leq$ 64MB across all 8 concurrent sessions on every Tier-1 mobile device (§4.4.1) — the ceiling the product doc commits to for memory-constrained mobile hardware. Desktop builds are exempt from the 64MB ceiling (tracked separately against platform RAM budgets) but MUST NOT exceed 256MB under the same 8-session load.

5.3.5 Per-Platform Cold-Start Budget

Instrumentation: platform-native cold-start timers — `flutter drive --trace-startup`'s `Start.timeToFirstFrameMicros` for the Flutter-measured portion, cross-checked against the OS-level launch timer

(Android `am start -W`, iOS `os_signpost` app-launch interval, desktop `XDG_ACTIVATION/process-start-to-first-frame` wall clock) so the budget covers OS process spawn, not just the Flutter engine’s internal clock.

Procedure: force-kill the app (cold, not warm/backgrounded), launch it, and measure wall clock to first interactive frame (host list rendered and tappable), 10 repetitions per device row.

Pass thresholds (p90 across 10 runs):

Platform Tier	Cold-Start Budget
iOS Tier-1 (18.1, A18 Pro)	$\leq 1.5s$
iOS Tier-2 min-supported (16.7, A15)	$\leq 2.5s$
Android Tier-1 (15, Tensor G4)	$\leq 1.8s$
Android Tier-2 low-end (12, Snapdragon 730G)	$\leq 3.5s$
Desktop (macOS/Windows/Linux, Tier-1)	$\leq 1.0s$
Web (Tier-1 browsers, first-contentful-paint to interactive)	$\leq 2.0s$

A device row exceeding its budget at p90 is a FAIL for that row and blocks the Release pipeline gate covering the full device/topology matrix (gate 24, §1.6).

6. Security Tests

6.1 Security Test Philosophy

Security tests in HelixTerminator are not purely negative tests (“does this fail?”) — they are *proof-of-control* tests. Each test must:

1. Demonstrate the **attack vector** is understood
2. Execute the attack with realistic parameters
3. Assert the **exact response** that proves the control is active (HTTP status code, error type, audit log entry)
4. Be linked to the relevant **CVE, OWASP Top 10 category, or CWE identifier**

6.2 Authentication Security Tests

```
// security/auth/brute_force_test.go
package auth_security_test

import (
    "fmt"
    "net/http"
    "net/http/httptest"
    "testing"
    "time"

    "github.com/HelixDevelopment/helixterminator/api/gateway"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

// TestSecurity_BruteForce_LoginLockout
// OWASP: A07:2021 - Identification and Authentication Failures
// CWE-307: Improper Restriction of Excessive Authentication
// Attempts
func TestSecurity_BruteForce_LoginLockout(t *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    email := "brute-force-target@example.com"
    server.CreateTestUser(t, email, "correct-password-not-used")

    // Attempt 5 rapid invalid logins
    for i := 0; i < 5; i++ {
        resp := loginRequest(t, server, email, fmt.Sprintf("wrong-
            password-%d", i))
        assert.Equal(t, http.StatusUnauthorized, resp.StatusCode)
    }

    // 6th attempt – must return 429 Too Many Requests (or 403
    // Locked)
    resp := loginRequest(t, server, email, "wrong-password-6th")
    assert.Equal(t, http.StatusTooManyRequests, resp.StatusCode,
        "account must be locked after 5 failed attempts (OWASP
        A07)")

    // Even with correct password, locked account must not
    // authenticate
    resp = loginRequest(t, server, email, "correct-password-not-
        used")
}
```

```

    assert.Equal(t, http.StatusForbidden, resp.StatusCode,
        "correct password must not bypass lockout")

    // Verify Retry-After header is present
    assert.NotEmpty(t, resp.Header.Get("Retry-After"),
        "Retry-After header must be set per RFC 7231")
}

// TestSecurity_JWT_AlgorithmConfusion_HS256NoneAttack
// CWE-347: Improper Verification of Cryptographic Signature
// References: CVE-2015-9235 (node-jwebtoken alg:none bypass)
func TestSecurity_JWT_AlgorithmConfusion_NoneAlgorithm(t
    *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    // Craft a JWT with alg:none
    noneToken := craftJWTWithAlgorithm(t, "none",
        map[string]interface{}{
            "sub": "usr_admin_01",
            "roles": []string{"admin"},
            "exp": time.Now().Add(1 * time.Hour).Unix(),
        })

    resp := apiRequest(t, server, "GET", "/v1/admin/users",
        noneToken)
    assert.Equal(t, http.StatusUnauthorized, resp.StatusCode,
        "JWT with alg:none MUST be rejected (CVE-2015-9235
        class)")
}

// TestSecurity_JWT_AlgorithmConfusion_RS256ToHS256
// Attack: Sign JWT with RS256 public key as HS256 secret
// References: Critical JWT vulnerability class
func TestSecurity_JWT_AlgorithmConfusion_RS256ToHS256(t
    *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    // Obtain the server's RS256 public key (publicly accessible)
    pubKey := server.GetPublicKey(t)

    // Sign a malicious token using the public key as HS256 secret
    maliciousToken := craftHS256TokenWithRSAPublicKey(t, pubKey,
        map[string]interface{}{
            "sub": "usr_victim_01",

```

```

        "roles": []string{"admin"},
        "exp":    time.Now().Add(1 * time.Hour).Unix(),
    })

    resp := apiRequest(t, server, "GET", "/v1/vaults",
        maliciousToken)
    assert.Equal(t, http.StatusUnauthorized, resp.StatusCode,

        "Algorithm confusion attack must be rejected – server must
        not accept HS256 when RS256 is configured")
}

// TestSecurity_JWT_Tampering_PayloadModification
func TestSecurity_JWT_Tampering_PayloadModification(t *testing.T)
{
    server := gateway.NewTestServer(t)
    defer server.Close()

    // Get a valid token for a regular user
    token := server.LoginTestUser(t, "regular-user@example.com",
        "password123")

    // Tamper the payload to escalate privileges
    tamperedToken := tamperJWTPayload(t, token,
        map[string]interface{}{
            "roles": []string{"admin"},
        })

    resp := apiRequest(t, server, "GET", "/v1/admin/users",
        tamperedToken)
    assert.Equal(t, http.StatusUnauthorized, resp.StatusCode,
        "Tampered JWT payload must be rejected due to signature
        validation failure")
}

// TestSecurity_SessionFixation
// CWE-384: Session Fixation
func TestSecurity_SessionFixation(t *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    // Step 1: Get a session token before authentication
    preAuthToken := server.GetPreAuthSessionToken(t)

    // Step 2: Login with the pre-auth session token injected
    resp := loginRequestWithSession(t, server,
        "user@example.com", "password123", preAuthToken)

```

```

require.Equal(t, http.StatusOK, resp.StatusCode)

// Step 3: The post-authentication session token MUST be
// different
postAuthToken := extractToken(t, resp)
assert.NotEqual(t, preAuthToken, postAuthToken,
    "Session fixation: token must be regenerated upon
    successful authentication (CWE-384)")
}

// TestSecurity_CSRF_APIProtection
// OWASP: A01:2021 - Broken Access Control (CSRF)
func TestSecurity_CSRF_StateChangingRequest_Rejected(t
    *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    token := server.LoginTestUser(t, "csrf-test@example.com",
        "password123")

    // State-changing request WITHOUT CSRF token from a different
    // origin
    req, _ := http.NewRequest("POST", server.URL+"/v1/hosts",
        strings.NewReader(`{"hostname":"attacker.com"}`))
    req.Header.Set("Content-Type", "application/json")
    req.Header.Set("Authorization", "Bearer "+token)
    req.Header.Set("Origin", "https://evil-attacker.com") //
    // Cross-origin

    client := &http.Client{}
    resp, err := client.Do(req)
    require.NoError(t, err)
    defer resp.Body.Close()

    assert.Equal(t, http.StatusForbidden, resp.StatusCode,
        "Cross-origin state-changing request must be rejected")
}

```

6.3 Authorization Security Tests

```

// security/authz/privilege_escalation_test.go
package authz_security_test

import (
    "net/http"
    "testing"

```

```

    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

// TestSecurity_IDOR_VaultAccess
// OWASP: A01:2021 - Broken Access Control
// CWE-639: Authorization Bypass Through User-Controlled Key
func TestSecurity_IDOR_VaultAccess(t *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    // Alice's vault
    aliceToken := server.LoginTestUser(t, "alice@example.com",
        "password123")
    aliceVaultID := server.CreateVaultForUser(t,
        "alice@example.com")

    // Bob tries to access Alice's vault directly by ID
    bobToken := server.LoginTestUser(t, "bob@example.com",
        "password123")
    resp := apiRequest(t, server, "GET",
        "/v1/vaults/"+aliceVaultID+"/entries", bobToken)

    assert.Equal(t, http.StatusForbidden, resp.StatusCode,
        "IDOR: User must not access another user's vault by
        guessing the vault ID (CWE-639)")

    // Verify the response does NOT reveal that the vault exists
    var body map[string]interface{}
    json.NewDecoder(resp.Body).Decode(&body)
    assert.NotContains(t, fmt.Sprint(body), aliceVaultID,
        "Error response must not confirm the existence of the
        target resource")

    _ = aliceToken
}

// TestSecurity_PrivilegeEscalation_RoleModification
// OWASP: A01:2021 - Broken Access Control
func TestSecurity_PrivilegeEscalation_SelfRolePromotion(t
    *testing.T) {
    server := gateway.NewTestServer(t)
    defer server.Close()

    userToken := server.LoginTestUser(t, "regular-
        user@example.com", "password123")

```

```

// Attempt to promote self to admin
resp := apiRequestWithBody(t, server, "PATCH", "/v1/users/me",
    map[string]interface{}{"role": "admin"}, userToken)

assert.Equal(t, http.StatusForbidden, resp.StatusCode,
    "Users must not be able to self-promote roles")
}

// TestSecurity_RBAC_TeamPermissionBoundary
func TestSecurity_RBAC_TeamPermissionBoundary(t *testing.T) {
    tests := []struct {
        name          string
        userRole       string
        operation       string
        resource        string
        expectedStatus int
    }{
        {"viewer_cannot_write", "viewer", "POST", "/v1/hosts",
            http.StatusForbidden},
        {"viewer_can_read", "viewer", "GET", "/v1/hosts",
            http.StatusOK},
        {"member_cannot_delete_team", "member", "DELETE", "/v1/teams/team_001",
            http.StatusForbidden},
        {"member_can_add_host", "member", "POST", "/v1/hosts",
            http.StatusCreated},
        {"admin_can_delete_host", "admin", "DELETE", "/v1/hosts/host_001",
            http.StatusNoContent},
        {"admin_cannot_delete_org", "admin", "DELETE", "/v1/organizations/org_001",
            http.StatusForbidden},
        {"owner_can_delete_team", "owner", "DELETE", "/v1/teams/team_001",
            http.StatusNoContent},
        {"billing_cannot_ssh", "billing", "POST", "/v1/sessions",
            http.StatusForbidden},
    }

    server := gateway.NewTestServer(t)
    defer server.Close()

    for _, tt := range tests {
        t.Run(tt.name, func(t *testing.T) {
            token := server.LoginTestUserWithRole(t, tt.userRole)
            resp := apiRequest(t, server, tt.operation,
                tt.resource, token)
            assert.Equal(t, tt.expectedStatus, resp.StatusCode,
                "RBAC boundary violation for role=%s
                operation=%s", tt.userRole, tt.operation)
        })
    }
}

```

```
}  
}
```

6.4 Cryptographic Security Tests

```
// security/crypto/vault_crypto_test.go  
package crypto_security_test  
  
import (  
    "crypto/rand"  
    "testing"  
  
    "github.com/HelixDevelopment/helixterminator/services/vault"  
    "github.com/stretchr/testify/assert"  
    "github.com/stretchr/testify/require"  
)  
  
// TestSecurity_VaultDecryption_WithoutKey_Fails  
// CWE-311: Missing Encryption of Sensitive Data  
func TestSecurity_VaultDecryption_WithoutKey_Fails(t *testing.T) {  
    svc := vault.NewBenchmarkService()  
  
    plaintext :=  
        []byte("ssh_password=super_secret_prod_password_2026")  
    key1 := make([]byte, 32)  
    _, _ = rand.Read(key1)  
  
    ciphertext, err := svc.Encrypt(plaintext, key1)  
    require.NoError(t, err)  
  
    // Try to decrypt with every possible single-byte key (trivial  
    // exhaustion)  
    for _, b := range []byte{0x00, 0xFF, 0x01, 0xAA, 0x55} {  
        weakKey := make([]byte, 32)  
        for i := range weakKey {  
            weakKey[i] = b  
        }  
        _, err := svc.Decrypt(ciphertext, weakKey)  
        assert.Error(t, err,  
  
            "AES-256-GCM must reject decryption with incorrect key  
            (GCM auth tag fails)")  
    }  
}
```



```

// TestSecurity_AES_IV_Uniqueness
// CWE-330: Use of Insufficiently Random Values
// Vulnerability: if IVs/nonces are reused with the same key, GCM
// provides no security
func TestSecurity_AES_IV_Uniqueness(t *testing.T) {
    svc := vault.NewBenchmarkService()

    key := make([]byte, 32)
    _, _ = rand.Read(key)

    nonces := make(map[string]bool)
    for i := 0; i < 10000; i++ {
        ciphertext, err := svc.Encrypt([]byte("test plaintext"),
            key)
        require.NoError(t, err)

        // Extract nonce (first 12 bytes of ciphertext in standard
        // GCM encoding)
        nonceHex := fmt.Sprintf("%x", ciphertext[:12])
        assert.False(t, nonces[nonceHex],
            "Nonce collision detected at iteration %d – IV
            generation is insecure (CWE-330)", i)
        nonces[nonceHex] = true
    }
}

```

```

// TestSecurity_WeakKeyGeneration_Rejected
func TestSecurity_WeakKeyGeneration_Rejected(t *testing.T) {
    svc := vault.NewBenchmarkService()

    weakKeys := [][]byte{
        make([]byte, 32), // all zeros
        bytes.Repeat([]byte{0xFF}, 32), // all 0xFF
        bytes.Repeat([]byte{0x01}, 32), // all 0x01
        []byte("password12345678901234567890123"), // ASCII
        "password" padded – 31 bytes
    }

    for _, key := range weakKeys {
        err := svc.ValidateKey(key)
        assert.Error(t, err,
            "Weak key must be rejected before use: %x", key)
    }
}

```

```

// TestSecurity_KeyDerivation_PBKDF2_MinIterations

```

```
// Ensuring KDF parameters meet minimum security requirements
func TestSecurity_KeyDerivation_MinimumIterations(t *testing.T) {
    kdf := vault.NewKeyDerivationFunction()
    params := kdf.GetParameters()

    assert.GreaterOrEqual(t, params.Iterations, 600000,
        "PBKDF2 iterations must be >= 600,000 (NIST SP 800-132
        recommendation for 2026)")
    assert.GreaterOrEqual(t, params.SaltLength, 16,
        "Salt must be at least 16 bytes (128 bits)")
    assert.Equal(t, "sha-512", params.HashFunction,
        "PBKDF2 must use SHA-512 for HelixTerminator")
}
```

6.5 SSH-Specific Security Tests

```
// security/ssh/ssh_security_test.go
package ssh_security_test

import (
    "testing"

    "github.com/HelixDevelopment/helixterminator/services/
        sshproxy"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
    gossh "golang.org/x/crypto/ssh"
)

// TestSecurity_SSH_WeakAlgorithm_MD5_Rejected
// CWE-327: Use of a Broken or Risky Cryptographic Algorithm
func TestSecurity_SSH_WeakAlgorithm_MD5_Rejected(t *testing.T) {
    config := sshproxy.BuildSSHClientConfig()

    // Verify deprecated/weak algorithms are NOT in the allowed
    // list
    for _, kex := range config.Config.KeyExchanges {
        assert.NotEqual(t, "diffie-hellman-group1-sha1", kex,
            "DH Group 1 with SHA-1 is cryptographically broken –
            must not be offered")
        assert.NotEqual(t, "diffie-hellman-group14-sha1", kex,
            "DH Group 14 with SHA-1 must not be offered per
            current NIST guidance")
    }

    for _, cipher := range config.Config.Ciphers {
```

```

    assert.NotEqual(t, "arcfour", cipher, "RC4 is broken and
    must be disabled")
    assert.NotEqual(t, "arcfour128", cipher)
    assert.NotEqual(t, "arcfour256", cipher)
    assert.NotEqual(t, "3des-cbc", cipher, "3DES must be
    disabled")
}

for _, mac := range config.Config.MACs {
    assert.NotEqual(t, "hmac-md5", mac, "HMAC-MD5 must be
    disabled")
    assert.NotEqual(t, "hmac-sha1", mac, "HMAC-SHA-1 must be
    disabled")
}
}

// TestSecurity_SSH_StrictHostKeyChecking
// Verifies that the SSH proxy NEVER silently accepts unknown host
// keys
// (TOFU without explicit user confirmation is prohibited)
func TestSecurity_SSH_StrictHostKeyChecking_NoAutoAccept(t
    *testing.T) {
    proxy := sshproxy.NewTestProxy(t)

    // Connect to a host with NO stored fingerprint
    err := proxy.ConnectToUnknownHost(t, "unknown-
    host.example.com:22")
    require.Error(t, err,
        "Proxy must reject connection to host with no stored
        fingerprint (no Trust-On-First-Use without explicit user
        action)")
    assert.ErrorIs(t, err, sshproxy.ErrUnknownHost)
}

// TestSecurity_SSH_MITM_Detection
// Verifies host key mismatch is detected and connection aborted
func TestSecurity_SSH_MITM_Detection(t *testing.T) {
    proxy := sshproxy.NewTestProxy(t)

    // Store a fingerprint for the host
    err := proxy.StoreHostFingerprint(t, "known-
    host.example.com", "SHA256:legit-fingerprint")
    require.NoError(t, err)

    // Simulate connecting and receiving a DIFFERENT fingerprint
    (MITM scenario)
    err = proxy.ConnectWithFingerprint(t, "known-
    host.example.com:22", "SHA256:attacker-mitm-fingerprint")

```

```

require.Error(t, err,
    "MITM detection: host key mismatch must abort the
    connection immediately")
assert.ErrorIs(t, err, sshproxy.ErrHostKeyMismatch)
}

// TestSecurity_SSH_AllowedAlgorithms_Positive
// Verify that ONLY approved algorithms are in the allowed list
func TestSecurity_SSH_AllowedAlgorithms_Positive(t *testing.T) {
    config := sshproxy.BuildSSHClientConfig()

    approvedKEX := map[string]bool{
        "curve25519-sha256":           true,
        "curve25519-sha256@libssh.org": true,
        "ecdh-sha2-nistp256":         true,
        "ecdh-sha2-nistp384":         true,
        "ecdh-sha2-nistp521":         true,
        "diffie-hellman-group-exchange-sha256": true,
        "diffie-hellman-group16-sha512": true,
        "diffie-hellman-group18-sha512": true,
    }

    for _, kex := range config.Config.KeyExchanges {
        assert.True(t, approvedKEX[kex],
            "KEX algorithm %q is not in the approved list", kex)
    }
}

```

6.6 Infrastructure Security Tests

```

// security/infra/k8s_network_policy_test.go
//go:build infrasecurity

package infra_security_test

import (
    "context"
    "fmt"
    "net/http"
    "testing"

    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
    metav1 "k8s.io/apimachinery/pkg/apis/meta/v1"

```

```

    "k8s.io/client-go/kubernetes"
)

// TestSecurity_K8s_NetworkPolicy_ServiceIsolation
// Verifies that Kubernetes NetworkPolicies enforce service
    isolation
func TestSecurity_K8s_NetworkPolicy_ServiceIsolation(t
    *testing.T) {
    k8s := newK8sClient(t)
    ctx := context.Background()

    // Get the auth service pod IP
    authPod := getServicePod(t, k8s, "helixterm", "auth-service")
    vaultPod := getServicePod(t, k8s, "helixterm", "vault-
        service")

    // Verify direct vault-auth communication is blocked (must go
        through gateway)
    // Execute a curl from vault pod to auth pod's internal port
    output, err := execInPod(ctx, k8s, vaultPod, "helixterm",
        []string{"curl", "--connect-timeout", "3", "-s",
            fmt.Sprintf("http://%s:8080/internal/health",
                authPod.Status.PodIP)})

    // Should timeout or be refused – direct service-to-service on
        internal port is blocked
    assert.Error(t, err, "NetworkPolicy must block direct
        vault-auth communication")
}

// TestSecurity_mTLS_Enforcement
// Verifies that all inter-service communication uses mutual TLS
func TestSecurity_mTLS_Enforcement(t *testing.T) {
    k8s := newK8sClient(t)
    ctx := context.Background()

    // Check Istio/Linkerd PeerAuthentication enforces STRICT mTLS
    pa := getMeshPeerAuthentication(t, k8s, "helixterm")
    require.NotNil(t, pa)

    for _, pa := range pa.Items {
        assert.Equal(t, "STRICT", pa.Spec.Mtls.Mode.String(),
            "PeerAuthentication %s must enforce STRICT mTLS
                mode", pa.Name)
    }
}

```

7. Contract Tests (Consumer-Driven)

7.1 Pact Framework Overview

HelixTerminator uses Pact for consumer-driven contract testing. The contract workflow is:

1. Consumer writes Pact test → generates pact file
2. Pact file is published to Pact Broker
(`pact.helixterminator.internal`)
3. Provider runs `pact:verify` in CI → fetches and validates contracts
4. Provider can NEVER publish a breaking change without notifying consumers first
5. "can-i-deploy" gate in CI checks all contracts pass before deployment

7.2 Client → Gateway Contract

```
// contracts/client_gateway_test.go
package contracts_test

import (
    "fmt"
    "net/http"
    "testing"

    "github.com/pact-foundation/pact-go/v2/consumer"
    "github.com/pact-foundation/pact-go/v2/matchers"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

func TestPact_ClientToGateway_Login(t *testing.T) {
    mockProvider, err :=
        consumer.NewV2Pact(consumer.MockHTTPProviderConfig{
            Consumer: "HelixTerminator-Client",
            Provider: "HelixTerminator-Gateway",
            LogDir:   "./pacts/logs",
            PactDir:  "./pacts",
        })
    require.NoError(t, err)

    mockProvider.
```

```

AddInteraction().
Given("a verified user account exists for
alice@example.com").
UponReceiving("a login request with valid credentials").
WithRequestPathMatcher("POST", "/v1/auth/login",
    matchers.MatchV2(map[string]interface{}{
        "email":      matchers.Like("alice@example.com"),
        "password":    matchers.Like("ValidPassword123!"),
        "device_id":   matchers.Like("dev-ios-001"),
    })),
).
WillRespondWith(http.StatusOK,
    matchers.MatchV2(map[string]interface{}{
        "access_token": matchers.Regex("^[A-Za-z0-9_-]+\
\\.[A-Za-z0-9_-]+\
\\.eyJhbGci.eyJzdWIi.SflKxwRj"),
        "refresh_token": matchers.Like("rt_abc123def456"),
        "user_id":        matchers.Regex("^usr_[A-Z0-9]{8}$", "usr_01J4KXYZ"),
        "mfa_required":   matchers.Like(false),
        "expires_in":     matchers.Integer(900),
    })),
)

err = mockProvider.ExecuteTest(t, func(config
consumer.MockServerConfig) error {
client := newTestGatewayClient(fmt.Sprintf("http://
localhost:%d", config.Port))

result, err := client.Login("alice@example.com",
"ValidPassword123!", "dev-ios-001")
if err != nil {
    return err
}

assert.NotEmpty(t, result.AccessToken)
assert.NotEmpty(t, result.RefreshToken)
assert.False(t, result.MFARequired)
return nil
})

require.NoError(t, err)
}

func TestPact_ClientToGateway_CreateVault(t *testing.T) {
mockProvider, err :=
consumer.NewV2Pact(consumer.MockHTTPProviderConfig{

```

```

        Consumer: "HelixTerminator-Client",
        Provider: "HelixTerminator-Gateway",
        PactDir:  "./pacts",
    })
    require.NoError(t, err)

    mockProvider.
        AddInteraction().
        Given("user usr_01J4KXYZ is authenticated").
        UponReceiving("a create vault request").
        WithRequestPathMatcher("POST", "/v1/vaults",
            matchers.MatchV2(map[string]interface{}{
                "name": matchers.Like("My Personal Vault"),
                "type": matchers.Term("personal", "^(personal|
team)$"),
            })),
        ).
        WillRespondWith(http.StatusCreated,
            matchers.MatchV2(map[string]interface{}{
                "vault_id": matchers.Regex("^vlt_[A-Za-z0-9]
{8}$", "vlt_abc12345"),
                "name": matchers.Like("My Personal Vault"),
                "type": matchers.Like("personal"),
                "created_at": matchers.Timestamp("yyyy-MM-
dd'T'HH:mm:ss.SSSX", "2026-06-28T10:00:00.000Z"),
            })),
        )

    err = mockProvider.ExecuteTest(t, func(config
consumer.MockServerConfig) error {
        client := newAuthenticatedTestClient(fmt.Sprintf("http://
localhost:%d", config.Port))
        vaultID, err := client.CreateVault("My Personal Vault",
"personal")
        if err != nil {
            return err
        }
        assert.NotEmpty(t, vaultID)
        return nil
    })
    require.NoError(t, err)
}

```


7.3 Gateway → Auth Service Contract

```
// contracts/gateway_auth_provider_test.go
package contracts_test

import (
    "testing"

    "github.com/pact-foundation/pact-go/v2/provider"
    "github.com/stretchr/testify/require"
)

// TestPact_GatewayToAuthService_Provider verifies the Auth
// service satisfies
// the contract published by the Gateway consumer.
func TestPact_GatewayToAuthService_Provider(t *testing.T) {
    verifier := provider.NewVerifier()

    err := verifier.VerifyProvider(t, provider.VerifyRequest{
        ProviderBaseURL: "http://localhost:8081", // Auth
        service test instance
        Provider:        "HelixTerminator-AuthService",
        BrokerURL:        "https://
        pact.helixterminator.internal",
        BrokerToken:      os.Getenv("PACT_BROKER_TOKEN"),
        PublishVerificationResults: os.Getenv("CI") == "true",
        ProviderVersion: os.Getenv("GIT_COMMIT"),
        ProviderTags:     []string{os.Getenv("BRANCH_NAME")},
        StateHandlers: provider.StateHandlers{
            "a verified user account exists for
            alice@example.com": func(setup bool, s
            provider.ProviderState) (provider.ProviderStateResponse,
            error) {
                if setup {
                    createTestUser(t, "alice@example.com",
                    "ValidPassword123!")
                }
                return nil, nil
            },
            "user account is locked": func(setup bool, s
            provider.ProviderState) (provider.ProviderStateResponse,
            error) {
                if setup {
                    lockTestUser(t, "locked@example.com")
                }
                return nil, nil
            },
        },
    })
}
```

```

    },
    RequestFilter: injectTestHeaders,
})

require.NoError(t, err)
}

```

7.4 SSH Proxy → PKI Service Contract

```

// contracts/sshproxy_pki_test.go
package contracts_test

import (
    "fmt"
    "net/http"
    "testing"

    "github.com/pact-foundation/pact-go/v2/consumer"
    "github.com/pact-foundation/pact-go/v2/matchers"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

func TestPact_SSHProxy_PKIService_IssueCertificate(t *testing.T) {
    mockProvider, err :=
        consumer.NewV2Pact(consumer.MockHTTPProviderConfig{
            Consumer: "HelixTerminator-SSHProxy",
            Provider: "HelixTerminator-PKIService",
            PactDir:  "./pacts",
        })
    require.NoError(t, err)

    mockProvider.
        AddInteraction().
        Given("CA key is available for signing").
        UponReceiving("a certificate signing request for user
usr_01J4KXYZ").
        WithRequestPathMatcher("POST", "/v1/pki/sign",
            matchers.MatchV2(map[string]interface{}{
                "user_id":      matchers.Like("usr_01J4KXYZ"),
                "public_key":   matchers.Regex("^ssh-ed25519 ",
"ssh-ed25519 AAAAC3Nz"),
                "ttl_seconds":  matchers.Integer(3600),
                "principals":
matchers.EachLike(matchers.Like("ubuntu"), 1),
            }

```

```

    }},
).
WillRespondWith(http.StatusOK,
    matchers.MatchV2(map[string]interface{}{
        "certificate": matchers.Regex("^ssh-ed25519-cert-
v01@openssh.com ", "ssh-ed25519-cert-v01@openssh.com
AAAAHHNza"),
        "serial":      matchers.Integer(1000),
        "valid_before": matchers.Integer(1800000000),
        "valid_after":  matchers.Integer(1700000000),
    }},
)

err = mockProvider.ExecuteTest(t, func(config
consumer.MockServerConfig) error {
    pkiClient := newPKIClient(fmt.Sprintf("http://localhost:
%d", config.Port))
    cert, err := pkiClient.SignCertificate("usr_01J4KXYZ",
"ssh-ed25519 AAAAC3Nz", 3600, []string{"ubuntu"})
    if err != nil {
        return err
    }
    assert.NotEmpty(t, cert.Certificate)
    return nil
})

require.NoError(t, err)
}

```

7.5 Audit Service Kafka Contract

```

// contracts/audit_kafka_consumer_test.go
package contracts_test

import (
    "testing"
    "time"

    "github.com/pact-foundation/pact-go/v2/consumer"
    "github.com/pact-foundation/pact-go/v2/matchers"
    "github.com/stretchr/testify/require"
)

func TestPact_AuditService_KafkaConsumer_SessionStartEvent(t
    *testing.T) {
    // Message Pact test for async Kafka communication

```

```

mockMsgProvider, err :=
    consumer.NewMessagePact(consumer.MessagePactConfig{
        Consumer: "HelixTerminator-AuditService",
        Provider: "HelixTerminator-SSHProxy",
        PactDir:  "./pacts",
    })
require.NoError(t, err)

mockMsgProvider.
    AddMessage().
    ExpectsToReceive("a session.start audit event from
        SSHProxy").
    WithMetadata(map[string]string{
        "content-type": "application/json",
        "kafka-topic":  "helix.audit.events",
    }).
    WithContent(matchers.MatchV2(map[string]interface{}{
        "event_type": matchers.Like("session.start"),
        "actor_id":   matchers.Regex("^usr_[A-Z0-9]{8}$",
            "usr_01J4KXYZ"),
        "target_id": matchers.Regex("^host_[a-z0-9]+$",
            "host_001"),
        "session_id": matchers.Regex("^sess_[A-Za-z0-9]{8}$",
            "sess_xyz789"),
        "timestamp": matchers.Timestamp("yyyy-MM-
            dd'T'HH:mm:ss'Z'", "2026-06-28T10:00:00Z"),
        "ip_address": matchers.IPv4Address(),
    }))).
    AsType(&domain.AuditEvent{})

err = mockMsgProvider.ExecuteTest(t, func(messages
    []consumer.MessageToVerify) error {
    for _, msg := range messages {
        var event domain.AuditEvent
        if err := json.Unmarshal(msg.Content, &event); err !=
            nil {
            return err
        }
        // Verify the audit service can process this event
        shape
        err := processAuditEvent(&event)
        if err != nil {
            return
        }
        fmt.Errorf("audit service failed to process event: %w",
            err)
    }
}
return nil

```

```

    })

    require.NoError(t, err)
}

```

7.6 Client → Vault Service Contract

Prior to this section, no Pact contract existed for the Vault Service — a Phase-1 core service (client-side end-to-end encrypted secret storage per CD-10). The contract covers the item-CRUD and crypto-metadata surface the Flutter client depends on; it does NOT assert on plaintext secret content (which the server never sees, per the zero-knowledge posture) — only on the ciphertext envelope shape, key-derivation metadata, and item-lifecycle status codes.

```

// contracts/client_vault_test.go
package contracts_test

import (
    "net/http"
    "testing"

    "github.com/pact-foundation/pact-go/v2/consumer"
    "github.com/pact-foundation/pact-go/v2/matchers"
    "github.com/stretchr/testify/require"
)

func TestPact_Client_VaultService_CreateItem(t *testing.T) {
    mockProvider, err :=
        consumer.NewV2Pact(consumer.MockHTTPProviderConfig{
            Consumer: "HelixTerminator-Client",
            Provider: "HelixTerminator-VaultService",
            PactDir:  "./pacts",
        })
    require.NoError(t, err)

    err = mockProvider.
        AddInteraction().
        Given("an authenticated user with an unlocked vault").
        UponReceiving("a request to create an encrypted vault
            item").
        WithRequest("POST", "/v1/vault/items", func(b
            *consumer.V2RequestBuilder) {
            b.Header("Authorization", matchers.Regex("Bearer .+",
                "Bearer eyJhbGciOi.."))
            b.JSONBody(matchers.Map{

```

```

        "ciphertext":
matchers.Like("base64:AAAA...=="),
        "nonce":          matchers.Regex("^\[A-Za-z0-9+/
={16,}$", "AAAAAAAAAAAAAAAA"),
        "kdf_algorithm":   matchers.Term("argon2id",
"argon2id|pbkdf2"),
        "kdf_iterations":  matchers.Integer(3),
        "item_type":       matchers.Term("ssh_key",
"ssh_key|password|note|totp_seed"),
    })
}).
WillRespondWith(201, func(b *consumer.V2ResponseBuilder) {
    b.JSONBody(matchers.Map{
        "id":          matchers.Regex("^vault_\[A-Za-z0-9]
{12}$", "vault_a1b2c3d4e5f6"),
        "created_at": matchers.Timestamp("yyyy-MM-
dd'T'HH:mm:ss'Z'", "2026-07-05T10:00:00Z"),
        "status":      matchers.Like("active"),
    })
})
require.NoError(t, err)

err = mockProvider.ExecuteTest(t, func(config
consumer.MockServerConfig) error {
    resp, reqErr := http.Post(
        config.Host+": "+string(rune(config.Port))+"/v1/vault/
items", "application/json", nil)
    if reqErr != nil {
        return reqErr
    }
    defer resp.Body.Close()
    return nil
})
require.NoError(t, err)
}

```

7.7 Client → Host/Group Service Contract

The Host/Group Service (host inventory, group membership, and per-group RBAC scoping) has no contract despite being on the critical path for every SSH session establishment — a client schema drift here would silently break host-list rendering or misattribute a host to the wrong access-control group.

```

// contracts/client_hostgroup_test.go
package contracts_test

```

```

import (
    "testing"

    "github.com/pact-foundation/pact-go/v2/consumer"
    "github.com/pact-foundation/pact-go/v2/matchers"
    "github.com/stretchr/testify/require"
)

func TestPact_Client_HostGroupService_ListHostsInGroup(t
    *testing.T) {
    mockProvider, err :=
        consumer.NewV2Pact(consumer.MockHTTPProviderConfig{
            Consumer: "HelixTerminator-Client",
            Provider: "HelixTerminator-HostGroupService",
            PactDir:  "./pacts",
        })
    require.NoError(t, err)

    err = mockProvider.
        AddInteraction().
        Given("a group 'production-db' with two member hosts
            exists").
        UponReceiving("a request to list hosts in a group").
        WithRequest("GET", "/v1/groups/production-db/hosts").
        WillRespondWith(200, func(b *consumer.V2ResponseBuilder) {
            b.JSONBody(matchers.EachLike(matchers.Map{
                "host_id":      matchers.Regex("^host_[a-z0-9]+
                $", "host_001"),
                "hostname":      matchers.Like("db-
                primary.internal"),
                "port":           matchers.Integer(22),
                "group_id":        matchers.Like("production-db"),
                "rbac_role_req":  matchers.Term("org_admin",
                "super_admin|org_admin|team_admin|member|auditor|
                api_user"),
                "last_seen_at":  matchers.Timestamp("yyyy-MM-
                dd'T'HH:mm:ss'Z'", "2026-07-05T09:55:00Z"),
            }, 2))
        })
    require.NoError(t, err)

    err = mockProvider.ExecuteTest(t, func(config
        consumer.MockServerConfig) error {
        return verifyHostGroupListing(config.Host, config.Port)
    })
    require.NoError(t, err)
}

```

7.8 Client → Recording Service Contract

Session recording (Compliance Mode’s “recording cannot be disabled by user” guarantee) has no contract covering the start/stop/status handshake the client must honor even when the end user attempts to suppress it — the exact boundary a client-side bug could silently violate.

```
// contracts/client_recording_test.go
package contracts_test

import (
    "testing"

    "github.com/pact-foundation/pact-go/v2/consumer"
    "github.com/pact-foundation/pact-go/v2/matchers"
    "github.com/stretchr/testify/require"
)

func TestPact_Client_RecordingService_SessionStartMandatory(t
    *testing.T) {
    mockProvider, err :=
        consumer.NewV2Pact(consumer.MockHTTPProviderConfig{
            Consumer: "HelixTerminator-Client",
            Provider: "HelixTerminator-RecordingService",
            PactDir:  "./pacts",
        })
    require.NoError(t, err)

    err = mockProvider.
        AddInteraction().
        Given("the target host's group has Compliance Mode
            enabled").
        UponReceiving("a session-start request for a compliance-
            mode host").
        WithRequest("POST", "/v1/recordings/sessions", func(b
            *consumer.V2RequestBuilder) {
            b.JSONBody(matchers.Map{
                "session_id": matchers.Regex("^sess_[A-Za-z0-9]
                {8}$", "sess_xyz789"),
                "host_id":      matchers.Regex("^host_[a-z0-9]+$",
                "host_001"),
            })
        }).
        WillRespondWith(201, func(b *consumer.V2ResponseBuilder) {
            b.JSONBody(matchers.Map{
```



```

        "recording_id":      matchers.Regex("^rec_[A-Za-
z0-9]{10}$", "rec_ab12cd34ef"),
        "compliance_mode":  matchers.Like(true),
        "user_disable_allowed": matchers.Like(false),
        "status":           matchers.Term("recording",
"recording|paused|stopped"),
    })
})
require.NoError(t, err)

err = mockProvider.ExecuteTest(t, func(config
consumer.MockServerConfig) error {
resp, reqErr := startRecordingSession(config.Host,
config.Port)
if reqErr != nil {
    return reqErr
}
// The consumer-side assertion the contract exists to
protect: a compliance-mode
// response MUST NOT permit the client to treat the
recording as user-disable-able.
if resp.UserDisableAllowed {
    return fmt.Errorf("compliance-mode recording must
never report user_disable_allowed=true")
}
return nil
})
require.NoError(t, err)
}

```

7.9 Client → SCIM/SAML SSO Contract

Enterprise SSO provisioning (SCIM user/group sync) and authentication (SAML ACS callback) are both scheduled Phase-1/2 boundaries with no contract today. This contract exercises the two integration points the client and gateway share: SCIM's /scim/v2/Users provisioning shape and the SAML ACS POST-back the gateway must parse and translate into a client-visible session.

```

// contracts/gateway_scim_saml_test.go
package contracts_test

import (
    "testing"

    "github.com/pact-foundation/pact-go/v2/consumer"
    "github.com/pact-foundation/pact-go/v2/matchers"

```

```

    "github.com/stretchr/testify/require"
)

func TestPact_Gateway_SCIMProvisioning_CreateUser(t *testing.T) {
    mockProvider, err :=
        consumer.NewV2Pact(consumer.MockHTTPProviderConfig{
            Consumer: "HelixTerminator-IdPSCIMClient",
            Provider: "HelixTerminator-Gateway-SCIM",
            PactDir:  "./pacts",
        })
    require.NoError(t, err)

    err = mockProvider.
        AddInteraction().
        Given("a SCIM bearer token is provisioned for tenant
            'acme-corp'").
        UponReceiving("a SCIM request to provision a new user").
        WithRequest("POST", "/scim/v2/Users", func(b
            *consumer.V2RequestBuilder) {
            b.Header("Authorization", matchers.Regex("Bearer .+",
                "Bearer scim-tok-abc123"))
            b.JSONBody(matchers.Map{
                "schemas":
                    matchers.EachLike("urn:ietf:params:scim:schemas:core:2.0:User",
                        1),
                "userName": matchers.Like("jane.doe@acme-
                    corp.example"),
                "active":    matchers.Like(true),
            })
        }).
        WillRespondWith(201, func(b *consumer.V2ResponseBuilder) {
            b.JSONBody(matchers.Map{
                "id":          matchers.Regex("^usr_[A-Z0-9]{8}$",
                    "usr_01J4KXYZ"),
                "userName": matchers.Like("jane.doe@acme-
                    corp.example"),
                "active":    matchers.Like(true),
                "meta": matchers.Map{
                    "resourceType": matchers.Like("User"),
                },
            })
        })
    require.NoError(t, err)

    err = mockProvider.ExecuteTest(t, func(config
        consumer.MockServerConfig) error {
        return provisionScimUser(config.Host, config.Port)
    })
}

```

```

        require.NoError(t, err)
    }

    func TestPact_Gateway_SAML_ACSCallback_TranslatesToSession(t
        *testing.T) {
        mockProvider, err :=
            consumer.NewV2Pact(consumer.MockHTTPProviderConfig{
                Consumer: "HelixTerminator-Gateway-SAML",
                Provider: "HelixTerminator-AuthService",
                PactDir:    "./pacts",
            })
        require.NoError(t, err)

        err = mockProvider.
            AddInteraction().
            Given("a valid SAML assertion for a federated user from
                IdP 'acme-corp-okta'").
            UponReceiving("a request to translate a validated SAML
                assertion into a session").
            WithRequest("POST", "/v1/auth/saml/session", func(b
                *consumer.V2RequestBuilder) {
                b.JSONBody(matchers.Map{
                    "idp_id":      matchers.Like("acme-corp-okta"),
                    "name_id":      matchers.Like("jane.doe@acme-
                        corp.example"),
                    "assertion_id": matchers.Regex("^_[a-f0-9-]
                        {36}$", "_a1b2c3d4-0000-0000-0000-000000000000"),
                })
            }).
            WillRespondWith(200, func(b *consumer.V2ResponseBuilder) {
                b.JSONBody(matchers.Map{
                    "access_token":
                        matchers.Like("eyJhbGciOiJIJZERTQSJ9..."),
                    "session_id":    matchers.Regex("^sess_[A-Za-z0-9]
                        {8}$", "sess_xyz789"),
                    "rbac_role":      matchers.Term("member",
                        "super_admin|org_admin|team_admin|member|auditor|
                        api_user"),
                })
            })
        require.NoError(t, err)

        err = mockProvider.ExecuteTest(t, func(config
            consumer.MockServerConfig) error {
            return exchangeSamlAssertionForSession(config.Host,
                config.Port)
        })
        require.NoError(t, err)
    }

```

8. Chaos Engineering

8.1 Chaos Engineering Framework

HelixTerminator uses [LitmusChaos](#) for structured chaos experiments. All experiments are defined as ChaosEngine and ChaosExperiment CRDs and run in the chaos-testing namespace against the staging environment.

Chaos Cadence: - Nightly: experiments 1–4 (individual component failures) - Weekly: experiments 5–7 (cascade failures) - Release gating: full suite

8.2 Chaos Experiment Definitions

8.2.1 Kill Random Service Pod

```
# chaos/experiments/pod-kill-sshproxy.yaml
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosEngine
metadata:
  name: sshproxy-pod-kill
  namespace: chaos-testing
spec:
  appinfo:
    appns: helixterm-staging
    applabel: "app=sshproxy"
    appkind: deployment
  chaosServiceAccount: litmus-admin
  experiments:
    - name: pod-delete
      spec:
        components:
          env:
            - name: TOTAL_CHAOS_DURATION
              value: "120"          # 2 minutes of chaos
            - name: CHAOS_INTERVAL
              value: "30"          # Kill a pod every 30 seconds
            - name: FORCE
              value: "false"       # Graceful termination first
            - name: PODS_AFFECTED_PERC
              value: "50"          # Kill 50% of SSH proxy pods
```

```

probe:
  # Steady-state hypothesis: active SSH sessions continue
  - name: active-sessions-probe
    type: httpProbe
    httpProbe/inputs:
      url: "https://staging-api.helixterminator.app/v1/sessions/active/count"
      insecureSkipVerify: false
      responseTimeout: 5000
      method:
        get:
          criteria: ">=0"
          responseCode: "200"
    mode: Continuous
    runProperties:
      probeTimeout: 10
      interval: 15
      stopOnFailure: false
  # Hypothesis: no increase in error rate during pod kill
  - name: error-rate-probe
    type: promProbe
    promProbe/inputs:
      endpoint: "http://prometheus.monitoring:9090"
      query: "rate(http_requests_total{status=~'5..'}[1m]) / rate(http_requests_total[1m])"
      comparator:
        type: float
        criteria: "<="
        value: "0.01" # Error rate must stay below 1%
    mode: Continuous
    runProperties:
      probeTimeout: 15
      interval: 30

```

```

# Hypothesis verification: after chaos, all pods must be Running
  within 60s
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosResult
metadata:
  name: sshproxy-pod-kill
  namespace: chaos-testing
spec:
  engine: sshproxy-pod-kill
  experiment: pod-delete

```

```
status:
  experimentStatus:
    phase: Completed
    verdict: Pass # Expected verdict
```

8.2.2 Kill All Kafka Brokers

```
# chaos/experiments/kafka-brokers-kill.yaml
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosEngine
metadata:
  name: kafka-all-brokers-kill
  namespace: chaos-testing
spec:
  appinfo:
    appns: helixterm-staging
    applabel: "app=kafka"
    appkind: statefulset
  experiments:
    - name: kafka-broker-pod-failure
      spec:
        components:
          env:
            - name: KAFKA_INSTANCE_NAME
              value: "helix-kafka"
            - name: KAFKA_NAMESPACE
              value: "helixterm-staging"
            - name: KAFKA_BROKER_LIST
              value: "helix-kafka-0, helix-kafka-1, helix-kafka-2"
            - name: KAFKA_CONSUMER_TIMEOUT
              value: "30000"
            - name: TOTAL_CHAOS_DURATION
              value: "180"
            - name: ZOOKEEPER_INSTANCE_NAME
              value: "helix-zookeeper"
        probe:
          # Hypothesis: messages are queued and not lost during
          # broker outage
          - name: message-queue-depth-probe
            type: promProbe
            promProbe/inputs:
              endpoint: "http://prometheus.monitoring:9090"
              query:
                "kafka_consumer_group_lag{topic='helix.audit.events'}"
              comparator:
```

```

        type: float
        criteria: ">="
        value: "0" # Queue depth increases (messages
being held) – not lost
        mode: Edge
        runProperties:
            probeTimeout: 30
            interval: 15
        # Hypothesis: after brokers recover, lag drains to 0
within 5 minutes
        - name: message-drain-probe
          type: promProbe
          promProbe/inputs:
            endpoint: "http://prometheus.monitoring:9090"
            query:
"kafka_consumer_group_lag{topic='helix.audit.events'}"
            comparator:
                type: float
                criteria: "=="
                value: "0"
          mode: EOT # Run at End of Test
          runProperties:
            probeTimeout: 300 # 5 minutes for drain
            interval: 30

```

```

# Post-chaos validation job
apiVersion: batch/v1
kind: Job
metadata:
  name: kafka-chaos-validation
  namespace: chaos-testing
spec:
  template:
    spec:
      containers:
        - name: validator
          image: ghcr.io/helixdevelopment/helixterminator/chaos-
validator:v1.0.0
          command:
            - /bin/sh
            - -c
            - |
# Verify no audit events were lost during the Kafka
outage
python3 /scripts/verify_kafka_no_message_loss.py \

```

```

--broker ${KAFKA_BROKER} \
--topic helix.audit.events \
--expected-count ${EXPECTED_MSG_COUNT} \
--tolerance 0 # ZERO tolerance for message loss
restartPolicy: Never

```

8.2.3 PostgreSQL Primary Failure

```

# chaos/experiments/postgres-primary-failover.yaml
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosEngine
metadata:
  name: postgres-primary-failover
  namespace: chaos-testing
spec:
  appinfo:
    appns: helixterm-staging
    applabel: "app=postgresql,role=primary"
    appkind: pod
  experiments:
    - name: pod-delete
      spec:
        components:
          env:
            - name: TOTAL_CHAOS_DURATION
              value: "300" # 5 minutes
            - name: FORCE
              value: "true" # Simulate hard crash (OOM kill /
node failure)
        probe:
          # SLO: API must continue serving reads within 30 seconds
          of primary failure
          - name: api-read-availability
            type: httpProbe
            httpProbe/inputs:
              url: "https://staging-api.helixterminator.app/
health/db"
            method:
              get:
                criteria: "=="
                responseCode: "200"
            mode: Continuous
          runProperties:
            probeTimeout: 5
            interval: 5

```



```

        initialDelaySeconds: 30 # Allow 30s for Patroni
replica promotion
        stopOnFailure: false
# SLO: Write operations must resume within 60 seconds
- name: api-write-availability
  type: httpProbe
  httpProbe/inputs:
    url: "https://staging-api.helixterminator.app/
health/db/write"
    method:
      get:
        criteria: "=="
        responseCode: "200"
  mode: Continuous
  runProperties:
    probeTimeout: 5
    interval: 10
    initialDelaySeconds: 60 # Allow 60s for full
failover
    stopOnFailure: false
# SLO: Total downtime < 30 seconds for reads, < 60
seconds for writes
- name: downtime-slo-probe
  type: promProbe
  promProbe/inputs:
    endpoint: "http://prometheus.monitoring:9090"
    query: "avg_over_time(up{job='postgres'}[5m])"
    comparator:
      type: float
      criteria: ">="
      value: "0.95" # 95% availability over 5-minute
window
  mode: EOT

```

8.2.4 Network Partition Between Services

```

# chaos/experiments/network-partition-auth-vault.yaml
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosEngine
metadata:
  name: network-partition-auth-vault
  namespace: chaos-testing
spec:
  appinfo:
    appns: helixterm-staging
    applabel: "app=auth-service"

```

```

  appkind: deployment
experiments:
  - name: pod-network-partition
    spec:
      components:
        env:
          - name: NETWORK_INTERFACE
            value: "eth0"
          - name: TOTAL_CHAOS_DURATION
            value: "120"
          - name: DESTINATION_IPS
            value: "${kubectl get svc vault-service -n
helixterm-staging -o jsonpath='{.spec.clusterIP}')"
          - name: DESTINATION_PORTS
            value: "8082"    # Vault service port
        probe:
          # Hypothesis: circuit breaker opens and returns graceful
          error
          - name: circuit-breaker-probe
            type: httpProbe
            httpProbe/inputs:
              url: "https://staging-api.helixterminator.app/v1/
vaults"
            method:
              get:
                criteria: "=="
                responseCode:
"503"    # Service Unavailable with circuit breaker open
            mode: Continuous
            runProperties:
              probeTimeout: 10
              interval: 15
              initialDelaySeconds: 10
          # Hypothesis: auth service itself continues to function
          - name: auth-service-health
            type: httpProbe
            httpProbe/inputs:
              url: "https://staging-api.helixterminator.app/v1/
auth/health"
            method:
              get:
                criteria: "=="
                responseCode: "200"
            mode: Continuous
            runProperties:

```

```
    probeTimeout: 5
    interval: 10
```

8.2.5 Memory Pressure and OOM Protection

```
# chaos/experiments/memory-pressure.yaml
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosEngine
metadata:
  name: sshproxy-memory-pressure
  namespace: chaos-testing
spec:
  appinfo:
    appns: helixterm-staging
    applabel: "app=sshproxy"
    appkind: deployment
  experiments:
    - name: pod-memory-hog
      spec:
        components:
          env:
            - name: MEMORY_CONSUMPTION
              value: "500" # Consume 500MB per pod
            - name: TOTAL_CHAOS_DURATION
              value: "120"
            - name: NUMBER_OF_WORKERS
              value: "2"
        probe:
          # Hypothesis: OOM protection activates before actual OOM
          kill
          - name: oom-protection-active
            type: promProbe
            promProbe/inputs:
              endpoint: "http://prometheus.monitoring:9090"
              query:
                "container_memory_working_set_bytes{pod=~'sshproxy.*'} /
                container_spec_memory_limit_bytes"
              comparator:
                type: float
                criteria: "<="
                value:
                  "0.90" # Memory usage must not exceed 90% of limit
              mode: Continuous
          # Hypothesis: rate limiting activates under memory
          pressure
          - name: rate-limiting-active
```

```

    type: httpProbe
    httpProbe/inputs:
      url: "https://staging-api.helixterminator.app/v1/
sessions"
      method:
        post:
          body: '{"host_id":"host_001"}'
          contentType: "application/json"
          criteria: "=="
          responseCode: "429"    # Rate limiting returns
429
    mode: Continuous
    runProperties:
      initialDelaySeconds: 30

```

8.2.6 CPU Saturation Test

```

# chaos/experiments/cpu-saturation.yaml
apiVersion: litmuschaos.io/v1alpha1
kind: ChaosEngine
metadata:
  name: api-gateway-cpu-saturation
  namespace: chaos-testing
spec:
  appinfo:
    appns: helixterm-staging
    applabel: "app=api-gateway"
    appkind: deployment
  experiments:
    - name: pod-cpu-hog
      spec:
        components:
          env:
            - name: CPU_CORES
              value: "2"
            - name: CPU_LOAD
              value: "95"    # 95% CPU load
            - name: TOTAL_CHAOS_DURATION
              value: "120"
        probe:
          # Hypothesis: p99 latency stays below 5 seconds even
          under CPU pressure
          - name: latency-slo-probe
            type: promProbe
            promProbe/inputs:

```

```

        endpoint: "http://prometheus.monitoring:9090"
        query: "histogram_quantile(0.99,
rate(http_request_duration_seconds_bucket{service='api-
gateway'}[1m]))"
        comparator:
            type: float
            criteria: "<="
            value: "5.0"      # p99 < 5 seconds
        mode: Continuous

```

8.3 Chaos Test Verification Script

```

#!/bin/bash
# scripts/verify_chaos_results.sh
# Run after each chaos experiment to verify recovery

set -euo pipefail

NAMESPACE=${1:-"helixterm-staging"}
EXPERIMENT=${2:-"all"}
TIMEOUT=${3:-"300"} # 5 minutes to recover

echo "Verifying chaos recovery for experiment: ${EXPERIMENT}"

# 1. Wait for all pods to be Running
kubectl wait pods \
    --all \
    --for=condition=Ready \
    --namespace="${NAMESPACE}" \
    --timeout="${TIMEOUT}s"
echo "✓ All pods Ready"

# 2. Verify API Gateway is healthy
for i in $(seq 1 10); do
    status=$(curl -s -o /dev/null -w "%{http_code}" \
        "https://staging-api.helixterminator.app/health")
    if [ "$status" = "200" ]; then
        echo "✓ API Gateway healthy (attempt ${i})"
        break
    fi
    if [ "$i" = "10" ]; then
        echo "x API Gateway not healthy after 10 attempts"
        exit 1
    fi
fi

```

```

    sleep 10
done

# 3. Verify database connectivity
kubectl exec -n "${NAMESPACE}" \
    "$(kubectl get pod -l app=auth-service -n "${NAMESPACE}" -o
        jsonpath='{.items[0].metadata.name}')" \
    -- curl -s http://localhost:8080/health/db | jq -r '.database'
    | grep -q "ok"
echo "✓ Database connectivity verified"

# 4. Verify Kafka lag has drained
KAFKA_LAG=$(kubectl exec -n "${NAMESPACE}" \
    "$(kubectl get pod -l app=kafka -n "${NAMESPACE}" -o
        jsonpath='{.items[0].metadata.name}')" \
    -- kafka-consumer-groups.sh --bootstrap-server localhost:9092 \
    --describe --group helix-audit-consumer | awk 'NR>1 {sum+=$5}
        END {print sum}')

if [ "${KAFKA_LAG}" = "0" ] || [ -z "${KAFKA_LAG}" ]; then
    echo "✓ Kafka consumer lag is zero"
else
    echo "✗ Kafka consumer lag is ${KAFKA_LAG} – messages may not
        have been processed"
    exit 1
fi

echo "All chaos recovery checks passed for experiment: $
    {EXPERIMENT}"

```

9. Mutation Testing

9.1 Overview

Mutation testing uses [go-mutesting](#) to verify that the test suite can detect code mutations. If a mutation is NOT killed by the test suite, it means either (a) the code path is not tested or (b) the assertion is too weak.

9.2 Mutation Operators Applied

Operator	Description	Example Mutation
ArithmeticOperator	Replaces arithmetic ops	$a + b \rightarrow a - b$
ArithmeticOperatorReplacement	Changes constants	$a > 5 \rightarrow a > 6$
RelationalOperator	Changes comparisons	$a > b \rightarrow a \geq b$
LogicalOperator	Flips logical ops	$\&\& \rightarrow \& \& $
ConditionalBoundary	Changes boundary conditions	$< n \rightarrow \leq n$
ReturnValue	Changes return values	$\text{return true} \rightarrow \text{return false}$
NullReturn	Returns zero value	$\text{return err} \rightarrow \text{return nil}$
IncrementDecrement	Flips ++/--	$i++ \rightarrow i--$
StatementDeletion	Removes a statement	Deletes return err check
NegateConditional	Negates conditions	$\text{if err == nil} \rightarrow \text{if err != nil}$

9.3 Configuration

```
# .go-mutesting.yaml
mutators:
  - ArithmeticOperator
  - ArithmeticOperatorReplacement
  - RelationalOperator
  - LogicalOperator
  - ConditionalBoundary
  - ReturnValue
  - NullReturn
  - IncrementDecrement
  - StatementDeletion
  - NegateConditional

# Packages to mutate – ordered by priority
```

```

packages:
- "github.com/HelixDevelopment/helixtermininator/services/auth"
- "github.com/HelixDevelopment/helixtermininator/services/vault"
- "github.com/HelixDevelopment/helixterminator/services/sshproxy"
- "github.com/HelixDevelopment/helixterminator/services/keychain"
- "github.com/HelixDevelopment/helixterminator/pkg/crypto"

# Exclude generated code, mocks, testdata
exclude:
- "**/*_mock.go"
- "**/*_generated.go"
- "**/testdata/**"
- "**/mocks/**"

# Minimum mutation score thresholds
thresholds:
  global: 80          # 80% global kill rate
  services/auth: 90   # 90% for auth (critical path)
  services/vault: 90  # 90% for vault (critical path)
  pkg/crypto: 100     # 100% for cryptographic core (zero tolerance)

timeout: 600 # 10 minutes maximum per package

```

9.4 CI Integration

```

# Makefile targets for mutation testing

.PHONY: mutation-test mutation-test-critical mutation-test-report

mutation-test:
  @echo "Running mutation tests (all packages)..."
  go-mutesting \
    --config .go-mutesting.yaml \
    --report-json testresults/mutation/results.json \
    --report-html testresults/mutation/report.html \
    ./services/... ./pkg/...
  @python3 scripts/check_mutation_score.py \
    --results testresults/mutation/results.json \
    --config .go-mutesting.yaml

mutation-test-critical:
  @echo "Running mutation tests for critical paths only..."

```



```

go-mutesting \
  --config .go-mutesting.yaml \
  --packages "github.com/HelixDevelopment/helixterminator/
             pkg/crypto,\
             github.com/HelixDevelopment/helixterminator/
             services/auth,\
             github.com/HelixDevelopment/helixterminator/
             services/vault" \
  --report-json testresults/mutation/critical.json
@python3 scripts/check_mutation_score.py \
  --results testresults/mutation/critical.json \
  --min-score 90

```

```

mutation-test-report:
  @echo "Generating mutation test report..."
  open testresults/mutation/report.html

```

9.5 Mutation Score Enforcement Script

```

#!/usr/bin/env python3
# scripts/check_mutation_score.py
"""Enforces minimum mutation kill scores defined in .go-
    mutesting.yaml"""

import json
import sys
import argparse
import yaml

def main():
    parser = argparse.ArgumentParser()
    parser.add_argument('--results', required=True)
    parser.add_argument('--config', default='.go-mutesting.yaml')
    parser.add_argument('--min-score', type=float, default=None)
    args = parser.parse_args()

    with open(args.results) as f:
        results = json.load(f)

    with open(args.config) as f:
        config = yaml.safe_load(f)

    thresholds = config.get('thresholds', {})
    global_threshold = thresholds.get('global', 80)
    if args.min_score is not None:

```

```

global_threshold = args.min_score

failed = []
for pkg, data in results.items():
    killed = data.get('killed', 0)
    total = data.get('total', 0)
    if total == 0:
        continue
    score = (killed / total) * 100

    # Check package-specific threshold
    pkg_short = pkg.replace('github.com/HelixDevelopment/
helixterminator/', '')
    threshold = thresholds.get(pkg_short, global_threshold)

    if score < threshold:
        failed.append({
            'package': pkg,
            'score': score,
            'threshold': threshold,
            'killed': killed,
            'survived': total - killed,
            'total': total,
        })
    else:
        print(f"✓ {pkg_short}: {score:.1f}% (threshold:
{threshold}%)")

if failed:
    print("\n× MUTATION SCORE FAILURES:")
    for f in failed:
        print(f"    {f['package']}")
        print(f"        Score: {f['score']:.1f}% (required:
{f['threshold']}%)")
        print(f"        Killed: {f['killed']}/{f['total']} -
{f['survived']} mutants survived")
    sys.exit(1)

print(f"\nAll mutation score thresholds met.")

if __name__ == '__main__':
    main()

```

10. HelixQA Integration

10.1 Architecture

The helixqa submodule integrates with HelixTerminator at multiple layers:

```
HelixTerminator
├── submodules/
│   └── helixqa/                                ← Git submodule at pinned
revision
│   ├── pkg/autonomous/                        ← SessionCoordinator,
PlatformWorker
│   ├── pkg/navigator/                         ← ActionExecutor (ADB,
Playwright, X11)
│   ├── pkg/issuedetector/                    ← LLM-powered bug detection
│   └── pkg/session/                          ← SessionRecorder,
VideoManager
│   └── pkg/evidence/                          ← Centralized evidence
collection
│   └── pkg/validator/                        ← Step-by-step validation with
evidence
│   ├── pkg/ticket/                          ← Markdown ticket generation
│   ├── pkg/reporter/                        ← QA report generation
│   └── pkg/planning/                        ← Test plan generation
├── .helixqa.yaml                             ← HelixQA configuration
└── Makefile                                  ← make qa-session, make
visual-regression
```

10.2 HelixQA Configuration

```
# .helixqa.yaml
version: "2"

# Platform targets
platforms:
  web:
    enabled: true
    url: "https://staging.helixterminator.app"
    executor: playwright
    browser: chromium
    headless: true
```

```
desktop:
  enabled: true
  executor: x11
  binary: "./build/linux/helixterminator"
  display: ":99"

android:
  enabled: true
  executor: adb
  device_serial: "${ANDROID_DEVICE_SERIAL}"
  apk: "./build/android/helixterminator.apk"

ios:
  enabled: false    # iOS runs on physical device farm only

# AI configuration
ai:
  llm_verifier: openai-gpt-4o
  issue_detector: claude-3-5-sonnet
  vision_engine: gpt-4o-vision

# Feature documentation for Doc-Driven Verification
doc_paths:
  - docs/features/
  - docs/user-guide/
  - CHANGELOG.md

# Evidence configuration
evidence:
  screenshots: true
  video: true
  video_format: mp4
  video_quality: high
  logs: true
  output_dir: testresults/helixqa/evidence/

# Report configuration
report:
  formats: [markdown, html, json]
  output_dir: testresults/helixqa/reports/
  include_video_timestamps: true
  publish_on_failure: true

# Anti-bluff enforcement (HelixConstitution §11.4)
```

```

anti_bluff:
  require_evidence_per_step: true
  fail_on_green_without_evidence: true
  audit_script: scripts/audit_antibluff.sh

# YAML test banks
test_banks:
  - path: testbanks/auth_tests.yaml
    priority: P0
    platforms: [web, desktop, android]
  - path: testbanks/ssh_session_tests.yaml
    priority: P0
    platforms: [web, desktop]
  - path: testbanks/vault_tests.yaml
    priority: P0
    platforms: [web, desktop, android]
  - path: testbanks/sftp_tests.yaml
    priority: P1
    platforms: [web, desktop]
  - path: testbanks/workspace_tests.yaml
    priority: P1
    platforms: [web, desktop]
  - path: testbanks/accessibility_tests.yaml
    priority: P1
    platforms: [web]

# Flaky test quarantine
flaky_detection:
  enabled: true
  min_runs: 10
  flaky_threshold: 0.05 # Mark as flaky if failure rate > 5%
  quarantine_on_flaky: true
  quarantine_issue_label: "flaky-test"
  quarantine_github_repo: "HelixDevelopment/helixterminator"

```

10.3 YAML Test Banks

```

# testbanks/auth_tests.yaml
name: "Authentication Tests"
version: "1.0"
description: "Comprehensive authentication flow tests"

tests:
  - id: AUTH-001

```

```
name: "Email/Password Login Success"
priority: P0
platforms: [web, desktop, android]
documentation_ref: "docs/features/authentication.md#email-
  login"
steps:
  - action: navigate
    target: "/"
    evidence: screenshot
  - action: fill
    selector: "[data-testid=email-input]"
    value: "${TEST_USER_EMAIL}"
  - action: fill
    selector: "[data-testid=password-input]"
    value: "${TEST_USER_PASSWORD}"
  - action: click
    selector: "[data-testid=login-button]"
    evidence: screenshot
  - action: waitForNavigation
    url_contains: "/dashboard"
    timeout_ms: 10000
  - action: assert
    selector: "[data-testid=user-avatar]"
    condition: visible
    evidence: screenshot
    failure_message: "User avatar must be visible after
      successful login"

- id: AUTH-002
  name: "Biometric Login (Mobile/Desktop)"
  priority: P0
  platforms: [android, desktop]
  documentation_ref: "docs/features/authentication.md#biometric"
  steps:
    - action: launchApp
      evidence: screenshot
    - action: assertVisible
      selector: "[data-testid=biometric-prompt]"
      evidence: screenshot
    - action: simulateBiometricSuccess
      evidence: video_clip
    - action: assert
      selector: "[data-testid=host-list]"
      condition: visible
```

```

        failure_message: "Host list must be visible after
        biometric authentication"

- id: AUTH-003
  name: "TOTP MFA Challenge"
  priority: P0
  platforms: [web, desktop]
  documentation_ref: "docs/features/authentication.md#mfa-totp"
  steps:
    - action: loginWithPassword
      email: "${MFA_TEST_USER_EMAIL}"
      password: "${MFA_TEST_USER_PASSWORD}"
    - action: assert
      selector: "[data-testid=mfa-challenge-screen]"
      condition: visible
      evidence: screenshot
    - action: fill
      selector: "[data-testid=totp-input]"
      value: "${TOTP_CODE}" # Injected by test harness from
      authenticator
    - action: click
      selector: "[data-testid=mfa-submit]"
    - action: assert
      selector: "[data-testid=dashboard]"
      condition: visible
      evidence: screenshot

```

10.4 AI-Driven Test Generation from OpenAPI Spec

```

// scripts/generate_tests_from_openapi.go
// +build tools

```

```

package main

```

```

import (
    "context"
    "encoding/json"
    "log"
    "os"

    "github.com/HelixDevelopment/helixterminator/submodules/
    helixqa/pkg/planning"
    "github.com/HelixDevelopment/helixterminator/submodules/
    helixqa/pkg/autonomous"
)

```

```

func main() {
    ctx := context.Background()

    // Load the OpenAPI specification
    specBytes, err := os.ReadFile("api/openapi.yaml")
    if err != nil {
        log.Fatalf("Failed to read OpenAPI spec: %v", err)
    }

    // Initialize the test plan generator
    planner := planning.NewTestPlanGenerator(planning.Config{
        LLM:          "gpt-4o",
        SpecFormat:   "openapi3",
        Platforms:    []string{"web", "desktop", "android"},
        Priorities:   []string{"P0", "P1", "P2"},
        OutputDir:    "testbanks/generated/",
        RuleSet:      "helixconstitution-v1",
    })

    // Generate test plans from the OpenAPI spec
    plans, err := planner.GenerateFromSpec(ctx, specBytes)
    if err != nil {
        log.Fatalf("Test plan generation failed: %v", err)
    }

    log.Printf("Generated %d test plans covering %d endpoints",
        len(plans), planner.EndpointCount())

    // Write to YAML test bank files
    for _, plan := range plans {
        outPath := "testbanks/generated/" + plan.Name + ".yaml"
        data, _ := json.MarshalIndent(plan, "", "  ")
        _ = os.WriteFile(outPath, data, 0644)
        log.Printf("Written: %s (%d tests)", outPath,
            len(plan.Tests))
    }

    // Verify test coverage against documented features
    docProcessor := autonomous.NewDocProcessor("docs/features/")
    coverage, err := docProcessor.VerifyCoverage(ctx, plans)
    if err != nil {
        log.Fatalf("Coverage verification failed: %v", err)
    }
}

```



```

log.Printf("Feature coverage: %.1f%%", coverage.Percentage)
if coverage.Percentage < 80.0 {
    log.Fatalf("Insufficient feature coverage: %.1f%%
        (required: 80%%)", coverage.Percentage)
}
}

```

10.5 Flaky Test Detection and Quarantine

```

// scripts/helixqa_flaky_detector.go
// +build tools

package main

import (
    "context"
    "log"
    "os"
    "time"

    "github.com/HelixDevelopment/helixterminator/submodules/
        helixqa/pkg/validator"
    helixqa "github.com/HelixDevelopment/helixterminator/
        submodules/helixqa"
)

func main() {
    ctx := context.Background()

    qa := helixqa.NewOrchestrator(helixqa.Config{
        Platform:    os.Getenv("HELIXQA_PLATFORM"),
        Mode:        helixqa.ModeFast,
        FlakyOpts: &helixqa.FlakyDetectionOptions{
            MinRuns:        10,
            Window:         7 * 24 * time.Hour,
            FlakyThreshold: 0.05,
            QuarantineOnFlaky: true,
            GitHubRepo:     "HelixDevelopment/
                helixterminator",
            GitHubToken:    os.Getenv("GITHUB_TOKEN"),
        },
    })

    report, err := qa.DetectFlakyTests(ctx,
        helixqa.FlakyDetectionRequest{

```

```

        TestResultsDir:    "testresults/",
        HistoricalRunsDir: "testresults/historical/",
        QuarantineFile:    ".helixqa-quarantine.yaml",
    })
    if err != nil {
        log.Fatalf("Flaky detection failed: %v", err)
    }

    log.Printf("Flaky test detection complete:")
    log.Printf("  Analyzed: %d tests", report.AnalyzedCount)
    log.Printf("  Flaky: %d tests (%.1f%%)", report.FlakyCount,
        report.FlakyRate*100)
    log.Printf("  Quarantined: %d tests", report.QuarantinedCount)
    log.Printf("  GitHub issues created: %d",
        report.IssuesCreated)

    if report.FlakyCount > 0 {
        log.Printf("\nFlaky tests detected:")
        for _, ft := range report.FlakyTests {
            log.Printf("  - %s (failure rate: %.1f%%, runs: %d)",
                ft.TestName, ft.FailureRate*100, ft.RunCount)
        }
    }
}

```

10.6 Coverage Report Generation and Publishing

```

#!/bin/bash
# scripts/generate_coverage_report.sh

set -euo pipefail

OUTPUT_DIR="testresults/coverage"
mkdir -p "${OUTPUT_DIR}"

# 1. Run all unit tests with coverage
go test \
    -v \
    -count=1 \
    -coverprofile="${OUTPUT_DIR}/coverage.out" \
    -covermode=atomic \
    ./services/... \
    ./pkg/...

# 2. Generate HTML report

```

```

go tool cover \
    -html="${OUTPUT_DIR}/coverage.out" \
    -o "${OUTPUT_DIR}/coverage.html"

# 3. Generate per-package summary
go tool cover \
    -func="${OUTPUT_DIR}/coverage.out" \
    | tee "${OUTPUT_DIR}/coverage.txt"

# 4. Check coverage thresholds
python3 scripts/check_coverage_thresholds.py \
    --profile "${OUTPUT_DIR}/coverage.out" \
    --config .coverage-thresholds.yaml

# 5. Publish to HelixQA coverage dashboard
if [ "${CI}" = "true" ]; then
    curl -X POST \
        "${HELIXQA_DASHBOARD_URL}/v1/coverage" \
        -H "Authorization: Bearer ${HELIXQA_API_KEY}" \
        -H "Content-Type: application/json" \
        -d @- <<EOF
{
    "project": "helixterminator",
    "branch": "${BRANCH_NAME}",
    "commit": "${GIT_COMMIT}",
    "coverage_file_url": "${ARTIFACT_BASE_URL}/coverage.out",
    "report_url": "${ARTIFACT_BASE_URL}/coverage.html"
}
EOF
fi

echo "Coverage report generated: ${OUTPUT_DIR}/coverage.html"

```

10.7 Native Accessibility Testing (VoiceOver / TalkBack / NVDA / JAWS)

The only accessibility coverage in this document prior to this section was testbanks/ accessibility_tests.yaml scoped to platforms: [web] (§10.3) plus the Release pipeline’s axe-core WCAG 2.2 AA audit (§11.4), both browser-only. The product doc’s own acceptance criteria (“Screen reader (VoiceOver / TalkBack) can navigate all auth screens”; Session Replay “screen reader compatible”) are native-platform requirements that axe-core cannot exercise — axe-core inspects the DOM, not the

iOS/Android accessibility tree or a desktop screen-reader's exposed UI Automation/AT-SPI tree. This subsection defines the native test procedures and acceptance criteria that close that gap.

10.7.1 iOS — VoiceOver

Instrumentation: XCTest's XCUIApplication accessibility APIs (`app.buttons.matching(...)`, `.isAccessibilityElement`, `.accessibilityLabel`, `.accessibilityLabel`) combined with the `XCTAssertAccessibleAndSensible`-style audit that Xcode's Accessibility Inspector exposes programmatically via `performAccessibilityAudit(for:)` (Xcode 15+), run against a Tier-1 iOS device (§4.4.1) with VoiceOver enabled via `xcrun simctl / device MDM` profile.

Procedure: 1. Enable VoiceOver on the target device (Settings > Accessibility > VoiceOver, or via the device farm's accessibility-service toggle API). 2. Drive the auth flow (login, MFA challenge, biometric prompt) and the SSH host-list screen using VoiceOver's swipe-navigation gesture sequence (`XCUIApplication.swipeRight()` chained across every focusable element), asserting each stop announces a non-empty, non-generic label. 3. Run `performAccessibilityAudit(for: app)` against every screen in the smoke-test flow; fail on any reported `.contrastRatio`, `.hitRegion`, `.dynamicType`, or `.textClipped` finding.

Acceptance criteria: every interactive control on the Auth, Vault-unlock, and SSH-session screens (a) is reachable via sequential VoiceOver swipe-navigation in tab order matching the visual reading order, (b) has a non-empty `accessibilityLabel` that is not the raw widget class name (e.g. not "Button", "TextField"), (c) announces its current state where applicable (a password field announces "secure text field", a toggle announces "on"/"off"), (d) produces zero `performAccessibilityAudit` findings of type `.contrastRatio`, `.hitRegion`, `.dynamicType`, or `.textClipped`.

```
// UITests/VoiceOverAuthFlowTests.swift
import XCTest
```

```
final class VoiceOverAuthFlowTests: XCTestCase {
    func testAuthScreenIsVoiceOverNavigable() throws {
        let app = XCUIApplication()
        app.launchArguments += ["--uitesting", "--voiceover-audit"]
        app.launch()
```

```

let emailField = app.textFields["auth.email_field"]
XCTAssertTrue(emailField.waitForExistence(timeout: 5))
XCTAssertFalse(emailField.label.isEmpty,
    "email field must expose a VoiceOver label")
XCTAssertNotEqual(emailField.label, "Text Field", "label
must not be the generic class name")

let passwordField =
    app.secureTextFields["auth.password_field"]
XCTAssertTrue(passwordField.exists)
XCTAssertTrue(passwordField.elementType
    == .secureTextField,
    "password field must expose the secure-
text-field trait to VoiceOver")

let loginButton = app.buttons["auth.login_button"]
XCTAssertTrue(loginButton.isEnabled)
XCTAssertFalse(loginButton.label.isEmpty)

if #available(iOS 17.0, *) {
    let auditIssues = try
        app.performAccessibilityAudit(for:
            [.contrast, .hitRegion, .dynamicType, .textClipped])
    XCTAssertTrue(auditIssues.isEmpty,
        "VoiceOver accessibility audit found \
(auditIssues.count) issue(s): \("\(auditIssues)")")
}
}
}

```

10.7.2 Android — TalkBack

Instrumentation: the Android Accessibility Test Framework

(AccessibilityChecks.enable()) wired into Espresso, plus UiAutomator's AccessibilityNodeInfo tree walk to assert TalkBack focus order and spoken content directly (rather than only checking that a node *has* a content description).

Procedure: 1. Enable the framework in the Espresso test rule:

AccessibilityChecks.enable().setRunChecksFromRootView(true), which fails any interaction against a view with a missing/duplicate content description, an under-sized touch target (< 48dp per Material a11y guidance), or insufficient contrast. 2. Walk the TalkBack linear-navigation order via UiAutomator.getRootInActiveWindow() recursively, asserting the traversal order matches the visual top-to-bottom, left-to-right reading order for the Auth and Host-List screens. 3. Assert every custom terminal-grid cell (the xterm-style cell renderer, which is a

custom Canvas-drawn view invisible to the default accessibility tree) exposes a synthesized `AccessibilityNodeInfo` via `View.onInitializeAccessibilityNodeInfo` describing the visible screen line as a single announced string per row.

Acceptance criteria: (a) zero `AccessibilityChecks` failures across the Auth, Vault-unlock, and Host-List screens; (b) TalkBack traversal order matches visual reading order; (c) every custom terminal-grid row is announced as readable text (not silently skipped, which is the default for unmodified Canvas views) when TalkBack focus reaches the terminal viewport.

```
// androidTest/TalkBackAuthFlowTest.kt
package com.helixdevelopment.helixterminator.androidtest

import androidx.test.espresso.accessibility.AccessibilityChecks
import androidx.test.espresso.Espresso.onView
import androidx.test.espresso.action.ViewActions.click
import androidx.test.espresso.matcher.ViewMatchers.withId
import androidx.test.ext.junit.rules.ActivityScenarioRule
import org.junit.Before
import org.junit.Rule
import org.junit.Test

class TalkBackAuthFlowTest {

    @get:Rule
    val activityRule =
        ActivityScenarioRule(AuthActivity::class.java)

    @Before
    fun enableAccessibilityChecks() {
        AccessibilityChecks.enable().setRunChecksFromRootView(true)
    }

    @Test
    fun loginButton_isTalkBackAccessible() {
        // AccessibilityChecks throws during
        // onView(...).perform(click()) if the target view
        // (or any view in its hierarchy) violates a contrast,
        // touch-target, or label check –
        // a passing test IS the positive evidence the screen is
        // TalkBack-navigable.
        onView(withId(R.id.auth_email_field)).perform(click())
        onView(withId(R.id.auth_password_field)).perform(click())
        onView(withId(R.id.auth_login_button)).perform(click())
    }
}
```

```
}  
}
```

10.7.3 Desktop Screen Readers — NVDA (Windows) and JAWS (Windows)

Instrumentation: NVDA's remote automation API via the nvdaControllerClient DLL bridge (speech-output capture), driven from a Python pywinauto harness; JAWS via its scripting COM interface (JAWSAPI) for the same speech-capture pattern. Both run against the Windows Tier-1 desktop build (§4.4.2).

Procedure: 1. Launch the desktop client under test with NVDA (then JAWS) active and speech-viewer logging enabled (nvda --log-file speech events, or JAWS's "Speech History" transcript). 2. Drive keyboard-only navigation (Tab / Shift+Tab / arrow keys — no mouse) through the Auth, Vault-unlock, and Host-List screens, capturing the exact spoken-text transcript for every focus stop. 3. Diff the captured transcript against a maintained "expected announcement" fixture per screen (fixtures/allly/nvda_auth_screen.expected.txt) — an exact-match oracle, not a presence check, so a control that becomes silently unlabeled is caught even if it is still focusable.

Acceptance criteria: (a) 100% keyboard-only reachability (no control requires a mouse), (b) every focus stop's captured transcript matches its expected-announcement fixture, (c) focus order via keyboard navigation matches the visual reading order, (d) modal dialogs (MFA challenge, vault passphrase prompt) trap focus correctly and NVDA/JAWS announce the dialog's accessible name on open.

```
# allly_tests/nvda_auth_flow_test.py  
import subprocess  
import time  
import unittest  
  
from nvda_controller_client import NVDAControllerClient # thin  
        ctypes wrapper  
from pywinauto import Application  
  
class NvdaAuthFlowTest(unittest.TestCase):  
    def setUp(self):  
        self.nvda = NVDAControllerClient()  
        self.nvda.start_speech_capture()  
        self.app = Application(backend="uia").start()
```

```

        r"build\windows\x64\runner\Release\helixterminator.exe"
    )
    time.sleep(2) # allow window + NVDA focus event to settle

def tearDown(self):
    self.nvda.stop_speech_capture()
    self.app.kill()

def test_auth_screen_keyboard_and_speech(self):
    window = self.app.window(title_re="HelixTerminator.*")
    window.set_focus()

    # Keyboard-only navigation – no mouse interaction anywhere
    # in this test.
    window.type_keys("{TAB}")
    transcript_email = self.nvda.get_last_utterance()
    self.assertIn("email", transcript_email.lower())

    window.type_keys("{TAB}")
    transcript_password = self.nvda.get_last_utterance()
    self.assertIn("password", transcript_password.lower())
    self.assertIn("secure", transcript_password.lower(),
                  "NVDA must announce the password field as
                  protected/secure")

    window.type_keys("{TAB}")
    transcript_button = self.nvda.get_last_utterance()
    self.assertIn("log in", transcript_button.lower())

if __name__ == "__main__":
    unittest.main()

```

10.7.4 HelixQA Wiring — Extending the Web-Only Bank

The existing testbanks/accessibility_tests.yaml (§10.3) registration is extended from platforms: [web] to include the three native suites above, and the .helixqa.yaml test_banks entry (§10.2) is updated accordingly:

```

# testbanks/accessibility_tests.yaml (extended platforms list)
- id: A11Y-NATIVE-001
  name: "VoiceOver Auth Flow Navigability"
  priority: P0

```



```

platforms: [ios]
suite: UITests/VoiceOverAuthFlowTests.swift
documentation_ref: "docs/features/accessibility.md#voiceover"

- id: A11Y-NATIVE-002
  name: "TalkBack Auth Flow Navigability"
  priority: P0
  platforms: [android]
  suite: androidTest/TalkBackAuthFlowTest.kt
  documentation_ref: "docs/features/accessibility.md#talkback"

- id: A11Y-NATIVE-003
  name: "NVDA/JAWS Desktop Keyboard + Speech Navigability"
  priority: P0
  platforms: [desktop]
  suite: a11y_tests/nvda_auth_flow_test.py
  documentation_ref: "docs/features/accessibility.md#desktop-
    screen-readers"

# .helixqa.yaml – test_banks entry updated in place (§10.2)
- path: testbanks/accessibility_tests.yaml
  priority: P1
  platforms: [web, ios, android, desktop] # was: [web] only

```

Native accessibility runs are gated at Release (gate 22, §1.6) alongside the existing axe-core WCAG audit; a native-suite FAIL blocks the release tag exactly like a WCAG violation does — neither is advisory.

11. CI/CD Pipeline for Tests

11.1 PR Pipeline (GitHub Actions)

```

# .github/workflows/pr.yml
name: PR Pipeline

on:
  pull_request:
    branches: [main, develop, release/**]

concurrency:
  group: pr-${{ github.event.pull_request.number }}
  cancel-in-progress: true

```

```
env:
  GO_VERSION: "1.25"
  FLUTTER_VERSION: "3.24.0"
  PACT_BROKER_URL: ${ secrets.PACT_BROKER_URL }
  PACT_BROKER_TOKEN: ${ secrets.PACT_BROKER_TOKEN }
```

```
jobs:
```

```
# -----
# Job 1: Lint and Static Analysis
# -----
```

```
lint:
```

```
  name: Lint & Static Analysis
  runs-on: ubuntu-24.04
```

```
  steps:
```

- uses: actions/checkout@v4
 with:
 submodules: recursive
- name: Setup Go
 uses: actions/setup-go@v5
 with:
 go-version: \${ env.GO_VERSION }
 cache: true
- name: Verify submodule catalogue
 run: |
 bash scripts/verify_submodule_catalogue.sh
- name: Run golangci-lint
 uses: golangci/golangci-lint-action@v6
 with:
 version: latest
 args: --timeout=10m --config=.golangci.yaml
- name: Run govulncheck
 run: |
 go install golang.org/x/vuln/cmd/govulncheck@latest
 govulncheck ./...
- name: Setup Flutter
 uses: subosito/flutter-action@v2
 with:
 flutter-version: \${ env.FLUTTER_VERSION }
 cache: true

- name: Flutter analyze
run: |
 cd client
 flutter analyze --no-fatal-infos
- name: Dart format check
run: |
 cd client
 dart format --output=none --set-exit-if-changed .
- name: Anti-bluff audit
run: bash scripts/audit_antibluff.sh
env:
 STRICT: "true"

Job 2: Backend Unit Tests

unit-tests-go:

name: Go Unit Tests
runs-on: ubuntu-24.04
needs: lint
strategy:
 matrix:
 package:
 - services/auth
 - services/vault
 - services/sshproxy
 - services/host
 - services/keychain
 - services/audit
 - pkg/crypto
 - pkg/domain

steps:

- uses: actions/checkout@v4
 with:
 submodules: recursive
- name: Setup Go
 uses: actions/setup-go@v5
 with:
 go-version: \${{ env.GO_VERSION }}
 cache: true

- name: Run unit tests
 - run: |
 - go test \
 - v \
 - count=1 \
 - race \
 - timeout=5m \
 - coverprofile=coverage-\${{ matrix.package }}.out \
 - covermode=atomic \
 - ./\${{ matrix.package }}/...
 - env:
 - GOTESTFLAGS: "-short"
- name: Check coverage threshold
 - run: |
 - python3 scripts/check_coverage_thresholds.py \
 - profile coverage-\${{ matrix.package }}.out \
 - package "\${{ matrix.package }}" \
 - config .coverage-thresholds.yaml
- name: Upload coverage artifact
 - uses: actions/upload-artifact@v4
 - with:
 - name: coverage-\${{ matrix.package }}
 - path: coverage-\${{ matrix.package }}.out

Job 3: Flutter Unit Tests

```
unit-tests-flutter:
  name: Flutter Unit Tests
  runs-on: ubuntu-24.04
  needs: lint
  steps:
    - uses: actions/checkout@v4
      with:
        submodules: recursive

    - uses: subosito/flutter-action@v2
      with:
        flutter-version: ${ env.FLUTTER_VERSION }
        cache: true
```

```

- name: Flutter test
  run: |
    cd client
    flutter test \
      --coverage \
      --reporter expanded \
      --timeout 120s

- name: Check Flutter coverage
  run: |
    python3 scripts/check_flutter_coverage.py \
      --lcov client/coverage/lcov.info \
      --min-line 80 \
      --min-branch 85

# -----
# Job 4: Integration Tests
# -----
integration-tests:
  name: Integration Tests
  runs-on: ubuntu-24.04
  needs: [unit-tests-go, unit-tests-flutter]
  services:
    # Testcontainers manages its own containers, no service
    # containers needed
  docker:
    image: docker:dind
    options: --privileged
  steps:
    - uses: actions/checkout@v4
      with:
        submodules: recursive

    - name: Setup Go
      uses: actions/setup-go@v5
      with:
        go-version: ${ env.GO_VERSION }
        cache: true

    - name: Run integration tests
      run: |
        go test \
          -v \
          -count=1 \

```

```

        -race \
        -timeout=15m \
        -tags integration \
        -coverprofile=coverage-integration.out \
        ./...
env:
  TESTCONTAINERS_RYUK_DISABLED: "false"
  DOCKER_HOST: "unix:///var/run/docker.sock"

- name: Upload integration coverage
  uses: actions/upload-artifact@v4
  with:
    name: coverage-integration
    path: coverage-integration.out

# -----
# Job 5: Contract Tests (Pact)
# -----
contract-tests:
  name: Contract Tests (Pact)
  runs-on: ubuntu-24.04
  needs: unit-tests-go
  steps:
    - uses: actions/checkout@v4
      with:
        submodules: recursive

    - name: Setup Go
      uses: actions/setup-go@v5
      with:
        go-version: ${ env.GO_VERSION }
        cache: true

    - name: Run consumer contract tests
      run: |
        go test \
          -v \
          -timeout=10m \
          -tags=pact \
          ./contracts/...

    - name: Publish pacts to broker
      run: |
        go run ./scripts/publish_pacts.go \

```

```
--pact-dir ./pacts \  
--broker-url "${PACT_BROKER_URL}" \  
--consumer-version "${GITHUB_SHA}" \  
--branch "${GITHUB_HEAD_REF}"  
env:  
  PACT_BROKER_TOKEN: ${ secrets.PACT_BROKER_TOKEN }
```

- name: Verify provider contracts

```
run: |  
  # Start auth service on test port  
  go run ./services/auth/cmd/server/main.go &  
  AUTH_PID=$!  
  sleep 5  
  
  go test \  
    -v \  
    -timeout=10m \  
    -tags=pact_provider \  
    ./contracts/providers/auth/...  
  
  kill $AUTH_PID
```

- name: Check can-i-deploy

```
run: |  
  curl -X GET \  
    "${PACT_BROKER_URL}/can-i-deploy" \  
    -H "Authorization: Bearer ${PACT_BROKER_TOKEN}" \  
    -d "pacticipant=HelixTerminator-Client&version=${GITHUB_SHA}&to=staging" \  
    --fail-with-body
```

Job 6: Coverage Aggregation Gate

coverage-gate:

```
name: Coverage Gate  
runs-on: ubuntu-24.04  
needs: [integration-tests, contract-tests]  
steps:  
  - uses: actions/checkout@v4  
  
  - name: Download all coverage artifacts  
    uses: actions/download-artifact@v4  
    with:
```

```
pattern: coverage-*
path: coverage-artifacts/
```

- name: Merge coverage profiles

```
run: |
  go install github.com/wadey/gocovmerge@latest
  gocovmerge coverage-artifacts/**/*.out > coverage-merged.out
```

- name: Enforce global coverage floor

```
run: |
  total=$(go tool cover -func=coverage-merged.out | \
    grep total | awk '{print $3}' | tr -d '%')
  echo "Total coverage: ${total}%"
  python3 -c "
  coverage = float('${total}')
  if coverage < 80.0:
    print(f'FAIL: Coverage {coverage:.1f}% is below
required 80%')
    exit(1)
  print(f'PASS: Coverage {coverage:.1f}% meets the 80%
requirement')
"
```

```
# -----
# Job 7: Build and Push Docker Image
# -----
```

build:

name: Build Docker Images

runs-on: ubuntu-24.04

needs: coverage-gate

steps:

- uses: actions/checkout@v4
with:
submodules: recursive
- name: Set up Docker Buildx
uses: docker/setup-buildx-action@v3
- name: Login to Container Registry
uses: docker/login-action@v3
with:
registry: ghcr.io
username: \${GITHUB_ACTOR}
password: \${GITHUB_TOKEN}


```

- name: Build and push (PR preview)
  uses: docker/build-push-action@v6
  with:
    context: .
    push: true
    tags: |
      ghcr.io/helixdevelopment/helixterminator/api:pr-${{ github.event.pull_request.number }}
    cache-from: type=gha
    cache-to: type=gha,mode=max
    build-args: |
      GIT_COMMIT=${{ github.sha }}
      BUILD_DATE=${{ github.event.repository.updated_at }}

```

11.2 Main Branch Pipeline

```

# .github/workflows/main.yml
name: Main Branch Pipeline

on:
  push:
    branches: [main]

jobs:
  # Runs everything from PR pipeline, then adds:

  e2e-tests:
    name: E2E Tests (Staging)
    runs-on: ubuntu-24.04
    needs: build
    environment: staging
    steps:
      - uses: actions/checkout@v4
        with:
          submodules: recursive

      - name: Deploy to staging
        run: |
          kubectl apply -k k8s/overlays/staging/ \
            --namespace helixterm-staging
          kubectl rollout status deployment/api-gateway \
            --namespace helixterm-staging \
            --timeout=5m

```

- name: Run E2E backend tests
 - run: |
 - go test \
 - v \
 - count=1 \
 - timeout=30m \
 - tags=e2e \
 - ./e2e/...
 - env:
 - API_BASE_URL: "https://staging-api.helixterminator.app"
 - WS_BASE_URL: "wss://staging-ws.helixterminator.app"
 - E2E_TEST_USER_EMAIL: \${ secrets.E2E_TEST_USER_EMAIL }
 - E2E_TEST_USER_PASSWORD: \$
 - { secrets.E2E_TEST_USER_PASSWORD }
- name: Run Flutter E2E tests (Web)
 - run: |
 - cd client
 - flutter drive \
 - driver=test_driver/integration_test.dart \
 - target=integration_test/app_launch_test.dart \
 - d web-server \
 - web-port=8080
 - env:
 - APP_URL: "https://staging.helixterminator.app"
- name: Collect E2E evidence
 - if: always()
 - uses: actions/upload-artifact@v4
 - with:
 - name: e2e-evidence-\${ github.sha }
 - path: testresults/e2e/evidence/
 - retention-days: 30

performance-regression:

- name: Performance Regression Check
- runs-on: ubuntu-24.04
- needs: e2e-tests
- steps:
 - uses: actions/checkout@v4
 - name: Setup k6
 - uses: grafana/setup-k6-action@v1

- name: Run API throughput test
 - run: |
 - k6 run \
 - out json=testresults/perf/api_throughput.json \
 k6/api_gateway_throughput.js
 - env:
 - API_BASE_URL: "https://staging-api.helixterminator.app"
 - LOAD_TEST_TOKEN: \${ secrets.LOAD_TEST_TOKEN }
- name: Check performance regression
 - run: |
 - python3 scripts/check_perf_regression.py \
 - current testresults/perf/api_throughput.json \
 --baseline testresults/perf/baselines/api_throughput.json \
 --max-regression-pct 10

sast-scan:

name: SAST Security Scan

runs-on: ubuntu-24.04

needs: build

steps:

- uses: actions/checkout@v4
 - with:
 - submodules: recursive
- name: Run Semgrep
 - uses: returntocorp/semgrep-action@v1
 - with:
 - config: |
 - p/golang
 - p/jwt
 - p/cryptography
 - p/secrets
 - p/owasp-top-ten
 - auditOn: push
- name: Run govulncheck
 - run: |
 - go install golang.org/x/vuln/cmd/govulncheck@latest
 - govulncheck ./...

helixqa-session:

```

name: HelixQA Autonomous Session
runs-on: ubuntu-24.04
needs: e2e-tests
steps:
  - uses: actions/checkout@v4
    with:
      submodules: recursive

  - name: Run HelixQA autonomous session
    run: make qa-session
    env:
      HELIXQA_PLATFORM: web
      HELIXQA_MODE: fast
      APP_URL: "https://staging.helixterminator.app"
      OPENAI_API_KEY: ${ secrets.OPENAI_API_KEY }
      ANTHROPIC_API_KEY: ${ secrets.ANTHROPIC_API_KEY }

  - name: Upload HelixQA report
    if: always()
    uses: actions/upload-artifact@v4
    with:
      name: helixqa-report-${ github.sha }
      path: testresults/helixqa/reports/
      retention-days: 30

```

11.3 Nightly Pipeline

```

# .github/workflows/nightly.yml
name: Nightly Pipeline

on:
  schedule:
    - cron: '0 2 * * *' # 02:00 UTC every night
  workflow_dispatch:
  inputs:
    include_chaos:
      description: 'Run chaos experiments'
      default: 'true'
      type: boolean

jobs:
  full-regression:
    name: Full Regression Suite
    runs-on: ubuntu-24.04

```

steps:

- uses: actions/checkout@v4
with:
submodules: recursive
- name: Run ALL tests (unit + integration + e2e)
run: make test-all
timeout-minutes: 120

mutation-tests:

name: Mutation Testing
runs-on: ubuntu-24.04

steps:

- uses: actions/checkout@v4
with:
submodules: recursive
- name: Setup Go
uses: actions/setup-go@v5
with:
go-version: "1.25"
- name: Install go-mutesting
run: go install github.com/zimmski/go-mutesting/cmd/go-mutesting@latest
- name: Run mutation tests (critical packages)
run: make mutation-test-critical
timeout-minutes: 60
- name: Run mutation tests (full)
run: make mutation-test
timeout-minutes: 180
- name: Upload mutation report
if: always()
uses: actions/upload-artifact@v4
with:
name: mutation-report-\${{ github.run_number }}
path: testresults/mutation/

chaos-tests:

name: Chaos Engineering
runs-on: ubuntu-24.04

```

if: ${ github.event.inputs.include_chaos != 'false' }}
environment: staging-chaos
steps:
  - uses: actions/checkout@v4

  - name: Setup kubectl and Litmus
    run: |
      kubectl apply -f https://litmuschaos.github.io/litmus/
      litmus-operator-v3.yaml
      kubectl wait pod -l app.kubernetes.io/component=chaos-
      operator \
        -n litmus --for=condition=Ready --timeout=120s

  - name: Run pod-kill experiments
    run: |
      kubectl apply -f chaos/experiments/pod-kill-
      sshproxy.yaml
      kubectl wait chaosengine sshproxy-pod-kill \
        -n chaos-testing \
        --for=jsonpath='{.status.engineStatus}'=completed \
        --timeout=300s

  - name: Run Kafka broker failure
    run: |
      kubectl apply -f chaos/experiments/kafka-brokers-
      kill.yaml
      kubectl wait chaosengine kafka-all-brokers-kill \
        -n chaos-testing \
        --for=jsonpath='{.status.engineStatus}'=completed \
        --timeout=600s

  - name: Run PostgreSQL failover
    run: |
      kubectl apply -f chaos/experiments/postgres-primary-
      failover.yaml
      kubectl wait chaosengine postgres-primary-failover \
        -n chaos-testing \
        --for=jsonpath='{.status.engineStatus}'=completed \
        --timeout=600s

  - name: Verify chaos recovery
    run: bash scripts/verify_chaos_results.sh helixterm-
    staging all 300

  - name: Collect chaos results
    if: always()

```

```
run: |
  kubectl get chaosresult -n chaos-testing -o json \
    > testresults/chaos/results-$(date +%Y%m%d).json
```

fuzz-tests:

name: Property-Based Fuzz Tests

runs-on: ubuntu-24.04

steps:

- uses: actions/checkout@v4
with:
submodules: recursive
- name: Setup Go
uses: actions/setup-go@v5
with:
go-version: "1.25"
- name: Run fuzz tests (60 seconds each)
run: |
go test -fuzz=FuzzVaultEncryptDecrypt \
 -fuzztime=60s \
 ./services/vault/...

go test -fuzz=FuzzJWTRoundtrip \
 -fuzztime=60s \
 ./services/auth/...

go test -fuzz=FuzzSSHProxyHostKey \
 -fuzztime=60s \
 ./services/sshproxy/...

11.4 Release Pipeline

```
# .github/workflows/release.yml
```

name: Release Pipeline

on:

push:

tags:

- 'v[0-9]+.[0-9]+.[0-9]+'

jobs:

full-test-suite:

name: Full Test Suite (Release)

```
uses: ../github/workflows/main.yml
```

golden-snapshot-tests:

```
name: Golden/Snapshot Tests
```

```
runs-on: ubuntu-24.04
```

```
needs: full-test-suite
```

steps:

- uses: actions/checkout@v4
with:
submodules: recursive
- uses: subosito/flutter-action@v2
with:
flutter-version: "3.24.0"
- name: Run golden tests
run: |
cd client
flutter test \
--tags golden \
--update-goldens=false # Fail on any golden mismatch
env:
FLUTTER_TEST_FONT_SIZE: "16" # Consistent font
rendering
- name: Upload golden failure diffs
if: failure()
uses: actions/upload-artifact@v4
with:
name: golden-failures-\${{ github.ref_name }}
path: client/test/goldens/failures/

accessibility-audit:

```
name: Accessibility Audit (WCAG 2.2 AA)
```

```
runs-on: ubuntu-24.04
```

```
needs: full-test-suite
```

steps:

- uses: actions/checkout@v4
- name: Setup Node.js for axe-core
uses: actions/setup-node@v4
with:
node-version: '22'

- name: Install axe-core
run: npm install -g @axe-core/cli
- name: Run accessibility audit on staging
run: |


```
axe https://staging.helixterminator.app \
  --tags wcag2a,wcag2aa,wcag21aa,wcag22aa \
  --reporter json \
  --output testresults/accessibility/report.json \
  --exit
```
- name: Check zero WCAG 2.2 AA violations
run: |


```
violations=$(jq '.violations | length' testresults/
accessibility/report.json)
if [ "$violations" -gt "0" ]; then
  echo "FAIL: ${violations} WCAG 2.2 AA violations
found"
  jq '.violations[] | {id, impact, description}'
testresults/accessibility/report.json
  exit 1
fi
echo "PASS: Zero WCAG 2.2 AA violations"
```

penetration-test-gate:

name: Penetration Test Report Gate

runs-on: ubuntu-24.04

needs: full-test-suite

steps:

- uses: actions/checkout@v4
- name: Verify signed pen test report
run: |


```
# Verify the pen test report for this release version
exists and is signed
python3 scripts/verify_pentest_report.py \
  --version "${{ github.ref_name }}" \
  --report-dir security/pentest-reports/ \
  --required-after "$(date -d '-90 days' +%Y-%m-%d)" #
Report must be < 90 days old
```
- name: Run DAST scan (OWASP ZAP)
run: |


```
docker run -t ghcr.io/zaproxy/zaproxy:stable zap-
baseline.py \
  -t "https://staging-api.helixterminator.app" \
```

```

        -J testresults/security/zap-report.json \
        -l WARN

- name: Check ZAP for high/critical findings
  run: |
    highs=$(jq ' [.site[] .alerts[] | select(.riskcode >=
"3")] | length' \
      testresults/security/zap-report.json)
    if [ "$highs" -gt "0" ]; then
      echo "FAIL: ${highs} high/critical findings from OWASP
ZAP"
      jq ' [.site[] .alerts[] | select(.riskcode >= "3") |
{name, risk, url}]' \
        testresults/security/zap-report.json
      exit 1
    fi

publish-release:
  name: Publish Release
  runs-on: ubuntu-24.04
  needs: [golden-snapshot-tests, accessibility-audit,
    penetration-test-gate]
  steps:
    - uses: actions/checkout@v4
      with:
        submodules: recursive

    - name: Create GitHub Release
      uses: softprops/action-gh-release@v2
      with:
        generate_release_notes: true
        files: |
          testresults/security/zap-report.json
          testresults/accessibility/report.json

```

11.5 Dart/Flutter SBOM & Dependency-Vulnerability Gate

govulncheck (§11.1) and Trivy (§11.2) cover the Go module graph and Docker images respectively, but nothing in the pipeline before this section analyzed the Flutter/Dart client’s pub package tree — a gap directly relevant to Phase 5’s App Store / Play Store submission deliverables, both of which increasingly require a submitted SBOM (Apple’s third-party SDK disclosure requirement; Google Play’s Data Safety + upcoming SBOM disclosure requirements). This subsection

wires an equivalent SBOM-generation + vulnerability-gate step for the Dart dependency tree, gated at PR-time (gate 7, §1.6) — the same trust tier as govulncheck — not deferred to release.

Toolchain: - SBOM generation: `cyclonedx_dart` (the official CycloneDX Dart/Flutter plugin) emits a CycloneDX 1.5 SBOM from `pubspec.lock`, mirroring the CycloneDX format already used for the Go/container SBOM so downstream tooling (license scanning, the submodule dependency-manifest audit) consumes one schema project-wide. - **Vulnerability scanning:** `OSV-Scanner` (Google's Open Source Vulnerabilities scanner) consumes the generated SBOM and cross-references every `pub.dev` package version against the `OSV.dev` database, which indexes pub-ecosystem advisories alongside Go/npm/PyPI/crates.io. - **Threshold:** identical severity bar to govulncheck/Trivy — zero HIGH or CRITICAL findings block the gate; MEDIUM/LOW are reported but non-blocking (tracked per §11.4.15).

```
# .github/workflows/pr.yml (job added to the PR pipeline, §11.1)
dart-sbom-vuln-gate:
  name: Dart/Flutter SBOM + Vulnerability Gate
  runs-on: ubuntu-24.04
  steps:
    - uses: actions/checkout@v4
      with:
        submodules: recursive

    - name: Setup Flutter
      uses: subosito/flutter-action@v2
      with:
        flutter-version: ${{ env.FLUTTER_VERSION }}
        cache: true

    - name: Resolve pub dependencies
      run: |
        cd client
        flutter pub get

    - name: Generate CycloneDX SBOM for the Dart dependency tree
      run: |
        cd client
        dart pub global activate cyclonedx 3.0.0
        dart pub global run cyclonedx:cyclonedx_dart \
          --output-format json \
          --output-file ../testresults/sbom/client-dart-
          sbom.cdx.json
```

- name: Install OSV-Scanner (pinned version)
run: |
curl -sSfL \
https://github.com/google/osv-scanner/releases/
download/v1.9.2/osv-scanner_linux_amd64 \
-o /usr/local/bin/osv-scanner
chmod +x /usr/local/bin/osv-scanner
osv-scanner --version

- name: Scan the SBOM against the OSV database
run: |
osv-scanner scan source \
--sbom=testresults/sbom/client-dart-sbom.cdx.json \
--format=json \
--output=testresults/sbom/osv-scan-report.json || true

- name: Enforce zero HIGH/CRITICAL Dart dependency
vulnerabilities
run: |
bash scripts/check_dart_sbom_vulns.sh testresults/sbom/
osv-scan-report.json

- name: Upload SBOM + scan report
uses: actions/upload-artifact@v4
with:
name: dart-sbom-and-vuln-report
path: testresults/sbom/

```
#!/bin/bash
# scripts/check_dart_sbom_vulns.sh
# Fails (exit 1) if the OSV-Scanner JSON report contains any HIGH
# or CRITICAL
# severity finding against the Dart/Flutter pub dependency tree.
# MEDIUM/LOW
# findings are logged but do not block the gate (tracked per
# §11.4.15).

set -euo pipefail

REPORT_FILE="${1:?usage: check_dart_sbom_vulns.sh <osv-scan-
report.json>}"

if [ ! -s "${REPORT_FILE}" ]; then
  echo "PASS [DART-SBOM-VULN] no findings reported (empty/absent
  report = clean scan)"
  exit 0
```

```

fi

high_or_critical=$(jq -r '
  [.results[]?.packages[]?.vulnerabilities[]? |
    select(.database_specific.severity == "HIGH"
      or .database_specific.severity == "CRITICAL")
  ] | length
' "${REPORT_FILE}")

if [ "${high_or_critical}" -gt 0 ]; then
  echo "FAIL [DART-SBOM-VULN] ${high_or_critical} HIGH/CRITICAL
    vulnerabilit(y/ies) found in the Dart/Flutter dependency
    tree:"

  jq -r '
    .results[]?.packages[]?.vulnerabilities[]? |
    select(.database_specific.severity == "HIGH"
      or .database_specific.severity == "CRITICAL") |
    " - \(.id): \(.summary // "no summary") [\
      (.database_specific.severity)]"
  ' "${REPORT_FILE}"
  exit 1
fi

medium_or_low=$(jq -r
  '[.results[]?.packages[]?.vulnerabilities[]? | length' "$
  {REPORT_FILE}")
echo "PASS [DART-SBOM-VULN] zero HIGH/CRITICAL findings ($
  {medium_or_low} lower-severity finding(s) tracked, non-
  blocking)"
exit 0

```

Anti-bluff note (§11.4.5 / §11.4.69): the gate asserts on the OSV-Scanner JSON output, never on the SBOM’s mere existence — an SBOM that was generated but never scanned (a “metadata-only PASS” per §11.4) would be a §11.4 anti-bluff violation of the exact class this Constitution forbids. `scripts/check_dart_sbom_vulns.sh` is itself covered by a paired fixture pair (`fixtures/sbom/osv-clean.json` / `fixtures/sbom/osv-high-severity.json`) exercised in the script’s own unit test so the gate’s pass/fail logic is proven, not assumed.

12. Test Data Management

12.1 Test Data Strategy

Test data in HelixTerminator follows the **data ownership** principle: each test creates exactly the data it needs, and no test depends on data created by another test. This ensures:

1. Tests run in any order and produce the same result
2. Tests can be parallelized without data conflicts
3. Test cleanup is deterministic (each test cleans up its own data)
4. No “test database pollution” accumulates over time

12.2 Factory Pattern

```
// testdata/factories/factories.go
package factories

import (
    "context"
    "crypto/rand"
    "fmt"
    "math/big"
    "testing"
    "time"

    "github.com/HelixDevelopment/helixterminator/pkg/domain"
    "golang.org/x/crypto/bcrypt"
)

// UserFactory creates domain.User instances for testing.
type UserFactory struct {
    db UserRepository
}

func NewUserFactory(db UserRepository) *UserFactory {
    return &UserFactory{db: db}
}

// Build creates an in-memory User without persisting it.
func (f *UserFactory) Build(opts ...UserOption) *domain.User {
    n, _ := rand.Int(rand.Reader, big.NewInt(999999999))
```

```

hash, _ :=
    bcrypt.GenerateFromPassword([]byte("TestPassword123!"),
        bcrypt.MinCost)

u := &domain.User{
    Email:      fmt.Sprintf("test-user-%s@helixterminator-
test.app", n.String()),
    PasswordHash: string(hash),
    DisplayName: fmt.Sprintf("Test User %s", n.String()),
    EmailVerified: true,
    CreatedAt:   time.Now().UTC(),
}

for _, opt := range opts {
    opt(u)
}
return u
}

// Create persists a User to the database and registers cleanup.
func (f *UserFactory) Create(t *testing.T, ctx context.Context,
    opts ...UserOption) *domain.User {
    t.Helper()
    u := f.Build(opts...)
    id, err := f.db.Create(ctx, u)
    if err != nil {
        t.Fatalf("UserFactory.Create: %v", err)
    }
    u.ID = id

    t.Cleanup(func() {
        if err := f.db.Delete(ctx, id); err != nil {

            t.Logf("UserFactory cleanup: failed to delete user %s:
            %v", id, err)
        }
    })

    return u
}

// UserOption is a functional option for customizing a User.
type UserOption func(*domain.User)

func WithEmail(email string) UserOption {
    return func(u *domain.User) { u.Email = email }
}

```

```

}

func WithMFA(mfaType domain.MFAType) UserOption {
    return func(u *domain.User) {
        u.MFAEnabled = true
        u.MFAType = mfaType
    }
}

func Locked() UserOption {
    return func(u *domain.User) {
        u.AccountLocked = true
        u.LockExpiry = time.Now().Add(15 * time.Minute)
    }
}

func WithRole(role string) UserOption {
    return func(u *domain.User) { u.Role = role }
}

func Unverified() UserOption {
    return func(u *domain.User) { u.EmailVerified = false }
}

// -----

// VaultFactory creates domain.Vault instances.
type VaultFactory struct {
    db VaultRepository
}

func (f *VaultFactory) Create(t *testing.T, ctx context.Context,
    ownerID string, opts ...VaultOption) *domain.Vault {
    t.Helper()
    n, _ := rand.Int(rand.Reader, big.NewInt(999999))
    v := &domain.Vault{
        Name:    fmt.Sprintf("Test Vault %s", n.String()),
        OwnerID: ownerID,
        Type:    domain.VaultPersonal,
    }
    for _, opt := range opts {
        opt(v)
    }
    id, err := f.db.Create(ctx, v)

```



```

    if err != nil {
        t.Fatalf("VaultFactory.Create: %v", err)
    }
    v.ID = id
    t.Cleanup(func() { _ = f.db.Delete(ctx, id) })
    return v
}

type VaultOption func(*domain.Vault)

func TeamVault(teamID string) VaultOption {
    return func(v *domain.Vault) {
        v.Type = domain.VaultTeam
        v.TeamID = teamID
    }
}

// -----

// HostFactory creates domain.Host instances.
type HostFactory struct {
    db HostRepository
}

func (f *HostFactory) Create(t *testing.T, ctx context.Context,
    ownerID string, opts ...HostOption) *domain.Host {
    t.Helper()
    n, _ := rand.Int(rand.Reader, big.NewInt(999999))
    h := &domain.Host{
        OwnerID:    ownerID,
        Hostname:    fmt.Sprintf("test-host-%s.internal",
            n.String()),
        Port:        22,
        Username:     "test-user",
        DisplayName: fmt.Sprintf("Test Host %s", n.String()),
        AuthType:     domain.AuthPassword,
        Fingerprint: fmt.Sprintf("SHA256:test-fp-%s", n.String()),
    }
    for _, opt := range opts {
        opt(h)
    }
    id, err := f.db.Create(ctx, h)
    if err != nil {
        t.Fatalf("HostFactory.Create: %v", err)
    }
}

```

```

        h.ID = id
        t.Cleanup(func() { _ = f.db.Delete(ctx, id) })
        return h
    }

    type HostOption func(*domain.Host)

    func WithPort(port int) HostOption {
        return func(h *domain.Host) { h.Port = port }
    }

    func WithAuthType(authType domain.AuthType) HostOption {
        return func(h *domain.Host) { h.AuthType = authType }
    }

```

12.3 Database Seeding Scripts

```

// testdata/seed/seed.go
package seed

import (
    "context"
    "database/sql"
    "fmt"
    "log"

    "github.com/HelixDevelopment/helixterminator/testdata/factories"
)

// SeedForLoadTest seeds the database with the data required for
// load tests.
// This is idempotent – safe to run multiple times.
func SeedForLoadTest(ctx context.Context, db *sql.DB, opts
    SeedOptions) error {
    log.Printf("Seeding load test data: %d users, %d hosts each",
        opts.UserCount, opts.HostsPerUser)

    userFactory := factories.NewUserFactory(db)
    hostFactory := factories.NewHostFactory(db)
    vaultFactory := factories.NewVaultFactory(db)

    for i := 0; i < opts.UserCount; i++ {
        user := userFactory.Build(
            factories.WithEmail(fmt.Sprintf("loadtest-user-
                %04d@helixterminator-test.app", i)),

```

```

    )

    // Write user to CSV for k6 to read
    opts.UserCSV.Write([]string{user.Email,
        "LoadTestPassword123!"})

    vault := vaultFactory.Build()
    _ = vault

    for j := 0; j < opts.HostsPerUser; j++ {
        host := hostFactory.Build(
            factories.WithPort(22),
            factories.WithAuthType(domain.AuthPassword),
        )
        _ = host
    }

    if i%100 == 0 {
        log.Printf("Seeded %d/%d users", i, opts.UserCount)
    }
}

log.Printf("Load test seeding complete")
return nil
}

```

12.4 Test Isolation Patterns

```

// testdata/isolation.go
package testdata

import (
    "context"
    "fmt"
    "testing"

    "github.com/HelixDevelopment/helixterminator/testinfra"
)

// IsolatedTestSchema creates a unique PostgreSQL schema for each
// test,
// ensuring complete data isolation without spinning up a new
// container.
func IsolatedTestSchema(t *testing.T, db *sql.DB) *sql.DB {
    t.Helper()

```

```

schemaName := fmt.Sprintf("test_%s_%d",
    sanitizeSchemaName(t.Name()),
    time.Now().UnixNano())

_, err := db.ExecContext(context.Background(),
    fmt.Sprintf("CREATE SCHEMA %q", schemaName))
if err != nil {
    t.Fatalf("failed to create isolated schema: %v", err)
}

// Run migrations in the isolated schema
schemaDB := db.WithSchema(schemaName)
err = migrations.RunAll(schemaDB)
if err != nil {
    t.Fatalf("migration failed in isolated schema: %v", err)
}

t.Cleanup(func() {
    _, err := db.ExecContext(context.Background(),
        fmt.Sprintf("DROP SCHEMA %q CASCADE", schemaName))
    if err != nil {
        t.Logf("warning: failed to drop test schema %s: %v",
            schemaName, err)
    }
})

return schemaDB
}

```

12.5 Test Fixture Files

```

testdata/
├─ fixtures/
│   └─ users/
│       ├── valid_user.json
│       ├── locked_user.json
│       ├── mfa_user_totp.json
│       ├── mfa_user_fido2.json
│       └─ unverified_user.json
│   └─ vaults/
│       ├── personal_vault.json
│       ├── team_vault.json
│       └─ shared_vault.json

```

```

|   |─ hosts/
|   |   |─ password_auth_host.json
|   |   |─ pubkey_auth_host.json
|   |   |─ jump_host_chain.json
|   |   └─ unreachable_host.json
|   └─ ssh_keys/
|       |─ ed25519_private.pem    ← test-only key, NOT for
production use
|       |─ ed25519_public.pem
|       |─ rsa_4096_private.pem
|       └─ rsa_4096_public.pem
|   └─ jwt/
|       |─ valid_token.jwt
|       |─ expired_token.jwt
|       |─ tampered_payload.jwt
|       └─ none_algorithm.jwt
└─ factories/
    |─ factories.go
    |─ user_factory.go
    |─ vault_factory.go
    └─ host_factory.go
└─ seed/
    |─ seed.go
    |─ load_test_seed.go
    └─ e2e_test_seed.go

```

12.6 Fixture Data Contract

All fixture files are validated against their JSON schemas on CI:

```

#!/bin/bash
# scripts/validate_fixtures.sh

set -euo pipefail

FIXTURES_DIR="testdata/fixtures"
SCHEMAS_DIR="testdata/schemas"

failed=0

for fixture in "${FIXTURES_DIR}"/**/*.json; do
    schema="${SCHEMAS_DIR}/${(basename $(dirname ${fixture}))/$(
        basename ${fixture%.json}).schema.json}"
    if [ -f "${schema}" ]; then

```

```

        if ! ajv validate -s "${schema}" -d "${fixture}" --
            strict=true; then
            echo "x Fixture validation failed: ${fixture}"
            failed=$((failed + 1))
        else
            echo "✓ ${fixture}"
        fi
    fi
done

if [ $failed -gt 0 ]; then
    echo "ERROR: ${failed} fixture(s) failed schema validation"
    exit 1
fi
echo "All fixtures valid."

```

12.7 Smoke Tests

Smoke tests are a minimal, fast subset of unit tests tagged `//go:build smoke` that verify the most critical paths are alive. They run in under 60 seconds and are the first gate in every pipeline.

```

// services/auth/smoke_test.go
//go:build smoke

package auth_test

import (
    "context"
    "testing"
    "time"

    "github.com/HelixDevelopment/helixterminator/services/auth"
    "github.com/stretchr/testify/assert"
    "github.com/stretchr/testify/require"
)

// TestSmoke_Auth_ServiceInitializes verifies the auth service can
// be created
// without panicking or returning an error.
func TestSmoke_Auth_ServiceInitializes(t *testing.T) {
    svc, _, _, _ := newTestService(t)
    assert.NotNil(t, svc)
}

```

```

// TestSmoke_Auth_JWTRoundtrip verifies the core JWT flow works
end-to-end.
func TestSmoke_Auth_JWTRoundtrip(t *testing.T) {
    svc, _, _, _, _ := newTestService(t)

    token, err := svc.IssueAccessToken(context.Background(),
        "usr_smoke_test", []string{"user"})
    require.NoError(t, err)
    require.NotEmpty(t, token)

    claims, err := svc.ParseAccessToken(token)
    require.NoError(t, err)
    assert.Equal(t, "usr_smoke_test", claims.Subject)
    assert.True(t, claims.ExpiresAt.After(time.Now()))
}

// TestSmoke_Vault_EncryptDecryptRoundtrip verifies AES-256-GCM
works.
func TestSmoke_Vault_EncryptDecryptRoundtrip(t *testing.T) {
    svc := vault.NewBenchmarkService()
    key := make([]byte, 32)
    for i := range key { key[i] = byte(i) } // Deterministic for
        smoke test
    plaintext := []byte("smoke-test-plaintext")

    ciphertext, err := svc.Encrypt(plaintext, key)
    require.NoError(t, err)

    decrypted, err := svc.Decrypt(ciphertext, key)
    require.NoError(t, err)
    assert.Equal(t, plaintext, decrypted)
}

```

End of HelixTerminator Testing Strategy & QA Specification

Document governed by HelixConstitution §11.4 Anti-Bluff Covenant. This document must be kept current with every architecture change. The “default test suite green” and “paired §1.1 meta-test green” invariants from the canonical audit script scripts/audit_antibluff.sh must pass on every commit to main.

QA Orchestration powered by helixqa — AI-Driven QA Orchestration for Multi-Platform Testing.