

Helix Thready — API Materials (Index)

Contents

Headline findings

How this maps to the parent area

Open items (rolled up)

Rev	Date	Author	Change
1	2026-07-22	swarm (API & SDKs — materials)	Initial materials pack: request collections, codegen harness, OpenAPI validation report

Concrete, hands-on artifacts derived from the API area's schema-first contracts (`../openapi.yaml` , `../event-bus-contract.md`). Where the parent area *specifies* the contract, this folder makes it **executable**: copy-pasteable requests, a working codegen Makefile, and a validation record.

Contents

Path	What it is	Runnable?
<code>examples/</code>	Per-endpoint-group request collections — curl (<code>*.curl.sh</code>) and HTTPIe (<code>*.http</code>) for all 10 groups (auth, accounts, channels, posts, processing, assets, search, skills, billing, events), plus <code>env.example</code> .	<code>curl</code> scripts pass <code>bash -n</code> ; need a token + base URL to hit a server.
<code>codegen/</code>	The buf + openapi-generator codegen harness (<code>Makefile</code> , <code>buf.gen.yaml</code> , <code>buf.yaml</code>) implementing the <code>helix_proto</code> pattern → 11 SDK languages.	REST/lint targets run now; <code>proto</code> targets skip cleanly until <code>proto/</code> exists (<code>[OPEN: api-1]</code>).
<code>validation.md</code>	Structural validation of <code>../openapi.yaml</code> with <code>@redocly/cli</code> 2.40.0 + a PyYAML hand-lint of the required 3.1 fields.	— record only.

Headline findings

- **Validation:** `../openapi.yaml` is a structurally valid OpenAPI 3.1 skeleton (46 paths / 59 ops / 40 schemas / 1 webhook, all `$ref` s resolve) but currently **FAILS lint with 2 errors** — two `description:` values contain an unquoted comma, so YAML mis-parses each into a spurious schema property (independently confirmed with PyYAML). Both are one-line quote fixes in `../openapi.yaml` ; raised as

[OPEN: val-1] because this pack writes only inside `materials/`. The 39 warnings are style/convention advisories (details in `validation.md`).

- **Codegen:** the REST-plane and lint targets are real and were parse/dry-run verified (`make help` , `make tools` , `make -n`); the proto plane is a **verified-pattern scaffold** that is inert until the `helix_thready_proto` repo provides `proto/...`. No SDK was actually generated in this environment — see the anti-bluff note in `codegen/README.md` §8.

How this maps to the parent area

Parent doc	Materials that exercise it
<code>../openapi.yaml</code>	<code>examples/*</code> (every operation), <code>codegen/</code> (<code>openapi-generate-*</code>), <code>validation.md</code>
<code>../event-bus-contract.md</code>	<code>examples/events.*</code> (catalog, sticky, sinks, SSE, WS note)
<code>../authn-authz.md</code>	<code>examples/auth.*</code> , the Bearer/HMAC/idempotency conventions
<code>../sdk-strategy.md</code>	<code>codegen/Makefile</code> + <code>buf.gen.yaml</code> + <code>buf.yaml</code> (helix_proto pattern)

Open items (rolled up)

- [OPEN: val-1] Fix the two `description` mis-parses in `../openapi.yaml` (out of this pack's write scope; materials-only).
- [OPEN: val-3] Only redocly ran here; re-run Spectral + `openapi-generator validate` with network for independent structural opinions.
- [OPEN: api-1] Proto plane produced in `helix_thready_proto` ; codegen proto targets are ready-but-inert until then.
- [OPEN: ex-1 / ex-2] WebSocket is not curl/HTTPie-able (SSE shown; WS via `websocat`); no request was run against a live server.

This folder obeys `../CONVENTIONS.md` and never contradicts the authoritative sources (final answered request, subsystem gap register). Facts tagged [VERIFIED] were observed in-tool; proposals are [DEFAULT — adjustable] ; unresolved work is tracked [OPEN: ...] .

Made with love ♥ by Helix Development.