

Helix Thready — Component Library

Table of contents

1. Layering
2. Component taxonomy
3. Shared primitives (verbatim from design_system)
4. Angular adapters (verbatim interfaces)
5. Thready composite components
- 5b. Component state lifecycle
6. Component contract (anatomy · props · states · ally)
 - 6.1 Additional component contracts
7. Per-platform adapters
 - 7.1 Per-component variant matrix (all platforms)
8. States, empty/skeleton/error
9. Testing the library
10. Build backlog & gaps
11. Open items

Rev	Date	Author	Change
1	2026-07-21	swarm (design)	Initial complete draft: shared <code>.ds-*</code> primitives (verbatim), Thready composites, per-platform adapters, states/anatomy, build backlog, testing
2	2026-07-21	swarm (design · review)	Second-pass review: added a TDD reproduce-first (RED) test for <code>thready-processing-pipeline</code> ; added the mandated Challenges scenario-bank test type (<code>[GAP: 9.3]</code>) + backlog item
3	2026-07-22	swarm (design · Pass 3)	Depth pass: verbatim primitives table completed against source (<code>--btn--secondary/--ghost</code> , <code>--elev-flat</code> , <code>--fg-2</code> / <code>--meta</code> / <code>--border-soft</code> aliases); component state-lifecycle diagram (§5b) + <code>.mmd</code> ; per-platform variant matrix for every composite (§7.1 Angular/React/KMP/Flutter/TUI + status); five more component contracts (thread-row, hashtag-chip, search-bar, wizard, branding-editor, toast, §6.1); a11y name/role/keyboard per composite

Table of contents

- 1. Layering
- 2. Component taxonomy
- 3. Shared primitives (verbatim from `design_system`)
- 4. Angular adapters (verbatim interfaces)
- 5. Thready composite components
- 5b. Component state lifecycle
- 6. Component contract (anatomy · props · states · a11y)
 - 6.1 Additional component contracts
- 7. Per-platform adapters
 - 7.1 Per-component variant matrix (all platforms)

- 8. States, empty/skeleton/error
- 9. Testing the library
- 10. Build backlog & gaps
- 11. Open items


1. Layering

Three layers, bottom-up:

1. **Tokens** — `core.css` + `themes/thready.css` (see `design-system.md`).
2. **Primitives** — the **shared, framework-agnostic** `.ds-*` components from `vasic-digital/design_system` (`components/css/components.css`) + the three Angular adapters. **Consumed, not re-authored** [CONSTITUTION §11.4.28].
3. **Composites / Surfaces** — the **Thready-specific** components (thread rows, processing pipeline, search bar, branding editor, etc.) built *from* primitives and contributed upstream where generic.

The rule: **if a component is generic, it belongs in `design_system`** (contribute upstream); if it is Thready-domain (a thread/reply chain, a processing pipeline), it lives in Thready's component package but is still built entirely on tokens + primitives.

2. Component taxonomy



Rendered PNG/SVG exported via Docs Chain (\$11.4.65). Source: `diagrams/component-taxonomy.mmd`.

Explanation (for readers/models that cannot see the diagram). Tokens feed the **primitives** — the shared `.ds-*` set (`ds-btn`, `ds-input`, `ds-card`, `ds-nav`, `ds-footer`, `ds-badge`, `ds-link`) plus the two Angular utility components (`ds-theme-toggle`, `ds-language-picker`). Those primitives compose into the **Thready composites**: the stat card; the thread row and reply-chain; the processing pipeline and its progress+retry control; the direct/indirect hashtag chip; the search bar with filters and the search-result row; the asset card and media viewer; the wizard/stepper; the account switcher; the branding editor with its live AA meter; the toast/live-region; and the shared empty/skeleton/error states. Composites in turn assemble into **surfaces/templates** — the app shell, the dashboard, and the generic detail layout — which the concrete screens in `wireframes.md` instantiate. Everything above the token line is built only from the line below it, so a token or theme change re-skins the entire tree.

3. Shared primitives (verbatim from `design_system`)

These ship today `[VERIFIED — components/css/components.css]`. The `.ds-` prefix avoids host-framework collisions. All are token-bound (a theme swap re-tints them) and AA-inherited.

Component	Class(es)	Notes
Container / section	<code>.ds-container</code> , <code>.ds-section</code>	responsive gutters + section rhythm
Button	<code>.ds-btn</code> + <code>--primary</code> / <code>--secondary</code> / <code>--ghost</code>	focus-ring, reduced-motion aware
Card	<code>.ds-card</code> + <code>--raised</code>	<code>--elev-raised</code> shadow
Input	<code>.ds-input</code>	<code>--border-strong</code> , focus-ring, placeholder <code>--muted</code>
Link	<code>.ds-link</code>	<code>--accent</code> , underline on hover
Nav	<code>.ds-nav</code> , <code>.ds-nav__links</code> , <code>.ds-nav__link</code>	<code>aria-current</code> styling
Footer	<code>.ds-footer</code>	carries the slogan (\$brand-assets)
Badge	<code>.ds-badge</code> + <code>--success</code> / <code>--warn</code> / <code>--danger</code>	semantic, <code>color-mix</code> tint
Brand mark	<code>.ds-brand-mark</code>	decorative <code>--brand</code> only

Example (verbatim button contract, **all three variants**

[[VERIFIED](#) — [components/css/components.css](#)]):

```
.ds-btn { display:inline-flex; align-items:center; gap:var(--space-2);
  font:500 var(--text-base)/1 var(--font-body); padding:var(--space-3) var(--space-5);
  border-radius:var(--radius-sm); border:1px solid transparent; cursor:pointer;
  transition: background-color var(--motion-fast) var(--ease-standard),
    color var(--motion-fast) var(--ease-standard),
    box-shadow var(--motion-fast) var(--ease-standard); }
.ds-btn:focus-visible { outline:none; box-shadow:var(--focus-ring); }
.ds-btn--primary { background:var(--accent); color:var(--accent-on); }
.ds-btn--primary:hover { background:var(--accent-hover); } /* color-mix(accent, black 8%) */
.ds-btn--primary:active { background:var(--accent-active); } /* color-mix(accent, black 14%) */
.ds-btn--secondary { background:transparent; color:var(--fg); border-color:var(--border-
  strong); }
.ds-btn--secondary:hover { background:var(--surface-warm); }
.ds-btn--ghost { background:transparent; color:var(--accent); }
.ds-btn--ghost:hover { background:color-mix(in oklab, var(--accent), transparent 90%); }
@media (prefers-reduced-motion: reduce) { .ds-btn { transition:none; } }
```

The `.ds-container` responsive gutters and `.ds-section` rhythm are token-driven at the two breakpoints (768 / 1024px) [[VERIFIED](#)]; the badge tints use `color-mix(in oklab, <semantic>, transparent 90%)`, so a theme swap re-tints every semantic badge without new CSS. Additional verified structural aliases the primitives lean on: `--elev-flat: none`, `--fg-2 / --meta (= --fg / --muted)`, and `--border-soft (= --border)` — declared once in `core.css` /theme so composites never hard-code a value.

4. Angular adapters (verbatim interfaces)

Three shipped Angular adapters [[VERIFIED](#) — [components/angular/*](#)] that Thready consumes as-is:

- **ThemeService** — signal `choice: 'light' | 'dark' | 'system'`, `set()`, `resolved()`; stamps `data-theme / .dark`, persists to `${prefix}-theme`; SSR-safe.
- **I18nService** — signal `lang`, `t(key)`, `set(code)`; injected `DS_DICTIONARY / DS_LOCALES`; persists to `${prefix}-lang`; roadmap notes drop-in Transloco migration.
- **FooterComponent** — the “Made with ♥ by Helix Development” pattern (lucide `Heart` SVG + `U+2665` + text fallback, `aria-label="love"`).
- Utility components: **ThemeToggleComponent** (`ds-theme-toggle`), **LanguagePickerComponent** (`ds-language-picker`).
- Config: **DS_CONFIG** (`storagePrefix`, `defaultTheme`, `defaultLocale`), **DS_LOCALES**, **DS_DICTIONARY** injection tokens.

```
// The exact injection contract Thready provides at bootstrap (see design-system.md §3.3)
export interface DsConfig { storagePrefix: string; defaultTheme?: 'light'|'dark'|'system';
  defaultLocale?: string; }
export type DsDictionary = Record<string, Record<string, string>>;
export interface Locale { code: string; label: string; }
```


5. Thready composite components

Built on §3/§4. Each is listed with its purpose and the primitives it uses. `[DEFAULT – adjustable]` API names.

Component	Purpose	Built from	Used in
<code>thready-stat-card</code>	KPI tile (channels, posts, assets)	<code>.ds-card</code> , type tokens	Dashboard
<code>thready-thread-row</code>	One complete post = root + reply count	<code>.ds-card</code> /list, <code>hashtag-chip</code> , <code>status-badge</code>	Channel detail, Dashboard
<code>thready-reply-chain</code>	Expandable organic replies (system replies separated)	list, tokens	Post detail
<code>thready-hashtag-chip</code>	Tag with direct/indirect distinction	<code>.ds-badge</code> , <code>--brand</code> / <code>--muted</code>	everywhere tags show
<code>thready-processing-pipeline</code>	Ordered steps download→...→reply + per-step status	<code>progress</code> , <code>status-badge</code>	Post detail
<code>thready-progress</code>	Determinate/indeterminate bar + retry affordance	tokens, <code>.ds-btn--ghost</code>	Dashboard queue, Post detail
<code>thready-status-badge</code>	queued/running/processed/failed	<code>.ds-badge</code> semantics	lists, detail
<code>thready-search-bar</code>	Query + scope + mode + filters	<code>.ds-input</code> , chips, <code>.ds-btn</code>	Search, app shell
<code>thready-search-result</code>	Scored result row → route	list, tokens	Search
<code>thready-asset-card</code> / <code>thready-media-viewer</code>	Media tile + Range/HLS viewer	<code>.ds-card</code> , native <code><video></code> / player	Assets
<code>thready-wizard</code> (stepper)	Multi-step flows (Add-Channel)	<code>.ds-card</code> , <code>.ds-btn</code> , form fields	Add-Channel
<code>thready-account-switcher</code>	Multi-Account membership switch	menu, <code>.ds-nav</code>	app shell
<code>thready-branding-editor</code>	White-label editor + live AA meter	<code>.ds-input</code> , swatches, <code>.ds-badge</code>	Settings › Branding
<code>thready-messenger-signin</code>	Interactive/non-interactive sign-in	form, <code>.ds-btn</code>	Settings, Add-Channel
<code>thready-toast</code> / live-region	Async result + SR announcements	tokens, ARIA live	global
<code>thready-empty</code> / <code>thready-skeleton</code>	Empty & loading states	tokens	every list/detail

5b. Component state lifecycle

Every data-bearing composite moves through **one** state machine (the legend in [wireframes §1.1](#)). Specifying it once means no screen ships a missing state and the visual-regression matrix (§9) has an exhaustive list of cells to cover.



Rendered PNG/SVG exported via Docs Chain (§11.4.65). Source: `diagrams/component-state-lifecycle.mmd`.

Explanation (for readers/models that cannot see the diagram). A component starts **Idle**, then enters **Loading** on mount or fetch. To avoid a flash of placeholder for fast responses, the skeleton only shows after ~150ms (**Loading** → **Skeleton**); a fast response goes straight to **Content**. A resolved fetch with zero rows becomes **Empty** (never a blank pane — an icon, a one-line reason, and a primary action), and a failed fetch becomes **Error** (page-level with retry, or field-level inline).

From **Content** the component can refetch (back to **Loading**), take keyboard focus (**Focused**, drawn with the verified `--focus-ring`), or — for forms — submit into **Validating**. A validating submit that the server accepts returns to **Content** with the optimistic value confirmed; one the server rejects with `4xx` field errors moves to **InvalidInline** (`--danger`, `aria-describedby` to the message), from which the user corrects and resubmits. **Disabled** covers RBAC-gated or offline controls (muted, `aria-disabled`, not

focus-trapping). Retry and the empty-state primary action both re-enter Loading, so the loop is closed. Every arrow here is a **test cell**: the Challenges scenario banks (§9) drive a component through each transition and capture runtime evidence, and each terminal state is a row in the visual-regression themexstate matrix.

6. Component contract (anatomy · props · states · a11y)

Every Thready component is documented to this contract. Worked example — `thready-processing-pipeline`:

```
// thready-processing-pipeline — anatomy + props (Angular signal inputs) [DEFAULT — adjustable]
export interface ProcessingStep {
  id: 'classify'|'download'|'convert'|'analyze'|'research'|'reply';
  label: string;
  state: 'queued'|'running'|'done'|'failed'|'skipped';
  progress?: number;           // 0..1 for running
  error?: string;
}
@Component({ selector: 'thready-processing-pipeline', /* ... */ })
export class ProcessingPipelineComponent {
  steps      = input.required<ProcessingStep[]>();           // ordered per precedence
  precedence = input<string>('download > convert > analyze > research > reply');
  retryStep  = output<ProcessingStep['id']>();              // idempotent single-claim retry
}
```

- **Anatomy:** ordered step rows (icon + label + state + optional progress), a precedence caption, and an inline retry on `failed`.
- **States:** `queued` (muted), `running` (accent progress), `done` (success), `failed` (danger + retry), `skipped` (muted italic).
- **Events:** binds `processing.progress` / `processing.completed` / `processing.failed` from WS/SSE.
- **A11y:** each step is a list item with `aria-label` = “`label` : `state`”; progress uses `role="progressbar"` with `aria-valuenow`; the retry is a real `<button>` with a clear name; updates are announced via a polite live region; motion honors `prefers-reduced-motion`.

The same contract (anatomy / props / all interaction states / a11y name+role+keyboard / theme light+dark) is authored for **every** component in §5 — this is the spec the Figma component set (`prototypes.md`) and the implementation must both satisfy.

6.1 Additional component contracts

The five most load-bearing composites, to the same contract `[DEFAULT — adjustable API names, OPEN THREADY-DES-11]`:

`thready-thread-row` — one complete post (root + organic reply count).

```
export interface ThreadRow {
  postId: string; author: string; excerpt: string; replyCount: number;
  tags: HashTag[]; status: 'queued'|'running'|'processed'|'failed';
  hasSystemReplies: boolean; // system replies are separated, not counted
}
@Component({ selector: 'thready-thread-row' })
export class ThreadRowComponent {
  row = input.required<ThreadRow>();
  expanded = model(false); // >/> discloses the organic reply chain inline
  open = output<string>(); // routes to Post detail
}
```

- **Anatomy:** excerpt + ↵N reply count + hashtag chips + status badge + disclosure caret.
- **States:** default / hover / focus-visible / expanded / running (inline % on the status badge) / failed (danger badge). **A11y:** row is a `role="button"` with `aria-expanded`; Enter/Space toggles disclosure, → / ← expand/collapse; the count reads “12 replies”.

thready-hashtag-chip — a tag with the **direct vs. AI-indirect** distinction.

```
export interface HashTag { label: string; origin: 'direct'|'indirect'; }
// direct = --brand fill / brand-ink; indirect = --muted outline + a "derived" tooltip.
```

- **A11y:** indirect chips append “(derived)” to the accessible name so the origin is not color-only; chips are focusable when interactive (filter-on-click) and inert when decorative.

thready-search-bar — query + mode + scope + filters.

- **Props:** `query = model<string>()`, `mode = model<'semantic'|'keyword'|'hybrid'>()`, `scope = model<Scope[]>()`, `filters`, `search = output<SearchRequest>()`.
- **States:** idle (recent searches) / typing / validating (busy) / degraded (`--warn` banner + score column hidden when on the hash-embedder `[GAP: 2.1]`). **A11y:** a labelled `role="search"`; mode is a radio group, scope a checkbox group with ≥ 1 enforced; results announced via a polite live region.

thready-wizard (stepper) — multi-step flows (Add-Channel).

- **Props:** `steps`, `current = model<number>()`, per-step `valid` guard, `complete = output()`.
- **Behavior:** Next gated on step validity; Back/ Esc never loses entered data. **A11y:** `aria-current="step"`; each step is a labelled region; the busy step sets `aria-busy` (Resolve).

thready-branding-editor + **live AA meter** — the white-label surface.

```

export interface AccentCheck { hex: string; surface: string; ratio: number; passes: boolean;
  suggestion?: string; }
@Component({ selector: 'thready-branding-editor' })
export class BrandingEditorComponent {
  value = model<Branding>();
  aaLight = computed<AccentCheck>(() => contrast(this.value().accentLight, '#ffffff'));
  aaDark = computed<AccentCheck>(() => contrast(this.value().accentDark, '#020817'));
  save = output<Branding>(); // disabled while any AccentCheck.passes === false
}

```

- **Contract:** the client meter and the server `ValidateAccent` gate **MUST agree on the ratio** (theming §10.1); a server `422` re-opens the offending field. **States:** default / dirty (unsaved guard) / previewing / validating / `422` / success (audit-logged). **A11y:** each swatch pairs a hex `<input>` with a color picker sharing one label; the AA readout is `aria-live="polite"` (“accent 3.1:1, below AA 4.5:1 — try #446E12”).

thready-toast / **live-region** — async results + SR announcements.

- **Props:** `kind: 'success' | 'warn' | 'danger' | 'info'`, `message`, `action?`, `timeout`.
- **A11y:** `role="status"` (polite) for info/success, `role="alert"` (assertive) for danger; auto-dismiss pauses on hover/focus; never the only channel for a critical error (also inline).

7. Per/platform adapters

The composites are specified once and realized per platform from the same tokens. Honest status:

Platform	Realization	Status
Angular (Web/Desktop)	Standalone Angular components on <code>.ds-*</code> + adapters	Primary; Web first [OPERATOR]
React	<code>UI-Components-React</code>	SCAFFOLD/FLAGGED [GAP: 8.6] — re-audit before use
KMP/Compose	<code>UI-Components-KMP</code> + token bridge	SCAFFOLD, no CI/publish [GAP: 8.4]
Flutter / Qt-Aurora	<code>helix_design</code> + <code>helix_ui</code>	SCAFFOLD [GAP: 8.2/8.3] ; Qt/ArkTS via <code>helix_shims</code> [GAP: 8.5]
TUI	Lipgloss component styles	pattern exists [VERIFIED — <code>helix_track/llms_verifier/.../tui</code>]

Cross-platform component parity is a contract, not an aspiration: each composite's states and a11y semantics must match across platforms (a `processing-pipeline` behaves the same on Web, Compose and the TUI). Parity is enforced by the visual-regression bank (\$9) once CI lands `[GAP: 9.3]`.

7.1 Per/omponent variant matrix (all platforms)

Each composite is realized per platform from the same tokens. The cell records the **realization mechanism** and honest **status**; a blank/ `—` means “renders as its primitives, no bespoke work”. Legend: usable today
• ◐ scaffold/needs-hardening • ◯ not-yet / deferred.

Composite	Angular (Web/Desktop)	React ◀ [GAP: 8.6]	KMP/Compose ◀ [GAP: 8.4]	Flutter/Qt ◀ [GAP: 8.2/8.3]	TUI [VERIFIED]
stat-card	.ds-card + type tokens	Card ◀	Card / Surface ◀	Card ○	Lipgloss bordered box
thread-row / reply-chain	standalone cmp	list item ◀	LazyColumn row ◀	ListTile ○	list row + disclosure
hashtag-chip (direct/indirect)	.ds-badge variants	badge ◀	AssistChip ◀	Chip ○	tinted #tag span
processing-pipeline	signal-input cmp	◀	Column of step rows ◀	○	vertical step list
progress + retry	<progress> / .ds-btn--ghost	◀	LinearProgressIndicator ◀	LinearProgressIndicator ○	 bar + [r]etry
status-badge	.ds-badge semantics	◀	badge ◀	badge ○	glyph ✓🔍⚠
search-bar + filters	.ds-input + chips	◀	SearchBar ◀	TextField ○	query line + selectors
search-result	list row	◀	row ◀	row ○	scored row
asset-card / media-viewer	<video> + Range/HLS	◀	ExoPlayer / AVPlayer ◀	platform player ○	(link-out; no inline media) ◀
wizard (stepper)	.ds-card steps	◀	HorizontalPager ◀	Stepper ○	numbered steps
account-switcher	menu on .ds-nav	◀	DropDownMenu ◀	PopupMenu ○	acct: selector
branding-editor + AA meter	inputs + swatches	◀	color pickers ◀	○	(read-only preview) ◀
		◀	form ◀	form ○	

Composi e	Angular (Web/ Desktop)	React ◀ [GAP: 8.6]	KMP/Compose ◀ [GAP: 8.4]	Flutter/Qt ◀ [GAP: 8.2/8.3]	TUI [VERIFIED]
messenger- signin	form + .ds-btn				prompt sequence
toast / live-region	ARIA live	◀	Snackbar ◀	SnackBar ○	notifications.go pane
empty / skeleton n	tokens	◀	shimmer/ placeholder ◀	shimmer ○	text placeholder

How to read the honesty here. Only the **Angular** and **TUI** columns are grounded in usable in-house code today (the `.ds-*` set + adapters, and the verified Bubble Tea/Lipgloss pattern). The **KMP/Compose**, **Flutter/Qt** and **React** columns are the *plan* on scaffolds — their status badges are the gap-register reality (`[GAP: 8.2/8.3/8.4/8.6]`), and the token bridge (\$7) is what makes a Compose/Flutter cell a re-tint rather than a re-author. A cell is only marked ◀ when its platform package is real; nothing in a ◀/○ column may be claimed to “work” until its workable item (\$10) closes. Two intentional non-parity cells: the TUI `media-viewer` and `branding-editor` are link-out / read-only (a terminal cannot show inline video or a live color picker), which is a documented, tested divergence rather than a missing state.

8. States, empty/skeleton/error

Uniform, reusable states (the request demands “full forms validations, hints, tooltips”):

- **Empty:** `thready-empty` — icon + one-line explanation + a primary action (e.g. “Add your first channel”). Never a blank screen.
- **Skeleton:** `thready-skeleton` — token-tinted placeholder blocks during load (respects reduced motion — static shimmer off).
- **Error:** inline (`--danger` , field-level, with hint) and page-level (`thready-error` with retry).
- **Validation:** synchronous + server-side; messages are specific and actionable (e.g. branding accent “6.03:1 needed, got 3.1:1 — try #446E12”).
- **Tooltips/hints:** on every non-obvious control; keyboard-reachable, SR-described.

9. Testing the library

Per `[CONSTITUTION §11.4.27/162]` and `../testing/index.md`:

- **Unit** (Jasmine/Karma) — component logic, inputs/outputs.
- **a11y** (`cypress-axe` /Playwright+axe) — zero critical violations per component/state.

- **Visual-regression** — `ScreenDiff` (pixel) + `VisualRegression` (LLM-vision) across the theme×state matrix (§ design-system.md §8); `ReplayBuffer` for interaction sequences. The family has **no CI today** `[GAP: 9.3]` → workable item **THREADY-DES-VR-01** adds it.
- **Interaction** (Cypress/Playwright) — the flows in `ux-flows.md`.
- **Challenges** (`vasic-digital/challenges`) — one of the 15 mandated test types `[CONSTITUTION §11.4.27]`. Author Thready UI/UX **scenario banks** (adversarial/edge-case decks: a 40-step reply chain, an all-`failed` pipeline, a 12-hashtag post, RTL + Cyrillic overflow, a white-label accent at the 4.5:1 boundary) run against the real component tree. This is the second half of `[GAP: 9.3]` (the first half is CI for the visual-regression family) → workable item **THREADY-DES-CHAL-01**.
- **Runtime evidence mandatory** (HelixQA anti-bluff): screenshots + DOM snapshot + axe report per case — a green test proves real rendering, not a stub.

TDD reproduce-first (RED → GREEN) `[CONSTITUTION §11.4.27/43]`. Every component test starts as a **failing RED test that reproduces the defect**, then the component is implemented/fixed to GREEN, then the case matrix (§6) is filled in. Worked example — the `thready-processing-pipeline` invariant “a **failed** step **MUST** expose a keyboard-focusable retry, and retry **MUST** be idempotent (single claim, never double-process)”:

```
// processing-pipeline.spec.ts — RED FIRST (written before the component/behavior exists).
import { render, screen } from '@testing-library/angular';
import userEvent from '@testing-library/user-event';
import { ProcessingPipelineComponent } from './processing-pipeline.component';

describe('thready-processing-pipeline (reproduce-first)', () => {
  it('RED: a failed step exposes a focusable retry button', async () => {
    const emitted: string[] = [];
    await render(ProcessingPipelineComponent, {
      inputs: { steps: [{ id: 'convert', label: 'convert', state: 'failed' }] },
      on: { retryStep: (id: string) => emitted.push(id) },
    });
    const retry = screen.getByRole('button', { name: /retry/i }); // FAILS until the button
      exists → RED
    retry.focus();
    expect(document.activeElement).toBe(retry); // keyboard-reachable

    // EXTEND: retry is single-claim/idempotent — double activation emits exactly one retry.
    await userEvent.click(retry);
    await userEvent.click(retry);
    expect(emitted).toEqual(['convert']); // debounced/disabled-after-claim; never double-
      processes [$3.3]
  });

  it('a running step announces progress via role=progressbar with aria-valuenow', async () => {
    await render(ProcessingPipelineComponent, {
      inputs: { steps: [{ id: 'download', label: 'download', state: 'running', progress:
        0.63 }] },
    });
    const bar = screen.getByRole('progressbar');
    expect(bar).toHaveAttribute('aria-valuenow', '63');
  });
});
```

```
# per-component contract test (excerpt)
component: thready-processing-pipeline
cases:
  - state: running,    step: download, progress: 0.63, expect: [progressbar aria-valuenow=63, no-
    retry]
  - state: failed,     step: convert,  expect: [danger badge, retry button focusable, axe: 0
    critical]
  - theme: [thready-light, thready-dark]
  - reduced_motion: true, expect: no-animation
evidence: [screenshot, dom-snapshot, axe-report]
```

10. Build backlog & gaps

Ordered by the **Web + CLI first** priority `[OPERATOR]`:

1. **THREADY-DES-WEB-01** — Angular composite set (\$5) on the published `design_system` primitives. Blocks on `[GAP: 8.1]` (publish `@vasic-digital/design-system` to npm) — until then consume via git dependency.
2. **THREADY-DES-TUI-01** — Lipgloss component styles from the token export (`[VERIFIED]` pattern).
3. **THREADY-DES-VR-01** — CI for the visual-regression family `[GAP: 9.3]`.
4. **THREADY-DES-CHAL-01** — Thready UI/UX **Challenges** scenario banks (mandated test type, `vasic-digital/challenges`) — the second half of `[GAP: 9.3]` `[CONSTITUTION §11.4.27]`.
5. **THREADY-DES-KMP-01** — `UI-Components-KMP` CI + Maven publish + token bridge `[GAP: 8.4]`.
6. **THREADY-DES-FLUT-01 / -QT-01** — `helix_design` per-platform packages `[GAP: 8.2/8.3]`; native ArkTS/Qt via `helix_shims` `[GAP: 8.5]`.
7. **THREADY-DES-REACT-01** — only if a React surface is required; re-audit `UI-Components-React` first `[GAP: 8.6]`.

Honesty: only the Web (Angular) and TUI (Lipgloss) realizations are grounded in verified, usable in-house code today. Every other platform's component package is a **scaffold** — do not claim those components work until their workable item closes.

11. Open items

- `[OPEN: THREADY-DES-11]` — finalize the Thready composite public API names with the web implementation team (names here are `[DEFAULT – adjustable]`).
- `[OPEN: THREADY-DES-12]` — decide which composites are generic enough to contribute upstream to `design_system` vs. keep in Thready's package.
- `[OPEN: THREADY-DES-04]` — Cyrillic font-subset verification affects text-bearing components.

Made with love ♥ by Helix Development.