

Helix Thready — Desktop (Tauri 2) Screen Designs

Table of contents

- 1. Position
- 2. Catalogue
- 3. Desktop-differences catalogue
 - 3.1 Keyboard shortcuts
 - 3.2 Offline cache
 - 3.3 Notifications
 - 3.4 File-drop
 - 3.5 Tray — deferred to v2 ([CLOSED: THREADY-DES-08]) [DEFAULT — adjustable]
 - 3.6 Native menus & title bar
 - 3.7 Theming
- 4. Open items

Rev	Date	Author	Change
1	2026-07-22	swarm (design · screens)	Initial: Tauri shell artifact + desktop-differences catalogue (shortcuts, offline cache, notifications, file-drop, tray, menus)
2	2026-07-22	swarm (design · decisions)	Operator ruling ([CLOSED: THREADY-DES-08]): desktop v1 ships the wrapped web UI only; tray / native notifications / file-drop deferred — §1/§3 designs re-labelled as the v2 contract ; THREADY-DES-16 unaffected

Table of contents

- 1. Position
- 2. Catalogue
- 3. Desktop-differences catalogue
- 4. Open items

1. Position

The desktop client is **Tauri 2 wrapping the Angular 19 product portal** — “no separate token work; OS-specific chrome overrides only”

[[VERIFIED — design-system.md §7 platform table; wireframes.md §1](#)]. There are therefore **no separate desktop screen designs**: every screen is the responsive web portal ([wireframes.md §3](#), realized in [screens/web/](#)). What *is* desktop-specific is the shell around it — title bar, menus, tray, native notifications, shortcuts-as-accelerators, offline behavior, drag-and-drop — and that is what this directory designs.

Decided (operator ruling 2026-07-22, [[CLOSED: THREADY-DES-08](#)]): **desktop v1 ships the wrapped web UI only** — tray, native notifications and file-drop are **designed-but-deferred**, and the mocks below are the **v2 contract** (their details stay [[DEFAULT — adjustable](#)]), not v1 scope.

2. Catalogue

File	Content	Ground truth	Status
desktop-shell.html	Self-contained artifact: Tauri window with per-OS custom title bar (macOS traffic lights + global menu bar / Windows caption buttons / Linux CSD), native menu map, wrapped app shell + Dashboard, tray popover mock, native notification mock, file-drop overlay; light+dark via [data-theme="dark"]	design-system §7 , wireframes §3.1/§3.3/§1.2 , theming §2	shell grounded (v1); tray/notifications/file-drop deferred — v2 contract ([CLOSED: THREADY-DES-08])

3. Desktop-differences catalogue

Everything the desktop build adds/changes relative to the same web app running in a browser tab.

3.1 Keyboard shortcuts

The web keyboard model is **verified ground truth** ([wireframes §1.2](#)) and works unchanged; desktop promotes it to native menu accelerators so shortcuts appear in menus and work when focus is in webview chrome:

Binding	Action	Source
<code>/</code> or <code>Ctrl/⌘+K</code>	focus global search	wireframes \$1.2 (verified web model)
<code>g</code> then <code>d/c/s/a/k</code>	go to Dashboard/Channels/Search/Assets/Skills	wireframes \$1.2
<code>Esc</code> , <code>?</code> , <code>[/]</code> , <code>Tab</code> , <code>Enter</code> / <code>Space</code>	overlays / help / nav collapse / focus / activate	wireframes \$1.2
<code>Ctrl/⌘+N</code>	New Channel (Add-Channel wizard)	<code>[DEFAULT — adjustable]</code> desktop accelerator
<code>Ctrl/⌘+W</code>	close window (v1) — hide-to-tray is the v2 behavior	<code>[DEFAULT — adjustable]</code> , tray deferred to v2 (<code>[CLOSED: THREADY-DES-08]</code>)
<code>Ctrl/⌘+ +/- /0</code>	zoom in/out/reset (webview zoom)	<code>[DEFAULT — adjustable]</code>
Global (system-wide) show/hide shortcut	none by default	deliberately omitted — not grounded

Rule: desktop MUST NOT rebind any verified web binding; accelerators are additive.

3.2 Offline cache

The web app already specifies connectivity states for mobile (banner *live/reconnecting/offline*, cached snapshot reads “stale · updated 3m ago”, queued optimistic mutations, WS→polling fallback — wireframes §6.2). Desktop adopts the **same contract** `[DEFAULT — adjustable]`:

- Last-snapshot cache for Dashboard/Channels/Search results renders when offline; footer shows `offline cache: fresh | stale (3m) | offline`.
- Mutations queue and flush on reconnect with the same conflict-resolution toast.
- The Tauri shell adds nothing beyond persistence of the webview cache — no separate sync engine is designed (or claimed).

3.3 Notifications

- In-focus: the standard in-app toast (`thready-toast`) — identical to web.
- Hidden/unfocused: native OS notification on `processing.completed` / `processing.failed` (the verified Event Bus contract, ux-flows §3); click focuses the window on the Post detail. Never both at once. **Deferred to v2** (`[CLOSED: THREADY-DES-08]` , operator ruling 2026-07-22): v1 ships the in-app toast only; this native-notification design is the v2 contract.

3.4 File-drop

File-drop ships **nothing in v1** ([CLOSED: THREADY-DES-08] — deferred; the designs below are the v2 contract). Two distinct cases, deliberately separated for honesty:

1. **Text/URL drop** (grounded): a dropped string matching `t.me/...` or `max.ru/join/...` opens the **Add-Channel wizard at step 3 with the link pre-filled** — exactly the paste+Resolve step that already exists (wireframes §3.4). Non-matching text is rejected with the same `422` message the Resolve step uses.
2. **Media-file drop** ([OPEN: THREADY-DES-16]): there is **no ground-truth ingest path for local files** — posts and assets originate from messenger channels, and the Assets library has no upload flow in the wireframes. Until product decides whether local-file ingest exists at all, the drop overlay names the gap and does nothing else. Never fake an upload UI.

3.5 Tray — deferred to v2 ([CLOSED: THREADY-DES-08]) [DEFAULT — adjustable]

Close hides to tray; background WS/SSE subscriptions continue; tray badge = active processing count (danger tint on failure); popover: live queue summary, Open, Pause polling, Quit. See the mock in `desktop-shell.html`.

3.6 Native menus & title bar

Per-OS chrome only (macOS global menu bar + traffic lights; Windows/Linux in-window menu row + caption buttons); the menu **map** mirrors the web IA and verified shortcuts (table in `desktop-shell.html`); menu structure itself [DEFAULT — adjustable]. Window title carries the active Account (`Thready — Acme`).

3.7 Theming

Identical to web: shared `ThemeService` (`thready-theme` storage, system default) + the per-Account white-label `:root[data-account=...]` injection (theming §2/§6). The View ▶ Appearance menu drives the same three-state toggle. A pre-paint head script avoids the wrong-theme flash on the webview (theming §2).

4. Open items

- [CLOSED: THREADY-DES-08] — **decided** (operator ruling 2026-07-22): desktop v1 ships the wrapped web UI only; tray, native notifications, close-to-tray and file-drop are **designed-but-deferred** — the §3 designs and the `desktop-shell.html` mocks are the **v2 contract** (details stay [DEFAULT — adjustable] until v2 lands).
- [OPEN: THREADY-DES-16] — local media-file ingest (file-drop case 2): decide whether a local upload path into the Asset Service exists at all; no UI is designed until it does.

Made with love ♥ by Helix Development.