

Helix Thready — Marketing Site SEO / Meta Specification

Table of contents

1. Scope and ground rules

2. Canonical origin and URL model

3. Per-page titles and descriptions

4. Open Graph and Twitter cards

4.1 Image slots — what actually exists

4.2 Per-page template

5. JSON-LD — SoftwareApplication

6. sitemap.xml template

7. robots.txt template

8. Canonical and hreflang notes (en / ru / sr-Cyrl)

9. Operator placeholders and open ends

Rev	Date	Author	Change
1	2026-07-22	swarm (design · marketing)	Initial SEO/meta spec under the active scoping of <code>[OPEN: THREADY-DES-MKT-02]</code> : per-page title/description/OG/Twitter values derived from real product copy; JSON-LD <code>SoftwareApplication</code> template restricted to doc-backed fields; sitemap.xml + robots.txt templates; canonical/hreflang notes for en / ru / sr-Cyrl

Table of contents

- 1. Scope and ground rules
- 2. Canonical origin and URL model
- 3. Per-page titles and descriptions
- 4. Open Graph and Twitter cards
- 5. JSON-LD — SoftwareApplication
- 6. sitemap.xml template

- 7. robots.txt template
- 8. Canonical and hreflang notes (en / ru / sr-Cyrl)
- 9. Operator placeholders and open ends

1. Scope and ground rules

This document is the meta/SEO deliverable of the **active scoping of** `[OPEN: THREADY-DES-MKT-02]` (see `README.md` §7). It covers the six designed marketing pages — `landing`, `features`, `download`, `privacy`, `terms`, `imprint` — rendered by the **Angular 22 marketing app with SSR + SSG/prerender** (`design-system.md` §7 note `[Q17]`), where every value below lives as route-level metadata emitted at prerender time.

Ground rules, identical to the page set `[CONVENTIONS §7 — no bluff]`:

- **Every description derives from real product copy** already registered in `README.md` §5 — no new product claim is minted here.
- **No invented assets:** every image slot references a file the **raster pipeline** actually emits, or the hand-authored master SVGs in `../../assets/`.
- **No invented identities:** social handles, organization URLs and final locale URLs are `[OPERATOR]` slots, never guessed.
- Copy contract as everywhere on the marketing surface: calm, understated, no exclamation marks (`DESIGN.md` §1 voice and tone).

2. Canonical origin and URL model

The deployment ground truth names exactly one production domain (`deployment index` §1, table “The three subdomains (from §8.2)”):

Environment	Domain
Development	<code>dev.thready.hxd3v.com</code>
Staging	<code>sta.thready.hxd3v.com</code>
Production	<code>thready.hxd3v.com</code>

Throughout this spec, `{ORIGIN}` denotes the marketing-site origin. `[OPERATOR]` : **confirm whether the marketing site is served from** `https://thready.hxd3v.com` **itself or from a dedicated host** — the deployment docs name the production domain for the system as a whole and do not separately place the marketing app.

Path model `[DEFAULT — adjustable]` (mirrors the designed page set one-to-one):

Page	Path (en default)
Landing	/
Features	/features
Download	/download
Privacy policy	/legal/privacy
Terms of service	/legal/terms
Imprint	/legal/imprint

Locale URLs for ru and sr-Cyrl: **[OPERATOR: final locale URLs]**. The working default in the templates below is a path prefix (`/ru/...`, `/sr/...`) **[DEFAULT – adjustable]**; see §8 for the hreflang mechanics either way.

3. Per-page titles and descriptions

Titles are the `<title>` values already carried by the designed pages. Descriptions are assembled only from copy on those pages (register rows cited). Targets: title ≤ 60 characters, description ≤ 160 characters.

Page	<title>	meta description	Provenance
Landing	Thready – read your threads, smarter	Thready follows the channels you already read, processes every post through an accountable AI pipeline, and turns threads into searchable research.	Tagline: brand-assets.md \$8.1 (README \$5 row 1); sentence: landing.html hero sub (rows 2/6/8)
Features	Features – Thready	Channels with visible backfill, threads kept intact, an AI pipeline you can watch, and search that admits its limits – how Thready works today.	landing.html feature cards / features.html card grid (rows 2, 4, 6, 8, 9)
Download	Download – Thready	Where Thready runs: the web portal first, a desktop app wrapping the same UI, a terminal client, and mobile clients in development. No store listing is live yet.	download.html statuses (rows 15–19, 26)
Privacy	Privacy policy – Thready	How Thready handles account data, connected channel content and processing artifacts. — interim, structural; [OPERATOR – replace after counsel text lands]	privacy.html \$2 inventories (rows 3, 5, 6, 12, 13, 25)
Terms	Terms of service – Thready	The agreement covering use of Thready. — interim, structural; [OPERATOR – replace after counsel text lands]	terms.html structure
Imprint	Imprint – Thready	Provider identification for Thready. — interim, structural; [OPERATOR – replace after counsel text lands]	imprint.html structure

Deployment gate: the three legal pages must not be deployed at all until their [OPERATOR – legal counsel text required] placeholders are replaced (each page’s design contract strip states this), so their interim descriptions can never reach an index ahead of counsel.

4. Open Graph and Twitter cards

4.1 Image slots — what actually exists

The raster pipeline (`generate-raster.sh`), honest-output contract — it never writes placeholder PNGs) emits, per `icon-export-matrix.md` and `brand-assets.md` \$5/\$5.1:

- `raster/web/icon-192.png` , `raster/web/icon-512.png` — PWA icons (deployed as `/icons/icon-192.png` , `/icons/icon-512.png` per the `manifest.webmanifest` block in `brand-assets.md` \$5.1);

- `raster/web/maskable-192.png`, `raster/web/maskable-512.png` — maskable variants;
- `raster/web/favicon.svg`, `favicon-16/32/48.png`, `favicon.ico` — favicon set;
- `raster/brand/logo-mark-128/256/512.png`, `raster/brand/logo-full-h64/h128.png`, `raster/brand/footer-slogan-h44.png` — brand lockup conveniences.

There is no 1200×630 (1.91:1) social-card render in the pipeline today. This spec does not pretend one exists: the `og:image` slot uses the real 512×512 launcher icon (`{ORIGIN}/icons/icon-512.png`) as the interim value, and the Twitter card type is `summary` (square art), **not** `summary_large_image`, until a dedicated social card is added to `generate-raster.sh` — tracked in §9.

4.2 Per-page template

One block per page; `{PATH}`, `{TITLE}`, `{DESCRIPTION}` come from §2/§3.

```
<link rel="canonical" href="{ORIGIN}{PATH}">
<meta property="og:type" content="website">
<meta property="og:site_name" content="Thready">
<meta property="og:title" content="{TITLE}">
<meta property="og:description" content="{DESCRIPTION}">
<meta property="og:url" content="{ORIGIN}{PATH}">
<meta property="og:image" content="{ORIGIN}/icons/icon-512.png">
<meta property="og:image:width" content="512">
<meta property="og:image:height" content="512">
<meta property="og:image:alt" content="Thready launcher icon — double-spiral mark">
<meta name="twitter:card" content="summary">
<meta name="twitter:title" content="{TITLE}">
<meta name="twitter:description" content="{DESCRIPTION}">
<meta name="twitter:image" content="{ORIGIN}/icons/icon-512.png">
```

Notes:

- `og:locale` / `og:locale:alternate` require `language_TERRITORY` values; the mapping from en / ru / sr-Cyrl to territory-qualified locales is `[OPERATOR]` (part of the final locale decision, §8) and the tags are omitted until then rather than guessed.
- `twitter:site` / `twitter:creator`: `[OPERATOR — social handles, if any exist]` — no handle is documented anywhere in the ground truth, so none is invented.
- The favicon and manifest `<head>` block is already specified verbatim in `brand-assets.md` §5.1 and is not duplicated here.

5. JSON-LD — SoftwareApplication

Emitted on the landing page only `[DEFAULT — adjustable]`. Restricted to fields with a documented source; everything else is deliberately omitted.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "SoftwareApplication",
  "name": "Thready",
  "slogan": "read your threads, smarter",
  "description":
    "Thready follows the channels you already read, processes every post through an
    accountable AI pipeline, and turns threads into searchable research.",
  "operatingSystem": "Web",
  "url": "{ORIGIN}/",
  "image": "{ORIGIN}/icons/icon-512.png",
  "applicationCategory": "[OPERATOR – category claim, not documented; choose or omit]",
  "author": {
    "@type": "Organization",
    "name": "Helix Development",
    "url": "[OPERATOR – organization URL, not documented]"
  }
}
</script>
```

Field provenance and deliberate omissions:

Field	Status	Source / reason
<code>name</code>	doc-backed	Product name throughout the design pack
<code>slogan</code>	doc-backed	brand-assets.md §8.1 tagline (README §5 row 1)
<code>description</code>	doc-backed	landing.html hero sub (README §5 rows 2/6/8)
<code>operatingSystem:</code> <code>"Web"</code>	doc-backed	Web is the primary and only production-usable surface today (README §5 row 15); scaffold clients are not listed as shipped platforms
<code>image</code>	doc-backed	Raster-pipeline output, §4.1
<code>author.name</code>	doc-backed	Locked attribution “Made with ♥ by Helix Development” (brand-assets.md §8)
<code>applicationCategory</code>	<code>[OPERATOR]</code>	No category claim documented — supply or omit
<code>author.url</code>	<code>[OPERATOR]</code>	No organization site documented — supply or omit
<code>offers</code>	omitted	No public pricing exists (terms.html §8 fact panel); inventing a price or “free” claim is a bluff either way
<code>aggregateRating</code> / <code>review</code>	omitted	No ratings exist; never fabricated
<code>downloadUrl</code> / <code>installUrl</code>	omitted	No installer is published (README §5 row 26)
<code>softwareVersion</code>	omitted	MVP in active development; no published version

6. sitemap.xml template

Six canonical URLs; each entry carries hreflang alternates for the three locales (values per §8; ru/sr URLs are the `[DEFAULT — adjustable]` path prefixes until `[OPERATOR: final locale URLs]` lands). `lastmod` is emitted by the SSG prerender build, not hand-maintained.

```

<?xml version="1.0" encoding="UTF-8"?>
<urlset xmlns="http://www.sitemaps.org/schemas/sitemap/0.9"
        xmlns:xhtml="http://www.w3.org/1999/xhtml">
  <url>
    <loc>{ORIGIN}</loc>
    <lastmod>{BUILD_DATE}</lastmod>
    <xhtml:link rel="alternate" hreflang="en" href="{ORIGIN}/"/>
    <xhtml:link rel="alternate" hreflang="ru" href="{ORIGIN}/ru"/>
    <xhtml:link rel="alternate" hreflang="sr-Cyrl" href="{ORIGIN}/sr"/>
    <xhtml:link rel="alternate" hreflang="x-default" href="{ORIGIN}/"/>
  </url>
  <url>
    <loc>{ORIGIN}/features</loc>
    <lastmod>{BUILD_DATE}</lastmod>
    <xhtml:link rel="alternate" hreflang="en" href="{ORIGIN}/features"/>
    <xhtml:link rel="alternate" hreflang="ru" href="{ORIGIN}/ru/features"/>
    <xhtml:link rel="alternate" hreflang="sr-Cyrl" href="{ORIGIN}/sr/features"/>
    <xhtml:link rel="alternate" hreflang="x-default" href="{ORIGIN}/features"/>
  </url>
  <url>
    <loc>{ORIGIN}/download</loc>
    <lastmod>{BUILD_DATE}</lastmod>
    <xhtml:link rel="alternate" hreflang="en" href="{ORIGIN}/download"/>
    <xhtml:link rel="alternate" hreflang="ru" href="{ORIGIN}/ru/download"/>
    <xhtml:link rel="alternate" hreflang="sr-Cyrl" href="{ORIGIN}/sr/download"/>
    <xhtml:link rel="alternate" hreflang="x-default" href="{ORIGIN}/download"/>
  </url>
  <url>
    <loc>{ORIGIN}/legal/privacy</loc>
    <lastmod>{BUILD_DATE}</lastmod>
    <xhtml:link rel="alternate" hreflang="en" href="{ORIGIN}/legal/privacy"/>
    <xhtml:link rel="alternate" hreflang="ru" href="{ORIGIN}/ru/legal/privacy"/>
    <xhtml:link rel="alternate" hreflang="sr-Cyrl" href="{ORIGIN}/sr/legal/privacy"/>
    <xhtml:link rel="alternate" hreflang="x-default" href="{ORIGIN}/legal/privacy"/>
  </url>
  <url>
    <loc>{ORIGIN}/legal/terms</loc>
    <lastmod>{BUILD_DATE}</lastmod>
    <xhtml:link rel="alternate" hreflang="en" href="{ORIGIN}/legal/terms"/>
    <xhtml:link rel="alternate" hreflang="ru" href="{ORIGIN}/ru/legal/terms"/>
    <xhtml:link rel="alternate" hreflang="sr-Cyrl" href="{ORIGIN}/sr/legal/terms"/>
    <xhtml:link rel="alternate" hreflang="x-default" href="{ORIGIN}/legal/terms"/>
  </url>
  <url>
    <loc>{ORIGIN}/legal/imprint</loc>
    <lastmod>{BUILD_DATE}</lastmod>
    <xhtml:link rel="alternate" hreflang="en" href="{ORIGIN}/legal/imprint"/>
    <xhtml:link rel="alternate" hreflang="ru" href="{ORIGIN}/ru/legal/imprint"/>
    <xhtml:link rel="alternate" hreflang="sr-Cyrl" href="{ORIGIN}/sr/legal/imprint"/>
    <xhtml:link rel="alternate" hreflang="x-default" href="{ORIGIN}/legal/imprint"/>
  </url>

```



```
</url>
</urlset>
```

The three legal URLs enter the sitemap **only once** **counsel text has replaced every placeholder** — before that the pages do not deploy at all (§3 deployment gate).

7. robots.txt template

Production marketing origin:

```
User-agent: *
Allow: /

Sitemap: {ORIGIN}/sitemap.xml
```

Operational notes, grounded in the deployment ground truth (deployment index §1):

- `dev.thready.hxd3v.com` and `sta.thready.hxd3v.com` are real, publicly-routable environment subdomains. They must not be indexed: serve them `User-agent: * / Disallow: /` and an `X-Robots-Tag: noindex` header `[DEFAULT — adjustable]` — robots.txt alone does not prevent indexing of discovered URLs.
- The signed-in product portal is an application, not a content site; whether any of it is crawlable is out of scope here and default-deny `[DEFAULT — adjustable]`.

8. Canonical and hreflang notes (en / ru / sr-Cyrl)

The locale set comes from the designed language picker (EN / RU / SR with values `en` / `ru` / `sr-Cyrl`) present on every marketing page.

- **Canonical:** every locale variant is self-canonical (its `rel=canonical` points to its own URL, never to the en page) — the variants are translations, not duplicates.
- **hreflang codes:** `en`, `ru`, and `sr-Cyrl` — the Serbian tag is script-qualified BCP-47, matching the picker value exactly (Serbian in Cyrillic script). If a Latin-script Serbian variant is ever added it would be `sr-Latn`, a separate alternate — not claimed today.
- **x-default:** points to the en URL `[DEFAULT — adjustable]` — en is the authoring language of the entire design pack.
- **Reciprocity:** every page's alternate cluster lists all three locales plus x-default, and every variant emits the same cluster (hreflang is only honored when reciprocal). The sitemap entries in §6 mirror the same clusters.
- **URL shape:** the `/ru/...`, `/sr/...` path prefixes are a working default only — `[OPERATOR: final locale URLs]` decides prefix vs subdomain vs anything else. Whatever lands, the invariants above (self-canonical, reciprocal clusters, script-qualified Serbian tag) carry over unchanged.

- **HTML `lang`**: each variant sets `<html lang>` to its locale (`en` , `ru` , `sr-Cyrl`) — the designed artifacts carry `lang="en"` as the en originals.

9. Operator placeholders and open ends

Everything a human must supply before this spec is deployable, in one place:

#	Slot	Where
1	Marketing-site origin (<code>{ORIGIN}</code>) — confirm <code>https://thready.hxd3v.com</code> or a dedicated host	\$2
2	Final locale URLs for ru / sr-Cyrl (prefix vs subdomain vs other)	\$2, \$6, \$8
3	Final meta descriptions for privacy / terms / imprint after counsel text lands	\$3
4	<code>og:locale</code> territory mapping for the three locales	\$4.2
5	Social handles (<code>twitter:site</code> / <code>twitter:creator</code>), if any exist	\$4.2
6	JSON-LD <code>applicationCategory</code> and <code>author.url</code> — supply or omit	\$5
7	A dedicated 1200×630 social-card render added to <code>generate-raster.sh</code> (then upgrade <code>og:image</code> and the Twitter card type to <code>summary_large_image</code>)	\$4.1
8	Analytics decision — adoption or deliberate absence — still open under <code>[OPEN: THREADY-DES-MKT-02]</code> ; it interacts with the privacy page's \$2.4 placeholder	README.md \$7

No JSON-LD, sitemap or robots artifact ships until slots 1–2 are decided; the legal URLs additionally wait on slot 3 and the counsel placeholders in the pages themselves.

Made with love ♥ by Helix Development.