

Helix Thready — Wireframes (Web · CLI/TUI · Mobile)

Table of contents

0. Upstream / Downstream & rendered screen sets

1. Conventions & responsive breakpoints

1.1 Interaction-state legend

1.2 Keyboard & focus model

1.3 Validation model

2. Web portal — information architecture

3. Web portal — screen wireframes

3.1 App shell

3.2 Login / MFA

3.3 Dashboard

3.4 Channels list & Add-Channel wizard

3.5 Channel detail (thread list)

3.6 Post detail (processing)

3.7 Search

3.8 Assets

3.9 Skills / Recipes

3.10 Admin (Accounts, Users, Billing, Audit)

3.11 Settings — Branding & Messenger accounts

4. CLI

4.1 Global flags & configuration

4.2 Exit codes & error model

4.3 Output contract (`--json` / `--output`) & worked examples

5. TUI

5.1 Verified keybinding map

5.2 Lipgloss style bindings

5.3 Channel / Post / Search layouts

6. Mobile wireframes

6.1 Per-platform realization

6.2 Gestures, offline & sync states

7. Gaps & open items

Rev	Date	Author	Change
1	2026-07-21	swarm (design)	Initial complete draft: web portal IA + screen wireframes, CLI command tree, TUI layouts, mobile wireframes
2	2026-07-21	swarm (design · review)	Second-pass review: fixed Add-Channel flow anchor (<code>#2-add-channel</code>)
3	2026-07-22	swarm (design · Pass 3)	Depth pass: global interaction-state + keyboard model (§1.1–1.3); per-screen validation/state tables for Login, Dashboard, Add-Channel, Post detail, Search, Branding; CLI global flags + exit-code + <code>--json</code> / <code>--output</code> contract (§4.1–4.3); verified TUI keybinding map + Lipgloss style bindings + channel/post/search TUI layouts (grounded in <code>helix_track/llms_verifier/.../tui</code>); per-platform mobile realization map (Compose/SwiftUI/ArkTS/Qt), gestures, offline/sync states; two new diagrams (mobile fan-out)
4	2026-07-22	swarm (design · package critic)	Wired each wireframe surface to its rendered high-fidelity screen set now on disk (new §0 map + Upstream/Downstream note): web → <code>screens/web/</code> , TUI → <code>screens/tui/</code> , mobile → <code>screens/mobile/</code> , desktop → <code>screens/desktop/</code> . Wireframes remain the structural contract ; the rendered screens are the fidelity realization. Sign-off in <code>DESIGN_PACKAGE_REPORT.md</code> .
5	2026-07-22	swarm (design · decisions)	Operator ruling: <code>[CLOSED: THREADY-DES-08]</code> — desktop v1 = wrapped web UI only; tray / native notifications / file-drop designed-but-deferred (the <code>screens/desktop/</code> mocks are the v2 contract); §7 updated

Table of contents

- 0. Upstream / Downstream & rendered screen sets
- 1. Conventions & responsive breakpoints
 - 1.1 Interaction-state legend
 - 1.2 Keyboard & focus model
 - 1.3 Validation model
- 2. Web portal — information architecture
- 3. Web portal — screen wireframes
 - 3.1 App shell
 - 3.2 Login / MFA
 - 3.3 Dashboard
 - 3.4 Channels list & Add-Channel wizard
 - 3.5 Channel detail (thread list)
 - 3.6 Post detail (processing)
 - 3.7 Search
 - 3.8 Assets
 - 3.9 Skills / Recipes
 - 3.10 Admin (Accounts, Users, Billing, Audit)
 - 3.11 Settings — Branding & Messenger accounts
- 4. CLI
 - 4.1 Global flags & configuration
 - 4.2 Exit codes & error model
 - 4.3 Output contract (`--json` / `--output`) & worked examples
- 5. TUI
 - 5.1 Verified keybinding map
 - 5.2 Lipgloss style bindings
 - 5.3 Channel / Post / Search layouts
- 6. Mobile wireframes
 - 6.1 Per-platform realization
 - 6.2 Gestures, offline & sync states
- 7. Gaps & open items

0. Upstream / Downstream & rendered screen sets

Upstream (this file consumes / must not contradict): `component-library.md` (the `.ds-*` components each block references), `theming.md` (light/dark + white-label), `../api/index.md` (endpoints/events the

screens bind to), and `../architecture/index.md` (entities the screens render). The token/brand source of truth is `design-system.md` / `opendesign/`.

Downstream (consumes this file): every wireframe surface is now **realized as a rendered, self-contained high-fidelity screen set** on disk. The wireframes remain the **structural contract** (low-fidelity, diff-reviewable); the rendered screens are the fidelity realization and the source for the PNG/PDF/Figma-IR exports. The `ux-flows.md` journeys and the `prototypes.md` prototype are assembled from them.

Wireframe surface (this file)	Rendered screen set (downstream)
\$2-\$3 Web portal	<code>screens/web/</code> — 13 screens + interactive <code>index.html</code>
\$5 TUI	<code>screens/tui/</code> — <code>tui-screens.html</code> (Bubble Tea/Lipgloss)
\$6 Mobile	<code>screens/mobile/</code> — 11 device-framed screens
(Desktop shell)	<code>screens/desktop/</code> — <code>desktop-shell.html</code> (Tauri 2)

1. Conventions & responsive breakpoints

Wireframes are drawn as **monospace block layouts** (unambiguous in plain text and reviewable in diffs) plus **Mermaid** navigation/screen maps (each followed by the mandatory prose explanation and saved as a sibling `.mmd`). They are **low-fidelity structure**, not final visuals — final visuals live in the rendered `screens/` sets and Figma (`prototypes.md`). Every block references design-system components (`.ds-*`, see `component-library.md`) and API endpoints/events (see `../api/index.md`).

Breakpoints (from `core.css` container/gutter tokens): **phone** < 768px, **tablet** 768–1024px, **desktop** ≥ 1024px (`--container-max 1200px`). The web app is a responsive single codebase; the Tauri desktop client wraps it with OS chrome only. The exact `.ds-container` media queries are `[VERIFIED — components/css/components.css]`: gutter `--container-gutter-phone 12px` below 768px, `--container-gutter-tablet 16px` at ≥ 768px, `--container-gutter-desktop 24px` at ≥ 1024px; section rhythm `--section-y-{phone|tablet|desktop}` = 32/48/80px.

1.1 Interaction-state legend

Every screen below is specified against **one uniform state set** so no surface ships a half state. The composite that renders each state is in `component-library.md §8`; the state machine is in `component-library.md`.

State	Trigger	Visual contract	Component
default	data present	token surfaces; <code>--fg</code> / <code>--muted</code> text	any
loading	fetch in flight < 150ms	inline spinner only (no layout shift)	<code>thready-skeleton</code>
skeleton	fetch in flight ≥ 150ms	token-tinted placeholder blocks (static under reduced-motion)	<code>thready-skeleton</code>
empty	resolved, zero rows	icon + one-line reason + a primary action; never a blank pane	<code>thready-empty</code>
error	fetch/mutation failed	page-level <code>thready-error</code> (retry) or field-level <code>--danger</code> inline	<code>thready-error</code>
focus-visible	keyboard focus	<code>--focus-ring</code> (3px accent-tinted) <code>[VERIFIED]</code>	all interactive
disabled	RBAC / offline / busy	<code>--muted</code> , <code>aria-disabled</code> , not focus-trapping	all interactive
validating	form submit	control busy + polite live-region announce	forms
success	mutation confirmed	<code>--success</code> badge/toast; optimistic value confirmed	<code>thready-toast</code>

1.2 Keyboard & focus model

The whole portal is keyboard-complete `[CONSTITUTION §11.4.190]` . Global bindings are consistent across Web, Desktop (Tauri) and — with the single-key equivalents — the TUI (§5.1):

Binding	Action	Scope
<code>/</code> or <code>Ctrl/⌘+K</code>	focus global search	app shell
<code>g</code> then <code>d/c/s/a/k</code>	go to Dashboard/Channels/Search/Assets/Skills	app shell
<code>Tab</code> / <code>Shift+Tab</code>	move focus in DOM order	any
<code>Enter</code> / <code>Space</code>	activate focused control	any
<code>Esc</code>	close drawer/modal/wizard step; walk back	overlays
<code>?</code>	keyboard-shortcut help sheet	app shell
<code>[</code> / <code>]</code>	collapse / expand left nav	app shell

Focus order follows DOM order (no positive `tabindex`); modals/drawers **trap focus** and restore it to the invoking control on close; the theme toggle uses `aria-pressed` and the language picker is a native `<select>` `[VERIFIED — theme-toggle.component.ts / language-picker.component.ts]` . A visible **skip-to-content** link is the first tab stop.


1.3 Validation model

Forms validate on **three** occasions, and the messages are always specific and actionable (never “invalid input”):

1. **On blur** (per field) — synchronous format checks (email shape, hex `#RRGGBB`, required).
2. **On submit** (whole form) — cross-field checks + a summary region announced to screen readers.
3. **Server echo** — the API’s `422` field errors (shared **error model**) are mapped back to the originating field inline with `--danger` (never `--accent`).

Each field carries: a persistent **hint** (below the control), a **tooltip** on the label for non-obvious inputs, and — on error — an `aria-describedby` link from the control to the message so the screen reader announces the reason. Per-screen field tables below enumerate the exact rules.

2. Web portal — information architecture



Rendered PNG/SVG exported via Docs Chain (\$11.4.65). Source: `diagrams/web-portal-ia.mmd`.

Explanation (for readers/models that cannot see the diagram). After Login/MFA the user lands on the Dashboard, the hub from which seven primary areas branch: Channels, Search, Assets, Skills/Recipes, Admin, and Settings. Channels leads to the Add-Channel wizard and to a Channel detail (the thread list); a thread opens a Post detail, which shows processing status, generated assets and replies, and links onward to an Asset detail. Search reaches both Post detail and Asset detail (it queries posts and generated materials). Assets is the media library and also reaches Asset detail. Skills/Recipes lists the processing recipes and opens a Skill detail/editor. Admin — visible per RBAC tier — contains Accounts, Users & roles, Billing & usage, and the Audit log. Settings contains Branding/white-label, the Messenger accounts management, and per-user Preferences (theme, language). This map is the navigation contract the app shell (\$3.1) implements.

3. Web portal — screen wireframes


3.1 App shell

The persistent frame: top bar (product logo, global search, theme toggle, language picker, account switcher, user menu) + collapsible left nav + content region.



Explanation. The top bar is the shared `.ds-nav`: product mark (Account-branded when white-labeled), a global semantic-search field (routes to §3.7), the `ds-theme-toggle`, the `ds-language-picker`, an **account switcher** (a user may belong to multiple Accounts — §6.1), and the user menu. The left nav lists the primary areas from §2, filtered by RBAC (Admin hidden for Standard Users). The footer is the shared `.ds-footer` carrying the locked Helix Development attribution + slogan (§brand-assets §8). On phones the left nav collapses to a hamburger and the global search collapses to an icon.

3.2 Login / MFA




Explanation. Email/username + password (`.ds-input`), Argon2id-hashed server-side, min-12 + breach-check `[CONSTITUTION §6.3]`. Primary CTA is `.ds-btn--primary`. OAuth2 links external services. For **Root Admin / Account Admin**, MFA (TOTP) is a **mandatory** second step; optional for Standard Users `[DEFAULT — adjustable, §6.3/Q9]`. Errors use `--danger` inline (never `--accent`). Session policy: access 15 min / refresh 7 d / idle 30 min `[§6.3]`.

Fields, validation & states.

Field	Rule (blur → submit → server)	Hint	Error message
Email / username	required; email shape if it contains <code>@</code>	“Email or username”	“Enter your email or username”
Password	required; never length-validated on login (only at set-password)	—	“Enter your password”
TOTP code	6 digits, numeric, auto-advance per box; paste-aware	“6-digit code from your authenticator”	“That code didn’t match — try the current code”


- **States:** default; **validating** (button shows spinner, inputs read-only); **error** — invalid credentials return a **generic** “Email or password is incorrect” (no user-enumeration) with a `--danger` summary; **locked** — after N failures the form shows a cooldown timer (rate-limit / brute-force guard `[CONSTITUTION §6.3]`); **MFA-required** — step 2 replaces step 1, `Esc` cancels back to step 1; **SSO** — the OAuth2 button routes out and returns to the post-login destination.
- **A11y:** the error summary is an `aria-live="assertive"` region; the TOTP group is a labelled `role="group"`; `Caps Lock` on the password field surfaces a warning hint.
- **Empty-of-account edge:** a valid login with **no** account membership lands on a “You’re not a member of any account yet” empty state with a create/join affordance (ties to `ux-flows §5`).

3.3 Dashboard



Explanation. A stat-card row (`.ds-card`) summarizes the Account's footprint. The **Live activity** panel subscribes to the Event Bus over **WebSocket/SSE** (`post.received` , `processing.progress` , `processing.completed` , `processing.failed`) so it updates in real time without polling (`API real-time`). The **Processing queue** shows per-job progress bars (download / convert / analyze / research phases) with an inline **retry** affordance for failures (`--danger` badge → retry). The **Recent threads** table previews each thread's root excerpt, reply count (↻N), detected tags, and processing status; a row opens Post detail (§3.6). Aggressive SLO: the page target is < 1.5 s and API calls p95 < 150 ms (`OPERATOR $Q14`).

3.4 Channels list & Add/Channel wizard



Explanation. The list shows each channel’s messenger, **auto-detected content type**, post count, health, and an overflow menu (⋮: pause, re-detect, remove). The **Add-Channel wizard** (driven by the `ux-flows.md` journey) is five steps: choose the source messenger; pick or interactively/non-interactively sign in a messenger account (Accounts Management sub-system); paste + **Resolve** the invite/link (previews resolved title/kind/size); review the **auto-detected** recipe/type with an override, and set the schedule (poll interval and/or on-event trigger); confirm. A “Max: auth” warning state demonstrates a channel needing re-auth — its row surfaces a fix action. Note the Max adapter is `[GAP: 5.1 herald — Max stub]`: the UI is specified now; the adapter is BUILD-NEW.

Per-step validation & states (wizard). The wizard is a `thready-wizard` (stepper); each step gates *Next* until valid, and *Back*/`Esc` never loses entered data (state persists in the wizard model):

Step	Field	Rule	Error / empty state
1 Source	radio (Telegram/Max)	required; exactly one	<i>Next</i> disabled until chosen
2 Account	messenger-account select	required; must be an established session	“No signed-in Telegram account — sign in” (inline <code>thready-messenger-signin</code>)
3 Target	invite/link text	required; must match <code>t.me/...</code> or <code>max.ru/join/...</code> ; Resolve must succeed	<code>422</code> unresolvable → “We couldn’t resolve that link”; <code>403</code> private → “This account can’t access that channel”
4 Recipes	type (auto-detected) + schedule	type required (defaults to auto); poll interval 1–60m or on-event ≥ 1	uncertain auto-type → banner “We guessed Notes — change if wrong” (never silently drops <code>[\$Q32]</code>)
5 Confirm	—	all prior steps valid	on <code>POST</code> failure, stay on step 5 with a retry + the server reason

- **States:** each step has default / validating (**Resolve** shows a spinner + disables *Next*) / error / **resolved-preview** (step 3 shows title-kind-size once resolved). Submitting shows an optimistic “Adding...” row in the channels list that reconciles on the `channel.added` event.
- **A11y:** the stepper exposes `aria-current="step"`; the resolved preview is announced politely; the *Resolve* button has an explicit busy state (`aria-busy`).

3.5 Channel detail (thread list)

```
#ml-papers · Telegram · type: Research [edit] · poll 5m + on-event
[ ⌕ Re-sync ] [ ⏸ Pause ] [ 🍳 Recipes ] search in channel
Thread
├─ "Diffusion models for..." ↩ 12 replies #Research #TODO ✓ processed
├─ "magnet:?xt=urn:btih:..." ↩ 3 #Movie #ToDownload ⌕ 63%
└─ "https://youtu.be/..." ↩ 0 #Video (indirect) ⌕ queued
```

Explanation. Header shows the channel’s messenger, auto/overridden type, and schedule. Each row is a **complete post** = root + its **organic reply chain** (↩N), the extracted/derived hashtags (with an “indirect” badge when tags were AI-derived — §3.5 of the request), and processing status. Expanding (↳) reveals the reply chain inline; the system’s own status replies are visually separated and **excluded from processing**. A row opens Post detail.

3.6 Post detail (processing)

```
Post · #ml-papers [ ⌕ Reprocess ]
ROOT @author · 2026-07-20 14:02
"New paper on diffusion... https://github.com/x/y https://youtu.be/z"
Tags: #Research #Video #TODO #ToDownload (● direct ○ indirect: #Video)
Thread (organic replies ↩12) Processing
├─ ↳ @b "see also ..."
├─ ↳ @c "#ToDownload"
├─ ...
└─ (system replies hidden ▼)
├─ Generated assets
├─ 📄 video.mp4 📄 video-web.mp4
├─ 📄 research.md (semantic-indexed)
└─ ↳ classify ✓
└─ ↳ download (MeTube/Boba) 📊 63%
└─ ↳ convert ...-web ⌕ queued
└─ ↳ research (deep) ⌕ queued
└─ ↳ reply status ⌕ queued
precedence: download>convert>analyze
>research>reply
△ failed step → [ retry step ]
```

Explanation. The root post, its links, and its tags (marking **direct** vs. AI-**indirect** tags). The **Thread** panel shows organic replies with system replies collapsed. The **Processing** panel shows the ordered pipeline — classify → download → convert (**...-web**) → research → reply — with the documented **precedence** (download > convert > analyze > research > reply) and per-step status via **processing.progress** events; a failed step exposes **retry step** (idempotent single-claim, so retry never double-processes) [§3.3]. **Generated assets** link to the Asset detail (raw + **...-web** rendition + generated research). **Reprocess** triggers an explicit refresh (client → REST → System) [§3.2.3].

3.7 Search

```

Search [ semantic query: "papers about retrieval-augmented generation" ] [Go]
Filters: [ posts ☒ ] [ generated docs ☒ ] [ assets ☐ ] type[▼] channel[▼] tag[▼]
Mode: ( ● semantic ○ keyword ○ hybrid ) sort: [ relevance ▼ ]
Results (semantic < 500ms)
0.94 #ml-papers "RAG survey..." #Research ↗ open post
0.91 research.md "...retrieval augmented..." (generated) ↗ open doc
0.88 #nlp "dense retrieval..." #Research ↗ open post

```

Explanation. The Lumen-style semantic search over **both** original posts **and** generated materials [\[§1.3\]](#). Users choose scope (posts / generated docs / assets), a mode (semantic / keyword / hybrid), and filters (type, channel, tag). Results show a relevance score and route to Post or Asset detail. SLO: semantic search < 500 ms [\[OPERATOR §Q14\]](#); results hydrate ids from the relational store (vectors are reference-only) [\[§2.1.1\]](#).

States & validation. default (recent searches + suggested filters); **skeleton** while the embedder/ANN runs; **empty** (“No matches — broaden your query” + a *clear filters* affordance when filters exclude everything); **error/timeout** (a slow embedder yields a graceful “narrow your query” nudge, not a spinner that hangs); **degraded** — if the deployment is running the `HashEmbedder` stub, a `--warn` banner states scores are **not** semantic and hides the score column [\[GAP: 2.1\]](#). The query field is never *required* (empty = recent); mode/scope are radio/checkbox groups with at least one scope enforced on submit. Results are a keyboard-navigable list (`↑/↓`, `Enter` opens); each row’s score is exposed to SR as “relevance 0.94”.

3.8 Assets

```

Assets [ grid ■ | list ≡ ] filter[▼]
■ video-web.mp4 ■ movie.mkv ■ cover.jpg ■ book.pdf ■ track.flac
  linked: post... #Movie OCR ✓ author... #Music
Asset detail (drawer): raw + ...-webrenditions · checksum · linked post(s) ·
[ ⊥ re-download ] (if broken link) [ ▶ stream ] (Range/HLS) [ sensitive ]

```

Explanation. The media library (Asset Service, Catalogizer-backed). Grid/list toggle; each tile shows the linked post and type. The Asset **detail** drawer exposes raw + `...-web` renditions, the content-hash checksum, linked posts, a **re-download** action for broken physical links (via REST), streaming (Range/`OpenSeekable` + HLS/DASH), and a **sensitive** lock for encrypted assets (credit-cards/contracts/QR) [\[§7\]](#). Client links resolve **through** the Asset Service, never raw paths [\[§7.1\]](#).

3.9 Skills / Recipes

```

Skills / Recipes ————— [ + New recipe ] —————
Graph view: atomic → composite → umbrella | list ≡
Recipe: Research (#Research) —————
| triggers: #Research, GitHub link, IT content | order: research > reply
| steps: web-research(multi-pass) → docs gen → skill-graph grow → semantic idx
| [ edit ] [ test on sample post ] version: v3 🐛 last edited by root

```

Explanation. Recipes map hashtag/content-type → Skill(s). The editor shows triggers, the ordered steps, and version. **Important honesty:** HelixSkills provides the Skill-Graph knowledge DAG but **no execution engine** — the Thready dispatch engine is BUILD-NEW `[GAP: 4.1 helix_skills]`. This screen is the management surface for that dispatch mapping; it does not imply the engine exists yet. “Test on sample post” exercises the dispatch against a fixture.

3.10 Admin (Accounts, Users, Billing, Audit)

```

Admin —————
[ Accounts ] [ Users & roles ] [ Billing & usage ] [ Audit log ]
Users & roles:
User           Account(s)      Role           MFA    Status
root@...       (all)           Root Admin     ✓      active
alice@...      Acme, ML        Account Admin  ✓      active
bob@...        ML              Standard User  —      invited
[ + Invite user ] [ edit roles ]
Billing & usage: plan[ Pro ▼ ] metered: 1.2M posts · 42 TB · [ view invoices ]

```

Explanation. The three-tier RBAC (Root / Account Admin / Standard User) surface `[$6.1]`. A user may belong to multiple Accounts; role is per-Account. Invites, role edits, and MFA status are shown. Billing shows the **subscription + metered** model `[OPERATOR $Q11]` (usage: posts, storage) and invoices. The **Audit log** tab is an append-only, queryable view of all admin/user actions `[$14.4]`. Admin is RBAC-gated (hidden for Standard Users).

3.11 Settings — Branding & Messenger accounts

```

Settings › Branding (white-label)
Effective for account: [ Acme ▼ ] (Root/Account-Admin only)
Primary [#12A3FF ■] Secondary [#0D6EFD ■] Accent(light)[#0B5ED7 ■] AA:6.1 ✓
Accent(dark) [#7DB3FF ■] AA:7.2 ✓
Product logo: [ light.svg ↑ ] [ dark.svg ↑ ] (transparent)
Slogan: [ Acme reads your threads ]
@ Helix Development attribution is always shown in footers (locked).
[ Live preview ▶ ] [ Save ] (rejects AA-failing accent → 422)

Settings › Messenger accounts
Telegram: @me (session ✓) [ re-auth ] Max: (not signed in) [ sign in ]
Sign-in: ( ) interactive (phone+code+2FA) ( ) non-interactive (env vars)

```

Explanation. The white-label editor (see [theming.md](#)): color swatches with **live AA readout**, light+dark product-logo upload, slogan; a locked note that Helix Development attribution persists; a **live preview**; and a Save that server-side **rejects AA-failing accents (422)**. The **Messenger accounts** panel is the Accounts Management sub-system: per-messenger interactive (phone/code/2FA) or non-interactive (env-var) sign-in, with re-auth. Telegram is live via `gotd/td` `[IN-HOUSE: herald]`; Max is `[GAP: 5.1 — BUILD-NEW]`.

Branding editor — fields, validation & states. Every swatch is a hex input paired with a color picker and a **live AA meter** (`thready-branding-editor`, see [component-library §6](#)):

Field	Rule	Live feedback	Server
Primary / Secondary (<code>--brand / --brand-2</code>)	<code>^[0-9a-fA-F]{6}\$</code>	decorative — no AA gate; shows on a mark preview	stored as-is
Accent (light)	hex; ≥ 4.5:1 on <code>#ffffff / --surface-warm</code>	meter turns <code>--danger</code> + suggests a darker hex below AA	<code>422</code> <code>accent_below_wcag_a</code> if it fails (theming §7)
Accent (dark)	hex; ≥ 4.5:1 on <code>#020817</code>	same meter on the dark surface	<code>422</code> on fail
Product logo (light/dark)	SVG/PNG, transparent, ≤ size cap	thumbnail preview; rejects non-transparent with a hint	Asset-Service ref
Slogan	free text, length-capped	live footer preview	stored

- **The client meter and the server `ValidateAccent` gate MUST agree on the ratio** ([theming §10.1](#)); the Save button stays disabled while any accent is below AA, and a server `422` re-opens the offending field with the measured ratio + suggestion.

- **States:** default; **dirty** (unsaved-changes guard on navigate-away); **previewing** (live preview applies the `data-account` scoped block, `theming $6`); **validating/error** (422); **success** (audit-logged, toast). The locked Helix Development attribution note is always present and non-editable.
- **RBAC:** the “Effective for account” selector and the whole editor are Root/Account-Admin only; whether Account Admins may edit **their own** branding is `[OPEN: THREADY-DES-06]`.

4. CLI

Everything the TUI/Web can do, headless, for pipelines `[ $10.1 ]`. Go + Cobra, sharing the SDK. Command tree `[DEFAULT — adjustable]`:

```
thready
├── auth          login | logout | mfa | whoami | token create --scope ...
├── account       list | switch | create | branding get|set
├── channel       list | add --source telegram --link ... | detail <id> | pause | resync | rm
├── messenger     login <telegram|max> [--interactive|--env] | status
├── post          list --channel <id> | show <id> | reprocess <id> | replies <id>
├── search        "<query>" [--semantic|--keyword|--hybrid] [--scope posts,docs,assets] --json
├── asset         list | show <id> | download <id> | redownload <id> | stream <id>
├── skill         list | show <id> | test <id> --post <id>
├── user          list | invite --account <id> --role ... | role set ...
├── billing       usage | invoices
└── events        tail [--type processing.*] [--channel <id>]          # live WS/SSE stream
```

Explanation. Verbs mirror the web IA. `--json` on every read makes the CLI pipeline-friendly (the operator’s **Web + CLI first** priority `[OPERATOR $Q13]`). `thready events tail` subscribes to the real-time bus so scripts can react to `processing.completed`. Auth uses **scoped API keys** for non-interactive use `[ $6.3 ]`. The CLI and TUI share one Go SDK, so behavior is identical.

4.1 Global flags & configuration

Every command accepts the same global flags (Cobra persistent flags) `[DEFAULT — adjustable]`:

Flag / env	Meaning	Default
<code>--json</code>	machine-readable output on any read	off (human table)
<code>--output <table\ json\ yaml\ csv> / -o</code>	explicit output format	<code>table</code>
<code>--account <id> / THREADY_ACCOUNT</code>	act within an account (multi-membership)	last used
<code>--profile <name> / THREADY_PROFILE</code>	named credential/endpoint profile	<code>default</code>
<code>--endpoint <url> / THREADY_ENDPOINT</code>	API base	prod URL
<code>--token <key> / THREADY_TOKEN</code>	scoped API key (non-interactive)	keychain/ <code>~/.config/thready</code>
<code>--quiet / -q, --verbose / -v</code>	suppress / expand logging	normal
<code>--no-color, --yes / -y</code>	disable ANSI; skip confirmation prompts	off
<code>--timeout <dur></code>	per-request timeout	<code>30s</code>

Config precedence is **flag → env → profile file → default**. Credentials resolve from the OS keychain first (never plaintext on disk when a keychain exists); `--token / THREADY_TOKEN` is the CI/pipeline path. Config lives at `~/.config/thready/config.yaml` (XDG-respecting).

4.2 Exit codes & error model

Exit codes are **stable and scriptable** (mapped from the shared [API error model](#)):

Code	Meaning	Example
<code>0</code>	success	any completed read/write
<code>1</code>	generic / unexpected error	unhandled
<code>2</code>	usage error (bad flags/args)	Cobra arg parse
<code>3</code>	auth required / expired (<code>401</code>)	missing or expired token
<code>4</code>	forbidden — RBAC (<code>403</code>)	Standard User calling <code>user invite</code>
<code>5</code>	not found (<code>404</code>)	<code>post show <bad-id></code>
<code>6</code>	validation (<code>422</code>)	branding accent below AA; unresolvable link
<code>7</code>	conflict (<code>409</code>)	<code>post reprocess</code> already in flight
<code>8</code>	rate-limited (<code>429</code>)	back off + retry
<code>124</code>	timeout	<code>--timeout</code> exceeded

With `--json`, errors are emitted as `{"error":{"code","message","field?","request_id"}}` on `stderr` so stdout stays a clean data stream for piping. `request_id` mirrors the API trace id for support.

4.3 Output contract (`--json` / `--output`) & worked examples

Reads default to a compact human table; `--json` emits the same records the SDK returns (stable keys), enabling `jq` pipelines. Writes echo the created/updated resource. Examples:

```
# List channels needing attention, pipe to jq (stable JSON keys)
thready channel list --json | jq '.[ ] | select(.health!="healthy") | {id,name,health}'

# Add a Telegram channel non-interactively in CI (scoped token + env account)
THREADY_TOKEN=$KEY THREADY_ACCOUNT=$ACC \
  thready channel add --source telegram --link "https://t.me/ml_papers" --type research --poll
  5m -y


# React to completions in a script (long-lived SSE stream, one JSON object per line)
thready events tail --type 'processing.completed' --json \
  | while read -r ev; do notify-send "done: $(echo "$ev" | jq -r .post_id)"; done

# Semantic search, machine-readable, top 5
thready search "retrieval augmented generation" --semantic --scope posts,docs -o json | jq '.[0:5]'
```

- **Determinism:** `--json` / `-o` output is field-stable across releases (additive only) so pipelines don't break; human table columns may change and MUST NOT be parsed.
- **Streaming:** `events tail` is newline-delimited JSON (NDJSON), one event per line, so `read / jq -c` consume it incrementally; it reconnects with backoff on drop and prints nothing but events on stdout.
- **Honesty:** commands whose backend is a stub (`messenger login max`, semantic `search` on the hash-embedder deployment) print a `--warn` notice to `stderr` and set a non-zero advisory code where the result is not trustworthy `[GAP: 5.1 / 2.1]`.

5. TUI

Bubble Tea + Cobra + **Lipgloss**, styled from the Thready Lipgloss palette (\$ `design-system.md` §7). The pattern is **verified in-house**: `helix_track/llms_verifier/llm-verifier/tui` is a real Bubble Tea program (`tui/app.go`, `tui/screens/*.go`, `tui/notifications.go`) using `github.com/charmbracelet/lipgloss` styles and a `tea.KeyMsg` update loop `[VERIFIED — inspected source]`. Thready reuses this structure (app model → screen models → Lipgloss-styled views + a notifications/live pane).



Rendered PNG/SVG exported via Docs Chain (§11.4.65). Source: `diagrams/tui-navigation.mmd`.

Explanation (for readers/models that cannot see the diagram). The TUI is a keyboard-driven state machine. Login transitions to Dashboard on auth. Single-key shortcuts jump between areas: `c` Channels, `/` Search, `a` Assets, `k` Skills. `enter` drills into a Channel then a Post; `esc` walks back. `n` opens the Add-Channel form (submit or `esc` returns). From a Post, `r` triggers Reprocess, and incoming `processing.progress` events update the same Post view live (the TUI holds a WS/SSE subscription). `q` quits from the Dashboard. This mirrors the web IA (§2) so muscle memory transfers.

TUI layout (Dashboard):

```

Thready — acct: Acme — ( dark ————— [q]uit [?]help
Channels 128 | Live:
| c channels | ✓ #Research processed      2s
| / search   | ⚡ #Video download 63%      9s ██████████
| a assets   | ⚠ #Movie failed → r retry   34s
| k skills   | — recent threads —
|            | #ml-papers "Diffusion..." ↩12 #Research ✓
|            | #films     magnet:...      ↩3  #Movie   ⚡

```

Made with ♥ by Helix Development

Explanation. A left key-hint rail + a live pane (WS/SSE) and a threads table — the same information as the web Dashboard, in Lipgloss styles bound to the Thready palette. The heart in the footer uses the `U+2665` glyph tinted with the Lipgloss `Accent` (`$brand-assets $8`).

5.1 Verified keybinding map

Thready's TUI adopts the **exact key model already shipped** in the in-house pattern `helix_track/llms_verifier/llm-verifier/tui` `[VERIFIED – grepped case tea.KeyMsg in app.go / screens/dashboard.go ]`, so muscle memory transfers and the model is proven, not invented:

Key(s)	Action	Verified source binding
<code>ctrl+c</code> , <code>q</code>	quit	<code>app.go</code> <code>case "ctrl+c", "q"</code>
<code>1-4</code> , <code>F1-F4</code>	jump to primary tab/area	<code>app.go</code> <code>case "1", "F1" ... "4", "F4"</code>
<code>left/h</code> , <code>right/l</code>	move between areas/tabs	<code>app.go</code> <code>case "left", "h" / "right", "l"</code>
<code>tab</code>	cycle focusable region	<code>app.go</code> <code>case "tab"</code>
<code>home</code> , <code>end</code>	first / last	<code>app.go</code> <code>case "home" / "end"</code>
<code>up/k</code> , <code>down/j</code>	list navigation	<code>screens/dashboard.go</code> <code>case "up", "k" / "down", "j"</code>
<code>enter</code> , <code>space</code>	open / activate selection	<code>screens/dashboard.go</code> <code>case "enter", " "</code>
<code>f</code> , <code>/</code>	filter / search	<code>screens/dashboard.go</code> <code>case "f", "/"</code>
<code>r</code> , <code>R</code>	refresh / reprocess	<code>case "r", "R" (both files)</code>
<code>esc</code>	back / cancel	<code>screens/dashboard.go</code> <code>case "esc"</code>
<code>?</code>	help overlay	<code>app.go</code> <code>case "?"</code>

Thready adds domain keys layered on the same switch: **c** Channels, **a** Assets, **k** Skills, **n** new-channel, **p** pause — chosen not to collide with the verified navigation set. Every key is echoed in the on-screen `[?]help` rail (Lipgloss `help` style), so the TUI is discoverable without docs.

5.2 Lipgloss style bindings

The TUI reads the **generated** Thready Lipgloss palette (`$ design-system.md $7`). The verified pattern builds a header/footer with bordered styles, a right-aligned nav, and a dimmed help line `[VERIFIED - lipgloss.NewStyle().BorderForeground(...).Foreground(...).Align(lipgloss.Right) in app.go ]`. Thready binds those style roles to token values instead of raw ANSI indices:

```
// tui/theme_bindings.go - map Lipgloss roles to the generated Thready palette ($design-system
// $7).
// Replaces raw ANSI indices ("205","39","240","62","241") seen in the reference with tokens.
var (
    Title    = lipgloss.NewStyle().Foreground(Accent).Bold(true)           // was Color("205")
    NavOn    = lipgloss.NewStyle().Foreground(Accent)                       // active tab (was
    "39")
    NavOff   = lipgloss.NewStyle().Foreground(Muted)                       // inactive tab (was
    "240")
    Border   = lipgloss.NewStyle().BorderForeground(BorderColor)           // header/footer (was "62")
    Help     = lipgloss.NewStyle().Foreground(Muted)                       // key hints (was
    "241")
    Danger   = lipgloss.NewStyle().Foreground(DangerColor)                 // failed steps /
    retry
)
```

Because the palette is generated from the same `thready.css` tokens as the web app, a theme or white-label change re-tints the TUI without editing Go. Under a non-truecolor terminal the tokens degrade to the nearest 256-color; the border styles (not just color) keep boundaries legible, matching the “prefer ring elevation in dark” rule (`$ design-system.md $5`).

5.3 Channel / Post / Search layouts

Channel detail (enter on a channel)

```
#ml-papers · Telegram · Research — r v
├─ "Diffusion models..." ↵12 #Research ✓
├─ "magnet:?xt=..." ↵3 #Movie 63%
├─ "https://youtu..." ↵0 #Video 0
└─ [n]ew [p]ause [f]ilter [esc]back
```

Search (/ or f)

```
query: retrieval augmented ... [enter]
├─ ●semantic ○keyword ○hybrid scope:posts
├─ 0.94 #ml-papers "RAG survey..." ↵
├─ 0.91 research.md "...retrieval..." ↵ (gen)
└─
```

Post detail (enter on a thread)

```
< #ml-papers · @author 14:02 — r reprocess
├─ "New paper on diffusion... github...youtu..."
├─ tags: ●#Research ●#Video ○#Video(indirect)
├─ — pipeline — — replies ↵12 —
├─ classify ✓ ↳@b "see also..."
├─ download 63% ↳@c "#ToDownload"
├─ convert 0 queued (system replies hidden)
├─ research 0 queued video-web.mp4
└─ △ failed → [r]etry step (idempotent)
```


Made with ♥ by Helix Development

Explanation. These three TUI screens mirror the web §3.5–3.7 exactly, re-laid for an 80-column terminal.

Channel detail lists complete posts (root + reply count ↩N), the detected tags, and per-post status glyphs (✓ processed, 🔄 running with %, ⏸ queued), with the domain keys on a hint rail. **Post detail** splits into a live pipeline pane (the same ordered steps and precedence as the web, updating on `processing.progress`) and a replies pane (organic replies shown, system replies hidden), with the generated assets listed and a keyboard **retry step** on failure — the retry is the same idempotent single-claim action as everywhere else, so pressing `r` twice never double-processes. **Search** is a query line + mode/scope selectors + a scored, keyboard-navigable result list that opens Post/Asset detail on `enter`. All three carry the locked footer slogan with the ❤️ glyph tinted by the Lipgloss `Accent`.

6. Mobile wireframes


Native per platform (Compose/Android, SwiftUI/iOS, ArkTS/HarmonyOS, Qt/Aurora) + KMP shared logic `[§10.1]`. Bottom-tab navigation.



Rendered PNG/SVG exported via Docs Chain (§11.4.65). Source:

`diagrams/mobile-navigation.mmd`.


Explanation (for readers/models that cannot see the diagram). Mobile uses a five-item bottom tab bar: Home (a real-time activity/processing feed), Channels (list → add-channel bottom sheet, or a channel’s thread list → Post detail → media player/asset viewer), Search (query + filters → Post detail), Assets (a media grid → viewer), and More (account switch, Settings incl. Branding, theme and language, sign out). The information architecture is the same as web/TUI, re-laid for touch: the Add-Channel wizard becomes a bottom sheet, and media opens a full-screen player.



Explanation. Touch-sized rows, a bottom tab bar, and a full Post detail with the same processing pipeline and reprocess action. Compose/SwiftUI read the effective Account branding at login (§ theming §8).

6.1 Per-platform realization

The **same** composite spec (states + all semantics) is realized natively on each platform from the Thready tokens; the KMP fleet supplies shared *logic* (not UI). Honest status per [GAP: 8.x]:



Rendered PNG/SVG exported via Docs Chain (§11.4.65). Source: `diagrams/mobile-platform-fanout.mmd`.

Explanation (for readers/models that cannot see the diagram). The Thready token set — the same `thready.css` values, delivered to native code through the KMP token bridge (§ design-system.md §7) — is the single upstream for all four mobile platforms. **Android** realizes the composites in Jetpack Compose (Material 3 surfaces tinted by the generated `ThreadyColors`), **iOS** in SwiftUI (Color/theme from the same bridge), and **HarmonyOS** (ArkTS) and **Aurora** (Qt Quick) through the `helix_shims` native clients — both of which are **scaffolds** today [GAP: 8.5].

The middle band is the **KMP shared-logic fleet** consumed by Android and iOS: `Auth-KMP`, `Security-KMP`, `Database-KMP`, `Concurrency-KMP`, and `UI-Components-KMP`. This is *logic*, not pixels — it carries no UI. Two of these are the release-gating honesty items: `Security-KMP`'s secure storage is an **in-memory stub** [GAP: 7.3] and `UI-Components-KMP` is a **scaffold with no CI/publish** [GAP: 8.4].

Each platform assembles the **same composites** (thread row, processing pipeline, search, branding read), and the bottom band is the crucial contract: cross-platform **parity** — identical interaction states and accessibility semantics — is not aspirational but a **tested** contract, locked by the `ScreenDiff` / `VisualRegression` bank once CI lands `[GAP: 9.3]`. Because everything descends from one token source, a theme or white-label change re-skins every platform at once.

Platform accessibility & branding mapping (the a11y contract from `design-system $6` realized per OS):

Platform	A11y API	Theme source	Dynamic type	Status
Android (Compose)	TalkBack + <code>semantics{}</code>	<code>ThreadyColors</code> (bridge) + <code>isSystemInDarkTheme()</code>	<code>sp</code> + font scale	KMP logic SCAFFOLD [GAP: 8.4]
iOS (SwiftUI)	VoiceOver + <code>accessibilityLabel</code>	bridge Color + <code>@Environment(\.colorScheme)</code>	Dynamic Type	KMP logic SCAFFOLD
HarmonyOS (ArkTS)	Barrier-Free (a11y) kit	bridge + system dark	system font scale	client SCAFFOLD [GAP: 8.5]
Aurora (Qt Quick)	Qt Accessibility	bridge + Silica ambience	Qt font scaling	client SCAFFOLD [GAP: 8.5]

6.2 Gestures, offline & sync states

Touch gestures map to the same actions as the keyboard/pointer surfaces, so behavior is consistent:

Gesture	Action	Screen
pull-to-refresh	re-sync channel / refetch feed	Home, Channels, Channel threads
long-press row	context menu (pause, re-detect, remove)	Channels, threads
swipe row	quick actions (pause / mark)	Channels list
tap tag chip	filter by tag	anywhere tags show
pinch / double-tap	zoom media	asset viewer
swipe-down on sheet	dismiss Add-Channel bottom sheet (<code>Esc</code> equiv.)	Add-Channel

Offline & sync states (mobile is often intermittently connected): a persistent **connectivity banner** shows *live* / *reconnecting* / *offline*; reads render from the last cached snapshot with a “stale · updated 3m ago” note; mutations queue optimistically and flush on reconnect (with a conflict-resolution toast if the server diverged); the real-time pane degrades from WS/SSE push to a polling fallback and back. Processing progress bars freeze at the last known value under `offline` rather than resetting. Secrets (session tokens)

must live in Keychain/KeyStore — shipping on the `Security-KMP` in-memory stub would store them in plaintext memory `[GAP: 7.3]` (release gate below).

Release gate (honesty). Two gaps **block a production mobile release** and are called out on every mobile screen that stores secrets or targets HarmonyOS/Aurora: `[GAP: 7.3 Security-KMP]` mobile secure storage is an **in-memory stub** (Keychain/KeyStore must be implemented — shipping on the stub would store tokens in plaintext memory), and `[GAP: 8.5 helix_shims / HarmonyOS+Aurora clients]` those native clients are **skeletons**. The wireframes are design-complete; the platforms are not build-ready.

7. Gaps & open items

- `[GAP: 5.1 herald — Max stub]` — Add-Channel and Messenger-accounts screens include Max now; the adapter is BUILD-NEW. UI shows a clear “not signed in / auth” state until it lands.
- `[GAP: 4.1 helix_skills]` — the Skills/Recipes screen manages a dispatch mapping that needs the BUILD-NEW Thready dispatch engine; the screen does not imply the engine exists.
- `[GAP: 7.3 Security-KMP]`, `[GAP: 8.5 HarmonyOS/Aurora]` — mobile release gates (above).
- `[CLOSED: THREADY-DES-08]` — **decided** (operator ruling 2026-07-22): desktop (Tauri) v1 ships the **wrapped web UI only**; tray, native notifications and file-drop are designed-but-deferred — the mocks in `screens/desktop/` are the **v2 contract**, not v1 scope.
- `[OPEN: THREADY-DES-09]` — high-fidelity Figma frames for every screen above are produced in `prototypes.md`; these low-fi wireframes are the structural contract they refine.

Made with love ♥ by Helix Development.