

Helix Thready — Figma Import Kit

Catalogue

Materialization path A — Figma MCP (`use_figma` Plugin API)

Materialization path B — manual import

Provenance (no bluff)

Open items

Rev	Date	Author	Change
1	2026-07-22	swarm (design · figma)	Initial kit: complete token set as Figma Variables JSON (light+dark), 8-page file-plan blueprint for “Thready — Design Library”, two materialization paths (MCP / manual); actual Figma file creation tracked as <code>[OPEN: THREADY-DES-FIG-01]</code>

The **bridge that materializes the Thready design system as a real Figma library file**. It packs the canonical tokens (`../opendesign/tokens.css`) into Figma’s Variables format and specifies, page by page, the Figma file an agent (or a designer) builds from the existing library and screen artifacts.

Honest status: no Figma file exists yet. This kit is the *executable plan* — the variables payload plus a blueprint precise enough to execute mechanically. Creating the actual “Thready — Design Library” Figma file is `[OPEN: THREADY-DES-FIG-01]` . Nothing in this directory claims otherwise. (It also *implements* the hi-fi-frames intent of `[OPEN: THREADY-DES-09]` — that item closes only when the file is built.)

Catalogue

File	What it is	How to use
<code>figma-variables.json</code>	The complete token set as Figma Variables: collection <code>Thready / Color</code> (16 variables × Light/Dark modes, incl. <code>ds-heart</code> as a <code>VARIABLE_ALIAS</code> → <code>accent</code>) + collection <code>Thready / Structure</code> (25 FLOAT variables: spacing 4–48, radius sm/md/lg/pill, type sizes 12–64, leadings, motion 150/200, container-max 1200). Shape: Figma Variables REST API bulk-change payload with temporary ids; per-variable <code>scopes</code>, <code>description</code> (carrying the verbatim hex + provenance) and <code>codeSyntax.WEB</code>. Every hex is verbatim from <code>tokens.css</code>; floats are hex/255 — nothing invented	Strip the documentation keys (<code>jq 'del(._meta) \ walk(if type == "object" then del(._hex) else . end)'</code>), then POST to <code>/v1/files/{key}/variables</code> (Enterprise token required) or replay 1:1 through the Plugin API (<code>figma.variables.*</code>) — step 3 of the file plan's build order
<code>figma-file-plan.md</code>	The page-by-page blueprint of the “Thready — Design Library” file: Cover · Foundations (variables, type ramp in Space Grotesk / Hanken Grotesk / JetBrains Mono, color roles light+dark, elevation, motion) · 14 component sets with variant axes · Screens Web (14 × 1440w) / Mobile (8 × 390w, Android+iOS chrome variants) / Desktop + TUI (1 + 5 mono 80-col) · Platform overrides (6 boards) · Prototype wiring (4 ux-flows journeys) — plus the build order & Plugin-API execution notes (fonts preflight with <code>listAvailableFontsAsync</code>, Inter fallback flagged never silent, one page per <code>use_figma</code> call)	Read top-to-bottom before building; execute \$11 build order strictly; check off \$12 acceptance
<code>README.md</code> (this file)	Catalogue + the two materialization paths	Start here

Materialization path A — Figma MCP (`use_figma` Plugin API)

Requires **OAuth** to Figma (the Figma MCP server's `authenticate` flow) and a seat that can run plugin code.

1. Authenticate the Figma MCP server (OAuth) and create the empty file `Thready — Design Library`.
2. Drive the Plugin API through `use_figma`, executing `figma-file-plan.md` §11 in order: fonts preflight → variables (replay `figma-variables.json` via `figma.variables.createVariableCollection` / `createVariable` / `setValueForMode` / `createVariableAlias`) → text+effect styles → components → screens → overrides → prototype reactions. **One page per `use_figma` call.**
3. Run the acceptance checklist (file-plan §12), record the build in the revision tables, and close `[OPEN: THREADY-DES-FIG-01]`.

Materialization path B — manual import

No plugin execution; a designer with any Figma plan.

1. Create the file `Thready — Design Library` with the 8 pages named in the file plan.
2. **Components:** drag `../library/components-sheet.svg` into the Components page — it is a valid standalone SVG with grouped, named layers, so it imports as structured vectors (light panel + dark panel). Use it as the tracing/reference base and rebuild the 14 component sets per file-plan §5, binding to variables as you go.
3. **Variables:** Figma's UI has **no built-in JSON variables import** — use either the REST bulk endpoint (`POST /v1/files/{key}/variables`, Enterprise token) with the stripped JSON, or a variables-import plugin that accepts the collection/mode/variable structure, or enter the 41 variables by hand from the JSON (the `description` fields carry the verbatim hex values — no hex ever needs to be re-derived). Path decision tracked as `[OPEN: THREADY-DES-FIG-02]`.
4. Continue with screens/overrides/wiring per the file plan; the same acceptance checklist applies.

Provenance (no bluff)

- Every color/number in the kit traces to `../opendesign/tokens.css` `[VERIFIED]`; contrast claims (accent 6.03:1 light / 13.56:1 dark, brand 1.47:1 decorative only) come from `../opendesign/DESIGN.md` §2 measurements.
- Component axes and counts trace to `../library/README.md` (14 groups, ~38 components, ~118 state cells — the file plan reconciles its 108 static variant cells against that number honestly, §5).
- Screen frames trace 1:1 to the artifacts under `../screens/{web, mobile, desktop, tui}/`; the two non-artifact-backed frames are flagged (`mobile/channels-list` `[OPEN: THREADY-DES-FIG-03]`, notifications `[OPEN: THREADY-DES-15]`).

- Deliberately **not** in the variables payload (documented in the JSON `_meta` and file-plan §2): CSS-only constructs — B-slot aliases, `color-mix()` hover/elevation/focus formulas, easing curve, section rhythm/gutters, font families, tracking.

Open items

- `[OPEN: THREADY-DES-FIG-01]` — **create the actual Figma file** by executing the plan (path A or B); until then no Figma artifact exists.
 - `[OPEN: THREADY-DES-FIG-02]` — variables import mechanism (Enterprise REST vs Plugin-API replay vs plugin).
 - `[OPEN: THREADY-DES-FIG-03]` — `mobile/channels-list` frame lacks a mid-fi HTML source.
 - Inherited: `[OPEN: THREADY-DES-02]` (PenPot/Lottie bridges — out of scope here), `[OPEN: THREADY-DES-04]` (Cyrillic subsets), `[OPEN: THREADY-DES-09]` (hi-fi frames — closed by executing this kit), `[OPEN: THREADY-DES-11/12]` (component API names / upstream split), `[OPEN: THREADY-DES-13]` (PenPot's role).
-

Made with love ♥ by Helix Development.