

Helix Thready — Figma File Plan ("Thready — Design Library")

Table of contents

1. Ground truth & non-negotiables

2. File-level conventions

3. Page 1 — Cover

4. Page 2 — Foundations

5. Page 3 — Components (14 sets)

6. Page 4 — Screens · Web (14 frames, 1440w)

7. Page 5 — Screens · Mobile (8 frames, 390w)

8. Page 6 — Screens · Desktop + TUI

9. Page 7 — Platform overrides

10. Page 8 — Prototype wiring

11. Build order & Plugin-API execution notes

12. Acceptance checklist

13. Open items

Rev	Date	Author	Change
1	2026-07-22	swarm (design · figma)	Initial 8-page blueprint: foundations, 14 component sets with variant axes, web/mobile/desktop/TUI screen frames, platform overrides, prototype wiring, Plugin-API build order. Every value traced to <code>tokens.css</code> / <code>DESIGN.md</code> / <code>library/</code> / <code>screens/</code> — nothing invented

The page-by-page blueprint of the “**Thready — Design Library**” Figma file, precise enough for an agent with Figma Plugin API access (Figma MCP `use_figma`) to execute mechanically. The Figma file **does not exist yet** — building it is `[OPEN: THREADY-DES-FIG-01]` . Until then this plan plus `figma-variables.json` is the deliverable.

Table of contents

- 1. Ground truth & non-negotiables

- 2. File-level conventions
- 3. Page 1 — Cover
- 4. Page 2 — Foundations
- 5. Page 3 — Components (14 sets)
- 6. Page 4 — Screens · Web (14 frames, 1440w)
- 7. Page 5 — Screens · Mobile (8 frames, 390w)
- 8. Page 6 — Screens · Desktop + TUI
- 9. Page 7 — Platform overrides
- 10. Page 8 — Prototype wiring
- 11. Build order & Plugin-API execution notes
- 12. Acceptance checklist
- 13. Open items

1. Ground truth & non-negotiables

- **Tokens:** `../opendesign/tokens.css` is canonical; the Figma Variables in `figma-variables.json` carry it verbatim `[VERIFIED — generated 1:1, hex → r/g/b floats]`. **Never restate a hex inline in Figma** — bind fills/strokes/radii/gaps/font-sizes to variables; anything unbindable gets an annotation naming its token.
- **Brand contract:** `../opendesign/DESIGN.md` — brand is decorative, accent is interactive, semantic is state; `--danger` never masked by brand; one brand-gradient focal element per screen; locked footer “Made with ♥ by Helix Development” on every screen.
- **Component inventory:** `../library/README.md` — 14 groups, ~38 components, ~118 component-state cells; `components.html` is the visual source the Figma components must reproduce, not reinterpret.
- **Screens:** the `../screens/{web,mobile,desktop,tui}/` HTML artifacts are the mid/high-fi source of every frame — copy their **realistic Thready data** (no lorem ipsum) and their honest gap banners (`[GAP: 5.1]` Max stub, `[GAP: 2.1]` degraded search, etc.).
- **No invented values** `[CONSTITUTION §11.4.6]` — if a needed value is missing, flag it and use the nearest token.

2. File-level conventions

- **File name:** `Thready — Design Library`. **Pages** exactly as numbered below (Figma page names: `1 · Cover`, `2 · Foundations`, `3 · Components`, `4 · Screens — Web`, `5 · Screens — Mobile`, `6 · Screens — Desktop + TUI`, `7 · Platform Overrides`, `8 · Prototype Wiring`).

- **Modes:** collection `Thready / Color` has modes **Light** and **Dark**; components are built once and previewed in both by section frames with an explicit mode override (light section = Light mode, dark section = Dark mode). Collection `Thready / Structure` is single-mode.
- **Frame naming:** `web/<screen>`, `mobile/<screen>/<android|ios>`, `desktop/shell`, `tui/<screen>`, `overrides/<platform>` — stable names, referenced by the prototype wiring.
- **Fonts:** Space Grotesk (display, 600–700), Hanken Grotesk (body, 400–500; buttons 500, badges 600), JetBrains Mono (code/metadata, tabular figures) `[VERIFIED — DESIGN.md §3]`. Availability check + substitution rule in §11 step 2.
- **Elevation & focus (effect styles,** because shadows are not variables): `elev/ring` = inner-shadow-like 1px stroke or drop shadow `0 0 0 1px` in `border`; `elev/raised` = drop shadow `0 2px 8px` of `fg` at **8% opacity** (faithful translation of `color-mix(in oklab, var(--fg), transparent 92%)`); `focus/ring` = `0 0 0 3px` of `accent` at **30% opacity** (`transparent 70%`) `[VERIFIED formulas — tokens.css]`. Effect colors bind to the `fg` / `border` / `accent` variables so both modes resolve correctly.
- **Not carried as variables (deliberate,** mirrors `figma-variables.json` `_meta`): B-slot aliases `fg-2 / meta / border-soft`; `accent-hover / accent-active` (oklab mixes — baked into hover-state variants per mode with an annotation naming the formula); `ease-standard` (prototype easing setting `cubic-bezier(0.2, 0, 0, 1)`); section rhythm 80/48/32 and gutters 24/16/12 (layout annotations on screen frames); `tracking-display` `-0.01em` (text styles).

3. Page 1 — Cover

One frame `cover` (1440×1024):

- Brand mark from `../assets/logo-mark.svg` (import the SVG — never redraw), title **Thready — Design Library** in Space Grotesk 700 / `text-3xl` 48, tagline “*read your threads, smarter*” `[VERIFIED — DESIGN.md §1 Voice & tone]` in Hanken Grotesk / `text-lg`.
- The brand gradient `brand → brand-2` as the single decorative focal element (one per screen — contract rule).
- Status block (JetBrains Mono, `text-sm`): file status **Draft v0.1**, source-of-truth pointers (this plan + `tokens.css`), the build date, and — if §11 step 2 substituted any font — the **red substitution notice** (see §11).
- Locked footer lockup: “*Made with ♥ by Helix Development*”, heart bound to `ds-heart`.

4. Page 2 — Foundations

Five section frames, each duplicated Light/Dark via mode override where color-bearing:

1. **foundations/variables** — two auto-layout tables rendering the imported collections: `Thready / Color` (16 variables × Light/Dark swatches + hex labels sourced from the variable values, not typed by hand) and `Thready / Structure` (25 variables: 8 spacing, 4 radius, 8 text sizes, 2 leadings, 2 motion

durations, container-max). Note under the table: `ds-heart` is an **alias** → **accent**; `fg-2` / `meta` / `border-soft` are CSS B-slot aliases not imported.

2. **foundations/type** — the type ramp in the three faces. Text styles to create (names `[DEFAULT — adjustable]`, values `[VERIFIED — tokens.css]`):

Style	Face / weight	Size (variable)	Line-height	Tracking
<code>display/4xl</code>	Space Grotesk 700	<code>text-4xl</code> 64	120% (<code>leading-tight</code> 1.2)	-1% (-0.01em)
<code>display/3xl</code>	Space Grotesk 700	<code>text-3xl</code> 48	120%	-1%
<code>heading/2xl</code>	Space Grotesk 600	<code>text-2xl</code> 32	120%	-1%
<code>heading/xl</code>	Space Grotesk 600	<code>text-xl</code> 24	120%	-1%
<code>title/lg</code>	Space Grotesk 600	<code>text-lg</code> 20	120%	-1%
<code>body/base</code>	Hanken Grotesk 400	<code>text-base</code> 16	150% (<code>leading-body</code> 1.5)	0
<code>body/medium</code>	Hanken Grotesk 500	<code>text-base</code> 16	150%	0
<code>small/sm</code>	Hanken Grotesk 400	<code>text-sm</code> 14	150%	0
<code>caption/xs</code>	Hanken Grotesk 400	<code>text-xs</code> 12	150%	0
<code>mono/base</code>	JetBrains Mono 400	<code>text-base</code> 16	150%	0 (tabular figures ON)
<code>mono/sm</code>	JetBrains Mono 400	<code>text-sm</code> 14	150%	0

Line-height ratios 1.5/1.2 are stored as unitless floats in the Structure collection but **MUST** be applied as **percentages** in text styles (Figma has no unitless line-height).

3. **foundations/color-roles** — the role grid from DESIGN.md §2 with the measured contrast annotations: accent **6.03:1** on white (light) / **13.56:1** on `#020817` (dark), brand **1.47:1** (decorative-only warning), `accent ≠ danger` contract note `[VERIFIED — DESIGN.md §2]`.
4. **foundations/elevation** — three cards demonstrating `elev/flat` (none), `elev/ring` (preferred in dark), `elev/raised`, plus the `focus/ring` demo; formulas printed verbatim.
5. **foundations/motion** — spec board: `motion-fast` **150ms** (hover/press), `motion-base` **200ms** (enter/exit), easing `cubic-bezier(0.2, 0, 0, 1)`; all motion honors `prefers-reduced-motion` `[VERIFIED — tokens.css]`. Reference (annotation, not embed — Figma can't play Lottie): the shipped Lottie set in `../motion/` (`helix-spinner`, `processing-pulse`, `success-check`, `error-cross`, `thread-sync`, `transition-fade-slide`).

5. Page 3 — Components (14 sets)

The 14 groups of `../library/README.md` (anchors `#buttons` ... `#tooltips`), each as a Figma **component set** with variant properties. Visual truth is `../library/components.html`; state styling (hover mixes, focus ring, disabled at reduced opacity, error = `danger`) follows `DESIGN.md §4` and the shipped `.ds-btn` CSS.

#	Group (library anchor)	Component set(s)	Variant properties	Cells
1	Buttons <code>#buttons</code>	<code>Button</code>	<code>variant</code> = primary / secondary / ghost / destructive; <code>state</code> = default / hover / focus / disabled / loading	20 <code>[VERIFIED count - library README]</code>
2	Inputs <code>#inputs</code>	<code>Input</code>	<code>control</code> = text / select / checkbox / radio / switch / date; <code>state</code> = default(+hint) / focus / error(+hint) / disabled	24 <code>[VERIFIED count - library README]</code>
3	Cards <code>#cards</code>	<code>Card</code> [<code>elevation</code> = flat / ring / raised]; <code>StatCard</code> (thready-stat KPI); <code>ThreadRow</code> [<code>state</code> = default / hover / focus]	axes at left	7
4	Tables <code>#tables</code>	<code>TableHeaderCell</code> [<code>sort</code> = none / asc / desc]; <code>TableRow</code> [<code>state</code> = default / hover]; <code>Table</code> (composite incl. pagination strip) ×2	axes at left	7
5	Badges & chips <code>#badges-chips</code>	<code>Badge</code> [<code>tone</code> = success / warn / danger / neutral]; <code>TagChip</code> [<code>origin</code> = direct / indirect “(derived)”]; <code>ProcessingChip</code> [<code>state</code> = pending / processing / done / failed(+retry) / retrying]	axes at left	11
6	Navigation <code>#navigation</code>	<code>Topbar</code> ; <code>Sidebar</code> [<code>state</code> = expanded /	axes at left	10

#	Group (library anchor)	Component set(s)	Variant properties	Cells
		collapsed]; SidebarItem [state = default / active / hover]; Tab [state = default / active / focus]; Breadcrumbs		
7	Dialogs #dialogs	Dialog	kind = standard / destructive-confirm	2
8	Toasts & alerts #toasts-alerts	Alert [tone = success / warn / danger]; Toast [role = status / alert]	axes at left	5
9	Progress #progress	ProgressBar [state = determinate / indeterminate / failed]; SpinnerRing; SpinnerHelix (helix-motif)	axes at left	5
10	Avatars #avatars	Avatar [size = sm / md / lg; presence = none / online]; AvatarGroup	axes at left	7
11	Empty states #empty-states	EmptyState	kind = empty / error(+retry)	2
12	Skeletons #skeletons	Skeleton	shape = text-row / card	2
13	Pagination #pagination	PaginationItem [state = default / current / disabled]; Pagination (composite < 1 [2] 3 >)	axes at left	4
14	Tooltips #tooltips	Tooltip	trigger = hover / focus	2

Count reconciliation (honest): rows 1–2 are the library’s own verified counts (20 + 24). The remaining axes are derived from the exhibits listed in the library README; this plan enumerates **108 static variant cells** against the library’s **≈118 state cells** — the delta is *behavioral* states (live table sorting/paging, toast auto-dismiss + hover-pause, `<dialog>` open/close, theme cycling) that are interactions, not static variants. The builder **MUST** reconcile the finished sets against `components.html` exhibit-by-exhibit and record the final per-group counts on the page. The 14 sets fold the library’s ~38 distinct components into variant axes (e.g. `Input` folds 6 controls), so set-count ≠ component-count by design. Component API names remain `[OPEN: THREADY-DES-11]`; upstream-vs-Thready split `[OPEN: THREADY-DES-12]`.

Page layout: one section frame per group, Light column + Dark column (mode override), each cell labeled `variant · state` in `mono/sm`. Both-mode preview target ≈ 2 × cells.

6. Page 4 — Screens · Web (14 frames, 1440w)

One frame per artifact in `../screens/web/`, **1440×auto**, content copied from the HTML (same realistic data, same state banners), composed from Page-3 instances. Layout constants: `container-max` 1200 centered, 24px desktop gutters, 80px section rhythm (annotated, not variables).

Frame	Source artifact	Screen
<code>web/login</code>	<code>login.html</code>	Login / MFA
<code>web/dashboard</code>	<code>dashboard.html</code>	Dashboard (stats 128 / 1,204 / 17 / 42.1 TB, live activity, queue)
<code>web/channels</code>	<code>channels.html</code>	Channels list + Add-Channel wizard modal
<code>web/thread-explorer</code>	<code>thread-explorer.html</code>	Channel detail / thread list
<code>web/post-detail</code>	<code>post-detail.html</code>	Post detail / processing pipeline
<code>web/search</code>	<code>search.html</code>	Search (semantic/keyword/hybrid, scores 0.94/0.91/0.88)
<code>web/assets-browser</code>	<code>assets-browser.html</code>	Assets grid/list + detail drawer
<code>web/skills-manager</code>	<code>skills-manager.html</code>	Skills / Recipes + skill graph
<code>web/research-viewer</code>	<code>research-viewer.html</code>	Generated research doc
<code>web/accounts-admin</code>	<code>accounts-admin.html</code>	Admin — Accounts / Users & roles / Audit
<code>web/billing</code>	<code>billing.html</code>	Billing & usage (amounts stay — placeholders <code>[OPEN: THREADDY-DESCR-01]</code>)
<code>web/settings</code>	<code>settings.html</code>	Settings — Prefs / Branding white-label (AA meter) / Messengers
<code>web/events-monitor</code>	<code>events-monitor.html</code>	Events monitor (live tail)
<code>web/index</code>	<code>index.html</code>	Prototype shell / gallery (becomes the Page-8 hub frame)

Each frame ships Light; a Dark duplicate (`web/<screen>/dark`) is generated for the four journey-critical screens (dashboard, post-detail, search, settings) — full dark duplication of all 14 is deferred to the build `[DEFAULT — adjustable]`.

7. Page 5 — Screens • Mobile (8 frames, 390w)

Frames at **390×844** from `../screens/mobile/`. Each screen gets **two platform-annotation variants** — `mobile/<screen>/android` (Material 3 chrome: punch-hole status bar, ← + predictive back, 80dp pill-indicator nav bar) and `mobile/<screen>/ios` (Dynamic Island, < Title + edge swipe, 49pt tab bar + home indicator) — mirroring the artifacts' chrome toggle. 8 screens × 2 = 16 frames.

Frame base	Source artifact	Screen	Status
mobile/home-feed	home-feed.html	Home — live activity + processing + threads	grounded
mobile/channels-list	— no HTML artifact	Channels tab list (#ml-papers ✓ / #films ↻ / Max: dev-notes ⚠)	derived from wireframes \$6 IA (CHLIST node) + channel-threads.html chrome [DEFAULT — adjustable] [OPEN: THREADY-DES-FIG-03]
mobile/channel-threads	channel-threads.html	Channel detail — thread list	grounded
mobile/post-detail	post-detail.html	Post detail — tags, pipeline, Reprocess	grounded
mobile/search	search.html	Search — modes, scope, scored results	grounded
mobile/notifications	notifications.html	Notifications centre	derived surface [OPEN: THREADY-DES-15]
mobile/account	account.html	Account — switcher, RBAC, sign out	grounded
mobile/settings	settings.html	Settings — theme/ language, branding (read-only [OPEN: THREADY-DES-06]), messengers	grounded

Honesty banners carried into the frames: Security-KMP [GAP: 7.3] and UI-Components-KMP [GAP: 8.4] are mobile **release gates**; Max adapter [GAP: 5.1] ; degraded search [GAP: 2.1] .

8. Page 6 — Screens · Desktop + TUI

- **desktop/shell** — one **1440×900** frame from `../screens/desktop/desktop-shell.html` : Tauri window, per-OS title-bar strip (macOS traffic lights / Windows caption buttons / Linux CSD), native menu map, wrapped Dashboard (instance of `web/dashboard` content), tray popover mock + native notification mock both labeled [OPEN: THREADY-DES-08] , file-drop overlay (media-file case labeled [OPEN: THREADY-DES-16]).
- **Five TUI frames** from `../screens/tui/tui-screens.html` , each a **mono-text 80-column** frame: JetBrains Mono 16/120%, fixed width 800px (80ch ≈ 768px + padding [DEFAULT — adjustable]), **dark palette only** — the TUI defaults to the terminal's dark surface (design-system \$7); box-drawing text pasted verbatim from the artifact so alignment survives.

Frame	TUI screen	Status
<code>tui/dashboard</code>	1 · Dashboard (key rail + live viewport + threads + statusbar)	grounded
<code>tui/channels</code>	2 · Channels (inverse-accent selection)	grounded
<code>tui/thread-view</code>	3 · Thread view / Post detail (409 idempotent retry)	grounded
<code>tui/search</code>	4 · Search (degraded-embedder banner <code>[GAP: 2.1]</code>)	grounded
<code>tui/processing-queue</code>	5 · Processing queue	derived <code>[DEFAULT — adjustable]</code>

ANSI-16 mappings on these frames are annotations from `../screens/tui/lipgloss-theme.md` and stay ASSUMED pending terminal verification `[OPEN: THREADY-DES-17]`.

9. Page 7 — Platform overrides

Six annotation frames (`overrides/<platform>`), each a callout board sourced from `../library/platform-map.md` §2/§4 and design-system §7 — the per-platform customization deltas plus the **honest scaffold status** (never claim a scaffold works):

Frame	Content highlights	Status callout
<code>overrides/android</code>	Compose realizations (<code>TopAppBar</code> , <code>Snackbar</code> , <code>DatePickerDialog</code> ...), focus → ripple, native date sheet, <code>ANIMATOR_DURATION_SCALE</code> reduced-motion	<code>UI-Components-KMP</code> = utilities-only scaffold, foreign (Vole) palette <code>[GAP: 8.4]</code> — all widget cells ASSUMED
<code>overrides/ios</code>	SwiftUI mappings (<code>Picker</code> instead of radio groups — documented divergence; <code>.redacted</code> skeletons; <code>UIAccessibility.isReduceMotionEnabled</code>)	no in-house SwiftUI package — column entirely ASSUMED <code>[OPEN: THREADY-DES-LIB-02]</code>
<code>overrides/harmonyos</code>	ArkTS mappings (<code>promptAction.showToast</code> , <code>Toggle(Switch)</code> accent track)	native via <code>helix_shims</code> , uninspected <code>[GAP: 8.5]</code> <code>[OPEN: THREADY-DES-LIB-03]</code>
<code>overrides/aurora</code>	Qt/QML mappings (<code>TableView</code> , <code>BusyIndicator</code>), layered icon JSON	<code>helix_design</code> = empty scaffold <code>[GAP: 8.2/8.3]</code> ; density buckets <code>[OPEN: THREADY-DES-05]</code>
<code>overrides/desktop</code>	Tauri chrome, accelerators additive to verified web keys, close-to-tray, offline cache contract	tray/notifications scope <code>[OPEN: THREADY-DES-08]</code>
<code>overrides/tui</code>	Lipgloss role styles, <code>[r]etry</code> key binding, dimmed+ <code>~</code> indirect tags, braille helix spinner	pattern VERIFIED (llms_verifier); Thready style set PROPOSED; ANSI picks ASSUMED <code>[OPEN: THREADY-DES-17]</code>

10. Page 8 — Prototype wiring

The four `../ux-flows.md` journeys, mirroring the working shell `../screens/web/index.html` §4. Hub frame: `web/index`. Default transition: **Smart Animate, 200ms (`motion-base`), easing `cubic-bezier(0.2, 0, 0, 1)`** ; overlays (wizard modal, drawers) open as Figma overlays with **Dissolve 150ms (`motion-fast`)** ; mobile back = swipe-right gesture on iOS variants, back-hotspot on Android variants.

Journey (ux-flows \$)	Frame chain (trigger = ON_CLICK on the named hotspot)
1 · Add channel (\$2 + \$2.1)	<code>web/login</code> [Sign in] → <code>web/dashboard</code> [Add channel] → <code>web/channels</code> [+ Add] ⇒ overlay wizard steps 1–4 (incl. messenger sign-in sub-flow \$2.1 as nested overlay) → <code>web/thread-explorer</code> (backfilling 54/128 state)
2 · Process post + Reprocess (\$3 + \$3.1)	<code>web/dashboard</code> [thread row] → <code>web/thread-explorer</code> [post] → <code>web/post-detail</code> [pipeline step] → <code>web/events-monitor</code> [research.md] → <code>web/research-viewer</code> [assets] → <code>web/assets-browser</code> ; back on <code>web/post-detail</code> : [Reprocess] ⇒ confirm overlay → 202 state; second click ⇒ 409 toast state
3 · Search (\$4)	<code>web/search</code> [result 0.94 · post] → <code>web/post-detail</code> ; [doc result] → <code>web/research-viewer</code>
4 · Manage account (\$5)	<code>web/accounts-admin</code> [Billing] → <code>web/billing</code> [Settings] → <code>web/settings</code> (branding editor: [Save] wired to the 422-AA-gate state, then success)

Error/degraded states are wired as **variant swaps inside the frame** (e.g. search → degraded-embedder banner), not separate journeys. Endpoint/event names on annotations stay `[DEFAULT – adjustable]` until `[OPEN: THREADY-DES-10]` closes.

11. Build order & Plugin-API execution notes

Execute strictly in this order — later steps consume earlier ones:

- Create the file** `Thready – Design Library` (Figma MCP `figma-create-new-file` , or manually — see `README.md` path B).
- Fonts preflight.** `figma.listAvailableFontsAsync()` ; require *Space Grotesk*, *Hanken Grotesk*, *JetBrains Mono*. If Space Grotesk or Hanken Grotesk is unavailable → substitute **Inter** `[OPERATOR–specified fallback]` ; if JetBrains Mono is unavailable → substitute **Roboto Mono** `[DEFAULT – adjustable]` . **Every substitution is flagged, never silent:** red notice on the Cover, `(SUBSTITUTED)` suffix on affected text-style descriptions, and a line in the build log.
- Variables.** Import `figma-variables.json` : strip `_`-prefixed keys, then replay via Plugin API — `figma.variables.createVariableCollection("Thready / Color")` (rename default mode → Light, `addMode("Dark")`), `createVariableCollection("Thready / Structure")` (default mode → Value), then per variable `createVariable(name, collection, type)` + `setValueForMode(...)` per mode + `scopes / description / codeSyntax` from the JSON; `ds-heart` set with `figma.variables.createVariableAlias(accent)` in both modes. (The REST bulk endpoint `POST /v1/files/{key}/variables` accepts the file as-is but requires an Enterprise token — see README.)

4. **Styles.** Text styles (§4 table, sizes bound to `text-*` variables) and effect styles (`elev/ring`, `elev/raised`, `focus/ring` — colors bound to variables).
5. **Page 2 Foundations** frames (§4).
6. **Page 3 Components** — one group per `use_figma` call (14 calls minimum; payload limits): build set → bind every fill/stroke/radius/gap/font-size to a variable → verify against `components.html` → label cells.
7. **Pages 4–6 Screens** — one page per `use_figma` call, screens composed from Page-3 instances; explicit Dark mode override on dark sections; realistic data copied from the HTML artifacts.
8. **Page 7 Platform overrides** annotation frames.
9. **Page 8 Prototype wiring** — `setReactionsAsync` per the §10 table (Smart Animate 200ms / Dissolve 150ms, easing `cubic-bezier(0.2, 0, 0, 1)`).
10. **Acceptance pass** (§12) + record the run in this file’s revision table and close/update `[OPEN: THREADY-DES-FIG-01]`.

Standing rules for the executing agent: one page per `use_figma` call; never hard-code a hex — bind a variable or annotate the token name; never redraw brand assets — import the SVGs from `../assets/`; when anything cannot be reproduced (font, Lottie, live behavior), annotate the limitation on-canvas rather than approximating silently.

12. Acceptance checklist

- ☐ 41 variables imported (16 color × Light/Dark incl. `ds-heart` alias, 25 structure) — values diff clean against `tokens.css` (script-diff hex ↔ r/g/b floats).
- ☐ 11 text styles + 3 effect styles created; substitutions (if any) flagged on Cover.
- ☐ 14 component sets built; per-group cell counts recorded and reconciled vs `components.html` (plan enumerates 108 static cells; library counts ≈118 incl. behavioral states).
- ☐ Frames: 1 cover + 5 foundations + 14 web + 16 mobile (8 × android/ios) + 1 desktop + 5 TUI + 6 overrides.
- ☐ 4 prototype journeys wired per §10; transitions 200ms/150ms on `cubic-bezier(0.2,0,0,1)`.
- ☐ Contrast annotations present (6.03:1 / 13.56:1 / 1.47:1); `danger` never brand-tinted.
- ☐ Honesty markers rendered on-canvas: `[GAP: 5.1]` Max, `[GAP: 2.1]` degraded search, `[GAP: 8.4]` / `[GAP: 7.3]` mobile gates, `[OPEN: THREADY-DES-08/15/16/17]`.
- ☐ Locked footer “Made with ♥ by Helix Development” on the cover and every screen frame, heart bound to `ds-heart`.

13. Open items

- `[OPEN: THREADY-DES-FIG-01]` — **the Figma file does not exist yet**; this plan is the executable blueprint. Requires Figma MCP OAuth (or manual path). Owner: design · figma.
 - `[OPEN: THREADY-DES-FIG-02]` — variables import path decision: Plugin API replay (any plan) vs REST bulk `POST /v1/files/{key}/variables` (Enterprise-only token).
 - `[OPEN: THREADY-DES-FIG-03]` — `mobile/channels-list` has no mid-fi HTML artifact; the frame is derived from wireframes \$6 IA and must be back-ported into `../screens/mobile/` (or the frame count revised) once the screens area rules on it.
 - Inherited, affecting this file: `[OPEN: THREADY-DES-04]` (Cyrillic subsets — affects Figma font choice for ru/sr-Cyrl frames), `[OPEN: THREADY-DES-09]` (these frames ARE the hi-fi pass — closing it happens by executing this plan), `[OPEN: THREADY-DES-11/12]` (component names), `[OPEN: THREADY-DES-13]` (PenPot mirror role), `[OPEN: THREADY-DES-02]` (PenPot/Lottie bridges are separate deliverables, not Figma work).
-

Made with love ♥ by Helix Development.