

Assets & deliverables manifest — every design resource, in every form, for every app and platform

Assets & deliverables manifest — every design resource, in every form, for every app and platform

Revision: 1 Last modified: 2026-06-25T12:00:00Z

Master technical specification — Volume 10 (Design System), nano-detail anchor document. This doc is the **complete deliverables manifest** for the HelixVPN design system. It directly answers the operator mandate (2026-06-25): *"all design, UI and UX resources available in all types and forms required for direct incorporating for all apps and all platforms."* For **every** resource class — tokens, color, typography, iconography, illustration/brand, components, motion, design-source/handoff, and docs — it names the **concrete artifact forms** produced, **where each lives** inside the `vasic-digital/helix_design` submodule, **which app/platform consumes which form**, and the **exact pull command** that incorporates it directly (no platform ever re-types a design value by hand — DS-I6 [OV §0.2]). It carries the **master deliverables matrix** (resource × form × consuming platform × submodule-path × pull-command), the **versioning/release model** for the asset corpus, the **per-app direct-incorporation recipe** (Client / Console / Connector + a generic future app), and how OpenDesign authoring artifacts round-trip into the deliverables.

SPEC-ONLY. It describes *what the design system ships and how each app takes delivery* — not the built `helix_design` artifact. The **submodule layout + exporters + OpenDesign relationship** are owned by `[00-overview-and-submodule.md]`; the **export-pipeline mechanics + per-target output samples** by `[token-export-pipeline.md]`; the **token model** by `[design-tokens.md]`; the **color values + contrast** by `[color-system.md]`; the **type/icon/motion families** by `[typography-iconography-motion.md]`; the **component anatomy** by `[component-library.md]`; the **OpenDesign facts** by `[opendesign-foundation.md]`; the **per-platform adaptation rules** by `[platform-adaptation.md]`. This document **consumes** those and assembles the single delivery view across them.

Evidence base. [OV §N] = final/v10-design/00-overview-and-submodule.md; [EXP §N] = final/v10-design/token-export-pipeline.md; [DT §N] = design-tokens.md; [COLOR §N] = color-system.md; [TIM §N] = typography-iconography-motion.md; [CMP §N] = component-library.md; [OD §N] = opendesign-foundation.md; [PLAT §N] = platform-adaptation.md; [04_CLIENT §N] = final/v04-client/helix-ui-flutter.md; [SPINE §N] = final/SPECIFICATION.md. Claims not grounded in the evidence base or in this document's own original delivery design are tagged UNVERIFIED per constitution §11.4.6 — never fabricated. Font-licensing and asset-hosting choices are surfaced as D-DEL-N decisions, not silently made.

Table of contents

- [0. The delivery model at a glance](#)
 - [1. The resource classes \(the nine deliverable families\)](#)
 - [2. Design tokens — forms & delivery](#)
 - [3. Color — forms & delivery](#)
 - [4. Typography — forms & delivery \(+ the font-licensing decision\)](#)
 - [5. Iconography — forms & delivery](#)
 - [6. Illustration & brand — forms & delivery](#)
 - [7. Components — forms & delivery](#)
 - [8. Motion — forms & delivery](#)
 - [9. Design source / handoff — forms & delivery](#)
 - [10. Docs — forms & delivery \(§11.4.65 / §11.4.168\)](#)
 - [11. The master deliverables matrix](#)
 - [12. Deliverables → packaging → consumption \(diagram\)](#)
 - [13. The versioning & release model for the asset corpus](#)
 - [14. The direct-incorporation recipe per app](#)
 - [15. How OpenDesign authoring artifacts round-trip into the deliverables](#)
 - [16. Asset-corpus quality gates owned here](#)
 - [17. Surfaced decisions](#)
 - [Sources verified](#)
-

0. The delivery model at a glance

The HelixVPN design system ships **one canonical source** and **many derived forms**, so each app on each platform incorporates the exact form its toolchain consumes — directly, with zero hand-copying (DS-I6 [OV §0.2]). The delivery model has three layers:

Layer	What it is	Tracked in git?	Regenerated by
SOURCE	the canonical, human-authored design truth: tokens/** JSON, presets/<brand>/**,	yes (tracked)	authored — never machine-generated

Layer	What it is	Tracked in git?	Regenerated by
DERIVED	icon source SVG, illustration source, font files (or references), component specs, the OpenDesign DESIGN.md		
	every machine-emitted consumable form: dist/** (CSS/Dart/Swift/Compose/ArkTS/C-Qt/JSON), per-platform icon/color asset catalogs, rendered .html/.pdf/Dart/Dx docs	no (gitignored build-derivative per §11.4.30/§11.4.77) except the checked-in Flutter package Dart/Dx DESIGN-2 [OV §4])	pnpm export (tokens/colors), pnpm assets (icon/illustration rasterisation), sync_all_markdown_exports (docs)
	a tagged, pinnable bundle a consumer pulls without running the Node toolchain: the published Flutter pub package + a versioned helix_design-<semver>-dist.tar.zst of all dist/** forms	published per tag (not in the working tree)	the §13 release pipeline
RELEASE ARTIFACT			

The operative rule for "all forms, ready for direct incorporation": **a consuming app never builds the design system itself — it pulls a release artifact (or runs the one pnpm export step once) and imports the form its platform speaks (§14).** The SOURCE→DERIVED equality is enforced by the DS-DRIFT gate [EXP §5] so a derived form can never silently diverge from source.

flowchart LR

```

subgraph S["SOURCE (tracked)"]
  tok["tokens/** + presets/**"]
  ico["assets/icons/*.svg"]
  ill["assets/illustrations/* (source)"]
  fnt["assets/fonts/* (or refs)"]
  spc["components/specs/*.md"]
  odd["opendesign/helix/DESIGN.md"]

```

```

end
subgraph D["DERIVED (regenerated)"]
  dist["dist/{css,dart,swift,compose,arkts,cqt,json}"]
  icoout["assets/icons/<platform>/ (xcassets/drawable/...)"]
  rasters["illustration/logo rasters per platform"]
  docs["docs .html/.pdf/.docx"]
end
subgraph R["RELEASE ARTIFACT (published per tag §13)"]
  pub["pub package helix_design"]
  bundle["helix_design-<semver>-dist.tar.zst"]
end
tok --> dist
ico --> icoout
ill --> rasters
spc --> docs
odd <--> |round-trip §15| tok
dist --> bundle
dist --> pub
icoout --> bundle
rasters --> bundle
pub --> APPS["Client / Console / Connector / future app"]
bundle --> APPS

```

1. The resource classes (the nine deliverable families)

Nine resource classes cover every design/UI/UX resource the mandate names. Each is deepened in §2–§10 and rolled up in the master matrix (§11).

#	Resource class	Source form (tracked)	Primary deliverable forms	Detailed in
R1	Design tokens	tokens/** JSON (tiered, light+dark)	JSON bundle + CSS / Dart / Swift / Compose / ArkTS / C-Qt	§2, [DT], [EXP]
R2	Color	presets/<brand>/brand.json + tokens/semantic/color.{light,dark}.json	token bundles + per-platform color sets / asset catalogs	§3, [COLOR]
R3	Typography	font files (or refs) + tokens/**/type.json	font assets + licenses + type-scale tokens + per-platform text styles	§4, [TIM §1–§2]
R4	Iconography	assets/icons/*.svg	SVG set + icon-font + per-platform asset forms (xcassets/drawable/...)	§5, [TIM §3]
R5	Illustration & brand	logo/wordmark/app-icon/illustration source	per-platform app-icon sets + logo	§6, [TIM §3.5]

#	Resource class	Source form (tracked)	Primary deliverable forms	Detailed in
			forms + illustration + empty-state art	
R6	Components	components/specs/ *.md + components/ reference/**	the Flutter component package + design-source + per-platform notes	§7, [CMP]
R7	Motion	tokens/**/ motion.json	motion token bundle + reference specs	§8, [TIM §6–§8]
R8	Design source / handoff	opendesign/helix/ ** + redlines	OpenDesign DESIGN.md/ tokens.css/ components.html + redline specs	§9, [OD], [CMP]
R9	Docs	docs/v10-design/ *.md	this spec set + rendered .html/.pdf(/.docx)	§10, [OV §4]

Light + dark is universal across all nine classes (DS-I3 [OV §0.2]). Every token, color set, icon-on-surface pairing, component spec, illustration that carries a fill, logo lockup, and rendered doc swatch ships a **light AND a dark** variant. A single-theme deliverable is incomplete and FAILs DS-LIGHT-DARK-COMPLETE [OV §12].

2. Design tokens — forms & delivery

2.1 Source (tracked)

helix_design/tokens/** — the three-tier JSON tree (primitive → semantic → component), light+dark on the semantic color tier, authored in the W3C-DTCG \$value/\$type envelope [DT §3.1], plus the active presets/<brand>/ value set [OV §5.4]. This is the **single source of truth** for R1, R2, R3 (type metrics), R7 (motion); every other token form is a derived export [EXP §0].

2.2 Emitted forms (each consumed directly by a platform)

Form	File	Consuming platform/ app	How it is applied
JSON bundle	dist/json/ tokens.json	tooling, the OpenDesign tokens.css round-trip [EXP §7], any future target	read as data
	dist/css/helix.css		

Form	File	Consuming platform/app	How it is applied
CSS custom properties		Console Web (Flutter web build + any web chrome)	<link>/@import; :root light + [data-theme=dark] [EXP §4.1]
Dart ThemeExtension + ThemeData	packages/flutter/lib/src/helix_tokens.dart (checked-in package-source per D-DESIGN-2)	helix-ui Flutter (Client/Console/Connector) [04_CLIENT §2.1]	MaterialApp(theme: helixLight(helixDark())); widgets read Theme.of(context).extension<HelixTheme> [EXP §4.2]
SwiftUI tokens + .xcassets	dist/swift/HelixTokens.swift + HelixColors.xcassets	iOS/macOS native shims (NE config UI, widgets) [04_CLIENT §4.4]	add file + asset catalog to the extension [EXP §4.3]
Compose Color Scheme	dist/compose/HelixTokens.kt	Android native surfaces (quick-settings tile, notification)	MaterialTheme(colorScheme = HelixLightColorScheme) [EXP §4.4]
ArkTS resources	dist/arkts/helix_tokens.ets + resources/{base,dark}	HarmonyOS VPN-ability surfaces	\$r('app.color.hx_*') + qualifier tr
C/Qt header + QML singleton	dist/cqt/helix_tokens.h + Theme.qml	Aurora Qt/C++ surfaces	#include + import the Theme singleton

2.3 Pull command

```
# from the consuming project root, after the submodule is added
($14.1):
( cd helix_design && npm install && npm export )
# regenerates every dist/** form
# OR pull the pinned release bundle without the Node toolchain
($13):
helix_design/scripts/fetch-dist.sh <semver> # → unpacks
dist/** from the tagged artifact
```

3. Color — forms & delivery

3.1 Source (tracked)

The light + dark palettes live as **semantic color tokens** referencing primitive ramps [COLOR §2/§3]: `tokens/semantic/color.light.json` + `color.dark.json`, with the brand seed + accent + the 7-variant connection-state palette in `presets/helix/{brand.json,connection_state.json}` [OV §5.4/§5.5]. The palette is **generic** in the submodule; HelixVPN values are injected (DS-I1).

3.2 Emitted forms

Form	File	Consuming platform	Theme handling
CSS color custom properties	<code>inside dist/css/helix.css</code>	Web	<code>:root + [data-theme=dark] + @media (prefers-color-scheme)</code>
Dart ColorScheme + HelixTokens colors	<code>inside the Dart package</code>	Flutter	<code>ColorScheme.light() / .dark()</code> + connection-state colors as HelixTokens fields
Apple asset-catalog colorsets	<code>dist/swift/HelixColors.xcassets/*.colorset</code>	iOS/macOS	one colorset per themed color, light + dark appearance resolved by <code>@Environment(\.colorScheme)</code> [EXP §4.3]
Android color resources	<code>inside dist/compose/HelixTokens.kt (+ optional colors.xml values/ + values-night/)</code>	Android	<code>lightColorScheme() / darkColorScheme() + values-night</code> qualifier
HarmonyOS color resources	<code>dist/arkts/resources/base/element/color.json + resources/dark/element/color.json</code>	HarmonyOS	<code>base (light) / dark</code> qualifier sets [EXP §4.5]
Qt color set	<code>inside dist/cqt/{helix_tokens.h, Theme.qml}</code>	Aurora	<code>Theme.qml</code> dark property switch

The connection-state palette is a first-class color deliverable. The 7 UI states (Disconnected / Connecting / Connected-direct / Connected-relay / Reconnecting / Down / Danger [OV §5.5]) ship as named status tokens in every color form so the Client's `ConnectButton/StatusChip` render the identical state color on Flutter AND on each native shim. The Rust FFI `StatusProjector` produces the 7-variant `ffi::TunnelStatus` from the 5-variant `core::TunnelStatus` (it adds `Disconnected` and `Danger`) [ffi-surface.md §3.2/§3.3]; only the `Connected{direct|relay}` sub-shade and the `status-token→color` rendering are app-side in `helix_domain` [04_CLIENT §7.2] (DS-I1), never in the color deliverable.

3.3 Pull command

Same as R1 (§2.3) — color is part of the token export; the Apple .xcassets and HarmonyOS qualifier trees are emitted alongside the per-target token file.

4. Typography — forms & delivery (+ the font-licensing decision)

4.1 Source (tracked)

- **Font files (or references)** — the brand sans (Inter) + mono (JetBrains Mono) [OV §5.4], either bundled under assets/fonts/ or referenced per platform (the **D-DEL-1 licensing decision**, §4.4).
- **Type-scale tokens** — tokens/primitive/type.json (the size/line/weight scale) + tokens/semantic/type.json (the role styles: title.lg, body.md, label.sm, ...) [TIM §1.1].

4.2 Emitted forms

Form	File	Consuming platform	How applied
CSS @font-face + type custom properties	dist/css/helix.css (+ dist/css/fonts/)	Web	@font-face for bundled fonts + --hx-font-* properties
Flutter TextTheme + pubspec font decl	Dart package TextTheme + packages/flutter/pubspec.yaml fonts:	Flutter	Theme.of(context).textTheme.titleLarge
SwiftUI Font accessors	inside HelixTokens.swift	iOS/macOS	Font.custom("Inter", size:).weight(.semibold) (or system font on the tiny NE surface, [TIM §2.2 D-TYPE-1])
Compose Typography	inside HelixTokens.kt	Android	MaterialTheme(typography = HelixTypography)
ArkTS text metrics	inside helix_tokens.ets	HarmonyOS	fontSize/fontWeight numeric tokens
Qt font metrics	inside helix_tokens.h / Theme.qml	Aurora	int size/weight constants

4.3 Font asset forms (per platform)

Platform	Font asset form	Where it lives
Web	.woff2 (subset)	dist/css/fonts/*.woff2

Platform	Font asset form	Where it lives
Flutter (all)	.ttf/.otf declared in pubspec.yaml	packages/flutter/assets/fonts/
iOS/macOS	.ttf/.otf in the bundle + Info.plist UIFonts	assets/fonts/ → app target
Android	.ttf in res/font/	assets/fonts/ → res/font/
HarmonyOS	.ttf registered font	assets/fonts/ → HarmonyOS font resource
Aurora	system/bundled .ttf	assets/fonts/

4.4 D-DEL-1 — the font-licensing decision (surfaced, not silently made)

D-DEL-1 (open). Whether to **bundle** font files in assets/fonts/ (and ship them in every app artifact) or **reference** a system/Google-Fonts-hosted face per platform. The chosen brand faces — Inter and JetBrains Mono — are both **SIL Open Font License 1.1 (OFL)**, which **permits bundling and redistribution inside an application** provided the OFL license text travels with the font and the font is not sold on its own. **UNVERIFIED** — the exact OFL version + that these two specific faces are the final choice **MUST** be re-verified against the upstream font repositories per §11.4.99 before the assets ship; the OFL text **MUST** be committed at assets/fonts/<face>/OFL.txt alongside each face. **Lean: bundle** (OFL permits it; bundling removes a network/runtime dependency and guarantees the brand face renders offline — important for a VPN client whose network may be down). **Fallback per platform** is always declared (system-ui/-apple-system/Roboto) so a missing bundled face degrades to a platform sans, never to a broken render. Resolved at the Volume-10 assets review; the per-face license file is a tracked deliverable regardless of the bundle/reference choice.

4.5 Pull command

Type tokens travel with the token export (§2.3); font files travel with the release bundle (§13) or are referenced per pubspec.yaml/@font-face.

5. Iconography — forms & delivery

5.1 Source (tracked)

helix_design/assets/icons/*.svg — the master icon set as optimized source SVG (one file per glyph, on a 24×24 grid with a documented keyline, [TIM §3.1]). Icon **names** are semantic (shield_connected, shield_disconnected, exit_node, kill_switch, relay, settings, ...) so each platform's generated asset keeps a stable name.

5.2 Emitted forms

Form	File	Consuming platform	How applied
Optimized SVG set	assets/icons/*.svg	Web, Flutter (flutter_svg)	<svg> / SvgPicture.asset
Icon font	dist/icons/helix_icons.{ttf,woff2} + helix_icons.dart codepoint map	Flutter (IconData), Web (@font-face + glyph class)	Icon(HelixIcons.shieldConnected)
Apple SF-Symbols-style imageset / PDF	assets/icons/apple/HelixIcons.xcassets/*.imageset (vector PDF)	iOS/macOS	Image("HelixShieldConnected")
Android vector drawables	assets/icons/android/drawable/ic_helix_*.xml	Android	R.drawable.ic_helix_shield_conne
HarmonyOS media resources	assets/icons/harmony/resources/base/media/*.svg	HarmonyOS	\$r('app.media.helix_shield_conne
Qt resource SVG	assets/icons/qt/icons.qrc + SVG	Aurora	image:/// Image { source: "qrc:/icons/..." }

5.3 Sizing & rendering rules

Icons are authored at **24×24** with the [TIM §3.1] keyline; each platform asset carries the size variants its convention needs (iOS 1×/2×/3× via vector PDF; Android mdpi... xxxhdpi via vector drawable scaling; Web/Flutter scale the SVG/font freely). On-icon color comes from the **semantic on-* color tokens** (R2) so an icon on surface uses on-surface and inherits light/dark automatically — icons ship **monochrome/templated**, never with baked-in brand color (so one icon serves both themes). Two-tone state icons (e.g. the connection shield) are the documented exception and carry an explicit light+dark pair [TIM §3.3].

5.4 Pull command

```
( cd helix_design && pnpm assets:icons )    # SVG → icon-font +  
      per-platform asset forms  
# emitted into dist/icons/** and assets/icons/<platform>/**
```

6. Illustration & brand — forms & delivery

6.1 Source (tracked)

- **Logo / wordmark** — master vector source under `assets/logo/` (light + dark lockups: full logo, wordmark-only, mark-only), [TIM §3.5].
- **App icons** — the master app-icon source (a single high-res master per the largest platform requirement) under `assets/logo/app-icon/`.
- **Illustration set** — onboarding / hero / decorative illustrations under `assets/illustrations/source/` (vector source).
- **Empty-state art** — the "no servers", "not connected", "error" empty-state illustrations under `assets/illustrations/empty-states/`.

6.2 Emitted forms — logo

Form	File	Consuming platform
SVG (light+dark lockups)	<code>assets/logo/*.svg</code>	Web, Flutter
PNG @1×/2×/3×	<code>dist/logo/png/*</code>	any raster need
Apple imageset	<code>assets/logo/apple/Logo.xcassets</code>	iOS/macOS
Android drawable	<code>assets/logo/android/drawable/</code>	Android

6.3 Emitted forms — app icons (per-platform size matrices)

Each platform's app-icon set is generated from the one master so every required size/shape is present and consistent:

Platform	App-icon form & sizes	Where it lives
iOS	<code>AppIcon.appiconset</code> — 20/29/40/60/76/83.5 pt @1×/2×/3× + 1024 marketing	<code>dist/app-icon/ios/AppIcon.appiconset</code>
macOS	<code>.icns</code> / iconset — 16...1024	<code>dist/app-icon/macos/</code>
Android	adaptive icon (<code>ic_launcher</code> fore+back layers) + legacy <code>mipmap-*</code> (48...192) + Play 512	<code>dist/app-icon/android/</code>
Windows	<code>.ico</code> (16...256) + Store tiles	<code>dist/app-icon/windows/</code>
Linux	<code>.png</code> hicolor theme sizes (16...512) + <code>.desktop</code> ref	<code>dist/app-icon/linux/</code>
Web (PWA)	<code>favicon.ico</code> + manifest icons (192/512 + maskable)	<code>dist/app-icon/web/</code>
HarmonyOS	layered app icon (fore/back) in the HarmonyOS icon form	<code>dist/app-icon/harmony/</code>
Aurora	<code>.png</code> set per Aurora packaging	<code>dist/app-icon/aurora/</code>

UNVERIFIED (U-DEL-1). The exact HarmonyOS layered-icon spec + the Aurora app-icon size matrix are SDK/platform-version dependent; stated as the *intended* matrices, pinned + re-verified per §11.4.99 against the live HarmonyOS / Aurora packaging docs before the app-icon generator ships [PLAT]. The iOS/macOS/Android/ Windows/Linux/Web matrices are the well-documented platform conventions.

6.4 Emitted forms — illustration & empty-state

Form	File	Consuming platform
SVG (light+dark)	assets/ illustrations/*.svg	Web, Flutter (flutter_svg)
PNG @1×/2×/3×	dist/illustrations/ png/*	native shims, raster fallback
Lottie JSON (animated onboarding/empty- state)	assets/ illustrations/ lottie/*.json	Flutter (lottie), Web (lottie-web) — D- DEL-3

D-DEL-3 (open). Whether onboarding/empty-state illustrations are **static** (SVG/PNG only) or **animated** (Lottie). Lottie adds a dependency but gives one cross-platform animated source (Flutter + Web + native). UNVERIFIED — decided at the Volume-10 motion review with [TIM §6]; static SVG/PNG is the guaranteed floor, Lottie the enhancement. Either way, every illustration ships light+dark.

6.5 Pull command

```
( cd helix_design && pnpm assets:brand )    # logo + app-icon
      matrices + illustration rasters
# emitted into dist/{logo,app-icon,illustrations}/** and assets/
  logo/<platform>/**
```

7. Components — forms & delivery

7.1 Source (tracked)

- **Component specs** — components/specs/*.md, one per component (anatomy / states / variants / ally / light+dark), the **platform-neutral** contract [CMP].
- **Reference implementations** — components/reference/**, per-platform reference impls where a component is platform-native.

7.2 The deliverable forms

Form	What it is	Consuming platform	Where it lives
Flutter component package	the <code>helix_design</code> Dart package that re-exports the tokens AND ships the reference Flutter widgets (<code>ConnectButton</code> , <code>StatusChip</code> , <code>ExitPicker</code> , ...)	<code>helix-ui</code> Flutter (Client/ Console/ Connector)	<code>packages/flutter/lib/</code> [OV §4]
Design-source / authoring form	the <code>OpenDesign</code> <code>components.html</code> + the <code>DESIGN.md</code> component section (§9, §15) — the designer-facing component definitions	<code>designers / OpenDesign</code>	<code>opendesign/helix/components.html</code>
Per-platform component notes	for surfaces the Flutter package can't reach (native shims), the spec doc states how to compose the same component from the native token form (Swift/Compose/ArkTS/C-Qt)	<code>native-shim</code> authors	<code>components/specs/*.md</code> per-platform notes section + [PLAT]
Component tokens	the <code>tokens/component/*.json</code> per-widget tokens every form reads	all	<code>tokens/component/</code> [DT §8]

Why the component deliverable is spec-first, package-second. The three HelixVPN apps are one Flutter codebase [04_CLIENT §5], so the **Flutter package** is the primary component delivery — a widget imported directly. The native-shim surfaces (iOS NE config UI, Android tile, HarmonyOS ability, Aurora Qt) are tiny and platform-native; they don't import Dart, so their delivery is the **spec + the native token form** (R1/R2/R3 per-platform), from which the small native UI is composed. This is why R6 ships BOTH a package (Flutter) AND specs+notes (native): no surface is left to guess a component's anatomy.

7.3 Pull command

```
# Flutter apps depend on the package directly (path/replace),  
  §14.2:  
#   dependency_overrides: helix_design: { path: ../helix_design/  
    packages/flutter }  
# native-shim authors read components/specs/*.md + the per-  
  platform token form (§2.2)
```

8. Motion — forms & delivery

8.1 Source (tracked)

tokens/primitive/motion.json + tokens/semantic/motion.json — the duration scale (fast120/base220/slow360), the standard easings (cubic-bezier sets), and the named semantic motions (connectPulse, statusTransition, sheetEnter, ...) [TIM §6–§7], with the prefers-reduced-motion zero-duration rule [TIM §8.1].

8.2 Emitted forms

Form	Where	Consuming platform
CSS motion custom properties (--hx-motion-*--dur, *--ease) + a prefers-reduced-motion block	dist/css/helix.css [EXP §4.1]	Web
Dart Duration + Curve tokens	Dart package	Flutter
Swift Double seconds + Animation accessors	HelixTokens.swift	iOS/macOS
Compose Int ms + Easing	HelixTokens.kt	Android
ArkTS numeric ms	helix_tokens.ets	HarmonyOS
Qt int ms	helix_tokens.h	Aurora
Motion reference specs	docs/v10-design/typography-iconography-motion.md §6–§8 (rendered)	designers + devs

8.3 Pull command

Motion tokens travel with the token export (§2.3); the reduced-motion guard is emitted per platform (CSS @media, Flutter MediaQuery.disableAnimations, etc.) so the accessibility contract is honored everywhere [TIM §8.1].

9. Design source / handoff — forms & delivery

9.1 Source (tracked)

The **OpenDesign-native design system** under helix_design/opendesign/helix/ [OV §10.3] — the authoring + handoff artifacts:

Artifact	What it is	Audience
DESIGN.md	the 9-section design-system spec (visual theme, color, type, spacing,	designers + devs

Artifact	What it is	Audience
	layout, components, motion, voice/ tone, anti-patterns) [OD §3.3]	
tokens.css	compiled CSS custom properties (light+dark) — the OpenDesign- consumed form [OD §4]	OpenDesign + Web
components.html	rendered component gallery	designers + reviewers
manifest.json	OpenDesign design-system manifest (schemaVersion/id/name/files) [OD §3.3]	OpenDesign tooling
assets/ fonts/ preview/ source/	the OpenDesign asset/preview subtree	OpenDesign
Redline / handoff specs	per-screen redlines + spacing/ measure callouts (rendered with the docs §10)	devs implementing a screen

9.2 How a designer / dev pulls the handoff

```
# designer: open the OpenDesign design system (desktop / od CLI /
MCP) §15
od open helix_design/opendesign/helix           # UNVERIFIED exact
CLI verb (U-OD §15)
# dev: read the rendered DESIGN.md + components.html + redlines:
open helix_design/opendesign/helix/DESIGN.html # §11.4.65
rendered sibling
open helix_design/opendesign/helix/components.html
```

The handoff is **self-contained in the submodule** — a designer or dev pulls the one submodule and has the authoring source, the rendered gallery, the redlines, and the tokens, all in sync (§11.4.65). No external design-tool URL is the source of truth (that would be a §11.4.13 sink-side violation).

9.3 Pull command

Travels with the submodule clone; rendered .html/.pdf siblings refresh via the docs export (§10, §11.4.65).

10. Docs — forms & delivery (§11.4.65 / §11.4.168)

10.1 Source (tracked)

Every Volume-10 nano-detail document under helix_design/docs/v10-design/*.*md* (this manifest included) — so the design system is **self-documenting** and a future project that pulls helix_design gets the full spec set [OV §1.2(8)].

10.2 Emitted forms

Form	Generated by	Constitution clause
.html sibling per .md	sync_all_markdown_exports.sh (pandoc)	§11.4.65
.pdf sibling per .md	weasyprint from the HTML	§11.4.65
.docx sibling (feature-status class only)	the §11.4.153 export	§11.4.153
visual-validated rendered docs	the §11.4.168 check (pdftotext no-raw-source + pdfimages diagrams-rasterised + swatch-block-present)	§11.4.168 [EXP §6]

10.3 Pull command

```
( cd helix_design && bash scripts/testing/
  sync_all_markdown_exports.sh )
# every docs/v10-design/*.md → .html + .pdf (+ .docx where in
  scope), §11.4.168-validated
```

11. The master deliverables matrix

The single delivery view: **resource** × **form** × **consuming platform** × **where it lives in the submodule** × **pull command**. Every row is a concrete, directly-incorporable artifact. (R# = the §1 resource class; light+dark applies to every row per DS-I3.)

R#	Resource → form	Consuming platform(s)	Submodule path	Pull command
R1	tokens → JSON bundle	tooling, round-trip	dist/json/tokens.json	pnpm export
R1	tokens → CSS vars	Web (Console)	dist/css/helix.css	pnpm export
R1	tokens → Dart ThemeExtension	Flutter (Client/ Console/ Connector)	packages/flutter/lib/src/helix_tokens.dart	pub path/rep
R1	tokens → SwiftUI tokens	iOS, macOS shims	dist/swift/HelixTokens.swift	pnpm export target
R1	tokens → Compose Kt	Android shims	dist/compose/HelixTokens.kt	pnpm export module
R1	tokens → ArkTS resources	HarmonyOS	dist/arkts/helix_tokens.ets + resources/{base,dark}	pnpm export
R1	tokens → C/Qt header + QML	Aurora	dist/cqt/{helix_tokens.h,Theme.qml}	pnpm export

R#	Resource → form	Consuming platform(s)	Submodule path	Pull command
R2	color → light+dark palettes (tokens)	all	tokens/semantic/color. {light,dark}.json	(source)
R2	color → Apple colorsets	iOS, macOS	dist/swift/HelixColors.xcassets	pnpm export
R2	color → Android color res	Android	dist/compose/HelixTokens.kt (+ values-night)	pnpm export
R2	color → HarmonyOS color res	HarmonyOS	dist/arkts/resources/{base,dark}/ element/color.json	pnpm export
R2	color → connection-state palette	all (Client)	presets/helix/connection_state.json → every form	pnpm export
R3	type → font files + license	all	assets/fonts/<face>/*.{ttf,woff2} + OFL.txt	release bundle
R3	type → type-scale tokens	all	tokens/{primitive,semantic}/ type.json	pnpm export
R3	type → per-platform text styles	each	inside each dist/** token form	pnpm export
R4	icons → SVG set	Web, Flutter	assets/icons/*.svg	(source)
R4	icons → icon font + codepoint map	Flutter, Web	dist/icons/helix_icons.{ttf,woff2} + .dart	pnpm assets
R4	icons → Apple imageset (PDF)	iOS, macOS	assets/icons/apple/ HelixIcons.xcassets	pnpm assets
R4	icons → Android vector drawables	Android	assets/icons/android/drawable/ ic_helix_*.xml	pnpm assets
R4	icons → HarmonyOS media	HarmonyOS	assets/icons/harmony/resources/base/ media/*.svg	pnpm assets
R4	icons → Qt resource SVG	Aurora	assets/icons/qt/icons.qrc	pnpm assets
R5	brand → logo (SVG+raster, light+dark)	all	assets/logo/*.svg + dist/logo/png/*	pnpm assets
R5	brand → iOS appiconset	iOS	dist/app-icon/ios/AppIcon.appiconset	pnpm assets
R5	brand → macOS icns	macOS	dist/app-icon/macos/	pnpm assets
R5	brand → Android adaptive icon	Android	dist/app-icon/android/	pnpm assets
R5		Windows	dist/app-icon/windows/	pnpm assets

R#	Resource → form	Consuming platform(s)	Submodule path	Pull command
	brand → Windows ico + tiles			
R5	brand → Linux hicolor png	Linux	dist/app-icon/linux/	pnpm assets
R5	brand → Web PWA icons	Web	dist/app-icon/web/	pnpm assets
R5	brand → HarmonyOS layered icon UNVERIFIED	HarmonyOS	dist/app-icon/harmony/	pnpm assets
R5	brand → Aurora app-icon set UNVERIFIED	Aurora	dist/app-icon/aurora/	pnpm assets
R5	brand → illustration + empty-state	all	assets/illustrations/*.svg (+ Lottie DEL-3)	pnpm assets
R6	components → Flutter package	Flutter (3 apps)	packages/flutter/lib/	pub path/rep
R6	components → design-source gallery	designers	opendesign/helix/components.html	submodule cl
R6	components → per-platform notes	native shims	components/specs/*.md + [PLAT]	submodule cl
R6	components → component tokens	all	tokens/component/*.json	pnpm export
R7	motion → token bundle	all	tokens/{primitive,semantic}/motion.json → every form	pnpm export
R7	motion → reference specs	designers + devs	docs/v10-design/typography-iconography-motion.md	docs export
R8	handoff → OpenDesign DESIGN.md + tokens.css	designers + Web	opendesign/helix/{DESIGN.md,tokens.css,manifest.json}	submodule cl
R8	handoff → redline specs	devs	rendered with docs (§10)	docs export
R9	docs → this spec set	everyone	docs/v10-design/*.md	submodule cl
R9	docs → rendered html/pdf(docx)	everyone	docs/v10-design/*.{html,pdf,docx}	sync_all_ma

12. Deliverables → packaging → consumption (diagram)

flowchart TB

```
    subgraph SRC["SOURCE (tracked in helix_design)"]
        tk["R1 tokens/**"]
        cl["R2 color tokens + presets"]
        ty["R3 type.json + fonts"]
        ic["R4 icons/*.svg"]
        br["R5 logo/app-icon/illustration source"]
        cp["R6 component specs + reference"]
        mo["R7 motion.json"]
        hd["R8 opendesign/helix/**"]
        dc["R9 docs/v10-design/*.md"]
    end
    subgraph PKG["PACKAGING (regenerate)"]
        exp["pnpm export (tokens/color/type/motion → 7 forms)"]
        asi["pnpm assets:icons (SVG → icon-font + platform asset forms)"]
        asb["pnpm assets:brand (logo/app-icon matrices/illustration rasters)"]
        mds["sync_all_markdown_exports (docs → html/pdf/docx, $11.4.168)"]
        rel["$13 release pipeline → pub package + dist tarball (tagged)"]
    end
    subgraph CONS["CONSUMPTION (direct incorporation)"]
        flutter["Flutter helix-ui → Client / Console / Connector<br/>(Dart pkg + icon font + fonts)"]
        web["Console Web (helix.css + PWA icons + woff2)"]
        ios["iOS/macOS NE shim (Swift colorsets + appiconset/icns + imageset)"]
        and["Android tile/notif (Compose + adaptive icon + drawables)"]
        win["Windows (Flutter + ico/tiles)"]
        lin["Linux (Flutter + hicolor png)"]
        hm["HarmonyOS ability (ArkTS resources + media + layered icon)"]
        au["Aurora Qt (C/Qt header+QML + qrc icons + app-icon)"]
        fut["ANY future Helix app (drops presets/&lt;x&gt;/ - inherits all forms)"]
    end
    tk & cl & ty & mo --> exp
    ic --> asi
    br --> asb
    dc & hd & cp --> mds
    exp & asi & asb & mds --> rel
    flutter --> rel
    web --> rel
    ios --> rel
    and --> rel
    win --> rel
    lin --> rel
    hm --> rel
    au --> rel
    fut --> rel
```

13. The versioning & release model for the asset corpus

The asset corpus versions **with** the design system (one semver per `helix_design` tag [OV §8]) — assets are not versioned independently of tokens, because a logo recolor, an icon addition, and a token change are all "design-system change". The release model adds the **asset-corpus-specific** rules on top of [OV §8]:

Change class	Bump	Asset examples
MAJOR	breaking asset rename/removal, app-icon shape change, dropped component	rename <code>ic_helix_shield</code> → <code>ic_helix_lock</code> ; drop an illustration a screen imports; change the app-icon master silhouette
MINOR	additive — new icon, new illustration, new app-icon platform, new font weight, new component	add <code>ic_helix_relay</code> ; add the Aurora app-icon matrix; add an empty-state illustration
PATCH	value-only — recolor within contrast, re-export an asset, fix a dark variant, license-text update	nudge the logo color; re-rasterise an icon; commit a corrected <code>OFL.txt</code>

Release mechanics (compose [OV §8] + §13-specific):

1. **Source is tracked; raster/derived asset forms are gitignored build-derivatives** (§11.4.30/§11.4.77) — regenerated by `pnpm assets:*`; the §11.4.77 regeneration mechanism is declared per `.gitignore-meta/<form>.yaml`. The icon SVG source, illustration source, logo source, font files, and the checked-in Flutter-package Dart are tracked; the per-platform raster matrices are not (they are regenerated from the masters).
 2. **Each tag publishes a pinnable bundle** — `helix_design-<semver>-dist.tar.zst` (all `dist/**` forms + the generated icon font + the app-icon matrices) so a consumer pulls the assets without the Node toolchain (D-DESIGN-2 [OV §4] rationale generalised to assets).
`scripts/fetch-dist.sh <semver>` unpacks it.
 3. **A consuming app pins a tag**, bumps the pointer deliberately (§11.4.26 step 7); a pointer bump that changes any asset triggers the app's **visual-regression suite** (DS-I5 [OV §12]) — a logo recolor or icon change must pass golden screenshots before the app ships it.
 4. **Release tags follow §11.4.151** — `<PREFIX>-helix_design-<semver>` in a HelixVPN wave, plain `helix_design-<semver>` standalone. **No force-push, ever** (§11.4.113) — every publish is a merge-onto-latest-main fast-forward to all mirrors.
 5. **Asset provenance is captured** — the release bundle carries `.export-manifest.json` (every emitted form + its content hash + the source-commit it came from [EXP §6.1]) so a consumer can prove which source produced the asset it ships (§11.4.108 SOURCE→ARTIFACT).
-

14. The direct-incorporation recipe per app

14.1 The common five steps (every app, same model — [OV §9.1])

```
# 1. Add the decoupled submodule at the FLAT parent-root path
    (§11.4.28(C)/.29):
git submodule add git@github.com:vasic-digital/helix_design.git
    helix_design

# 2. Install upstream push mirrors (§11.4.36):
( cd helix_design && install_upstreams )

# 3. Brand preset: HelixVPN apps use presets/helix/ (default – no
    flag);
#   a future app drops presets/<app>/ (§14.5).

# 4. Generate the forms the app needs – OR pull the pinned release
    bundle:
( cd helix_design && pnpm install && pnpm export && pnpm
    assets:icons && pnpm assets:brand )
#   OR (no Node toolchain): helix_design/scripts/fetch-dist.sh
    <semver>

# 5. Wire the generated form(s) into the app build (per-app,
    §14.2–§14.5).
```

14.2 Client (end-user VPN app, 8 platforms)

The Client is one Flutter codebase + per-platform native shims [04_CLIENT §5], so it consumes the **Dart package** for the app body and the **native forms** for the shim surfaces:

```
# helix-ui (Client) pubspec.yaml – primary delivery: the Flutter
    package
dependencies:
  helix_design:
    path: ../helix_design/packages/flutter      # direct import,
    no hand-copy

// app entry – apply the generated themes (light+dark) directly:
import 'package:helix_design/helix_design.dart';
MaterialApp(theme: helixLight(), darkTheme: helixDark(), /* ... */);
// fonts come from packages/flutter/pubspec.yaml fonts: (§4.3)
// icons: Icon(HelixIcons.shieldConnected)           (§5.2)
```

Client platform	Form(s) incorporated	Where
iOS / macOS	Dart package (app) + HelixTokens.swift + HelixColors.xcassets + AppIcon.appiconset/.icns + icon imageset (NE config UI, widget)	Flutter target + NE- extension target
Android		

Client platform	Form(s) incorporated	Where
	Dart package (app) + <code>HelixTokens.kt</code> + adaptive icon + vector drawables (quick-settings tile, notification)	Flutter target + native module
Windows / Linux	Dart package + <code>.ico</code> /hicolor app icon	Flutter target
HarmonyOS	Dart package (if Flutter-on-Harmony) or ArkTS forms + media + layered icon (native ability) UNVERIFIED	per [PLAT]
Aurora	Dart package (if Flutter-on-Aurora) or C/Qt forms + qrc icons + app-icon	per [PLAT]
Web (if the Client ships a web build)	<code>helix.css</code> + PWA icons + <code>woff2</code>	web build

14.3 Console (admin web app)

```
# Console is a Flutter web build → Dart package (primary) +
  helix.css for web chrome:
# pubspec.yaml: helix_design: { path: ../helix_design/packages/
  flutter }
# web/index.html: <link rel="stylesheet" href="dist/css/
  helix.css">
# web/ PWA icons from dist/app-icon/web/, fonts from dist/css/
  fonts/*.woff2
```

The Console renders the **same** palette/type/components as the Client because both read the one design source — the admin UI is visibly part of the same product family with zero extra design work (§2.1 reuse payoff).

14.4 Connector (appliance config UI)

```
# Connector is the helix-ui Flutter codebase in its connector
  flavor [04_CLIENT $5]:
dependencies:
  helix_design: { path: ../helix_design/packages/flutter }
# applies helixLight()/helixDark(); uses the connector-relevant
  subset of components
# (no consumer-only screens) gated by the app's capability flags –
  design forms identical.
```

14.5 A generic FUTURE Helix-ecosystem app

```
# Identical five steps; step 3 drops a NEW preset instead of using
  presets/helix/:
mkdir -p helix_design/presets/acme
cat > helix_design/presets/acme/brand.json <<'JSON'
{ "brand": { "seed": "#7C3AED", "accent": "#F59E0B",
  "fontFamily": { "sans": "Inter", "mono": "JetBrains
    Mono" },
  "productName": "Acme" } }
```

```
JSON
( cd helix_design && pnpm export --preset presets/acme/ ) # →
  every form in Acme's palette
# inherits ALL nine resource classes' machinery with ZERO HelixVPN
  coupling (DS-I1).
```

The future app gets the entire deliverable set — tokens, color, type, icons, illustration scaffold, components, motion, handoff, docs — for free; it supplies only its own brand values + its own logo/illustration source. This is the §11.4.74 reuse the decoupling exists to make real [OV §2.1].

15. How OpenDesign authoring artifacts round-trip into the deliverables

OpenDesign (§11.4.162, mandatory authoring/refinement [OD]) is where designers **author and refine** the system; the deliverables are **derived from** the authored source, and refinements made in OpenDesign are reconciled **back** into the token source so every derived form follows (DS-I6):

```
sequenceDiagram
    participant D as Designer (OpenDesign desktop / od CLI / MCP)
    participant ODD as opendesign/helix/ (DESIGN.md + tokens.css + components.html)
    participant J as tokens/** (JSON source of truth)
    participant E as exporters (pnpm export / assets)
    participant DEL as deliverables (dist/** + asset matrices + docs)

    D->>ODD: author / refine the HelixVPN design system
    ODD->>J: css→json reconcile (refinement diff, same-$type) [EXP §7]
    J->>E: pnpm export + pnpm assets:* (regenerate ALL forms)
    E->>DEL: dist/** (7 token forms) + icon font + app-icon matrices + rendered docs
    J->>E: export/targets/css.ts → opendesign/helix/tokens.css (round-trip back)
    E->>ODD: tokens.css refreshed (OpenDesign previews the authored system)
    DEL->>DEL: DS-DRIFT + visual-regression + §11.4.168 gates (§16) before publish
```

Key facts (web-verified [OD], honest boundaries stated, §11.4.6):

1. **OpenDesign authors the design system**; it owns DESIGN.md + tokens.css + components.html [OD §3.3]. The **deliverable token forms** (Dart/Swift/Compose/ ArkTS/C-Qt) are **helix_design's own exporters** — OpenDesign does **not** emit them [OD §1.2] — so the round-trip touches only the verified tokens.css surface, never an unverified OpenDesign API [EXP §7.2].
2. **JSON is the source of truth (D-DESIGN-3 lean (b) [OV §10.2])**. tokens.css is a generated export target; designer refinements in OpenDesign reconcile back into tokens/** via the css→json reconciler, then **all** deliverable forms regenerate. A tokens.css edit that doesn't map to a known token path is surfaced to the operator, never silently merged (§11.4.6 [EXP §7.2]).

3. **Missing-pattern policy** — if OpenDesign lacks a deliverable pattern HelixVPN needs (a richer multi-theme token model, a new export form, a VPN-specific component archetype), the fix is an **upstream PR to nexu-io/open-design** (§11.4.74), recorded Catalogue-Check: extend nexu-io/open-design@<sha> — never a private fork [OV §10.4].

UNVERIFIED (U-OD-DEL). The exact OpenDesign CLI verbs (od open/od build) and whether OpenDesign honors the [data-theme=dark] tokens.css convention vs twin light/dark systems are [OD §5.2 U4] / [EXP §7 U-EXP-3] — confirmed against a live OpenDesign system in the refinement pass + pinned per §11.4.99 before the round-trip ships. Not asserted as fact.

16. Asset-corpus quality gates owned here

Every deliverable form is anti-bluff-gated so "the asset shipped" means "the asset is correct, present, non-degenerate, and light+dark complete" — never a §11.4.38 stripped-asset bluff. These compose the [OV §12] / [EXP §5] gates with the asset-specific checks:

Gate	Asserts	Class
DS-DRIFT [EXP §5]	every dist/** token form byte-matches a fresh pnpm export (no hand-edit drift)	§11.4.12/.108
DS-ASSET-PRESENT	every asset a component/screen references resolves to a present, non-empty file in every platform form (a referenced-but-missing icon FAILs)	§11.4.38 installable-asset evidence
DS-ASSET-NON-DEGENERATE	each emitted raster/icon is non-blank (non-zero pixels, correct dimensions per the platform matrix)	§11.4.38 + §11.4.107(10) self-validated analyzer
DS-APP-ICON-MATRIX-COMPLETE	every platform's app-icon set has every required size/shape (no missing iOS size, no missing Android density)	§11.4.110 build-readiness
DS-LIGHT-DARK-COMPLETE [OV §12]	every themed token, color set, two-tone icon, illustration fill, logo lockup, and component spec defines BOTH light and dark	§11.4.162
DS-FONT-LICENSE-PRESENT	every bundled font face has its committed OFL.txt (or the per-platform reference is documented)	§11.4.10/.99 (D-DEL-1)
DS-CONTRAST [OV §12]	every on-X / X color pair clears WCAG AA in light AND dark	ally (static, captured-evidence)
DS-EXPORTED-DOC-VISUAL [EXP §6]	the rendered docs show no raw Mermaid/diagram source as body text + every swatch/diagram rasterised	§11.4.168

Honest boundary (DS-17 [OV §0.2]): these gates prove the **deliverables'** internal correctness + visual integrity + completeness. They do **not** prove a consuming app's feature works — that is the app's functional/UI-driven testing (Volumes 4/8). A green deliverable set is necessary, not sufficient, for a shipped UI.

17. Surfaced decisions

ID	Decision	Lean	Resolves at
D-DEL-1	Font licensing/ distribution: bundle font files (OFL permits) vs reference system/ Google fonts per platform	bundle (OFL-licensed Inter + JetBrains Mono; commit <code>OFL.txt</code> ; per- platform fallback always declared); exact OFL version + final face choice UNVERIFIED until §11.4.99 re-verify	Volume-10 assets review
D-DEL-2	Asset hosting: ship raster matrices as gitignored build- derivatives (regenerated from masters) + a per-tag release bundle vs commit every raster	gitignore rasters + publish <code>helix_design- <semver>- dist.tar.zst</code> ; track only masters + checked-in Flutter Dart (D- DESIGN-2)	Volume-10 review + §11.4.30 audit
D-DEL-3	Illustration form: static SVG/PNG only vs animated Lottie	static is the floor; Lottie the enhancement (one animated cross-platform source); decided with [TIM §6]	Volume-10 motion review
D-DEL-4	Icon delivery: icon- font + per-platform asset forms (this doc) vs SVG-only everywhere	icon-font for Flutter/Web (perf) + native asset forms for shims; SVG source is canonical	Volume-10 review
U-DEL-1 UNVERIFIED	Exact HarmonyOS layered-icon spec + Aurora app-icon size matrix	stated as intended matrices; pinned + re- verified per §11.4.99 before the app-icon generator ships	per [PLAT]
U-OD-DEL UNVERIFIED	OpenDesign CLI verbs + dark-mode tokens. <code>css</code> convention for the round-trip	confirmed against a live OpenDesign system + pinned per §11.4.99	refinement pass

Sources verified

- **The delivery model, the nine resource classes, the per-resource form sets, the master deliverables matrix (§11), the deliverables→packaging→consumption diagram (§12), the versioning/release model for the asset corpus (§13), the per-app direct-incorporation recipes (§14), and the asset-corpus gates (§16) — NO external source needed — original HelixVPN design work**, layered on each platform's documented asset conventions (Apple asset catalogs / .appiconset / .icns; Android adaptive icons + vector drawables + values-night; Windows .ico/ Store tiles; Linux hicolor theme; Web PWA manifest icons + @font-face/woff2; Flutter pubspec fonts + flutter_svg + icon-font; HarmonyOS resource qualifiers; Qt .qrc/QML) and the W3C-DTCG token + Style-Dictionary-class export pattern. The conventions are each framework's documented norms; the *delivery manifest* assembling them is HelixVPN's own design.
- **The submodule layout, the dist/**-is-a-build-derivative + checked-in Flutter-Dart (D-DESIGN-2) rule, the exporter set, the 8-platform target list, the OpenDesign relationship, and the verified fact that OpenDesign does NOT emit Dart/Swift/Compose/ArkTS/C-Qt** — final/v10-design/00-overview-and-submodule.md §0/§4/§6/§8/§9/§10/§12 + final/v10-design/token-export-pipeline.md §0/§4/§5/§6/§7 + final/v10-design/opendesign-foundation.md §0/§1.2/§3.3/§4/§5.2 (siblings, this wave, read **2026-06-25**). The "OpenDesign authors the system / helix_design owns the polyglot distribution" split + the round-trip mechanics are grounded there (web-verified 2026-06-25), not assumed.
- **The token model, color hexes, type metrics, icon grid, motion scale, connection- state palette, and component anatomy referenced in the form tables** — design-tokens.md, color-system.md, typography-iconography-motion.md, component-library.md, platform-adaptation.md (siblings, this wave) + final/v04-client/helix-ui-flutter.md (the helix_design Flutter package, the 5-variant core::TunnelStatus (wire) → 7-variant ffi::TunnelStatus (Dart-facing), the native-shim languages, the one-codebase/3-flavor app model) + final/SPECIFICATION.md (roles Client/Console/Connector, 8 platforms), this repo, read **2026-06-25**.
- **Font-license fact** — Inter and JetBrains Mono are distributed under the **SIL Open Font License 1.1**, which permits bundling/redistribution inside an application with the OFL text included and the font not sold standalone. This is the well-established OFL term; the exact OFL version + that these two faces are the final choice is **D-DEL-1 UNVERIFIED**, re-verified against the upstream font repositories per §11.4.99 before the assets ship — not asserted as a settled fact.
- **Constitution clauses** §11.4.6 (no-guessing), §11.4.10 (credentials/licenses), §11.4.12 (auto-generated docs sync), §11.4.26 (submodule pointer-bump), §11.4.28 (equal-codebase + decoupling + flat layout), §11.4.29 (snake_case), §11.4.30/ §11.4.77 (no versioned build derivatives + regeneration mechanism), §11.4.38 (installable-asset evidence), §11.4.65 (universal Markdown export), §11.4.74 (catalogue-first / extend upstream), §11.4.99 (latest-source verification), §11.4.107(10) (self-validated analyzer), §11.4.108 (SOURCE→ARTIFACT equality), §11.4.110 (build-readiness), §11.4.113 (no force-push), §11.4.151 (release-prefix naming), §11.4.162 (OpenDesign UI design-system mandate), §11.4.168 (exported-doc visual validation) — constitution submodule text embedded in this repo's constitution/CLAUDE.md, accessed **2026-06-25**.

- Items explicitly marked UNVERIFIED (D-DEL-1 exact OFL version/face choice, U-DEL-1 HarmonyOS/Aurora icon matrices, U-OD-DEL OpenDesign CLI/dark-mode convention, D-DEL-3 Lottie) are pending their named §11.4.99 verification pass per §11.4.6 — not asserted as fact.