

Data Model — full Postgres DDL + RLS

Data Model — full Postgres DDL + RLS

Revision: 1 Last modified: 2026-06-25T00:00:00Z

Master technical specification — Volume 3 (Control Plane, Go), nano-detail deepening of [02-control-plane.md §2](#). Scope: the **complete, runnable Postgres schema** that is the single source of truth for HelixVPN identity, topology and policy — every table, type, constraint, FK, index; the Row-Level Security (RLS) regime that enforces multi-tenant isolation at the database under a non-superuser role; the SET LOCAL per-tx pattern; goose/atlas migrations; sqlc typed queries; and the **provable absence** of any connection/traffic/flow table (no-logging by construction). This is a SPEC — it describes the implementation exactly; it does not build the product. Source evidence cited inline by id: [04_P1] HelixVPN-Phase1-MVP.md, [04_ARCH §N] HelixVPN-Architecture-Refined.md, [research-go_cp] the control-plane overview doc 02, [SYNTHESIS §N] the cross-document synthesis. Unproven assertions are marked UNVERIFIED per constitution §11.4.6.

0. Position, ownership & governing invariants

This document owns **helix-go/internal/store** and **helix-go/migrations** — the durable-state layer of the control plane. It is the authoritative, byte-level expansion of the abbreviated DDL in [research-go_cp §2]. It does **not** own the in-memory coordinator graph (volatile, doc 02 §6), the Redis event bus (ephemeral, doc 02 §5), the wire .proto (doc 02 §4 / doc 03), or the policy *compiler* (doc 02 §7 — but it owns the policies table the compiler reads/writes).


0.1 Invariants this layer must mechanically enforce

#	Invariant	Mechanism in THIS document	Source
C2	Postgres is the single source of truth; Redis is ephemeral.	All identity/topology/policy in the 11 tables below; no durable state elsewhere.	[04_P1], [SYNTHESIS §2]
C3	No-logging by construction — the schema holds no connection/traffic/packet/flow table.	§7 schema-lint gate + the exhaustive forbidden-shape allowlist.	[04_ARCH §7], [04_P1 §2], [SYNTHESIS §7]
C4	Default-deny, need-to-know.	policies.spec is the only grant source; no implicit visibility row exists.	[04_ARCH §3.4], [04_P1 §3]
C6	Device private keys never leave the device.	devices.wg_pubkey bytea stores only the 32-byte public key; no private-key column exists anywhere.	[04_P1 §6], [SYNTHESIS §7]
C8	Multi-tenant isolation enforced at the database via RLS under a non-superuser role — not merely WHERE.	§4 RLS (ENABLE + FORCE), §5 helix_app/helix_owner/helix_sys roles, §6 WithTenant.	[04_P1 §2.2]

0.2 Settled stack floor (this layer)

PostgreSQL 16 (row_security=on); pgx/v5 pool; sqlc (compile-checked typed queries); goose SQL migrations as the schema authority with atlas as the declarative drift/CI checker; extension pgcrypto for gen_random_uuid() (built-in to PG 13+ but declared explicitly). Containers booted on-demand for integration tests via the vasic-digital/containers submodule (§11.4.76) — never `ad-hoc docker run` [SYNTHESIS §8].

1. Entity-relationship overview



Ten tenant-scoped tables (every one carries `tenant_id` and gets identical RLS, §4). Two PostgreSQL enums (`user_role`, `device_kind`). `tenants` is the only non-tenant-scoped table — it is the tenant root; RLS on it would be self-referential, so it is governed by the `helix_sys` role (§5.3) instead, and is never reachable from a request-scoped `helix_app` connection except through its own row (§4.3).

2. Full DDL — migrations (goose, ordered)

The migration set below is the authoritative schema. Files live under `helix-go/migrations/` named `NNNN_<slug>.sql` and run as `helix_owner` (§5.1). Every file is reversible (`-- +goose Down`). `goose` statement boundaries (`-- +goose StatementBegin/End`) wrap any statement containing a semicolon-bearing body (functions, DDL blocks). Atlas (§8.2) re-derives the same schema declaratively and fails CI on drift.

2.1 0001_extensions_and_roles.sql

```
-- +goose Up
-- pgcrypto provides gen_random_uuid(); explicit so a fresh
-- cluster is reproducible (§11.4.77).
CREATE EXTENSION IF NOT EXISTS pgcrypto;

-- Three roles, least-privilege (C8). Created idempotently so re-
-- running the migration is safe.
-- helix_owner : owns the schema; runs migrations; NEVER used by
-- request handlers.
-- helix_app : request-scoped role; RLS APPLIES to it (non-
-- superuser, non-owner).
-- helix_sys : narrow system role for tenant-create + cross-
-- tenant ops; NOT a superuser.
-- +goose StatementBegin
DO $$
BEGIN
    IF NOT EXISTS (SELECT 1 FROM pg_roles WHERE rolname =
        'helix_app') THEN
        CREATE ROLE helix_app NOLOGIN;
    END IF;
    IF NOT EXISTS (SELECT 1 FROM pg_roles WHERE rolname =
        'helix_sys') THEN
        CREATE ROLE helix_sys NOLOGIN;
    END IF;
END$$;
-- +goose StatementEnd

-- +goose Down
DROP EXTENSION IF EXISTS pgcrypto;
-- Roles are NOT dropped on Down: they may own grants on other
-- DBs; dropping is an ops decision.
```

Note: helix_owner is the database/schema owner created at cluster provisioning (outside migrations, by helixvpncctl bootstrap), because a role cannot be the owner of the schema it is created inside. helix_app and helix_sys are created here. The LOGIN roles that helixd actually authenticates as (helix_app_login, helix_sys_login) are GRANTED membership in helix_app / helix_sys respectively (§5.2) and carry passwords managed per §11.4.10 — never in a migration, never git-tracked.

2.2 0002_enums.sql

```
-- +goose Up
CREATE TYPE user_role AS ENUM ('admin','operator','member');
CREATE TYPE device_kind AS ENUM ('client','connector');

-- +goose Down
DROP TYPE device_kind;
DROP TYPE user_role;
```

user_role ordering is semantic (admin > operator > member) — used by the RBAC middleware (doc 02 §8.1), not by SQL comparison (enums compare by declaration order, which here matches the privilege lattice; the application MUST NOT rely on that and instead maps explicitly).

2.3 0003_tenancy_identity.sql

```
-- +goose Up
-- ===== tenants (the tenancy root; NOT RLS-scoped – see
-- §4.3) =====
CREATE TABLE tenants (
  id          uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  name        text NOT NULL CHECK (length(name) BETWEEN 1 AND
    200),
  created_at  timestampz NOT NULL DEFAULT now()
);

-- ===== users =====
CREATE TABLE users (
  id          uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  tenant_id   uuid NOT NULL REFERENCES tenants(id) ON DELETE
    CASCADE,
  email        text,                      -- NULLABLE: anonymous
    device-token users store NO PII (C6)
  oidc_sub     text,                      -- NULLABLE: present
    only when SSO is used
  role         user_role NOT NULL DEFAULT 'member',
  created_at   timestampz NOT NULL DEFAULT now(),
  -- Partial UNIQUEs: two anonymous users (both NULL email) are
    allowed; two named users
  -- sharing an email within a tenant are not. A plain
    UNIQUE(tenant_id,email) would (in
  -- Postgres) permit many NULLs anyway, but the partial index
    documents intent and is index-lean.
  CONSTRAINT users_email_not_blank CHECK (email IS NULL OR
    length(email) > 0)
);
CREATE UNIQUE INDEX users_tenant_email_uq ON users (tenant_id,
  email) WHERE email IS NOT NULL;
CREATE UNIQUE INDEX users_tenant_oidcsub_uq ON users (tenant_id,
  oidc_sub) WHERE oidc_sub IS NOT NULL;

-- +goose Down
DROP TABLE users;
DROP TABLE tenants;
```

Refinement over [04_P1 §2.1], which used table-level UNIQUE (tenant_id, email): the partial unique indexes make the "many anonymous users, no PII" posture (C6) explicit and avoid relying on the NULL-distinctness subtlety of UNIQUE. Behaviourally compatible.

2.4 0004_devices.sql

```
-- +goose Up
-- ===== devices (clients AND connectors – one table, kind
-- discriminator) =====
CREATE TABLE devices (
  id          uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  tenant_id   uuid NOT NULL REFERENCES tenants(id) ON DELETE
    CASCADE,
  user_id     uuid REFERENCES users(id) ON DELETE SET NULL, --
    NULLABLE: anon device w/o user
  kind        device_kind NOT NULL,
  name        text NOT NULL CHECK (length(name) BETWEEN 1 AND
    200),
  wg_pubkey   bytea NOT NULL, -- EXACTLY 32 bytes,
    Curve25519 PUBLIC key only (C6)
  overlay_ip  inet NOT NULL,
    -- allocated from tenant ULA /48 (D4); see overlay_pools
  os          text, -- ios|android|linux|
    windows|macos|harmonyos|aurora (free text, validated app-
    side)
  enrolled_at timestampz NOT NULL DEFAULT now(),
  last_seen_at timestampz, -- COARSE presence
    (heartbeat-refreshed, NOT per-packet, C3)
  revoked_at  timestampz, -- NULL = active; non-
    NULL = revoked (soft, for audit)
  CONSTRAINT devices_wg_pubkey_len CHECK (octet_length(wg_pubkey)
    = 32),
  -- overlay_ip is stored as inet; enforce it is a single host
  -- (no /prefix) and IPv6 (ULA, D4).
  CONSTRAINT devices_overlay_is_host CHECK (masklen(overlay_ip) =
    128),
  CONSTRAINT devices_overlay_is_v6 CHECK (family(overlay_ip) =
    6),
  UNIQUE (tenant_id, wg_pubkey),
  UNIQUE (tenant_id, overlay_ip)
);
-- Hot lookups: by tenant (list), by pubkey within tenant (enroll
-- dedupe / cert resolve),
-- and active-only filtering for the coordinator hydrate.
CREATE INDEX devices_tenant_idx ON devices (tenant_id);
CREATE INDEX devices_tenant_active_idx ON devices (tenant_id)
  WHERE revoked_at IS NULL;

-- +goose Down
DROP TABLE devices;
```

Decisions captured in the constraints. `octet_length(wg_pubkey)=32` is the database-level proof of C6 (a 32-byte value is a Curve25519 public key; a private key is also 32 bytes, so the *length* alone does not distinguish them — the guarantee is procedural: Enroll only ever receives the device-generated public key, and there is no column anywhere to store a private key). The

masklen=128/family=6 checks make overlay_ip a single ULA host, never a subnet, never IPv4 — matching D4 (IPv6 ULA /48 per tenant) and preventing a malformed allocation from corrupting IPAM.

2.5 0005_connectors_prefixes.sql

```
-- +goose Up
-- A connector IS a device (kind='connector') with a 1:1 detail
  row. Inherits all device
-- machinery (enroll, cert, revoke); the asymmetry (advertises
  CIDs) lives below.
CREATE TABLE connectors (
  device_id  uuid PRIMARY KEY REFERENCES devices(id) ON DELETE
    CASCADE,
  tenant_id  uuid NOT NULL REFERENCES tenants(id) ON DELETE
    CASCADE,
  site_name  text NOT NULL CHECK (length(site_name) BETWEEN 1
    AND 200),
  site_id    int  NOT NULL,                -- per-tenant 4via6 site
    index (D4 §3.2); from overlay_pools.next_site_id
  CONSTRAINT connectors_site_id_range CHECK (site_id BETWEEN 1
    AND 65535),
  UNIQUE (tenant_id, site_id)
);

-- CIDs a connector advertises into the overlay. enabled=false
  soft-disables without delete.
CREATE TABLE advertised_prefixes (
  id          uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  tenant_id   uuid NOT NULL REFERENCES tenants(id) ON DELETE
    CASCADE,
  connector_id uuid NOT NULL REFERENCES connectors(device_id) ON
    DELETE CASCADE,
  cidr        cidr NOT NULL,                -- RFC1918 LAN prefix,
    e.g. 192.168.50.0/24
  enabled      boolean NOT NULL DEFAULT true,
  created_at   timestampz NOT NULL DEFAULT now(),
  -- The SAME connector must not advertise the identical CIDR
    twice; cross-connector overlap is
  -- ALLOWED (it is a real topology condition resolved by 4via6
    site disambiguation, D4) and is
  -- surfaced as route.conflict.detected (doc 02 §5.3), NOT
    blocked here.
  UNIQUE (tenant_id, connector_id, cidr)
);
CREATE INDEX advertised_prefixes_conn_idx ON
  advertised_prefixes (tenant_id, connector_id);
CREATE INDEX advertised_prefixes_enabled_idx ON
  advertised_prefixes (tenant_id) WHERE enabled;

-- +goose Down
DROP TABLE advertised_prefixes;
DROP TABLE connectors;
```

connectors.site_id is added here (it was implicit in [research-go_cp §3.2 "per-connector site-id"]; this document makes it a stored, uniquely-constrained column allocated from overlay_pools.next_site_id, §2.8). It is the index embedded in the 4via6 prefix fd7a:helix:<rand>:<site-id>::/96 so a colliding IPv4 LAN is deterministically addressable.

2.6 0006_groups.sql

```
-- +goose Up
CREATE TABLE groups (
  id          uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  tenant_id   uuid NOT NULL REFERENCES tenants(id) ON DELETE
              CASCADE,
  name        text NOT NULL CHECK (length(name) BETWEEN 1 AND
              200),
  created_at  timestamptz NOT NULL DEFAULT now(),
  UNIQUE (tenant_id, name)
);

-- group_members carries tenant_id REDUNDANTLY (vs the source's 2-
--   col PK) so RLS applies to it
-- directly – a refinement over [04_P1 §2.1] which left the join
--   table un-RLS'd. The composite
-- PK (group_id, device_id) is preserved; a CHECK ties the
--   redundant tenant_id to the parents
-- via FK (the FKs alone cannot assert all three agree, so see the
--   trigger in §4.4).
CREATE TABLE group_members (
  tenant_id   uuid NOT NULL REFERENCES tenants(id) ON DELETE
              CASCADE,
  group_id    uuid NOT NULL REFERENCES groups(id) ON DELETE
              CASCADE,
  device_id   uuid NOT NULL REFERENCES devices(id) ON DELETE
              CASCADE,
  PRIMARY KEY (group_id, device_id)
);
CREATE INDEX group_members_tenant_idx ON group_members
  (tenant_id);
CREATE INDEX group_members_device_idx
  ON group_members (tenant_id, device_id);

-- +goose Down
DROP TABLE group_members;
DROP TABLE groups;
```

2.7 0007_policies.sql

```
-- +goose Up
CREATE TABLE policies (
  id          uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  tenant_id   uuid NOT NULL REFERENCES tenants(id) ON DELETE
              CASCADE,
```



```

spec          jsonb NOT NULL,          -- the declarative ACL
            document (doc 02 §7.1)
version       bigint NOT NULL,         -- monotonic per tenant
            (allocated app-side, §3.4)
active        boolean NOT NULL DEFAULT false,
compiled_at   timestamptz,             -- set when this version
            is activated (compiled artifact valid)
created_at    timestamptz NOT NULL DEFAULT now(),
CONSTRAINT policies_version_positive CHECK (version > 0),
UNIQUE (tenant_id, version)
);
-- AT MOST ONE active policy per tenant. Instant rollback =
--   activate an older version in one tx
-- (deactivate-all then activate-N). The partial unique index
--   makes the flip atomic (doc 02 §7.4).
CREATE UNIQUE INDEX policies_one_active_per_tenant ON policies
    (tenant_id) WHERE active;

-- +goose Down
DROP TABLE policies;

```

2.8 0008_overlay_pools.sql

```

-- +goose Up
-- One row per tenant: the ULA /48 plus the two monotonic
--   allocators (host + 4via6 site).
CREATE TABLE overlay_pools (
    tenant_id    uuid PRIMARY KEY REFERENCES tenants(id) ON DELETE
        CASCADE,
    ula_prefix    cidr NOT NULL,
        -- fd7a:helix:<rand>::/48 (D4); generated at tenant create
    next_host     bigint NOT NULL DEFAULT 2,  -- ::1 reserved for
        the gateway; hosts start at ::2
    next_site_id  int NOT NULL DEFAULT 1,    -- per-connector
        4via6 site index allocator
    CONSTRAINT overlay_prefix_is_v6 CHECK (family(ula_prefix) = 6),
    CONSTRAINT overlay_prefix_is_48 CHECK (masklen(ula_prefix) =
        48),
    CONSTRAINT overlay_prefix_is_ula CHECK (ula_prefix <<
        'fc00::/7'), -- inside the ULA space
    CONSTRAINT overlay_next_host_ok CHECK (next_host BETWEEN 2 AND
        1152921504606846976),
    CONSTRAINT overlay_next_site_ok CHECK (next_site_id BETWEEN 1
        AND 65535)
);

-- +goose Down
DROP TABLE overlay_pools;

```

next_host and next_site_id are bumped with UPDATE ... RETURNING under a row lock so two concurrent enrollments/attachments never collide (§3.3, §6.3). The << 'fc00::/7' check is the database-level proof the allocated prefix is genuinely ULA (D4), not a routable address.

2.9 0009_device_certs.sql

```
-- +goose Up
-- Short-lived control-channel mTLS certs (≈24h). NO private key
--   stored – pki holds the CA key
-- out-of-band (KMS/offline); this table records issued cert
--   metadata + revocation state.
CREATE TABLE device_certs (
  id          uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  tenant_id   uuid NOT NULL REFERENCES tenants(id) ON DELETE
    CASCADE,
  device_id   uuid NOT NULL REFERENCES devices(id) ON DELETE
    CASCADE,
  serial      text NOT NULL,           -- cert serial; the
    lookup key from mTLS handshake (doc 02 §8.2)
  not_after   timestampz NOT NULL,
  revoked     boolean NOT NULL DEFAULT false,
  created_at  timestampz NOT NULL DEFAULT now(),
  UNIQUE (tenant_id, serial)
);
-- Resolve an active cert fast (authDevice path); revoked/expired
--   filtered in query (§3.7).
CREATE INDEX device_certs_active_idx ON device_certs (tenant_id,
  device_id) WHERE NOT revoked;
CREATE INDEX device_certs_serial_idx ON device_certs (tenant_id,
  serial) WHERE NOT revoked;

-- +goose Down
DROP TABLE device_certs;
```

2.10 0010_audit_events.sql

```
-- +goose Up
-- CONTROL actions only – NEVER traffic/flows/packets (C3). This
--   is the ONLY append log; it
-- records who did what to the control plane (revoke, policy
--   activate, enroll-token mint), never
-- anything about user data flows.
CREATE TABLE audit_events (
  id          bigint GENERATED ALWAYS AS IDENTITY PRIMARY KEY,
  tenant_id   uuid NOT NULL REFERENCES tenants(id) ON DELETE
    CASCADE,
  actor       text NOT NULL,           -- user uuid (as text) or
    the literal "system"
  action      text NOT NULL,           -- dotted verb, e.g.
    "device.revoke","policy.activate"
  target      text,                   -- the affected entity id
    (nullable)
  ts          timestampz NOT NULL DEFAULT now(),
  meta        jsonb,                  -- structured context;
    MUST NOT contain traffic data (lint §7)
  CONSTRAINT audit_action_shape CHECK (action ~ '^[a-z_]+\.[a-z_]+
    $')
);
```

```
CREATE INDEX audit_events_tenant_ts_idx ON audit_events
(tenant_id, ts DESC);
```

```
-- +goose Down
```

```
DROP TABLE audit_events;
```

2.11 Column-type rationale (nano-detail)

Column	Type	Why exactly this type
*.id (most)	uuid DEFAULT gen_random_uuid()	Tenant-opaque, non-enumerable PKs; safe to expose in URLs; no cross-tenant guessability.
audit_events.id	bigint GENERATED ALWAYS AS IDENTITY	Append-only ordered log wants a cheap monotonic key + ts DESC index; UUID would bloat the hot index.
devices.wg_pubkey	bytea (CHECK len=32)	Raw 32-byte Curve25519 key; bytea avoids base64 round-trips and stores the exact wire bytes (C6).
devices.overlay_ip	inet (CHECK /128, v6)	Native IPv6 host type; enables inet containment ops and a single-host guarantee (D4).
advertised_prefixes.cidr, overlay_pools.ula_prefix	cidr	Network-prefix type; <=> containment for conflict + ULA checks; rejects host bits set.
policies.spec, audit_events.meta	jsonb	Binary JSON: indexable,

Column	Type	Why exactly this type
*.created_at/ts/not_after/ last_seen_at	timestampz	dedup-keyed, validated; spec is the compiler input (doc 02 §7). Always UTC-anchored; never naive timestamp.
connectors.site_id, overlay_pools.next_site_id	int (CHECK 1..65535)	16-bit 4via6 site index fits the / 96→/48 site field; int for arithmetic headroom.
roles enum	user_role/ device_kind	Closed sets enforced at the type level; a typo'd kind is a write error, not a silent bug.

3. sqlc typed queries (the only SQL helixd runs)

All SQL lives in `helix-go/internal/store/queries/*.sql`; `sqlc generate` emits `internal/store/db/*.go` with a `Queries` struct whose methods take `pgx-compatible` args. Per wiring-rule R4 (doc 02 §1.2) no handler issues raw `db.Query` — a `golangci-lint` custom analyzer flags it. Every query below is parameterized; RLS (§4) is the tenant floor so most do **not** carry a `WHERE tenant_id = $1` — but the IPAM/cert hot paths add it for index selectivity (RLS predicate + explicit predicate both apply; the explicit one steers the planner).

3.1 sqlc.yaml

```
version: "2"
sql:
  - engine: postgresql
    schema: "migrations/" # the goose DDL IS the schema authority
    queries: "internal/store/queries/"
  gen:
    go:
      package: "db"
```

```

out:      "internal/store/db"
sql_package: "pgx/v5"
emit_pointers_for_null_types: true
overrides:
  - { db_type: "uuid",          go_type: "github.com/google/
    uuid.UUID" }
  - { db_type: "inet",         go_type: "net/netip.Addr" }
  - { db_type: "cidr",         go_type: "net/
    netip.Prefix" }
  - { db_type: "timestampz", go_type: "time.Time" }

```

3.2 Device queries — queries/devices.sql

```

-- name: InsertDevice :one
INSERT INTO devices (tenant_id, user_id, kind, name, wg_pubkey,
    overlay_ip, os)
VALUES ($1, $2, $3, $4, $5, $6, $7)
RETURNING *;

-- name: DevicesForTenant :many
SELECT * FROM devices WHERE revoked_at IS NULL ORDER BY
    enrolled_at;

-- name: DeviceByPubkey :one
SELECT * FROM devices WHERE wg_pubkey = $1;
-- RLS scopes to current tenant

-- name: TouchPresence :exec
UPDATE devices SET last_seen_at = now() WHERE id = $1; --
    COARSE; heartbeat only (C3)

-- name: RevokeDevice :exec
UPDATE devices SET revoked_at = now() WHERE id = $1; -- soft
    revoke; audit retains the row

```

3.3 IPAM allocation — queries/ipam.sql (concurrency-safe)

```

-- name: ProvisionOverlayPool :one
-- Called once at tenant create (within WithSystem). ula_prefix
    generated app-side (random /48).
INSERT INTO overlay_pools (tenant_id, ula_prefix) VALUES ($1, $2)
RETURNING *;

-- name: BumpOverlayNextHost :one
-- Atomic next-host hand-out. The UPDATE ... RETURNING takes a row
    lock; two concurrent
-- enrollments serialise on it and CANNOT receive the same host
    id. ::1 reserved (default 2).
UPDATE overlay_pools
    SET next_host = next_host + 1
    WHERE tenant_id = $1
RETURNING ula_prefix, next_host - 1 AS host_id; -- returns the
    value JUST consumed

```

```

-- name: BumpNextSiteId :one
-- Atomic per-connector 4via6 site index (D4). Same row-lock
  serialisation as host alloc.
UPDATE overlay_pools
  SET next_site_id = next_site_id + 1
  WHERE tenant_id = $1
RETURNING next_site_id - 1 AS site_id;

```

BumpOverlayNextHost returns `next_host - 1` (the value just consumed) so the Go layer computes `embedHost(ula_prefix.Addr().As16(), host_id)` (doc 02 §3.2) without a second round trip. Because the whole call runs inside `WithTenant` (§6) the `UPDATE` is inside the request transaction and the lock is held only until commit.

3.4 Policy queries — `queries/policies.sql`

```

-- name: NextPolicyVersion :one
-- Monotonic per tenant. COALESCE handles the first policy (no
  rows yet → version 1).
SELECT COALESCE(MAX(version), 0) + 1 AS next_version FROM
  policies;

-- name: InsertPolicy :one
INSERT INTO policies (tenant_id, spec, version) VALUES ($1, $2,
  $3) RETURNING *;

-- name: DeactivateAllPolicies :exec
UPDATE policies SET active = false WHERE active;
  -- RLS scopes to tenant

-- name: ActivatePolicyVersion :exec
UPDATE policies SET active = true, compiled_at = now() WHERE
  version = $1;

-- name: ActivePolicy :one
SELECT * FROM policies WHERE active;                                -- at most
  one (partial unique index)

-- name: PolicyByVersion :one
SELECT * FROM policies WHERE version = $1;

```

`NextPolicyVersion` + `InsertPolicy` run in one `WithTenant` tx; the `UNIQUE(tenant_id,version)` constraint is the race backstop — if two admins insert concurrently, one commit wins and the loser retries (the application catches the unique-violation and re-reads `NextPolicyVersion`).

3.5 Connector / prefix queries — queries/connectors.sql

```
-- name: InsertConnector :one
INSERT INTO connectors (device_id, tenant_id, site_name, site_id)
VALUES ($1, $2, $3, $4)
RETURNING *;

-- name: SetAdvertisedPrefix :one
INSERT INTO advertised_prefixes (tenant_id, connector_id, cidr)
VALUES ($1, $2, $3)
ON CONFLICT (tenant_id, connector_id, cidr) DO UPDATE SET enabled
= true
RETURNING *;

-- name: DisablePrefix :exec
UPDATE advertised_prefixes SET enabled = false WHERE id = $1;

-- name: EnabledPrefixesForTenant :many
SELECT * FROM advertised_prefixes WHERE enabled ORDER BY
connector_id, cidr;

-- name: ConflictingPrefixes :many
-- Two ENABLED prefixes from DIFFERENT connectors whose CIDRs
-- overlap → route.conflict (D4).
SELECT a.id, a.connector_id, a.cidr, b.id AS other_id,
       b.connector_id AS other_connector, b.cidr AS other_cidr
FROM advertised_prefixes a
JOIN advertised_prefixes b
ON a.connector_id <> b.connector_id
AND (a.cidr && b.cidr) -- inet/cidr overlap
operator
WHERE a.enabled AND b.enabled AND a.id < b.id;
```

3.6 Group queries — queries/groups.sql

```
-- name: InsertGroup :one
INSERT INTO groups (tenant_id, name) VALUES ($1, $2) RETURNING *;

-- name: AddGroupMember :exec
INSERT INTO group_members (tenant_id, group_id, device_id) VALUES
($1, $2, $3)
ON CONFLICT (group_id, device_id) DO NOTHING;

-- name: GroupMembersForTenant :many
SELECT gm.group_id, gm.device_id FROM group_members gm ORDER BY
gm.group_id;
```

3.7 Cert queries — queries/certs.sql

```
-- name: InsertDeviceCert :one
INSERT INTO device_certs (tenant_id, device_id, serial,
not_after) VALUES ($1, $2, $3, $4)
```

```
RETURNING *;
```

```
-- name: ActiveCertBySerial :one  
-- The authDevice hot path (doc 02 §8.2): mTLS serial → cert →  
   device, rejecting revoked/expired.
```

```
SELECT c.*, d.id AS d_id, d.revoked_at AS d_revoked  
FROM device_certs c JOIN devices d ON d.id = c.device_id  
WHERE c.serial = $1 AND NOT c.revoked AND c.not_after > now();
```

```
-- name: RevokeCertsForDevice :exec
```

```
UPDATE device_certs SET revoked = true WHERE device_id = $1;
```

3.8 Audit query — queries/audit.sql

```
-- name: AppendAudit :exec
```

```
INSERT INTO audit_events (tenant_id, actor, action, target, meta)  
VALUES ($1, $2, $3, $4, $5);
```

```
-- name: AuditTail :many
```

```
SELECT * FROM audit_events ORDER BY ts DESC LIMIT $1;
```

4. Row-Level Security — tenant isolation at the database (C8)

RLS is the **floor**, not the only line of defence. Even a handler that forgets `WHERE tenant_id` cannot read another tenant's rows, because Postgres evaluates the policy predicate on every row [04_P1 §2.2]. This is strictly stronger than `WHERE`-clause discipline: it survives a bug, a crafted query, and a SQL-injection that escapes the intended predicate.

4.1 The policy applied to every tenant-scoped table

```
-- +goose Up (migration 0011_rls.sql) – applied identically to  
   ALL TEN tenant-scoped tables:  
-- users, devices, connectors, advertised_prefixes, groups,  
   group_members,  
-- policies, overlay_pools, device_certs, audit_events  
-- (tenants is governed by helix_sys, NOT RLS – see §4.3)
```

```
ALTER TABLE devices ENABLE ROW LEVEL SECURITY;
```

```
ALTER TABLE devices FORCE ROW LEVEL SECURITY; -- applies EVEN  
   to the table owner (hardening, §4.2)
```

```
CREATE POLICY tenant_isolation ON devices
```

```
USING (tenant_id =  
current_setting('app.tenant_id')::uuid) -- read/update/  
delete visibility
```



```

WITH CHECK (tenant_id =
    current_setting('app.tenant_id')::uuid);
    -- insert/update row must match
-- ... identical block repeated for the other nine tables ...

```

The USING clause filters rows for SELECT/UPDATE/DELETE; the WITH CHECK clause rejects any INSERT/UPDATE that would write a row with a foreign tenant_id — so a handler cannot *plant* a row into another tenant either. A single CREATE POLICY with both clauses covers all four verbs.

4.2 Why FORCE (the hardening refinement over [04_P1 §2.2])

ENABLE ROW LEVEL SECURITY alone does **not** apply to the table *owner* — and migrations create the tables as helix_owner, which would therefore silently bypass RLS if helixd ever connected as the owner. FORCE ROW LEVEL SECURITY closes that gap: the policy applies even to the owner. Combined with the §5 role split (helixd never authenticates as the owner) this is belt-and-braces. Superusers and roles with BYPASSRLS still bypass — which is exactly why §5/§6.1 assert helix_app_login has neither attribute, checked at startup.

4.3 tenants is deliberately NOT RLS-scoped

tenants *is* the tenancy root: a row's own id is the tenant id, so a self-referential RLS predicate (id = current_setting('app.tenant_id')) would let a request-scoped connection read only its own tenant row — acceptable — but tenant *creation* (no app.tenant_id exists yet) must happen through helix_sys (§5.3). Decision: tenants has **no** RLS; the helix_app role is **not** granted INSERT/UPDATE/DELETE on it (only SELECT of its own row via a view-less direct grant scoped by a tenant_self policy below). This keeps tenant lifecycle in the narrow helix_sys lane.

```

-- tenants gets a minimal self-read policy so a request CAN read
   its own tenant name, nothing else:
ALTER TABLE tenants ENABLE ROW LEVEL SECURITY;
ALTER TABLE tenants FORCE ROW LEVEL SECURITY;
CREATE POLICY tenant_self ON tenants
    FOR SELECT USING (id = current_setting('app.tenant_id')::uuid);
-- No INSERT/UPDATE/DELETE policy for helix_app → those verbs are
   denied to it entirely.
-- helix_sys (§5.3) runs tenant create via a SECURITY DEFINER
   function or a BYPASSRLS-free grant.

```

current_setting('app.tenant_id') raises if the GUC is unset. For helix_app paths this is a *feature*: a query that runs without SET LOCAL app.tenant_id (a forgotten WithTenant) errors loudly rather than leaking. WithSystem (§6.4) sets the GUC to a sentinel for


the few cross-tenant ops. UNVERIFIED: exact error class/SQLSTATE of an unset-GUC cast under all PG16 minor versions — the integration test (§9) asserts the observed behaviour rather than assuming it.

4.4 Cross-table tenant coherence (group_members trigger)

group_members references groups and devices by id; the three tenant_ids must agree. FKs cannot express "all three tenants are equal", and RLS WITH CHECK only validates group_members's own tenant_id. A constraint trigger closes the gap:

```
-- +goose StatementBegin
CREATE OR REPLACE FUNCTION assert_group_member_tenant() RETURNS
    trigger AS $$
BEGIN
    IF (SELECT tenant_id FROM groups WHERE id = NEW.group_id) <>
        NEW.tenant_id
    OR (SELECT tenant_id FROM devices WHERE id = NEW.device_id) <>
        NEW.tenant_id THEN
        RAISE EXCEPTION 'group_member tenant mismatch (group=%
            device=% tenant=%)',
            NEW.group_id, NEW.device_id, NEW.tenant_id USING ERRCODE =
            'check_violation';
    END IF;
    RETURN NEW;
END$$ LANGUAGE plpgsql;
-- +goose StatementEnd
CREATE CONSTRAINT TRIGGER group_members_tenant_coherent
    AFTER INSERT OR UPDATE ON group_members
    FOR EACH ROW EXECUTE FUNCTION assert_group_member_tenant();
```

The same pattern applies to connectors, advertised_prefixes, and device_certs (each has a tenant_id that must equal its parent device/connector's tenant). One trigger per table; bodies are structurally identical. UNVERIFIED: whether the sub-SELECTs inside the trigger themselves run under RLS — they execute as the function definer's privileges only if SECURITY DEFINER; here they are SECURITY INVOKER (default) so they see the same RLS scope, which is correct because both rows must be in the current tenant anyway.



5. Database roles & least privilege

5.1 helix_owner — schema owner, migrations only

Owns the database, schema public, all tables, types, sequences, functions. Migrations (goose up) run as helix_owner. **helixd never authenticates as helix_owner**. Because FORCE ROW LEVEL SECURITY is set, even helix_owner is RLS-bound on SELECT/etc., but helix_owner may carry BYPASSRLS for migration DDL convenience — it is never on a request path, so this is safe.

5.2 helix_app — the request-scoped role (RLS applies)


```
-- +goose Up (migration 0012_grants.sql)
-- helix_app is NOLOGIN; helixd logs in as helix_app_login (a
  LOGIN role member of helix_app).
GRANT USAGE ON SCHEMA public TO helix_app;
GRANT SELECT, INSERT, UPDATE, DELETE ON ALL TABLES IN SCHEMA
  public TO helix_app;
GRANT USAGE, SELECT ON ALL SEQUENCES IN SCHEMA public TO
  helix_app;
-- tenants: helix_app gets ONLY SELECT (tenant_self policy, §4.3);
  revoke write verbs explicitly.
REVOKE INSERT, UPDATE, DELETE ON tenants FROM helix_app;
-- Future tables inherit the grant via default privileges set by
  the owner:
ALTER DEFAULT PRIVILEGES IN SCHEMA public
  GRANT SELECT, INSERT, UPDATE, DELETE ON TABLES TO helix_app;

-- +goose Down
REVOKE ALL ON ALL TABLES IN SCHEMA public FROM helix_app;
```

helix_app_login (created out-of-band by helixvpncctl bootstrap, password per §11.4.10) carries **neither** SUPERUSER **nor** BYPASSRLS **nor** CREATEROLE — asserted at startup (§6.1).

5.3 helix_sys — narrow cross-tenant role

Used only by WithSystem (§6.4) for tenant create, overlay_pools provisioning at tenant create, and the handful of genuinely cross-tenant maintenance jobs. It is granted INSERT on tenants and overlay_pools and SELECT where needed; it is **not** a superuser and does **not** carry BYPASSRLS — instead WithSystem sets app.tenant_id to a per-operation sentinel and the few queries it runs are explicit and reviewed. Most of the system never touches it.



6. The SET LOCAL per-transaction pattern

6.1 Startup safety assertion (run once on boot, before serving)

```

// internal/store/safety.go
// MustVerifyAppRole aborts boot if helixd connected with a role
// that can bypass RLS.
func (s *Store) MustVerifyAppRole(ctx context.Context) error {
    var super, bypass bool
    if err := s.pool.QueryRow(ctx,

        `SELECT rolsuper, rolbypassrls FROM pg_roles WHERE rolname
        = current_user`,
    ).Scan(&super, &bypass); err != nil {
        return fmt.Errorf("role self-check: %w", err)
    }
    if super || bypass {
        return fmt.Errorf("FATAL: helixd must run as a non-
        superuser, non-BYPASSRLS role "+
            "(current_user has super=%v bypassrls=%v) – RLS (C8)
            would be defeated", super, bypass)
    }
    return nil
}

```

6.2 WithTenant — the only request-path DB entry (R4)

```

// internal/store/tenant.go
//
// WithTenant runs fn inside ONE transaction whose RLS scope is
// pinned to tenantID.
// set_config(name, value, is_local=true) == SET LOCAL: the GUC is
// transaction-scoped and

```

```

// CANNOT leak across pooled connections (it is reset on COMMIT/
// ROLLBACK). This is the load-
// bearing reason a connection-pool + RLS is safe together.
func (s *Store) WithTenant(ctx context.Context, tenantID
    uuid.UUID,
    fn func(q *db.Queries) error) error {

    tx, err := s.pool.BeginTx(ctx, pgx.TxOptions{}) // default
        isolation: READ COMMITTED
    if err != nil {
        return fmt.Errorf("begin tenant tx: %w", err)
    }
    defer func() { _ = tx.Rollback(ctx) }() // no-op
        after a successful Commit

    if _, err := tx.Exec(ctx,
        `SELECT set_config('app.tenant_id', $1, true)`,
        tenantID.String()); err != nil {
        return fmt.Errorf("pin tenant %s: %w", tenantID, err)
    }
    if err := fn(db.New(tx)); err != nil {
        return err // rollback
        via defer; tenant scope discarded
    }
    return tx.Commit(ctx)
}

```

6.3 Why SET LOCAL (not SET) is mandatory under pooling

A plain SET app.tenant_id = ... (session-scoped) on a pooled connection would persist after the connection returns to the pool — the **next** request reusing that connection would inherit a stale tenant scope, a catastrophic cross-tenant leak. SET LOCAL / set_config(..., true) binds the GUC to the transaction lifetime: it is automatically cleared on COMMIT or ROLLBACK, so the connection returns to the pool *clean*. This is the single most important correctness property of the layer and is asserted directly by a test (§9, concurrency/atomicity type) that interleaves two tenants on one pooled connection and proves no bleed.

6.4 WithSystem — the narrow exception

```


// internal/store/system.go – tenant create + cross-tenant ops
// ONLY; uses the helix_sys role.
func (s *Store) WithSystem(ctx context.Context, fn func(q
    *db.Queries) error) error {
    tx, err := s.sysPool.BeginTx(ctx,
        pgx.TxOptions{}) // sysPool authenticates as
        helix_sys_login
    if err != nil { return err }
    defer func() { _ = tx.Rollback(ctx) }()
}

```

```

// sentinel scope: the all-zero UUID; tenants/overlay_pools
// writes here are reviewed & narrow.
if _, err := tx.Exec(ctx,
    `SELECT set_config('app.tenant_id', $1, true)`,
    uuid.Nil.String()); err != nil {
    return err
}
if err := fn(db.New(tx)); err != nil { return err }
return tx.Commit(ctx)
}

```



7. No-logging by construction — provable absence (C3)

The strongest privacy claim HelixVPN makes is mechanical, not promised: **there is no table, view, or column in which connection/traffic/flow/packet data could be stored.** The schema above contains identity, topology, and policy only. A pre-build gate proves it.

7.1 The forbidden-shape lint

```
// tools/schemalint/main.go – runs in the pre-build sweep
// (constitution §11.4.27 / §1.1 / §11.4.108).
// Parses every migrations/*.sql AND introspects the live schema
// (information_schema), then FAILS
// the build if any table/view/column matches a traffic-logging
// shape.
var forbiddenTables = regexp.MustCompile(
    `(?!i)\b(connections?|sessions?|flows?|traffic|packets?|netflow|
    bandwidth_samples?|dns_queries?|conn_log|access_log|
    flow_records?)\b`)
var forbiddenCols = regexp.MustCompile(
    `(?!i)\b(src_ip|dst_ip|dest_ip|source_ip|src_port|dst_port|
    dest_port|bytes_(in|out)|tx_bytes|rx_bytes|packet_count|
    payload|sni_host|query_name|dns_name)\b`)

// EXCEPTION ALLOWLIST – the ONLY ip/port-shaped identifiers
// permitted, each justified:
// devices.overlay_ip          (identity: the device's stable
//                             overlay address, not a flow)
// devices.wg_pubkey          (identity: the WG public key)
// advertised_prefixes.cidr    (topology: a connector-advertised
//                             LAN prefix)
// overlay_pools.ula_prefix    (topology: the tenant ULA /48)
// connectors.site_id          (topology: the 4via6 site index)
// The lint asserts these are the EXHAUSTIVE set of address-shaped
// columns; ANY other match FAILS.
```

7.2 The §1.1 paired mutation (proves the gate is not a bluff)


```
-- tools/schemalint/testdata/mutation_connections.sql – a
// deliberately-forbidden migration.
CREATE TABLE connections (          -- MUTATION: must make the lint
// FAIL
    id          bigint GENERATED ALWAYS AS IDENTITY PRIMARY KEY,
    src_ip      inet,                -- forbidden column shape
    dst_ip      inet,                -- forbidden column shape
    bytes_in    bigint,
    bytes_out    bigint
);
```

The meta-test asserts: with the mutation present the lint exits non-zero (FAIL); removed, it exits zero (PASS). This is the runtime signature (§11.4.108) that C3 is *live*, not merely documented — an analyzer that passes its golden-bad fixture is itself the bluff (§11.4.107(10)).

7.3 Audit is the only append log — and it is control-only

audit_events records *control actions* (device.revoke, policy.activate, enroll_token.mint) with an action ~ '^[a-z_]+\.[a-z_]+\$' shape check and a meta jsonb that the §7.1 lint also scans for forbidden keys — so even

the audit log cannot smuggle a `src_ip`. Coarse presence (`devices.last_seen_at`) is the only time-varying device field, and it is a single heartbeat-refreshed timestamp, never a per-packet or per-flow record.



8. Migration tooling — goose (authority) + atlas (drift gate)

8.1 goose — the schema authority

goose SQL migrations under `helix-go/migrations/` are the source of truth; `sqlc` reads them for type generation (§3.1). Apply with `goose -dir migrations postgres "$HELIX_DB_OWNER_URL" up` (authenticated as

helix_owner). Each file is up/down reversible. helixvpctl migrate wraps goose so operators never call it raw; it runs the §6.1 role self-check afterward against helix_app_login.

8.2 atlas — declarative drift detection (CI/pre-build, local-only per §11.4.156)

Atlas re-derives the expected schema from the goose-applied database and **fails the pre-build sweep on any drift** between migrations/ and a hand-edited live schema:

```
# atlas.hcl
env "local" {
  url      = getenv("HELIX_DB_OWNER_URL")
  dev      = "docker://postgres/16/helix_dev"  # ephemeral dev DB
  (containers submodule §11.4.76)
  migration { dir = "file://migrations" }
}
```

atlas migrate lint + atlas schema diff run in the local gate (no remote CI per §11.4.156). A declarative diff catching an unmigrated ALTER TABLE is the second mechanical guard (the first being goose's own version table) that the live schema equals the committed authority.

8.3 Migration ordering & the risk-descending rule (§11.4.132)

#	File	Why this order
0001	extensions + roles	nothing references tables yet; roles must exist before grants
0002	enums	referenced by tables
0003	tenants + users	tenancy root before anything FK-ing it
0004	devices	FKs tenants, users
0005	connectors + advertised_prefixes	FK devices
0006	groups + group_members	FK devices
0007	policies	FK tenants
0008	overlay_pools	FK tenants
0009	device_certs	FK devices
0010	audit_events	FK tenants
0011	RLS enable/force/policies + coherence triggers	tables must exist first; this is the correctness floor

#	File	Why this order
0012	grants + default privileges	last; references all tables

RLS (0011) lands as early as the tables permit — it is the irreversible correctness floor, validated first (§11.4.132 risk-descending: a tenant leak is the highest-severity failure in this layer).

9. Test points — mandatory comprehensive coverage (§11.4.169)

§11.4.169 mandates the CLOSED enumerated test-type set, each to as-close-to-100% as the domain permits, every PASS citing rock-solid captured physical evidence (§11.4.5/.69/.107), zero bluff; the only permitted absence is an honest §11.4.3 SKIP-with-reason. This is the per-type coverage map for the data-model layer.

Test type (§11.4.169)	Concrete data-model test point	Evidence captured
unit	embedHost overlay-IP composition is deterministic; NextPolicyVersion COALESCE returns 1 on empty; type overrides round-trip (netip.Addr [?] inet).	Go test logs + golden vectors.
integration (real PG via containers §11.4.76)	Full migrate (goose up 0001–0012), then enroll→advertise→policy insert→activate against a real Postgres 16 booted by the containers submodule.	Container boot log + query result snapshots.
integration — RLS isolation	Tenant A connection (helix_app_login, WithTenant(A)) executes SELECT * FROM devices and gets ZERO of tenant B's rows even with a crafted OR tenant_id = B; an INSERT of a B-tenant row is rejected by WITH CHECK. Run with FORCE RLS on.	Captured query output (0 rows) + the rejected-insert error.
e2e	helixvpctl bootstrap → create tenant (WithSystem) → enroll a device → read back via helix_app_login — the whole role/RLS/SET-LOCAL chain end to end.	CLI transcript + DB state diff.
	The integration suite re-runs -count=3, byte-identical PASS each	3× identical run hashes.

Test type (§11.4.169)	Concrete data-model test point	Evidence captured
full-automation (deterministic §11.4.50)	iteration; ephemeral DB torn down + rebooted per run.	
Challenges (challenges submodule §11.4.27(B))	A Challenge drives create- tenant→enroll→policy and asserts cross-tenant denial, scoring PASS only on captured 0-row evidence.	Challenge result.json + captured rows.
HelixQA (helix_qa submodule)	A store test bank: RLS, IPAM concurrency, schema-lint, migration up/down round-trip; run in an autonomous QA session.	HelixQA session report.
DDoS / load- flood	10k concurrent WithTenant enrollments against the pool; assert no connection exhaustion, no GUC bleed, bounded p99 insert latency.	Latency histogram + error count = 0.
security (§11.4.10 + security submodule)	Role self-check (MustVerifyAppRole) aborts boot under a superuser/ BYPASSRLS role; no credential in any migration or log; WITH CHECK blocks tenant-spoofing inserts.	Boot-abort log + grep- clean credential audit.
stress + chaos (§11.4.85)	Kill the DB mid-WithTenant (chaos): the tx rolls back, GUC clears, the pooled conn recovers clean; disk-full on audit_events append degrades, never corrupts.	Recovery trace + post- chaos RLS still intact.
concurrency / atomicity	Two tenants interleaved on ONE pooled connection prove SET LOCAL scoping (§6.3); BumpOverlayNextHost under N goroutines yields N distinct host ids (no double-alloc).	Distinct-id set assertion + interleave log.
race-condition / deadlock	–race build of the IPAM + pool paths; concurrent Activate flips never violate policies_one_active_per_tenant; no lock-order inversion between devices/ group_members triggers.	go test –race clean + unique- violation retry log.
memory	24h soak of repeated WithTenant cycles; process_resident_memory_bytes slope ≈ 0 (no pgx conn/GUC leak).	RSS time series slope.

Test type (§11.4.169)	Concrete data-model test point	Evidence captured
benchmarking / performance	EnabledPrefixesForTenant + ActiveCertBySerial index-only/partial-index plans verified via EXPLAIN; policy insert+activate p99 within the doc-02 §10.2 budget.	EXPLAIN (ANALYZE) output + bench numbers.

Four-layer enforcement (§11.4.4(b)): pre-build (schema-lint §7, atlas drift §8.2, sqlc compile), post-build (migrate up/down on a real container), runtime-on-clean-target (RLS denial proven on a freshly-migrated DB, §11.4.108/.139), paired §1.1 mutations (§7.2 connections-table; an RLS-policy strip that must make the isolation test FAIL; a FORCE→ENABLE-only downgrade that must let the owner read cross-tenant). Any genuinely-infeasible point is an honest §11.4.3 SKIP-with-reason, never a silent gap.

10. Edge cases & error taxonomy

Edge case	Behaviour	Where enforced
Query runs without WithTenant (forgotten scope)	current_setting('app.tenant_id')::uuid errors → query fails loud, no leak.	RLS predicate (§4.3)
Two concurrent enrollments	Row-locked BumpOverlayNextHost serialises; distinct host ids.	§3.3 / §6.3
Two admins insert a policy at once	UNIQUE(tenant_id,version) rejects the loser; app catches 23505, re-reads NextPolicyVersion, retries.	§2.7 / §3.4
Concurrent Activate of different versions	policies_one_active_per_tenant partial-unique makes the deactivate-all+activate flip atomic; second flip retries.	§2.7 / §3.4
Overlapping CIDRs from two connectors	NOT blocked — surfaced as route.conflict.detected; resolved by 4via6 site index (D4).	§3.5 ConflictingPrefixes
Anonymous user (no email/SSO)	users.email/oidc_sub NULL; partial-unique indexes permit many anon users (C6).	§2.3

Edge case	Behaviour	Where enforced
Revoked device	revoked_at set (soft); excluded by devices_tenant_active_idx queries; certs revoked; open stream force-closed (doc 02 §8.2).	§3.2 / §3.7
group_member tenant mismatch	Constraint trigger raises check_violation.	§4.4
Malformed overlay IP (subnet or IPv4)	masklen=128/family=6 CHECK rejects the insert.	§2.4
Non-ULA pool prefix	ula_prefix << 'fc00::/7' CHECK rejects.	§2.8

Error taxonomy (Go side, mapped from PG SQLSTATE):

SQLSTATE	Go sentinel	Meaning	Handler action
23505 unique_violation	ErrConflict	dup pubkey / overlay_ip / policy version	409 (REST) / AlreadyExists (Connect); version path retries
23503 foreign_key_violation	ErrNotFound	parent tenant/ device gone	404 / NotFound
23514 check_violation	ErrInvalid	bad pubkey len / overlay shape / tenant-coherence trigger	400 / InvalidArgument
22023/unset GUC	ErrUnscoped	query ran outside WithTenant	500 + alert (a bug, never a client error)
P0001 raise_exception	ErrInvalid	coherence trigger message	400 / InvalidArgument
context deadline	ErrTimeout	tx exceeded budget	503 + retry-after

11. Cross-references & provenance

- **Coordinator** consumes the compiled view of policies + devices + advertised_prefixes (doc 02 §6); this layer only stores + serves the rows. **Compiler** (doc 02 §7) reads policies.spec, writes version/active/compiled_at.
- **Proto package** is helix.coordinator.v1 (unified across the set; doc 02 §4) — the EnrollResponse.overlay_ip string is the §2.4 devices.overlay_ip rendered, the Peer.allowed_ips are compiled from policies + advertised_prefixes.
- **Events** (doc 02 §5): every mutation here is followed (same logical unit of work) by an events.Publish (R3) — e.g. InsertDevice → device.enrolled, Activate → policy.compiled.
- **Constitution wiring**: containers submodule for on-demand test infra (§11.4.76); helix_qa + challenges for the §9 anti-bluff suites (§11.4.27/.5/.69/.107); §11.4.169 test-type ledger above; §11.4.10 credentials (role passwords never git-tracked); §11.4.156 local-only gates; §11.4.132 risk-descending migration order; §11.4.108/.139 runtime-signature (RLS proven on a clean DB).

Sources

[04_P1] HelixVPN-Phase1-MVP.md — control-plane DDL, RLS, role split, no-log lint, IPAM, policy versioning · [04_ARCH §3/§4/§7] HelixVPN-Architecture-Refined.md — ULA /48 + 4via6 (D4), no-logging, default-deny, generated clients · [research-go_cp §2/§3/§7] doc 02 control-plane overview (the Data Model section this document deepens) · [SYNTHESIS §2/§3/§7/§8/§9] cross-document synthesis (stack floor, D3/D4 decisions, privacy invariants, ecosystem + constitution bindings).