

Apple shim (iOS/macOS NEPacketTunnelProvider)

Apple shim (iOS/macOS NEPacketTunnelProvider)

Revision: 1 Last modified: 2026-06-25T00:00:00Z

Master technical specification — Volume 4 (Clients), nano-detail deep-dive. This document **deepens** the Apple row of the per-platform shim matrix [03-client §5.1] into an implementation-ready specification of the apps/access/{ios,macos} NEPacketTunnelProvider (Swift), the Apple impl of the TunnelPlatform contract [03-client §4], the Swift $\rightleftharpoons$ Rust helix-core staticlib FFI surface, the two-process status bridge, the **iOS Network-Extension memory ceiling** (the program's single hardest constraint, CI4), the size-first aarch64-apple-ios build, and macOS desktop-class differences. SPEC-ONLY: it describes **what to build**, not the shipping product. Sources cited inline by id — [03-client §N] = final/03-client-core-and-ui.md; [01-TT §N] = final/v02-data-plane/transport-trait.md; [01-ORCH §N] = final/v02-data-plane/orchestrator-and-state.md; [04_UI] = 04_VPN_CLD/HelixVPN-helix-ui-Flutter.md; [04_ARCH §N] = 04_VPN_CLD/HelixVPN-Architecture-Refined.md; [04_P0 §N] = 04_VPN_CLD/HelixVPN-Phase0-Spike.md; [research-ios_android] = v09-research/research-ios_android.md; [research-flutter_ffi] = the flutter_rust_bridge/UniFFI research digest; [SYN §N] = the cross-document synthesis. Any claim not grounded in that evidence base is tagged UNVERIFIED per constitution §11.4.6 — never fabricated.

Table of contents

- 0. Position, ownership, and invariants
- 1. The two-process reality (extension vs containing app)

- [2. The Apple TunnelPlatform implementation \(Dart side\)](#)
 - [3. NEPacketTunnelProvider \(Swift\) — full lifecycle](#)
 - [4. The Swift \$\rightleftharpoons\$ Rust FFI surface \(C ABI / UniFFI\)](#)
 - [5. The status bridge — core TunnelStatus \$\rightarrow\$ Dart EventChannel](#)
 - [6. The iOS NE memory ceiling — the hard constraint](#)
 - [7. Swift \$\rightleftharpoons\$ Rust staticlib build \(aarch64-apple-ios\)](#)
 - [8. macOS desktop-class differences](#)
 - [9. Lifecycle state machines](#)
 - [10. Error handling & edge cases](#)
 - [11. Memory / size / performance budgets](#)
 - [12. Test points — tied to the §11.4.169 test-type vocabulary](#)
 - [13. Cross-doc seams & surfaced decisions](#)
 - [Sources verified](#)
-

0. Position, ownership, and invariants

0.1 What this document owns

This document owns the **Apple TunnelPlatform shim** — the only Apple-specific code in the client stack [03-client §4 O-payoff]. Concretely:

1. The Dart `IosTunnelPlatform` / `MacosTunnelPlatform` impls of the `TunnelPlatform` contract [03-client §4] that marshal `startTunnel/stopTunnel/events()` onto `NETunnelProviderManager` (§2).
2. The `NEPacketTunnelProvider` subclass (`PacketTunnelProvider.swift`) that owns `packetFlow`, configures `NEPacketTunnelNetworkSettings`, and pumps packets through the in-extension Rust `helix-core` (§3) [03-client §5.1, 04_P0 §6].
3. The **Swift $\rightleftharpoons$ Rust C-ABI FFI surface** the extension links against (the `cbindgen` header over the `helix-ffi` crate; UniFFI is the typed alternative — decision D-CLIENT-3) (§4) [03-client §3, D-CLIENT-3].
4. The **two-process status bridge** that carries the core's `TunnelStatus` stream (emitted *inside the extension process*) back to the Flutter UI (running in the *containing app process*) as `PlatformTunnelEvents` (§5) [01-ORCH §4].
5. The **iOS NE memory-ceiling discipline** (G3 make-or-break) — measurement, budgets, and the documented fallback ladder (§6) [04_P0 §6.4, research-ios_android §1].
6. The **size-first aarch64-apple-ios staticlib build** of `helix-core` (§7) [research-ios_android §2].

0.2 What this document does NOT own

- The `helix-core` internals (WG crypto, `helix-transport` carriers, the orchestrator three-loop, the ladder) — owned by Volume 2 [01-TT, 01-ORCH]; this doc links the `staticlib` and drives its *exported* surface only [03-client §0].
- The shared Flutter UI (`ConnectButton`, `ExitPicker`, `helix_design`, `Riverpod`) — it is byte-identical across all platforms and ports for free; the shim does not [03-client §5 payoff, §7, §8].
- The FFI *surface contract* itself (`start/stop/status_stream/attach_tun/...` + the mirrored `TunnelStatus`) — fixed by [03-client §3]; this doc owns only the *Apple binding* of that surface (the `cbindgen/UniFFI` header + the in-extension call sites).
- The `TransportConfig` source (`WatchNetworkMap`) — doc 02; the shim hands the core a resolved session/map token and never invents an endpoint (I3) [01-TT §3.1].


0.3 Invariants this document inherits and tightens

#	Invariant	Source	Apple-specific tightening
CI1	The shim owns the OS tunnel lifecycle; <code>helix_core_ffi</code> owns logic + status.	[03-client §0.1 CI1]	On Apple the tunnel lives in a separate extension process ; the core runs <i>inside</i> that process, so the status stream must be bridged cross-process to the app (§5).
CI2	The UI is a pure function of the core status stream; never paints green on intent.	[03-client §0.1 CI2]	<code>NEVPNStatus</code> (coarse, app-side) is not the source of truth — the fine-grained <code>TunnelStatus</code> pushed from the extension is (§5.4).
CI4	The iOS NE memory ceiling is the hardest constraint and the reason the core is Rust.	[03-client §0.1 CI4, 04_ARCH §5.6]	Quantified, measured-on-device, fallback-laddered in §5.6; design budget is ~12–15 MB working set , NOT the 50 MiB headline (<code>research-ios_android</code> §1).
O1	<code>startTunnel</code> is idempotent + permission-aware; deny $\Rightarrow$ <code>permissionDenied</code> , no half-open TUN.	[03-client §4.1 O1]	Maps to <code>NETunnelProviderManager.loadAllFromPreferences + saveToPreferences + startVPNTunnel(options:)</code> ; permission denial surfaces as a specific <code>NEVPNError</code> (§2 §10).
O2			

#	Invariant	Source	Apple-specific tightening
	The shim hands the core a packet path; it never does crypto/obfuscation.	[03-client §4.1 O2]	Apple has no userspace TUN fd — it pumps NEPacketTunnelFlow packets via callbacks (helix_core_tun_out / helix_core_set_tun_writer), attach_tun(fd) (§3.3, §4.2). This is the load-bearing Apple-vs-Android difference.
O3	events() reports revoked when the OS/admin kills the tunnel out-of-band.	[03-client §4.1 O3]	stopTunnel(with:.userInitiated/.providerFailed/ + device.revoked (doc O2) → Down{reason:"auth-failed"} → revoked (§5.5, §10).
O4	On stopTunnel the shim restores a quiescent OS state on every exit path.	[03-client §4.1 O4]	helix_core_stop() in stopTunnel's completion + the k switch posture is handled <i>inside</i> the core (includeAllNetworks/excludeLocalNetworks + on-demand rules) (§3.4, §10).
I1	The transport never sees plaintext; the shim never inspects payload.	[01-TT §1 I1]	packetFlow packets are plaintext IP only on the app→core inbound write to the tunnel ; the shim co bytes opaquely and never logs them (§3.3, §11.4.10).

1. The two-process reality (extension vs containing app)

The single fact that shapes every Apple decision: **on Apple a Packet Tunnel Provider is a separate process from the app that hosts the UI** [research-ios_android §1.4, O4_P0 §6]. The Flutter UI runs in the *containing app* (Helix Access.app); the NEPacketTunnelProvider runs in a *system-spawned extension process* (HelixTunnel.appex) with its **own address space and its own jetsam memory budget**. helix-core runs **inside the extension**, because that is where packetFlow (the packet I/O) lives. Therefore the core's TunnelStatus stream is generated in the extension and must cross a process boundary to reach the UI.



Why this matters (CI2). The app cannot read the core's in-process broadcast channel directly. It must (a) observe `NEVPNStatusDidChange` for coarse transitions (connecting/connected/reconnecting/disconnected), and (b) receive the *fine* status (Handshaking vs Connecting, Connected{transport, rtt}, Down{reason}) via the cross-process push of §5. Painting the UI on `NEVPNStatus` alone would lose the transport/rtt/reason detail the `StatusChip` needs and would risk the "connected but actually handshaking" lie CI2 forbids.

2. The Apple TunnelPlatform implementation (Dart side)

The Apple shim satisfies the shared `TunnelPlatform` contract [03-client §4]:

```
abstract class TunnelPlatform {
  Future<void> startTunnel(TunnelConfig cfg);
  Future<void> stopTunnel();
  Stream<PlatformTunnelEvent> events();
}
```

2.1 IosTunnelPlatform (Dart) — the marshaller

```
// helix_core_ffi/lib/src/platform/ios_tunnel_platform.dart
class IosTunnelPlatform implements TunnelPlatform {
  static const _method = MethodChannel('helixvpn/tunnel');
  static const _events = EventChannel('helixvpn/tunnel/events');

  @override
  Future<void> startTunnel(TunnelConfig cfg) async {
    // App-side ONLY configures + starts NETunnelProviderManager;
    // it does NOT touch packets.
    await _method.invokeMethod('startTunnel', <String, dynamic>{
      'overlayIp':   cfg.overlayIp,           // 100.64.0.7/32
                or fd7a::/128
      'routes':      cfg.routes,              // AllowedIPs →
                includedRoutes
      'dnsServers':  cfg.dnsServers,          // tunnel DNS
                (anti-leak)
      'mtu':         cfg.mtu,                 // 1280 MASQUE /
                1420 plain WG [01-TT §4.8]
      'sessionToken': cfg.sessionOrMapToken,  // →
                helix_core_start, never logged (§11.4.10)
    });
    // NOTE: splitExcludeApps is NOT honoured on iOS (no per-app
    // VPN for 3rd-party apps,
    // §10 E7); macOS supports excludeLocalNetworks only.
    // Surfaced, not silently dropped.
  }
}
```

```

@override
Future<void> stopTunnel() => _method.invokeMethod('stopTunnel');

@override
Stream<PlatformTunnelEvent> events() =>
    _events.receiveBroadcastStream().map(_decodeEvent); // §5.6
}

```

2.2 Channel verbs (Dart → app-side Swift)

Verb	Direction	Swift handler	Effect
startTunnel(args)	Dart → app Swift	AppTunnelChannel.start	load/save NETunnelProviderManager, startVPNTunnel(options: {token,...})
stopTunnel()	Dart → app Swift	AppTunnelChannel.stop	session.stopVPNTunnel()
events() stream	app Swift → Dart	EventChannel.EventSink	emits up/down/ permissionDenied/ revoked/error decoded from §5

startTunnel/stopTunnel complete on the app-side MethodChannel; they do **not** carry status — status flows out-of-band on the EventChannel fed by the §5 bridge so the contract's "events() is lifecycle only, never data" rule [O3-client §4 O3] holds.

2.3 Permission-aware start (O1)

```

// apps/access/ios/Runner/AppTunnelChannel.swift (app process)
func start(_ args: [String: Any], result: @escaping
    FlutterResult) {
    NETunnelProviderManager.loadAllFromPreferences { managers, err
        in
        if let err { return result(self.flError("load",
            err)) } // O1: surface, no half-open
        let mgr = managers?.first ?? NETunnelProviderManager()
        let proto = NETunnelProviderProtocol()
        proto.providerBundleIdentifier =
            "io.helixvpn.access.tunnel" // the .appex bundle id
        proto.serverAddress = (args["overlayIp"] as? String) ??
            "HelixVPN"
        // Non-secret config travels in providerConfiguration; the
        // SESSION TOKEN travels in
        // startVPNTunnel(options:) (kept out of the saved preferences
        // plist → §11.4.10):
        proto.providerConfiguration = ["routes": args["routes"]!,
            "dns": args["dnsServers"]!,

```

```

                                "mtu": args["mtu"]!]
mgr.protocolConfiguration = proto
mgr.localizedDescription = "HelixVPN"
mgr.isEnabled = true
mgr.saveToPreferences { saveErr in
    if let saveErr = saveErr as NSError? {
        // Permission sheet declined →
        NEVPNErr.configurationReadWriteFailed / .Code(1)
        if saveErr.domain == NEVPNErrDomain { return
            result(self.flPermissionDenied()) } // 01
        return result(self.flError("save", saveErr))
    }
mgr.loadFromPreferences { _ in
    do {
        let opts: [String: NSObject] = [
            "sessionToken": (args["sessionToken"] as! String) as
            NSObject // ephemeral, not persisted
        ]
        try (mgr.connection as!
            NETunnelProviderSession).startVPNTunnel(options: opts)

        result(nil) //
        start accepted (NOT "connected")
    } catch { result(self.flError("startVPNTunnel", error)) }
}
}
}
}
}

```

O1 honesty (§11.4.6). A declined VPN-permission sheet MUST surface as PlatformTunnelEventKind.permissionDenied, never error, and leave **no** saved-enabled manager behind (the next loadAllFromPreferences must not find a dangling config). The session token rides in startVPNTunnel(options:) and is therefore **never written to the preferences plist** (§11.4.10 no-secret-at-rest).

3. NEPacketTunnelProvider (Swift) — full lifecycle

The make-or-break class [04_P0 §6]. It runs in the extension process, owns packetFlow, configures the tunnel network settings, links the Rust staticlib, and pumps packets.

3.1 Class skeleton

```

// apps/access/ios/HelixTunnel/PacketTunnelProvider.swift
// (extension process)
import NetworkExtension

```

```

import os

final class PacketTunnelProvider: NEPacketTunnelProvider {
    private let log = Logger(subsystem: "io.helixvpn.tunnel",
                             category: "provider")
    private var started = false // idempotency
                                guard (01)

    override func startTunnel(options: [String: NSObject]?,
                              completionHandler: @escaping (Error?)
                                -> Void) {
        guard !started else { return completionHandler(nil) } //
            idempotent (01)
        started = true
        let cfg = decodeTunnelConfig(options, protocolConfig:
            self.protocolConfiguration)
        applyNetworkSettings(cfg) { [weak self] err in
            guard let self else { return }
            if let err { self.started = false; return
                completionHandler(err) } // no half-open (01/04)
            // 1. Wire the core's outbound writer (core → packetFlow →
            // OS) BEFORE start, so no race:

            installTunWriter() //
                §3.3

            installStatusCallback() //
                §5.2
            // 2. Start the Rust core in-process (it owns WG + transport
            // ladder + kill-switch):
            var c = HelixClientConfig(
                sessionToken:
                cfg.sessionToken, //
                ephemeral, never logged
                mode: HELIX_MODE_CLIENT,
                mtu: cfg.mtu)
            let rc =
                helix_core_start(&c) //
                §4.1
            guard rc == HELIX_OK else {
                self.started = false
                return
                completionHandler(self.mapCoreError(rc)) //
                §10 error map
            }
            // 3. Begin the read pump (packetFlow → core), recursively:

            self.pumpOutbound() //
                §3.3
            // 4. Return SUCCESS once the carrier+settings are ready.
            // The fine status
            // (Handshaking→Connected) is pushed via the §5 bridge,
            // NOT here (CI2).
            completionHandler(nil)
        }
    }
}

```



```

s6.includedRoutes = cfg.routes6.map {
    NEIPv6Route(destinationAddress: $0.addr,

        networkPrefixLength: $0.prefix) }
settings.ipv6Settings = s6
}
// tunnel DNS – the anti-leak core: all :53 goes into the
// tunnel:
let dns = NEDNSSettings(servers: cfg.dnsServers)
dns.matchDomains = [""] // match ALL
// domains → no plaintext :53 off-tunnel
settings.dnsSettings = dns
settings.mtu = NSNumber(value: cfg.mtu) // 1280 MASQUE /
// 1420 plain WG [01-TT §4.8]
setTunnelNetworkSettings(settings, completionHandler: done)
}

```

DNS-leak note (CI-aligned). `matchDomains = [""]` forces every DNS query through the tunnel DNS — the iOS-NE realization of the orchestrator's "force tunnel DNS; block plaintext :53 off-tunnel" rule [01-ORCH §8.3]. iOS NE has **no userspace firewall**, so the kill-switch is realized by (a) `includeAllNetworks / excludeLocalNetworks` on the protocol (§3.4), and (b) the default-route capture above — not by nft rules as on Linux.

3.3 The packet pump (the O2 seam — no TUN fd on Apple)

Apple gives the extension `packetFlow: NEPacketTunnelFlow` with `readPackets/writePackets` — there is **no file descriptor** to hand to the core, so the Android/Linux `attach_tun(fd)` path does **not** apply here [research-ios_android §3 contrast, 03-client §5.1]. Instead the shim pumps packets across the FFI by value:

```

// Outbound: OS app traffic → packetFlow → core (encrypt+send over
// transport)
private func pumpOutbound() {
    packetFlow.readPackets { [weak self] packets, protocols in
        guard let self else { return }
        for (i, pkt) in packets.enumerated() {
            let isV6 = protocols[i].int32Value == AF_INET6
            pkt.withUnsafeBytes { raw in
                helix_core_tun_out(raw.bindMemory(to:
                    UInt8.self).baseAddress,
                                UInt(pkt.count),
                                isV6) // §4.2 – opaque copy (I1)
            }
        }
    }
    self.pumpOutbound() // recurse (NE idiom)
}
}

```

```

// Inbound: core (decrypted IP packets) → packetFlow → OS.
// Registered ONCE at start:
private func installTunWriter() {
    // The C callback trampolines back into Swift; `ctx` carries
    // `self` (Unmanaged).
    let ctx = Unmanaged.passUnretained(self).toOpaque()
    helix_core_set_tun_writer({ pkt, len, isV6, ctx in
        let me =
            Unmanaged<PacketTunnelProvider>.fromOpaque(ctx!).takeUnretainedValue()
        let data = Data(bytes: pkt!, count: Int(len))
        let proto = isV6 ? NSNumber(value: AF_INET6) :
            NSNumber(value: AF_INET)
        me.packetFlow.writePackets([data], withProtocols:
            [proto]) // §4.2
    }, ctx)
}

```

O2/I1 discipline. The shim copies packet bytes opaquely (`Data(bytes:count:)`) and never parses, logs, or mutates them. All crypto + obfuscation lives in `helix-core` (one core, no fork) [O3-client §4 O2, O1-TT §1 I1]. The recursive `readPackets` continuation is the canonical NE pump idiom; it is cancel-safe (a `stopTunnel` tears the provider down and the continuation simply stops being called).

3.4 Kill-switch posture on Apple (O4)

iOS/macOS NE realize the "no leaks if the tunnel drops" guarantee [O4_ARCH §5.6] through the **protocol configuration**, set on the app side at save time, not by in-extension firewall rules:

Knob	Effect	Helix mapping
<code>NETunnelProviderProtocol.includeAllNetworks</code>	route ALL traffic into the tunnel; on drop, traffic is blocked	the iOS kill-switch (Strict mode [O1-C
<code>.excludeLocalNetworks</code>	permit RFC1918 LAN (printers) even when <code>includeAllNetworks</code>	<code>KillSwitchConfig</code> [O1-ORCH §8.2]
<code>.enforceRoutes</code>	OS enforces <code>includedRoutes</code> even when other VPNs/configs exist	hardens <code>AllowedIP</code>
on-demand rules (<code>NEOnDemandRule</code>)	auto-reconnect / always-on	the "always-on VP (Phase 2)

The core's internal kill-switch state machine [01-ORCH §8] still drives *when* the tunnel should be up; on Apple the *enforcement* is the OS routing + includeAllNetworks, so the in-extension core does NOT install nft-equivalent rules (none exist in the NE sandbox). UNVERIFIED: whether includeAllNetworks fully blocks egress during the extension-restart window on every iOS version — measured in the G3/SC soak (§12), never assumed (§11.4.6).

4. The Swift $\rightleftarrows$ Rust FFI surface (C ABI / UniFFI)

The extension links helix-core as a **staticlib** (crate-type = ["staticlib"]) and calls its exported C surface generated from the helix-ffi crate [03-client §3, research-ios_android §2.4]. Decision **D-CLIENT-3**: UniFFI for typed Swift, cbindgen as the fallback for the raw-callback pump where UniFFI's async/callback ergonomics are thin [03-client D-CLIENT-3]. This section pins the **cbindgen C ABI** (the lowest common denominator both binding generators agree on); the UniFFI typed wrapper is a thin overlay.

4.1 Lifecycle + config (C ABI)

```
// helix_core.h - cbindgen-generated from helix-ffi/src/
// ffi_capi.rs
#include <stdint.h>

typedef enum {                                // mirrors api.rs CoreMode
    [03-client §3.1]
    HELIX_MODE_CLIENT      = 0,
    HELIX_MODE_CONNECTOR   = 1,
} HelixCoreMode;

typedef enum {                                // start/stop result; maps to
    NEVPNError + Down.reason (§10)
    HELIX_OK                = 0,
    HELIX_ERR_CONFIG        = 1,                // bad token / unparseable
        map      → "host-fatal"
    HELIX_ERR_HANDSHAKE     = 2,                // carrier dialled, WG never
        replied → retry/escalate
    HELIX_ERR_HOST          = 3,                // settings/packetFlow
        unusable → "host-fatal"
    HELIX_ERR_AUTH          = 4,                // WG handshake rejected
        (revoked) → "auth-failed", NO retry
} HelixResult;

typedef struct {
    const char*
        session_token;                // ephemeral; NEVER persisted or
        logged (§11.4.10)
```

```

HelixCoreMode mode;
uint16_t      mtu;                // inner WG MTU ceiling [01-
    TT §4.8]
} HelixClientConfig;

// Start the in-extension core. Returns once WG+transport tasks
// are spawned (NOT once
// the tunnel is "connected" – that is reported via the status
// callback, CI2).
HelixResult helix_core_start(const HelixClientConfig* cfg);

// Idempotent graceful stop: FIN the carrier, revert state, stop
// loops (04).
void helix_core_stop(void);

// Apply a fresh resolved map (Phase 1 WatchNetworkMap delta;
// Phase 0 static map).
HelixResult helix_core_apply_map(const uint8_t* map_cbor,
    uintptr_t len);

```

4.2 The packet pump (C ABI – the Apple-specific seam)

```

// Outbound: hand ONE plaintext IP packet from packetFlow to the
// core (it encrypts+sends).
// `is_v6` selects the AF for the inner WG router. Bytes are
// copied in-crate; the caller's
// buffer is NOT retained past the call (no aliasing of packetFlow
// storage).
void helix_core_tun_out(const uint8_t* pkt, uintptr_t len, bool
    is_v6);

// Inbound writer: the core invokes this callback with a DECRYPTED
// IP packet to write to
// packetFlow. Registered ONCE before start. `ctx` is an opaque
// app pointer (Unmanaged self).
typedef void (*HelixTunWriter)(const uint8_t* pkt, uintptr_t len,
    bool is_v6, void* ctx);
void helix_core_set_tun_writer(HelixTunWriter cb, void* ctx);

```

Why a callback pump and not `attach_tun(fd)`.

NEPacketTunnelFlow exposes `readPackets/writePackets`, never a kernel `fd`, so the [03-client §3] `attach_tun(fd:i32)` entry point is unused on Apple. Android/Linux DO use `attach_tun(fd)` (the `ParcelFileDescriptor/tun fd`) [research-ios_android §3]. The FFI crate exports **both** entry points; each platform shim wires the one its OS provides — the core's internal `tun` → `wg` loop A and `wg` → `tun` loop B [01-ORCH §3] read/write through whichever sink was installed. This is the only place the otherwise-uniform FFI surface diverges per OS.

4.3 Status callback (C ABI — feeds the §5 bridge)

```
// The core pushes EVERY TunnelStatus transition here (in-
// extension). Payload is a compact
// CBOR/JSON encoding of the 5-variant TunnelStatus enum (§5.1).
// Called from the core's
// state-driver task; the Swift handler must be cheap + non-
// blocking (§5.2).
typedef void (*HelixStatusCb)(const uint8_t* status_cbor,
                               uintptr_t len, void* ctx);
void helix_core_set_status_cb(HelixStatusCb cb, void* ctx);

// Pull the latest status synchronously (for handleAppMessage
// "getStatus", §5.3).
// Writes up to `cap` bytes into `out`, returns the written length
// (0 if none yet).
uintptr_t helix_core_current_status(uint8_t* out, uintptr_t
cap);
```

4.4 FFI safety & memory rules (release-blocking)

#	Rule	Why
F1	Every <code>*const u8/*mut u8</code> is copied in-crate on entry; no Rust struct ever aliases a Swift-owned buffer past the call.	avoids use-after-free across the FFI; required for panic=abort safety (§7).
F2	The status/writer callbacks are extern "C" fn pointers with a <code>void* ctx</code> ; the core stores them behind an <code>AtomicPtr</code> set once before <code>helix_core_start</code> .	no captured-closure ABI mismatch; callback set is happens-before the loops.
F3	A Rust panic inside the core MUST NOT unwind across the C ABI — panic = "abort" (§7) makes any panic a clean process abort (the extension is restarted by NE) rather than UB.	panic=abort is both a size win AND an FFI-soundness requirement.
F4	The session token (<code>*const c_char</code>) is copied into a <code>SecretBytes</code> -class buffer [01-TT §3.2] and zeroized on drop; it is never logged on either side (§11.4.10).	no-secret-leak.
F5	All FFI functions are <code>#[no_mangle] pub extern "C"</code> ; the header is drift-checked in CI against the crate (a divergence FAILs the build, mirroring the frb contract test [03-client §12]).	one source of truth, no silent surface drift.

5. The status bridge — core TunnelStatus → Dart EventChannel

The core's status stream lives **inside the extension**; the UI lives **in the app**. This section pins how a TunnelStatus transition becomes a Dart PlatformTunnelEvent. **The core-emitted enum is the 5-variant TunnelStatus from [01-ORCH §4.1]** — this doc keeps the FFI status payload byte-consistent with that enum; the richer Dart-facing TunnelStatus (adding Disconnected/path/Danger) [03-client §3.1] is a *UI projection* layered in helix_core.dart, not a second wire enum.


5.1 The canonical core-emitted enum (consistency anchor)

```
// helix-core/src/status.rs – the SINGLE wire enum the FFI status
// callback serializes.
// IDENTICAL to [01-ORCH §4.1]; the Apple bridge MUST NOT invent
// variants.
#[derive(Clone, Debug, PartialEq, Eq)]
pub enum TunnelStatus {
    Connecting, // dialling a
    Handshaking, // carrier up;
    Connected { transport: String, rtt_ms: u32 }, // ("masque-
    Reconnecting, // a working
    Down { reason:
    }
}
```

Down.reason uses the [01-ORCH §4.4] stable prefixes ("stopped" | "pinned-transport-failed" | "ladder-exhausted" | "auth-failed" | "no-route" | "host-fatal") so the bridge can classify without parsing prose (§11.4.6 no-guessing).

5.2 Push path (extension → app): App-Group file + Darwin notify

The extension cannot call into the app process directly. The recommended **push** mechanism (UNVERIFIED exact API names verified on device, but all are standard NE-IPC primitives):



- The status callback writes the latest TunnelStatus (CBOR) **atomically** (write-temp + rename) into the App-Group container both processes share, then posts a **Darwin notification** (CFNotificationCenterGetDarwinNotifyCenter) — a payload-less cross-process wake. The app's observer reads the *latest* file (coalesced; only the newest state matters, matching the broadcast "skip-to-latest" semantics [01-ORCH §4.2/§4.6]).
- The status callback is **cheap**: serialize + one atomic write + one notify post; it never blocks the core's state-driver task (§4.3 contract).
- **Why not sendProviderMessage for push?**
NETunnelProviderSession.sendProviderMessage is **app→extension request/response only**; the extension cannot originate it. Hence the App-Group-file + Darwin-notify push for extension→app, and sendProviderMessage for the *pull* path (§5.3).

5.3 Pull path (app → extension): sendProviderMessage

On app foreground / cold start / after a Darwin-notify miss, the app pulls the current status to resync (defends against a dropped notification):

```
// app process
func refreshStatus() {
  guard let session = mgr.connection as? NETunnelProviderSession
    else { return }
  try?
    session.sendProviderMessage("getStatus".data(using: .utf8)!)
    { reply in
      if let reply { self.emit(decodeTunnelStatus(reply)) } // →
        EventChannel (§5.6)
    }
}
```

The extension answers in handleAppMessage (§3.1) via helix_core_current_status (§4.3).

5.4 Coarse NEVPNStatus as a backstop only

NEVPNStatusDidChange

(.connecting/.connected/.reconnecting/.disconnecting/.disconnected/ .invalid)
is observed by the app as a **backstop** — it guarantees the app learns of OS-side transitions (e.g. the OS tearing the tunnel) even if a Darwin notify is

missed. But it is **coarse** (no transport/rtt/reason), so the fine TunnelStatus from §5.2/§5.3 is always the source of truth for the StatusChip; NEVPNStatus only triggers a §5.3 pull (CI2).

5.5 NEProviderStopReason → Down{reason} mapping (O3)

```
func downReasonFor(_ r: NEProviderStopReason) -> String {
  switch r {
  case .userInitiated:          return "stopped"           //
    user toggled off (§8.6 only open path)
  case .providerFailed,
    .internalError:             return "host-fatal"
  case .authenticationCanceled,
    .configurationFailed:       return "auth-failed"        // →
    revoked (O3)
  case .noNetworkAvailable,
    .unrecoverableNetworkChange: return "ladder-exhausted"
  case .providerDisabled,
    .configurationDisabled,
    .configurationRemoved,
    .superseded:                return "auth-failed"        //
    admin/OS revoked the config (O3)
  @unknown default:            return "host-fatal"
  }
}
```

device.revoked propagated from the control plane (doc 02) reaches the core as a map delta whose peers_removed includes the active peer → the core emits Down{reason:"auth-failed"} [01-ORCH §6.4] → the bridge maps it to PlatformTunnelEventKind.revoked (§5.6).

5.6 TunnelStatus → PlatformTunnelEvent decode (Dart)

```
PlatformTunnelEvent _decodeEvent(dynamic raw) {
  final s = TunnelStatus.fromCbor(raw as Uint8List); // mirrors
    the §5.1 enum
  return switch (s) {
    Connecting() || Handshaking() || Reconnecting() =>
      PlatformTunnelEvent(PlatformTunnelEventKind.up), // "in
        motion"; UI shows amber via the richer projection
    Connected() =>
      PlatformTunnelEvent(PlatformTunnelEventKind.up),
    Down(:final reason) when reason == 'auth-failed' =>
      PlatformTunnelEvent(PlatformTunnelEventKind.revoked,
        reason),
    Down(:final reason) when reason == 'stopped' =>
      PlatformTunnelEvent(PlatformTunnelEventKind.down, reason),
    Down(:final reason) =>
      PlatformTunnelEvent(PlatformTunnelEventKind.error,
        reason),
  };
}
```

Boundary note. PlatformTunnelEvent (lifecycle: up/down/permissionDenied/revoked/error) [03-client §4] is intentionally coarser than TunnelStatus. The *rich* status (Connected{transport, rtt}, Handshaking, Danger) reaches the UI **directly** via tunnelStatusProvider folding the core's statusStream() projection [03-client §8.2] — on Apple that stream is fed by the same App-Group/Darwin bridge. events() carries only the lifecycle transitions the TunnelPlatform contract owns; the two are complementary, not redundant.

6. The iOS NE memory ceiling — the hard constraint

CI4: this is the single strongest architectural driver and the reason the core is Rust, not Go [04_ARCH §5.6, SYN §5]. The facts (every figure cited; never hardcoded — §11.4.6):

6.1 The facts (research-ios_android §1)

Fact	Value	Source / status
Documented Packet-Tunnel-Provider limit (iOS 15–18)	50 MiB	Apple DTS (Quinn), measured iOS 16, reconfirmed 17/18 [research-ios_android §1]
Historical limit (iOS 11–14, 64-bit)	15 MiB	[research-ios_android §1]
Observed real-world jetsam kill on iOS 17.3.1	~15 MB (despite 50 MiB docs)	reported, root cause PENDING_FORENSICS [research-ios_android §1]
Dominant kill cause	transient spikes during upload-heavy throughput (buffer-pool/QUIC)	sing-box/WireGuard jetsam during speedtest [research-ios_android §1]
Scope	the whole extension process — Swift + Rust staticlib + every linked lib	[research-ios_android §1.4]
Official guidance	"do not hard code knowledge of these	Quinn, verbatim [research-ios_android §1.2]

Fact	Value	Source / status
	limits"; measure on device	

6.2 The design rule (engineering conclusion)

Target a steady-state working set of ~12–15 MB, NOT the 50 MiB headline [research-ios_android §1, §4]. The 50 MiB is undocumented, may be lower on older devices, and 15 MB kills are reported in the wild. Because WireGuard is IP-level with no TCP connection tracking, a WG-class datapath fits comfortably; the risk is **spikes**, not steady state.

Concrete budget-keeping rules the Rust core **MUST** honour (the in-extension build):

#	Rule	Realization
M1	Bound every buffer pool. No per-flow state growth.	fixed-size receive buffer = negotiated MTU + headroom (not an arbitrary large value) [research-ios_android §1.6]; pre-allocated send scratch reused per loop [01-ORCH §3.1].
M2	Cap QUIC flow-control windows in the iOS build.	masque-h3 carrier built with reduced quinn receive_window/stream_receive_window (iOS profile) — the §6.4 fallback rung 1.
M3	No backtrace/unwind machinery.	panic = "abort" + build-std panic_immediate_abort (§7) drops gimli/format code [research-ios_android §2].
M4	Single fixed receive buffer , sized to MTU+headroom.	bound the NE read-buffer; do not allocate per readPackets burst.
M5	No durable per-connection state (also I5).	only aggregate TransportHealth counters [01-TT §2.3]; nothing per-packet retained.

6.3 How to measure on device (G3)

There is **no API to query or raise** the NE limit [research-ios_android §1.5]; footprint must be measured empirically:

1. Build helix-core as aarch64-apple-ios (z/s + LTO + panic=abort + strip, §7); record the static archive size.
2. Attach Instruments **Allocations** + **VM Tracker** (or the Xcode Memory gauge) to the **extension** target (debug-attach to the running .appex,


NOT the app). **Simulator memory is not representative** — real device only [04_P0 §6.3].

3. Drive a **sustained 1 GB transfer** with `plain-udp` **and** `masque-h3` **separately** (QUIC buffers cost more memory; both must pass) [04_P0 §6.3].
4. Sample `phys_footprint` via Mach `task_vm_info` (the value jetsam accounts against; UNVERIFIED — verify on device) and/or log Rust allocator stats periodically to catch spikes [research-ios_android §1.5].
5. Run the **upload-heavy speedtest scenario** specifically — it is the documented spike trigger that kills sing-box/WireGuard extensions [research-ios_android §1].

G3 pass = steady-state `phys_footprint` under the device-enforced ceiling with ≥ 30 % headroom across a 30-minute soak, for both transports, on a real device [04_P0 §6.4, 03-client §5.1]. The number is captured evidence (Instruments RSS report + window-scoped MP4 per §11.4.159), never asserted (§11.4.6/.123).

6.4 The fallback ladder (if G3 fails) — D-CLIENT-1

Each rung is a real product decision, surfaced to the operator (§11.4.66), never hand-waved [04_P0 §6.4, 03-client D-CLIENT-1]:



- **Rung 1** (preferred): cap QUIC flow-control windows (M2) + shrink buffer pools (M1) in the iOS build profile; re-soak. Prefer this if it reaches $\geq 30\%$ headroom [03-client D-CLIENT-1].
- **Rung 2**: move MASQUE off-device for iOS — ship only plain-udp + on-path/lwo obfs in-extension; the heavier QUIC carrier is not used on iOS. **Partial feature loss** (no MASQUE on the most censorship-hostile networks for iOS) — an explicit product decision.
- **Rung 3**: split the core — only the lean WG datapath runs in the extension; QUIC CONNECT-UDP negotiation runs in the *app* process and the established carrier is handed to the extension via app-extension IPC. Highest complexity; last resort.

6.5 macOS does NOT share this constraint

macOS NEPacketTunnelProvider (delivered as a System Extension or app-extension) runs with **desktop-class memory** — there is **no 15/50 MiB jetsam cap** equivalent [research-ios_android §3.5 contrast (Android), §8 here]. The full masque-h3 carrier and generous buffers are fine on macOS. **Only iOS is the binding memory constraint**; the same Rust core links into both, but the **iOS build profile** (M1–M5, §6.2) is the lean one (§7, §8).

7. Swift $\rightleftharpoons$ Rust staticlib build (aarch64-apple-ios)

The core is built as a size-first static archive and linked into the extension [research-ios_android §2]. Smaller code = fewer mapped pages = lower NE footprint *and* smaller app.

7.1 Crate type & Cargo profile

```
# helix-ffi/Cargo.toml
[lib]
crate-type = ["staticlib"]          # .a linked into the .appex
                                     (no dylib entitlement friction)

# Cargo.toml – size-first release profile (research-ios_android
# §2)
[profile.release]
opt-level      = "z"
               # smallest code (benchmark "s" too – often faster, ~same
               # size)
lto            = "fat"                # whole-program; max size
               # reduction
codegen-units = 1
               # better cross-module size opt (slower compile)
panic         = "abort"              # drops unwinding tables +
               FFI-soundness (F3) – REQUIRED
strip         = true                 # strip symbols (~3–8% extra)
```

7.2 iOS target build (size-first), with the nightly build-std win

```
# Stable, baseline:
cargo build --release --target aarch64-apple-ios -p helix-ffi

# Largest reduction (nightly build-std – drops std unwinding/
# format machinery, incl. gimli):
cargo +nightly build --release --target aarch64-apple-ios -p
helix-ffi \
```

```

-Z build-std=std,panic_abort \
-Z build-std-features=panic_immediate_abort,optimize_for_size
# Representative reported reduction ~43% (build-std +
  panic_immediate_abort + optimize_for_size)
# [research-ios_android §2].

```

Flag	Effect	Source
opt-level="z"/"s"	smallest code; benchmark both	[research-ios_android §2]
lto="fat"	whole-program inlining/ dead-strip	[research-ios_android §2]
codegen-units=1	cross-module size opt	[research-ios_android §2]
panic="abort"	drops unwind tables; FFI-sound (F3)	[research-ios_android §2]
strip=true	removes names/debug (~3–8%)	[research-ios_android §2]
build-std + panic_immediate_abort + optimize_for_size	drops gimli/format from std (~43%)	[research-ios_android §2]
dependency audit	avoid fat deps (regex/ format/heavy async) that bloat code	bitdrift [research-ios_android §2]
prefer dyn over generic explosion on cold paths	curb monomorphization bloat	bitdrift [research-ios_android §2]

7.3 Linking into the extension & binding generation

- The `.a` is linked into the `HelixTunnel.appex` target; the linker dead-strips unreferenced symbols [research-ios_android §2.4]. A universal/xcframework packaging is UNVERIFIED per device-arch matrix — Phase-0/1 ships `aarch64-apple-ios` device + `aarch64-apple-ios-sim`
 - `aarch64/x86_64-apple-darwin` for macOS, assembled into an xcframework.
- **Bindings (D-CLIENT-3):** UniFFI generates the typed Swift wrapper (`HelixClientConfig`, enums) from the `helix-ffi` UDL/proc-macro; the

raw callback pump (§4.2/§4.3) uses the cbindgen C header where UniFFI's callback ergonomics are thin [03-client D-CLIENT-3, research-flutter_ffi]. Both read **one** Rust surface; a header/UDL drift FAILs CI (F5).

- The Dart side links the **same** core via flutter_rust_bridge for the in-app logic-only calls (exits/setExit/setShields) that do not touch the OS tunnel [03-client §3.2] — but those run in the **app** process, distinct from the extension's linked copy. The two linked copies share source, never runtime state (the extension's core owns the tunnel; the app's frb core is logic-only). UNVERIFIED: whether Phase-1 links the frb core in the app at all on iOS, or routes all logic calls through sendProviderMessage to the single in-extension core — a Phase-0 G5 decision (recommend the latter to keep ONE live core).

8. macOS desktop-class differences


The same Apple shim serves macOS with three differences from iOS:

Aspect	iOS	macOS
Memory	hard jetsam ceiling (~50 MiB doc / ~12–15 MB budget, §6)	desktop-class, no NE jetsam cap [research-ios_android §3.5 contrast] — full masque-h3 + generous buffers
Extension packaging	app-extension (.appex) bundled in the app	System Extension (.systemextension, NEMachServiceName) OR app-extension; sysext needs OSSystemExtensionRequest activation + user approval in System Settings
Per-app split tunnel	not available to 3rd-party apps	excludeLocalNetworks + app-aware routing possible; still no arbitrary per-app like Android
Build profile	the lean §6.2 M1–M5 profile	may relax buffer caps (M1/M2) for throughput; same source, different feature flags
Signing	Apple notarize (App Store / TestFlight)	Apple notarize + System Extension entitlement (com.apple.developer.networking.networkextension = packet-tunnel-provider, sysext gatekeeper) [03-client §11]


The Swift PacketTunnelProvider source is **shared** between iOS and macOS targets (one PacketTunnelProvider.swift); the build flavors differ only in (a) extension packaging, (b) the Rust core build profile, and (c) entitlements/signing. The Dart TunnelPlatform impl is shared too (AppleTunnelPlatform with a thin Platform.isMacOS branch only for the sysexit activation request) [03-client \$5 payoff].

9. Lifecycle state machines

9.1 Extension-process tunnel lifecycle (NE provider)



9.2 App-side connect controller (drives the extension)



10. Error handling & edge cases

#	Edge case	Handling	Constitution / source
E1	VPN permission sheet declined	saveToPreferences returns NEVPNError → permissionDenied (not error); no enabled config left behind (O1)	§11.4.6, [03-client §4 O1]
E2	setTunnelNetworkSettings fails	started=false, completionHandler(err); never enter Pumping with no settings (no half-open)	[03-client §4 O1/O4]
E3	helix_core_start → HELIX_ERR_AUTH (revoked key)	terminal without retry ; Down{reason:"auth-failed"} → revoked; ladder escalation pointless (would mask revocation)	[01-ORCH §5.4]
E4	HELIX_ERR_HANDSHAKE (carrier up, WG silent)	core escalates the ladder internally; status shows Reconnecting; not a provider failure	[01-ORCH §7], [01-TT §6]
E5	iOS jetsam kills the extension (OOM)	NE restarts the provider; on-demand rules + includeAllNetworks keep traffic blocked during the gap (no leak); §6 budget is the prevention	[research-ios_android §1], §6

#	Edge case	Handling	Constitution / source
E6	Device sleep / network change (Wi-Fi→cellular)	wake() no-op; WG roams onto the new path on the next handshake/keepalive — no re-dial needed; the core's roam fast-path applies	[01-ORCH §7.5]
E7	Per-app split tunnel requested on iOS	NOT available to 3rd-party apps on iOS; splitExcludeApps is surfaced as unsupported (honest, not silently dropped)	§11.4.6, [03-client §4]
E8	App killed/backgrounded while connected	the extension keeps running (separate process); on app relaunch the §5.3 pull resyncs status — UI never lies (CI2)	§1, §5.3
E9	Darwin notification missed (delivery is best-effort)	the §5.4 NEVPNStatus backstop + the §5.3 cold-start pull recover the latest status	§5.3/§5.4
E10	Oversize datagram from the core	the core lowers inner MTU / fragments; the shim never truncates a packet (I2)	[01-TT §4.8], [01-ORCH §6.6]
E11	Rust panic across the C ABI	panic=abort → clean process abort (NE restarts), never UB across FFI (F3)	§4.4 F3, §7
E12	Session token leak risk	token rides in startVPNTunnel(options:) (never in saved prefs plist), copied to SecretBytes, zeroized, never logged (F4)	§11.4.10, §4.4 F4
E13	macOS System Extension not yet approved	OSSystemExtensionRequest pends; surface a "approve in System Settings" prompt; do not claim connected	§11.4.6, §8

11. Memory / size / performance budgets

Budget	Target	How	Source
iOS extension steady-state ph ys_footprint	under device ceiling, ≥ 30 % headroom across a 30-min soak, both transports (G3)	M1–M5 (§6.2): bounded buffer pools, capped QUIC windows, single MTU-sized rx buffer, no per-flow state, panic=abort	[04_P0 §6.4], [research- ios_android §1]
iOS design working-set	~12–15 MB (NOT 50 MiB)	the budget the build targets; 50 MiB is undocumented + 15 MB kills observed	[research- ios_android §1, §4]
Rust staticlib size	as small as feasible	z/s + fat LTO + codegen-units=1 + panic=abort + strip; build- std/optimize_for_size (~43%)	[research- ios_android §2]
iOS spike avoidance (upload-heavy)	no jetsam during 1 GB speedtest	bound send/QUIC buffers (M1/ M2); the documented kill scenario	[research- ios_android §1]
macOS memory	desktop- class, no NE cap	full masque-h3 + generous buffers permitted	[research- ios_android §3.5], §8
Inner WG MTU	1280 over MASQUE / 1420 plain WG	settings.mtu = min(active.effective_mtu(), path_mtu)	[01-TT §4.8], [01- ORCH §6.6]
Status bridge latency	sub- second app- visible transition	Darwin notify + atomic App- Group read; coalesced (latest only)	§5.2
Pump overhead	no per- packet heap growth	opaque copy into a reused path; core reuses scratch buffers	[01-ORCH §3.1], M1

All budgets are **captured evidence** (Instruments RSS report + throughput CSV + window-scoped MP4 per §11.4.159), measured on a real device, never asserted (§11.4.6/.123).

12. Test points — tied to the §11.4.169 test-type vocabulary

Every Apple-shim workable item declares its required test types from the §11.4.169 closed set; the only permitted absence of a warranted type is an honest §11.4.3 SKIP-with-reason, never a silent gap. Four-layer enforcement per §11.4.4(b) applies to every closure. Codes match the sibling data-plane spec [01-TT §9].

Code	Type	Concrete Apple-shim test point	Evidence (§11.4.5/.69/.107)
UT	unit	decodeTunnelConfig/ downReasonFor/ _decodeEvent mapping tables; TunnelStatus CBOR round-trip identity; FFI header drift check (F5)	xcodebuild test + cargo test logs; drift diff
IT	integration	app[?]extension sendProviderMessage round- trip returns current status; App-Group write + Darwin notify → app observer fires; core staticlib links + starts in a host-extension harness	provider-message capture; notify- observed log
E2E	end-to-end	real-device: tap Connect → overlay IP assigned → curl http://<LAN host>/ over plain-udp and masque-h3; tap Disconnect → traffic blocked (kill-switch)	window-scoped MP4 of the journey (§11.4.159) + OCR StatusChip "masque-h3 · 23ms"
FA	full-automation (§11.4.25/.52/.98, deterministic §11.4.50)	scripted XCUITest drives connect→status→disconnect N=3 identical runs producing the same ordered PlatformTunnelEvent trace	3× identical event-trace artifacts
CH	Challenges (challenges submodule §11.4.27(B))	a Challenge scores the captured G3 + E2E evidence (not config)	Challenge result.json
HQA	HelixQA (helix_qa submodule)	autonomous QA session drives connect/roam/revoke across iOS + macOS targets	HelixQA session evidence

Code	Type	Concrete Apple-shim test point	Evidence (§11.4.5/.69/.107)
LOAD	DDoS / load-flood	sustained 1 GB transfer + handshake churn; no fd/ buffer leak in the extension	throughput CSV + footprint trace
SEC	security (§11.4.10 + security submodule)	(a) session token appears in no log / no saved prefs plist (plant-and-grep); (b) tshark shows masque-h3 flow = HTTP/3 with no WG signature (G2); (c) no plaintext packet logged by the shim	grep-empty proof; tshark classification
SC	stress + chaos (§11.4.85)	iface flap (Wi-Fi→cellular) → reconnect < 3 s (roam); kill the extension mid-transfer → NE restart, no leak during gap (E5); device sleep/wake	recovery trace; no-leak capture
CONC	concurrency / atomicity	concurrent outbound pump + inbound writer under load; status push during a transport swap drops zero packets	concurrency harness log
RACE	race / deadlock	cargo test --features loom on the in-crate status/ writer atomics; TSan on the Swift bridge	loom + TSan report
MEM	memory (G3 make-or-break)	extension phys_footprint under ceiling with ≥ 30 % headroom, 30-min soak, both transports, real device + upload-heavy spike scenario	Instruments RSS report (§6.3)
BENCH	benchmarking / performance	per-transport through-tunnel throughput / CPU on device; status-bridge latency; staticlib size delta per build flag	throughput/CPU/ size CSV

12.1 Apple-specific acceptance gates

- **G3 (iOS NE memory) — make-or-break** [04_P0 §6.4]: §6.3 soak passes for both transports with ≥ 30 % headroom; if it fails, the §6.4 fallback

ladder is engaged and the chosen rung is surfaced to the operator (§11.4.66) — never a silent feature drop.

- **G5 (FFI drives the core)** [04_P0 §9]: the extension's `helix_core_start` + pump + status callback drive a Connecting → Handshaking → Connected{masque-h3,23} transition observed by the Dart UI via the §5 bridge — recorded.
- **No-leak gate** (SEC + SC): with `includeAllNetworks`, no egress escapes during the extension-restart window; proven by capture, not assumed (§11.4.6).

12.2 Anti-bluff rule for this shim (§11.4.5/.69/.107)

The shim is the **only untyped seam** (Swift $\rightleftharpoons$ Rust $\rightleftharpoons$ Dart, cross-process) [03-client §4 O5] and is covered on **real devices**, never by a mock-claiming-PASS (§11.4.27). A green Swift unit test does NOT prove the user is protected — the authoritative evidence is the on-device E2E window-scoped MP4 with the `StatusChip` reading `masque-h3 · direct · 23ms` confirmed by OCR/vision validation (§11.4.158/.159), plus the Instruments G3 RSS report.

13. Cross-doc seams & surfaced decisions

Seam	Fixed value	Owned by / consumed from
FFI surface (<code>helix_core_start/stop/apply_map,tun_out,set_tun_writer,set_status_cb,current_status</code>)	§4 (cbindgen C ABI)	binds [03-client §3] (the surface contract); the core internals are [01-TT]/[01-ORCH]
Core-emitted TunnelStatus (5-variant, byte-consistent)	§5.1 = [01-ORCH §4.1]	the Dart UI projection extension is [03-client §3.1]; this doc keeps the wire enum consistent
TunnelPlatform channel (<code>startTunnel/stopTunnel/events,PlatformTunnelEvent</code>)	§2	[03-client §4]; <code>device.revoked</code> → revoked from doc 02
Packet-pump-not-fd (Apple uses <code>tun_out/tun_writer</code> ; Android/Linux use <code>attach_tun(fd)</code>)	§3.3, §4.2	the only per-OS FFI divergence; [research-ios_android §3]
iOS NE memory ceiling = the Rust-not-Go justification (G3)	§6	[04_ARCH §5.6], the whole "Rust core" thesis; build flags §7

13.1 Surfaced decisions (per §11.4.66 — options + recommendation, never silently resolved)

#	Decision	Option A	Option B	Recommendation
D-CLIENT-1	iOS NE memory fallback if G3 fails	shrink buffers / cap QUIC windows in iOS build (rung 1)	move MASQUE off-device (rung 2) or split-core app-extension IPC (rung 3)	Gate on the G3 measurement (§6.3). Prefer A if it reaches $\geq 30\%$ headroom; B only if A insufficient. Each is a real product decision — surface to operator [04_P0 §6.4].
D-CLIENT-3	Native binding generator	UniFFI (typed Swift) + cbindgen for the raw pump	cbindgen C header everywhere	UniFFI for typed types, cbindgen for the callback pump (§4) [03-client D-CLIENT-3].
D-APPLE-1	iOS logic-only calls (exits/setExit) location	frb core linked in the app (second linked copy, logic-only)	route all logic via <code>sendProviderMessage</code> to the single in-extension core	B (single live core) to avoid two cores' state divergence; confirm at Phase-C G5. UNVERIFIED until measured.
D-APPLE-2	Status push mechanism (ext→app)	App-Group file + Darwin notify (push) + <code>sendProviderMessage</code> (pull backstop)	poll <code>sendProviderMessage</code> on a timer only	A — push is sub-second + battery-friendly; the pull is the cold-start/missed-notify backstop (§5.2/§5.3).

Sources verified

- `final/03-client-core-and-ui.md` [03-client] — §0.1 (client invariants CI1–CI6), §3 (FFI surface + `TunnelStatus/Shields/ExitOption`), §4 (`TunnelPlatform` contract + obligations O1–O5), §5.1 (iOS/macOS NE shim skeleton + memory gate + fallbacks), §10 (budgets), §11 (signing/CI), §12 (testing), §14 (D-CLIENT-1/2/3).

- `final/v02-data-plane/orchestrator-and-state.md` [01-ORCH] — §4.1 (the 5-variant `TunnelStatus` enum — the consistency anchor), §4.4 (`Down.reason` prefixes), §5.4 (auth-failed terminal-no-retry), §6.4 (revocation), §6.6 (MTU coupling), §7.5 (roam fast-path), §8 (kill-switch + DNS coupling).
- `final/v02-data-plane/transport-trait.md` [01-TT] — §1 (invariants I1/I2), §2.3 (`TransportHealth`), §3.2 (`SecretBytes` redaction/zeroize), §4.8 (`effective_mtu` per carrier), §6 (ladder), §9 (the §11.4.169 test-type vocabulary).
- `v09-research/research-ios_android.md` [research-ios_android] — §1 (NE 50 MiB documented / 15 MB historical / 15 MB observed kills / do-not-hardcode / measure on device / whole-process scope / spike-driven jetsam), §2 (`staticlib` `opt-level=z+fat-LTO+codegen-units=1+panic=abort+strip+build-std/optimize_for_size` ~43%), §3 (Android fd contrast: `detachFd/protect` — Apple has no userspace fd), §4 (cross-platform synthesis: iOS is the binding constraint, ~12–15 MB budget). All sources accessed 2026-06-25.
- `04_VPN_CLD/HelixVPN-Phase0-Spike.md` [04_P0] — §6 (iOS NE memory experiment G3 + fallbacks), §9 (FFI boundary G5). `04_VPN_CLD/HelixVPN-Architecture-Refined.md` [04_ARCH] — §5.6 (iOS NE ceiling = Rust-not-Go), §5.1–§5.7 (shim matrix). `04_VPN_CLD/HelixVPN-helix-ui-Flutter.md` [04_UI] — §5/§6 (FFI surface, per-platform shim). [SYN] — §5 (client architecture), §3 (D4 overlay addressing).

Constitution: §11.4.44 (revision header), §11.4.6/§11.4.66 (decisions = options + recommendation; UNVERIFIED never fabricated), §11.4.10 (no secret leak — session token never persisted/logged), §11.4.5/§11.4.69/§11.4.107/§11.4.158/§11.4.159 (captured/window-scoped evidence; G3 RSS + on-device MP4), §11.4.169 (test-type coverage), §11.4.133 (signed privileged code / target safety).

End of nano-detail specification — Apple shim (iOS/macOS `NEPacketTunnelProvider`), Volume 4 (Clients). Pairs with [03-client §5.1] (the overview this deepens), [01-ORCH §4] (the `TunnelStatus` enum it mirrors), and [01-TT] (the carrier the core drives). Surfaced decisions: D-CLIENT-1 (iOS memory fallback), D-CLIENT-3 (binding generator), D-APPLE-1 (single-core vs dual), D-APPLE-2 (status push mechanism) — all presented, none silently resolved (§11.4.66).