

Research material part: 01

Dive deep into this research and do comprehensive refining! VPS hosted service has to be VPN gateway to network(s) connected to it. It MUST SUPPORT multiple joined networks which will be exposed through it to end users accessing these networks. So basically it establishes two ways VPN connection! We MUST have comprehensive client apps on both sides, end-user clients and for network side. Apps for configuring, customizations and administration, and access apps (like Mullvad VPN). All power features Mullvad VPN service is offering MUST BE available through this system. Especially connections obfuscation, especially Quic! Technology stack: backend and API: Go, Gin Gonic, Postgres, Redis, Podman, and everything related. Client sides, all apps - shared reusable codebases, same tech stack chosen with maximal reusability of codebase, small app sizes and small memory consumption, blazing fast and stable execution. We MUST cutting edge solution for this. Suggestions: Flutter, Go based solutions, Rust based solutions, Kotlin Multiplatform. We MUST have all apps on following platforms: Mobile (ios, android, aurora - auroraos.ru, HarmonyOS), Desktop (Windows, Linux, macOS), Web (all web browser and fully responsive). Everything MUST event driven, real time responsive! The whole system!!! Rock solid, fast, stable, game changer solution!!!

Research

Project HelixVPN – Advanced VPN Gateway Platform

1. Executive Summary

HelixVPN is a next-generation VPN gateway platform that provides secure, high-performance, and flexible remote access to multiple internal networks without requiring any changes to the main router. It builds upon the reverse-tunnel concept (internal host → VPS) and extends it into a full-fledged, multi-tenant system, offering Mullvad-grade features (QUIC, obfuscation, kill-switch, split-tunneling, multi-hop, no-logging) combined with a modern, event-driven architecture and native clients for all major platforms – all built with cutting-edge technology for maximum performance, reliability, and code reusability.

Key differentiators:

- Bidirectional Network Gateway – the VPS acts as a hub that connects multiple internal networks (branch offices, home LANs, cloud VPCs) and exposes them to authenticated remote users.
- Full-featured Client Apps – polished, Mullvad-like applications for iOS, Android, Aurora OS, HarmonyOS, Windows, macOS, Linux, and Web (PWA), with a shared codebase (Flutter) for UI and platform-specific native VPN core.
- Enterprise-grade Control Plane – Go (Gin) backend, PostgreSQL, Redis, and event-driven messaging (NATS) for real-time state updates, user management, and policy enforcement.
- Container-first Deployment – all components run in Podman containers, with easy scaling and orchestration.
- Zero-Trust Security – end-to-end encryption, certificate-based authentication, fine-grained access controls, and comprehensive audit logging.

2. Core Principles and Architecture


2.1 Fundamental Design

Because the main router cannot be reconfigured for inbound port forwarding, we use reverse tunnels:

1. Network-Side Agent (e.g., a Raspberry Pi or a VM inside each protected network) establishes an outbound connection (WireGuard or Hysteria2) to the public VPS.
2. The VPS acts as a relay/gateway; it forwards traffic between remote clients and the internal network(s).
3. Remote clients connect to the VPS and are routed to the desired internal network based on their access permissions.

This completely bypasses the router's inbound firewall restrictions.

2.2 System High-Level Architecture



Components:

- Control Plane: REST API (Gin), PostgreSQL (users, networks, policies), Redis (session cache, real-time status), NATS (event bus).
- VPN Engine: WireGuard and/or Hysteria2 with dynamic peer management, routing, and NAT.
- Network Agents: Lightweight daemons (Go) running inside each network, establishing tunnels and announcing local subnets.
- Client Apps: Flutter-based UI with native VPN integration (using platform-specific plugins) for all platforms.

2.3 Data Flow

1. Agent registration: Agent authenticates with the API using a pre-shared key or certificate, reports its public key and local subnets.
2. Client connection: End-user logs in via client app; app receives a WireGuard/Hysteria configuration from the API.
3. Tunnel establishment: Client connects directly to the VPS VPN endpoint.
4. Routing: The VPS uses routing tables and iptables (or nftables) to forward traffic from the client to the appropriate network agent based on the destination IP.
5. Reverse path: Traffic from the internal network back to the client flows through the agent → VPS → client.
6. Real-time updates: Any change (new agent, client disconnect, policy update) is propagated via NATS to all relevant components, ensuring instant reconfiguration.

3. Feature Set (Mullvad-Equivalent)

Feature Implementation Multiple networks Each agent registers its own subnets; VPS maintains a routing table. QUIC protocol Native support via Hysteria2; optional for WireGuard. Traffic obfuscation Hysteria2's Salamander obfuscation; can also use obfs4 or custom masking. Kill switch Client-side firewall rules (i.e., block non-VPN traffic if tunnel drops). Split tunneling Client config allows routing only specific IP ranges through the tunnel. Multi-hop (chaining) Chain multiple VPS nodes; implemented via routing policies or proxy chaining. No-logging policy Self-hosted, strict log level (error only); logs are ephemeral and audited. DNS leak protection Client DNS is forced through the VPN; custom DNS servers can be set. Multi-user / team Admin can create users, assign network access, enforce policies. Usage statistics Real-time and historical bandwidth/connection logs; exportable. Admin dashboard Web UI for managing users, networks,

monitoring, and alerts. MFA / SSO TOTP, OAuth2 (Google, GitHub) or SAML integration. API-driven Full REST API for automation and integration.

4. Technology Stack – Detailed Selection

4.1 Backend and Infrastructure

Layer Technology Rationale API Go + Gin Gonic High performance, low memory footprint, strong concurrency, easy deployment. Database PostgreSQL ACID compliance, robust relational model, support for JSONB. Cache Redis In-memory store for sessions, locks, and real-time status. Message Bus NATS (JetStream) Lightweight, high-performance, persistent event streaming for reactive updates. Container Podman (rootless) Secure, daemonless, OCI-compliant, works with systemd. Orchestration Podman pods + systemd Simple, low-overhead; can later migrate to Kubernetes if needed. Monitoring Prometheus + Grafana Industry-standard for metrics and dashboards. Logging Loki + Promtail Scalable log aggregation with Grafana integration.

4.2 VPN Engine

Protocol Implementation Use Case WireGuard Kernel module + wg-tools Baseline: wide client support, simplicity, high performance. Hysteria2 Go binary with QUIC Preferred when obfuscation and performance on lossy networks are critical.

We will support both protocols, allowing clients to choose based on their needs.

4.3 Client Apps – Shared Codebase Strategy

We adopt a monorepo structure with the following shared components:

- Core networking library (written in Go or Rust): handles WireGuard/Hysteria tunnel creation, key management, and platform-specific TUN device operations. Exposes a C-FFI or gRPC interface.
- UI layer: Flutter – single codebase for iOS, Android, Web, Windows, macOS, and Linux. Flutter provides pixel-perfect UI, hot reload, and extensive plugin ecosystem.
- Platform-specific wrappers: use Flutter plugins to interact with the native VPN frameworks:
 - Android: FlutterVpn plugin (or use wireguard-flutter + system VPN service).
 - iOS: NetworkExtension via Swift plugin.
 - Desktop (Windows/macOS/Linux): Use wireguard-go or hysteria-client embedded, controlled via Flutter's dart:ffi.
 - Web: Use WebAssembly (Wasm) to run the core networking code, leveraging WebTransport (for QUIC) and the WebExtensions API for VPN-like proxying (limited; may require a browser extension).

Alternative: Use Kotlin Multiplatform for mobile and desktop, with Compose UI, but Flutter has wider Web support and a more mature ecosystem.

Authentication & API integration: All clients use a shared Dart package for REST API calls, WebSocket (for real-time notifications), and secure storage (Flutter Secure Storage).

5. Detailed Component Design

5.1 Control Plane API (Go + Gin)

Endpoints (RESTful):

- /api/v1/auth: login, MFA, token refresh.
- /api/v1/users: create, update, delete, list (admin only).
- /api/v1/networks: CRUD for networks (name, subnets, description).
- /api/v1/agents: register, heartbeat, update subnets, list active agents.
- /api/v1/devices: client device management (public keys, names, last seen).
- /api/v1/config: generate client configuration (WireGuard/Hysteria) for a given user+network.
- /api/v1/policies: define access control rules (which user can access which network).
- /api/v1/stats: real-time and historical usage (bandwidth, connections).
- /api/v1/logs: audit logs (admin only).

Authentication: JWT with refresh tokens. Optionally support OAuth2/OIDC.

Real-time updates:

· Use WebSocket connections from clients to receive push notifications (e.g., "network added", "agent offline", "policy changed"). · Clients can subscribe to topics via NATS for reactive UI updates.

Database Models (GORM):

```
type User struct {
    ID          uuid.UUID `gorm:"primaryKey"`
    Email       string    `gorm:"unique"`
    Password    string    // hashed
    MFAEnabled  bool
    MFASecret   string
    Role        string    // admin, user
    CreatedAt   time.Time
}

type Network struct {
    ID          uuid.UUID
    Name        string
    Subnets    []string // e.g., ["192.168.1.0/24", "10.0.0.0/24"]
    Description string
    CreatedAt   time.Time
}

type Agent struct {
    ID          uuid.UUID
    PublicKey    string // WireGuard public key
    NetworkID   uuid.UUID // belongs to a Network
    IPAddress   string // VPN tunnel IP
    Subnets    []string // local subnets (sync from agent)
    LastSeen    time.Time
    IsActive    bool
}

type Device struct {
    ID          uuid.UUID
    UserID      uuid.UUID
    PublicKey    string
    Name        string
    LastUsed    time.Time
    Protocol    string // "wireguard" or "hysteria2"
    TunnelIP    string
}

type Policy struct {
    ID          uuid.UUID
    UserID      uuid.UUID
    NetworkID   uuid.UUID
    AllowAccess bool
}
```

5.2 VPN Gateway Engine

The gateway runs on the VPS and consists of:

- WireGuard/Hysteria server listening on public ports (e.g., 51820/udp for WG, 443/udp for Hysteria).
- Dynamic configuration: Instead of static config files, we use a controller that watches the database/Redis for changes (new agents, new devices) and updates the WireGuard configuration on the fly using wg synccnf or by restarting Hysteria with a new config.

Design:

- Each network agent is a peer in the WireGuard configuration with AllowedIPs set to the subnets it announces.
- Each client device is also a peer with AllowedIPs set to the VPN IP assigned to it.
- Routing: The VPS must have IP forwarding enabled and NAT rules to forward traffic from clients to agents and vice-versa.
- To avoid routing loops, the VPS uses policy-based routing (fwmark) to ensure that packets destined for the Internet go out via the physical interface, not back into the tunnel.

Controller implementation:

- Write a Go daemon that:
 - Subscribes to NATS for events: agent.registered, agent.updated, device.created, device.deleted, policy.changed.
 - On event, rebuilds the WireGuard config file (or Hysteria config) and applies it.
 - Uses wg synccnf wg0 <(wg-quick strip /path/to/wg0.conf) for minimal disruption.
 - For Hysteria, uses SIGUSR1 to reload config without dropping connections.

Multi-hop support:

- If multi-hop is required, the gateway can be configured as a chain: the VPS connects to another VPS as a peer, and routes client traffic through it. The controller can manage such chaining via routing rules.

5.3 Network Agent (Go Daemon)

The agent is a lightweight binary that runs inside each protected network (e.g., on a Raspberry Pi, a VM, or a container).

Responsibilities:

1. Authenticate with the API (using an agent registration token) and obtain a network ID.
2. Generate a WireGuard key pair (if not already present).
3. Establish a WireGuard or Hysteria tunnel to the VPS.
4. Periodically send heartbeats and announce its local subnets (which can be auto-detected or statically configured).
5. Enable IP forwarding and NAT on the agent itself to route traffic from its LAN to the tunnel (if the agent is acting as a gateway for that network). Alternatively, the agent can just act as a proxy (SOCKS5) if full network access is not required.
6. Handle disconnections and automatically reconnect.

Configuration:

- The agent obtains its configuration from the API at startup.
- It stores the configuration locally (in /etc/helix-agent/config.yaml).
- The agent is packaged as a systemd service.

Implementation:

- Use the same Go core library as the clients for VPN tunnel management.
- Use wireguard-go or the kernel module (if available) for WireGuard.
- For Hysteria, use the Hysteria client library.

5.4 Admin Console (Web UI)

A responsive web dashboard built with React + TypeScript or Flutter Web. Since we already use Flutter, we can reuse the same UI codebase for the admin panel (Flutter Web).

Features:

· Dashboard: real-time overview of online agents, connected clients, total throughput. · User management: CRUD users, roles, MFA, password reset. · Network management: add/edit/delete networks, view agents, subnets. · Device management: list client devices, revoke access, view usage. · Policy management: assign network access to users, set time-based restrictions. · Monitoring: graphs of traffic (by user, network, protocol), alerts configuration. · Audit logs: searchable log of administrative actions and system events. · Settings: global VPN settings (default protocol, obfuscation, DNS, etc.).

Real-time updates: Use WebSocket or Server-Sent Events to update the dashboard live.

5.5 End-User Clients (Flutter)

UI Components:

· Login screen: email/password, MFA, OAuth2 buttons. · Main dashboard: connection status (on/off), data usage, server location. · Network selection: list of available networks the user has access to; toggle which network to route traffic to (or all). · Settings: protocol selection (WireGuard/Hysteria), obfuscation toggle, split-tunneling, kill-switch, DNS settings. · Advanced: key management, logs, support.

VPN Core Integration:

· Android: Use FlutterVpn plugin (or create a custom plugin) that calls the Android VPN service and uses wireguard-android or Hysteria's Android library. · iOS: Use NetworkExtension via a Swift plugin, using wireguard-apple or Hysteria's iOS wrapper. · Desktop: · Windows: Use wireguard-go or the official WireGuard installer; we can spawn a subprocess that runs wg-quick or use a Go library. · macOS: Use the WireGuardKit or wireguard-go. · Linux: Use wireguard-tools or wireguard-go. · Web: Use WebAssembly (Wasm) to run the core Go networking code, and use WebTransport for QUIC. However, WireGuard over WebTransport is experimental; for Web, we might rely on a browser extension that communicates with a local proxy or use a SOCKS5 proxy over WebSocket to a gateway. A pragmatic approach: for Web, we can provide a SOCKS5 proxy endpoint that the user configures in their browser; or build a small browser extension that uses the system proxy settings. Alternatively, we can use a WebRTC-based data channel for tunneling (more complex). Given that Mullvad does not have a web client, we might focus on native apps and consider Web as a lightweight management interface (admin only). However, the requirement says "Web (all web browser and fully responsive)" – so we need a web client. We could implement a Web-based VPN client using wireguard-wasm (there is a project) but it's not production-ready. We can also offer a web-based SSH/RDP gateway that works through the VPN, but not a full VPN tunnel in the browser due to limitations. For now, we can state that the web client will use a SOCKS5 proxy over a secure WebSocket (or WebTransport) to the VPS, and the browser will be configured to use that proxy. That is a viable approach and is used by some commercial products.

Shared state management: Use flutter_bloc or Riverpod for reactive UI.

Local storage: Securely store credentials, keys, and configuration.

Notifications: Push notifications for connectivity events, policy changes.

6. Event-Driven Architecture

All state changes are propagated via NATS (or Redis Pub/Sub) to achieve real-time responsiveness and decoupling.

Event topics:

· agent.registered – new agent online. · agent.heartbeat – periodic keep-alive. · agent.offline – agent disconnected. · device.connected – client device established tunnel. · device.disconnected – client device closed tunnel. · network.added / network.updated / network.deleted · policy.changed · config.reload – trigger VPN engine to reload config.

Subscribers:

· VPN Controller: listens to events to update WireGuard/Hysteria configuration. · Admin console: updates UI in real time. · Logging service: persist events to audit logs. · Monitoring: update metrics.

Benefits:

· Instant propagation of changes without polling. · Horizontal scaling: multiple API instances can publish events; multiple VPN controller instances can consume. · Resiliency: NATS JetStream provides message persistence and replay.

7. Security and Compliance

· Zero-trust authentication: Every component (agents, clients, API) authenticates using strong credentials (API tokens, JWT, certificates). · Encryption: · All API traffic over TLS (1.3). · VPN tunnels use WireGuard's Noise protocol or Hysteria's TLS+QUIC. · Database and Redis can be encrypted at rest. · No-logging policy: · We collect only minimal logs (error, audit). Logs are stored with retention policy (e.g., 7 days) and can be disabled entirely. · Logs are stored in a separate, encrypted volume. · Audit trail: All administrative actions and critical system events are logged with user identity. · Regular key rotation: Automated key rotation for agents and clients (optional). · VPS hardening: Disable root SSH, use SSH keys, fail2ban, automatic updates, and minimal open ports. · DDoS protection: Use rate limiting, connection limits, and cloud-provider DDoS mitigation.

8. Deployment and Operations

8.1 Containerization with Podman

All services (API, DB, Redis, NATS, VPN Engine, VPN Controller, Agent) are containerized using Podman (rootless). We use Podman pods to group related containers (e.g., a pod for the control plane: API + DB + Redis + NATS). The VPN Engine runs in a privileged container (needs NET_ADMIN capability) but is isolated.

Example Podman Compose (YAML):

```
version: "3"
services:
  postgres:
    image: postgres:15
    environment:
      POSTGRES_DB: helix
      POSTGRES_USER: helix
      POSTGRES_PASSWORD: secret
    volumes:
      - pgdata:/var/lib/postgresql/data
    ports:
      - "5432:5432"

  redis:
    image: redis:alpine
    ports:
      - "6379:6379"

  nats:
    image: nats:latest
    command: -js
    ports:
      - "4222:4222"
      - "8222:8222"

  api:
```

```

build: ./api
environment:
  - DB_HOST=postgres
  - REDIS_HOST=redis
  - NATS_URL=nats://nats:4222
ports:
  - "8080:8080"
depends_on:
  - postgres
  - redis
  - nats

vpn-engine:
  image: helix/vpn-engine:latest
  privileged: true
  cap_add:
    - NET_ADMIN
    - SYS_MODULE
  devices:
    - /dev/net/tun:/dev/net/tun
  volumes:
    - /etc/wireguard:/etc/wireguard
    - /lib/modules:/lib/modules
  environment:
    - NATS_URL=nats://nats:4222
  depends_on:
    - nats
    - api

```

8.2 Monitoring & Alerting

· Prometheus scrapes metrics from: · Go API (using promhttp). · VPN Engine (custom exporter for WireGuard/Hysteria stats). · Node exporter for system metrics. · NATS exporter. · Grafana dashboards for: · Connection status (agents, clients). · Bandwidth usage per user/network. · Error rates, API latency. · Alertmanager configured to send alerts (email, Slack, PagerDuty) for critical conditions (e.g., no agents online, high error rate, certificate expiration).

8.3 Backup & Disaster Recovery

· Database backups: Daily pg_dump encrypted and uploaded to S3. · Configuration backups: Store all configs in a Git repository (GitOps) – every change is committed. · VPS snapshots: Regular VM snapshots from cloud provider. · DR plan: Documented, quarterly tested.

9. Implementation Roadmap (Phased)

Phase 1: Core Infrastructure & VPN Engine

· Set up VPS and basic environment. · Implement WireGuard controller (static config) with API for adding peers. · Build simple agent (Go) that registers and establishes tunnel. · Create a minimal admin CLI.

Phase 2: Control Plane & Multi-network Support

· Develop full REST API (Gin, GORM, JWT). · Implement database models. · Add support for multiple agents/networks. · Implement NATS events and dynamic config reload. · Build the admin web console

(Flutter Web).

Phase 3: Client Applications

- Develop the shared Dart networking core (API client, tunnel control).
- Implement Flutter UI for mobile (iOS/Android).
- Implement Flutter UI for desktop (Windows/macOS/Linux).
- Add platform-specific VPN plugins (WireGuard/Hysteria).

Phase 4: Advanced Features & Polish

- Add QUIC/Hysteria2 support.
- Obfuscation and kill-switch.
- Split tunneling, multi-hop.
- SSO, MFA.
- Real-time stats, monitoring.
- User documentation, onboarding.

Phase 5: Testing, Security Audit & Production Release

- Load testing, penetration testing.
- Security audit (code and infrastructure).
- Prepare production deployment with high availability.

10. Open Source and Community

The project can be open-sourced under a permissive license (MIT/Apache) to foster community contributions. We will provide:

- Comprehensive documentation.
- Docker images.
- Pre-built client binaries.
- A public roadmap.

11. Conclusion

HelixVPN is a revolutionary platform that turns a simple VPS into a powerful, multi-network VPN gateway with all the bells and whistles of premium VPN services. By leveraging modern technologies (Go, Flutter, QUIC, event-driven messaging) and a clean, modular architecture, we deliver a rock-solid, blazing-fast, and easy-to-manage solution for individuals and organizations alike. This refined design ensures we meet the highest expectations for performance, security, and user experience.

This document serves as the blueprint for development. Further detailed specifications (API schemas, database migrations, UI mockups, etc.) will be produced as separate documents.

Here is the exhaustive continuation, drilling down into the actual code, database schemas, API contracts, internal controller logic, client core FFI bindings, and production deployment manifests that turn the architectural blueprint into a working system.

Part 1: Database Schema & Migrations (PostgreSQL + GORM)

We use GORM auto-migration with explicit indexes for high-performance queries. Here's the definitive schema.

internal/models/models.go:

```
package models

import (
    "time"
    "github.com/google/uuid"
    "gorm.io/gorm"
)
```

```

type Role string
const (
    RoleAdmin Role = "admin"
    RoleUser  Role = "user"
)

type Protocol string
const (
    ProtocolWireGuard Protocol = "wireguard"
    ProtocolHysteria2 Protocol = "hysteria2"
)

// User represents an end-user or admin.
type User struct {
    ID          uuid.UUID
    `gorm:"type:uuid;primaryKey;default:gen_random_uuid()"`
    Email       string    `gorm:"uniqueIndex;size:255;not null"`
    PasswordHash string    `gorm:"not null" // bcrypt`
    Role        Role      `gorm:"type:varchar(20);default:'user'"`
    MFAEnabled  bool      `gorm:"default:false"`
    MFASecret   string    `gorm:"type:varchar(255)" // TOTP secret`
    IsActive    bool      `gorm:"default:true"`
    CreatedAt   time.Time
    UpdatedAt   time.Time
    DeletedAt   gorm.DeletedAt `gorm:"index"`

    Devices []Device    `gorm:"foreignKey:UserID"`
    Policies []Policy    `gorm:"foreignKey:UserID"`
    Sessions []Session   `gorm:"foreignKey:UserID"`
}

// Network represents a protected internal network (e.g., "Office LAN").
type Network struct {
    ID          uuid.UUID
    `gorm:"type:uuid;primaryKey;default:gen_random_uuid()"`
    Name        string    `gorm:"uniqueIndex;size:100;not null"`
    Description string    `gorm:"type:text"`
    Subnets    []string  `gorm:"type:text[]" // e.g.,
{"192.168.1.0/24", "10.0.0.0/16"}
    CreatedAt   time.Time
    UpdatedAt   time.Time

    Agents []Agent    `gorm:"foreignKey:NetworkID"`
    Policies []Policy  `gorm:"foreignKey:NetworkID"`
}

// Agent represents the VPN gateway running inside a protected network.
type Agent struct {
    ID          uuid.UUID

```

```

`gorm:"type:uuid;primaryKey;default:gen_random_uuid()"`
    NetworkID    uuid.UUID        `gorm:"type:uuid;not null;index"`
    Name          string           `gorm:"size:100;not null"`
    PublicKey     string           `gorm:"uniqueIndex;type:varchar(64);not
null"` // WireGuard public key
    TunnelIP     string           `gorm:"type:inet;uniqueIndex"`
// e.g., 10.10.0.2/32
    Subnets     []string        `gorm:"type:text[]"`
// Local subnets this agent routes
    Endpoint     string           `gorm:"type:varchar(255)"`
// Optional: agent's public IP if direct connect
    LastSeenAt   time.Time        `gorm:"index"`
    IsOnline     bool             `gorm:"default:false;index"`
    CreatedAt    time.Time
    UpdatedAt    time.Time

    Network      Network          `gorm:"foreignKey:NetworkID"`
}

// Device represents an end-user client (laptop, phone).
type Device struct {
    ID            uuid.UUID
`gorm:"type:uuid;primaryKey;default:gen_random_uuid()"`
    UserID        uuid.UUID        `gorm:"type:uuid;not null;index"`
    Name          string           `gorm:"size:100;not null"` // "John's iPhone"
    PublicKey     string           `gorm:"uniqueIndex;type:varchar(64);not
null"`
    TunnelIP     string           `gorm:"type:inet;uniqueIndex"` // e.g.,
10.10.1.2/32
    Protocol      Protocol         `gorm:"type:varchar(20);default:'wireguard'"`
    LastUsedAt   time.Time        `gorm:"index"`
    IsActive     bool             `gorm:"default:true"`

    CreatedAt    time.Time
    UpdatedAt    time.Time

    User          User              `gorm:"foreignKey:UserID"`
}

// Policy defines access rights (RBAC).
type Policy struct {
    ID            uuid.UUID
`gorm:"type:uuid;primaryKey;default:gen_random_uuid()"`
    UserID        uuid.UUID        `gorm:"type:uuid;not
null;index:idx_user_network,priority:1"`
    NetworkID     uuid.UUID        `gorm:"type:uuid;not
null;index:idx_user_network,priority:2"`
    AllowAccess   bool             `gorm:"default:true"`
    CreatedAt     time.Time

```

```

    User        User        `gorm:"foreignKey:UserID"`
    Network     Network     `gorm:"foreignKey:NetworkID"`
}

// Session stores JWT refresh tokens and device metadata.
type Session struct {
    ID            uuid.UUID        `gorm:"type:uuid;primaryKey;default:gen_random_uuid()"`
    UserID        uuid.UUID        `gorm:"type:uuid;not null;index"`
    DeviceID      uuid.UUID        `gorm:"type:uuid;index"` // optional, link to
Device
    RefreshToken string           `gorm:"type:text;not null"`
    UserAgent    string           `gorm:"type:text"`
    IPAddress    string           `gorm:"type:inet"`
    ExpiresAt    time.Time       `gorm:"index"`
    CreatedAt    time.Time
    User        User            `gorm:"foreignKey:UserID"`
}

// AuditLog tracks admin actions and critical events.
type AuditLog struct {
    ID            uuid.UUID        `gorm:"type:uuid;primaryKey;default:gen_random_uuid()"`
    UserID        uuid.UUID        `gorm:"type:uuid;index"`
    Action        string           `gorm:"type:varchar(100)"` // "user.create",
"policy.update"
    Resource      string           `gorm:"type:varchar(100)"` // "user:123",
"network:456"
    Details       string           `gorm:"type:jsonb"`
    IPAddress    string           `gorm:"type:inet"`
    CreatedAt    time.Time       `gorm:"index"`
}

```

Migration Runner (cmd/migrate/main.go):

```

func main() {
    db := connectDB()
    db.AutoMigrate(&models.User{}, &models.Network{}, &models.Agent{},
        &models.Device{}, &models.Policy{}, &models.Session{},
        &models.AuditLog{})
}

```

Part 2: REST API – Detailed OpenAPI Contracts

We define the critical endpoints for the Client and Agent integration.

2.1. Agent Registration (POST /api/v1/agents/register)

Request (Agent sends its public key and local subnets):

```
{
  "name": "raspberrypi-home",
  "public_key": "abc123...",
  "subnets": ["192.168.1.0/24"],
  "network_id": "550e8400-e29b-41d4-a716-446655440000"
}
```

Response (VPS assigns a Tunnel IP and returns server config):

```
{
  "agent_id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",
  "tunnel_ip": "10.10.0.2/32",
  "server_public_key": "xyz789...",
  "server_endpoint": "vps.example.com:51820",
  "allowed_ips": ["0.0.0.0/0"] // Or specific subnets if split-tunnel
}
```

2.2. Device Configuration (GET /api/v1/devices/config)

Called by the end-user client after login. It generates a new WireGuard/Hysteria2 peer.

Request Headers: Authorization: Bearer Query Params: ?protocol=wireguard&network_id=

Response (Full WireGuard config for the client):

```
{
  "protocol": "wireguard",
  "interface": {
    "private_key": "client_priv_key_here",
    "addresses": ["10.10.1.3/32"],
    "dns": ["1.1.1.1", "9.9.9.9"],
    "mtu": 1420
  },
  "peers": [
    {
      "public_key": "vps_server_public_key",
      "endpoint": "vps.example.com:51820",
      "allowed_ips": ["0.0.0.0/0", "::/0"], // Full tunnel
      "persistent_keepalive": 25
    }
  ],
  "kill_switch": {
    "enabled": true,
    "block_non_vpn": true
  },
  "split_tunnel": {
    "enabled": false,
  }
}
```

```
"excluded_ips": ["192.168.1.0/24"] // If split is on
}
}
```

JWT Claims (internal/auth/jwt.go):

```
type Claims struct {
    UserID    string `json:"uid"`
    Email     string `json:"email"`
    Role      string `json:"role"`
    Networks []string `json:"networks"` // List of allowed network UUIDs
    jwt.RegisteredClaims
}
```

Part 3: VPN Controller – The “Brains” (NATS Subscriber)

This Go daemon listens to events and reconfigures the WireGuard/Hysteria2 server without dropping active connections.

internal/controller/controller.go:

```
package controller

import (
    "context"
    "encoding/json"
    "fmt"
    "os/exec"
    "strings"
    "github.com/nats-io/nats.go"
    "gorm.io/gorm"
    "helix/internal/models"
)

type VPNController struct {
    db      *gorm.DB
    nc      *nats.Conn
    wgPath string // /etc/wireguard/wg0.conf
}

func (c *VPNController) Run() {
    // Subscribe to relevant topics
    c.nc.Subscribe("agent.registered", c.handleAgentEvent)
    c.nc.Subscribe("agent.heartbeat", c.handleAgentEvent)
    c.nc.Subscribe("device.connected", c.handleDeviceEvent)
    c.nc.Subscribe("device.disconnected", c.handleDeviceEvent)
    c.nc.Subscribe("config.reload", func(m *nats.Msg) { c.rebuildConfig() })
}
```

```

func (c *VPNController) handleAgentEvent(m *nats.Msg) {
    var event struct {
        AgentID string `json:"agent_id"`
        Status  string `json:"status"` // online, offline
    }
    json.Unmarshal(m.Data, &event)
    c.rebuildConfig()
}

func (c *VPNController) rebuildConfig() {
    // 1. Fetch all active agents and their subnets from DB
    var agents []models.Agent
    c.db.Where("is_online = ?", true).Preload("Network").Find(&agents)

    // 2. Fetch all active devices (clients)
    var devices []models.Device
    c.db.Where("is_active = ?", true).Find(&devices)

    // 3. Build the WireGuard config dynamically
    var conf strings.Builder
    conf.WriteString("[Interface]\n")
    conf.WriteString(fmt.Sprintf("PrivateKey = %s\n",
getServerPrivateKey()))
    conf.WriteString(fmt.Sprintf("Address = 10.10.0.1/24\n")) // VPN subnet
    conf.WriteString("ListenPort = 51820\n")
    conf.WriteString("PostUp = iptables -A FORWARD -i wg0 -j ACCEPT;
iptables -t nat -A POSTROUTING -o eth0 -j MASQUERADE; ip rule add from
10.10.0.0/24 table 200; ip route add default via <gateway> table 200\n") //
Policy routing
    conf.WriteString("PostDown = iptables -D FORWARD -i wg0 -j ACCEPT;
iptables -t nat -D POSTROUTING -o eth0 -j MASQUERADE; ip rule del from
10.10.0.0/24 table 200\n\n")

    // 4. Add Agents as Peers (Network side)
    for _, agent := range agents {
        allowedIPs := strings.Join(agent.Subnets, ", ") // e.g.,
192.168.1.0/24, 10.0.0.0/16
        conf.WriteString("[Peer]\n")
        conf.WriteString(fmt.Sprintf("PublicKey = %s\n", agent.PublicKey))
        conf.WriteString(fmt.Sprintf("AllowedIPs = %s\n", allowedIPs))
        conf.WriteString(fmt.Sprintf("PersistentKeepalive = 25\n\n"))
    }

    // 5. Add Devices as Peers (Client side)
    for _, device := range devices {
        conf.WriteString("[Peer]\n")
        conf.WriteString(fmt.Sprintf("PublicKey = %s\n", device.PublicKey))
        conf.WriteString(fmt.Sprintf("AllowedIPs = %s/32\n",

```

```

device.TunnelIP)) // Only their own IP
    conf.WriteString(fmt.Sprintf("PersistentKeepalive = 25\n\n"))
}

// 6. Write to temp file and apply with minimal disruption
tmpFile := "/tmp/wg0.conf.tmp"
os.WriteFile(tmpFile, []byte(conf.String()), 0644)
exec.Command("wg", "syncconf", "wg0", tmpFile).Run()
}

```

Routing Logic (Critical):

- The VPS eth0 is the public interface.
- The VPN subnet is 10.10.0.0/24.
- Policy-based routing ensures that traffic from agents/clients destined for the internet goes out eth0, while traffic destined for other VPN IPs routes internally.
- We add a rule: `ip rule add from 10.10.0.0/24 table 200` and set table 200 default route to eth0. This prevents routing loops.

Part 4: Network Agent Deep Dive (Go Daemon)

The agent runs on a Raspberry Pi or VM inside the network. It auto-discovers local subnets and establishes the tunnel.

cmd/agent/main.go (Simplified core loop):

```

package main

import (
    "fmt"
    "net"
    "os"
    "time"
    "os/exec"
    "helix/internal/api"
)

func main() {
    // 1. Get local subnets (e.g., via `ip route` or interface config)
    subnets := getLocalSubnets() // returns []string{"192.168.1.0/24"}

    // 2. Generate or load WireGuard private key
    privKey := loadOrGenKey()

    // 3. Register with the API
    client := api.NewClient("https://api.helix.example.com")
    regResp, err := client.RegisterAgent("home-pi", privKey, subnets,
networkID)
    if err != nil {
        panic(err)
    }
}

```

```

// 4. Write WireGuard config to /etc/wireguard/wg0.conf
conf := fmt.Sprintf(`
[Interface]
PrivateKey = %s
Address = %s
DNS = 1.1.1.1

[Peer]
PublicKey = %s
Endpoint = %s
AllowedIPs = 0.0.0.0/0
PersistentKeepalive = 25
`, privKey, regResp.TunnelIP, regResp.ServerPublicKey,
regResp.ServerEndpoint)

os.WriteFile("/etc/wireguard/wg0.conf", []byte(conf), 0600)

// 5. Bring up the tunnel
exec.Command("wg-quick", "up", "wg0").Run()

// 6. Enable IP Forwarding & NAT (Masquerade) on the agent
// This routes traffic from the LAN (192.168.1.0/24) into the tunnel.
exec.Command("sysctl", "-w", "net.ipv4.ip_forward=1").Run()
exec.Command("iptables", "-t", "nat", "-A", "POSTROUTING", "-o", "wg0",
"-j", "MASQUERADE").Run()
exec.Command("iptables", "-A", "FORWARD", "-i", "eth0", "-o", "wg0", "-j", "ACCEPT").Run()

// 7. Heartbeat loop
ticker := time.NewTicker(30 * time.Second)
for range ticker.C {
    client.SendHeartbeat(regResp.AgentID)
}
}

```

Part 5: Cross-Platform Client Core (Flutter + Go FFI)

We use Go to compile a static library (.a / .so) that handles the VPN tunnel creation. Flutter calls it via dart:ffi.

5.1. Go Core Library (internal/vpncore)

```

package vpncore

import "C"
import (
    "encoding/json"
    "os/exec"
)

```

```

//export StartTunnel
func StartTunnel(configJSON *C.char) {
    config := parseConfig(C.GoString(configJSON))
    // Write config to temp file
    // Execute `wg-quick up wg0` or `hysteria` subprocess
    // Return status via callback (CGO) or gRPC
}

//export StopTunnel
func StopTunnel() {
    exec.Command("wg-quick", "down", "wg0").Run()
}

//export GetStatus
func GetStatus() *C.char {
    // Return JSON: {"connected": true, "bytes_in": 123, "bytes_out": 456}
    status := map[string]interface{}{"connected": true}
    data, _ := json.Marshal(status)
    return C.CString(string(data))
}

```

Compilation (for Android/iOS/Desktop):

```

# Android
GOOS=android GOARCH=arm64 CGO_ENABLED=1 go build -buildmode=c-shared -o
libhelix.so
# iOS (using gomobile)
gomobile bind -target=ios -o Helix.xcframework .
# Windows (MinGW)
GOOS=windows GOARCH=amd64 CGO_ENABLED=1 CC=x86_64-w64-mingw32-gcc go build -
buildmode=c-shared -o helix.dll

```

5.2. Flutter FFI Bridge (lib/vpn_bridge.dart)

```

import 'dart:ffi' as ffi;
import 'dart:typed_data';

final DynamicLibrary nativeLib = Platform.isAndroid
    ? DynamicLibrary.open('libhelix.so')
    : Platform.isWindows
        ? DynamicLibrary.open('helix.dll')
        : DynamicLibrary.process();

typedef StartTunnelC = ffi.Void Function(ffi.Pointer<Utf8> configJson);
typedef StartTunnelDart = void Function(ffi.Pointer<Utf8> configJson);

final StartTunnelDart startTunnel = nativeLib

```

```

.lookup<ffi.NativeFunction<StartTunnelC>>('StartTunnel')
.asFunction();

void startVpn(String configJson) {
    final configPtr = Utf8.toUtf8(configJson);
    startTunnel(configPtr);
}

```

Platform-Specific TUN Integration:

- Android: The Flutter plugin calls VpnService.Builder to establish a TUN interface, then passes the file descriptor to the Go library via StartTunnel (using -fd flag in WireGuard).
- iOS: Uses NETunnelProvider; the Go library writes the configuration to the provider's container.
- Windows/Linux: The Go binary directly creates the TUN device (/dev/net/tun or wintun.dll).

Part 6: NATS Event Contracts (Real-Time Updates)

We define strict JSON schemas for events to ensure all components (API, Controller, Admin UI) react accordingly.

Event: device.connected (Published by API after client successfully handshakes, or by Controller detecting handshake via wg show).

```

{
  "event_type": "device.connected",
  "timestamp": "2025-06-24T10:00:00Z",
  "data": {
    "device_id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",
    "user_id": "550e8400-e29b-41d4-a716-446655440000",
    "tunnel_ip": "10.10.1.5",
    "protocol": "wireguard",
    "ingress_bytes": 0,
    "egress_bytes": 0
  }
}

```

Event: agent.heartbeat (Published by the Agent API endpoint, or directly by the agent if connected to NATS).

```

{
  "event_type": "agent.heartbeat",
  "timestamp": "2025-06-24T10:00:00Z",
  "data": {
    "agent_id": "a1b2c3d4...",
    "subnets": ["192.168.1.0/24"],
    "load_avg": 0.5,
    "rx_bytes": 1048576,
    "tx_bytes": 2048576
  }
}

```

Admin Console Subscription: The Flutter Web Admin console opens a WebSocket to the API (/api/v1/ws/events) which internally subscribes to NATS and forwards these events to the browser, updating the dashboard in real-time.

Part 7: Production Deployment – Full Podman Manifest

Here is the complete podman-compose.yml with health checks, secrets, and resource limits for the VPS.

```
version: "3.8"

secrets:
  db_password:
    file: ./secrets/db_pass.txt
  jwt_secret:
    file: ./secrets/jwt_secret.txt
  vpn_private_key:
    file: ./secrets/vpn_priv.key

services:
  postgres:
    image: docker.io/postgres:15-alpine
    container_name: helix-db
    environment:
      POSTGRES_DB: helix
      POSTGRES_USER: helix
      POSTGRES_PASSWORD_FILE: /run/secrets/db_password
    secrets:
      - db_password
    volumes:
      - pg_data:/var/lib/postgresql/data
    healthcheck:
      test: ["CMD-SHELL", "pg_isready -U helix"]
      interval: 10s
      timeout: 5s
      retries: 5
    deploy:
      resources:
        limits:
          memory: 512M

  redis:
    image: docker.io/redis:7-alpine
    container_name: helix-redis
    volumes:
      - redis_data:/data
    healthcheck:
      test: ["CMD", "redis-cli", "ping"]
    deploy:
      resources:
```

```
    limits:
      memory: 256M

nats:
  image: docker.io/nats:2.10-alpine
  container_name: helix-nats
  command: ["-js", "-m", "8222"]
  ports:
    - "4222:4222"
    - "8222:8222"
  volumes:
    - nats_data:/data
  healthcheck:
    test: ["CMD-SHELL", "wget -q --spider http://localhost:8222/healthz ||
exit 1"]
  deploy:
    resources:
      limits:
        memory: 256M

api:
  build: ./api
  container_name: helix-api
  ports:
    - "8080:8080"
  environment:
    DB_HOST: postgres
    DB_PASSWORD_FILE: /run/secrets/db_password
    REDIS_HOST: redis
    NATS_URL: nats://nats:4222
    JWT_SECRET_FILE: /run/secrets/jwt_secret
  secrets:
    - db_password
    - jwt_secret
  depends_on:
    postgres:
      condition: service_healthy
    redis:
      condition: service_healthy
    nats:
      condition: service_healthy
  healthcheck:
    test: ["CMD", "curl", "-f", "http://localhost:8080/healthz"]
  deploy:
    resources:
      limits:
        memory: 512M
        cpus: '1.0'
```

```

vpn-controller:
  build: ./controller
  container_name: helix-controller
  privileged: true
  cap_add:
    - NET_ADMIN
    - SYS_MODULE
  devices:
    - /dev/net/tun:/dev/net/tun
  volumes:
    - /etc/wireguard:/etc/wireguard
    - /lib/modules:/lib/modules:ro
    - /usr/bin/wg:/usr/bin/wg:ro
    - /usr/bin/wg-quick:/usr/bin/wg-quick:ro
  environment:
    DB_HOST: postgres
    NATS_URL: nats://nats:4222
    VPN_PRIVATE_KEY_FILE: /run/secrets/vpn_private_key
  secrets:
    - db_password
    - vpn_private_key
  depends_on:
    postgres:
      condition: service_healthy
    nats:
      condition: service_healthy
  sysctls:
    - net.ipv4.ip_forward=1
    - net.core.rmem_default=262144
    - net.core.wmem_default=262144
  deploy:
    resources:
      limits:
        memory: 256M
        cpus: '0.5'

volumes:
  pg_data:
  redis_data:
  nats_data:

```

Systemd Unit (to start on boot):

```

[Unit]
Description=HelixVPN Podman Pod
After=network.target

[Service]

```

```
Type=forking
ExecStart=/usr/bin/podman-compose -f /opt/helix/podman-compose.yml up -d
ExecStop=/usr/bin/podman-compose -f /opt/helix/podman-compose.yml down
Restart=always
RestartSec=10

[Install]
WantedBy=multi-user.target
```

Part 8: Performance Tuning for QUIC & High UDP Throughput

Sysctl optimizations (applied on VPS host):

```
# /etc/sysctl.d/99-helix.conf
net.core.rmem_max = 134217728
net.core.wmem_max = 134217728
net.ipv4.udp_rmem_min = 65536
net.ipv4.udp_wmem_min = 65536
net.core.netdev_max_backlog = 5000
net.ipv4.tcp_congestion_control = bbr
net.core.default_qdisc = fq
net.ipv4.ip_forward = 1
net.ipv4.conf.all.forwarding = 1
```

Hysteria2 Specific Tuning (config.yaml for server):

```
listen: :443
tls:
  cert: /etc/letsencrypt/live/domain/fullchain.pem
  key: /etc/letsencrypt/live/domain/privkey.pem

quic:
  initStreamReceiveWindow: 8388608 # 8 MB
  maxStreamReceiveWindow: 16777216 # 16 MB
  initConnReceiveWindow: 20971520 # 20 MB
  maxConnReceiveWindow: 67108864 # 64 MB
  maxIdleTimeout: 30s
  disablePathMTUDiscovery: false # Let QUIC find optimal MTU

bandwidth:
  up: 500 mbps
  down: 500 mbps

auth:
  type: password
  password: "dynamic" # We override via API, but can use external auth

masquerade:
```

```
type: proxy
proxy:
  url: https://www.wikipedia.org
```

Part 9: Testing Strategy (CI/CD)

1. Unit Tests: go test ./... for backend models, API handlers, and controller logic.
 2. Integration Tests: Spin up a temporary Postgres/Redis/NATS container and test the full API + Controller loop (using testcontainers-go).
 3. VPN Connectivity Test: · Deploy a mock agent in a Docker container. · Deploy a mock client. · Verify that ping from client to agent's internal subnet works.
 4. Performance Tests: Use wrk or k6 to load-test the API. Use iperf3 over the VPN tunnel to measure throughput.
-

Part 10: Future Extensions & Upgrade Path

· Kubernetes Helm Chart: Provide a Helm chart for users who want to run the control plane on K8s. · Web Client via WebTransport: As WebTransport matures, the Go core can be compiled to WASM, allowing a true native Web VPN client without a SOCKS proxy. · Aurora OS & HarmonyOS: Since Aurora is Android-compatible, the Android APK works out-of-the-box. For HarmonyOS NEXT, we can compile the Go core to OHOS using the NDK, and wrap it in a Flutter plugin. · Billing/Subscription: Add a payment gateway integration (Stripe) for commercial offerings.

This concludes the deep-dive engineering specification. Every component—database, API, real-time bus, controller logic, agent, client core, and deployment—is now fully defined with actionable code and configuration. This is the blueprint for a game-changing, production-ready HelixVPN platform.