

# workable\_items\_loader.py

## workable\_items\_loader.py

Revision: 1 Last modified: 2026-06-26T15:30:00Z

### Overview

Parses the four HelixVPN WBS Markdown documents and their subtask deepening companions, then populates the §11.4.93 SQLite single-source-of-truth at docs/workable\_items.db. This is the **md-to-db** direction of the bidirectional sync contract.

### Prerequisites

- Python 3.10+ (stdlib only — no external packages)
- SQLite 3 (via Python's sqlite3 module)
- The WBS source docs must exist at their canonical paths

### Usage

```
# Full load (clears + re-creates all items)
python3 scripts/workable_items_loader.py

# Dry run (prints what would be loaded)
python3 scripts/workable_items_loader.py --dry-run
```

### Inputs

| File           | Phase | Path                                           |
|----------------|-------|------------------------------------------------|
| Phase 0<br>WBS | P0    | docs/research/mvp/final/06-phase0-spike-wbs.md |
|                | P1    | docs/research/mvp/final/07-phase1-mvp-wbs.md   |

| File            | Phase | Path                                                          |
|-----------------|-------|---------------------------------------------------------------|
| Phase 1<br>WBS  |       |                                                               |
| Phase 2<br>WBS  | P2    | docs/research/mvp/final/08-phase2-parity-wbs.md               |
| Phase 3<br>WBS  | P3    | docs/research/mvp/final/09-phase3-reach-wbs.md                |
| P1<br>deepening | P1    | docs/research/mvp/final/v07-execution/subtask-deepening-p1.md |
| P2<br>deepening | P2    | docs/research/mvp/final/v07-execution/subtask-deepening-p2.md |
| P3<br>deepening | P3    | docs/research/mvp/final/v07-execution/subtask-deepening-p3.md |

## Output

- docs/workable\_items.db — SQLite database with tables: items, item\_history, test\_diary, gates, operator\_block\_details, obsolete\_details, meta

## Item counts (expected)

| Phase        | Epics/Milestones | Tasks      | Subtasks   | Total      |
|--------------|------------------|------------|------------|------------|
| P0           | 9                | 27         | —          | 36         |
| P1           | 15               | 65         | 130        | 210        |
| P2           | 11               | 54         | 77         | 142        |
| P3           | 8                | 35         | 53         | 96         |
| <b>Total</b> | <b>43</b>        | <b>181</b> | <b>260</b> | <b>484</b> |

## Parsing patterns

- **Phase 0 tasks:** ### TASK HVPN-P0-NNN – Title headings
- **Phase 1+ tasks:** – \*\*HVPN-P1-NNN – Title.\*\* inline bold format
- **Epics:** ## N. E01 – Title or ## N. Milestone S0 – Title
- **Subtasks:** Table rows in deepening docs:
  - | .k | Title | Acceptance | Tests | Cx |

# Field extraction

Fields are extracted from task body text using regex patterns:

- • module: <name> → module
- • gate: G1 → gate
- • type: Task|Feature|Bug → type
- • deps: HVPN-P1-001 → deps (JSON array)
- • effort: M(5) or • effort: 3 days → effort\_days
- • tests: UNIT,INT → test\_types (normalized to canonical §11.4.169 codes)

## Cross-references

- Constitution §11.4.93 (SQLite-backed SSoT)
- Constitution §11.4.95 (DB tracked in git)
- Constitution §11.4.54 (HVPN-Pn-NNN id convention)
- Spec: v07-execution/workable-items-model.md
- Go replacement: cmd/workable-items/ (HVPN-P1-150)