

pki service

pki service

Revision: 2 Last modified: 2026-07-04T12:00:00Z Rev 2: §2.3
CA rotation split into two DISTINCT paths — scheduled (safe, 24h overlap) vs. compromise (fast, zero-overlap, force-revoke+re-enroll every device chaining through the compromised issuing CA) — the prior revision conflated both under one overlap window, which would have kept a compromised CA trusted for up to 24h. Wired the AuthDevice hot path (§8.2) to reject a compromised-status issuer regardless of leaf not_after; added ErrIssuingCACompromised (§10.1) and the ca.issuing.compromised event (§9.1). Added a KMS/signer-unavailability blast-radius + mitigation note (§2.3) closing an unstated availability dependency (a KMS outage longer than the renew-skew window cascades into fleet-wide expiry).

Master technical specification — Volume 3 (Control Plane, Go), service internal/pki. This document is the **nano-detail deepening** of [02-control-plane §9 (Identity, enrollment & PKI)] for the pki module: the tenant CA hierarchy, short-lived (~24h) mTLS device certificates (issue / auto-renew / revoke), the device WireGuard public-key registry (private key never leaves the device), the rotation schedule and on-revoke behaviour, and the optional post-quantum (ML-KEM) pre-shared material. SPEC ONLY — it describes the implementation; it does not build the product. Evidence cited inline by id: [04_P1 §n] = HelixVPN-Phase1-MVP.md; [04_ARCH §n] = HelixVPN-Architecture-Refined.md; [research-pki_pq_nat §n] = the cited PKI/PQ/NAT research; [02-CP §n] = 02-control-plane.md; [SYNTHESIS §n] = the cross-doc synthesis. Unproven facts are marked **UNVERIFIED** per constitution §11.4.6.

1. Scope, position & governing invariants

1.1 What this service owns

internal/pki is the credential-lifecycle authority of the control plane. It owns **three** durable concerns and **one** ephemeral concern:

#	Concern	Durable?	Owns table(s)
O1	Tenant CA hierarchy — per-tenant root + issuing-CA key material + chain	yes	ca_keys
O2	Short-lived mTLS device certificates — issue / auto-renew / revoke	yes	device_certs (extended from [02-CP §2.2])
O3	WireGuard public-key registry — bind 32-byte Curve25519 <i>public</i> key to a device; the private key never leaves the device (C6)	yes	device_wg_keys
O4	PQ pre-shared material (optional) — ML-KEM-derived PSK metadata fed into the WG handshake	yes (metadata only)	device_pq_material

It does **not** own: device rows (registry), overlay-IP allocation (ipam), policy visibility (policy), enroll-token mint/consume (identity), or the data-path WG peer config (the Rust edge, doc 01). It exposes its capabilities to those modules through the PKI interface (§4.1) and emits events on the bus (§9); it never imports another module's store (R1 of [02-CP §1.2]).

1.2 The WireGuard reality this design is built around

WireGuard has **no native PKI**: one Curve25519 keypair per device, the **public key IS the device identity**, access = adding the peer's public key to the peer set, and **revocation is structurally trivial** — remove the public key and the device is instantly cut off; there is no CA, cert expiry, CRL, OCSP, or enrollment protocol in WireGuard itself [research-pki_pq_nat

§1.1]. Therefore the cert/PKI lifecycle, granular revocation, and rotation are built **around** WireGuard, not inside it [research-pki_pq_nat §1.1].

The chosen pattern is the SPIFFE/SPIRE-style **two-identity split** [research-pki_pq_nat §1.2]:

1. a **long-lived device-attestation cert** (a CA-signed leaf proving "I am a genuine enrolled device of tenant T"), and
2. a **short-lived mTLS credential** (the per-device control-channel cert, "I am authorised to call the control API right now"), auto-rotated by the agent before expiry.

Revocation therefore has two cooperating teeth (belt-and-suspenders, the dominant 2025 model) [research-pki_pq_nat §1.2/§1.3]:

- **(a) stop renewing** the short-lived mTLS cert → it self-expires within its TTL, AND
- **(b) remove the WG public key** from every peer set → instant data-path cutoff.

1.3 Governing invariants (every clause below obeys these)

#	Invariant	Source
P1	Device private keys never leave the device. The control plane receives and stores only the 32-byte WG <i>public</i> key.	[02-CP C6], [research-pki_pq_nat §1.3]
P2	Short-lived control-channel certs. Default device-cert TTL $\approx$ 24h ([04_P1 §6.3]); agent auto-renews ahead of expiry; revocation latency target == the < 1 s convergence SLO.	[04_P1 §6.3], [02-CP §9.3/§10.2]
P3	The tenant CA key is the one true secret. Back it by KMS/HSM or offline; it + Postgres are the only stateful things to protect. Never git-tracked, never logged (§11.4.10).	[04_P1 §6.3], [04_ARCH §10]
P4	Hybrid-never-PQ-only PQ. PQ is a PSK fed into WG (Mullvad/Rosenpass pattern), classical X25519 + ML-KEM; never a forked WG handshake, never PQ-only.	[research-pki_pq_nat §2.1/§2.4], [SYNTHESIS §4 Ph2]
P5	Default-deny, fail-closed. A revoked or expired credential never authenticates; an unknown serial is rejected, not trusted.	[02-CP C4], [04_P1 §7.3]
P6		

#	Invariant	Source
	Every credential mutation emits a bus event (R3) so coordinator and audit react without polling.	[02-CP §1.2 R3/§5.3]
P7	Tenant-isolated at the DB. Every pki table is RLS-scoped under FORCE ROW LEVEL SECURITY and accessed only via store.WithTenant (C8).	[02-CP §2.3]

2. CA hierarchy

2.1 The three-tier model (per tenant)

Each tenant gets its **own** isolated certificate hierarchy — there is no shared global root (multi-tenant isolation reaches into the trust anchor, not just the row filter).

[MERMAID RENDER FAILED — block #1]

- **Tenant Root CA** — Ed25519, validity ~10y, basicConstraints CA:TRUE, pathlen:1, keyUsage = keyCertSign,cRLSign. **Held offline or in KMS/HSM** (P3); used exactly once per tenant to sign the issuing CA, then sealed. Its private key never touches the request path.
- **Issuing CA (intermediate)** — Ed25519, validity ~1y, CA:TRUE, pathlen:0. This is the **online** signer helixd/pki actually uses; rotating or compromising it does not require re-establishing the root. Stored encrypted at rest (KMS data key or sealed file under /var/lib/helix/ca, [02-CP §11.1 Volume=helix-ca]).
- **Device leaves** — Ed25519:
 - **Control-channel mTLS leaf** (O2): TTL ≈ 24h (P2), CA:FALSE, EKU = clientAuth + serverAuth, SAN = SPIFFE URI spiffe://<tenant_id>/device/<device_id> [research-pki_pq_nat §1.2 — structured URI bound at issuance, not IP/hostname].
 - **Device-attestation leaf** (optional, O1 companion): TTL ≈ 90d, proves genuine enrollment; TPM / Secure-Enclave-bound when the platform exposes it [research-pki_pq_nat §1.2]. **Phase-1 status:** the attestation leaf is *modelled and schema-provisioned* but the hardware-binding path is **Phase 2** — Phase 1 issues the mTLS leaf only and treats the device row + consumed enroll token as the attestation surrogate. Marked so honestly per §11.4.6; do not claim hardware attestation ships in Phase 1.

Key-algorithm choice — Ed25519 for all CA + leaf signing. Rationale: small keys, fast sign/verify, no parameter pitfalls, broad TLS 1.3 support. **UNVERIFIED** whether every target platform's mTLS stack (HarmonyOS Network Kit, Aurora Qt TLS) accepts Ed25519 client certs; if a platform rejects them, that tenant's issuing CA MAY be provisioned as ECDSA-P256 instead — the `ca_keys.key_alg` column (§3.1) carries the choice so the issuer is algorithm-agnostic. This is a per-tenant provisioning decision, not a code branch in the hot path.

2.2 Chain delivery & verification

- The `EnrollResponse` (§8.1) ships the device leaf **plus the issuing-CA cert** so the agent can build and pin the chain root→issuing→leaf.
- The agent pins the **tenant root CA** public key (delivered once at enroll, embedded in the bootstrap bundle) and verifies every future leaf/issuing cert against it — so a rogue control plane cannot substitute a different root.
- The control plane (Connect server) verifies the **client** leaf against the tenant's issuing CA on every handshake (§8.2) — mutual.

2.3 CA rotation — two DISTINCT paths (scheduled vs. compromise) — Enterprise Hardening

These are not the same operation and MUST NOT share the same overlap window. An earlier revision of this document treated "scheduled ~annually" and "on suspected compromise" as one path with a shared 24h trust-overlap; that is wrong — a compromised issuing CA must be distrusted immediately, never carried through a grace period during which the attacker (or anyone holding the leaked key) could still mint valid-looking leaves. The two paths now diverge at the `ca_keys.status` transition:

- **(a) Scheduled rotation (safe, has overlap).** Cadence ~annually, or ahead of the issuing CA's own `not_after`. The root signs a *new* issuing CA (`status='active'`); the *old* issuing CA is marked `status='retiring'` and **both remain trusted** for an overlap window = max device-cert TTL (24h) + renew-sweeper margin so every in-flight 24h leaf signed by the old CA remains valid until it naturally expires or renews under the new CA. After the window, `status='retired'`. This is the path modelled in §2.1/§2.2.
- **(b) Compromise rotation (fast, NO overlap, P3/P5).** Triggered by `RevokeReason ::=compromise-class` evidence (leaked `key_sealed`/KMS credential, HSM tamper alert, unexplained cert issuance the audit log cannot attribute). The compromised issuing CA is flipped **directly to `status='compromised'`** (the

terminal `ca_keys.status` value already present in the §3.1 DDL enum but previously undocumented in this rotation prose — it is now load-bearing, not vestigial) — **zero overlap**: `AuthDevice` (§8.2) is extended to reject any leaf whose `issuing_ca_id` resolves to a compromised row, regardless of the leaf's own `not_after` (P5 fail-closed — an unexpired-but-compromised-issuer leaf is untrusted the instant the flip commits). The root immediately signs a *new* issuing CA (`status='active'`) and **every device whose active cert chains through the compromised CA is force-revoked and re-enrolled** — not renewed, because renewal reuses the device's *existing* cert-issuance path which itself ran through the compromised signer; re-enrollment via a fresh `Enroll` (or an operator-driven bulk `helixvpctl ca reissue-affected --ca <id>`) is the only path that provably re-establishes trust from the new CA. **Blast-radius bound**: the compromise event is scoped to the *tenant* whose `ca_keys` row was compromised (per-tenant CA hierarchy, §2.1) — no cross-tenant blast radius. **Time-to-full-recovery** = `device count × reissue round-trip` (§10.3, <150ms) , parallelized; a fleet of 10k devices re-issues in well under a minute of pure compute, gated in practice by how fast each agent's control channel reconnects with the new CA's chain (bounded by the agent's own reconnect/backoff policy, out of pki's control).

- **Root-CA rotation** (rare, multi-year, unaffected by the a/b split above): cross-sign the new root with the old during a long overlap; **operator-gated** (§11.4.66 / §11.4.101 — irreversible, high blast radius, cannot be auto-decided). Phase-1 spec models the schema + the manual `helixvpctl ca rotate-root` path; automation is Phase 2. A compromised **root** (as opposed to the online issuing CA) is the catastrophic case: it invalidates the tenant's entire trust anchor, including any still-valid issuing CA it signed. Recovery requires **operator-driven, out-of-band re-establishment of trust** (a brand-new root + a fresh enrollment bundle re-distributed to every device by the operator, since the agent's pinned root, §2.2, can no longer be updated *through* the now-untrusted channel) — this is why P3 mandates the root key be the most tightly protected secret in the system and why root rotation is never autonomous.

KMS / signer unavailability — the resilience gap this closes

`CASigner` (§4.3) is a hard dependency for **every** issuance and renewal (§5.2/§6.2). If the KMS backend (or the sealed-file decryption path) is unreachable for longer than the renew skew window (~4.8h before a 24h leaf's expiry, §6.1), devices approaching expiry start failing `RenewDeviceCert` and — once past `not_after` — fail `AuthDevice` (P5 fail-closed), losing their control channel fleet-wide as leaves expire on a rolling basis. This is a genuine availability dependency the earlier revision did not name. **Mitigations (operational, not a code change to this spec):**

(1) the signer backend (KMS/HSM) MUST carry its own HA/SLA appropriate to the fleet's cert TTL — a KMS outage budget of < renewSkew ($\approx 4.8h$ for the default 24h TTL) keeps the fleet inside its existing grace margin; a longer TTL (e.g. 7d, within the [minTTL,maxTTL] clamp, §5.2) buys more outage tolerance at the cost of a slower revocation-by-non-renewal fallback; (2) helix_pki_certs_expired_total (§6.3) climbing is the leading alert — page on any sustained increase, not just on ErrNoActiveCA; (3) the file-sealed backend (§4.3) has no external-service dependency once the KMS-wrapped data key is cached in memory at boot — it degrades gracefully to "control-plane-process-availability only," which is why it is the recommended default for the self-hosted/homelab primary buyer (SPECIFICATION.md §2) who has no KMS/HSM budget; a managed KMS is the enterprise-tier upgrade for regulatory key-custody requirements, not a Phase-1 requirement.

3. Data model (DDL + RLS)

Extends [02-CP §2.2]. Three new tables (ca_keys, device_wg_keys, device_pq_material) + the **extended** device_certs. Every table is tenant-scoped and RLS-forced (P7).

3.1 ca_keys — the CA hierarchy

```
CREATE TYPE ca_tier AS ENUM ('root','issuing');
CREATE TYPE ca_status AS ENUM
    ('active','retiring','retired','compromised');
CREATE TYPE key_alg AS ENUM ('ed25519','ecdsa_p256');

CREATE TABLE ca_keys (
    id          uuid PRIMARY KEY DEFAULT gen_random_uuid(),
    tenant_id   uuid NOT NULL REFERENCES tenants(id) ON DELETE
                CASCADE,
    tier         ca_tier NOT NULL,
    status      ca_status NOT NULL DEFAULT 'active',
    key_alg     key_alg NOT NULL DEFAULT 'ed25519',
    parent_id   uuid REFERENCES ca_keys(id),           -- NULL for
                root; root.id for issuing
    cert_pem    text NOT NULL,                         -- the CA
                certificate (public)
    subject_skid bytea NOT NULL,                        -- Subject
                Key Identifier (chain build)
    -- PRIVATE KEY HANDLING (P3): exactly one of the two is set,
    -- never the raw key in cleartext col.
    key_ref     text,                                   -- KMS/HSM
                key URN when KMS-backed
    key_sealed  bytea,                                  -- envelope-
                encrypted DER (KMS data key) when file-backed
    not_before  timestampz NOT NULL,
```



```

renewed_from uuid REFERENCES device_certs(id),           -- chain:
               predecessor on rotation
revoked_at    timestampz,
revoked_reason text,                                   -- closed-
               set §10.2 reason code
created_at    timestampz NOT NULL DEFAULT now(),
UNIQUE (tenant_id, serial)
);
-- hot path: resolve a presented serial to a LIVE cert in 0(1)
CREATE UNIQUE INDEX device_certs_serial_live
  ON device_certs (tenant_id, serial) WHERE status = 'active';
-- at most one ACTIVE mTLS cert per device (renew flips the old to
  'renewed')
CREATE UNIQUE INDEX one_active_mtls_per_device
  ON device_certs (device_id) WHERE usage = 'mtls' AND status =
    'active';
CREATE INDEX ON device_certs (tenant_id, device_id) WHERE status
  = 'active';
CREATE INDEX ON device_certs (tenant_id, not_after) WHERE status
  = 'active'; -- renew sweeper (§6.3)

```

3.3 device_wg_keys — the WG public-key registry (C6/P1)

The WG identity is separated from the cert lifecycle: a device's WG public key changes on WG-key rotation (§7) independently of its 24h mTLS cert.

```

CREATE TABLE device_wg_keys (
  id          uuid PRIMARY KEY DEFAULT gen_random_uuid(),
  tenant_id   uuid NOT NULL REFERENCES tenants(id) ON DELETE
              CASCADE,
  device_id   uuid NOT NULL REFERENCES devices(id) ON DELETE
              CASCADE,
  wg_pubkey   bytea NOT NULL,
              -- 32-byte Curve25519 PUBLIC key (NEVER private, P1)
  active      boolean NOT NULL DEFAULT true,
  rotated_from uuid REFERENCES device_wg_keys(id),
  created_at  timestampz NOT NULL DEFAULT now(),
  retired_at  timestampz,
  CONSTRAINT wg_pubkey_len32 CHECK (octet_length(wg_pubkey) = 32),
  UNIQUE (tenant_id, wg_pubkey)
);
-- exactly one active WG key per device (rotation overlaps then
  retires the old)
CREATE UNIQUE INDEX one_active_wg_key_per_device
  ON device_wg_keys (device_id) WHERE active;

```

devices.wg_pubkey from [02-CP §2.2] remains the *denormalised current* pubkey (a cache of the active row here) so coordinator.buildMap reads one table; device_wg_keys is the authoritative history + rotation ledger. A trigger (or the pki write path inside one WithTenant tx) keeps

devices.wg_pubkey == the active row. The 32-byte CHECK is the structural guarantee a private key (also 32 bytes for Curve25519 — so length alone cannot distinguish) is never *accepted*: the API contract names the field wg_pubkey, the agent generates the pair locally and transmits only the public half (P1), and a §1.1 mutation test asserts the enroll/rotate handlers reject any payload that is not the agent-derived public key (verified by re-deriving the public key from a known private in the test fixture and asserting the stored value equals the *public*, never the private).

3.4 device_pq_material — optional PQ PSK metadata (P4)

PQ is a **PSK fed into WG** [research-pki_pq_nat §2.1]; the control plane stores only the **metadata** needed to coordinate PSK derivation, **never** the PSK itself nor any PQ private key (the PSK is established peer-to-peer / device↔gateway, ephemerally).

```
CREATE TYPE pq_kem AS ENUM
    ('none', 'x25519_mlkem768', 'x25519_mlkem768_mceliece');
```

```
CREATE TABLE device_pq_material (
    id          uuid PRIMARY KEY DEFAULT gen_random_uuid(),
    tenant_id   uuid NOT NULL REFERENCES tenants(id) ON DELETE
                CASCADE,
    device_id   uuid NOT NULL REFERENCES devices(id) ON DELETE
                CASCADE,
    kem         pq_kem NOT NULL DEFAULT 'none',
    mlkem_pubkey bytea, -- ML-
                KEM-768 encapsulation (PUBLIC) key, ~1184B
    psk_epoch   bigint NOT NULL DEFAULT 0, --
                monotonic; bumps on each PSK rotation (§7.3)
    last_rotated timestampz,
    enabled     boolean NOT NULL DEFAULT false,
    created_at  timestampz NOT NULL DEFAULT now(),
    CONSTRAINT pq_pubkey_when_enabled CHECK (NOT enabled OR
        mlkem_pubkey IS NOT NULL),
    UNIQUE (tenant_id, device_id)
);
```

Stored: the device's ML-KEM **public** encapsulation key + the PSK epoch counter + the negotiated KEM suite. **Never stored:** the derived PSK, the ML-KEM decapsulation (private) key, the X25519 private half. The actual PSK is mixed into the WG handshake at the endpoints (P4); the control plane only *coordinates which suite + which epoch* applies, and ships the peer's mlkem_pubkey inside the network map so two endpoints can encapsulate to each other.

Phase-1 default kem='none', enabled=false (PQ is Phase 2 in the roadmap, [SYNTHESIS §4]) — the table + plumbing exist so enabling it is config, not a schema change.

3.5 RLS (identical pattern, all four tables)

```
-- applied to ca_keys, device_certs, device_wg_keys,
    device_pq_material:
ALTER TABLE device_certs ENABLE ROW LEVEL SECURITY;
ALTER TABLE device_certs FORCE ROW LEVEL SECURITY; -- applies
    even to the owner (C8)
CREATE POLICY tenant_isolation ON device_certs
    USING      (tenant_id = current_setting('app.tenant_id')::uuid)
    WITH CHECK (tenant_id = current_setting('app.tenant_id')::uuid);
-- helixd connects as helix_app (non-superuser, non-owner); RLS is
    the floor under RBAC.
```

All pki DB access runs through store.WithTenant (R4, [02-CP §2.3]); the CA signing read of ca_keys for the *active issuing* CA runs inside the same tenant tx as the cert insert so issuance is atomic with its audit row.

4. Go interface & type surface

4.1 The PKI interface (extends [02-CP §1.3])

```
// internal/pki/iface.go
package pki

import (
    "context"
    "crypto/x509"
    "time"
    "github.com/google/uuid"
)

type PKI interface {
    // --- CA lifecycle (01) ---
    ProvisionTenantCA(ctx context.Context, t uuid.UUID, opt
        CAOptions) (CAChain, error)
    RotateIssuingCA(ctx context.Context, t uuid.UUID) (CAChain,
        error)

    // --- device mTLS certs (02) ---
    IssueDeviceCert(ctx context.Context, in IssueInput) (Cert,
        error) // enroll path
    RenewDeviceCert(ctx context.Context, in RenewInput) (Cert,
        error) // auto-renew (§6)
    Revoke(ctx context.Context, deviceID uuid.UUID, reason
        RevokeReason) error // < 1s (P2/§9.3)
```

```

AuthDevice(ctx context.Context, leaf *x509.Certificate)
    (AuthedDevice, error) // hot path (§8.2)

// --- WG public-key registry (03/C6) ---
RegisterWGKey(ctx context.Context, deviceID uuid.UUID, pub
    WGPublicKey) error
RotateWGKey(ctx context.Context, deviceID uuid.UUID, newPub
    WGPublicKey) (WGRotation, error)
ActiveWGKey(ctx context.Context, deviceID uuid.UUID)
    (WGPublicKey, error)

// --- optional PQ material (04/P4) ---
SetPQMaterial(ctx context.Context, deviceID uuid.UUID, m
    PQMaterial) error
RotatePSKEpoch(ctx context.Context, deviceID uuid.UUID)
    (int64, error)
}

```

4.2 Concrete types

// internal/pki/types.go

```

type CAOptions struct {
    KeyAlg      KeyAlg      // ed25519 (default) | ecdsa_p256
    RootTTL     time.Duration // ≈ 10y
    IssuingTTL  time.Duration // ≈ 1y
    KMSKeyRef   string       // non-empty => KMS-backed (P3);
                else file-sealed
}

type KeyAlg uint8
const ( KeyAlgEd25519 KeyAlg = iota; KeyAlgECDSAP256 )

type CACHain struct {
    RootCertPEM    []byte
    IssuingCertPEM []byte
    IssuingCAID    uuid.UUID
}

type IssueInput struct {
    TenantID uuid.UUID
    DeviceID uuid.UUID
    TTL      time.Duration // default 24h (P2); clamped to
                [maxRenewSkew, 7d]
    SPIFFE   string       // spiffe://<tenant>/device/<device>
}

type RenewInput struct {
    TenantID uuid.UUID
    DeviceID uuid.UUID
    PriorCert
        uuid.UUID // device_certs.id being renewed (chain via
                renewed_from)
    TTL      time.Duration
}

```

```

type Cert struct {
    ID          uuid.UUID
    Serial      string
    SPIFFE      string
    LeafPEM     []byte
    IssuingPEM []byte      // chain for the agent
    NotBefore   time.Time
    NotAfter    time.Time
}

type AuthedDevice struct {
    DeviceID uuid.UUID
    TenantID uuid.UUID
    CertID   uuid.UUID
    Revoked  bool      // belt-and-suspenders: caller still
              rejects (P5)
    Expired  bool
}

type WGPublicKey [32]byte      // Curve25519 PUBLIC key only
              (P1)

type WGRotation struct {
    OldKey, NewKey WGPublicKey
    RotatedAt      time.Time
}

type PQMaterial struct {
    KEM      PQKem      // none | x25519_mlkem768 |
              x25519_mlkem768_mceliece
    MLKEMPubKey []byte      // ML-KEM-768 encapsulation
              (public) key (~1184B)
    Enabled    bool
}

type PQKem uint8
const ( PQNone PQKem = iota; PQX25519MLKEM768;
        PQX25519MLKEM768McEliece )

type RevokeReason uint8
const (
    RevokeManual RevokeReason = iota // operator/Console action
    RevokeCompromise                // suspected key compromise
    RevokeSuperseded                 // replaced by re-enroll
    RevokeDeprovision                // device decommissioned
)

```

4.3 The signer seam (KMS vs file)

```

// internal/pki/signer.go – the CA-key signing seam; the private
// key never leaves the
// chosen backend's trust boundary (P3). Same interface for both
// backends.

```

```

type CASigner interface {
    // Sign produces an X.509 leaf for tmpl signed by the tenant's
    // active issuing CA.
    Sign(ctx context.Context, t uuid.UUID, tmpl
        *x509.Certificate, leafPub crypto.PublicKey) ([]byte,
            error)
}
// kmsSigner: tmpl digest sent to KMS Sign API; raw key stays in
// the HSM/KMS.
// fileSigner: key_sealed envelope-decrypted into a locked,
// zeroed-after buffer.

```

5. Certificate issuance — state machine & flow

5.1 Device-cert lifecycle state machine

[MERMAID RENDER FAILED — block #2]

5.2 Issuance algorithm (enroll path)

IssueDeviceCert runs inside the same WithTenant tx as the enroll device-insert ([02-CP §9.2]) so a half-enrolled device with a cert but no row cannot exist.

```

func (s *Service) IssueDeviceCert(ctx context.Context, in
    IssueInput) (Cert, error) {
    if in.TTL == 0 { in.TTL = 24 * time.Hour }           // P2
    // default
    if in.TTL < minTTL || in.TTL > maxTTL {              //
        // [renewSkew, 7d] — fail-closed (P5)
        return Cert{}, ErrCertTTLOutOfRange
    }
    var out Cert
    err := s.store.WithTenant(ctx, in.TenantID, func(q
        *db.Queries) error {
        ca, err := q.ActiveIssuingCA(ctx, in.TenantID)    // FOR
        // SHARE
        if err != nil { return ErrNoActiveCA }           // §10.2
        serial := randSerial(20)                         // 20
        // random bytes
        tmpl := leafTemplate(in.SPIFFE, serial, time.Now(),
            in.TTL) // ECU clientAuth+serverAuth
        leafPEM, err := s.signer.Sign(ctx, in.TenantID, tmpl,
            in.LeafPub)
        if err != nil { return err }
        row, err := q.InsertDeviceCert(ctx, db.InsertCertParams{
            TenantID: in.TenantID, DeviceID: in.DeviceID,
            IssuingCaID: ca.ID,
            Usage: "mtls", Serial: serial, SpiffeUri: in.SPIFFE,

```

```

        Fingerprint: sha256DER(leafPEM), CertPem: leafPEM,
        NotBefore: tmpl.NotBefore, NotAfter: tmpl.NotAfter,
    })
    if err != nil { return err } //
    unique-idx violation => bug, surfaced
    if err := q.InsertAudit(ctx, audit("cert.issued",
    in.DeviceID, serial)); err != nil {
        return err
    }
    out = Cert{ID: row.ID, Serial: serial, SPIFFE: in.SPIFFE,
    LeafPEM: leafPEM,
        IssuingPEM: ca.CertPem, NotBefore: tmpl.NotBefore,
    NotAfter: tmpl.NotAfter}
    return nil
})
if err != nil { return Cert{}, err }
_, _ = s.bus.Publish(ctx, "events:devices",
    events.New("cert.issued",
    in.TenantID, "system", map[string]any{"device_id":
    in.DeviceID, "serial": out.Serial}))
return out, nil
}

```

5.3 Enroll → issue sequence (the device never surrenders its private key, P1)

[MERMAID RENDER FAILED — block #3]

6. Auto-renew (the ~24h cadence)

6.1 Who drives renewal

The **agent** drives renewal over the **existing authenticated channel** ([04_P1 §6.3], [research-pki_pq_nat §1.2 — auto-rotated by the agent before expiry]). It renews at **T – renewSkew** where $\text{renewSkew} = \max(1h, 0.2 \times \text{TTL}) \rightarrow$ for a 24h TTL the agent renews ~4.8h before expiry, giving generous margin for a flapping link. The renew RPC is authenticated by the *current still-valid* leaf, so renewal never needs the enroll token again.

6.2 Renew RPC + algorithm

```

func (s *Service) RenewDeviceCert(ctx context.Context, in
    RenewInput) (Cert, error) {
    // caller (api/coordinator) has already AuthDevice'd the
    // CURRENT leaf (P5).
    return s.issueRenew(ctx, in) // same tx shape as §5.2 but:
    // - new leaf inserted Active

```

```

// - q.MarkCertRenewed(priorCertID) flips prior -> 'renewed'
//   (one_active_mtls_per_device holds)
// - renewed_from = priorCertID (chain)
// - WG pubkey unchanged (renewal != WG rotation; those are
//   independent, §7)
// - audit "cert.renewed"; bus "cert.renewed"
}

```

Renewal does **not** rotate the WG key and does **not** interrupt the open WatchNetworkMap stream (the stream keeps using the still-valid old leaf until the agent reconnects with the new one; both leaves are valid during the overlap because the old is only flipped to renewed — AuthDevice accepts renewed for the remainder of its not_after to avoid a mid-stream cutoff). This is the **only** non-active status AuthDevice tolerates, and only until the old not_after.

6.3 Server-side expiry sweeper (safety net, not the primary path)

A background sweeper (one per helixd, leader-elected via a Redis lock so N replicas don't duplicate) runs every 60s:

```

-- mark leaves whose not_after has passed and that were never
   renewed
UPDATE device_certs SET status='expired'
WHERE status='active' AND not_after < now();

```

An expired-but-still-streaming device is force-reconnected (its AuthDevice now fails → the stream is closed by the next keepalive boundary). The sweeper is a **safety net** — the agent's proactive renewal (§6.1) is the primary path; the sweeper only catches agents that went away. helix_pki_certs_expired_total counts sweeps for the §10 SLO.

6.4 Renew sequence

[MERMAID RENDER FAILED — block #4]

7. WG public-key registry & rotation

7.1 Registration (C6/P1)

RegisterWGKey stores the 32-byte Curve25519 **public** key as the device's active WG identity. The private key was generated on the device and is never transmitted [research-pki_pq_nat §1.3]. The active row also denormalises into devices.wg_pubkey so coordinator.buildMap reads one table ([02-CP §6.2]).

7.2 WG-key rotation (overlap-then-retire)

WG-key rotation is independent of cert renewal (a device can keep its 24h-cert cadence while rotating its WG key on a slower schedule or on demand):

```
func (s *Service) RotateWGKey(ctx context.Context, deviceID
    uuid.UUID, newPub WGPublicKey) (WGRotation, error) {
    // one tx: insert newPub active, mark old retired
    (rotated_from set), update devices.wg_pubkey
    // emit wg.key.rotated -> coordinator pushes a MapDelta
    replacing the peer's wg_pubkey to
    // EVERY node that may reach this device (need-to-know, C4).
    Edge swaps the WG peer key.
}
```

Overlap window: because the data path is hub-and-spoke through the gateway in MVP ([02-CP §6.2]), the gateway holds both old+new WG peer keys for a short window (default 30s) so in-flight handshakes complete, then drops the old — preventing a momentary blackout. The window is UNVERIFIED as a tuned value; it MUST be validated by the §10 rotation soak (no dropped sessions across rotation) before being treated as fact.

7.3 PQ PSK epoch rotation (when enabled, P4)

When `device_pq_material.enabled`, the PSK is rotated by bumping `psk_epoch` and re-publishing the peer ML-KEM public keys in the network map; the endpoints re-derive a fresh PSK via X25519+ML-KEM-768 encapsulation and mix it into the WG handshake [research-pki_pq_nat §2.1/§2.4]. Rosenpass-style aggressive rotation refreshes the symmetric key every ~2 min [research-pki_pq_nat §2.3]; HelixVPN's control-plane role is only to bump the epoch + ship the public keys — **the PSK itself is never seen by the control plane** (P4). Cadence is a tenant setting; the default when enabled is epoch bump on WG-key rotation + a slow timer (Phase-2 tuning).

8. Protobuf & API surface

8.1 Protobuf additions (helix.coordinator.v1)

Extends the [02-CP §4] Coordinator service (package `helix.coordinator.v1`, unified across the set). PKI adds `RenewCert` + `RotateWGKey` RPCs and `PQ/chain` fields:

```

// proto/helix/coordinator/v1/coordinator.proto (package
// helix.coordinator.v1)

service Coordinator {
    // ... Enroll, WatchNetworkMap, AdvertisePrefixes, ReportStatus
    // from [02-CP §4] ...

    // Auto-renew the short-lived mTLS device cert over the EXISTING
    // channel (P2/§6).
    rpc RenewCert(RenewCertRequest) returns (RenewCertResponse);

    // Rotate the device WG public key (independent of cert renewal,
    // §7.2).
    rpc RotateWGKey(RotateWGKeyRequest) returns
        (RotateWGKeyResponse);
}

message EnrollResponse { // extends [02-CP §4]
    string device_id = 1;
    string overlay_ip = 2;
    bytes device_cert = 3; // short-lived mTLS leaf
                           (DER)
    bytes issuing_ca =
        4; // issuing-CA cert so the agent builds
           the chain (§2.2)
    bytes root_ca = 5; // tenant root CA to PIN
                    (verify future leaves, §2.2)
    GatewayInfo gateway = 6;
    PQParams pq = 7; // PQ suite the tenant
                    negotiated (none in Ph1)
}

message RenewCertRequest {
    string device_id = 1;
    bytes new_leaf_pub = 2; // device-generated leaf
                           PUBLIC key (private stays local, P1)
}

message RenewCertResponse {
    bytes device_cert = 1; // new 24h leaf
    bytes issuing_ca = 2;
    int64 not_after_unix = 3;
}

message RotateWGKeyRequest { string device_id = 1; bytes
    new_wg_pubkey = 2; } // 32B public (P1)
message RotateWGKeyResponse { bool accepted = 1; }

message PQParams {
    enum Kem { KEM_NONE = 0; KEM_X25519_MLKEM768 = 1;
        KEM_X25519_MLKEM768_MCELIECE = 2; }
    Kem kem = 1;
    bytes mlkem_pubkey = 2; // peer's ML-KEM-768
                           encapsulation key when enabled (P4)
    int64 psk_epoch = 3;
}

```

```

}

// Peer (extends [02-CP §4]) gains the peer's PQ public material
// so endpoints can encapsulate.
message Peer {
    string device_id      = 1;
    bytes  wg_pubkey      = 2;
    repeated string allowed_ips = 3;
    string endpoint       = 4;
    bool   is_connector   = 5;
    repeated Via6Route via6 = 6;
    PQParams pq           = 7;           // present only when the
                                        // tenant has PQ enabled (P4)
}

```

RenewCert and RotateWGKey carry only **public** key bytes (P1).
 buf generate emits Go/Dart/Rust stubs from this one file —
 the agent's renewal logic cannot drift from the server's
 expectation ([02-CP §4]).

8.2 Hot-path device authentication (AuthDevice)

Every agent RPC (WatchNetworkMap/AdvertisePrefixes/ReportStatus/RenewCert/ RotateWGKey) is authenticated by the presented mTLS leaf. AuthDevice resolves the leaf to a device and applies fail-closed checks (P5):

```

func (s *Service) AuthDevice(ctx context.Context, leaf
    *x509.Certificate) (AuthedDevice, error) {
    serial := serialHex(leaf.SerialNumber)
    // 1. chain: verify leaf against the tenant issuing CA (root
    // pinned client-side, §2.2)
    if err := s.verifyChain(ctx, leaf); err != nil { return
        AuthedDevice{}, ErrCertChainInvalid }
    // 2. resolve serial -> live cert row (unique idx
    // device_certs_serial_live, §3.2)
    row, err := s.lookupBySerial(ctx, serial) // accepts
    // status active OR (renewed && now<not_after)
    if err != nil { return AuthedDevice{},
        ErrCertUnknownSerial } // unknown => reject (P5)
    if row.Status == "revoked" { return AuthedDevice{},
        ErrCertRevoked }
    if time.Now().After(row.NotAfter) { return AuthedDevice{},
        ErrCertExpired }
    // 2b. COMPROMISE FAST-PATH (§2.3(b)): reject regardless of
    // not_after – an issuer flip
    // to 'compromised' is a zero-overlap distrust event, unlike
    // scheduled 'retiring' (§2.3(a)).
    if s.issuingCAStatus(ctx, row.IssuingCaID) == "compromised" {
        return AuthedDevice{}, ErrIssuingCACompromised
    }
    // 3. SPIFFE URI in leaf SAN must match the resolved device
    // (binding, not just serial)
}

```

```

if leaf.URIs[0].String() != row.SpiffeUri { return
    AuthedDevice{}, ErrSpiffeMismatch }
return AuthedDevice{DeviceID: row.DeviceID, TenantID:
    row.TenantID, CertID: row.ID}, nil
}

```

issuingCAStatus reads the in-memory CA-status cache (same pattern as the §8.2 revoke cache — hydrated at boot, invalidated on ca.issuing.rotated/a new ca.issuing.compromised event, §9.1) so the compromise check costs no DB round-trip on the hot path. ErrIssuingCACompromised maps to Connect PermissionDenied / HTTP 403 (§10.1) and triggers the same force-close + re-enroll flow as ErrCertRevoked from the caller's perspective.

A **fast revocation cache** (in-memory map[serial]struct{} of revoked serials, hydrated from device_certs WHERE status='revoked' on boot and updated by the device.revoked event) lets AuthDevice reject a revoked serial without a DB round-trip on the hot path — the cache is the data structure that makes the **< 1 s** revocation SLO (§10) achievable on open streams.

8.3 REST + authz (admin/operator/console surfaces)

Route	admin	operator	member	Effect
POST /v1/devices/{id}/revoke	✓	✗	✗	Revoke() → device.revoked (§9.3)
POST /v1/devices/{id}/rotate-wg	✓	✓	✗	RotateWGKey()
GET /v1/devices/{id}/certs	✓	✓	own	list cert lifecycle (audit)
POST /v1/ca/rotate-issuing	✓	✗	✗	RotateIssuingCA()
POST /v1/ca/rotate-root	✓	✗	✗	operator-gated (§2.3, §11.4.66)
POST /v1/tenants/{id}/pq	✓	✗	✗	enable/disable PQ suite

RBAC gates the route; RLS is the database floor even if RBAC is misconfigured (defense in depth, [02-CP §8.1]). Agent RPCs use device mTLS (§8.2); Enroll is the only unauthenticated RPC (it validates a single-use hashed enroll token, [02-CP §8.2]).

9. Events & revocation convergence

9.1 Event envelopes (bus-agnostic, [02-CP §5.2])

```
{ "id": "<stream-id>", "type": "cert.issued", "tenant_id": "uuid",  
  "ts": "RFC3339",  
  "actor": "user-uuid|system", "trace_id": "...", "payload":  
    {"device_id": "uuid", "serial": "hex"} }
```

Type	Stream	Payload	Coordinator / consumer reaction
cert.issued	events:devices	{device_id, serial}	audit; no map change (issue is paired with device.enrolled)
cert.renewed	events:devices	{device_id, serial, prior_serial}	audit; revocation cache unaffected
device.revoked	events:devices	{device_id, serial, reason}	remove node; push peer-removal MapDelta to everyone who saw it; edge drops WG peer; add serial to revoke cache (§8.2)
wg.key.rotated	events:devices	{device_id, old_pub, new_pub}	push MapDelta replacing the peer wg_pubkey to all nodes that may reach it (C4)
pq.psk.rotated	events:devices	{device_id, psk_epoch}	push updated PQParams to relevant peers (when PQ enabled)
ca.issuing.rotated	events:gateway		

Type	Stream	Payload	Coordinator / consumer reaction
ca.issuing.compromised	events:gateway	{tenant_id, old_ca, new_ca}	extend trust set during overlap window (§2.3(a) scheduled path only)
		{tenant_id, ca_id, new_ca_id}	zero-overlap distrust: invalidate the in-memory CA-status cache entry immediately (§8.2), force-close every open agent stream whose cert chains through ca_id, drive bulk re-enrollment (§2.3(b))

9.2 Revocation algorithm (the two teeth, P5)

```

func (s *Service) Revoke(ctx context.Context, deviceID uuid.UUID,
    reason RevokeReason) error {
    var serial string
    err := s.store.WithTenant(ctx, tenantOf(ctx), func(q
        *db.Queries) error {
        // tooth (a): stop renewing – mark the LIVE mtls cert
        // revoked (self-expiry safety net)
        c, err := q.RevokeActiveCert(ctx,
            db.RevokeParams{DeviceID: deviceID,
                Reason: reason.String(), RevokedAt: time.Now()})
        if err != nil { return err }
        serial = c.Serial
        // tooth (b): retire the WG key so the data path is cut
        // even before TTL
        if err := q.RetireWGKey(ctx, deviceID); err != nil {
            return err }
        return q.InsertAudit(ctx, audit("device.revoke",
            deviceID, reason.String()))
    })
    if err != nil { return err }
    s.revokeCache.Add(serial)                                //
        instant hot-path reject (§8.2)
    _, err = s.bus.Publish(ctx, "events:devices",
        events.New("device.revoked",

```

```

        tenantOf(ctx), actorOf(ctx), map[string]any{
            "device_id": deviceID, "serial": serial, "reason":
            reason.String()})})
    return err
}

```

9.3 Revoke → enforced sequence (< 1 s, P2)

[MERMAID RENDER FAILED — block #5]

10. Error taxonomy & SLOs

10.1 Error taxonomy (Connect/gRPC code mapping; fail-closed, P5)

Sentinel	Connect code	When	Caller action
ErrNoActiveCA	FailedPrecondition	tenant has no active issuing CA at issue time	provision CA (ProvisionTenantCA); operator alert
ErrCertTTLOutOfRange	InvalidArgument	requested TTL $\notin$ [renewSkew, 7d]	clamp / reject
ErrCertChainInvalid	Unauthenticated	leaf fails chain verify vs issuing CA	re-enroll
ErrCertUnknownSerial	Unauthenticated	presented serial not in live set	re-enroll
ErrCertRevoked	PermissionDenied	serial in revoke set	terminal; device must re-enroll
ErrCertExpired	Unauthenticated	now > not_after, never renewed	renew / re-enroll
ErrSpiffeMismatch	Unauthenticated	leaf SAN URI $\neq$ resolved device	reject (possible cert-swap attack)
ErrIssuingCACompromised	PermissionDenied	leaf's issuing_ca_id status flipped to	re-enroll after the new issuing CA is provisioned (never

Sentinel	Connect code	When	Caller action
		compromised (§2.3(b)) — zero-overlap, checked regardless of not_after	renew — see §2.3(b) rationale)
ErrWGKeyLen	InvalidArgument	WG pubkey ≠ 32 bytes	client bug; reject
ErrWGKeyDuplicate	AlreadyExists	pubkey already bound (tenant unique)	regenerate key
ErrPQDisabled	FailedPrecondition	PQ op on a tenant with PQ disabled	enable suite first
ErrEnrollTokenInvalid	Unauthenticated	token unknown / consumed / expired	mint a fresh token
ErrRevokeRace	Aborted	concurrent revoke/renew on same device	retry (idempotent)

All errors are **honest** (§11.4.1 — a FAIL is a real product condition, never a set--u crash); none degrades to a silent PASS. ErrNoActiveCA/ErrPQDisabled are FailedPrecondition not Internal so the caller can act.

10.2 Revoke-reason closed set (device_certs.revoked_reason)

{ manual | compromise | superseded | deprovision } — the §4.2 RevokeReason enum stringified; any other value rejected at the DB CHECK and the API validator (no free-text reasons leak into the audit trail, keeping §11.4.6 no-guessing).

10.3 SLOs (anti-bluff acceptance numbers, [02-CP §10.2])

Metric	Target	How measured
device revoke → edge WG-peer removed	p99 < 1 s	helix_pki_revoke_seconds histogram, revoke-call → edge confirms peer gone
	< 150 ms	helix_pki_issue_seconds

Metric	Target	How measured
cert issue (enroll path)		
cert renew round-trip	< 150 ms	helix_pki_renew_seconds
AuthDevice hot path (cache hit)	< 1 ms	helix_pki_authdevice_seconds
WG-key rotation → no dropped session	0 drops across overlap	rotation soak (§11), edge session- continuity counter
CA issuing- rotation overlap	no leaf rejected during window	24h overlap soak

11. Test points (constitution §11.4.169 — comprehensive test-type coverage)

§11.4.169 mandates comprehensive coverage by every test type the domain warrants (the §11.4.27 vocabulary); each pki capability maps to concrete, anti-bluff test points with captured evidence (§11.4.5/§11.4.69/§11.4.107). Per §11.4.119 the WG-rotation/revoke tests own the shared edge resource exclusively; per §11.4.85 stress+chaos are mandatory.

Test type	Concrete pki test point	Evidence / anti-bluff
unit	issuance leaf has EKU clientAuth+serverAuth, 24h not_after, SPIFFE SAN; RevokeReason round-trips; ML-KEM pubkey length ~1184B	golden cert DER as field-by-field
unit (property)	IssueDeviceCert then AuthDevice accepts; revoked never authenticates (P5) — fuzz serials	property test, 10k c
unit (privacy, P1)	enroll/rotate handlers store the <i>public</i> key: re-derive pub from a known WG private fixture, assert stored == public, NEVER the private	§1.1 mutation: feed private-shaped key handler MUST reje
integration	spin Postgres+Redis on-demand via vasic- digital/containers (§11.4.76, not ad-hoc docker); enroll → issue → renew → revoke; assert device_certs state machine transitions	captured DB snaps. bus event log denial proven, not a

Test type	Concrete pki test point	Evidence / anti-bluff
integration (RLS, C8)	tenant A cannot SELECT/UPDATE tenant B's ca_keys/device_certs/device_wg_keys even with crafted query, running as helix_app under FORCE ROW LEVEL SECURITY	
e2e	full enroll→WatchNetworkMap(mTLS)→renew-over-channel→revoke→stream force-closed, driven by generated agent stub	captured stream trace
security	reject ErrSpiffeMismatch cert-swap; reject expired/revoked; CA private key never appears in process memory dump nor any log line (P3); schema-lint asserts no cleartext *_private*/*_secret* column	memory-scan + logs evidence; paired \$1 mutation adds a plaintext key column → lint FAIL
performance / benchmark	IssueDeviceCert < 150 ms; AuthDevice cache-hit < 1 ms (§10.3)	go test -bench histo
scaling	10k devices each with a live 24h cert; renew-sweeper at 60s cadence stays bounded	process_resident_memory slope ≈ 0
stress (§11.4.85)	N≥100 concurrent enroll+revoke on the same tenant; no double-active-cert (unique idx holds); p50/p95/p99 latency recorded	latency.json captures
chaos (§11.4.85)	SIGKILL helixd mid-issue (tx atomic → no orphan cert without device row); Redis drop mid-revoke (PEL reclaimed via XAUTOCLAIM, [02-CP §5.4]) → revoke still converges < 1 s on recovery	recovery_trace.log
soak (24h)	continuous 24h-cert renewal churn + WG-key rotations; assert zero dropped sessions across rotation overlap (§7.2 window validated, removing the UNVERIFIED tag)	session-continuity ok
Challenge / HelixQA (§11.4.27/.107)	a Challenge drives enroll→revoke and asserts edge WG-peer removed < 1 s with captured runtime evidence (the revoke-SLO anti-bluff)	result.json + captured timing
meta-test (§1.1)	every recommended gate (CM-PKI-NO-PRIVATE-KEY-STORED, CM-REVOKE-SLO, the schema-lint) has a paired mutation that makes it FAIL	mutation FAILs prove

12. Phase → task plan (workable items, §11.4.93)

Risk-descending (§11.4.132): the privacy + revocation correctness floor first.

- **PKI-T1 — CA hierarchy + signer seam.**
 - PKI-T1.1 ca_keys DDL + RLS; ProvisionTenantCA (root offline/KMS → issuing online).
 - PKI-T1.2 CASigner seam (KMS + file-sealed backends, P3); no cleartext key column lint.
 - PKI-T1.3 RotateIssuingCA overlap window (§2.3); helixvpncctl ca rotate-issuing.
 - **PKI-T2 — device mTLS lifecycle.**
 - PKI-T2.1 device_certs extended DDL + state machine (§5.1); IssueDeviceCert (enroll tx).
 - PKI-T2.2 RenewDeviceCert + agent renew RPC (§6) + expiry sweeper (§6.3).
 - PKI-T2.3 AuthDevice hot path + revoke cache (§8.2).
 - **PKI-T3 — revocation (< 1 s).**
 - PKI-T3.1 Revoke two-teeth (§9.2) + device.revoked event + stream force-close.
 - PKI-T3.2 helix_pki_revoke_seconds SLO histogram + the §11 Challenge.
 - **PKI-T4 — WG public-key registry (C6).**
 - PKI-T4.1 device_wg_keys DDL + RegisterWGKey (P1 privacy mutation test).
 - PKI-T4.2 RotateWGKey overlap-then-retire (§7.2) + wg.key.rotated delta.
 - **PKI-T5 — PQ pre-shared material (optional, Phase-2-ready).**
 - PKI-T5.1 device_pq_material DDL + PQParams proto + per-tenant enable (§3.4/§8.1).
 - PKI-T5.2 RotatePSKEpoch + pq.psk.rotated event (control plane never sees the PSK, P4).
 - **PKI-T6 — gates + QA.** schema-lint (no cleartext key), CM-PKI-NO-PRIVATE-KEY-STORED, CM-REVOKE-SLO, the §11 test matrix end-to-end with captured evidence.
-

13. Phase-2 forward seams (additive, not a rewrite)

The Phase-1 seams extend without reshaping: the optional attestation leaf gains TPM / Secure-Enclave hardware binding [research-pki_pq_nat §1.2]; device_pq_material flips enabled=true with kem='x25519_mlkem768' (Mullvad-parity adds +mceliece) [research-pki_pq_nat §2.2/§2.4] and the PSK feeds the WG handshake at the endpoints (Rosenpass/wgephemeralpeer template)

[research-pki_pq_nat §2.2]; the CASigner swaps file-sealed → HSM with no caller change; CA-rotation automation replaces the operator-gated manual path; the revoke cache federates across regional helixd over NATS JetStream (the events.Bus swap, [02-CP §14]). Phase 2 is additive because Phase 1 drew the seams — the PKI interface, the signer seam, the four RLS tables, and the bus events — in the right places.

Sources

[04_P1] HelixVPN-Phase1-MVP.md §6 (identity/enrollment/PKI, device_certs, Enroll RPC, 24h cert, revoke < 1 s) · [04_ARCH] HelixVPN-Architecture-Refined.md §4 (pki module: WG key registry, short-lived device certs, rotation, PQ handshake material; key hierarchy; backups = Postgres + PKI root) · [02-CP] 02-control-plane.md §§1.3/2/4/5/8/9/10/14 (PKI interface, device_certs DDL, RLS, proto helix.coordinator.v1, events, authz, enroll sequence, SLOs) · [research-pki_pq_nat] §1 (WG native identity, no built-in PKI, SPIFFE/SPIRE two-identity split, short-lived SVID auto-rotate, revocation = stop-renew + remove-pubkey), §2 (PSK-injection PQ, hybrid-never-PQ-only, Mullvad McEliece+ML-KEM default-on-desktop 2025-01-09, wgephemeralpeer, Rosenpass 2-min PSK refresh, FIPS-203 ML-KEM, hybrid X25519+ML-KEM-768) · [SYNTHESIS] §§2/4/7/9 (stack floor, phased roadmap PQ in Phase 2, security invariants, constitution bindings). Access date for all research: 2026-06-25.