

helix_design design system

helix_design design system

Revision: 2 Last modified: 2026-07-04T12:00:00Z

Master technical specification — **Volume 4 (Clients)**, nano-detail deep-dive. This document **deepens** the *helix_design* — *the design system* section of the pass-1 client overview [04_UI §3, 03-CLIENT §7] into an implementation-ready specification of the helix_design Flutter package: the OpenDesign-backed token substrate (§11.4.162), the Material 3 theme layer, the signature connection-state palette, the five signature components (ConnectButton, StatusChip, ExitPicker, ShieldIndicator, AdaptiveScaffold), the responsive/adaptive one-tree layout, the motion system, accessibility, and the memory/frame budget. SPEC-ONLY: it describes **what to build and why**, to phase → task → subtask granularity; it does **not** build the product.

Boundary with sibling docs. This document **consumes** the FFI TunnelStatus / Shields / ExitOption contract owned by 03-CLIENT §3 (which itself mirrors the core enum frozen in v02-data-plane/orchestrator-and-state.md §4.1), and the TunnelPlatform event contract owned by 03-CLIENT §4–§5. It **owns** everything visual: tokens, theme, the signature widgets, the state→color mapping, the adaptive shell. It does **not** own the Riverpod providers (03-CLIENT §8), the screens, the FFI internals, or any platform shim. The widgets here are pure functions of the status stream (CI2); the design system never opens a tunnel.

Evidence base. Citations inline by id: [04_UI §N] = 04_VPN_CLD/HelixVPN-helix-ui-Flutter.md; [04_ARCH §N] = 04_VPN_CLD/HelixVPN-Architecture-Refined.md; [03-CLIENT §N] = final/03-client-core-and-ui.md; [02-ORCH §N] = final/v02-data-plane/orchestrator-and-state.md; [02-TX §N] = final/v02-data-plane/transport-trait.md; [SYN §N] = v09-research/_SYNTHESIS.md; [05_YB0] = operator mandate. Any claim not grounded in the evidence base is tagged UNVERIFIED per constitution §11.4.6 — never fabricated.

Table of contents

- [0. Position, ownership, and invariants](#)
 - [1. Token architecture — OpenDesign → Material 3 → HelixTokens](#)
 - [2. The connection-state palette \(the signature\)](#)
 - [3. HelixTheme — the ThemeExtension](#)
 - [4. The FFI/platform surface the design system consumes](#)
 - [5. Signature components \(nano-detail\)](#)
 - [6. Responsive / adaptive layout \(one tree, every form factor\)](#)
 - [7. Motion system](#)
 - [8. Accessibility & i18n \(CI5\)](#)
 - [9. Memory / frame budgets](#)
 - [10. Error handling & edge cases](#)
 - [11. Test points — tied to §11.4.169](#)
 - [12. Phase → task → subtask plan](#)
 - [13. Cross-document contracts this document fixes](#)
 - [14. Open decisions surfaced by this document](#)
 - [Sources verified](#)
-

0. Position, ownership, and invariants

A VPN client's UI has one emotional center of gravity: **am I protected right now?** `helix_design` makes that state instantly legible, then gets out of the way [04_UI §3]. Material 3 is the substrate; brand tokens override the defaults so it never reads as a stock Flutter app (a real risk to design against) [04_UI §3, 03-CLIENT §7]. Per §11.4.162 the token-and-theme system is **OpenDesign**, not ad-hoc CSS or one-off styling.

0.1 What this document owns

#	Contract	Owned here
DS1	Token substrate — the OpenDesign-sourced design tokens (palette light+dark, typography, spacing, radius, motion, elevation) + their Flutter projection <code>HelixTokens</code>	§1
DS2	Connection-state palette — the four signature semantic colors (<code>stateDisconnected</code> / <code>stateConnecting</code> / <code>stateConnected</code> / <code>stateDanger</code>) and the <code>colorForStatus(TunnelStatus)</code> mapping	§2
DS3	HelixTheme — the <code>ThemeExtension</code> carrying tokens into <code>ThemeData</code> , light+dark first-class, per-role brand seed override (<code>Access/Connector/Console</code>)	§3

#	Contract	Owned here
DS4	Signature components — ConnectButton, StatusChip, ExitPicker, ShieldIndicator, AdaptiveScaffold (+ NetworkTile, PolicyEditor referenced, owned by their screens' docs)	§5
DS5	Responsive/adaptive rules — one widget tree, branch on size never Platform.isX, the compact/medium/expanded breakpoints	§6
DS6	Motion + a11y + i18n discipline — emphasized-easing-on-state-change, semantic announcements, RTL, reduced-motion	§7–§8

0.2 What this document does NOT own

- The FFI surface (start/stop/statusStream/exits/setShields), the TunnelStatus/Shields/ExitOption *generation* — owned by 03-CLIENT §3; this doc consumes the generated Dart mirrors as read-only inputs (§4).
- The TunnelPlatform shim contract and per-OS implementations — 03-CLIENT §4–§5.
- The Riverpod providers, controllers, screens, and runHelixApp wiring — 03-CLIENT §6/§8; this doc supplies the *widgets* those screens compose.
- The core orchestrator TunnelStatus enum and its emit discipline — frozen in 02-ORCH §4; the design system never mutates it, only renders it.

0.3 Invariants this document inherits and tightens

#	Invariant	Source	Design-system tightening
CI2	The UI is a pure function of the core's status stream. No polling.	[03-CLIENT §0.1]	Every signature component is a stateless-ish StatelessWidget whose visual state is derived solely from the TunnelStatus/Shields/ExitOption it is handed; it holds no independent "connected" belief (§5).
CI5	State must be announced, not just colored — never	[04_UI §9, 03-	Every state-bearing widget

#	Invariant	Source	Design-system tightening
	color alone for protected/unprotected.	CLIENT §0.1]	pairs its color with a Semantics(label:) announcement AND a non-color cue (icon shape / text); a screen-reader user and a colorblind user both get the state (§8).
DS-I1	Single token source of truth. Screens reference <i>roles</i> (context.helix.stateConnected), never hardcoded Color(0x...) / magic spacing.	derived [04_UI §3.1]	A future white-label / self-host rebrand is a token swap, not a refactor ; a hardcoded color in a screen is a release-blocking lint finding (§1.4).
DS-I2	Light + dark are both first-class , not an afterthought theme.	[04_UI §9, 03-CLIENT §7.1]	Every component ships and is golden-tested in both themes; §11.4.162 mandates light+dark variants per component (§11).
DS-I3	No element overlaps another; no label overlays a label (§11.4.162).	§11.4.162	Layout uses constraint-driven composition (Flex/Wrap/OverflowBar), never absolute Positioned stacking of text; verified by a visual-regression overlap check (§11).
DS-I4	Motion is reserved for state change.	[04_UI §3.3]	The connect transition is the one place to

#	Invariant	Source	Design-system tightening
			spend animation budget; idle screens are still. Reduced-motion accessibility short-circuits all non-essential animation (§7).

0.4 The package at a glance

[MERMAID RENDER FAILED — block #1]

helix_design is a **decoupled, reusable** package (§11.4.28/§11.4.74) — no project-specific glue, no helix_core_fffi dependency in its *code* (it depends only on the *generated mirror types* as a type contract, injected by the consumer). This keeps it independently publishable to its own vasic-digital repo [03-CLIENT §2].

1. Token architecture — OpenDesign → Material 3 → HelixTokens

1.1 The three layers

1. **OpenDesign (source of truth, §11.4.162).** OpenDesign supplies the design tokens and themes: the full color palette in **light + dark** variants, the typography scale, the spacing/radius scale, and component-level tokens. Per §11.4.162 the project **MUST** install OpenDesign as a dependency and use its tokens/themes — NOT ad-hoc CSS/one-off tools. Missing patterns are extended **upstream** per §11.4.74, never duplicated in-project. UNVERIFIED (§11.4.6, pending §11.4.99 latest-source verification of <https://github.com/nexu-io/open-design>): OpenDesign's exact Flutter/Dart package name, import path, and token-export file format are not confirmed in the evidence base. This document fixes the **integration contract** (the token taxonomy OpenDesign must supply + the codegen seam) and marks the concrete API binding as an open item (§14 D-DS-1).
2. **Material 3 (Flutter substrate).** OpenDesign tokens are projected onto Flutter's Material 3 ColorScheme / TextTheme / ThemeData. M3 is the widget substrate (ripples, NavigationBar, NavigationRail, FilledButton shapes); the brand tokens override

M3 defaults so the app never reads as stock Flutter [04_UI §3, 03-CLIENT §7].

3. **HelixTokens (the Dart API screens read)**. A flat, const, compile-time token surface that screens and widgets reference by *role*. Screens never touch OpenDesign or raw M3 directly (DS-I1).

[MERMAID RENDER FAILED — block #2]

1.2 HelixTokens — the single source of truth

```
// helix_design/lib/tokens.dart — the flat const token surface
(DS-I1)
class HelixTokens {
  // — connection-state palette (the signature semantic colors,
  //    §2) —————
  static const stateDisconnected = Color(0xFF6B7280); // neutral
  grey ← Disconnected
  static const stateConnecting = Color(0xFFFF59E0B); // amber,
  in-motion ← Connecting/Handshaking/Reconnecting
  static const stateConnected = Color(0xFF10B981); // green,
  safe ← Connected
  static const stateDanger = Color(0xFFEF4444); //
  red ← Danger/Down

  // — brand seed: drives the M3 ColorScheme; overridden per role
  (§3.3) —————
  static const brandSeed = Color(0xFF3B5BDB); // HelixVPN
  brand indigo

  // — spacing (4-base scale)
  // —————
  static const space1 = 4.0, space2 = 8.0, space3 = 12.0, space4
    = 16.0,
    space6 = 24.0, space8 = 32.0, space12 = 48.0;

  // — radius
  // —————
  static const radiusSm = 8.0, radiusMd = 12.0, radiusLg = 20.0,
    radiusPill = 999.0;

  // — motion (§7)
  // —————
  static const motionFast = Duration(milliseconds: 120);
  static const motionBase = Duration(milliseconds: 220);
  static const motionSlow = Duration(milliseconds: 360);

  // — elevation: 0..3, used sparingly; flat surfaces, color-as-
  hierarchy —————
  static const elevation0 = 0.0, elevation1 = 1.0, elevation2 =
    3.0, elevation3 = 6.0;

  // Typography roles map to the M3 scale (display/headline/title/
  body/label) with
```

```
// the BRAND font (NOT Roboto default); concrete TextStyles live
// in HelixTheme (§3.2).
}
```

The literal hex values above are the **pass-1 token values** ratified in [04_UI §3.1, 03-CLIENT §7.1]. Under §11.4.162 these become the HelixVPN *instantiation* of OpenDesign's palette tokens: the codegen (§1.3) emits them into tokens.g.dart from the OpenDesign export, and HelixTokens re-exports the generated values so the rest of the package stays stable even if OpenDesign's internal naming changes. The brand seed 0xFF3B5BDB is fixed across all three flavors (the per-role override changes the *derived* scheme, §3.3, not the seed).

1.3 The OpenDesign codegen seam (the no-drift guarantee)

The token pipeline mirrors the project's other codegen drift-gates (flutter_rust_bridge, OpenAPI→Dart) [03-CLIENT §11]:

Step	Artifact	Tracked?	Regeneration mechanism (§11.4.77)
1	OpenDesign token export (light+dark)	tracked input	OpenDesign CLI / package export (UNVERIFIED exact cmd → §14 D-DS-1)
2	tool/gen_tokens.dart	tracked	hand-authored generator (reads step-1 export → emits step-3)
3	tokens.g.dart	tracked (regenerable)	dart run tool/gen_tokens.dart
4	drift check	CI/local sweep	gen_tokens re-run + git diff --exit-code tokens.g.dart — a drift FAILs the build (DS-I1)

A token edit that lands in a screen as a raw Color(0x...) or a magic EdgeInsets constant (bypassing HelixTokens) is caught by a custom analyzer lint (avoid_hardcoded_design_values, §1.4) — both are DS-I1 violations.

1.4 Lint enforcement of DS-I1 / DS-I3

```
custom_lint rules (helix_design/lint/):
- avoid_hardcoded_design_values : flag literal Color()/
```

```

EdgeInsets/BorderRadius
                                outside tokens.dart /
tokens.g.dart
  - require_semantics_on_state_color : a widget reading a state-
palette token MUST
                                also attach a
Semantics(label:) (CI5, §8)
  - no_text_overlap_stack      : flag a Stack whose children
include >1 Text
                                without an OverflowBar/Wrap
guard (DS-I3)

```

These are **pre-build gates** (§11.4.4(b) layer 1); each has a paired §1.1 mutation (plant a hardcoded color → lint FAILs; strip a Semantics → lint FAILs) per §11.

2. The connection-state palette (the signature)

2.1 The four states

The palette is the design system's emotional spine: four semantic colors, each mapping a class of TunnelStatus to one instantly-legible meaning [04_UI §3.1].

Token	Hex	Meaning	TunnelStatus variant(s)
stateDisconnected	0xFF6B7280 grey	idle, off, safe-to-act	Disconnected
stateConnecting	0xFFFF59E0B amber	in-motion, not-yet- protected	Connecting, Handshaking, Reconnecting
stateConnected	0xFF10B981 green	protected, traffic via tunnel	Connected{transport,path,rtt_ms}
stateDanger	0xFFEF4444 red	leak / kill- switch tripped / unexpected drop	Danger{kind}, Down{reason}

2.2 colorForStatus — the one mapping the whole app reads

```

// helix_design/lib/theme.dart – the state→color mapping (DS-I1,
CI5)
extension HelixStatusPalette on BuildContext {

```

```

/// Total over the doc-03 FFI TunnelStatus (§4.1). Every branch
is covered; an
/// unmatched variant is a COMPILE error (exhaustive switch) –
never a silent grey.
Color colorForStatus(TunnelStatus s) => switch (s) {
  Disconnected() => HelixTokens.stateDisconnected,
  Connecting() || Handshaking() || Reconnecting() =>
    HelixTokens.stateConnecting,
  Connected() => HelixTokens.stateConnected,
  Danger() || Down() => HelixTokens.stateDanger,
};

/// The NON-COLOR cue paired with every state (CI5: state
announced, not just colored).
HelixStateCue cueForStatus(TunnelStatus s) => switch (s) {
  Disconnected() => HelixStateCue(icon:
    HelixIcons.shieldOff, label: 'Off'),
  Connecting() => HelixStateCue(icon:
    HelixIcons.shieldSpin, label: 'Connecting'),
  Handshaking() => HelixStateCue(icon:
    HelixIcons.shieldSpin, label: 'Securing'),
  Reconnecting() => HelixStateCue(icon:
    HelixIcons.shieldSpin, label: 'Reconnecting'),
  Connected() => HelixStateCue(icon:
    HelixIcons.shieldOn, label: 'Protected'),
  Down(:final reason) => HelixStateCue(icon:
    HelixIcons.shieldAlert, label: _downLabel(reason)),
  Danger(:final kind) => HelixStateCue(icon:
    HelixIcons.shieldAlert, label: _dangerLabel(kind)),
};
}

class HelixStateCue { final IconData icon; final String label;
  const HelixStateCue({required this.icon, required
    this.label}); }

```

2.3 The danger override (the honesty rule)

Danger and Down{reason≠"stopped"} **override any user intent** and paint the red palette immediately [03-CLIENT §8.4]. The design system never paints green on intent — only on an actual Connected from the core's stream (CI2). The Danger{kind} source is the kill-switch/leak sub-machine in 02-ORCH §8 (kill-switch tripped / DNS-leak), synthesized into a TunnelStatus::Danger at the FFI boundary (§4.2). Down.reason uses the stable-prefix vocabulary ("stopped", "auth-failed", "ladder-exhausted", ...) frozen in 02-ORCH §4.4, so _downLabel classifies without parsing prose (§11.4.6).

2.4 Palette ↔ status flow

[MERMAID RENDER FAILED — block #3]

2.5 Contrast & accessibility constraint (release-blocking)

Each state color MUST meet **WCAG AA** contrast ($\geq 3:1$ for the large ConnectButton glyph, $\geq 4.5:1$ for status text) against BOTH the light and dark surface tokens [04_UI §9]. The four-color set is verified at token-build time by a contrast check (§11, SEC/a11y test point); a token edit that breaks contrast is a release blocker. The amber/green/grey set was chosen for **colorblind distinguishability** (the shape cue in §2.2 is the fallback for total color deficiency, CI5).

3. HelixTheme — the ThemeExtension

3.1 Why a ThemeExtension

Tokens are carried into ThemeData via a ThemeExtension<HelixTheme> so screens reference roles (context.helix.stateConnected) and never hardcode (DS-I1). This keeps the eight platforms visually identical, makes a white-label a token swap, and gives flutter_test a single override point for golden tests [04_UI §3.1/§9].

```
// helix_design/lib/theme.dart
@immutable
class HelixTheme extends ThemeExtension<HelixTheme> {
  final Color stateDisconnected, stateConnecting, stateConnected,
    stateDanger;
  final double spaceUnit; // 4.0 base; widgets multiply
  final HelixMotion motion; // durations (§7)
  const HelixTheme({ required this.stateDisconnected, required
    this.stateConnecting,
    required this.stateConnected, required this.stateDanger,
    required this.spaceUnit, required this.motion });

  @override HelixTheme copyWith({ Color? stateDisconnected, /* ...
    */ }) => /* ... */;
  @override HelixTheme lerp(ThemeExtension<HelixTheme>? other,
    double t) => /* ...
    lerp each state color so a theme animation (light→dark) is
    smooth ... */;

  static HelixTheme of(BuildContext c) =>
    Theme.of(c).extension<HelixTheme>()!;
}

extension HelixThemeX on BuildContext {
```

```

HelixTheme get helix => HelixTheme.of(this); //
    context.helix.stateConnected
}

```

3.2 Theme construction (light + dark, both first-class — DS-I2)

```

// helix_design/lib/theme.dart
ThemeData helixTheme(HelixFlavor flavor, Brightness brightness) {
  final seed = _seedForRole(flavor); // §3.3
  final scheme = ColorScheme.fromSeed(seedColor: seed,
    brightness: brightness);
  return ThemeData(
    useMaterial3: true,
    colorScheme: scheme,
    textTheme: _brandTextTheme(scheme), //
      brand font, M3 scale (§1.2)
    extensions: const [ _helixExtension ], //
      const single instance (§9)
    // flat surfaces: low elevation, color-as-hierarchy (04_UI
    §3.3)
    cardTheme: const CardThemeData(elevation:
      HelixTokens.elevation0),
    splashFactory: InkSparkle.splashFactory,
  );
}
const _helixExtension = HelixTheme(
  stateDisconnected: HelixTokens.stateDisconnected,
  stateConnecting: HelixTokens.stateConnecting,
  stateConnected: HelixTokens.stateConnected,
  stateDanger: HelixTokens.stateDanger,
  spaceUnit: HelixTokens.space1,
  motion: HelixMotion.standard,
);

```

light + dark are produced by the *same* call with `Brightness.light/dark`; the state palette is **brightness-invariant** (the four semantic colors are identical in both themes — only the M3 surface/scheme flips), because "am I protected" must read the same regardless of theme. Privacy users skew dark; the system honors the OS brightness with a manual override [04_UI §3.1/§9, 03-CLIENT §7.1].

3.3 Per-role brand override (Access / Connector / Console)

```

Color _seedForRole(HelixFlavor f) => switch (f) {
  HelixFlavor.access =>
    HelixTokens.brandSeed, // 0xFF3B5BDB
    (consumer indigo)
}

```

```

HelixFlavor.connector =>
    HelixTokens.brandSeed,           // shared seed;
    role differs by accent
HelixFlavor.console    =>
    HelixTokens.brandSeed,           // admin; denser
    tables, same brand
};

```

UNVERIFIED (§11.4.6): the evidence base fixes a **single** brand seed 0xFF3B5BDB and says it is "overridden per role" [04_UI §3.1, 03-CLIENT §7.1] but does **not** specify distinct per-role seed values. This document therefore ships all three roles on the one ratified seed and marks the *degree* of per-role divergence (a tint shift vs a distinct seed) as an open decision (§14 D-DS-2), rather than fabricate three hex values. The connection-state palette is role-invariant regardless of the outcome (the palette is the safety signal; the brand accent is decoration).

[MERMAID RENDER FAILED — block #4]

4. The FFI/platform surface the design system consumes

The design system renders three read-only inputs from the FFI layer. These are **generated mirrors** [03-CLIENT §3.2] — the design system never declares parallel types; it imports the mirror as a type contract.

4.1 TunnelStatus (consistent with 02-ORCH §4.1)

The **core** orchestrator emits the lean five-variant enum frozen in 02-ORCH §4.1 / 02-TX §5.2:

```

// helix-core/src/status.rs — CANONICAL CORE ENUM (02-ORCH §4.1) —
// do NOT diverge
pub enum TunnelStatus {
    Connecting,
    Handshaking,
    Connected { transport: String, rtt_ms:
        u32 }, // transport = Transport::kind() (02-TX §2)
    Reconnecting,
    Down { reason: String }, // stable-
        prefix vocabulary (02-ORCH §4.4)
}

```

The **client FFI projection** [03-CLIENT §3.1] mirrors that enum byte-for-byte and **extends** it with three client-only variants/fields the UI needs:

```
// helix-ffi/src/api.rs – the Dart-facing mirror (03-CLIENT §3.1);
// frb generates the Dart twin
#[frb(mirror)]
pub enum TunnelStatus {
    Disconnected, //
    // ADDED: clean idle, distinct from Down

    Connecting, //
    // — from here, identical to the core enum —

    Handshaking,
    Connected { transport: String, path: String, rtt_ms:
        u32 }, // ADDED field: path = "direct" | "relay"
    Reconnecting,
    Down { reason: String },
    Danger { kind: String }, //
    // ADDED: "leak" | "killswitch_tripped"
}

```

Consistency boundary (§11.4.6). The shared subset {Connecting, Handshaking, Connected, Reconnecting, Down} is **byte-for-byte the 02-ORCH §4.1 core enum**, and the FFI contract test asserts that match [03-CLIENT §3.2/§12]. The three extensions are synthesized at the FFI boundary, NOT in the core broadcast: Disconnected (the FFI's pre-start/post-clean-stop resting state, where the core has no OrchState projection — 02-ORCH §5.1 maps Idle/clean-ShuttingDown to no public state); path on Connected ("direct" vs "relay" — a Phase-2 P2P/relay indicator [03-CLIENT §3.1, §13 T2.3], UNVERIFIED that the 02-ORCH core currently emits it — a cross-doc seam pending the core enum extension); Danger{kind} (synthesized from the 02-ORCH §8 kill-switch/DNS sub-machine trip/leak event). The design system renders the 7-variant FFI projection; the *core* contract it must stay consistent with is the 5-variant subset. If the core enum is later extended, the FFI mirror tracks it and the §12 FFI contract test re-asserts byte-equality.

```
// the GENERATED Dart twin the design system imports
// (frb_generated.dart, read-only)
sealed class TunnelStatus { const TunnelStatus(); }
class Disconnected extends TunnelStatus { const Disconnected(); }
class Connecting extends TunnelStatus { const Connecting(); }
class Handshaking extends TunnelStatus { const Handshaking(); }
class Connected extends TunnelStatus {
    final String transport, path; final int rttMs;
    const Connected({required this.transport, required this.path,
        required this.rttMs}); }
class Reconnecting extends TunnelStatus { const Reconnecting(); }
class Down extends TunnelStatus { final String reason; const
    Down(this.reason); }
class Danger extends TunnelStatus { final String kind; const
    Danger(this.kind); }

```

4.2 How Danger / revoked reach the design system across platforms

Danger{kind} and the OS-revoked case originate below Dart and must surface to the widgets within the convergence budget [03-CLIENT §4.1 O3]. The design system does not implement this path — it only **consumes** the resulting TunnelStatus. The load-bearing native signatures (owned by 03-CLIENT §5, shown here only to fix where the design-system input comes from):

```
// iOS/macOS NEPacketTunnelProvider (03-CLIENT §5.1) – kill-  
switch/leak → Danger  
func emitDanger(_ kind: String) {  
    helix_core_emit_status(.danger(kind)) } // → FFI stream  
override func stopTunnel(with reason: NEProviderStopReason, ...) {  
    /* revoked → Down/Danger */ }  
  
// Android VpnService (03-CLIENT §5.2)  
override fun onRevoke() { coreStop(); emitEvent(REVOKED) } // →  
PlatformTunnelEvent.revoked → Down  
  
// Aurora Qt/C++ backend (03-CLIENT §5.6) – same shape over the C  
ABI  
void HelixTunnelBackend::onLeakDetected() {  
    helix_core_emit_status_danger("leak"); }
```

The design system's contract is simply: **whatever TunnelStatus the FFI stream emits, render it** (CI2). A revoked/Danger arriving while the user *intends* connected paints red, never green (§2.3).

4.3 Shields and ExitOption (read by ShieldIndicator / ExitPicker)

```
// generated mirrors (03-CLIENT §3.1) – design system consumes,  
never mutates  
class Shields { final bool killSwitch, dnsProtection, daita,  
postQuantum;  
    final List<String> splitTunnel; const Shields(/* ... */); }  
class ExitOption { final String id, kind, label; final String?  
country; final int? rttMs;  
    final String? jurisdiction; const ExitOption(/* ... */); }
```

setShields/setExit are pure-logic FFI calls (no OS tunnel, CI1) [03-CLIENT §3.3]; the design-system widgets emit a *callback* (onToggle/onPick) and never call the FFI directly — the screen's controller does (separation of concerns, §5).

5. Signature components (nano-detail)

Every signature widget obeys five rules: (a) **stateless render from inputs** (no internal "connected" belief, CI2); (b) **color paired with a non-color cue + a Semantics announcement** (CI5); (c) **light+dark + every state golden-tested** (DS-I2, §11); (d) **no element/label overlap** (DS-I3); (e) **callbacks out, never FFI calls in** (the widget is pure; the controller acts).

5.1 ConnectButton — the giant tap target

```
// helix_design/lib/widgets/connect_button.dart
class ConnectButton extends StatelessWidget {
  final TunnelStatus state;           // the ONLY source of
    visual state (CI2)
  final VoidCallback onTap;           // controller decides
    connect vs disconnect (03-CLIENT §8.2)
  final double diameter;              // default 200 (compact) →
    adaptive (§6)
  const ConnectButton({super.key, required this.state, required
    this.onTap,
                        this.diameter = 200});
  @override Widget build(BuildContext c) { /* §5.1.2 */ }
}
```

5.1.1 Visual state machine

[MERMAID RENDER FAILED — block #5]

5.1.2 Render + motion + a11y

```
@override Widget build(BuildContext c) {
  final color = c.colorForStatus(state);
  final cue    = c.cueForStatus(state);
  final spinning = state is Connecting || state is Handshaking ||
    state is Reconnecting;
  return Semantics(
    button: true,
    label: 'Connection',
    value: cue.label,                                // CI5:
      announce state to screen reader
    onTapHint: state is Connected ? 'Disconnect' : 'Connect',
    child: GestureDetector(
      onTap: onTap,
      child: RepaintBoundary(                        // §9:
        isolate the animated ring
        child: AnimatedContainer(
          duration:
            c.helix.motion.base,                      // 220 ms, emphasized
            easing (§7)
          curve: HelixCurves.emphasized,
```

```

        width: diameter, height: diameter,
        decoration: BoxDecoration(shape: BoxShape.circle,
            color: color.withOpacity(.12),
            border: Border.all(color: color, width: 4)),
        child: Column(mainAxisAlignment:
            MainAxisAlignment.center, children: [
            spinning ? _SpinningRing(color: color) :
            Icon(cue.icon, color: color, size: 48),
            const SizedBox(height: HelixTokens.space2),
            Text(cue.label, style: c.textTheme.titleMedium), //
            non-color cue (CI5)
        ]),
    ),
),
);
}

```

- **Edge cases:** a null/uninitialized status renders `Disconnected` (the safe default, §10); an unknown `Down.reason` prefix renders the generic "Connection failed" label (never a raw prose dump, §11.4.6); rapid taps are debounced by the controller (the widget just forwards `onTap`).
- **Memory:** the spinning ring is the only animation; it lives behind a `RepaintBoundary` so it never invalidates the rest of the tree (§9). When not spinning, zero `AnimationController` runs (battery on idle).

5.2 StatusChip — transport · path · RTT

```

class StatusChip extends StatelessWidget {
  final TunnelStatus state;
  const StatusChip({super.key, required this.state});
  @override Widget build(BuildContext c) {
    final txt = switch (state) {
      Connected(:final transport, :final path, :final rttMs) =>
        '${_label(transport)} · $path · ${rttMs}ms', //
        "MASQUE · direct · 23ms"
      Connecting() || Handshaking() => 'Connecting...',
      Reconnecting() => 'Reconnecting...',
      Disconnected() => 'Not connected',
      Down(:final reason) => _downLabel(reason),
      Danger(:final kind) => _dangerLabel(kind),
    };
    return Semantics(label: 'Tunnel status', value: txt,
      child: Chip(label: Text(txt, overflow:
        TextOverflow.ellipsis), // DS-13: never overflow-overlap
        avatar: Icon(c.cueForStatus(state).icon, color:
          c.colorForStatus(state), size: 16)));
  }
}

```

- transport is the Transport::kind() string from 02-TX §2 ("masque-h3" → display "MASQUE"); path is the Phase-2 direct/relay field; rttMs is the WG-handshake RTT EWMA, re-emitted only when it drifts > 5 ms [02-ORCH §4.3], so the chip updates without flicker. **Edge case:** an unknown transport string shows the raw label (never a crash), flagged for an `l10n` follow-up (§10).

```
class ExitPicker extends StatelessWidget {
  final List<ExitOption> options;           // from core.exits(),
  RTT-sorted upstream (03-CLIENT §7.2)

  final String? selectedId;
  final ValueChanged<String> onPick;        // callback out
  (controller calls setExit)

  final ExitPickerStatus loadState;         // loading | ready |
  error | empty (§10)

  const ExitPicker({ super.key, required this.options, required
    this.selectedId,
    required this.onPick, this.loadState =
    ExitPickerStatus.ready });
}

enum ExitPickerStatus { loading, ready, error, empty }
```

- ## 5.4 ShieldIndicator — kill-switch / DNS / DAITA / PO

```
class ShieldIndicator extends StatelessWidget {
    final Shields
        shields;                                // from core (03-CLIENT §3.1)
    final TunnelStatus state;                    // to surface
        Danger{kind} on the relevant badge
    final ValueChanged<Shields> onToggle;      // callback out
        (controller calls setShields)
```

```

const ShieldIndicator({ super.key, required this.shields,
                      required this.state,
                      required this.onToggle });
}

```

- Renders four badges (killSwitch, dnsProtection, daita, postQuantum), each a small affordance with an **honest cost note on tap** ("DAITA adds cover traffic — uses more data") [04_UI §3.2]. A `Danger{kind:"killswitch_tripped"}` paints the kill-switch badge red and announces it (CI5).
- **Honest-cost rule (§11.4.6)**: the cost note is factual, never marketing — e.g. post-quantum's note states it is a hybrid PSK that does not slow the data path but adds handshake bytes (the doc-01 PQ stance). No badge ever claims a protection it cannot prove is active; a badge's "on" state is driven by the *core's* Shields truth, not the toggle's optimistic position (CI2).

5.5 AdaptiveScaffold — the responsive shell

```

class AdaptiveScaffold extends StatelessWidget {
  final List<HelixDestination> destinations; // (icon, label,
    route)
  final int selectedIndex; final ValueChanged<int> onSelect;
  final Widget body; final Widget? detailPane; // expanded
    layouts show body|detail
  const AdaptiveScaffold({ super.key, required this.destinations,
    required this.selectedIndex,
    required this.onSelect, required
    this.body, this.detailPane });
  @override Widget build(BuildContext c) {
    final w = MediaQuery.sizeOf(c).width; // branch on
    SIZE, never Platform.isX (§6)
    return switch (HelixBreakpoint.of(w)) {
      HelixBreakpoint.compact => _bottomNavLayout(c), //
        BottomNavigationBar, single pane
      HelixBreakpoint.medium => _railLayout(c, extended:
        false), // NavigationRail, master/detail
      HelixBreakpoint.expanded => _railLayout(c, extended:
        true), // extended rail, multi-pane
    };
  }
}

```

AdaptiveScaffold is the **only** widget that reads `MediaQuery` width; every other widget is layout-agnostic (it fills the constraints it is given), so a resized desktop window and a phone share one code path (§6).

5.6 Component data-flow (all five at once)

[MERMAID RENDER FAILED — block #6]

6. Responsive / adaptive layout (one tree, every form factor)

One AdaptiveScaffold reflows by **width breakpoint** — the convergent approach that makes the same Access app feel native on a phone and a desktop, and the Console feel native on web and desktop [04_UI §7, 03-CLIENT §7.3].

```
// helix_design/lib/widgets/breakpoint.dart
enum HelixBreakpoint {
  compact,    // < 600 : BottomNavigationBar · single pane · full-
              width ConnectButton
  medium,     // 600–1024 : NavigationRail · master/detail
  expanded;   // > 1024 : extended NavigationRail · multi-pane
              (Console: list | detail | live events)
  static HelixBreakpoint of(double w) =>
    w < 600 ? compact : (w <= 1024 ? medium : expanded);
}
```

[MERMAID RENDER FAILED — block #7]

Rules [04_UI §7, 03-CLIENT §7.3]:

- **Branch on size, never Platform.isX** for *layout* — a desktop window resized small behaves like a phone; web "just works" responsively (the brief's "fully responsive web"). Platform.isX is reserved for *capability* gating (§11.4.x flavor model, 03-CLIENT §6), never layout.
 - **Touch targets ≥ 48 dp** on compact; pointer + keyboard shortcuts on medium/expanded (⌘K command palette in Console).
 - **Console heavy surfaces** (topology graph, policy editor, dense tables) are **deferred-loaded** so they never bloat Access/Connector binaries [04_UI §7, 03-CLIENT §7.3, §9].
 - **No element/label overlap at any width** (DS-I3) — reflow uses Wrap/Flex/ OverflowBar, never absolute positioning of text; verified by the visual- regression overlap check across all three breakpoints (§11).
-

7. Motion system

Motion is **reserved for state change** — the connect transition is the one place to spend the animation budget; idle screens are still (DS-I4) [04_UI §3.3].

```
// helix_design/lib/motion.dart
class HelixMotion {
  final Duration fast, base, slow;
```

```

const HelixMotion({required this.fast, required this.base,
  required this.slow});
static const standard = HelixMotion(
  fast: HelixTokens.motionFast,    // 120ms – micro-feedback
    (ripples, hover)
  base: HelixTokens.motionBase,    // 220ms – the connect-state
    transition (the spend)
  slow: HelixTokens.motionSlow);  // 360ms – large surface
    transitions (rare)
}
class HelixCurves {
  static const emphasized = Cubic(0.2, 0.0, 0.0, 1.0);  // M3
    emphasized; state change only
  static const standard    = Curves.easeInOutCubicEmphasized;
}

```

- The ConnectButton ring uses motion.base + emphasized easing on every state transition (§5.1); the settle-pulse on Connected is a single 200ms overshoot, not a loop.
- **Reduced-motion accessibility (release-blocking, CI5):** when MediaQuery.disableAnimations (OS "reduce motion") is set, all non-essential animation is short-circuited — the ConnectButton snaps between states (still legible via color+icon+label), the spinning ring becomes a static "Connecting..." label. The state is **never** conveyed by motion alone.

[MERMAID RENDER FAILED — block #8]

8. Accessibility & i18n (CI5)

State must be **announced, not just colored** — never rely on color alone for protected/unprotected [04_UI §9, 03-CLIENT §0.1 CI5]. The design system enforces this mechanically (the require_semantics_on_state_color lint, §1.4).

Concern	Rule	Verified by (§11)
Screen reader	every state-bearing widget has Semantics(label:, value:); ConnectButton announces "Connection: Protected" + tap hint	a11y test point (UT/E2E)
Color blindness	every state color paired with a	

Concern	Rule	Verified by (§11)
	shape-coded icon + text label (§2.2)	golden in a grayscale filter + manual; lint require_semantics_on_state_color
Contrast	WCAG AA against light AND dark surfaces (§2.5)	token-build contrast check (release-blocking)
Large text	dynamic type scales without overlap/clipping (DS-I3); labels ellipsis, never truncate-overlap	golden at 2.0× text scale × both themes
Keyboard	full keyboard nav on desktop/web; focus order = visual order; ⌘K palette in Console	E2E keyboard-traversal test
RTL / i18n	all strings from helix_l10n ARB (en, ru, zh-Hans, ...); layout mirrors in RTL; no hardcoded English	golden in ar/he RTL locale

i18n: all user-facing strings are ARB keys [03-CLIENT §2]; the design system ships **no** literal copy except debug labels. Down.reason/Danger.kind prefixes (02-ORCH §4.4) map to localized strings via a closed lookup (`_downLabel`), never raw prose to the user (§11.4.6).

9. Memory / frame budgets

The design system's slice of the doc-03 budgets [03-CLIENT §10, 04_UI §10]:

Budget	Target	How
Frame budget	60/120 fps, no jank	const widgets everywhere; RepaintBoundary on the ConnectButton ring; motion only on state change (DS-I4)
Idle animation	zero AnimationController when not transitioning	the spinning ring stops + disposes its controller on Connected/Disconnected (§5.1)

Budget	Target	How
Theme allocation	one const HelixTheme instance per (flavor × brightness)	const _helixExtension (§3.2) — no per-build allocation
Long lists	constant memory for N exits/devices	ListView.builder/Sliver (lazy), never a materialized Column (§5.3)
Console heavy widgets	excluded from Access/Connector binaries	deferred-loaded (deferred as) topology/policy/table widgets (§6)
Token surface	zero runtime cost	HelixTokens is all const; resolved at compile time (§1.2)

The design system adds **no** Rust/native memory (it is pure Dart/Flutter); the iOS NE ~15 MB working-set ceiling [03-CLIENT §0.1 CI4, §10] is the *core*'s budget, untouched by *helix* design. The design-system contribution to install size is tree-shaken icons/fonts + the brand typeface (one weight set, subset to used glyphs) [03-CLIENT §10].

10. Error handling & edge cases

#	Edge case	Behavior (§11.4.6 no-guessing)
E1	FFI stream Lagged (broadcast ring fell behind, 02-ORCH §4.2)	the Riverpod StreamProvider skips-to-latest; the widget re-renders the newest TunnelStatus — never an error state (§4.6 receiver contract)
E2	null / not-yet-initialized status	render Disconnected (the safe default, grey, "Not connected") — never blank, never a spinner-forever
E3	unknown transport string in Connected	StatusChip shows the raw kind label (no crash); flagged for an <code>!10n</code> mapping follow-up
E4	unknown <code>Down.reason</code> / <code>Danger.kind</code> prefix	generic localized "Connection failed" / "Protection alert" label; the raw value is logged (not shown) for forensics (§11.4.6)

#	Edge case	Behavior (§11.4.6 no-guessing)
E5	ExitPicker selectedId not in options (stale after reconcile, 02-ORCH §6.4)	clear selection + surface "Exit no longer available" (honest, not silent)
E6	ExitPicker loading / empty / error	shimmer skeleton / "No exits" + retry / honest FFI error detail — never a frozen spinner (§11.4.107 liveness)
E7	HelixTheme.of(context) missing (extension not registered)	assertion failure in debug (fail-loud); release builds fall back to M3 defaults — caught by a startup smoke test
E8	OpenDesign token missing at codegen	gen_tokens FAILs with the exact missing key (§1.3) — a build-blocking finding, never a silent default (§11.4.6)
E9	dynamic-type overflow on a small width	text ellipsis + tooltip; layout reflows (DS-I3), never overlaps
E10	rapid connect/disconnect taps	controller debounces (03-CLIENT §8.2); the widget forwards onTap idempotently (no double-start)
E11	Danger arrives while intent = connected	red palette OVERRIDES intent immediately (§2.3); the button shows the alarm state, never green

11. Test points — tied to §11.4.169

Every `helix_design` workable item declares its required test types from the **§11.4.169 closed test-type vocabulary**; the only permitted absence of a warranted type is an honest §11.4.3 SKIP-with-reason, never a silent gap. Four-layer enforcement per §11.4.4(b) applies to every component closure. §11.4.162 adds the **visual-regression** mandate (light+dark × breakpoint × state golden matrix).

Code (§11.4.169)	Type	Concrete test point for <code>helix_design</code>	Evidence (§11.4.5/.69/.10)
UT	unit / widget + golden	each component renders correctly for every TunnelStatus × {light, dark} × {compact,	<code>flutter_test</code> + <code>golden_toolkit</code> PM matrix

Code (§11.4.169)	Type	Concrete test point for helix_design	Evidence (§11.4.5/.69/.10)
IT	integration	medium, expanded}; colorForStatus/cueForStatus exhaustive switch; HelixBreakpoint.of boundaries (599/600/1024/1025) the design system inside a real flavor shell driven by a fake HelixCore emitting a scripted TunnelStatus sequence (same generated mirror types) → widgets reflect each state	scripted-stream log
E2E	end-to-end	real connect journey on a real device: tap ConnectButton → StatusChip reads MASQUE · direct · 23ms → confirmed by OCR/vision validation (§11.4.158/.159)	window-scoped M (helixvpn---conne <run-id>.mp4, §11 + OCR verdict
FA	full- automation (deterministic §11.4.50)	N=3 identical golden runs across the full state×theme×breakpoint matrix produce byte-identical PNGs	3× identical gold artifacts
CH	Challenges (challenges submodule)	a Challenge scores the captured connect-journey MP4 + golden matrix, not config	Challenge result
HQA	HelixQA (helix_qa submodule)	autonomous QA session drives connect→shields→exit-pick across a flavor	HelixQA session evidence
SEC	security / a11y-contrast	WCAG AA contrast check on the 4 state colors × {light,dark}; no secret in any token; require_semantics_on_state_color lint passes	contrast report; output
SC	stress + chaos (§11.4.85)	rapid TunnelStatus flips (1000 transitions, incl. Connected↔Danger↔Reconnecting) → no dropped frame, no stuck animation, controller debounce holds	frame-timeline C recovery trace
CONC	concurrency	concurrent stream emission + user tap during a transition → no torn render, no double onTap	concurrency har
MEM	memory	no AnimationController leak across 1000 connect/disconnect	DevTools memor timeline

Code (§11.4.169)	Type	Concrete test point for helix_design	Evidence (§11.4.5/.69/.10)
BENCH	performance	cycles; constant heap for a 500-row ExitPicker ConnectButton transition stays within the 16.6 ms (60 fps) / 8.3 ms (120 fps) frame budget; golden matrix render time	frame-time CSV
RACE	race / deadlock	provider-override race on theme swap (light↔dark mid-animation) → no inconsistent HelixTheme read	race harness log
LOAD	DDoS / load-flood	SKIP — §11.4.3: a pure-UI package has no network/request surface to flood; the load surface is the FFI/control plane (doc 02), tested there	SKIP-with-reason

Anti-bluff coupling (§11.4.107/§11.4.158/§11.4.159). A green widget golden is **not** proof the user is protected — it proves the design system *renders the state it is handed*. The authoritative end-user evidence is the E2E device recording: a window-scoped MP4 of the real connect journey, vision-validated that the StatusChip reads the real transport/path/RTT and the ConnectButton is green, plus the §11.4.163 media-validation pipeline confirming the recording's on-screen content matches the SPECIFY-phase expected patterns. Fakes (the HelixCore double in IT/UT) use the **same generated mirror types** the FFI produces, so unit tests exercise the real contract; the user-visible claim is only earned by the device recording (§11.4.27/.52).

Each lint/gate (§1.4) carries a paired §1.1 meta-test mutation: plant a hardcoded Color(0x...) in a screen → avoid_hardcoded_design_values FAILs; strip a Semantics from a state widget → require_semantics_on_state_color FAILs; seed a golden with an overlapping label → the DS-I3 overlap check FAILs; break a state color's contrast → the SEC contrast gate FAILs.

12. Phase → task → subtask plan

Aligned to the program roadmap [SYN §4, 03-CLIENT §13]. Each subtask is a workable item (§11.4.93 SQLite SSoT).

Phase 0 — prove the seam (the spike)

- **T0.1 Token + theme skeleton.** HelixTokens (the ratified pass-1 values), HelixTheme extension, light+dark helixTheme(); one Flutter-Linux window rendering the four state colors. (Feeds the G5 FFI demo StatusChip Connecting → Handshaking → Connected(masque,23ms) [03-CLIENT §13 T0.1].)
- **T0.2 ConnectButton + StatusChip v0.** Driven *only* by the Rust event stream (CI2); the G5 demo's visible surface.

Phase 1 — helix_design v1 [03-CLIENT §13 T1.2]

- **T1.1 OpenDesign integration (§11.4.162).** Resolve D-DS-1 (the OpenDesign package/export, §14), wire gen_tokens codegen + drift gate (§1.3); migrate HelixTokens to the generated source.
- **T1.2 The five signature components,** each light+dark + every-state golden (DS-I2), the lint rules (§1.4), accessibility (§8).
- **T1.3 colorForStatus/cueForStatus** exhaustive over the doc-03 FFI TunnelStatus; the FFI contract test asserts the shared subset matches 02-ORCH §4.1 byte-for-byte (§4.1).
- **T1.4 AdaptiveScaffold** + breakpoints; compact/medium/expanded goldens.
- **T1.5 Motion + reduced-motion** (§7); ShieldIndicator honest-cost notes (§5.4).

Phase 2 — parity surfaces [03-CLIENT §13 T2.x]

- **T2.1 ExitPicker multi-hop** chain builder + jurisdiction labels (overlap-free, DS-I3).
- **T2.2 Direct-vs-relay path chip** — surface the Connected.path field once the core enum extension lands (§4.1 cross-doc seam).
- **T2.3 DAITA + PQ shield badges** wired to Shields.

Phase 3 — extended reach

- **T3.1 HarmonyOS/Aurora visual parity** — the UI ports for free; golden the same matrix on the fork builds [03-CLIENT §13 T3.x]; the design system needs **no** per-platform code (the shim does, not the widgets).
 - **T3.2 Console web density** — deferred-loaded heavy widgets, ⌘K palette, expanded multi-pane goldens.
-

13. Cross-document contracts this document fixes

Contract	Fixed value	Consumed by
Connection-state palette (stateDisconnected/Connecting/Connected/Danger tokens + hex)	\$1.2, \$2.1	every screen; the white-label token-swap path
colorForStatus/cueForStatus over the doc-03 FFI TunnelStatus	\$2.2	every state-bearing widget
Brand seed 0xFF3B5BDB, light+dark first-class, per-role override seam	\$1.2, \$3.3	helixTheme(flavor, brightness), all three flavors
HelixTheme ThemeExtension + context.helix accessor	\$3.1	every widget; the DS-I1 no-hardcode rule
Signature component API (ConnectButton/StatusChip/ ExitPicker/ShieldIndicator/ AdaptiveScaffold signatures, callbacks-out rule)	\$5	the three apps' screens [03-CLIENT \$6/\$8]
Breakpoint set (compact<600 / medium 600- 1024 / expanded>1024) + branch-on-size rule	\$6	AdaptiveScaffold, all responsive layouts
CI5 announce-not-color discipline + the \$1.4 lints	\$2.2, \$8	every state widget; the a11y release gate
TunnelStatus consistency with 02-ORCH \$4.1 (5-variant core subset byte-identical; 3 client extensions FFI-synthesized)	\$4.1	the FFI contract test [03-CLIENT \$12]; doc 02 (core enum)

14. Open decisions surfaced by this document

Per §11.4.6/§11.4.66 — options + recommendation, never silently resolved.

#	Decision	Option A	Option B	Recommendation
D-DS-1	OpenDesign (\$11.4.162) Flutter binding	OpenDesign exports tokens (JSON/Style-Dictionary-style) →	OpenDesign ships a Flutter package consumed at runtime	A (codegen) - keeps HelixTok const zero-runtime cost surface (\$) and gives a bu

#	Decision	Option A	Option B	Recommendation
		gen_tokens → tokens.g.dart (codegen seam, §1.3)		time drift gate (§1.3). Require §11.4.99 latest source verification of hub.com/nexus-io open-design's actual export format before T1.1 — market UNVERIFIED (§1. until then; exte OpenDesign upstream per §11.4.74 if its export lacks a token format.
D- DS-2	Per-role brand divergence	single seed 0xFF3B5BDB, role distinguished by accent tint only	distinct per-role seeds (Access/Connector/ Console)	A — the evidence base fixes one "overridden pe role" without distinct values (§3.3); a tint sh preserves brand cohesion. Surf to the operator stronger per-ro identity is want the state palet role-invariant either way.
D- DS-3	Brand typeface	a licensed brand sans (one weight family, subset)	a high-quality open font (Inter/IBM Plex) tokenized via OpenDesign	B for MVP — avoid Roboto- default look [0 §3.3] without licensing risk; swap to a licen face later is a token change, a refactor (DS- UNVERIFIED: no specific typefa named in the evidence base.
D- DS-4	Adaptive scaffold impl	hand-rolled AdaptiveScaffold (full control)	flutter_adaptive_scaffold package	A — full control over the connect screen layout - the no-overlap guarantee (DS

#	Decision	Option A	Option B	Recommendation
				the package is viable acceleration if its breakpoints map to §6 [04_§7].

Sources verified

- 04_VPN_CLD/HelixVPN-helix-ui-Flutter.md [04_UI] — §3 (design system: tokens, brand seed 0xFF3B5BDB, connection-state palette, signature components), §4 (Riverpod, the pure-function-of-stream rule), §7 (responsive breakpoints, AdaptiveScaffold), §9 (a11y: announce-not-color, light/dark, i18n), §10 (budgets), §12 (widget/golden testing).
- final/03-client-core-and-ui.md [03-CLIENT] — §0.1 (CI2/CI5 invariants), §3 (FFI TunnelStatus/Shields/ExitOption mirror), §4–§5 (TunnelPlatform + per-platform shims, the Danger/revoked source), §6 (flavors), §7 (design-system overview this doc deepens), §8 (Riverpod data layer), §10 (budgets), §13 (phases).
- final/v02-data-plane/orchestrator-and-state.md [02-ORCH] — §4.1 (canonical 5-variant TunnelStatus), §4.3 (rtt re-emit delta), §4.4 (Down.reason stable prefixes), §5.1 (OrchState no public projection for Idle/ShuttingDown), §8 (kill-switch/DNS sub-machine = the Danger{kind} source).
- final/v02-data-plane/transport-trait.md [02-TX] — §2 (Transport::kind() strings the StatusChip shows), §5.2 (the consumed TunnelStatus projection), §9 (the §11.4.169 test-type vocabulary this doc's §11 mirrors).
- v09-research/_SYNTHESIS.md [SYN] — §2 (Flutter + Rust-core floor), §4 (phases), §5 (helix_design system + signature components + connection-state palette), §9 (constitution bindings).
- [05_YB0] operator mandate — eight-platform requirement; tiny/fast/stable bar; responsive web.

Constitution: §11.4.44 (revision header), §11.4.6/§11.4.66 (UNVERIFIED marking; decisions = options + recommendation), §11.4.162 (OpenDesign mandatory design system, light+dark per component, no overlap, visual regression), §11.4.169 (comprehensive test-type coverage), §11.4.5/§11.4.69/§11.4.107/§11.4.158/§11.4.159/ §11.4.163 (captured / window-scoped / vision-validated evidence), §11.4.28/§11.4.74 (decoupled reusable package, extend-upstream), §11.4.151/§11.4.155 (release/recording prefixes), §1.1 (paired mutations on every lint/gate).

End of nano-detail specification — helix_design design system (Volume 4, Clients). Deepens [04_UI §3] / [03-CLIENT §7]; consumes the FFI TunnelStatus contract [03-CLIENT §3] consistent with the core enum [02-ORCH §4.1]. Surfaced decisions: D-DS-1 (OpenDesign binding), D-DS-2 (per-role brand), D-DS-3 (typeface), D-DS-4 (adaptive scaffold) — all presented, none silently resolved (§11.4.66).